

Lecture 16 – Access Control and Security Policies

Ryan Cunningham

University of Illinois

ECE 422/CS 461 – Fall 2017

Announcement

- Midterm:
 - Monday, Oct. 16th 7-9pm
 - ECEB 1002 (here)
- Conflict
 - Friday Oct. 13th 4-6pm
 - Siebel Center 4405
 - MUST have an email from you

Security News

- Verizon reveals Yahoo breach was all 3 billion accounts, includes Tumblr and Flickr
- Former DNI Clapper attributes 2012 DDoS to Iran, US decided not to hack back
- US DDoS of N. Korea, new connection through Russia
- Equifax CEO testified before House Energy and Commerce Committee

Access Control

- Access control is a collection of methods and components that support
 - confidentiality
 - integrity
 - accountability
- **Goal:** allow only authorized subjects to access permitted objects
- **E.g., Least privilege philosophy**
A subject is granted permissions needed to accomplish required tasks and nothing more


Principles

■ Context (entities and functions)

- Authentication - verifying credentials of users
- Authorization - granting rights/permissions to users
- Accountability- reviewing records and activities

■ Policies

- MAC - Mandatory access control
- DAC - Discretionary access control
- RBAC - Role-based access control (RBAC)
- ABAC - Attribute-based access control
- *ABACAB* - 11th studio album by the British band *Genesis*



Basic elements of access control

- **Subjects - entities capable of accessing objects (users)**
 - Owner - creator of object
 - Group - subjects grouped together
 - World - widest possible group; all valid subjects
- **Objects - resources with controlled access (files, programs)**
- **Access rights - what subjects are permitted do to objects**
 - Read, write, execute, delete, create, search

MAC vs DAC

- **MAC - administrator defines all of the access rights**
- **DAC - owners define access rights**

Mandatory Access Control

- It is a restrictive scheme that does not allow users to define permissions on files, regardless of ownership.
- Instead, security decisions are made by a central policy administrator.
- A common implementation is **rule-based** access control
 - Subject demonstrates need-to-know in addition to proper security clearance
 - Need-to-know indicates that a subject requires access to object to complete a particular task
- **Security-Enhanced Linux (SELinux)** incorporates mandatory access control.


Discretionary Access Control

- **Discretionary access control, or DAC, refers to a scheme where users are given the ability to determine the permissions governing access to their own files.**
 - DAC typically features the concept of both users and groups
 - In addition, DAC schemes allow users to grant privileges on resources to other users on the same system.
- **Most common design in commercial operating systems**
 - Generally less secure than mandatory control
 - Generally easier to implement and more flexible

Discretionary Access Control


- *Access matrix* of users and objects
- If matrix is sparse, can be reduced to an *access control list* (ACL)
- Row of access matrix gives us *capability tickets* for a user

	OBJECTS			
	File 1	File 2	File 3	File 4
User A	Own Read Write		Own Read Write	
User B	Read	Own Read Write	Write	Read
User C	Read Write	Read		Own Read Write



DAC Example

- Unix file system
 - 3 octets establishing permissions for each file



Role-Based Access Control

- The role-based access control (RBAC) model can be viewed as an evolution of the notion of group-based permissions in file systems.
- An RBAC system is defined with respect to an organization, such as company, a set of resources, such as documents, print services, and network services, and a set of users, such as employees, suppliers, and customers
- Uses a subject's role or task to grant or deny object access


Role-based access control (RBAC)

- Users are assigned roles
- Roles have permissions


	R_1	R_2	...	R_n
U_1	×			
U_2	×			
U_3		×		×
U_4				×
U_5				×
U_6				×
...				
U_m	×			

		OBJECTS								
		R ₁	R ₂	R _n	F ₁	F ₁	P ₁	P ₂	D ₁	D ₂
ROLES	R ₁	control	owner	owner control	read *	read owner	wakeup	wakeup	seek	owner
	R ₂		control		write *	execute			owner	seek *
	•									
	•									
	R _n			control		write	stop			

Role-based access control (RBAC)




Visualizing Role Hierarchy



Attribute-based access control (ABAC)

- Subjects and objects given *attributes*
- Decisions are made based on attributes of both
- Capable of enforcing any DAC, RBAC, or MAC idea



Attribute-based access control (ABAC)

- Define a *policy* to decide rules and relationships to govern allowable behavior
- Example rule:

$$(\text{Age}(u) \geq 17 \wedge \text{Rating}(m) \in \{R, PG-13, G\}) \vee$$
$$(\text{Age}(u) \geq 13 \wedge \text{Age}(u) < 17 \wedge \\ \text{Rating}(m) \in \{PG-13, G\}) \vee$$
$$(\text{Age}(u) < 13 \wedge \text{Rating}(m) \in \{G\})$$


SECURITY POLICIES

Security Policy

- Defining constraints and rules so that a system, asset, or organization is secure
- Designed by assessing risk and identifying potential adversaries
- Implemented by policy, crypto protocols, authentication systems, access control, etc.


E.g., Best Practices of Information Classification

- Military classifications of access rights for documents based on concepts
 - Unclassified
 - Confidential
 - Secret
 - Top secret



E.g., The Orange Book

- Trusted Computer System Evaluation Criteria (TCSEC)
 - Division D: “minimal protection”
 - Division C: “Discretionary protection”
 - Division B: “Mandatory protection”
 - Division A: “Verified protection”



E.g., Cisco Best Practices

- Preparation
 - Create Usage Policy Statement
 - Conduct a Risk Analysis
 - Establish a Security Team Structure
- Prevention
 - Approving Security Changes
 - Monitoring Security of Your Network
- Response
 - Security Violations
 - Restoration
 - Review

Network Security Policy: Best Practices White Paper

Document ID: 13601

Introduction

Preparation

- Create Usage Policy Statements
- Conduct a Risk Analysis
- Establish a Security Team Structure

Prevention

- Approving Security Changes
- Monitoring Security of Your Network

Response

- Security Violations
- Restoration
- Review

Related Information

Introduction

Without a security policy, the availability of your network can be compromised. The policy begins with assessing the risk to the network and building a team to respond. Continuation of the policy requires implementing a security change management practice and monitoring the network for security violations. Lastly, the review process modifies the existing policy and adapts to lessons learned.

This document is divided into three areas: preparation, prevention, and response. Let's look at each of these steps in detail.

Preparation

Prior to implementing a security policy, you must do the following:

- Create usage policy statements.
- Conduct a risk analysis.
- Establish a security team structure.

Create Usage Policy Statements

We recommend creating usage policy statements that outline users' roles and responsibilities with regard to security. You can start with a general policy that covers all network systems and data within your company. This document should provide the general user community with an understanding of the security policy, its purpose, guidelines for improving their security practices, and definitions of their security responsibilities. If your company has identified specific actions that could result in punitive or disciplinary actions against an employee, these actions and how to avoid them should be clearly articulated in this document.

The next step is to create a partner acceptable use statement to provide partners with an understanding of the information that is available to them, the expected disposition of that information, as well as the conduct of the employees of your company. You should clearly explain any specific acts that have been identified as

Cisco – Network Security Policy: Best Practices White Paper

Example of Implementing Policy

Filesystem Access Control

Unix Permissions

- Standard for all UNIXes
- Every file is owned by a user and has an associated group
- Permissions often displayed in compact 10-character notation (type, user, group, others)
- To view permissions: `ls -l` To change: `chmod`

```
jk@sphere:~/test$ ls -l
```

```
total 0
```

```
-rw-r----- 1 jk ugrad 0 2005-10-13 07:18 file1
```

```
-rwxrwxrwx 1 jk ugrad 0 2005-10-13 07:18 file2
```


Permissions Examples (Regular Files)

-rw-r--r--	read/write for owner, read-only for everyone else
-rw-r-----	read/write for owner, read-only for group, forbidden to others
-rwx-----	read/write/execute for owner, forbidden to everyone else
-r--r--r--	read-only to everyone, including owner
-rwxrwxrwx	read/write/execute to everyone

Permissions for Directories

- Permissions bits interpreted differently for directories
- *Read* bit allows listing names of files in directory, but not their properties like size and permissions
- *Write* bit allows creating and deleting files within the directory
- *Execute* bit allows entering the directory and getting properties of files in the directory
- Lines for directories in *ls -l* output begin with d, as below:

```
jk@sphere:~/test$ ls -l
```

```
Total 4
```

```
drwxr-xr-x  2 jk ugrad 4096 2005-10-13 07:37 dir1
```

```
-rw-r--r--  1 jk ugrad   0 2005-10-13 07:18 file1
```

Permissions Examples (Directories)

drwxr-xr-x	all can enter and list the directory, only owner can add/delete files
drwxrwx---	full access to owner and group, forbidden to others
drwx--x---	full access to owner, group can access known filenames in directory, forbidden to others
-rwxrwxrwx	full access to everyone

Special Permission Bits

- Three other permission bits exist
 - Set-user-ID (“suid” or “setuid”) bit
 - Set-group-ID (“sgid” or “setgid”) bit
 - Sticky bit

Set-user-ID

- Set-user-ID (“suid” or “setuid”) bit
 - On executable files, causes the program to run as file owner *regardless of who runs it*
 - Ignored for everything else
 - In 10-character display, replaces the 4th character (x or -) with s (or S if not also executable)
 - rwsr-xr-x: setuid, executable by all
 - rwxr-xr-x: executable by all, but not setuid
 - rwSr--r--: setuid, but not executable (not useful)

Root

- “root” account is a super-user account, like Administrator on Windows
- Multiple roots possible
- File permissions do not restrict root
- This is *dangerous*, but necessary, and OK with good practices

Becoming Root

- `su`
 - Changes home directory, PATH, and shell to that of root, but doesn't touch most of environment and doesn't run login scripts
- `su -`
 - Logs in as root just as if root had done so normally
- `sudo <command>`
 - Run just one command as root
- `su [-] <user>`
 - Become another non-root user
 - Root does not require to enter password

Changing Permissions

- Permissions are changed with `chmod` or through a GUI like Konqueror
- Only the file owner or root can change permissions
- If a user owns a file, the user can use `chgrp` to set its group to any group of which the user is a member
- root can change file ownership with `chown` (and can optionally change group in the same command)
- `chown`, `chmod`, and `chgrp` can take the `-R` option to recur through subdirectories

Examples of Changing Permissions

<code>chown -R root dir1</code>	Changes ownership of dir1 and everything within it to root
<code>chmod g+w,o-rwx file1 file2</code>	Adds group write permission to file1 and file2, denying all access to others
<code>chmod -R g=rwX dir1</code>	Adds group read/write permission to dir1 and everything within it, and group execute permission on files or directories where someone has execute permission
<code>chgrp testgrp file1</code>	Sets file1's group to testgrp, if the user is a member of that group
<code>chmod u+s file1</code>	Sets the setuid bit on file1. (Doesn't change execute bit.)

Example Threat and Policy

Lost Devices

Data Leakage by Lost Devices



Council confidential data loss causes ICO concern

By Arwyn Jones
BBC News Wales

Welsh councils are not doing enough to protect people's confidential data from falling into the wrong hands, according to the UK information watchdog.



Department	Number of records lost	Narrative	
Department for Work and Pensions	n/a	USB memory stick, apparently encrypted and containing passwords for an old version of the Government Gateway , a website giving access to millions of records of personal data.	
Ministry of Defence	1,700,000	Hard drive being held by contractor EDS is found to be missing.	
Service Personnel and Veterans Agency	50,500	Three USB portable hard drives with details of staff are allegedly stolen from a high security facility at RAF Innsworth . The Agency holds records on 900,000 current and former personnel. Stolen records included sensitive information about the private lives of senior staff.	containing 1 councils
Insolvency Service	400	Names, addresses and bank details of up to 400 directors of 122 firms were lost when four laptops were stolen from a Manchester premises.	
Tees, Esk and Wear Valleys NHS Trust	200	Memory stick with details of patients found in a public park.	
Home Office	84,000	PA Consulting lost an unencrypted memory stick containing details high risk, prolific and other offenders.	
Colchester Hospital University NHS Foundation Trust	21,000	A manager's unencrypted laptop holding patient addresses and treatment details is stolen from his car whilst on holiday in Edinburgh	
Department for Work and Pensions	45,000	West Yorkshire benefit claimants' in data lost.	
Department for Work and Pensions	000s	CDs with personal data found at the home of a former contractor.	
City and Hackney Teaching Primary Care Trust	160,000	"Heavily encrypted" disks containing details of children are lost by couriers. The loss prompted the agency to implement hard drive and USB memory stick encryption systems across all PCs.	
Foreign and Commonwealth Office	50,000	Details of visa applicants were made available on an FCO website.	
HM Revenue and Customs	25,000,000	Two CDs containing details of the families of child benefits claimants went missing in the post. HMRC's handling of data was described as "woefully inadequate" and staff were described as "muddling through" in a June 2008 Independent Police Complaints Commission report.	
Ministry of Justice	5,000	Hard disk with details of HM Prison Service staff is lost on the premises of EDS .	
Driving Standards Agency	3,000,000	Hard disk with details of candidates for the driving theory test was lost in a premises in Iowa by subcontractors.	
Foreign and Commonwealth Office	50	Details of individuals made public after "unauthorised disclosure by a contractor"	

Glue it?

1. Remove cap



2. Insert glue nozzle into USB port and apply liberally



3. Kick back and relax, your endpoint security problems are over!



memegenerator.net

Fine it?

£120,000 fine for lost USB stick

The ICO has fined Greater Manchester Police £120,000 after a memory stick containing sensitive personal data was stolen from an officer's home.

According to the ICO the device had no encryption or password protection, and contained details of more than a thousand people with links to serious crime investigations.

The ICO found that some officers across the force regularly used unencrypted memory sticks, which may also have been used to copy data from police computers to access away from the office. Despite a similar security breach in September 2010, the force had not put restrictions on downloading information, and staff were not sufficiently trained in data protection.

David Smith, ICO Director of Data Protection, said: "This is a substantial monetary penalty, reflecting the significant failings the force demonstrated. We hope it will discourage others from making the same data protection mistakes."

"It is easy to protect against such risks" says Jon Stanton from PEM IT Services. "The organisation could have installed security software such as DriveLock to control what USB devices can access their PCs. DriveLock would also have enabled them to encrypted their memory sticks, and given them an audit trail of what files had been transferred. This, combined with staff training, would have minimised the risks of any data loss."

Lost Laptops

- Lost and stolen laptops are a common occurrence
 - Estimated occurrences in US airports every week: 12,000
- Average cost of a lost laptop for a corporation is \$50K
 - Costs include data breach, intellectual property loss, forensics, lost productivity, legal and regulatory expenses
 - **Data breach** much more serious than hardware loss
- Data breach cost estimated at \$200 per customer record
 - Direct costs include discovery, notification and response
 - Indirect costs include customer turnover (higher loss and lower acquisition)
- Data can also be copied while laptop is unattended

From Device to Data – Encryption

- In a perfect world, we would not store sensitive data on portable devices
 - All sensitive data should be held on secure servers.
 - Unfortunately, this approach is not always practical.
- Keep the benefit of using portable devices
- Reduce the risk of data leakage by encryption

Encryption of File Systems

- Disk encryption
 - Block-level encryption
 - Encryption of physical or logical drive
 - BitLocker in Windows Vista and 7
 - TrueCrypt open source software
- File system encryption
 - File-level encryption
 - Encrypting File System (EFS) in Windows

Example Threat and Policy


Passwords

Warning to the Users

- Do not use shared credentials
- Strength your password
 - 2,295: “123456” or a sequential list of number
 - 780: “password”
 - 437: “welcome”

Compromised UofM Accounts

- **613 incidents** related to unauthorized use of university accounts during 2010 and first 6 months of 2011 at UofM



Compromised UofM Accounts

- What did they do with the compromised accounts?

Netflow data analysis

- ✓ Library website repeatedly visited
- ✓ 8.2% of HTTP flows visited consist of 10 websites blocked in China
- ✓ Login to accounts at 7 universities

- Market place for the compromised university accounts

The image displays two screenshots of online marketplaces. The top screenshot is from Taobao, showing a listing for 'Academic Publisher Steps Up Effort Its Online Products' with a price of 500.00 RMB. A red box highlights the price and text: '500 RMB ~ less than 100 USD = access to multiple databases for a year'. The bottom screenshot is from Free500beans, showing a 'Big Sale For Thanksgiving Day' banner and a listing for 'University Of Michigan Ezproxy Password 20111112(\$20)'. A red box highlights the listing with text: '\$20 = UofM account with VPN and Library access'.

New motivation of attackers who steal university credentials:

Free and unfettered access to information

Weak Password Scanning


- UofM scan weak password accounts twice a year using a commercial password cracker
- 2,284 weak password are detected in June, 2011
- Whether accounts with weak passwords are a problem?

	# of total	# of compromised	Pr (compromise)
Weak Password	2,284	12	0.525%
Total Population	550,000	380	0.069%

Test statistics of deviance of 28.09 and a p-value of 1.16^{-16}

Educating the Users

- From 'what tools to use' to 'who uses the tool'



Yearly Security Quiz at UofM

	# of total	# of compromised	Pr (compromise)
Passed Quiz	9,227	9	0.1%
NOT passed	41,924	105	0.25%

Test statistics of deviance of 13.52 and a p-value of 2.36^{-4}