

Open in app ↗

Medium

 Search

★ Get unlimited access to the best of Medium for less than \$1/week. [Become a member](#)



# Understanding of Convolutional Neural Network (CNN) — Deep Learning

Prabhu Raghav · [Follow](#)

5 min read · Mar 4, 2018



Listen




Share



More


In neural networks, Convolutional neural network (ConvNets or CNNs) is one of the main categories to do images recognition, images classifications. Objects detections, recognition faces etc., are some of the areas where CNNs are widely used.

CNN image classifications takes an input image, process it and classify it under certain categories (Eg., Dog, Cat, Tiger, Lion). Computers sees an input image as array of pixels and it depends on the image resolution. Based on the image resolution, it will see  $h \times w \times d$  ( $h$  = Height,  $w$  = Width,  $d$  = Dimension ). Eg., An image of  $6 \times 6 \times 3$  array of matrix of RGB (3 refers to RGB values) and an image of  $4 \times 4 \times 1$  array of matrix of grayscale image.



**Figure 1 : Array of RGB Matrix**

Technically, deep learning CNN models to train and test, each input image will pass it through a series of convolution layers with filters (Kernels), Pooling, fully connected layers (FC) and apply Softmax function to classify an object with probabilistic values between 0 and 1. The below figure is a complete flow of CNN to process an input image and classifies the objects based on values.




**Figure 2 : Neural network with many convolutional layers**

## Convolution Layer


Convolution is the first layer to extract features from an input image. Convolution preserves the relationship between pixels by learning image features using small squares of input data. It is a mathematical operation that takes two inputs such as image matrix and a filter or kernel.

- An image matrix (volume) of dimension **(h x w x d)**
- A filter **(f<sub>h</sub> x f<sub>w</sub> x d)**
- Outputs a volume dimension **(h - f<sub>h</sub> + 1) x (w - f<sub>w</sub> + 1) x 1**




**Figure 3: Image matrix multiplies kernel or filter matrix**

Consider a 5 x 5 whose image pixel values are 0, 1 and filter matrix 3 x 3 as shown in below



**Figure 4: Image matrix multiplies kernel or filter matrix**

Then the convolution of 5 x 5 image matrix multiplies with 3 x 3 filter matrix which is called “Feature Map” as output shown in below



**Figure 5: 3 x 3 Output matrix**

Convolution of an image with different filters can perform operations such as edge detection, blur and sharpen by applying filters. The below example shows various convolution image after applying different types of filters (Kernels).








Operation	Filter	Convolved Image
<b>Identity</b>	$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$	
<b>Edge detection</b>	$\begin{bmatrix} 1 & 0 & -1 \\ 0 & 0 & 0 \\ -1 & 0 & 1 \end{bmatrix}$	
	$\begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$	
	$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$	
<b>Sharpen</b>	$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 5 & -1 \\ 0 & -1 & 0 \end{bmatrix}$	
<b>Box blur</b> (normalized)	$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	
<b>Gaussian blur</b> (approximation)	$\frac{1}{16} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$	

Figure 7 : Some common filters

## Strides

Stride is the number of pixels shifts over the input matrix. When the stride is 1 then we move the filters to 1 pixel at a time. When the stride is 2 then we move the filters to 2 pixels at a time and so on. The below figure shows convolution would work with a stride of 2.




Figure 6 : Stride of 2 pixels

## Padding

Sometimes filter does not fit perfectly fit the input image. We have two options:

- Pad the picture with zeros (zero-padding) so that it fits
- Drop the part of the image where the filter did not fit. This is called valid padding which keeps only valid part of the image.

## Non Linearity (ReLU)

ReLU stands for Rectified Linear Unit for a non-linear operation. The output is  $f(x) = \max(0, x)$ .

Why ReLU is important : ReLU's purpose is to introduce non-linearity in our ConvNet. Since, the real world data would want our ConvNet to learn would be non-negative linear values.




Figure 7 : ReLU operation

There are other non linear functions such as tanh or sigmoid that can also be used instead of ReLU. Most of the data scientists use ReLU since performance wise ReLU is better than the other two.

## Pooling Layer

Pooling layers section would reduce the number of parameters when the images are too large. Spatial pooling also called subsampling or downsampling which reduces the dimensionality of each map but retains important information. Spatial pooling can be of different types:

- Max Pooling
- Average Pooling
- Sum Pooling

Max pooling takes the largest element from the rectified feature map. Taking the largest element could also take the average pooling. Sum of all elements in the feature map call as sum pooling.




Figure 8 : Max Pooling

## Fully Connected Layer

The layer we call as FC layer, we flattened our matrix into vector and feed it into a fully connected layer like a neural network.




Figure 9 : After pooling layer, flattened as FC layer

In the above diagram, the feature map matrix will be converted as vector (x1, x2, x3, ...). With the fully connected layers, we combined these features together to create a model. Finally, we have an activation function such as softmax or sigmoid to classify the outputs as cat, dog, car, truck etc.,






Figure 10 : Complete CNN architecture

## Summary

- Provide input image into convolution layer
- Choose parameters, apply filters with strides, padding if requires. Perform convolution on the image and apply ReLU activation to the matrix.
- Perform pooling to reduce dimensionality size
- Add as many convolutional layers until satisfied
- Flatten the output and feed into a fully connected layer (FC Layer)
- Output the class using an activation function (Logistic Regression with cost functions) and classifies images.

In the next post, I would like to talk about some popular CNN architectures such as AlexNet, VGGNet, GoogLeNet, and ResNet.

## References :

- <https://www.mathworks.com/discovery/convolutional-neural-network.html>
- <https://adeshpande3.github.io/adeshpande3.github.io/A-Beginner's-Guide-To-Understanding-Convolutional-Neural-Networks/>
- <https://ujjwalkarn.me/2016/08/11/intuitive-explanation-convnets/>
- <https://blog.datawow.io/interns-explain-cnn-8a669d053f8b>

Machine Learning

Cnn

Convolution Neural Net

Image Recognition

Neural Networks



Follow

## Written by Prabhu Raghav

1.9K Followers · 183 Following

SuperAgentX - <https://www.superagentx.ai/> OpenSource Agentic AGI Framework — [Decisionfacts.ai](#), [Deeplore.io](#)

## Responses (43)



What are your thoughts?

Respond



Saliya Ekanayake  
over 6 years ago



Really nice explanation. Thanks!



16

Reply



Hamid Haghdooost

about 6 years ago



Thank you for your clear and fluent tutorial, I enjoyed that and I learned the base of CNN in less than 10 minutes :)



14

Reply



veena tapaswi

almost 6 years ago



neat explanation... thanks



6

Reply

See all responses

## More from Prabhu Raghav



Name: Crema Coffee Roasting Company  
Address: San Jose, CA,  
Features: Coffee Roasting



Name: Nirvana Soul  
Address: 315 South 1st Street, San Jose, CA 95113  
Features: Internet Access, Outdoor Seating




Name: Philz Coffee  
Address: 118 Paseo De San Antonio, San Jose, CA 95112  
Features: Takeaway, Coffee Shop, Safety Mask



Name: Voyager Craft Coffee  
Address: 87 North San Pedro Street, San Jose, CA 95110




Name: Academic Coffee  
Address: 499 South 2nd Street, San Jose, CA 95113

 Prabhu Raghav

## Master Agentic AI: A Beginner's Step-by-Step Guide with SuperAgentX — Tutorial Series (Part 1)

Hello Everyone, Welcome to the Agent AI Tutorial Series — Part 1! 🚀



 In Towards Data Science by Prabhu Raghav

## Understanding NLP Word Embeddings — Text Vectorization

Processing natural language text and extract useful information from the given word, a sentence using machine learning and deep learning...

Nov 11, 2019  477  3




tds In Towards Data Science by Prabhu Raghav

## Linear Regression Simplified - Ordinary Least Square vs Gradient Descent

What is Linear Regression? Linear regression is a statistical method of finding the relationship between independent and dependent...

May 15, 2018 🖱️ 2.2K 💬 13



Prabhu Raghav

## CNN Architectures — LeNet, AlexNet, VGG, GoogLeNet and ResNet


In my previous blog post, explained about my understanding of Convolution Neural Network (CNN). In this post, I am going to detailing about...


Mar 15, 2018 🖱️ 348 💬 3



See all from Prabhu Raghav

## Recommended from Medium



 Rishabh Singh


### Convolutional Neural Network (CNN)—Part 1

When classifying images, traditional neural networks struggle because each pixel is treated as an independent feature, which misses...

Nov 6  100  2







In Lumos by Luqman Zaceria

## Understanding Convolutional Neural Networks (CNNs)

Hey everyone! We're going to explore one of the most influential and powerful tools in the world of deep learning: Convolutional Neural...




Aug 5



73



### Lists



#### Predictive Modeling w/ Python

20 stories · 1718 saves



#### Practical Guides to Machine Learning

10 stories · 2090 saves




#### Natural Language Processing

1856 stories · 1484 saves



#### The New Chatbots: ChatGPT, Bard, and Beyond

12 stories · 523 saves




**PY** In Python in Plain English by Jyoti Dabass, Ph.D.

## Friendly Introduction to Deep Learning Architectures (CNN, RNN, GAN, Transformers, Encoder-Decoder...

This blog aims to provide a friendly introduction to deep learning architectures involving Convolutional Neural Networks (CNN), Recurrent...

★ Apr 1 🖱 1.3K 💬 13






tds In Towards Data Science by Jonte Dancker

## A Brief Introduction to Recurrent Neural Networks

An introduction to RNN, LSTM, and GRU with their implementation




LM Po

## Self-Attention and Transformer Network Architecture

The introduction of Transformer models in 2017 marked a significant turning point in the fields of Natural Language Processing (NLP) and...


★ Oct 18 🖱 34 💬 1



 Jo Wang

## Autoencoder

An autoencoder is a type of neural network used primarily for unsupervised learning.

 Oct 21  4



See more recommendations