

3.8 (1) select distinct d.ID
from depositor as d
where not exist (select *
from borrower as b
where b.ID = d.ID) ;

(2). select c2.ID
from customer as c1, customer as c2
where c1.ID = '12345'
and c2.customer_city = c1.customer_city
and c2.customer_street = c1.customer_street
and c2.ID <> '12345' ;

(3). select branch_name
from account
where account_number in (
select account_number
from depositor
where ID in (
select ID
from customer
where customer_city = 'Harrison')) ;

3.15 (1) select c.ID, c.customer_name
from customer as c
where not exist (

select b.branch_name
from branch as b

where b.branch_city = 'Brooklyn'

except

select a.branch_name

from account as a natural join depositor as d
where d.ID = c.ID);

(2). select sum(amount) as total_loan_amount
from loan

(3). select branch_name
from branch

where assets > some (

select assets

from branch

where branch_city = 'Brooklyn');

3.17 (1) update works

set salary = salary * 1.1

where company_name = 'First Bank Corporation'

and ID in (

select ID

from employee);

(2) update works

set salary = salary * 1.1

where company_name = 'First Bank Corporation'

and ID in (

select ID

from manages);

(3) delete from works

where company_name = 'Small Bank Corporation'

and ID in (

select ID

from employee);