

FIELD SERVICE REPORT

Technical Maintenance & Equipment Inspection

Report ID: SR-20260927-185231

Date: 2026-09-27

1. CLIENT & SITE DETAILS

Client Name:	+564+456+456	Site / Branch:	yutyuit
Contact Person:	jkvfgghc	Contact Phone:	jkhouihgou

2. MACHINE SPECIFICATIONS

Equipment Model:	iohiy8	Serial Number:	ihioho
Operating Hours:	14	Service Type:	Preventive Maintenance

3. ISSUE DESCRIPTION & ROOT CAUSE

;khfudtxuyxdtkuyfligpoug9gu

4. ACTIONS TAKEN & REMARKS

ljbKhgzlUgzlugz;iugzug;zhuo;xz

5. REPLACED / REQUIRED SPARE PARTS

Part Number	Description	Qty	Status
54545545648		1	Installed
5+4564		1	Installed
54545545648		1	Installed
5+4564		1	Installed

6. SITE & FAULT PHOTOGRAPHIC EVIDENCE (1 Photos)

Service Training Section 6 Page 17 40 No function 41 No function 42 Feedback of intermediate circuit voltage power and pump meter 43 Feedback phase voltage L2 from power unit 142 44 Output relay driver 1 (only S2 stop light) 45 Output relay driver 2 (only S2 stop light) 46 SDC for LLC diagnosis 47 CCM for speed sensor unit 141, 142 48 No function 49 SDC for diagnosis, function 50 Supply voltage V2 for position 51 Enable feedback signal from power unit 241 52 Supply voltage U2 for position 53 Parameter track signal switch 155 (reference used position) 54 Signal from stop and lock 155 (reference used position) 55 No function 56 Channel A speed sensor 155 57 Signal from steering sensor 155 58 No function 59 No function 60 Brake voltage V4 for accelerator 61 Feedback phase voltage L1 from power unit 142 62 Feedback phase voltage L2 from power unit 142 63 Output relay driver 3 (activation of spreading hour meter) 64 Output relay driver 1 (spreading hour meter) 65 SDC for LLC diagnosis 66 CCM for speed sensor unit 141, 142 67 No function 68 SDC for diagnosis, function 69 Negative supply voltage for position 70 Negative supply voltage for accelerator 71 Parameter track signal switch 155 (normal used position) 72 Signal for speed reduction, function 73 Reference position signal from reference switch, single pedal 151 74 Channel B speed sensor 155 75 No function 76 No function 77 No function 78 Feedback phase voltage L2 from power unit 142 79 Feedback phase voltage L2 from power unit 142 80 Drive signal joystick lifting/lowering 81 Drive signal joystick lifting/lowering 82 Drive signal joystick aux, hydraulics 1 83 No function 84 Signal alarm reduction LLC from operator instrument 85 Input signal from sensor 155 (steering control valve) 86 No function 87 Coil activation/proportional valve 216 aux, hydraulics 14 Service Training Section 6 Page 18 88 Drive signal joystick aux, hydraulics 2 89 No function 90 No function 91 Signal for switch-controlled speed reduction LLC 92 No function 93 No function 94 Coil activation/proportional valve 216 aux, hydraulics 1B 95 Reference signal joystick lifting/lowering 96 Reference signal joystick lifting 97 Reference signal joystick aux, hydraulics 1 98 Channel A speed sensor 255 99 No function 100 No function 101 Coil activation/proportional valve 216 aux, hydraulics 1A 102 Reference signal joystick aux, hydraulics 2 103 No function 104 No function 105 Coil activation/proportional valve 216 aux, hydraulics 2A 106 Reference signal joystick aux, hydraulics 2 107 No function 108 No function 109 No function 110 Coil activation/proportional valve 216 lifting 111 No function 112 Coil activation/proportional valve 216 aux, hydraulics 2B 113 Coil activation/proportional valve 216 aux, hydraulics 2B 114 Negative supply voltage for handbrake, valve and activation 115 Coil activation, safety valve, steering 211 116 Reference signal joystick lifting 117 Coil activation, safety valve 211 118 Positive supply voltage, valve coil 119 Coil activation/proportional valve 211 steering 120 Coil activation/proportional valve 216 forward filling 121 Coil activation/proportional valve 216 forward filling 6.6.3 TRACTION FUNCTION A 24V battery voltage is supplied to the controller through X13.2. This voltage is grounded to the voltage transformer 01. The negative supply for the controller is effected via X13.2. In addition, positive battery voltage is supplied to the controller through X13.2. In the controller, this connection is connected to the contact from the traction safety relay. As soon as the safety relay is activated, positive battery voltage is connected to the coil of the main controller K1 through X13.2. Once the intermediate circuit capacitors have been charged, the main controller is activated via X13.1. To protect the controller coil from overvoltage, the negative signal is supplied. This reduces the voltage at the controller coil (nominal voltage 48 V) to a value of approx. 35 V.

7. VERIFICATION & SIGN-OFF

Service Engineer:	6685464	Customer Representative:	jlhfutkdtydsdydjxyrf
-------------------	---------	--------------------------	----------------------

Signature: _____ - Signature: _____ -