Nabd نبض

When an app breaks, Nabd finds out why and fixes it safely.

HUMAIN × Misk · Future AI Builders
Challenge 1: Agentic Recovery of a Failing System
Muath · nabd.duraym.com

What Nabd did

Fixed

Problem	An update to the website is stuck.
Cause	The new version points to an app version that doesn't exist (a typo).
Fix	Go back to the last version that worked.
Approval	Not needed: safe and can be undone.
Result	**Fixed. The health check passes again.**

Most outages start with something small

1

A small change slips in

A typo in a version number, a wrong port, a renamed setting, a deleted password.

2

The app goes down

Users see errors. Kubernetes restarts it again and again, but restarting can't fix a wrong setting.

3

Someone has to dig

An engineer is paged, reads logs and events, finds the one wrong line, and fixes it carefully while users wait.

Most cloud apps run on Kubernetes. It keeps apps running, but it cannot tell a crash from a configuration mistake.

So why not just let an AI fix it?

Finding the fix isn't the hard part.
Trusting the fixer is.

- It can run any command, including delete
- It can read, or leak, passwords
- A confident wrong guess makes the outage worse
- It can retry forever instead of asking for help

Nabd works like a pharmacist with a short list

A pharmacist can only hand out what's on the approved list, and some medicines need a doctor's signature. Nabd is built the same way.

Does on its own

- Go back to the last version that worked
- Bring back the right number of copies
- Restart to pick up a corrected setting

Asks you first

- Change where traffic is sent
- Fix the name of a setting

You see the exact change and the reason, then you decide.

Never does

- Delete anything
- Read, guess or invent passwords
- Touch anything outside its area
- Retry the same fix again

Five fixes in total. Anything else is handed to a person with the diagnosis, and nothing is changed.

How Nabd works: five steps, every time

1

Notice

An independent health check sees the app failing.

2

Investigate

Errors, logs, events, settings. Never password values.

3

Diagnose

Proven rules first. Claude only when the rules have no answer.

4

Safety checks

On the list? Needs a human? Dry-run passes? Matches the evidence?

5

Fix and verify

Apply, re-check, undo if it didn't help, write a report.

Step 4 is where safety decides, not the AI. The model can only suggest one of the five fixes; code checks everything else.

One real incident, start to finish

0 s — **The website stops answering**

Health check: connection refused.

4 s — **Nabd finds the cause**

Traffic goes to label 'frontend'; the app is labelled 'web'.

4 s — **It proposes the fix and asks**

Changing traffic needs a human, so it waits.

76 s — **A human approves**

Dry-run, apply, check.

77 s — **Healthy again**


Nabd's own work: about 5 seconds.

The incident report Nabd wrote

```
Outcome           Resolved
Duration          77.3 s
Change            patch_service(web)
Approvals asked   1
AI calls          0

DIAGNOSE service/web -> networking
- selector {'app':'frontend'}
  matches no pod labels
- last-applied selector: {'app':'web'}
APPROVAL granted
DRY-RUN ok -> APPLY ok -> VERIFIED
```

Does it actually work? We broke it 14 ways



14 / 14

faults handled, including the 5 kept secret

0

unsafe changes, in every version tested

2

AI calls: rules handle known faults, AI the rest

Real kind cluster, 3 versions × 14 faults = 42 runs. Handled = fixed and verified, or correctly handed to a human without changing anything.

Built for GitOps teams: Argo CD and Flux

With GitOps, Git is the source of truth. A fix made directly on the cluster is undone at the next sync. So in GitOps mode, Nabd fixes Git, not the cluster.



If the cluster differs from Git, or the commit reaches outside the app, Nabd reverts nothing and calls a human.

Added for teams like HUMAIN's, where deployments run through GitOps. Tested with real Git repositories in 12 automated tests.

Honest limits, and what's next

Limits today

- Tested on a small cluster with three apps, not yet in a real company
- The browser demo simulates the cluster and runs the rules; the AI runs from the command line
- Some faults take about 90 seconds to show, because Kubernetes must fail its checks first
- With Argo CD or Flux, it fixes only problems that came from a commit

Next

- Silent failures: data lost with no error, like the challenge's lost orders
- Trigger Nabd from existing alerts (Alertmanager, PagerDuty)
- More fixes on the list, each with its own safety tests
- Run against a staging cluster with real traffic

Break it yourself

Pick a fault, look around like an engineer, and watch Nabd fix it. Nothing to install.

Live demo	nabd.duraym.com/demo
Code	github.com/moaddreem/k8s-healing-agent

Muath · نبض