IMEN891K / IDSC501 / AXGS-501 · DATA ENGINEERING · FALL 2026


15.

LLM Systems

Sangwoo Mo · POSTECH

Industrial & Management Engineering

Where We Are



Part III connects stored data to models, retrieval, and actions

Outline: LLM Systems

01

Building an LLM Application

give instructions and check the answer format

02

Connecting LLM Calls

carry useful context between steps

03

Preparing Data and Checking Answers

test the application before releasing changes

01 · Building an LLM Application

01

Building an LLM Application

give instructions and check the answer format

02

Connecting LLM Calls


carry useful context between steps

03

Preparing Data and Checking Answers


test the application before releasing changes

§ Models and Prompts



Large Language Models


An LLM predicts tokens conditioned on the context



Several providers offer general-purpose models behind an **API**

Model Selection

Choose a model against application requirements



Pick the cheapest

that clears the quality line

Then check

latency tail and data handling

The cheapest model that clears **our** quality line

Autoregressive Generation

The next token depends on the tokens already in context

$$P(y \mid x) = \Pi_t P(y_t \mid x, y_{<t})$$



Each new token

joins the context
and costs compute

Each chosen token becomes **context** for the next

Caveat: Plausible Answers


A fluent answer can be unsupported by the supplied facts



A specific answer with **no evidence** behind it

LLM Application Control Flow


An application adds processing before and after a model call



The LLM call is one stage inside a larger workflow

Application Components

Model interfaces connect prompts, data, and output handling



An application connects these components around the **model call**

LangChain Model Interface

Choose a recorded response or a real locally served model

```
import { ChatOllama } from '@langchain/ollama';
import { FakeListChatModel } from '@langchain/core/utils/testing';

// Offline execution tests the application around a fixed response.
const replay = new FakeListChatModel({responses: [
  '{"label":"vibration","evidence":"vibrates"}'
]});
// Live inference requires an installed model and a running Ollama server.
const live = new ChatOllama({model: '<installed-chat-model>',
  baseUrl: 'http://127.0.0.1:11434', temperature: 0});
// makeModel(responses) selects replay or live in the code windows.
```

Chat Messages

Message roles distinguish instructions, user requests, and tool results

system	Classify notes as leak, vibration, or other. Quote evidence.
user	P-17 vibrates above 2500 rpm
assistant	`tool call: read_pressure(pump_id = "P-17")`
tool	`{"pump_id": "P-17", "pressure_bar": 4.2}`

Roles separate **policy**, request, model output and tool result

Prompt Templates

Compose reusable steps with LangChain.js core

```
const prompt = ChatPromptTemplate.fromMessages([
  ["system", "Classify notes as {labels}. Quote evidence."],
  ["human", "{note}"]
]);
const input = {labels: "leak, vibration, other",
  note: "Pump vibrates above 2500 rpm"};
const rendered = await prompt.invoke(input);
return rendered.toChatMessages().map(m => ({
  role: m.getType(), content: m.content
}));
```

Demo: Prompt Templates

Edit JavaScript and run the real LangChain core objects

1. Change the note and inspect the rendered messages.

2. Remove the note field and explain the missing-input error.

```
Type code or click Starter
```

```
Run code to inspect its output.
```

Run | Starter | Reset

Ready


LangChain.js · JavaScript · Ctrl/Cmd+Enter · Real library execution with local data

Answer: Prompt Templates

Inspect the output at the boundary that changed


```
[
  {
    "role": "system",
    "content": "Classify notes as leak, vibration, other. Quote evidence."
  },
  {
    "role": "human",
    "content": "Pump vibrates above 2500 rpm"
  }
]
```

§ Structured Outputs



Structured Output


A schema defines the shape of the response consumed by software



A schema turns the answer into **data** software can use

Output Validation

Syntax, schema, and meaning require different checks



`{"label": "vibration", "evidence": "vibrates"}` passes all three

Each check stops a **different** failure

Output Parsing and Validation

Compose reusable steps with LangChain.js core

```
const schema = z.object({
  label: z.enum(["leak", "vibration", "other"]),
  evidence: z.string().min(1)
}).strict();
const parser = new JsonOutputParser();
const note = "Pump vibrates above 2500 rpm";
const raw = '{"label":"vibration","evidence":"vibrates"}';
const parsed = await parser.invoke(raw);
const result = schema.parse(parsed);
if (!note.includes(result.evidence)) {
  throw new Error("Evidence is absent from the source");
}
return result;
```

Demo: Output Parsing and Validation

Edit JavaScript and run the real LangChain core objects

1. Try an unknown label and inspect the schema error.
2. Keep valid JSON but invent evidence; identify which check fails.

```
Type code or click Starter
```

```
Run code to inspect its output.
```

Run | Starter | Reset

Ready

LangChain.js · JavaScript · Ctrl/Cmd+Enter · Real library execution with local data

Answer: Output Parsing and Validation

Inspect the output at the boundary that changed

```
{
  "label": "vibration",
  "evidence": "vibrates"
}
```

Caveat: Valid JSON

A valid object can still contain the wrong answer

Original note

"Pump vibrates above 2500 rpm"

```
{"label": "leak",
"evidence": "liquid detected"}
```

- ✓ parses as JSON
- ✓ matches the schema
- × evidence occurs in the note

Format checks pass; the **meaning** is wrong

02 · Connecting LLM Calls

01

Building an LLM Application

give instructions and check the answer format

02

Connecting LLM Calls


carry useful context between steps

03

Preparing Data and Checking Answers

test the application before releasing changes

§ Context and Memory




Conversation Context

A model call sees the messages supplied to that call

Large Language Models are ‘stateless’

- Each transaction is independent

Chatbots appear to have memory by providing the full conversation as ‘context’




LangChain provides several kinds of ‘memory’ to store and accumulate the conversation

The application supplies the conversation history

Memory Mechanisms

Keep context selection separate from durable storage



Each mechanism sends a different part of the **history**

Conversation Memory

Compose reusable steps with LangChain.js core

```
const history = [
  new HumanMessage("Use Celsius. Monitor P-
17."),
  new AIMessage("Which period?"),
  new HumanMessage("Last 24 hours."),
  new AIMessage("Which measurement?")
];
const keep = 2;
const recent = keep === 0 ? [] :
history.slice(-keep);
```

```
const prompt =
ChatPromptTemplate.fromMessages([
  ["system", "Report maintenance
measurements."],
  new MessagesPlaceholder("history"), ["human",
"{question}"]
]);
const value = await prompt.invoke({history:
recent,
  question: "What was the maximum
temperature?"});
return value.toChatMessages().map(m =>
m.content);
```

Demo: Conversation Memory

Edit JavaScript and run the real LangChain core objects

1. Change keep from 2 to 0 or 4 and inspect the context.
2. Move the unit rule to the system message so trimming preserves it.

```
Type code or click Starter
```

```
Run code to inspect its output.
```

Run | Starter | Reset

Ready

LangChain.js · JavaScript · Ctrl/Cmd+Enter · Real library execution with local data

Answer: Conversation Memory

Inspect the output at the boundary that changed

```
[
  "Report maintenance measurements.",
  "Last 24 hours.",
  "Which measurement?",
  "What was the maximum temperature?"
]
```

Window Memory

A bounded window can discard a fact that remains relevant



The model never sees the unit instruction

The window dropped the **instruction** from turn 1

Summary Memory


A summary trades token count for information loss



The summary lost the **condition**

Context Budget


Instructions, evidence, history, and output share a finite budget



Reserve the **output** before filling the context

Caveat: Untrusted Context


Retrieved text can include instructions that conflict with the task



Retrieved text is data; tool permission comes from the application


Instructions inside retrieved text get **no permissions**

§ Chains and Routing



Sequential Chain


The output of one step becomes the input to the next



Step outputs form explicit dependencies

Parallel and Sequential Steps

Independent steps can run before their outputs are combined



Only dependencies require sequential execution


Sequential and Parallel Chains

Compose reusable steps with LangChain.js core

```
const prepare = RunnableLambda.from(note => note.trim());
const features = RunnableMap.from({
  equipment: RunnableLambda.from(s => s.match(/P-\d+/)?.[0] ?? null),
  characters: RunnableLambda.from(s => s.length)
});
const report = RunnableLambda.from(fields => ({
  ...fields, needsReview: fields.equipment === null
}));
const chain = prepare.pipe(features).pipe(report);
return await chain.invoke("  P-17 vibrates  ");
```

Router Chain

A router selects a destination for the request



Routing chooses among defined destinations


Routing and Fallbacks

Compose reusable steps with LangChain.js core

```
const branches = {
  maintenance: RunnableLambda.from(x => ({queue: "maintenance", note: x.note})),
  production: RunnableLambda.from(x => ({queue: "production", note: x.note})),
  unknown: RunnableLambda.from(x => ({queue: "review", note: x.note}))
};
const router = RunnableLambda.from(async x => {
  const route = Object.hasOwn(branches, x.route) ? x.route : "unknown";
  return await branches[route].invoke(x);
});
return await router.invoke({route: "maintenance", note: "P-17 vibrates"});
```

Caveat: Error Propagation

A downstream step can hide an upstream extraction error



An early extraction error makes the **whole report** wrong

Complete LLM Application

Render messages, invoke a model, parse JSON, and validate evidence

```
const prompt = ChatPromptTemplate.fromMessages([
  ["system", 'Return JSON with label and evidence. Use leak, vibration, or other.'],
  ["human", "{note}"]
]);
const model = makeModel(['{"label":"vibration","evidence":"vibrates"}']);
const chain = prompt.pipe(model).pipe(new JsonOutputParser());
const note = "P-17 vibrates above 2500 rpm";
const result = await chain.invoke({note});
const schema = z.object({label:z.enum(["leak","vibration","other"]),
  evidence:z.string().min(1)}).strict();
schema.parse(result);
if (!note.includes(result.evidence)) throw Error("Unsupported evidence");
const queue = result.label === "other" ? "review" : "maintenance";
return {mode: MODEL_MODE, result, queue};
```

Demo: Complete LLM Application

Inspect the prompt → model → parser boundary

1. Change the replay response to an unknown label or invented evidence.
2. Change note to a leak report. Why does the replay response stay unchanged?

Execution Offline replay | Installed model na | http://127.0.0.1:11434

Type code or click Starter

Run code to inspect its output.

Run | Starter | Reset

Ready

LangChain.js · JavaScript · Ctrl/Cmd+Enter · Offline replay uses fixed responses; local mode calls your model


Answer: Complete LLM Application

The baseline output comes from executing the shown code

```
{
  "mode": "Recorded response (no inference)",
  "result": {
    "label": "vibration",
    "evidence": "vibrates"
  },
  "queue": "maintenance"
}
```

LangChain Ecosystem

Open-source libraries build the workflow; LangSmith observes it



LangGraph adds stateful control; **LangSmith** adds tracing and evaluation

Implementation Choices

Choose a framework after defining the workflow

Choice	Useful when
Direct provider API	Small workflow with clear dependencies
LangChain	Reusable model and tool interfaces
LangGraph	Stateful control flow and recovery

Choose a framework after defining the workflow

03 · Preparing Data and Checking Answers

01

Building an LLM Application

give instructions and check the answer format

02

Connecting LLM Calls


carry useful context between steps

03

Preparing Data and Checking Answers


test the application before releasing changes

§ Data for LLMs



Data for LLM Applications

Different data collections serve different purposes




Four collections, four **different** uses

Evaluation Set

Define expected behavior before changing the model or prompt

case-017

input	**"P-17 vibrates above 2500 rpm"**
expected label	**vibration**
expected evidence	**"vibrates"**
rubric	**label correct and evidence quoted**



Every prompt version runs on the same **frozen** cases

Evaluation Cases


Cover routine requests, rare failures, and abstention

Input	Expected behavior
Clear vibration report	Label vibration; quote evidence
Conflicting measurements	Flag disagreement
Missing equipment identifier	Request clarification
Question without evidence	Abstain rather than invent

An evaluation set includes cases where answering is the failure

Synthetic Data

Generate candidates from a controlled seed and validate them



Generated notes stay **candidates** until checked

Synthetic Data Validation


Check more than whether the generated example reads well

Check	Maintenance-note example
Validity	The equipment type exists
Label consistency	Evidence supports the assigned label
Coverage	Include rare and ambiguous cases
Separation	Keep evaluation seeds out of training

Generated examples remain candidates until validated

Caveat: Synthetic Coverage

Generated variants may repeat the seed distribution




Volume grew 100×; the missing categories stayed missing

More variants of the seed add **no new** categories

Filtering and Deduplication

Clean records and keep their provenance before splitting



Each stage removes records and **keeps provenance**

Exact Deduplication

Hash normalized text and keep a reference to every source

```
import hashlib
def key(text):
    normalized = ' '.join(text.split())
    return hashlib.sha256(normalized.encode()).hexdigest()

# Group source records by key; retain provenance for the group.
```

Near-Duplicate Detection

Similarity finds candidates that exact hashes miss

Method	What it compares	Caveat
Shingles / MinHash	Token overlap	Misses deep paraphrases
Embeddings	Semantic similarity	May merge distinct facts
Source grouping	Document / event lineage	Needs metadata

Duplicate candidates need a task-specific merge rule

Dataset Split

Keep tuning examples separate from the final evaluation set


Development	Validation	Held-out test
event A	event B	event C
P-17 vibrates at 2500 rpm	P-18 leaks at the seal	P-17 noise after restart
pump P-17 shakes above 2500	seal leak on P-18	restart noise, P-17

Assign whole events to a split, never single paraphrases

Paraphrases of one event stay in **one** split


Caveat: Near-Duplicate Leakage

Paraphrases can leak the same case across splits



Exact hashing misses a **paraphrase** of the same case

§ Evaluation and Release



Evaluation Metrics


Measure task correctness and system behavior separately

Dimension	Measure
Task success	Rubric pass rate
Evidence	Supported claims / evaluated claims
Schema	Valid responses / responses
Operations	Latency, token cost, failure rate

One aggregate score cannot diagnose every failure

LLM-as-Judge

A judge applies a rubric to candidate outputs



Swap the order
same verdict? else position bias


Human-labeled sample
measure agreement first

Version the judge prompt
scores change with it

Check the judge **before** trusting its scores

LLMOps Trace

A trace connects the request to every intermediate step



The trace shows **which step** failed

Case study: Maintenance Triage


A prompt change must survive the same labeled cases

Version	Change	Comparison
p1	Free-text labels	Baseline
p2	Fixed enum + evidence field	Schema failures
p3	Explicit ambiguous-case policy	Wrong labels + abstentions

Changing the prompt changes the system under evaluation

Controlled LLM Release

Promote the versioned application after regression checks



Freeze → Evaluate → Release → Monitor

Takeaway: Build and evaluate the whole LLM application

1. Separate prompts, context, schemas, and control flow
2. Curate evaluation data before optimizing the application
3. Version the system and inspect failures in traces