IMEN574 / IDSC574 · PROGRAMMING FOR AX

22

AI for Data Science

Sangwoo Mo · POSTECH
Spring 2027

Where We Are

01 **Programming with AI**

Lectures 2–4

02 **Python and Classical Machine Learning**

Lectures 5–13

03 **Deep Learning and Foundation Models**

Lectures 14–22

Outline: AI for Data Science

01 **Tabular Learning**

Match model priors to tables

02 **Time-Series Forecasting**

Preserve the forecast origin

03 **Automating Experiments**

Search without moving the test

01 · Tabular Learning

01 **Tabular Learning**

Match model priors to tables

02 **Time-Series Forecasting**

Preserve the forecast origin

03 **Automating Experiments**

Search without moving the test

Why Data Modality Matters

A foundation model inherits assumptions from its training tasks

Data	Structure	Strong baseline
Table	Heterogeneous columns	Linear model or trees
Time series	Ordered history	Seasonal naive
Text or image	Pretrained representation	Frozen encoder

Tabular Prediction Contract

Columns, rows and target timing define the task

Schema	age	balance	default
Row A	23	100	0
Row B	42	80	1

A column is usable only if it exists at prediction time


Heterogeneous Features

Numeric scale and category identity need different treatment

Column	Type	Operation
Temperature	Numeric	Scale if needed
Machine ID	Categorical	Encode identity
Timestamp	Temporal	Respect ordering

Tree Baselines


A simple model establishes the value of added complexity



A baseline anchors the comparison

Gradient Boosting


Successive trees correct remaining prediction error



A boosted model accumulates targeted corrections

Tabular Foundation Models


Pretraining can supply a prior over supervised table tasks



https://arxiv.org/abs/2207.01848

Prior-Fitted Networks

Task simulation moves part of the learning effort into pretraining



The pretraining task distribution supplies the prior

https://arxiv.org/abs/2207.01848

Inference-Time Context

Training rows and query rows play different roles

Train row 1	x1	y1
Train row 2	x2	y2
Query row	x*	?

The query target must remain hidden


Caveat: Prior Mismatch

A learned task prior may not cover the deployment regime

Change	Check
More rows or columns	Supported limits
New target type	Model scope
Missing patterns	Validation slice
New domain	Held-out data

Text-to-SQL and Table QA

A fluent query must still match the data schema and intent



The database verifies syntax while task checks verify intent

A Table Model Decision

Compare predictive value, resource cost and auditability

Criterion	Evidence
Prediction	Same validation split
Cost	Measured runtime and memory
Scope	Supported task and input
Audit	Repeatable preprocessing

02 · Time-Series Forecasting

01 **Tabular Learning**

Match model priors to tables

02 **Time-Series Forecasting**

Preserve the forecast origin

03 **Automating Experiments**

Search without moving the test

Why Time Order Matters


Future observations cannot help a past forecast

Time	t1	t2	t3	t4	t5
Split	train	train	train	test	test

The evaluation origin separates history from the future

Forecast Horizon


The target is a future path with a stated length



A forecast is tied to an origin and horizon

Seasonal Naive Baseline

Repeat the last observed seasonal pattern before fitting complexity



The last cycle supplies a transparent forecast


Decomposition View

Trend, seasonality and residuals describe different variation

$$y_t = g(t) + s(t) + h(t) + \varepsilon_t$$

Decomposition Components

A structured forecast separates recurring and nonrecurring effects



The observed series combines a rising trend and a repeating seasonal component

Rolling-Origin Evaluation


Move the forecast origin while preserving temporal order

	t1	t2	t3	t4	t5
Origin 1	T	T	T	V	-
Origin 2	T	T	T	T	V

Each evaluation uses only the history available at its origin

Time-Series Foundation Models

Pretraining can transfer patterns across series



Transferred patterns condition a forecast for a new series

https://arxiv.org/abs/2310.10688

Patch-Based Forecasting

A sequence model can process time-series patches




Time patches form the forecasting context

https://arxiv.org/abs/2310.10688

Quantiles and Uncertainty


A forecast distribution supports several decision thresholds



Forecast intervals widen in this illustrative example

Distribution Shift

A new regime can invalidate an otherwise useful history



The historical level no longer matches the new regime

Caveat: Future Covariates

A forecast feature must be known at the forecast origin

Feature	Available?
Calendar day	Yes
Scheduled price	If published
Future actual demand	No
Revised final sensor data	Often no

03 · Automating Experiments

01 **Tabular Learning**

Match model priors to tables

02 **Time-Series Forecasting**


Preserve the forecast origin

03 **Automating Experiments**

Search without moving the test

Why an Experiment Agent

Automating model trials also automates the opportunity for leakage



Every automated trial must preserve the evaluation contract

Immutable Evaluation Contract

Freeze the split, metric and test boundary before search

Rule 1	Split	fixed
Rule 2	Metric	fixed
Rule 3	Test labels	sealed
Rule 4	Budget	bounded

Search changes candidates while the evaluation contract stays fixed


Candidate Registry

Each trial has a reproducible configuration and result

Trial	Model	Validation
A	Seasonal naive	0.80 MAE
B	Ridge	0.72 MAE
C	Small tree	0.76 MAE

Evidence Before Promotion


A validation winner needs one final held-out check



The test set evaluates a frozen selection procedure

Budget Allocation

Search breadth competes with repeatability and verification time




Illustrative ten-run budget

Some budget must remain for checking the chosen result

Failure Recovery


An exception should record the failed trial rather than erase it



A failed trial remains part of the experiment record

Data Access Boundaries

The experiment agent needs training access, not hidden test answers



Data permissions should enforce the intended split

Reproducibility Record

Keep code, data identity, seed and environment with the score

Artifact	Purpose
Code revision	Recreate the method
Data fingerprint	Recreate the input
Seed and environment	Interpret variation
Metric implementation	Recreate the score


Human Decision Point

A better score does not automatically justify deployment

Question	Decision evidence
Error cost	Task loss
Shift	New-domain evaluation
Runtime	Measured constraints
Explanation	Inspection and limits

A Verified AI Workflow

The output is a repeatable experiment with a defensible conclusion



A useful workflow connects a question to reproducible evidence

Takeaway: AI for Data Science

01 A strong baseline makes added complexity measurable

02 Forecasts use only information available at the origin

03 An experiment agent must preserve the evaluation contract