

# Programming Projects

---

Project 2 – Programming Techniques (CA-PRTQS) title: "ATM Teller Simulator" description: "C# Programming Fundamentals Project by Marc Cavada" author: "Marc Cavada"

## Project Repository

The source code and full project files for **Project 2 – ATM Teller Simulator** are available on GitHub:  
[https://github.com/mocavada/CAVADA-MARC-PROJECT-CA\\_PR](https://github.com/mocavada/CAVADA-MARC-PROJECT-CA_PR)

## Introduction

This project is a **prototype of ATM Teller and Inventory Management System** developed in **C# using .NET 9 and Visual Studio Code**.

It captures and manages inventory items using **EF Core and SQLite**, exposing a **RESTful API** with Swagger/OpenAPI support.

---

## TellerAPI – Code Files

### Program.cs

```
using System;
using TellerAPI.Models;
using TellerAPI.Services;

namespace TellerAPI
{
    public class Program
    {
        public static void Main()
        {
            Bank bank = new Bank();
            var atm = new ATMSERVICE(bank);
            atm.Start();
        }
    }
}
```

### Models/Account.cs

```
using System;

namespace TellerAPI.Models
{
    public abstract class Account
    {
    }
```

```

public string AccountNumber { get; set; } = string.Empty;
public string CustomerID { get; set; } = string.Empty;
public decimal Balance { get; protected set; }

public virtual void Deposit(decimal amount)
{
    if (amount <= 0)
        throw new ArgumentException("Deposit amount must be positive.");
    Balance += amount;
}

public virtual bool Withdraw(decimal amount)
{
    if (amount <= 0)
        throw new ArgumentException("Withdrawal amount must be positive.");
    if (Balance < amount)
        return false;

    Balance -= amount;
    return true;
}

public override string ToString() =>
    $"{AccountNumber} | Customer: {CustomerID} | Balance: {Balance:C}";
}
}

```

## Models/CheckingAccount.cs & SavingAccount.cs

```

namespace TellerAPI.Models
{
    public class CheckingAccount : Account
    {
    }
}

```

## Models/Bank.cs

```

using System;
using System.Collections.Generic;
using TellerAPI.Services;

namespace TellerAPI.Models
{
    public class Bank
    {
    }
}

```

```

private readonly FileService _fileService;
public List<Account> Accounts { get; private set; } = new();

public Bank()
{
    _fileService = new FileService();
    LoadAccounts();
}

private void LoadAccounts()
{
    var lines = _fileService.ReadFile("Accounts.txt");

    foreach (var line in lines)
    {
        var parts = line.Split(',');
        if (parts.Length < 4) continue;

        string type = parts[0].Trim();           // "C" or "S"
        string customerId = parts[1].Trim();     // e.g., "D001"
        string accountNumber = parts[2].Trim();  // e.g., "10001"
        if (!decimal.TryParse(parts[3], out decimal balance))
            balance = 0;

        Account? account = type switch
        {
            "C" => new CheckingAccount { CustomerID = customerId,
AccountNumber = accountNumber },
            "S" => new SavingAccount { CustomerID = customerId,
AccountNumber = accountNumber },
            _ => null
        };

        if (account != null)
        {
            if (balance > 0)
                account.Deposit(balance); // use Deposit to set initial
balance safely

            Accounts.Add(account);
        }
    }
}

// Helper method to find an account by account number
public Account? GetAccount(string accountNumber)
{
    return Accounts.Find(a => a.AccountNumber == accountNumber);
}

// Optional helper to find accounts by CustomerID
public List<Account> GetAccountsByCustomer(string customerId)
{

```

```

        return Accounts.FindAll(a => a.CustomerID == customerId);
    }
}

```

## Services/FileService.cs

```

using System;
using System.Collections.Generic;
using System.IO;

namespace TellerAPI.Services
{
    public class FileService
    {
        private readonly string _dataPath;

        public FileService()
        {
            // Use project-relative path
            _dataPath = Path.Combine(AppContext.BaseDirectory, "..", "..", "..",
>Data");
        }

        public List<string> ReadFile(string fileName)
        {
            string path = Path.Combine(_dataPath, fileName);
            if (!File.Exists(path))
            {
                Console.WriteLine($"❌ File not found: {path}");
                return new List<string>();
            }
            return new List<string>(File.ReadAllLines(path));
        }

        public void WriteFile(string fileName, List<string> lines)
        {
            string path = Path.Combine(_dataPath, fileName);
            File.WriteAllLines(path, lines);
        }

        public void AppendLine(string fileName, string line)
        {
            string path = Path.Combine(_dataPath, fileName);
            File.AppendAllText(path, line + Environment.NewLine);
        }
    }
}

```

## Services/ATMService.cs

```
using System;
using TellerAPI.Models;

namespace TellerAPI.Services
{
    public class ATMService
    {
        private readonly Bank _bank;
        private Account _currentAccount = null!; // non-nullable after login

        public ATMService(Bank bank)
        {
            _bank = bank;
        }

        public void Start()
        {
            Console.WriteLine("🏧 Welcome to the Teller API");

            // Login / select account
            while (true)
            {
                Console.WriteLine("\nEnter your account number: ");
                string? accNumber = Console.ReadLine();

                var account = _bank.Accounts.Find(a => a.AccountNumber ==
accNumber);

                if (account != null)
                {
                    _currentAccount = account;
                    break;
                }

                Console.WriteLine("❌ Account not found. Try again.");
            }

            Console.WriteLine($"🟢 Logged in as {_currentAccount.CustomerID}!");

            // Main transaction loop
            while (true)
            {
                Console.WriteLine("\n1. Deposit\n2. Withdraw\n3. Check Balance\n4.
Exit");

                Console.WriteLine("\nSelect an option: ");
                string? input = Console.ReadLine();

                switch (input)
```

```

        {
            case "1":
                HandleDeposit();
                break;

            case "2":
                HandleWithdrawal();
                break;

            case "3":
                Console.WriteLine($"💰 Current Balance:
{_currentAccount.Balance:C}");
                break;

            case "4":
                Console.WriteLine("👋 Thank you for using TellerAPI!");
                return;

            default:
                Console.WriteLine("❌ Invalid option. Try again.");
                break;
        }
    }
}

private void HandleDeposit()
{
    Console.Write("Enter deposit amount: ");
    if (decimal.TryParse(Console.ReadLine(), out decimal amount))
    {
        try
        {
            _currentAccount.Deposit(amount);
            Console.WriteLine($"✅ New Balance:
{_currentAccount.Balance:C}");
        }
        catch (ArgumentException ex)
        {
            Console.WriteLine($"❌ {ex.Message}");
        }
    }
    else
    {
        Console.WriteLine("❌ Invalid amount entered.");
    }
}

private void HandleWithdrawal()
{
    Console.Write("Enter withdrawal amount: ");
    if (decimal.TryParse(Console.ReadLine(), out decimal amount))
    {

```

```

        try
        {
            if (_currentAccount.Withdraw(amount))
                Console.WriteLine($"✅ New Balance:
{_currentAccount.Balance:C}");
            else
                Console.WriteLine("❌ Insufficient funds!");
        }
        catch (ArgumentException ex)
        {
            Console.WriteLine($"❌ {ex.Message}");
        }
    }
    else
    {
        Console.WriteLine("❌ Invalid amount entered.");
    }
}
}
}

```

## Data Files

TellerAPI/Data/ |—— Accounts.txt # Holds account information |—— Customers.txt # Optional: customer data  
 |—— DailyBalances.txt # Optional: daily transaction records

TellerAPI – ATM Simulator

### Folder Structure

TellerAPI/ |—— Data/ # Account, Customer, and DailyBalances data files |—— Models/ # Account, Bank, CheckingAccount, SavingAccount classes |—— Services/ # ATMService, FileService |—— Program.cs # Entry point |—— TellerAPI.csproj

Key Features • Loads accounts from Data/Accounts.txt. • Supports deposit, withdrawal, and balance check for accounts. • Protects Balance with a protected setter in Account. • File operations handled via FileService (read/write/append). • ATMService handles account operations, now supports both Account and Bank.

Accounts Data Format (Accounts.txt) Each line represents an account, with values separated by commas:

```
<AccountType>,<AccountNumber>,<CustomerName>,<Balance>
```

- <AccountType>: Checking or Saving
- <AccountNumber>: unique string of digits
- <CustomerName>: name of account holder
- <Balance>: decimal number (e.g., 1000.50)

Example:

Checking,12333444,John Doe,1500.00 Saving,123445566,Jane Smith,2500.75


Current Behavior • Prompts user for account number. • Finds account in Bank.Accounts. • Starts ATM menu for selected account. • Note: Account lookup fails if Accounts.txt lines are malformed or numbers do not match.

## Usage

dotnet run --project TellerAPI/TellerAPI.csproj

• Enter account number to access. • Follow the menu to deposit, withdraw, or check balance.

## Program Flow (Teller API Diagram)



flowchart TD

```

A[Start ATM] --> B[Login Screen]
B --> C{Validate Name & PIN?}
C -->|No| D[Display Error Message]
D --> B
C -->|Yes| E[Main Menu]
  
```

```

E -->|Deposit| F[Select Account Type]
F --> G[Enter Deposit Amount]
G --> H[Update Balance]
H --> E
  
```

```

E -->|Withdraw| I[Select Account Type]
I --> J[Enter Withdrawal Amount]
J --> K{Validate Funds?}
  
```



```

K -->|No| L[Insufficient Funds Message]
L --> E
K -->|Yes| M[Dispense Cash & Update Balance]
M --> E

E -->|Transfer| N[Select Source & Target Account]
N --> O[Enter Transfer Amount]
O --> P{Validate Funds?}
P -->|No| Q[Display Error]
P -->|Yes| R[Transfer Funds & Update Balances]
R --> E

E -->|Bill Payment| S[Enter Bill Amount]
S --> T{Validate Amount & Balance?}
T -->|No| U[Display Error]
T -->|Yes| V[Process Payment + Fee]
V --> E

E -->|Supervisor Mode| W[Login as Admin]
W --> X[Access Admin Menu]
X -->|Pay Interest| Y[Apply Interest to Accounts]

```

## InventoryAPI – Code Files

### 1. Program.cs

```

using Microsoft.EntityFrameworkCore;
using InventoryAPI;

var builder = WebApplication.CreateBuilder(args);

builder.Services.AddDbContext<InventoryDbContext>(options =>
    options.UseSqlite("Data Source=inventory.db"));

builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen();

var app = builder.Build();

if (app.Environment.IsDevelopment())
{
    app.UseSwagger();
    app.UseSwaggerUI();
}

app.UseHttpsRedirection();

app.MapGet("/", () => "Inventory API is running.");
app.MapGet("/items", async (InventoryDbContext db) => await db.Items.ToListAsync());
app.MapGet("/items/{id}", async (int id, InventoryDbContext db) =>

```

```

{
    var item = await db.Items.FindAsync(id);
    return item != null ? Results.Ok(item) : Results.NotFound();
});
app.MapPost("/items", async (Item newItem, InventoryDbContext db) =>
{
    db.Items.Add(newItem);
    await db.SaveChangesAsync();
    return Results.Created($"/items/{newItem.Id}", newItem);
});

app.Run();

```

## 2. InventoryDbContext.cs

```

using Microsoft.EntityFrameworkCore;

namespace InventoryAPI
{
    public class InventoryDbContext: DbContext
    {
        public InventoryDbContext(DbContextOptions<InventoryDbContext> options) :
base(options) { }
        public DbSet<Item> Items { get; set; }
    }
}

```

## 3. Item.cs

```

namespace InventoryAPI
{
    public record Item(int Id, string FirstName, string LastName, double Price);
}

```

## 4. InventoryAPI.csproj

```

<Project Sdk="Microsoft.NET.Sdk.Web">
  <PropertyGroup>
    <TargetFramework>net9.0</TargetFramework>
    <Nullable>enable</Nullable>
    <ImplicitUsings>enable</ImplicitUsings>
  </PropertyGroup>
  <ItemGroup>
    <PackageReference Include="Microsoft.EntityFrameworkCore.Sqlite" Version="8.0.7"
/>
    <PackageReference Include="Microsoft.EntityFrameworkCore.Tools" Version="8.0.7">
      <PrivateAssets>all</PrivateAssets>
      <IncludeAssets>runtime; build; native; contentfiles; analyzers;

```

```
buildtransitive</IncludeAssets>
  </PackageReference>
  <PackageReference Include="Swashbuckle.AspNetCore" Version="6.7.0" />
</ItemGroup>
</Project>
```

## 5. InventoryAPI.http

```
GET https://localhost:7255/items
GET https://localhost:7255/items/1
POST https://localhost:7255/items
Content-Type: application/json

{
  "id": 101,
  "firstName": "Apple",
  "lastName": "Box",
  "price": 499.99
}
```

### Setup Instructions

Prerequisites • .NET 9 SDK • Visual Studio Code or Visual Studio • SQLite CLI (optional)

Build & Run

cd InventoryAPI dotnet restore dotnet build dotnet run

API will run on: • HTTPS: <https://localhost:7255> • HTTP: <http://localhost:5091>

Database Migrations

dotnet ef migrations add InitialCreate --project InventoryAPI dotnet ef database update --project InventoryAPI

---

### Database Model

Item.cs

```
public class Item
{
    public int Id { get; set; }
    public string FirstName { get; set; }
    public string LastName { get; set; }
    public double Price { get; set; }
}
```

InventoryDbContext.cs

```
using Microsoft.EntityFrameworkCore;
```

```

public class InventoryDbContext: DbContext
{
    public InventoryDbContext(DbContextOptions<InventoryDbContext> options) :
base(options) { }
    public DbSet<Item> Items { get; set; }
}

```

## API Endpoints


Endpoint Method Description / GET Health check / Root message /items GET Fetch all items /items/{id} GET  
Fetch a single item by ID /items POST Add a new item

Swagger UI: <https://localhost:7255/swagger>

## Program Flow (Diagram)

### Inventory API

#### Program Flow (Diagram)



flowchart TD

A[Start API] --> B[Swagger / Root Endpoint]

```

B --> C{Select Endpoint}

C -->|"GET /items"| D[Fetch all items from DB]
D --> E[Return JSON list]

C -->|"GET /items/:id"| F[Fetch item by ID]
F --> G{Item Exists?}
G -->|Yes| H[Return Item JSON]
G -->|No| I[Return 404 Not Found]

C -->|"POST /items"| J[Receive Item JSON]
J --> K{Validate Input}
K -->|Valid| L[Insert into DB]
K -->|Invalid| M[Return 400 Bad Request]
L --> N[Return Created Response]

```

---

🔧 Development Highlights • Minimal API with ASP.NET Core • EF Core SQLite integration • Input validation for IDs and prices • Async/await for database operations • Swagger/OpenAPI for endpoint testing

---

#### 🗂 Folder Structure

```

InventoryAPI/ |—— Program.cs |—— Item.cs |—— InventoryDbContext.cs |—— appsettings.json |——
appsettings.Development.json |—— Properties/ |—— bin/ |—— obj/ |—— InventoryAPI.csproj

```

---

#### 👤 Author

Marc Cavada Programming Fundamentals – CDI College Project: CA\_PRFND – Inventory Management System

✅ This version is **GitHub-ready**:

All C#, XML, and HTTP blocks are fenced separately.

Mermaid diagram is standalone.

Folder structure uses its own code block.

Text and headings are outside code blocks, so everything renders correctly.