

Spatio-Spectral Structure Tensor Total Variation for Hyperspectral Image Denoising and Destriping

Shingo Takemoto, *Student Member, IEEE*, Shunsuke Ono, *Member, IEEE*,

Abstract—We propose a novel regularization function, Graph-Aided Spatio-Spectral Total Variation (GASSTV), for hyperspectral (HS) image denoising. Spatio-Spectral Total Variation (SSTV), defined using second-order spatio-spectral differences, is a widely used regularization approach that effectively captures the spatio-spectral piecewise smoothness specific to HS images, enabling robust noise removal. However, SSTV uniformly computes adjacent differences in spatial and spectral dimensions, leading to the corruption of complex spatial structures and abrupt spectral variations in HS images. To address these limitations, we incorporate spatial and spectral graphs that explicitly reflect the spatial and spectral structures into the regularization model. Furthermore, we design a framework to construct these graphs from the noisy HS image. In addition, we formulate the mixed noise removal problem as a convex optimization problem involving GASSTV and develop an efficient algorithm based on the preconditioned primal-dual splitting method to solve it. Experimental results on mixed noise removal demonstrate the superior performance of GASSTV compared with existing HS image regularization models.

Index Terms—Hyperspectral image, denoising, destriping, spatio-spectral regularization, total variation, structure tensor

I. INTRODUCTION

HYPERSPECTRAL (HS) images are three-dimensional data cubes, where each pixel contains a detailed spectrum spanning hundreds of contiguous wavelength bands from the ultraviolet to the near-infrared range. This rich spectral information can visualize materials and phenomena that are invisible in conventional RGB imagery. Furthermore, advanced analytical techniques, such as anomaly detection [1], [2], classification [3]–[5], and unmixing [6], [7], enable the extraction of advanced knowledge from HS images, which can be applied in various fields including agriculture, mineralogy, astronomy, and biotechnology [8]–[11]. Nevertheless, HS images are unavoidably degraded by various types of noise during acquisition arising from sensor defects, photon effects, atmospheric absorption, and other environmental factors [12]–[14]. Such degradations can severely hinder the performance of subsequent analyses, making effective HS image denoising an indispensable preprocessing step for ensuring reliable outcomes.

S. Takemoto is with the Department of Computer Science, Institute of Science Tokyo, Yokohama, 226-8501, Japan (e-mail: takemoto.s.e908@m.isct.ac.jp).

S. Ono is with the Department of Computer Science, Institute of Science Tokyo, Yokohama, 226-8501, Japan (e-mail: ono.s.5af2@m.isct.ac.jp).

This work was supported in part by Grant-in-Aid for JSPS Fellows Grant Number JP24KJ1068 and 23KJ0912, in part by JSPS KAKENHI under Grant 22H03610, 22H00512, 23H01415, 23K17461, 24K03119, and 24K22291, and in part by JST PRESTO under Grant JPMJPR21C4, JST AdCORP under Grant JPMJKB2307, and JST ACT-X Grant JPMJAX23CJ.

Over the past decade, HS image denoising methods have evolved along two main lines: deep neural network (DNN)-based approaches and model-based regularization approaches. DNN-based methods, including convolutional neural networks (CNNs), recurrent models, and transformer-based architectures, have achieved remarkable progress by learning complex spatial-spectral dependencies directly from data. Despite these capabilities, DNNs generally lack strong theoretical underpinnings, making their outputs difficult to interpret and their behavior hard to explain—an important drawback in applications where transparency and reliability are required. In contrast, model-based approaches explicitly encode the physical and statistical properties of HS images into mathematically well-defined formulations. While such methods require careful modeling of the complex nature of HS images, they can provide interpretable and theoretically grounded results. Motivated by these characteristics, this work focuses on advancing the model-based paradigm for HS image denoising.

Model-based approaches for HS image denoising can be broadly categorized into low-rank (LR) and total variation (TV) regularization frameworks. LR-based methods exploit the strong spectral correlations across all bands, modeling HS images as lying in a low-dimensional subspace. This enables the capture of nonlocal spectral relationships and effective suppression of random noise; however, LR models often incur high computational cost and may fail to preserve fine spatial details, especially when strong spatial structures are present. In contrast, TV-based methods are computationally efficient and have shown strong performance by modeling the spatial and spectral piecewise smoothness of HS images. Nevertheless, conventional TV formulations evaluate differences uniformly across adjacent pixels or bands, which limits their ability to preserve complex spatial structures and to capture abrupt spectral variations (spectral jumps), often resulting in the loss of important details. These limitations raise a natural research question: Can we design a TV-based regularization method that retains the efficiency and edge-preserving capabilities of TV while effectively capturing complex spatial structures and spectral jumps for robust HS image denoising and destriping? To answer this question, we would first like to provide a comprehensive review of existing TV-type regularization methods for HS images.

A. Existing TV-type Regularization Methods

The initial TV-based method for HS image denoising is the Spectral-Spatial Adaptive Hyperspectral TV (SSAHTV) [15], where proposed to model spatial piecewise smoothness. Subsequently, Anisotropic Spectral-Spatial TV (ASSTV) [2] was

introduced to incorporate spectral differences, capturing the correlation between bands. However, since these methods directly minimize the l_1 -norm of first-order differences, they tend to cause over-smoothing, as they cannot sufficiently distinguish between noise and inherent image gradients.

To overcome the over-smoothing issue associated with first-order differences, Spatio-Spectral Total Variation (SSTV) [4] was proposed. SSTV utilizes second-order spatio-spectral differences (i.e., spatial differences of spectral differences), which effectively models the spatial similarity between adjacent bands while avoiding the excessive smoothing typical of first-order methods [5]. Due to its effectiveness, SSTV has established itself as a strong baseline and has been extended into various forms.

Several variants have been developed to enhance SSTV's performance. Hybrid Spatio-Spectral TV (HSSTV) [7] incorporates first-order spatial differences into the SSTV framework to suppress the generation of continuous artifacts in the spectral direction [8]. To achieve sharper edges, l_0 - l_1 Hybrid TV (l_0 - l_1 HTV) [9] introduces an l_0 -norm constraint on spatial differences, allowing for direct control over the number of non-zero gradients (i.e., edge pixels) [10]. Furthermore, l_0 - l_1 - l_2 SSTV [11] employs the l_1 - l_2 metric (l_1 minus l_2) instead of the standard l_1 norm. This approach provides a tighter approximation to the l_0 norm, thereby sharpening sparsity and avoiding staircase artifacts [12]. Additionally, Spatio-Spectral Structure Tensor TV (S3TTV) captures semi-local spatial structures by evaluating the correlation of difference vectors within semi-local areas using the nuclear norm. However, a common limitation of SSTV and these variants is that they evaluate adjacent differences uniformly in both spatial and spectral directions. Consequently, they often fail to preserve complex spatial structures and spectral jumps (abrupt spectral changes), smoothing them out indistinguishably from noise.

On the other hand, Graph Spatio-Spectral TV (GSSTV) addresses the spatial limitation by weighting the spatial difference operator based on a spatial graph, successfully maintaining complex spatial structures. Nevertheless, GSSTV remains uniform in the spectral direction, failing to capture spectral discontinuities. Furthermore, since the graph weighting is directly incorporated into the SSTV formulation (second-order differences), it suffers from reduced power in determining the solution (regularization ability) compared to methods that explicitly constrain first-order characteristics.

B. Motivation and Contribution

In this paper, we propose a novel method that incorporates both spatial and spectral graph-based TVs into SSTV, called Graph-Aided Spatio-Spectral Total Variation (GASSTV). The main contributions of this article are listed below:

- We propose a novel regularization method, Graph-Aided Spatio-Spectral Total Variation (GASSTV), which incorporates spatial and spectral graph-based weighted TVs separately from SSTV. These graph-based TVs enhance the noise removal capabilities of SSTV while preserving complex spatial structures and spectral jumps. Furthermore, we robustly construct the spectral graph from the noisy HS image (Refer to GSSTV for constructing the spatial graph).

- We formulate the HS image denoising problem as a constrained convex optimization problem involving GASSTV. To simplify parameter tuning, we impose data fidelity and sparse noise characterization terms as constraints rather than adding them to the objective function.
- We develop an efficient algorithm based on Preconditioned Primal-Dual Splitting Method (P-PDS) [16], [17] to solve our optimization problem. Unlike standard PDS [18], [19], P-PDS automatically determines appropriate stepsizes.

Finally, we demonstrate the effectiveness of GASSTV by comparing it with state-of-the-art HS image regularization methods through HS image denoising experiments.

II. PRELIMINARIES

A. Notations

Throughout this paper, we denote vectors and matrices by boldface lowercase letters (e.g., $\mathbf{x}$) and boldface capital letters (e.g., $\mathbf{X}$), respectively. We treat an HS image, denoted by $\mathbf{u}$ with N_1 vertical pixels, N_2 horizontal pixels, and N_3 bands. We denote the total number of elements in the HS image by $N = N_1 N_2 N_3$. For a matrix data $\mathbf{X} \in \mathbb{R}^{N_1 \times N_2}$, the value at the location (i, j) is denoted by $[\mathbf{X}]_{i,j}$. The l_1 -norm and the l_2 -norm of a vector $\mathbf{x} \in \mathbb{R}^N$ are defined as $\|\mathbf{x}\|_1 := \sum_{n=1}^N |x_n|$ and $\|\mathbf{x}\|_2 := \sqrt{\sum_{n=1}^N x_n^2}$, respectively, where x_n represents the n -th entry of $\mathbf{x}$. The nuclear norm of a matrix, which is the sum of all the singular values, is denoted by $\|\cdot\|_*$. For an HS image $\mathbf{u} \in \mathbb{R}^N$, let $\mathbf{D}_v \in \mathbb{R}^{N \times N}$, $\mathbf{D}_h \in \mathbb{R}^{N \times N}$, and $\mathbf{D}_\lambda \in \mathbb{R}^{N \times N}$ be the forward difference operators along the horizontal, vertical, and spectral directions, respectively, with the periodic boundary condition. Here, a spatial difference operator is denoted by $\mathbf{D}_{vh} := (\mathbf{D}_v^\top \ \mathbf{D}_h^\top)^\top \in \mathbb{R}^{2N \times N}$. Using $\mathbf{D}_v$, $\mathbf{D}_h$, and $\mathbf{D}_\lambda$, we denote the second-order spatio-spectral differences by $\mathbf{D}_v \mathbf{D}_\lambda \mathbf{u} \in \mathbb{R}^N$ and $\mathbf{D}_h \mathbf{D}_\lambda \mathbf{u} \in \mathbb{R}^N$. Other notations will be introduced as needed.

B. Proximal Tools

In this chapter, we introduce basic proximal tools that play a central role in the optimization part of our method. Let f be a *proper lower semi-continuous convex function*.¹ Then, for $\gamma > 0$, the *proximity operator* of f is defined by

$$\text{prox}_{\gamma, f}(\mathbf{x}) := \arg \min_{\mathbf{y} \in \mathbb{R}^N} f(\mathbf{y}) + \frac{1}{2\gamma} \|\mathbf{x} - \mathbf{y}\|_2^2. \quad (1)$$

The *Fenchel-Rockafellar conjugate function* f^* of the function f is defined by

$$f^*(\mathbf{x}) := \sup_{\mathbf{y}} \langle \mathbf{x}, \mathbf{y} \rangle - f(\mathbf{y}), \quad (2)$$

where $\langle \cdot, \cdot \rangle$ is the Euclidean inner product. Thanks to a generalization of Moreau's identity [20], the proximity operator of f^* is calculated as

$$\text{prox}_{\gamma, f^*}(\mathbf{x}) = \mathbf{x} - \gamma \text{prox}_{\frac{1}{\gamma} f} \left(\frac{1}{\gamma} \mathbf{x} \right). \quad (3)$$

¹A function $f : \mathbb{R}^N \rightarrow (-\infty, \infty]$ is called a *proper lower semi-continuous convex function* if $\{\mathbf{x} \in \mathbb{R}^N | f(\mathbf{x}) < \infty\}$ is nonempty, $\{\mathbf{x} \in \mathbb{R}^N | f(\mathbf{x}) \leq \alpha\}$ is closed for every $\alpha \in \mathbb{R}$, and $f(\lambda \mathbf{x} + (1-\lambda)\mathbf{y}) \leq \lambda f(\mathbf{x}) + (1-\lambda)f(\mathbf{y})$ for every $\mathbf{x}, \mathbf{y} \in \mathbb{R}^N$ and $\lambda \in (0, 1)$.

The indicator function of a set $C \subset \mathbb{R}^N$, denoted by ι_C , is defined as

$$\iota_C(\mathbf{x}) := \begin{cases} 0, & \text{if } \mathbf{x} \in C, \\ \infty, & \text{otherwise.} \end{cases} \quad (4)$$

The function ι_C is proper lower semi-continuous convex when C is nonempty and closed convex. The proximity operator of ι_C is equivalent to the projection onto C , as given by

$$\text{prox}_{\iota_C}(\mathbf{x}) = P_C(\mathbf{x}) := \underset{\mathbf{y} \in C}{\operatorname{argmin}} \|\mathbf{y} - \mathbf{x}\|_2. \quad (5)$$

C. Primal-Dual Splitting Method (PDS)

The PDS [18], [19], on which our algorithm is based, is an efficient algorithm for solving the following generic form of convex optimization problems:

$$\min_{\mathbf{x}, \mathbf{y}} \varphi(\mathbf{x}) + f(\mathbf{x}) + g(\mathbf{y}) \text{ s.t. } \mathbf{y} = \mathbf{A}\mathbf{x}, \quad (6)$$

where $f : \mathbb{R}^n \rightarrow (-\infty, +\infty]$ and $g : \mathbb{R}^m \rightarrow (-\infty, +\infty]$ are proper lower semi-continuous convex functions, $\mathbf{A} \in \mathbb{R}^{m \times n}$ is a linear operator, φ is differentiable and its gradient $\nabla\varphi$ is β -Lipschitz continuous for some real constant $\beta > 0$, i.e., $\|\nabla\varphi(\mathbf{x}_1) - \nabla\varphi(\mathbf{x}_2)\| \leq \beta\|\mathbf{x}_1 - \mathbf{x}_2\|$ for any $\mathbf{x}_1, \mathbf{x}_2 \in \mathbb{R}^n$.

These methods solve Prob. (6) by the following iterative procedures:

$$\begin{cases} \mathbf{x}^{(t+1)} \leftarrow \text{prox}_{\gamma_1, f}(\mathbf{x}^{(t)} - \gamma_1(\nabla\varphi(\mathbf{x}^{(t)}) + \mathbf{A}^\top \mathbf{y}^{(t)})), \\ \mathbf{y}^{(t+1)} \leftarrow \text{prox}_{\gamma_2, g^*}(\mathbf{y}^{(t)} - \gamma_2 \mathbf{A}(2\mathbf{x}^{(t+1)} - \mathbf{x}^{(t)})), \end{cases} \quad (7)$$

where γ_1 and γ_2 are the stepsize parameters, satisfying

$$\gamma_1 \gamma_2 \sigma_{\max}(\mathbf{A}^\top \mathbf{A}) < 1, \quad (8)$$

where $\sigma_{\max}(\cdot)$ is the maximum singular value of $(\cdot)$. Then, the sequences $(\mathbf{x}^{(t)})_{t \in \mathbb{N}}$ converge to an optimal solution of Prob. (6) [18], [19].

D. Weighted Spatial Difference Operator based on Spatial Graph by GSSTV [21]

Since we only obtain a noisy HS image in real situations, we construct a spatial graph via a guide image computed by

$$\mathbf{v}'(i, j) := \frac{1}{N_3} \sum_{c=1}^{N_3} \mathbf{v}(i, j, c), \quad (9)$$

where $\mathbf{v}$ is a given HS image. The guide image is averaged in the spectral direction to reduce noise while maintaining the spatial structure. Next, we consider to construct a weighted graph $\mathcal{G}_{\text{sp}}(\mathbf{v}', \mathcal{E}_{\text{sp}}, \mathbf{W}'_{\text{sp}})$ with the edges $e_{p,q} \in \mathcal{E}_{\text{sp}}$ (p and q are indices of pixels ($1 \leq p < q \leq N_1 N_2$)). The weight matrix $\mathbf{W}'_{\text{sp}} \in \mathbb{R}^{|\mathcal{E}_{\text{sp}}| \times |\mathcal{E}_{\text{sp}}|}$ is a diagonal matrix whose entries are the weights $w_{e_{p,q}} \in (0, 1]$ assigned to the edges $e_{p,q}$, defined as

$$w_{e_{p,q}} := \exp\left(-\frac{(v'_p - v'_q)^2}{2\sigma_{\text{sp}}^2}\right), \quad (10)$$

where σ_{sp} is a parameter. The value of $w_{e_{p,q}}$ is large as the correlation between v'_p and v'_q is higher. We also introduce

the incidence matrix $\mathbf{D} \in \mathbb{R}^{|\mathcal{E}_{\text{sp}}| \times N_1 N_2}$ for a graph $\mathcal{G}_{\text{sp}}$ as follows:

$$\mathbf{D}_{e_{p,q},k} = \begin{cases} -1 & \text{if } p = k, \\ 1 & \text{if } q = k, \quad (\forall k = 1, \dots, N_1 N_2). \\ 0 & \text{otherwise,} \end{cases} \quad (11)$$

To apply the spatial graph total variation to the entire HS image, we extend the weight matrix $\mathbf{W}'_{\text{sp}}$ and the incidence matrix $\mathbf{D}$ to block diagonal matrices $\mathbf{W}_{\mathcal{G}_{\text{sp}}} \in \mathbb{R}^{N_3 |\mathcal{E}_{\text{sp}}| \times N_3 |\mathcal{E}_{\text{sp}}|}$ and $\mathbf{D}_{\mathcal{G}_{\text{sp}}} \in \mathbb{R}^{N_3 |\mathcal{E}_{\text{sp}}| \times N}$, each consisting of N_3 repetitions of $\mathbf{W}'_{\text{sp}}$ and $\mathbf{D}$, respectively, defined as:

$$\mathbf{W}_{\mathcal{G}_{\text{sp}}} := \text{diag}(\mathbf{W}'_{\text{sp}}, \dots, \mathbf{W}'_{\text{sp}}), \quad \mathbf{D}_{\mathcal{G}_{\text{sp}}} := \text{diag}(\mathbf{D}, \dots, \mathbf{D}). \quad (12)$$

Then, the weighted spatial graph difference operator for an HS image is given by $\mathbf{W}_{\mathcal{G}_{\text{sp}}} \mathbf{D}_{\mathcal{G}_{\text{sp}}}$.

III. PROPOSED METHOD

We propose a novel regularization function incorporating spatial and spectral graphs. For the spatial graph, we utilize the construction described in Sec. II-D. In the following, we first describe define the spectral graph and then present the proposed regularization function. Subsequently, we formulate an HS image denoising problem as a constrained convex optimization problem involving the GASSTV regularization function and finally develop an algorithm to solve it.

A. Spectral Graph-based Weighted Difference Operator

In constructing the spectral graph from a noisy HS image, we assume that when the HS image is segmented, each segment contains similar spectral characteristics. Based on this assumption, we first segment the noisy HS image into K regions and then construct a spectral graph for each segment using its representative spectrum. To obtain the segments, we compute the guide image $\mathbf{v}'$ that reflects the spatial structure of the target HS image according to Eq. (9). Using the k-means clustering algorithm [22] on the guide image $\mathbf{v}'$, we obtain K segments $\{\mathcal{S}_k\}_{k=1}^K$ by solving the following minimization problem:

$$\min_{\{\mathcal{S}_k\} \{\mu_k\}} \sum_{k=1}^K \sum_{(i,j) \in \mathcal{S}_k} \|\mathbf{v}'(i, j) - \mu_k\|_2^2, \quad (13)$$

where μ_k represents the centroid of the k -th segment. For each segment $\mathcal{S}_k$, we compute a representative spectrum $\mathbf{r}_k \in \mathbb{R}^{N_3}$ by averaging the spectral vectors of the noisy HS image within the segment:

$$\mathbf{r}_k := \frac{1}{|\mathcal{S}_k|} \sum_{(i,j) \in \mathcal{S}_k} \mathbf{v}(i, j, :), \quad (14)$$

where $\mathbf{v}(i, j, :)$ denotes the spectral vector with length N_3 at location (i, j) . By averaging the spectral vectors within each segment, the spectra of the segment can be effectively characterized while reducing noise.

Following the calculation of the representative spectra, we construct a spectral graph for each segment to explicitly capture spectral variations including smoothness and spectral

jumps. We design the graph nodes to represent the spectral adjacent differences and connect the nodes exhibiting similar variations. First, for the k -th segment, we calculate the spectral difference vector $\mathbf{d}_k \in \mathbb{R}^{N_3}$, where the p -th element $\mathbf{d}_{k,p}$ is defined as:

$$\mathbf{d}_{k,p} := \mathbf{r}_{k,p+1} - \mathbf{r}_{k,p}, \quad (1 \leq p \leq N_3 - 1) \quad (15)$$

where $\mathbf{r}_{k,p}$ is the p -th element of the representative spectrum $\mathbf{r}_k$. Here, we assume the Neumann boundary condition (i.e., $\mathbf{r}_{k,N_3} = 0$). Next, we define a graph $\mathcal{G}_\lambda^{(k)}$ where the nodes correspond to the difference indices. To construct the edges, we employ the M -nearest neighbor (M -NN) strategy based on the distance between the gradient values. Let $\mathcal{N}_k$ denote the set of the M nearest neighbors of the node p determined by the Euclidean distance $|\mathbf{d}_{k,p} - \mathbf{d}_{k,q}|$. The weight $w_{p,q}^{(k)}$ is defined as:

$$w_{p,q}^{(k)} := \begin{cases} \exp\left(-\frac{(\mathbf{d}_{k,p} - \mathbf{d}_{k,q})^2}{2\sigma_\lambda^2}\right) & \text{if } q \in \mathcal{N}_k \text{ or } p \in \mathcal{N}_k, \\ 0 & \text{otherwise,} \end{cases} \quad (16)$$

where for any $1 \leq p < q \leq N_3 - 1$ and σ_λ is a scaling parameter.

The Laplacian matrix $\mathbf{L}^{(k)} \in \mathbb{R}^{N_3 \times N_3}$ is then computed as $\mathbf{L}^{(k)} := \mathbf{D}^{(k)} - \mathbf{W}_\lambda^{(k)}$. Finally, we extend these local Laplacians to the global spectral graph Laplacian $\mathbf{L}_{\mathcal{G}_\lambda} \in \mathbb{R}^{N \times N}$. Let $l_p \in 1, \dots, K$ denote the segment label of the p -th spatial pixel. The global matrix is constructed as a block diagonal matrix:

$$\mathbf{L}_{\mathcal{G}_\lambda} := \text{diag}(\mathbf{L}^{(l_1)}, \mathbf{L}^{(l_2)}, \dots, \mathbf{L}^{(l_{N_1 N_2})}). \quad (17)$$

B. GASSTV

Incorporating both the spatial graph $\mathcal{G}_{\text{sp}}$ and the spectral graph $\mathcal{G}_\lambda$, our *Graph-Aided Spatio-Spectral Total Variation* (GASSTV) is defined as follows:

$$\begin{aligned} \text{GASSTV}(\mathbf{u}) &:= \|\mathbf{D}_{\text{vh}} \mathbf{D}_\lambda \mathbf{u}\|_1 + \frac{\omega}{2} (\mathbf{D}_\lambda \mathbf{u})^\top \mathbf{L}_{\mathcal{G}_\lambda} \mathbf{D}_\lambda \mathbf{u}, \\ \text{s.t. } &\|\mathbf{W}_{\mathcal{G}_{\text{sp}}} \mathbf{D}_{\mathcal{G}_{\text{sp}}} \mathbf{u}\|_1 \leq \rho_{\text{sp}}, \end{aligned} \quad (18)$$

where $\mathbf{D}_{\text{vh}} := (\mathbf{D}_{\text{v}}^\top \quad \mathbf{D}_{\text{h}}^\top)^\top \in \mathbb{R}^{2N \times N}$ is the spatial difference operator, ω and ρ_{sp} are the parameters. The formulation consists of three key components:

1) Spatio-Spectral Total Variation (SSTV):

The first term in (18) corresponds to the standard SSTV [23], which serves as the baseline for noise suppression. By promoting sparsity on the second-order spatio-spectral differences, SSTV effectively captures the spatio-spectral piecewise smoothness inherent in HS images. However, SSTV uniformly evaluates local adjacent differences and thus struggles to preserve complex spatial structures (e.g., fine edges and textures) and spectral jumps. To address this limitation, we introduce two graph-based terms that explicitly complement SSTV by preserving structural information.

2) Spectral Graph Laplacian Regularizer:

The second term in (18) introduces spectral graph regularization via the graph Laplacian quadratic form based on the spectral graph $\mathbf{L}_{\mathcal{G}_\lambda}$. Recall that the nodes of the

spectral graph represent spectral adjacent differences. By imposing smoothness on these difference values along the graph structure, this term ensures that bands with similar spectral variation patterns maintain consistent variations in the restored image. This mechanism effectively captures both smooth spectral transitions and abrupt spectral jumps. From an algorithmic perspective, the quadratic form provides computational advantages. This term is differentiable with a Lipschitz-continuous gradient, enabling an efficient update via a gradient descent step in the PDS framework (Sec. II-C) without requiring computationally expensive proximal operators.

3) Spatial Graph Total Variation Constraint:

The inequality constraint in (18) preserves complex spatial structures through weighted spatial graph-based total variation. By incorporating spatial graph weights that reflect the underlying spatial structure of the target HS image, this constraint promotes sparsity of spatial differences while faithfully preserving sharp edges and fine textures. By formulating this term as a hard constraint rather than a penalty in the objective function, we enable direct control of the spatial smoothness level. The upper bound ρ_{sp} is adaptively determined based on the observed image intensity and the guide image structure as:

$$\rho_{\text{sp}} := \omega_{\text{sp}} \frac{\|\mathbf{v}\|_1}{N_1 N_2} \|\mathbf{W}_{\text{sp}}' \mathbf{D} \mathbf{v}'\|_1, \quad (19)$$

where $\omega_{\text{sp}} > 0$ is a tuning parameter.

Consequently, by integrating these complementary regularization functions, GASSTV effectively suppresses mixed noise while faithfully preserving complex spatial structures and spectral jumps.

C. Problem Formulation

An observed HS image $\mathbf{v} \in \mathbb{R}^N$ contaminated by mixed noise is modeled by

$$\mathbf{v} = \bar{\mathbf{u}} + \bar{\mathbf{s}} + \bar{\mathbf{t}} + \mathbf{n}, \quad (20)$$

where $\bar{\mathbf{u}}$, $\bar{\mathbf{s}}$, $\bar{\mathbf{t}}$, and $\mathbf{n}$ represent a clean HS image, sparse noise such as outliers, stripe noise and random noise, respectively.

Based on the observation model (20), we formulate HS image denoising problem by GASSTV as a constrained convex optimization problem with the following form:

$$\min_{\mathbf{u}, \mathbf{s}, \mathbf{t}} \text{GASSTV}(\mathbf{u}) \quad \text{s.t.} \quad \begin{cases} \mathbf{s} \in B_{1,\alpha}, \\ \mathbf{t} \in B_{1,\beta}, \\ \mathbf{D}_{\text{v}} \mathbf{t} = \mathbf{0}, \\ \mathbf{u} + \mathbf{s} + \mathbf{t} \in B_{2,\varepsilon}^{\mathbf{v}}, \\ \mathbf{u} \in R_{\underline{\mu}, \bar{\mu}}, \end{cases} \quad (21)$$

where

$$B_{1,\alpha} := \{\mathbf{x} \in \mathbb{R}^N \mid \|\mathbf{x}\|_1 \leq \alpha\}, \quad (22)$$

$$B_{1,\beta} := \{\mathbf{x} \in \mathbb{R}^N \mid \|\mathbf{x}\|_1 \leq \beta\}, \quad (23)$$

$$B_{2,\varepsilon}^{\mathbf{v}} := \{\mathbf{x} \in \mathbb{R}^N \mid \|\mathbf{x} - \mathbf{v}\|_2 \leq \varepsilon\}, \quad (24)$$

$$R_{\underline{\mu}, \bar{\mu}} := \{\mathbf{x} \in \mathbb{R}^N \mid \underline{\mu} \leq x_i \leq \bar{\mu} \ (i = 1, \dots, N)\}. \quad (25)$$

Algorithm 1 P-PDS-based solver for (18)**Require:** $\mathbf{u}^{(0)}, \mathbf{s}^{(0)}, \mathbf{t}^{(0)}, \mathbf{y}_1^{(0)}, \mathbf{y}_2^{(0)}, \mathbf{y}_3^{(0)}, \mathbf{y}_4^{(0)}$ **Ensure:** $\mathbf{u}^{(t)}$

```

1: while A stopping criterion is not satisfied do
2:    $\tilde{\mathbf{y}} \leftarrow \mathbf{D}_\lambda^\top \mathbf{D}_{\text{vh}}^\top \mathbf{y}_1^{(t)} + \mathbf{D}_{\mathcal{G}_{\text{sp}}}^\top \mathbf{W}_{\mathcal{G}_{\text{sp}}}^\top \mathbf{y}_2^{(t)} + \mathbf{y}_4^{(t)}$ 
3:    $\mathbf{u}^{(t+1)} \leftarrow P_{R_{\underline{\mu}, \bar{\mu}}}(\mathbf{u}^{(t)} - \gamma_{\mathbf{u}}(\omega \mathbf{D}_\lambda^\top \mathbf{L}_{\mathcal{G}_\lambda} \mathbf{D}_\lambda \mathbf{u}^{(t)} + \tilde{\mathbf{y}}));$ 
4:    $\mathbf{s}^{(t+1)} \leftarrow P_{B_{1,\alpha}}(\mathbf{s}^{(t)} - \gamma_{\mathbf{s}} \mathbf{y}_4^{(t)});$ 
5:    $\mathbf{t}^{(t+1)} \leftarrow P_{B_{1,\beta}}(\mathbf{t}^{(t)} - \gamma_{\mathbf{t}}(\mathbf{D}_{\mathbf{v}}^\top \mathbf{y}_3^{(t)} + \mathbf{y}_4^{(t)}));$ 
6:    $\mathbf{u}' \leftarrow 2\mathbf{u}^{(t+1)} - \mathbf{u}^{(t)};$ 
7:    $\mathbf{s}' \leftarrow 2\mathbf{s}^{(t+1)} - \mathbf{s}^{(t)};$ 
8:    $\mathbf{t}' \leftarrow 2\mathbf{t}^{(t+1)} - \mathbf{t}^{(t)};$ 
9:    $\mathbf{y}_1' \leftarrow \mathbf{y}_1^{(t)} + \gamma_{\mathbf{y}} \mathbf{D}_{\text{vh}} \mathbf{D}_\lambda \mathbf{u}';$ 
10:   $\mathbf{y}_1^{(t+1)} \leftarrow \mathbf{y}_1' - \gamma_{\mathbf{y}} \text{prox}_{\gamma_{\mathbf{y}} \|\cdot\|_1} \left( \frac{1}{\gamma_{\mathbf{y}}} \mathbf{y}_1' \right);$ 
11:   $\mathbf{y}_2' \leftarrow \mathbf{y}_2^{(t)} + \gamma_{\mathbf{y}} \mathbf{W}_{\mathcal{G}_{\text{sp}}} \mathbf{D}_{\mathcal{G}_{\text{sp}}} \mathbf{u}';$ 
12:   $\mathbf{y}_2^{(t+1)} \leftarrow \mathbf{y}_2' - \gamma_{\mathbf{y}} P_{B_{1,\rho_{\text{sp}}}} \left( \frac{1}{\gamma_{\mathbf{y}}} \mathbf{y}_2' \right);$ 
13:   $\mathbf{y}_3^{(t+1)} \leftarrow \mathbf{y}_3^{(t)} + \gamma_{\mathbf{y}} \mathbf{D}_{\mathbf{v}} \mathbf{t}';$ 
14:   $\mathbf{y}_4' \leftarrow \mathbf{y}_4^{(t)} + \gamma_{\mathbf{y}} (\mathbf{u}' + \mathbf{s}' + \mathbf{t}');$ 
15:   $\mathbf{y}_4^{(t+1)} \leftarrow \mathbf{y}_4' - \gamma_{\mathbf{y}} P_{B_{2,\varepsilon}^{\mathbf{y}}} \left( \frac{1}{\gamma_{\mathbf{y}}} \mathbf{y}_4' \right);$ 
16:   $t \leftarrow t + 1;$ 
17: end while

```

The first constraint characterizes sparse noise $\mathbf{s}$ with the zero-centered ℓ_1 -ball of the radius $\alpha > 0$. The second constraint controls the intensity of stripe noise $\mathbf{t}$ and the third constraint captures the vertical flatness property by imposing zero to the vertical gradient of $\mathbf{t}$. These constraints effectively characterize stripe noise [24]. The fourth constraint serves as data-fidelity with the $\mathbf{v}$ -centered ℓ_2 -ball of the radius $\varepsilon > 0$. The fifth constraint is a box constraint with $\underline{\mu} < \bar{\mu}$ which represents the dynamic range of $\mathbf{u}$. For normalized HS images, we can set $\underline{\mu} = 0$ and $\bar{\mu} = 1$.

Using the first, second, and fourth constraints instead of adding terms to the objective function makes it much easier to adjust the parameters α , β , and ε . This is because by expressing multiple terms as constraints, rather than adding them to the objective function, the hyperparameters associated with each term are converted to be independent of each other, and appropriate parameters can be determined without interdependence. Such advantage has been addressed, e.g., in [25]–[29].

D. Optimization

We develop an efficient solver for Prob. (21) based on P-PDS [16]. Using the indicator functions, we rewrite Prob. (21)

into an equivalent form:

$$\begin{aligned}
 \min_{\mathbf{u}, \mathbf{s}, \mathbf{t}, \mathbf{y}_1, \mathbf{y}_2, \mathbf{y}_3, \mathbf{y}_4} \quad & \|\mathbf{y}_1\|_1 + \frac{\omega}{2} (\mathbf{D}_\lambda \mathbf{u})^\top \mathbf{L}_{\mathcal{G}_\lambda} \mathbf{D}_\lambda \mathbf{u} + \iota_{B_{1,\rho_{\text{sp}}}}(\mathbf{y}_2) \\
 & + \iota_{B_{1,\alpha}}(\mathbf{s}) + \iota_{B_{1,\beta}}(\mathbf{t}) + \iota_{\{0\}}(\mathbf{y}_3) \\
 & + \iota_{B_{2,\varepsilon}^{\mathbf{y}}}(\mathbf{y}_4) + \iota_{R_{\underline{\mu}, \bar{\mu}}}(\mathbf{u}) \\
 \text{s.t.} \quad & \begin{cases} \mathbf{y}_1 = \mathbf{D}_{\text{vh}} \mathbf{D}_\lambda \mathbf{u}, \\ \mathbf{y}_2 = \mathbf{W}_{\mathcal{G}_{\text{sp}}} \mathbf{D}_{\mathcal{G}_{\text{sp}}} \mathbf{u}, \\ \mathbf{y}_3 = \mathbf{D}_{\mathbf{v}} \mathbf{t}, \\ \mathbf{y}_4 = \mathbf{u} + \mathbf{s} + \mathbf{t}. \end{cases}
 \end{aligned} \tag{26}$$

Let $\mathbf{x} := (\mathbf{u}^\top, \mathbf{s}^\top, \mathbf{t}^\top)^\top$ be the primal variable and $\mathbf{y} := (\mathbf{y}_1^\top, \mathbf{y}_2^\top, \mathbf{y}_3^\top, \mathbf{y}_4^\top)^\top$ be the dual variables. Then, by defining,

$$\begin{aligned}
 \varphi(\mathbf{x}) &:= \frac{\omega}{2} (\mathbf{D}_\lambda \mathbf{u})^\top \mathbf{L}_{\mathcal{G}_\lambda} \mathbf{D}_\lambda \mathbf{u}, \\
 f(\mathbf{x}) &:= \iota_{R_{\underline{\mu}, \bar{\mu}}}(\mathbf{u}) + \iota_{B_{1,\alpha}}(\mathbf{s}) + \iota_{B_{1,\beta}}(\mathbf{t}), \\
 g(\mathbf{y}) &:= \|\mathbf{y}_1\|_1 + \iota_{B_{1,\rho_{\text{sp}}}}(\mathbf{y}_2) + \iota_{\{0\}}(\mathbf{y}_3) + \iota_{B_{2,\varepsilon}^{\mathbf{y}}}(\mathbf{y}_4), \\
 \mathbf{A} &:= \begin{pmatrix} \mathbf{D}_{\text{vh}} \mathbf{D}_\lambda & \mathbf{0} & \mathbf{0} \\ \mathbf{W}_{\mathcal{G}_{\text{sp}}} \mathbf{D}_{\mathcal{G}_{\text{sp}}} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{D}_{\mathbf{v}} \\ \mathbf{I} & \mathbf{I} & \mathbf{I} \end{pmatrix},
 \end{aligned} \tag{27}$$

Prob. (26) is reduced to Prob. (6). Therefore, PDS is applicable to Prob. (26). Prob. (26) can be solved by PDS [16] given by Alg. 1. The proximity operator of $\|\cdot\|_1$ is calculated by

$$[\text{prox}_{\gamma \|\cdot\|_1}(\mathbf{x})]_i = \text{sgn}(x_i) \max\{0, |x_i| - \gamma\}, \tag{28}$$

which is equivalent to soft thresholding. The projections onto $B_{2,\varepsilon}^{\mathbf{y}}$ and $R_{\underline{\mu}, \bar{\mu}}$ are calculated by

$$P_{B_{2,\varepsilon}^{\mathbf{y}}}(\mathbf{x}) = \begin{cases} \mathbf{x}, & \text{if } \mathbf{x} \in B_{2,\varepsilon}^{\mathbf{y}}, \\ \mathbf{v} + \frac{\varepsilon(\mathbf{x}-\mathbf{v})}{\|\mathbf{x}-\mathbf{v}\|_2}, & \text{otherwise,} \end{cases} \tag{29}$$

$$[P_{R_{\underline{\mu}, \bar{\mu}}}(\mathbf{x})]_i = \begin{cases} \underline{\mu}, & \text{if } x_i < \underline{\mu}, \\ \bar{\mu}, & \text{if } x_i > \bar{\mu}, \\ x_i, & \text{otherwise.} \end{cases} \tag{30}$$

The projection onto $B_{1,\alpha}$ can be efficiently computed by a fast ℓ_1 -ball projection algorithm [30]. According to [17], we set the stepsize parameters as

$$\begin{aligned}
 \gamma_{\mathbf{u}} &= \frac{1}{49 + 2\omega \max_k \sigma_{\max}(\mathbf{L}^{(k)})}, \\
 \gamma_{\mathbf{s}} &= 1, \quad \gamma_{\mathbf{t}} = \frac{1}{5}, \quad \gamma_{\mathbf{y}} = \frac{1}{3},
 \end{aligned} \tag{31}$$

where $\sigma_{\max}(\mathbf{L}^{(k)})$ is the maximum singular value of the Laplacian matrix of the segment k .

REFERENCES

- [1] S. Matteoli, M. Diani, and J. Theiler, "An overview of background modeling for detection of targets and anomalies in hyperspectral remotely sensed imagery," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 7, no. 6, pp. 2317–2336, 2014.
- [2] H. Su, Z. Wu, H. Zhang, and Q. Du, "Hyperspectral anomaly detection: A survey," *IEEE Geosci. Remote Sens. Mag.*, vol. 10, no. 1, pp. 64–90, 2022.
- [3] P. Ghamisi, J. Plaza, Y. Chen, J. Li, and A. J. Plaza, "Advanced spectral classifiers for hyperspectral images: A review," *IEEE Geosci. Remote Sens. Mag.*, vol. 5, no. 1, pp. 8–32, 2017.

- [4] S. Li, W. Song, L. Fang, Y. Chen, P. Ghamisi, and J. A. Benediktsson, "Deep learning for hyperspectral image classification: An overview," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 9, pp. 6690–6709, 2019.
- [5] N. Audebert, B. L. Saux, and S. Lefevre, "Deep learning for classification of hyperspectral data: A comparative review," *IEEE Geosci. Remote Sens. Mag.*, vol. 7, no. 2, pp. 159–173, 2019.
- [6] J. M. Bioucas-Dias, A. Plaza, N. Dobigeon, M. Parente, Q. Du, P. Gader, and J. Chanussot, "Hyperspectral unmixing overview: Geometrical, statistical, and sparse regression-based approaches," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 5, no. 2, pp. 354–379, 2012.
- [7] W. Ma, J. M. Bioucas-Dias, T. Chan, N. Gillis, P. Gader, A. J. Plaza, A. Ambikapathi, and C. Chi, "A signal processing perspective on hyperspectral unmixing: Insights from remote sensing," *IEEE Signal Process. Mag.*, vol. 31, no. 1, pp. 67–81, 2014.
- [8] M. Borengasser, W. S. Hungate, and R. Watkins, *Hyperspectral remote sensing: principles and applications*. CRC press, 2007.
- [9] H. Grahn and P. Geladi, *Techniques and applications of hyperspectral image analysis*. John Wiley & Sons, 2007.
- [10] P. S. Thenkabail, J. G. Lyon, and A. Huete, *Hyperspectral remote sensing of vegetation*. CRC press, 2016.
- [11] B. Lu, P. D. Dao, J. Liu, Y. He, and J. Shang, "Recent advances of hyperspectral imaging technology and applications in agriculture," *Remote Sens.*, vol. 12, no. 16, p. 2659, 2020.
- [12] H. Shen, X. Li, Q. Cheng, C. Zeng, G. Yang, H. Li, and L. Zhang, "Missing information reconstruction of remote sensing data: A technical review," *IEEE Geosci. Remote Sens. Mag.*, vol. 3, no. 3, pp. 61–85, 2015.
- [13] B. Rasti, P. Scheunders, P. Ghamisi, G. Licciardi, and J. Chanussot, "Noise reduction in hyperspectral imagery: Overview and application," *Remote Sens.*, vol. 10, no. 3, 2018.
- [14] H. Shen, M. Jiang, J. Li, C. Zhou, Q. Yuan, and L. Zhang, "Coupling model- and data-driven methods for remote sensing image restoration and fusion: Improving physical interpretability," *IEEE Geosci. Remote Sens. Mag.*, vol. 10, no. 2, pp. 231–249, 2022.
- [15] Q. Yuan, L. Zhang, and H. Shen, "Hyperspectral image denoising employing a spectral-spatial adaptive total variation model," *IEEE Trans. Geosci. Remote Sens.*, vol. 50, no. 10, pp. 3660–3677, 2012.
- [16] T. Pock and A. Chambolle, "Diagonal preconditioning for first order primal-dual algorithms in convex optimization," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, 2011, pp. 1762–1769.
- [17] K. Naganuma and S. Ono, "Variable-wise diagonal preconditioning for primal-dual splitting: Design and applications," *IEEE Trans. Signal Process.*, vol. 71, pp. 3281–3295, 2023.
- [18] A. Chambolle and T. Pock, "A first-order primal-dual algorithm for convex problems with applications to imaging," *J. Math. Imag. Vis.*, vol. 40, no. 1, pp. 120–145, 2011.
- [19] L. Condat, "A primal-dual splitting method for convex optimization involving lipschitzian, proximable and linear composite terms," *J. Optim. Theory Appl.*, vol. 158, no. 2, pp. 460–479, 2013.
- [20] P. L. Combettes and N. N. Reyes, "Moreau's decomposition in banach spaces," *Math. Program.*, vol. 139, no. 1, pp. 103–114, 2013.
- [21] S. Takemoto, K. Naganuma, and S. Ono, "Graph spatio-spectral total variation model for hyperspectral image denoising," *IEEE Geosci. Remote Sens. Lett.*, vol. 19, pp. 1–5, 2022.
- [22] D. Arthur and S. Vassilvitskii, "k-means++: The advantages of careful seeding," Stanford InfoLab, Technical Report 2006-13, June 2006.
- [23] H. K. Aggarwal and A. Majumdar, "Hyperspectral image denoising using spatio-spectral total variation," *IEEE Geosci. Remote Sens. Lett.*, vol. 13, no. 3, pp. 442–446, 2016.
- [24] K. Naganuma and S. Ono, "A general destriping framework for remote sensing images using flatness constraint," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, pp. 1–16, 2022.
- [25] M. V. Afonso, J. M. Bioucas-Dias, and M. Figueiredo, "An augmented lagrangian approach to the constrained optimization formulation of imaging inverse problems," *IEEE Trans. Image Process.*, vol. 20, no. 3, pp. 681–695, 2011.
- [26] G. Chierchia, N. Pustelnik, J.-C. Pesquet, and B. Pesquet-Popescu, "Epigraphical projection and proximal tools for solving constrained convex optimization problems," *Signal Image Video Process.*, vol. 9, no. 8, pp. 1737–1749, 2015.
- [27] S. Ono and I. Yamada, "Signal recovery with certain involved convex data-fidelity constraints," *IEEE Trans. Signal Process.*, vol. 63, no. 22, pp. 6149–6163, 2015.
- [28] S. Ono, "Primal-dual plug-and-play image restoration," *IEEE Signal Process. Lett.*, vol. 24, no. 8, pp. 1108–1112, 2017.
- [29] S. Ono, "Efficient constrained signal reconstruction by randomized epigraphical projection," in *Proc. IEEE Int. Conf. Acoust., Speech, Signal Process., (ICASSP)*, 2019, pp. 4993–4997.
- [30] L. Condat, "Fast projection onto the simplex and the ℓ_1 ball," *Math. Program.*, vol. 158, no. 1, pp. 575–585, 2016.



received the Student Award from IEEE SPS Tokyo Joint Chapter in 2022.



Science and Technology (PRESTO), Japan Science and Technology Agency (JST), Tokyo, Japan. Currently, he is an Associate Professor with Institute of Science Tokyo (Science Tokyo), Tokyo, Japan. His research interests include signal processing, image analysis, optimization, remote sensing, and measurement informatics. He has served as an Associate Editor for IEEE TRANSACTIONS ON SIGNAL AND INFORMATION PROCESSING OVER NETWORKS (2019–2024). Dr. Ono was a recipient of the Young Researchers' Award and the Excellent Paper Award from the IEICE in 2013 and 2014, respectively, the Outstanding Student Journal Paper Award and the Young Author Best Paper Award from the IEEE SPS Japan Chapter in 2014 and 2020, respectively, and the Best Paper Award in APSIPA ASC 2024. He also received the Funai Research Award in 2017, the Ando Incentive Prize in 2021, the MEXT Young Scientists' Award in 2022, and the IEEE SPS Outstanding Editorial Board Member Award in 2023.

Shingo Takemoto (S'22) received a B.E. degree and M.E. degree in Information and Computer Sciences in 2021 from Sophia University and in 2023 from Institute of Science Tokyo (formerly Tokyo Institute of Technology), respectively. He is currently pursuing a Ph.D. degree at the Department of Computer Science in the Institute of Science Tokyo. Since April 2024, he has been a Research Fellow (DC2) of Japan Society for the Promotion of Science (JSPS). His current research interests are in signal and image processing and optimization theory. Mr. Takemoto

Shunsuke Ono (S'11–M'15–SM'23) received a B.E. degree in Computer Science in 2010 and M.E. and Ph.D. degrees in Communications and Computer Engineering in 2012 and 2014 from the Tokyo Institute of Technology, respectively. From 2012 to 2014, he was a Research Fellow (DC1) of the Japan Society for the Promotion of Science (JSPS). He was an Assistant, then an Associate Professor with Tokyo Institute of Technology (TokyoTech), Tokyo, Japan, from 2014 to 2024. From 2016 to 2020, he was a Researcher of Precursory Research for Embryonic