

## COMMONWEALTH OF AUSTRALIA

### *Copyright Regulations 1969*

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act. Do not remove this notice

Prepared by: [Arun Konagurthu]

# FIT3155: Advanced Algorithms and Data Structures

## Weeks 5,6: **Binomial and Fibonacci heaps**

Faculty of Information Technology, Monash University

What is covered in these?

Binomial heap and Fibonacci heap

# Source material and recommended reading

- Weiss, Data Structures and Algorithm Analysis (Chapters 6.8, 11.1, 11.2)
- Cormen et al., Introduction to Algorithms (Chapter 19):  
Binomial heaps [\[online link\]](#)  
Fibonacci heaps [\[online link\]](#)

# Priority queues (implemented using heaps)

Recall from FIT2004 that the heap data structure was used in several applications:

- Heap sort
- Dijkstra's shortest path algorithm
- Prim's algorithm

Recall also that this data structure supports the following operations\*:

- **insert** a new element (key/priority+payload) into a heap
- identify the **min** element in an existing heap
- **extract-min** (identify and delete min) element in an existing heap
- **decrease-priority** of an element in an existing heap

---

\*As with these slides, default heap operations are defined over a **min**-heap. One could alternatively define **max**, **extract-max**, **increase-priority** operations on a **max**-heap.

# Mergeable heaps

Today (binomial heap) and next start of next lecture (Fibonacci heap), we will learn about mergeable heaps that support (at least) the following operations:

**insert:** inserts a new element into the existing heap

**min:** finds the min element in the heap

**extract-min:** finds and deletes the min element in the heap


**merge/union:** combines two heaps into one

**decrease-priority:** decreases the elements key/priority

**delete:** removes an element from the heap

## Part-1: Binomial heaps

# Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:

- The binomial tree of order **0** (or  $B_0$  in short) is a single node tree
- The binomial tree of order **1** ( $B_1$ ) is created from two  $B_0$  trees, by making one  $B_0$  tree the child of the other.
- The binomial tree of order **2** ( $B_2$ ) is created from two  $B_1$  trees, by making one  $B_1$  tree the child of the other.
- and so on...




# Properties of a Binomial tree

Any binomial tree of order  $k$  has the following properties:


- The number of nodes in any  $B_k$  is  $2^k$ .
- The height of any  $B_k$  is  $k$ .
- The root node of any  $B_k$  tree has  $k$  subtrees as children.
- Deleting the root node of  $B_k$  (with its edges/links) yields  $k$  independent lower order binomial trees  $B_{k-1}, B_{k-2}, \dots, B_0$ .

## Example



# Why are these trees called **binomial**?

## Example: $B_5$



## Main property

A main property of any  $B_k$  tree is that the **number of nodes** at any given depth  $d$  is given by the **binomial coefficient**  $\binom{k}{d}$ , that is “ $k$ -choose- $d$ ”

# What is a binomial heap?


A binomial **heap** is a collection/set of binomial **trees** such that:

- **each** binomial tree in the set satisfies the heap property – i.e., **each** tree-node's key/priority is  $\leq$  its children's keys/priorities.
- There is **at most** one (i.e. either 0 or 1) binomial tree of any given order in that set.

## Example

On the right is a binomial **heap** that contains a collection/set of binomial **trees**:

- one  $B_4$  tree
- zero  $B_3$  tree
- zero  $B_2$  tree
- one  $B_1$  tree
- one  $B_0$  tree




# Binomial heap properties

## Properties

For any binomial **heap** containing  $N$  elements, the following properties hold:

- There are at most  $\lfloor \log_2 N \rfloor + 1$  binomial **trees**
- The height of each binomial **tree** is  $\leq \lfloor \log_2 N \rfloor$
- The '1's in the **binary representation** of  $N$  tell us which order binomial **trees** are present in the collection forming this binomial **heap** of  $N$  elements.
- the element with **minimum** key is one of the root nodes of the **trees** in the collection.

# Binomial heap properties – Example



## Example

For the above binomial **heap**:

- $N = 19$ .
- Number of trees is 3
- binary representation of 19 is:  $\overset{4}{1} \overset{3}{0} \overset{2}{0} \overset{1}{1} \overset{0}{1}$  (therefore contains  $B_4, B_1, B_0$ )


# Representing a binomial heap

- Unlike **binary** heaps, **binomial** heaps are stored explicitly using a **tree** data structure.
- Each node  $x$ :
  - ▶ is denoted by a **key**,
  - ▶ has associated **payload** information
  - ▶ has a pointer **parent** $[x]$  to its parent node
  - ▶ has a pointer **child** $[x]$  to its **leftmost** child node
    - ★ If node  $x$  has zero children, then **child** $[x] = nil$
  - ▶ has a pointer **sibling** $[x]$  to the immediate **sibling** of  $x$  to its right.
    - ★ If node  $x$  is the rightmost child of its parent, then **sibling** $[x] = nil$
  - ▶ stores **degree** $[x]$  which is the number of children of  $x$  (i.e., same as the **order** of the binomial tree rooted at  $x$ )
- Finally, the roots of the binomial trees within a binomial heap are organized in a linked list, referred to as the **root list**.

operations on a binomial heap

# Merging two binomial **trees** into one

- First, merging two binomial **trees**, each of the **same** order (say)  $k$  results in an order  $k + 1$  binomial tree, where:
  - the two roots are linked, such that...
  - ...the root containing the **larger** key becomes the **child** of the smaller root.






## Binomial **heap** operation – **merge/consolidate** two binomial **heaps** into one

- With merging of two binomial **trees** established (see previous slide), we can now define **merge/consolidate** operation on two binomial **heaps**.
- Heaps are merged in a way that is reminiscent of how we add two numbers in binary:

Example: addition of  $19 + 7 = 26$  in binary

|         |   |   |   |   |   |
|---------|---|---|---|---|---|
| Order:  | 4 | 3 | 2 | 1 | 0 |
| carry:  |   | 1 | 1 | 1 |   |
|         | 1 | 0 | 0 | 1 | 1 |
| +       | 0 | 0 | 1 | 1 | 1 |
| Result: | 1 | 1 | 0 | 1 | 0 |

# Example of merging 2 binomial heaps containing 19 and 7 elements each



(To be discussed during the lecture)

# Running time of **merge** operation between 2 binomial heaps

- Running time is  $O(\log N)$  worst-case – **why?**
  - ▶ time is bounded by maximum number of possible merges between trees of the same order within the heaps.
  - ▶ the number of trees in each heap containing  $N$  elements is bounded by  $\lfloor \log N \rfloor + 1$
  - ▶ merging two heaps in worst case requires  $2 \times (\lfloor \log N \rfloor + 1)$  tree merges

## Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** root node among the trees in the heap.
- From slide #9, we know that deleting the root node of any  $B_k$  tree yields:  $B_{k-1}, B_{k-2}, \dots, B_0$ .
- If we promote these subtrees to the root level of the existing binomial heap...
- ...this might create multiple trees of the same order (violating the definition of a binomial heap – see slide #11).
- So, progressively **merge** the binomial trees of the same order (starting from 0) until the binomial heap definition is satisfied.

(Example will be handled during the lecture)

## Running time of **extract-min** operation

- Running time is  $O(\log N)$  worst-case – **why?**
- Effort required to find the **min** is  $O(\log N)$ . (see slide #12)
- Effort required to promote subtrees formed upon deletion to root level is  $O(\log N)$  – the number of these subtrees is bounded by  $\lfloor \log N \rfloor$ .
- Effort required to merge multiple trees into a binomial heap is also  $O(\log N)$ . (see slide #19)
- Total effort:  $O(\log N)$

## Binomial **heap** operation – **decrease-priority**

We want to decrease priority of any node  $x$  in a binomial heap containing  $N$  elements. <sup>†</sup>

- decrease priority of node  $x$ .
- if min-heap property is violated (i.e.  $x < \text{parent}[x]$ ), bubble up node  $x$ .
- Running time (worst-case):  $O(\log N)$ . Note: the depth of the binomial tree in which  $x$  resides is bounded above by  $\lfloor \log N \rfloor$

(Example will be handled during the lecture)

---

<sup>†</sup>Note: as with binary heaps, binomial heaps are inefficient to **search** for any node  $x$  (except the root); For this reason, **decrease-priority** on  $x$  assumes a pointer to  $x$  as part of its input.

## Binomial **heap** operation – **delete**

We want to delete any node  $x$  in a binomial heap containing  $N$  elements.

‡

- run **decrease-priority** by setting  $x$  to  $-\infty$ .
- run **extract-min**.
- Running time (worst-case):  $O(\log n)$ .

---

‡Note: as with binary heaps, binomial heaps are inefficient to **search** for any node  $x$  (except the root); For this reason, **delete**( $x$ ) assumes a pointer to  $x$  as part of its input.

## Binomial **heap** operation – **insert**

We want to insert a new element  $x$  into an existing binomial heap  $H_1$

- Make a new binomial heap  $H_2$  with  $x$  as its **only** element.
- run **merge**( $H_1, H_2$ ).
- At face value, the runtime per single **insert** takes  $O(\log N)$  effort.



# Amortized analysis of **insert** operation

Consider the problem of building a **binomial** heap of  $N$  elements:

- From FIT2004, we know that at least a **binary** heap of  $N$  elements can be built in  $O(N)$  time.
- What about a **binomial** heap then?

claim

A **binomial** heap of  $N$  elements can be built by  $N$  successive inserts in  $O(N)$ -time.

## Amortized analysis of **insert** operation ...continued(2)

- Time required for inserting **each** element  $x$  into a heap  $H_1$  (starting from an empty heap) involves:
  - ▶ time to create a new binomial heap  $H_2$  containing only 1 element  $x$  – which requires constant effort, **plus**
  - ▶ time to merge  $H_2$  into  $H_1$ . It isn't fully clear yet how many merges (between same-order binomial trees) will be required in each insert operation.
- Total over  $N$  insertions requires:
  - ▶  $O(N)$  **plus**
  - ▶ total merging time.

## Amortized analysis of **insert** operation ...continued(3)

It is easy to see (by beholding how the numbers starting from 0 change when 1 is added each time):

- the **first insertion** into an empty  $H_1$  heap requires **zero** merges. **Why?**
- the second insertion involves exactly **one** merge between two  $B_0$  binomial trees, yielding a heap containing one  $B_1$  tree.
- the **third insertion** involves **zero** merges
  - ▶  $H_1$  before insertion contains 2 elements (contained in 1  $B_1$  tree).
  - ▶ merging the new inserted element into  $H_1$  adds only a new  $B_0$  tree to the existing  $B_1$  tree. Therefore no merges.
- the fourth insertion involves exactly **two** merges – **why?**
- the **fifth insertion** involves **zero** merges – **why?**
- the sixth insertion involves **one** merge – **why?**
- $\vdots$

## Amortized analysis of **insert** operation ...continued(3)

When inserting  $N$  elements, if the binary representation of number elements in  $H_1$  before each insertion ends in

- .....**0**, the effort takes only 1 unit of time.
- .....**01**, the effort takes only 2 units of time.
- .....**011**, the effort takes only 3 units of time.
- ....**0111**, the effort takes only 4 units of time.
- ...**01111**, the effort takes only 5 units of time.
- $\vdots$

### Total time over $N$ insertions

- $T = \frac{N}{2} \times 1 + \frac{N}{4} \times 2 + \frac{N}{8} \times 3 \dots \leq 2N$
- Such series is called an **Arithmetico-Geometric series**.

Thus total time is bounded by  $O(N)$ , implying that each **insert** into a binomial heap is  $O(1)$  amortized!

# Summary of Binomial heaps

| Operation                | Binary heap                                | Binomial heap                              |
|--------------------------|--|--|
| <b>make-new-heap</b>     | $O(1)$                                     | $O(1)$                                     |
| <b>min</b>               | $O(1)$                                     | $O(\log N)$                                |
| <b>extract-min</b>       | $O(\log N)$                                | $O(\log N)$                                |
| <b>merge</b>             | $O(N)$                                     | $O(\log N)$                                |
| <b>decrease-priority</b> | $O(\log N)$                                | $O(\log N)$                                |
| <b>delete</b>            | $O(\log N)$                                | $O(\log N)$                                |
| <b>insert</b>            | $O(\log N)$ worst-case<br>$O(1)$ amortized | $O(\log N)$ worst-case<br>$O(1)$ amortized |


## Part-2: Fibonacci heaps

# Motivation for Fibonacci heaps

- Improve complexity of **Dijkstra's** shortest path algorithm – Recall this from FIT2004?
- Maintains a collection of trees (much like Binomial heaps), however:
  - ▶ ...trees in the collection are **less stringent** in their definitions.
    - ★ While a **binomial heap** performs **eager** merging/consolidation of trees after each and every **extract-min** or **insert** operations...
    - ★ ...**Fibonacci heap**, on the other hand, does a **lazy** consolidation/merging, by deferring any merging/consolidation until next **extract-min** operation.

# Example of a Fibonacci heap

- A Fibonacci heap  $H$  containing 5 trees, with total 14 elements.




- $H.min$  is a pointer to root node (of a tree in the collection) with the minimum element.
- In a Fibonacci heap, each node/element is:
  - ▶ either **marked** (shown as **black coloured nodes above**)...
  - ▶ ...or **unmarked**/regular (shown as the grey coloured nodes above)
  - ▶ We will examine in later slides what this means.




# Fibonacci heaps are best represented using circular doubly linked lists

- Circular doubly linked list representation of the example in the previous slide.



- This has several advantages:
  - ▶ This allows **insert** operations into any location in  $O(1)$  time.
  - ▶ This allows **delete** operations from any location in  $O(1)$  time.
  - ▶ This allows joining elements in one list to another in  $O(1)$  time.


# Fibonacci heaps – Attributes



Associated with each node/element  $x$  in a Fibonacci heap  $H$ , is:

- the **number of children** in the child list:
  - we will call the *degree* of a node ( $x.degree$ ).
  - Eg: (24) has *degree*=2. (7) has *degree*=0.
- whether a node is marked or not –  $x.mark$ 
  - It will become clear in **decrease-priority** operation what this means.
  - Quickly, '**marked**' implies the node has lost a child; '**unmarked**' implies it hasn't lost a child. Details when slides #51-54 are covered.
  - Eg: (18) is '**marked**'. (30) is '**unmarked**'.


## Fibonacci heaps – Attributes (continued)




- Access to the Fibonacci heap  $H$  is via the pointer to the **minimum** (priority) node in the entire heap, denoted by  $H.min$ .
- Roots of all trees in the Fibonacci heap are connected by a **root\_list**,
- ...where each tree's root can be accessed via *left* and *right* pointers, starting from  $H.min$ .

# Fibonacci heaps – **insert** operation

**insert**( $x$ ) into a Fibonacci heap  $H$ . (Here  $x = 21$ .)




↓ **insert** 21




- Access  $H$  via the pointer  $H.min$ .
- **insert** ( $x$ ) into the **root\_list**, making it the **left** sibling of  $H.min$  element/root.
- if  $x < H.min$  (comparing the respective priorities/keys), update  $H.min$  to point to the new  $x$  root element.
- This is  $O(1)$ -time operation.

# Fibonacci heaps – **extract-min** operation

Identify and delete the minimum (priority) node in the heap





↓ **extract-min**



- Identify minimum element via the pointer *H.min*.
- Extract minimum element (= 3 in this running example),...
- ...promote/add all children (subtrees) to the root list, and
- ...set the **current** pointer to the *right* sibling of *H.min*.
- **IMPORTANT:** Now run **consolidate** (or merge) operation.
  - ▶ **consolidate** operation ensures that no two roots have the same degree.



# Fibonacci heaps – consolidate operation

Fibonacci heaps run a **consolidate** operation after a call to **extract-min**.





- Starting from **current** which is pointing to 17...
- Maintain an auxiliary array  $A$  to keep track of the root nodes indexed by their *degrees* (i.e., number of children). Initially,  $A$  is empty.
- Since the root node at **current** = 17 has *degree* = 1...
- ...and  $A[1]$  slot is empty, so...
- ...get  $A[1]$  to point to the root node at **current** = 17.
- Next, move **current** to the right sibling, i.e. **current** = 24

# Fibonacci heaps – **consolidate** operation ...continued



- Now, **current** = 24 has *degree* = 2.
- Again,  $A[2]$  is empty, so...
- ...get  $A[2]$  to point to the root node at **current** = 24.
- Next, move **current** to the right sibling, i.e. move **current** from 24 to 23.  
**Why?**
  - ▶ **root\_list** is a circular doubly linked list...
  - ▶ ...so the right sibling of 24 is (circularly) 23.
  - ▶ therefore, **current** = 23.



# Fibonacci heaps – **consolidate** operation ...continued



- Now, **current** = (23) has *degree* = 0.
- $A[0]$  is empty, so...
- ...get  $A[0]$  to point to the root node at **current** = (23).
- Next, move **current** to the right sibling, i.e. **current** = (7).




# Fibonacci heaps – **consolidate** operation ...continued





- Now, **current** = (7) has *degree* = 0.
- But  $A[0]$  is already **occupied** with a pointer to (23).
- Therefore, resolve this clash by **merging** (consolidating) trees with roots (7) and (23), and set  $A[0]$  to empty.
- To maintain the (min-)heap property, root node (23) becomes the **child** of root node (7).
- **current** now points to the root of this merged tree, (7).
- Note: (7).*degree* goes up from 0 to 1.

# Fibonacci heaps – **consolidate** operation ...continued





- Repeat: **current**=**7** has **degree**=1.
- But **A[1]** is already **occupied** with a pointer to **17**.
- Therefore, resolve this clash by **merging** (consolidating) trees with roots **7** and **17**, and set **A[1]** to empty.
- To maintain the (min-)heap property, root node **17** becomes the **child** of root node **7**.
- current** now points to the root of this merged tree, **7**.
- Note: **7**.**degree** goes up from 1 to 2.

# Fibonacci heaps – **consolidate** operation ...continued





- Repeat: **current** = 7 has *degree* = 2.
- But  $A[2]$  is already **occupied** with a pointer to 24.
- Therefore, resolve this clash by **merging** (consolidating) trees with roots 7 and 24, and set  $A[2]$  to empty.
- To maintain the (min-)heap property, root node 24 becomes the **child** of root node 7.
- current** now points to the root of this merged tree, 7.
- Note: 7.*degree* goes up from 2 to 3.
- Since,  $A[3]$  is empty, get  $A[3]$  to point to the root node at **current** = 7.
- Next, move **current** to the right sibling, i.e. **current** = 21

# Fibonacci heaps – **consolidate** operation ...continued





- Now, **current**=21 has *degree*=0.
- $A[0]$  is empty, so...
- ...get  $A[0]$  to point to the root node at **current**=21.
- Next, move **current** to the right sibling, i.e **current**=18.

# Fibonacci heaps – **consolidate** operation ...continued





- Now, **current**=18 has *degree*=1.
- $A[1]$  is empty, so...
- ...get  $A[1]$  to point to the root node at **current**=18.
- Next, move **current** to the right sibling, i.e **current**=52.

# Fibonacci heaps – **consolidate** operation ...continued




- Now, **current** = 52 has *degree* = 0, but  $A[0]$  is occupied.
- So, in operations similar to those on slides #41-43...
- ...we get to the state shown in the figure on the left (below).
- current** now points to root 38.

# Fibonacci heaps – **consolidate** operation ...continued



- Now, **current** = (38) has *degree* = 1.
- $A[1]$  is empty, so...
- ...get  $A[1]$  to point to the root node at **current** = (38).
- This has now completed one full cycle on the doubly linked list. STOP!

## Fibonacci heaps – **consolidate** operation ...continued



- **extract-min** operation (and consolidation) is now complete.
- Note: during the process of cycling through the **root-list** (during consolidation), we can keep track of the minimum root encountered, and update *H.min*.

Run-time complexity is  $O(\log(N))$  amortized. We will intuit why this is so, at the end.



# Fibonacci heaps – **decrease-priority** operation

We want to decrease priority of any node  $x$  in a Fibonacci heap.<sup>§</sup>

- This can be handled in two cases:

case 1: When this operation does not violate the heap property  
(slide #50)

case 2: When it does!

- ▶ We will handle this over subcases, Case 2a (slide #51)  
and Case 2b (slide #52-54).

---

<sup>§</sup>Note: as with binary heaps, Fibonacci heaps are inefficient to **search** for any node  $x$ ; For this reason, **decrease-priority** on  $x$  assumes a pointer to  $x$  as part of its input.

## Fibonacci heaps – **decrease-priority**: Case 1



When **decrease-priority** does not violate the heap property. Simply decrease the priority on the node, and we are done!

---

<sup>§</sup>Note: as with binary heaps, Fibonacci heaps are inefficient to **search** for any node *x*; For this reason, **decrease-priority** on *x* assumes a pointer to *x* as part of its input.

## Fibonacci heaps – decrease-priority: Case 2a

Consider an example where we want to **decrease-priority** of node (with priority=)  $\textcircled{46}$  to  $\textcircled{15}$ .




- Decreasing  $\textcircled{46}$  to  $\textcircled{15}$  **violates** the heap property...
- ...because its parent  $\textcircled{24} > \textcircled{15}$  (previously  $\textcircled{46}$ ).
- To address this violation:
  - ▶ Cut the subtree rooted at  $\textcircled{15}$  (prev.  $\textcircled{46}$ )...
  - ▶ ...and promote it into the root list. (Update *H.min*, if necessary.)
  - ▶ If necessary, update the mark of  $\textcircled{15}$  to 'unmarked' after promoting to the root level.
  - ▶ Since parent  $\textcircled{24}$  was originally **unmarked** (i.e., hasn't yet lost a child), **mark it** (i.e., has lost a child);

§ Note: as with binary heaps, Fibonacci heaps are inefficient to **search** for any node  $x$ ; For this reason, **decrease-priority** on  $x$  assumes a pointer to  $x$  as part of its input.

## Fibonacci heaps – decrease-priority: Case 2b


Another case arises, when the original parent of the subtree, promoted to the root level, is already '**marked**' – consider the example where we want to **decrease-priority** of node (with priority=)  $\textcircled{35}$  to  $\textcircled{5}$ .



- Decreasing  $\textcircled{35}$  to  $\textcircled{5}$  **violates** the heap property...
- ...because its parent  $\textcircled{26} > \textcircled{5}$  (previously  $\textcircled{35}$ ).
- To address this violation:
  - ▶ Cut the subtree rooted at  $\textcircled{5}$  (prev.  $\textcircled{35}$ )...
  - ▶ ...and promote it into the root list. (Update *H.min*, if necessary.)
  - ▶ If necessary, update the mark of  $\textcircled{5}$  to '**unmarked**' after promoting to the root level.
  - ▶ **But** parent  $\textcircled{26}$  is already '**marked**' (i.e., has lost one child previously);
  - ▶ so, repeat this cut-and-promote-to-root process for  $\textcircled{26}$ ...


§Note: as with binary heaps, Fibonacci heaps are inefficient to **search** for any node *x*; For this reason, **decrease-priority** on *x* assumes a pointer to *x* as part of its input.

## Fibonacci heaps – **decrease-priority**: Case 2b (continued)



- ... so, cut the subtree rooted at (26).
- ...and promote it into the root list.
- If necessary, update the mark of (26) to 'unmarked' after promoting to the root level.
- **But** its parent (24) is again already 'marked' (i.e., has lost one child previously);
- so, repeat this cut-and-promote-to-root process for (24)...

## Fibonacci heaps – **decrease-priority**: Case 2b (continued)



- ...now, cut the subtree rooted at (24).
- ...and promote it into the root list.
- If necessary, update the mark of (24) to 'unmarked' after promoting to the root level.
- Finally, since its original parent (7) is 'unmarked', **STOP!**
  - ▶ Btw, we do **not** have to 'mark' a previously unmarked root (when it is a parent of a child that is cut and promoted) of a child that is cut and promoted.

Run-time complexity of **decrease-priority** is  $O(1)$  amortized. Unfortunately, we are short of time to prove this. We will omit it for now.

## Fibonacci heaps – **Union** operation:

**Union** operation involves combining two Fibonacci heaps,  $H_1$  and  $H_2$  into one (used during **consolidation**):

- Takes  $O(1)$  time. **Why?**
  - ▶ This involves combining two root lists...
  - ▶ ...each represented by a circular doubly-linked lists,
  - ▶ ... and accessible via their respective minimum (root) elements,  $H_1.min$  and  $H_2.min$ ...
  - ▶ ...before linking them into a single heap.
  - ▶ (reason this fully during self-study)

## Fibonacci heaps – **delete** operations:

**delete** operation deletes some specified node  $x$ . This can be composed using the following two operations, which we already discussed:

- **decrease-priority** of  $x$  to  $-\infty$ .
- **extract-min**.

---

<sup>§</sup>Note: as with binary heaps, Fibonacci heaps are inefficient to **search** for any node  $x$ ; For this reason, **delete**( $x$ ) assumes a pointer to  $x$  as part of its input.



## Summary of Fibonacci heaps

| Operation                | Fibonacci heap          | Binomial heap                              |
|--------------------------|-------------------------|--|
| <b>make-new-heap</b>     | $O(1)$                  | $O(1)$                                     |
| <b>min</b>               | $O(1)$                  | $O(\log N)$                                |
| <b>extract-min</b>       | $O(\log N)$ (amortized) | $O(\log N)$                                |
| <b>merge</b>             | $O(1)$                  | $O(\log N)$                                |
| <b>decrease-priority</b> | $O(1)$ (amortized)      | $O(\log N)$                                |
| <b>delete</b>            | $O(\log N)$ (amortized) | $O(\log N)$                                |
| <b>insert</b>            | $O(1)$                  | $O(\log N)$ worst-case<br>$O(1)$ amortized |

In the next lecture...

B-Trees

--o0o--

END

--o0o--