

Sheet: power

File: power.sch

Sheet: coreboard

File: coreboard.sch

Sheet: mechanics

File: mechanics.sch

Sheet: audio-codec

File: audio-codec.sch

Sheet: audio-inputs

File: audio-inputs.sch

Sheet: audio-outputs

File: audio-outputs.sch

Sheet: audio-headphones

File: audio-headphones.sch

Sheet: control-voltage

File: control-voltage.sch

Sheet: spdif

File: spdif.sch

Sheet: usb

File: usb.sch

Sheet: midi

File: midi.sch

Sheet: control-chain

File: control-chain.sch

## Notes

- All resistors named as RA\* must have at least 1% tolerance
- All non-polarized capacitors named as CA\* must use NPO Temp. Coef.
- All other non-polarized capacitors should use X7R Temp. Coef.
- Decoupling caps must be placed as close as possible of the IC power pins






USB outp Power: 1.5A  
Inp Power: 12V 700mA  
<https://github.com/moddevices/mod-hw-duoX>  
DuoX Audio processing board  
**MOD Devices GmbH**

Sheet: /  
File: bottom-board.sch

**Title: MOD DuoX – Bottom Board**

Size: A4 Date: 2019-12-19  
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

**Rev: Rev 1.1**  
Id: 1/13




# MOD

Sheet: /power/  
File: power.sch

**Title: MOD Duo – Bottom Board**

Size: A4 Date:  
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:  
Id: 2/13



# MOD

Sheet: /audio-codec/

File: audio-codec.sch

## Title: MOD Duo – Bottom Board







Size: A4

Date:



KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:





Id: 3/13



Used for I/O reference and to power the AT24 memory




**Rev: 2.1**  
Id: 4/13



GC2, GC1: GAIN (dB)		The gain calculation includes the RDSon value J110: RDSon = 18R
1, 1	0.0	
1, 0	6.0	
0, 1	15.0	
0, 0	20.4	

The CODEC only presents optimal dynamic range and THD+N for PGA setting: -12dB to +6dB.


<b>MOD</b>	
Sheet: /audio-inputs/	
File: audio-inputs.sch	
<b>Title: MOD Duo – Bottom Board</b>	
Size: A4	Date:
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1	
<b>Rev:</b>	
Id: 5/13	



• • • • •

UNIT  
.....

**Rev:**  
Id: 6/13



HP circuit values designed for Dual 70mW @  $R_L=32\Omega$

# MOD


Sheet: /audio-headphones/  
File: audio-headphones.sch

## Title: MOD Duo – Bottom Board


Size: A4 Date:  
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:  
Id: 7/13

## USB DEVICE



## USB HOST



### MOD

Sheet: /usb/

File: usb.sch

**Title: MOD Duo – Bottom Board**

Size: A4

Date:


KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:

Id: 8/13




## MIDI IN



MIDI In connector can be used to trigger a special boot mode by connecting pin 3 to GND.

## MIDI OUT



MIDI Out connector exposes the debug serial.



### MOD

Sheet: /midi/  
File: midi.sch

### Title: MOD Duo – Bottom Board

Size: A4 Date:  
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:  
Id: 9/13



# MOD

Sheet: /control-chain/

File: control-chain.sch

**Title: MOD Duo – Bottom Board**


Size: A4

Date:


KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Rev:

Id: 10/13







# **MOD**

Sheet: /spdif/  
File: spdif.sch

## **Title: MOD Duo – Bottom Board**

Size: A4  
KiCad E.D.A. kicad 5.1.5-52549c584ubuntu18.04.1

Date:  
Rev:  
Id: 13/13