26 February 2025 19:39

Graph Data Structure is a collection of nodes. Nodes are connected by edges. Edges represent connection

Directed graph:

You can go from node A to B, but not B to A. Arrow will be present.

Undirected graph:

You can go from B to A and also from B to A. Arrow is absent.


BFS is a graph traversal algorithm that explores all the neighbours of a node before moving on to their neighbours.

DFS is a graph traversal algorithm that explores as far as possible along each branch before backtracking.

Graphs Traversal

To traverse a Graph means to start in one vertex, and go along the edges to visit other vertices until all vertices, or as many as possible, have been visited.

2 techniques: BFS (Breadth first search), DFS (depth first search)





BFS Algorithm

- 1. Push the starting node into the queue and mark it as visited.
- 2. While the queue is not empty, repeat:
 - Remove an element (node) from the front of the queue.
 - Process the node (if required). Print it
 - Push all its unvisited neighboring nodes into the queue and mark them as visited.

Iterative DFS Algorithm (Using a Stack)

- 1. Push start element in stack and print it.
- 2. Repeat till stack is not empty:
 - a. See the top element in stack.
 - b. If all its neighbours have been visited, remove the top item from stack.
 - c. Else push one of its unvisited neighbours and continue the process.





finite number of vertices (nodes).

a Visit every node.

Graph Transat 2 techniques

Graph Transat 2 techniques

OFFS (Breadth First Search)

DFS (Depth First Search)
BFS - Level Order Traversal.

