



with tensorflow

# 구현을 위한 딥러닝

■ 고려대학교 물리학과 한승희

■ [mod96@naver.com](mailto:mod96@naver.com)

# Contents

---

1

**Review**

2

**Curse of Dimensionality**

3

**Dimension Reduction**

4

**Auto Encoder**

5

**VAE**

6

**Implementation**

# Contents

---

1

**Review**

2

Curse of Dimensionality

3

Dimension Reduction

4

Auto Encoder


5

VAE

6

Implementation

# Example



# Example

---

# Contents

---


- 1 Review
- 2 **Curse of Dimensionality**
- 3 Dimension Reduction
- 4 Auto Encoder
- 5 VAE
- 6 Implementation

# Curse of Dimensionality

---

- ❖ Model becomes complex
- ❖ Need exponentially many data
- ❖ Metric(distance) goes wrong

# Need exponentially many data





# Metric goes wrong

---

❖ In  $D$ -dimensional space,

# Contents

---

- 1 Review
- 2 Curse of Dimensionality
- 3 **Dimension Reduction**
- 4 Auto Encoder
- 5 VAE
- 6 Implementation


# Dimension Reduction

---

## ❖ Traditional Algorithms

- PCA
- LDA
- ICA
- CCA
- LLE
- MDS
- Isomap
- t-SNE

# PCA



- ❖ PCA defines a new orthogonal coordinate system that optimally describes variance in a single dataset.

# PCA


---

# Contents

---


- 1 Review
- 2 Curse of Dimensionality
- 3 Dimension Reduction
- 4 **Auto Encoder**
- 5 VAE
- 6 Implementation

## AE




# AE vs PCA

Linear vs nonlinear dimensionality reduction






# AE vs RBM\*



\* RBM : Restricted Boltzmann Machine

# AE...Conv2DTranspose?




# AE...Conv2DTranspose?


$$\begin{bmatrix} w_1 & w_2 & w_3 \\ w_4 & w_5 & w_6 \\ w_7 & w_8 & w_9 \end{bmatrix} * \begin{bmatrix} x_1 & x_2 & x_3 & x_4 \\ x_5 & x_6 & x_7 & x_8 \\ x_9 & x_{10} & x_{11} & x_{12} \\ x_{13} & x_{14} & x_{15} & x_{16} \end{bmatrix} = \begin{bmatrix} y_1 & y_2 \\ y_3 & y_4 \end{bmatrix}$$

$$\begin{bmatrix} w_1 & w_2 & w_3 & 0 & w_4 & w_5 & w_6 & 0 & w_7 & w_8 & w_9 & 0 & 0 & 0 & 0 & 0 \\ 0 & w_1 & w_2 & w_3 & 0 & w_4 & w_5 & w_6 & 0 & w_7 & w_8 & w_9 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & w_1 & w_2 & w_3 & 0 & w_4 & w_5 & w_6 & 0 & w_7 & w_8 & w_9 & 0 \\ 0 & 0 & 0 & 0 & 0 & w_1 & w_2 & w_3 & 0 & w_4 & w_5 & w_6 & 0 & w_7 & w_8 & w_9 \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_{15} \\ x_{16} \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ y_3 \\ y_4 \end{bmatrix}$$


# AE – Usage1 : Denoising



# AE – Usage1 : Denoising



# AE - Usage2 : Classification





# Contents

---


- 1 Review
- 2 Curse of Dimensionality
- 3 Dimension Reduction
- 4 Auto Encoder
- 5 **VAE**
- 6 Implementation

# Variational Auto Encoder (VAE)






# VAE – latent space sampling



# VAE – latent space sampling



# VAE – loss function

---

$$\begin{aligned} L(\theta, \phi; x^i) &= D_{KL}(q_\phi(z|x^i) || p_\theta(z)) - E_{z \sim q_\phi(z|x^i)} [\log p_\theta(x^i|z)] \\ &\approx -\frac{1}{2} \sum_{j=1}^J \left( 1 + \log(\sigma_j^i)^2 - (\mu_j^i)^2 - (\sigma_j^i)^2 \right) + H[q_\phi(z|x^i), p_\theta(x^i|z)] \end{aligned}$$

# Contents

---

- 1 Review
- 2 Curse of Dimensionality
- 3 Dimension Reduction
- 4 Auto Encoder
- 5 VAE
- 6 **Implementation**

# AE

---

❖ MNIST

# VAE

---

- ❖ MNIST
- ❖ CIFAR10