

R Library Functions by Package

Functions used in `spss_cod_district-1_23-25.rmd`, organized by package with linked documentation and short descriptions.

Package	Functions
base	20
stats	10
here	1
readr	1
dplyr	19
lubridate	1
rlang	2
tibble	1
purrr	1
tidyselect	2
kableExtra	3

base

Function	Description
readRDS	Reads a single R object saved with saveRDS(), commonly used for loading saved models, lists, or processed data objects.
list2env	Converts a named list into individual objects inside an environment, often used to unpack saved model lists.
ifelse	Vectorized conditional function: returns one value when a condition is true and another when false.
nrow	Returns the number of rows in a data frame, matrix, or similar object.
sprintf	Formats strings using C-style formatting, useful for fixed decimal places and formatted labels.
paste0	Concatenates strings together with no separator.
abs	Returns absolute values; commonly used in residual, error, and ratio calculations.
unname	Removes names from vectors, lists, or other named objects.
summary	Generic summary function; for models, it returns model fit statistics and coefficient tables.
attr	Gets or sets object attributes, such as labels, metadata, or custom stored values.
which.max	Returns the position of the maximum value in a vector.
as.integer	Converts an object to integer type.
as.numeric	Converts an object to numeric type.
as.list	Converts an object to a list.
as.character	Converts an object to character/string type.
tolower	Converts character strings to lowercase.
apply	Applies a function across rows or columns of a matrix/data-frame-like object.
trimws	Removes leading and/or trailing whitespace from strings.
seq	Creates regular numeric sequences.
lapply	Applies a function to each element of a list and returns a list.

stats

Function	Description
<u>lm</u>	Fits linear regression models.
<u>cor</u>	Computes correlation coefficients between numeric variables.
<u>model.frame</u>	Extracts the model frame used to fit a model, including the exact rows and variables used.
<u>model.matrix</u>	Builds the design matrix used by regression models, including dummy-coded variables.
<u>model.response</u>	Extracts the dependent variable from a model frame.
<u>update</u>	Updates and refits model calls, often used in stepwise or formula-adjustment workflows.
<u>mahalanobis</u>	Computes Mahalanobis distances, useful for multivariate outlier detection.
<u>df.residual</u>	Returns residual degrees of freedom from a fitted model.
<u>coef</u>	Extracts model coefficients from fitted model objects.
<u>sd</u>	Computes standard deviation.

here

Function	Description
<u>here</u>	Builds project-relative file paths, helping avoid hard-coded absolute paths.

readr

Function	Description
<u>read_csv</u>	Reads CSV files into R as tibbles.

dplyr

Function	Description
rename_with	Renames columns using a function, such as converting names to lowercase.
filter	Keeps rows that satisfy logical conditions.
mutate	Creates or modifies columns in a data frame.
arrange	Sorts rows by one or more variables.
group_by	Groups data for grouped summaries, mutations, or calculations.
ungroup	Removes grouping from a grouped data frame.
case_when	Vectorized multi-condition conditional logic; cleaner alternative to nested ifelse().
select	Selects, reorders, or drops columns.
setdiff	Returns elements in one vector/set but not another; often used for column-list comparisons.
bind_cols	Combines data frames column-wise.
bind_rows	Combines data frames row-wise.
pull	Extracts a single column as a vector.
relocate	Moves columns to a new position in a data frame.
all_vars	Legacy helper for applying a predicate across selected variables.
coalesce	Returns the first non-missing value among supplied vectors.
full_join	Joins two data frames while keeping all rows from both.
transmute	Creates new columns and drops all columns not explicitly created or kept.
distinct	Keeps unique rows based on one or more columns.
slice_head	Selects the first n rows from a data frame or from each group.

lubridate

Function	Description
parse_date_time	Parses dates/times from character strings using one or more possible date-time formats.

rlang

Function	Description
ensym	Captures a function argument as a symbol, useful for writing tidy-eval functions.
as_string	Converts symbols or names to character strings.

tibble

Function	Description
rownames_to_column	Converts row names into an explicit column.

purrr

Function	Description
map	Applies a function to each element of a vector/list and returns a list.

tidyselect

Function	Description
all_of	Selects columns using a character vector of names; errors if any names are missing.
everything	Selects all columns, usually inside <code>select()</code> , <code>relocate()</code> , or similar tidyselect contexts.

kableExtra

Function	Description
kable_styling	Adds styling options to <code>knitr::kable()</code> tables, including LaTeX/PDF formatting.
column_spec	Applies formatting to selected columns in a kableExtra table.
row_spec	Applies formatting to selected rows in a kableExtra table.

Note: Function names are clickable links to the documentation URLs supplied in the source list.