YOKOHAMA / T-RUCK 0W-20

TECHNICAL DATA SHEET | TDS

HEAVY-DUTY DIESEL ENGINE OIL

PRODUCT DESCRIPTION

YOKOHAMA T-RUCK 0W-20 is a low-viscosity heavy-duty diesel engine oil developed for applications specifying SAE 0W-20 and Daimler Truck DTFR 15C140. Its formulation supports engine protection and helps protect exhaust after-treatment systems while supporting fuel-efficient operation in compatible engines.

APPLICATIONS

For on-highway heavy-duty diesel engines equipped with exhaust after-treatment systems where SAE 0W-20 and Daimler Truck DTFR 15C140 are specified. Suitable for compatible engine designs requiring this performance profile.

PERFORMANCE SPECIFICATIONS

DAIMLER TRUCK	DTFR 15C140

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
SAE viscosity grade	—	—	**0W-20**
Kinematic viscosity at 40°C	ASTM D445	mm²/s	**42.0**
Kinematic viscosity at 100°C	ASTM D445	mm²/s	**7.8**
Viscosity index	ASTM D2270	—	**159.5**
Density at 15°C	ASTM D4052	kg/m³	**840**
Flash point, COC	ASTM D92	°C	**230**
Pour point	—	°C	**-45**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.