YOKOHAMA / T-RUCK 10W-40

TECHNICAL DATA SHEET | TDS

CH-4 | HEAVY-DUTY MULTIGRADE ENGINE OIL

PRODUCT DESCRIPTION

YOKOHAMA T-RUCK 10W-40 CH-4 is a heavy-duty multigrade engine oil for demanding on-road and off-highway service. Its additive system is designed to limit soot-related thickening, control oxidation and deposits, and help protect critical engine components under high loads and temperatures.

APPLICATIONS

For turbocharged and naturally aspirated four-stroke diesel engines in trucks, buses, agricultural and construction equipment requiring SAE 10W-40 and the listed performance levels. It is also suitable for gasoline engines requiring API SN where the viscosity grade and stated performance requirements apply. EGR, DPF or SCR-equipped engines may be served when the applicable oil requirements are met.

PERFORMANCE SPECIFICATIONS

API CI-4 / CI-4 PLUS / CJ-4 / CK-4
API SN
ACEA E11 / E7 / E9-16
JASO DH-1 / DH-2
CHINA STANDARD D1
CATERPILLAR ECF-1a / ECF-2 / ECF-3
CUMMINS CES 20076 / 20077 / 20078 / 20081 / 20086 / 20100
DAF PSQL 2.1 E
DETROIT DIESEL DFS 93K215 / 93K218 / 93K222
MERCEDES-BENZ DTFR 15C100
DEUTZ DQC-III-18 LA / DQC-III-10 LA
FORD WSS-M2C171-F1
JOHN DEERE JDQ-78X
MACK EO-M PLUS / EO-N / EO-N Premium Plus / EO-O Premium Plus / EO-S 4.5
MAN M3575 / M3775
MTU Oil Category 2.1
RENAULT TRUCKS RGD / RLD / RLD-2 / RLD-3 / RXD
VOLVO VDS-3 / VDS-4 / VDS-4.5

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
SAE viscosity grade	SAE J300	-	**10W-40**
Kinematic viscosity at 40°C	ASTM D445	mm²/s	**93.73**
Kinematic viscosity at 100°C	ASTM D445	mm²/s	**14.13**
Viscosity index	ASTM D2270	-	**155.00**
Density at 15°C	ASTM D4052	kg/m³	**848**
Flash point, COC	ASTM D92	°C	**256**
Pour point	ASTM D97	°C	**-36.7**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.