YOKOHAMA / T-RUCK 5W-30 CK-4

TECHNICAL DATA SHEET | TDS

HEAVY-DUTY DIESEL ENGINE OIL

PRODUCT DESCRIPTION

YOKOHAMA T-RUCK 5W-30 CK-4 is a heavy-duty diesel engine oil for demanding on-road and off-road operation. Its SAE 5W-30 viscosity and stated performance profile support engine cleanliness, wear protection and resistance to oil breakdown in compatible applications.

APPLICATIONS

For trucks, tractor units, buses and off-highway diesel equipment requiring SAE 5W-30 and one or more of the performance specifications listed below. It may also be used in gasoline engines where API SN in SAE 5W-30 is specified.

PERFORMANCE SPECIFICATIONS

ACEA	**E4 / E7 / E8 / E11**
JASO	**DH-1-17 / DH-2-17 / DL-0-17**
API	**CK-4 / CJ-4 / CI-4 PLUS / CI-4 / SN**
SFU	**Mercedes-Benz Trucks / MAN / DAF / IVECO / Mack**
SFU	**Cummins / Detroit Diesel / Caterpillar / Deutz / Liebherr**

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
SAE viscosity grade	—	—	**5W-30**
Kinematic viscosity at 40°C	ASTM D445	mm²/s	**73.13**
Kinematic viscosity at 100°C	ASTM D445	mm²/s	**11.97**
Viscosity index	ASTM D2270	—	**161**
Density at 15°C	ASTM D4052	kg/m³	**845**
Flash point, COC	ASTM D92	°C	**239**
Pour point	ASTM D97	°C	**-43.2**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.