日本の品質 JAPANESE QUALITY

YOKOHAMA® MOTOR OIL

YOKOHAMA / IMPROVE

TECHNICAL DATA SHEET | TDS

SAE 5W-50

API SN / CF

PRODUCT DESCRIPTION

YOKOHAMA IMPROVE SAE 5W-50 is a multi-grade engine oil developed for compatible gasoline and earlier-generation light-duty diesel engines. Its wide viscosity range is intended to support lubricating-film continuity, wear control and engine cleanliness across varying operating temperatures and demanding service conditions.

APPLICATIONS

For gasoline and earlier-generation light-duty diesel engines requiring SAE 5W-50 and API SN/CF.

PERFORMANCE SPECIFICATIONS

API	**SN / CF**	**SAE**	**5W-50**

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	TYPICAL VALUE
SAE Viscosity Grade	SAE J300	**5W-50**
Kinematic Viscosity at 40°C (mm²/s)	ASTM D445	**105.5**
Kinematic Viscosity at 100°C (mm²/s)	ASTM D445	**17.10**
Viscosity Index	ASTM D2270	**178**
Density at 15°C (g/cm³)	ASTM D4052	**0.850**
Flash Point, COC (°C)	ASTM D92	**231**
Pour Point (°C)	ASTM D97	**-39**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.

6F Kaneko 2nd Building, 2-6-23 Shin Yokohama,
Kouhoku-ku, Yokohama-shi, Kanagawa, 222-0033
JAPAN
www.yokohamamotoroil.com
info@yokohamamotoroil.com