日本の品質 JAPANESE QUALITY

YOKOHAMA® MOTOR OIL

YOKOHAMA / MOTISO HP

TECHNICAL DATA SHEET | TDS

2-T AMBER

TWO-STROKE MOTORCYCLE ENGINE OIL

PRODUCT DESCRIPTION

YOKOHAMA MOTISO HP 2-T AMBER is a two-stroke petrol engine oil for motorcycles and small-engine equipment requiring API TC and JASO FC performance. Its lubricating and deposit-control properties support component protection and engine cleanliness, while clean-burning behaviour helps limit exhaust smoke and spark-plug deposits.

APPLICATIONS

For two-stroke motorcycles, scooters, mopeds and compatible small engines using premix or oil-injection lubrication. Follow the equipment maker's specified fuel-to-oil ratio for premix use. Not intended for four-stroke crankcases, separate gearboxes or outboard engines requiring NMMA TC-W3 oil.

PERFORMANCE SPECIFICATIONS

API TC	**JASO** FC

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	TYPICAL VALUE
Kinematic viscosity at 40°C (mm²/s)	ASTM D445	**59.45**
Kinematic viscosity at 100°C (mm²/s)	ASTM D445	**8.72**
Viscosity index	—	**122.75**
Density at 15°C (kg/m³)	ASTM D4052	**863.0**
Flash point, COC (°C)	ISO 2592	**132**
Pour point (°C)	ASTM D97	**-23.2**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.

6F Kaneko 2nd Building, 2-6-23 Shin Yokohama,
Kouhoku-ku, Yokohama-shi, Kanagawa, 222-0033
JAPAN
www.yokohamamotoroil.com
info@yokohamamotoroil.com