YOKOHAMA / T-RUCK 422

TECHNICAL DATA SHEET | TDS

UNIVERSAL TRACTOR TRANSMISSION OIL (UTTO)

PRODUCT DESCRIPTION

YOKOHAMA T-RUCK 422 is a multipurpose tractor transmission oil for combined transmission and hydraulic duties in agricultural and off-highway equipment. Its balanced friction characteristics support wet-brake and clutch operation, while anti-wear, oxidation and foam-control properties help protect gears, hydraulic components and shared-sump systems. Deposit and corrosion control supports system cleanliness and reliable power transfer across changing load conditions.

APPLICATIONS

For tractors and off-highway equipment requiring UTTO performance such as API GL-4, Massey Ferguson M1135 and Ford ESEN-M2C86-B. Applications include transmissions, differentials, final drives, hydraulic lift and steering systems, wet brakes, wet clutches and PTO drives in agricultural, construction and field equipment.

PERFORMANCE SPECIFICATIONS

API GL-4
MASSEY FERGUSON M1135
FORD ESEN-M2C86-B

TYPICAL TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	**56.67**
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	**9.50**
Viscosity index	ASTM D2270	-	**148**
Density at 15°C	ISO 12185	kg/m^3	**882.0**
Flash point, COC	ISO 2592	°C	**220**
Pour point	-	°C	**-39.6**
Brookfield viscosity at -20°C	ASTM D2983	mPa·s	**4300**

Note: The values shown in this table are typical values and do not constitute product specifications. Minor variations may occur between production batches due to normal manufacturing tolerances.