



Mobil 1™ ESP X1 0W-30
Mobil Passenger Vehicle Lube, United States
Advanced Synthetic Motor Oil

Product Description

Mobil 1™ ESP X1 0W-30 is an advanced synthetic engine oil designed to help provide exceptional cleaning power, wear protection and overall performance. Mobil 1 ESP X1 0W-30 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline powered automobiles. Mobil 1 ESP X1 0W-30 meets or exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel and gasoline powered passenger car engines.

Features and Benefits

Mobil 1 ESP X1 0W-30 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's). Mobil 1 ESP X1 0W-30 has been designed to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits. Key features and potential benefits include:

Features	Advantages and Potential Benefits
Low Ash Content	Helps to reduce particulate build up in Diesel Particulate Filters
Low Sulfur and Phosphorous content	Helps to reduce poisoning of Gasoline Catalytic Converters
Active cleaning agents	Helps to reduce deposits and sludge build-up to enable long and clean engine life
Outstanding thermal and oxidation stability	Helps to reduce oil aging allowing extended drain interval protection
Low oil consumption	Less hydrocarbon pollution
Enhanced frictional properties	Potentially aids fuel economy
Excellent low temperature capabilities	Quick cold weather starting and ultra-fast protection Helps to extend engine life

Applications

Mobil 1 ESP X1 0W-30 is recommended for many types of modern automobile engines, especially the high-

performance gasoline and diesel engines found in the latest passenger cars, SUVs and light vans.

Mobil 1 ESP X1 0W-30 is especially suitable for extreme conditions, where conventional oil often may not perform. It is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

Mobil 1 ESP X1 0W-30 meets or exceeds the requirements of:	
ACEA C2, C3	X

Mobil 1 ESP X1 0W-30 has the following builder approvals:	
MB-Approval 229.31	X
MB-Approval 229.51	X
MB-Approval 229.52	X

Typical Properties

Mobil 1 ESP X1 0W-30	
Viscosity, ASTM D 445	
cSt @ 40°C	65.0
cSt @ 100°C	12.0
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous	0.08
Density @15° C kg/l, ASTM D 4052	0.847
Total Base Number (TBN) ASTM D 2896	7.6
MRV at -30°C	24,800
Viscosity Index	180
HTHS Viscosity, mPa•s @150°C, ASTM D 4683	3.5

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2016 Exxon Mobil Corporation. All Rights Reserved.
