



Shell Helix *HX5 SN 15W-40*

Premium multi-grade oil - Helps to keep engines clean

Shell Helix HX5 SN is designed to provide consistent gasoline engine performance. It works hard to help protect against engine sludge and reduce wear. It is suitable for use in a wide variety of vehicles for everyday driving conditions.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Active cleansing technology**
Actively locks away harmful performance-robbing deposits.
- **Good sludge protection**
Helps to prevent engine sludge build-up.
- **Excellent wear protection**
Helps to extend engine life by providing wear protection that no mineral oil can surpass ¹

¹ Based on Sequence IVA wear test using 5W-30

Specifications, Approvals & Recommendations

- API SN
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
<http://lubematch.shell.com>
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Main Applications

- Everyday motorway or city driving can mean severe conditions for engine oil. Shell Helix HX5 SN's premium multigrade formulation helps to provide protection in everyday daily driving conditions. Suitable for gasoline, gas or ethanol containing fuels.

Typical Physical Characteristics

Properties			Method	Shell Helix HX5 SN 15W-40
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.40
Kinematic Viscosity	@40°C	cSt	ASTM D445	108.60
Viscosity Index			ASTM D2270	135
MRV	@-25°C	cP	ASTM D4684	19200
Density	@15°C	kg/m ³	ASTM D4052	876.3
Flash Point		°C	ASTM D92	238
Pour Point		°C	ASTM D92	-30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

▪ Health and Safety

Shell Helix HX5 SN 15W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.epc.shell.com

▪ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.