



Shell Rimula R3 Multi 10W-30 (CH-4)

- Triple Action
- Resists Wear, Deposits and Heat

Multigrade Heavy Duty Diesel Engine Oils

Shell Rimula R3 Multi Energised Protection oils feature modern high performance lubricant chemistry specifically designed to protect against the changing needs of your driving conditions. This unique adaptive technology features multi-component systems to provide triple action protection; low wear for long engine life, low deposit formation to maintain engine performance and resists breakdown by heat for continuous protection.

With a range of leading engine maker approvals, it is suitable for many heavy duty engines, non-turbo-charged and turbo-charged alike, in on and off-highway service.



ENERGISED PROTECTION
Adapting to your engine's changing needs

Performance, Features & Benefits

Equipment manufacturer acceptance

Shell Rimula R3 Multi oils are approved for use in a variety of engine applications by leading OEMs.

Engine cleanliness

The high thermal stability and oil oxidation resistance provide a high standard of protection against piston deposits. Engine cleanliness is further enhanced through use of high performance dispersants to control sludge and deposits in other parts of the engine.

Low engine wear

The combination of active anti-wear additives and good engine cleanliness controls engine wear, gives long engine life, maintains engine power and efficiency and lowers servicing costs.

Dedicated diesel engine oil performance

Shell Rimula R3 Multi is the ideal choice for a wide range of turbo-charged and non-turbo-charged engines under normal operation. It is particularly recommended for use in older trucks and buses as well as for cost effective lubrication in off-highway applications such as agricultural tractors.

For more severe operation or application in modern low emission engines we recommend Shell Rimula R4 multigrade engine oils.

Specifications, Approvals & Recommendations

- Caterpillar ECF-1-A
- Cummins 20076, 75, 72, 71
- MACK EOM, EO-M+
- API CH-4, CG-4, CF-4, CF

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



Typical Physical Characteristics

Properties				Method	Shell Rimula R3 Multi (CH-4)
SAE Viscosity Grade					10W-30
Kinematic Viscosity	@40°C	mm ² /s		ASTM D445	75.1
Kinematic Viscosity	@100°C	mm ² /s		ASTM D445	11.5
Dynamic Viscosity	@-25°C	mPa s		ASTM D5293	6700
Viscosity Index				ASTM D2270	147
Density	@15°C	kg/l		ASTM D4052	0.881
Flash Point (COC)				ASTM D92	220

Properties		Method	Shell Rimula R3 Multi (CH-4)
Pour Point	°C	ISO 3016	-36
Total Base Number	mg KOH/g	ASTM D2896	10.8
Sulphated Ash	%	ASTM D874	1.44

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

▪ Health and Safety

Shell Rimula R3 Multi is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

▪ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

▪ Advice

Advice on applications not covered here may be obtained from your Shell representative.