



# Texol Multisyn™ TDX 5W-30

## Technical Data Sheet

### Texol Multisyn™ TDX 5W-30

Premium performance fuel efficient synthetic diesel engine oil

#### Product description

Texol Multisyn™ TDX 5W-30 is a premium performance fuel efficient, low emissions synthetic heavy duty diesel engine oil. It is designed to meet the performance requirements of a wide range of diesel and gas powered engines in off highway and construction applications, while offering improved fuel economy with lower exhaust emission output.

Texol Multisyn™ TDX 5W-30 is formulated for use in most Euro V and some Euro VI trucks fitted with advanced after treatment systems where low emission diesel lubricants are required.

Texol Multisyn™ TDX 5W-30 is formulated with Premium performance synthetic base oils and advanced technology dispersant and detergent additives, with robust oxidation wear and corrosion inhibitors, viscosity improver and foam suppression additives.

#### Customer benefits

- Designed to deliver improved fuel efficiency with low emissions performance, helping reduce total cost of ownership
- Low viscosity synthetic base oils promote rapid oil circulation and wear protection during cold or sub-zero engine start-ups
- Formulated for optimum engine wear and corrosion protection with reliable foam suppression performance
- Advanced piston cleanliness and good wear control offers optimum engine service life with lower Maintenance downtime
- Advanced formulation helps reduce emission control system service downtime and offers improved Diesel Particulate Filter (DPF) life
- Premium additive design with synthetic base stocks help control oxidation, sludge and oil thickening improving vehicle uptime

#### Applications

- Texol Multisyn™ TDX 5W-30 is a diesel engine oil recommended for four-stroke naturally aspirated and turbocharged diesel engines
- Texol Multisyn™ TDX 5W-30 is recommended for use in modern low emission diesel engines (most Euro V and Euro VI trucks fitted with advanced after-treatment systems such as DPFs and Selective Catalytic Reduction (SCR) reduction systems. It is also backwards compatible in older engines in service in markets using Euro V quality diesel fuel or ultra low sulphur diesel (ULSD), and many bio-fuel formulations



# Texol Multisyn™ TDX 5W-30

## Technical Data Sheet

### Texol Multisyn™ TDX 5W-30

Premium performance fuel efficient synthetic diesel engine oil

### Typical Properties

| Property (Unit)       | TDX 5W-30 | Method     |
|-----------------------|-----------|------------|
| Density at +15 °C     | 855       | ASTM D4052 |
| Viscosity @40°C, cSt  | 76        | ASTM D445  |
| Viscosity @100°C, cSt | 12.6      | ASTM D445  |
| Viscosity Index       | 162       | ASTM D2270 |
| Flash Point, °C       | 234       | ASTM D92   |
| Pour Point, °C        | -42       | ASTM D97   |
| Sulphated Ash, %wt    | 1.00      | ASTM D874  |

### Specifications

Multisyn™ TDX 5W-30 meets:

- ACEA E7  
E6
- API CI-4 including CH-4 and CG-4
- DDC/MTU Type 3.1
- JASO DH-2
- Mack EO-N
- Daimler MB 228.51
- Deutz DQC III-10 LA
- MAN M3271-1, M3477
- Renault RLD-2
- Volvo VDS-3

### Technical Expertise

Texol experts on Texol Multisyn™ series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.