

CLI Help Text Rewrites

Current vs. proposed output for each command | Primer CLI Design Guidelines applied | String changes only

1. mod

First run — user installs CLI and runs `mod` with no arguments.

CURRENT

```
$ mod
Moderne CLI 4.1.6
Usage: mod [-h] [--version] [COMMAND]
Powering software engineering at agent
scale.
Options:
-h, --help Display this help message.
--version Display version info.
Workflow:
config Configure the CLI.
git Multi-repository git operations.
build Generate LST artifacts.
run Run an OpenRewrite recipe locally.
study Produce studies.
search Search repositories.
publish Publish LST artifacts.
Operations:
audit (INCUBATING) Audit activity.
batch Add batch changes.
clean Clean artifacts.
exec Execute a shell command.
list List repositories.
...
```

PROPOSED (Primer-aligned)

```
$ mod
Moderne CLI 4.1.6
Powering software engineering at agent
scale.

USAGE
  mod <command> <subcommand> [flags]

GET STARTED
  1. mod config moderne edit <tenant-url>
     Connect to your Moderne tenant.
  2. mod config moderne login
     Authenticate with your account.

CONFIGURE YOUR ENVIRONMENT
  Get these values from your admin:
  3. mod config http trust-store edit
  4. mod config recipes artifacts
  artifactory add
  5. mod config lsts artifacts artifactory
  add
  6. mod config build maven settings edit

RUN RECIPES
  7. mod config recipes moderne sync
  8. mod build .
  9. mod run . --recipe <name>

FLAGS
-h, --help - Show help.
--version - Show version.

LEARN MORE
  Guide:
https://docs.moderne.io/cli/getting-started
```

2. mod config -h

User tries to figure out which config commands to run.

CURRENT

```
$ mod config -h
Usage:
Global configuration options...
mod config [-h] [COMMAND]

Commands:
agent-tools Manage agent tools.
build Configures build tools.
clone Configures cloning.
comms Configures comms.
dotnet Configures DotNet.
environment Build environment.
features Experimental features.
go Configures Go.
http Configures HTTP.
java Configures Java.
license Configure license.
llm LLM credentials.
lsts Configures LSTs.
metrics Configures metrics.
moderne Connection to Moderne.
node Configures Node.
python Configures Python.
recipes Recipe marketplace.
run Recipe run behavior.
scm (DEPRECATED)
```

PROPOSED (Primer-aligned)

```
$ mod config -h
Configure the Moderne CLI.

USAGE
  mod config <command> [flags]

SETUP (required)
  moderne – Moderne tenant.
  http – Trust store (HTTPS/SSL).
  recipes – Recipe sources.
  lsts – LST artifact storage.
  build – Build tools.

AUTO-CONFIGURED
  license – Syncs from login.

OPTIONAL
  java – JDK options.
  agent-tools – AI agents.
  environment – Build env.
  run – Run behavior.
  clone – Cloning.

LEARN MORE
  Full list: mod config -h --all
```

3. mod config http trust-store edit file -h

User needs to configure SSL trust store.

CURRENT

```
$ mod config http trust-store edit file -h
```

Configures truststore to point to a file.
All subsequent commands will use this.

Parameters:

<file> The absolute path to the truststore file.

Options:

--password=<password>

The password used to access the truststore.

--provider=<provider>

The provider of the truststore.

--type=<type>

The type of the truststore file.

PROPOSED (Primer-aligned)

```
$ mod config http trust-store edit file -h
```

Configure the trust store for HTTPS.

Lets the CLI connect to internal services.
Without it, commands fail with
PKIX path building errors.

USAGE

```
mod config http trust-store edit file  
<path> [flags]
```

? Hint: Dont know the path?

Ask your platform or security team.

Common locations:

Linux /etc/pki/java/cacerts

macOS /Library/Java/.../cacerts

Or try: `mod config http trust-store edit system`

FLAGS

--password – Often changeit.

--type – JKS or PKCS12.

EXAMPLES

```
$ mod config http trust-store edit file  
  /etc/pki/java/corp-truststore.jks  
  --password changeit
```

LEARN MORE

Verify: `mod config http trust-store show`

4. mod config recipes artifacts artifactory add -h

User needs to add Artifactory for recipes.

CURRENT

```
$ mod config recipes artifacts  
artifactory add -h
```

Configures the artifact repository
to resolve recipes from.
All subsequent recipe installation
commands will use this.

Parameters:
<url> The URL of the artifact
repository.

Options:
--authorization Auth header.
--jfrog-api-token JFrog token.
--password Password.
--skip-ssl Skip SSL.
--user Username.

PROPOSED (Primer-aligned)

```
$ mod config recipes artifacts  
artifactory add -h  
Connect to your artifact repo for recipes.
```

USAGE

```
mod config recipes artifacts  
artifactory add <url> [flags]
```

? **Hint:** Dont know the URL?
Check pom.xml or ~/.m2/settings.xml

FLAGS

Authentication (pick one):
--user + --password – Credentials.
--jfrog-api-token – API token.
--authorization – Bearer.

EXAMPLES

```
$ mod config recipes artifacts  
artifactory add  
https://artifactory.corp.com/recipes  
--user svc --password ****
```

LEARN MORE

Verify: `mod config recipes artifacts show`

5. mod config lsts artifacts artifactory add -h

User needs to add Artifactory for LSTs.

CURRENT

```
$ mod config lsts artifacts  
artifactory add -h
```

Configures the repository that LSTs will be published to and downloaded from.
Must be configured before you can run the publish command.

Parameters:
<url> The URL of the artifact repository.

Options:
--authorization Auth header.
--jfrog-api-token JFrog token.
--password Password.
--skip-ssl Skip SSL.
--user Username.

PROPOSED (Primer-aligned)

```
$ mod config lsts artifacts  
artifactory add -h  
Configure where the CLI stores LSTs.
```

LSTs are build outputs that recipes run against.

USAGE

```
mod config lsts artifacts  
artifactory add <url> [flags]
```

? **Hint:** Often same Artifactory server as recipes, different repo.
! **Note:** Needs read AND write access.

FLAGS

Authentication (pick one):
--user + --password – Credentials.
--jfrog-api-token – API token.
--authorization – Bearer.

Tip: Same creds as recipe repo often work.

LEARN MORE

Verify: `mod config lsts artifacts show`

6. mod config build maven settings edit -h

User needs to configure Maven settings.

CURRENT

```
$ mod config build maven
settings edit -h

Configure Maven settings.
Allows you to specify the location
of a Maven settings.xml file.

Parameters:
<settingsXml> The location of
a Maven settings.xml file.

Options:
--local Apply to repos in a dir.
--save Apply to moderne.yml.
```

PROPOSED (Primer-aligned)

```
$ mod config build maven
settings edit -h
Point the CLI to your Maven settings.

If your org uses a custom settings.xml,
the CLI needs it for builds.

USAGE
mod config build maven settings edit
<path> [flags]

? Hint: Dont know where it is?
Default: ~/.m2/settings.xml
Global:  $MAVEN_HOME/conf/settings.xml

EXAMPLES
$ mod config build maven settings edit
  ~/.m2/settings.xml

LEARN MORE
Verify: ...maven settings show
```

7. Wrong command path (bug)

User types wrong subcommand, CLI silently shows wrong help.

CURRENT

```
$ mod config java trust-store edit -h
```

Configures Java options used for building LSTs and running recipes.

```
mod config java [-h] [COMMAND]
```

Commands:

jdk Configures locations of JDKs.
options Configures JVM options.
version Configures the JDK to use.

PROPOSED (Primer-aligned)

```
$ mod config java trust-store edit -h
```

! Error: trust-store is not a subcommand of mod config java.

Did you mean:

```
mod config http trust-store edit
```

Available commands for

mod config java:

jdk – JDK locations.
options – JVM options.
version – JDK version.

8. mod config moderne edit -h

Step 1 of setup. User needs to connect to their Moderne tenant.

CURRENT

```
$ mod config moderne edit -h
```

Configures the connection to Moderne.
Must be configured before you can
install and run recipes.
All subsequent commands will use this
Moderne tenant.

Parameters:

The URL of the Moderne UI.

Options:

```
--api The URL of the tenant API.  
--password (DEPRECATED)  
--skip-ssl Skip SSL verification.  
--token (DEPRECATED)  
--user (DEPRECATED)
```

PROPOSED (Primer-aligned)

```
$ mod config moderne edit -h
```

Connect the CLI to your Moderne tenant.

This is step 1 of setup. Run this before
logging in or installing recipes.

USAGE

```
mod config moderne edit
```

? Hint: Your tenant URL is the address
you use to access Moderne in your
browser.

ARGUMENTS

– Your Moderne tenant URL.
e.g. <https://app.moderne.io>

FLAGS

```
--api – Tenant API URL (auto-detected  
from host if not set).  
--skip-ssl – Skip SSL verification.
```

EXAMPLES

```
$ mod config moderne edit  
https://app.moderne.io
```

NEXT STEP

Log in: `mod config moderne login`

LEARN MORE

Verify: `mod config moderne show`

9. mod config moderne login -h

Step 2 of setup. User authenticates with Moderne.

CURRENT

```
$ mod config moderne login -h
```

Logs the CLI into Moderne

The default authorization mode is a web-based browser flow. After login and consent, a PAT will be created and stored in the configuration.

Alternatively, use `--with-token` to pass in an existing token.

Options:

- `--expiration` Time to expiration as ISO-8601 duration. Example: `P180D` for 180 days.
- `--with-token` A Moderne personal access token to use.

PROPOSED (Primer-aligned)

```
$ mod config moderne login -h
Log in to Moderne.
```

Opens your browser for authentication. After login, a token is created and stored locally. Your license is also synced.

USAGE

```
mod config moderne login [flags]
```

FLAGS

- `--with-token` – Pass an existing token instead of browser flow.
- `--expiration` – Token lifetime (ISO-8601). e.g. `P180D` for 180 days.

? Hint: No browser available?
Use `--with-token` for CI/headless.

EXAMPLES

Browser flow:

```
$ mod config moderne login
```

Token flow (CI):

```
$ echo $TOKEN | mod config moderne
login
--with-token
```

NEXT STEP

Configure environment, or sync recipes:
`mod config recipes moderne sync`

LEARN MORE

Verify: `mod config moderne show`

10. mod config recipes moderne sync -h

User installs recipes from Moderne after logging in.

CURRENT

```
$ mod config recipes moderne sync -h
```

Synchronizes the local CLI recipe marketplace with Moderne.

Destroys all recipes in the local CLI marketplace and replaces them with the latest recipes available in Moderne.

The recipes defined by these artifacts will then be available to run.

PROPOSED (Primer-aligned)

```
$ mod config recipes moderne sync -h
Download the latest recipes from Moderne.
```

Refreshes your local recipe catalog with the latest recipes from your Moderne tenant.
Run this after logging in, or whenever you want to update to the latest recipes.

USAGE

```
mod config recipes moderne sync
```

! Note: This replaces your current local recipes with the latest from Moderne.

EXAMPLES

```
$ mod config recipes moderne sync
```

NEXT STEP

See available recipes:

```
mod config recipes list
mod config recipes search
```

Build and run:

```
mod build .
mod run . --recipe
```

LEARN MORE

List installed: `mod config recipes list`