CPU API and reverse-mode evidence | one CPU | dtype in workload name

cholesky_factor_64_f64/faer
cholesky_factor_64_f64/kernix
cholesky_factor_64_f64/nalgebra
cholesky_factor_64_f64/numpy
create_ones_64x64_f32/candle
create_ones_64x64_f32/faer
create_ones_64x64_f32/kernix
create_ones_64x64_f32/ndarray
create_ones_64x64_f32/numpy
create_zeros_64x64_f32/candle
create_zeros_64x64_f32/faer
create_zeros_64x64_f32/kernix
create_zeros_64x64_f32/ndarray
create_zeros_64x64_f32/numpy
matmul_128_f64/candle
matmul_128_f64/faer
matmul_128_f64/kernix
matmul_128_f64/nalgebra
matmul_128_f64/ndarray
matmul_128_f64/numpy
matmul_32_f64/candle
matmul_32_f64/faer
matmul_32_f64/kernix
matmul_32_f64/nalgebra
matmul_32_f64/ndarray
matmul_32_f64/numpy
matmul_batched_4x16x32x16_f64/candle
matmul_batched_4x16x32x16_f64/kernix
matmul_batched_4x16x32x16_f64/numpy
matmul_sum_backward_32x16x8_f64/candle
matmul_sum_backward_32x16x8_f64/kernix
qr_256x64_f64/faer
qr_256x64_f64/kernix
qr_256x64_f64/nalgebra
qr_256x64_f64/numpy
qr_96x32_f64/faer
qr_96x32_f64/kernix
qr_96x32_f64/nalgebra
qr_96x32_f64/numpy
softmax_256x64_f64/candle
softmax_256x64_f64/kernix
softmax_256x64_f64/ndarray
softmax_256x64_f64/numpy
training_backward_2x4x8x4_f64/candle
training_backward_2x4x8x4_f64/kernix
training_forward_2x4x8x4_f64/candle
training_forward_2x4x8x4_f64/kernix
training_record_2x4x8x4_f64/candle
training_record_2x4x8x4_f64/kernix
training_sgd_2x4x8x4_f64/kernix

10^{-1} 10^{0} 10^{1} 10^{2}

Microseconds per call: median (dot), p95 (line endpoint)