

2025 Formula Bharat Rules Booklet

PART 1: INTRODUCTION

Formula Bharat is an exclusive student design competition which focuses on safety, good engineering practice, engineering design, education and creating opportunities for participating students.

Throughout this entire booklet, “Formula Bharat” shall be referred to as “FB”.

Formula Bharat is hosted by Curiosum Tech Private Limited.

PART 2: ADAPTATION TO FORMULA STUDENT RULES

The following rule book is an adaptation to the FS-Rules_2024_v1.1 rules booklet, published by Formula Student Germany. The purpose of the adaptation is to eliminate the requirement for a separate addendum for the Formula Bharat competition. Changes, inserts and modifications have been highlighted accordingly so that participating teams will be aware of those required for the Formula Bharat competition.

Teams who have participated at previous Formula Bharat competitions, are encouraged to thoroughly familiarize themselves with the new version as there have been several changes implemented by Formula Student Germany.

Please note that section DV dedicated to Driverless / Autonomous Vehicle (or Driverless Cup) has been eliminated from this adaptation as the category is not included at the Formula Bharat 2025 competition.

Any mention of a competition handbook may be referred to as the competition website.

Legend:

- Changes issued by FS2024 Rules (by FSG): **Text in blue**
- Updates by FB: **Text in green**
- Eliminations: Text crossed out

CONTENTS

CHANGELOG	10
ABBREVIATIONS	17
A ADMINISTRATIVE REGULATIONS	18
A1 COMPETITION OVERVIEW	18
A1.1 Competition Objective	18
A1.2 Competition Procedure	18
A1.3 Competition Information	18
A2 VEHICLE ELIGIBILITY	18
A2.1 Student Competition	18
A2.2 First Year Vehicles	19
A2.3 Second Year Vehicles	19
A3 RULES OF CONDUCT	20
A3.1 General Officials Authority	20
A3.2 Official Instructions	20
A3.3 Arguments with Officials	20
A3.4 Unsportsmanlike Conduct	20
A3.5 Violations of Intent	20
A3.6 Questions about the Rules	20
A3.7 Protests	21
A3.8 Penalties	21
A4 GENERAL REQUIREMENTS FOR TEAMS & PARTICIPANTS	21
A4.1 Teams per University	21
A4.2 Team Members	22
A4.3 Student Status	22
A4.4 Age	22
A4.5 Driver's License	22
A4.6 Insurance	23
A4.7 Liability Waiver	23
A4.8 [EV ONLY] Electrical System Officer (ESO)	23
A4.9 Faculty Advisor	23
A5 DOCUMENTATION & DEADLINES	24
A5.1 Required Documents and Forms	24
A5.2 Submission	24
A5.3 Penalties	24
A5.4 De-registration	27
A5.5 Photographic Submissions (PS)	27
A5.6 Vehicle Status Video (VSV)	27
A5.7 [Removed]	28
A5.8 Team Member Information (TMI)	28

A5.9 Participation Certificates	28
A5.10 Teams Categorization	29
A5.11 Negative Scoring	29
A6 GENERAL RULES	29
A6.1 Arrival and Removal of Vehicle from the Site	29
A6.2 Forfeit for Non-Appearance	29
A6.3 Team and Driver Briefings	30
A6.4 Testing and Work Safety	30
A6.5 Onsite Working Safety	30
A6.6 Alcohol and Illegal Material	31
A6.7 Vehicle Movement	31
A6.8 [CV ONLY] Engine Running	31
A6.9 Fueling and Oil	32
A6.10 [EV ONLY] Working on the Vehicle	32
A6.11 [EV ONLY] Working on the Tractive System	32
A6.12 [EV ONLY] Working on Tractive System Accumulators	33
A6.13 [EV ONLY] Charging	34
A6.14 Trash Cleanup	34
T GENERAL TECHNICAL REQUIREMENTS	35
T1 DEFINITIONS	35
T1.1 Chassis Definitions	35
T1.2 Material Definitions	37
T1.3 Electrical Definitions	37
T2 GENERAL DESIGN REQUIREMENTS	37
T2.1 Vehicle Configuration	37
T2.2 Ground Clearance	38
T2.3 Bodywork	38
T2.4 Suspension	39
T2.5 Wheels	39
T2.6 Tires	39
T2.7 Steering	39
T2.8 Wheelbase	40
T2.9 Track and Rollover Stability	40
T3 GENERAL CHASSIS DESIGN	40
T3.1 General Requirements	40
T3.2 Minimum Material Requirements	41
T3.3 Alternative Materials	42
T3.4 Composite Structures	42
T3.5 Laminate Testing	43
T3.6 Structural Documentation	44
T3.7 Roll Hoops	44
T3.8 Main Hoop	45
T3.9 Front Hoop	45

T3.10 Main Hoop Bracing	46
T3.11 Front Hoop Bracing	46
T3.12 Mechanically Attached Roll Hoop Bracing	47
T3.13 Front Bulkhead	48
T3.14 Front Bulkhead Support	48
T3.15 Impact Structures	49
T3.16 Bolted Primary Structure Attachments	50
T3.17 Impact Attenuator (IA)	51
T3.18 Impact Attenuator Data Requirement	52
T3.19 Impact Attenuator Test Requirements	52
T3.20 Non-Crushable Objects	53
T4 COCKPIT	53
T4.1 Cockpit Opening	53
T4.2 Cockpit Internal Cross Section	53
T4.3 Percy (95th percentile male)	54
T4.4 Side Tubes	55
T4.5 Driver's Harness Attachment	56
T4.6 Driver's Seat	56
T4.7 Floor Closeout	57
T4.8 Firewall	57
T4.9 Accessibility of Controls	58
T4.10 Driver Visibility	58
T4.11 Driver Egress	58
T5 DRIVER RESTRAINT SYSTEM	58
T5.1 Definitions	58
T5.2 Belts - General	58
T5.3 Belt, Strap and Harness Installation - General	59
T5.4 Lap Belt Mounting	59
T5.5 Shoulder Harness	60
T5.6 Anti-Submarine Belt Mounting	60
T5.7 Head Restraint	61
T5.8 Roll Bar Padding	61
T5.9 Driver's Leg Protection	61
T6 BRAKE SYSTEM	61
T6.1 Brake System - General	61
T6.2 Brake Over-Travel Switch (BOTS)	62
T6.3 Brake Light	62
T7 POWERTRAIN	63
T7.1 Transmission and Drive	63
T7.2 Coolant Fluid and System Sealing	63
T7.3 Drive Train Shields and Guards	63
T8 AERODYNAMIC DEVICES	64
T8.1 Definition Aerodynamic Device	64

T8.2 Restrictions for Aerodynamic Devices	65
T8.3 Minimum Edge Radii of Bodywork and Aerodynamic Devices	66
T8.4 Aerodynamic Devices Stability and Strength	66
T9 COMPRESSED GAS SYSTEMS AND HIGH PRESSURE HYDRAULICS	66
T9.1 Compressed Gas Cylinders and Lines	66
T9.2 High Pressure Hydraulic Pumps and Lines	67
T10 FASTENERS	67
T10.1 Critical Fasteners	67
T10.2 Securing Fasteners	67
T10.3 Self-made Fasteners	68
T11 ELECTRICAL COMPONENTS	68
T11.1 Low Voltage System (LVS)	68
T11.2 Master Switches	68
T11.3 Low Voltage Master Switch (LVMS)	69
T11.4 Shutdown Buttons	69
T11.5 Inertia Switch	70
T11.6 Brake System Plausibility Device (BSPD)	70
T11.7 LV Batteries	71
T11.8 Accelerator Pedal Position Sensor (APPS)	71
T11.9 System Critical Signals (SCSs)	72
T11.10 Sensors, Cameras & Electrical Components Mounting	73
T12 VEHICLE IDENTIFICATION	74
T12.1 Vehicle Number	74
T12.2 University Name	74
T12.3 Timing Equipment	74
T13 VEHICLE AND DRIVER EQUIPMENT	74
T13.1 Pushbar	74
T13.2 Jacks	75
T13.3 Driver Equipment	75
T13.4 Fire Extinguishers	77
T13.5 Camera Mounts	77
CV INTERNAL COMBUSTION ENGINE VEHICLES	78
CV1 INTERNAL COMBUSTION ENGINE POWERTRAINS	78
CV1.1 Engine Limitation	78
CV1.2 Starter	78
CV1.3 Air Intake System	78
CV1.4 Throttle	78
CV1.5 Mechanical Throttle Actuation	79
CV1.6 Electronic Throttle Control (ETC)	79
CV1.7 Intake System Restrictor	80
CV1.8 Turbochargers and Superchargers	80
CV1.9 Crankcase / Engine Lubrication Venting	80
CV2 FUEL AND FUEL SYSTEM	81

CV2.1 Fuel	81
CV2.2 Fuel System Location Requirements	81
CV2.3 Fuel Tanks	82
CV2.4 Fuel Lines for Low Pressure Systems	82
CV2.5 Fuel Injection System Requirements	83
CV2.6 Fuel Tank Filler Neck and Sight Tube	83
CV2.7 Tank Filling Requirement	84
CV2.8 Venting Systems	84
CV3 EXHAUST SYSTEM AND NOISE CONTROL	85
CV3.1 Exhaust System General	85
CV3.2 Maximum Sound Level	85
CV4 SHUTDOWN SYSTEM	85
CV4.1 Shutdown Circuit	85
EV ELECTRIC VEHICLES	87
EV1 DEFINITIONS	87
EV1.1 Tractive System (TS)	87
EV1.2 Galvanic Isolation	87
EV2 ELECTRIC POWERTRAIN	87
EV2.1 Motors	87
EV2.2 Power Limitation	87
EV3 GENERAL REQUIREMENTS	87
EV3.1 Grounding	87
EV3.2 Overcurrent Protection	88
EV4 TRACTIVE SYSTEM (TS)	89
EV4.1 General Requirements	89
EV4.2 TS System Enclosures	89
EV4.3 Separation of Traction System and Grounded Low Voltage System	89
EV4.4 Positioning of Tractive System Parts	90
EV4.5 Tractive System Insulation, Wiring and Conduit	90
EV4.6 Data Logger	92
EV4.7 Tractive System Measuring point (TSMP)	92
EV4.8 High Voltage Disconnect (HVD)	93
EV4.9 Discharge Circuit	93
EV4.10 Tractive System Active Light (TSAL)	93
EV4.11 Activating the Tractive System	95
EV4.12 Ready-To-Drive Sound	95
EV5 TRACTIVE SYSTEM ENERGY STORAGE	95
EV5.1 Definitions	95
EV5.2 Allowed Tractive System Accumulators	96
EV5.3 Tractive System Energy Storage – General Requirements	96
EV5.4 Tractive System Energy Storage – Electrical Configuration	96
EV5.5 Tractive System Energy Storage – Mechanical Configuration	97
EV5.6 Accumulator Isolation Relays (AIRs)	99

EV5.7 Pre-Charge Circuit	99
EV5.8 Accumulator Management System (AMS)	99
EV6 SHUTDOWN CIRCUIT AND SYSTEMS	100
EV6.1 Shutdown Circuit	100
EV6.2 Tractive System Master Switch (TSMS)	102
EV6.3 Insulation Monitoring Device (IMD)	102
EV7 CHARGERS	103
EV7.1 Chargers General Requirements	103
EV7.2 Charging Shutdown Circuit	103
EV8 TS ACCUMULATOR CONTAINER HAND CART	104
EV8.1 TS Accumulator Container Hand Cart	104
EV9 ELECTRICAL SYSTEM FORM (ESF) and FAILURE MODES AND EFFECTS ANALYSIS (FMEA)	104
EV9.1 [EV ONLY] Electrical System Form (ESF)	104
EV9.2 [EV ONLY] Failure Modes and Effects Analysis (FMEA)	104
EV9.3 [EV ONLY] Accumulator Pre-Tech Inspection (ACC-PT)	105
IN TECHNICAL INSPECTIONS	105
IN1 GENERAL	105
IN1.1 Technical Inspection Process	105
IN1.2 General Rules	105
IN1.3 Technical Inspection Sticker	106
IN1.4 Inspection Responsible Person	106
IN1.5 Modifications and Repairs	107
IN2 PRE-INSPECTION	107
IN2.1 Pre-Inspection Required Items	107
IN3 [EV ONLY] ACCUMULATOR INSPECTION	108
IN3.1 Accumulator Inspection General Definitions	108
IN3.2 Accumulator Inspection Required Items	108
IN4 [EV ONLY] ELECTRICAL INSPECTION	109
IN4.1 Electrical Inspection General Definitions	109
IN4.2 Electrical Inspection Required Items	109
IN5 MECHANICAL INSPECTION	109
IN5.1 Mechanical Inspection Required Items	109
IN6 [DV ONLY] DRIVERLESS INSPECTION	110
IN7 TILT TEST	110
IN7.1 Tilt Test Procedure	110
IN8 VEHICLE WEIGHING	110
IN8.1 Vehicle Weighing Procedure	110
IN9 [EV ONLY] RAIN TEST	110
IN9.1 Rain Test General Definitions	110
IN9.2 Rain Test Procedure	110
IN10 [CV ONLY] NOISE TEST	111
IN10.1 Noise Test Procedure	111

IN11 BRAKE TEST	111
IN11.1 Brake Test Procedure	111
IN12 POST EVENT INSPECTION	112
IN12.1 Post Event Inspection Procedure	112
S STATIC EVENTS	114
S1 BUSINESS PLAN PRESENTATION EVENT (BPP)	114
S1.1 Business Plan Presentation Objective	114
S1.2 Business Plan Procedure	114
S1.3 Pitch Video (BPPV)	114
S1.4 Deep Dive Topic	115
S1.5 Presentation Prelims	115
S1.6 Business Plan Presentation Finals	115
S1.7 Business Plan Presentation Scoring	115
S2 COST AND MANUFACTURING EVENT	116
S2.1 Cost and Manufacturing Objective	116
S2.2 Cost and Manufacturing Procedure	116
S2.3 Cost Report Documents (CRD)	117
S2.4 Bill of Material (BOM)	117
S2.5 Detailed Bill of Material (DBOM)	118
S2.6 Costed Bill of Material (CBOM)	119
S2.7 Supporting Material File	119
S2.8 Cost Explanation File	119
S2.9 Cost and Manufacturing Vehicle Condition	120
S2.10 Cost and Manufacturing Scoring	120
S3 ENGINEERING DESIGN EVENT	121
S3.1 Engineering Design Objective	121
S3.2 Concept-Resources-Management Report (CRMR)	121
S3.3 Design Spec Sheet (DSS)	121
S3.4 Engineering Design Presentation (EDP)	121
S3.5 Engineering Design Event Procedure	122
S3.6 Engineering Design Vehicle Condition	122
S3.7 Engineering Design Judging Criteria	123
S3.8 Engineering Design Scoring	123
D DYNAMIC EVENT REGULATIONS	124
D1 DYNAMIC EVENTS GENERAL	124
D1.1 Driver Limitations	124
D1.2 Dynamic Area and Dynamic Vests	124
D2 DRIVING RULES	124
D2.1 Flags	124
D2.2 Driving Under Power	125
D2.3 Ground Clearance	125
D2.4 Practice Track	125
D3 WEATHER CONDITIONS	126

D3.1 Operating Conditions	126
D3.2 Tires Allowed	126
D4 SKIDPAD EVENT	126
D4.1 Skidpad Track Layout	126
D4.2 Skidpad Procedure	127
D4.4 Skidpad Scoring	128
D5 ACCELERATION EVENT	128
D5.1 Acceleration Track Layout	128
D5.2 Acceleration Procedure	128
D5.4 Acceleration Scoring	128
D6 AUTOCROSS EVENT	129
D6.1 Autocross Track Layout	129
D6.2 Autocross Procedure	129
D6.3 Autocross Scoring	129
D7 ENDURANCE AND EFFICIENCY EVENT	130
D7.1 Endurance Track Layout	130
D7.2 Endurance Procedure	130
D7.3 Endurance Running Order	131
D7.4 Passing	131
D7.5 Endurance Driver Change Procedure	131
D7.6 Endurance Event Tire Changes	132
D7.7 Endurance Specific Regulations	133
D7.8 Endurance Scoring	133
D7.9 Efficiency Scoring	133
D8 [DV ONLY] TRACKDRIVE AND EFFICIENCY EVENT	134
D9 DYNAMIC EVENTS PENALTIES	134
D9.1 General Penalties	134
D9.2 Endurance Penalties	135
D9.3 [CV ONLY] Efficiency Penalties	136
D9.4 [EV ONLY] Power and Voltage Violation Penalties	136

CHANGELOG

Rule	Ver	By	Change
A3.8.1	2024 1.1	FSG	Defined minimum penalty for rules violation
A4.1.3	2021 1.0	FB	Inform organizers if members are from 2 or more institutions.
A4.1.4	2021 1.0	FB	Clarification for teams from multiple colleges, under the same University.
A4.2.2	2021 1.0	FB	Current status of team captain
A4.2.4	2024 1.0	FB	Inclusion of communication liaisons at registration
A4.2.5	2024 1.0	FB	Communication protocol for change in leadership
A4.3.1	2021 1.0	FB	Increased graduation period to eleven months.
A4.3.2	2021 1.0	FB	Included mention of degree program
A4.3.4	2025 1.0	FB	Requirement for Student Membership with MFB
A4.4.1	2021 1.0	FB	Modified the minimum age to 16 years.
A4.5.2	2021 1.0	FB	Hardcopy of driver license required and driver's bond to be paid at event site
A4.6.1	2022 1.0	FB	Included Faculty Advisors and Volunteers.
A4.7.1	2021 1.0	FB	Included Faculty Advisors and Volunteers. Removed on-site mention.
A4.7.2	2021 1.0	FB	Mentioned Under 18 Liability waiver.
A4.8.1	2025 1.0	FB	Revised requirement of ESOs for the competition.
A4.8.8	2024 1.1	FSG	Replaced reference to HV by TS
A4.8.8	2024 1.0	FB	Mention of training requirements other than those mentioned on the competition website.
A4.8.9	2025 1.0	FB	Clarifies minimum training level requirement for ESO.
A4.8.10	2024 1.0	FB	Recommended training for all team members.
A4.9	2021 1.0	FB	Included requirement for Faculty Advisor.
A5.1.1	2025 1.0	FB	Removed PS & ACC-PT & VSV
A5.1.1	2025 1.1	FB	Re-introduced Photo Submission
A5.2.5	2025 1.0	FB	Addition of De-registration rule incase of forged / incorrect submissions
A5.3	2022 1.0	FB	Renamed to Penalties. Reworded the entire section.
A5.3	2025 1.0	FB	Removed PS & ACC-PT
A5.3	2025 1.1	FB	Re-introduced Photo Submission
A5.3.1	2025 1.0	FB	Extended Note 3
A5.3.1	2025 1.0	FB	Removed ACC-PT and PS. Added VSV. Split ESF into ESF-1 and ESF-2. Split CRD penalties into BOM, CEXP and CSUP.
A5.3.1	2025 1.1	FB	Re-introduced Photo Submission
A5.3.2	2024 1.0	FB	Addition of number of maximum correction requests until approval Inclusion of column in table
A5.3.2	2025 1.0	FB	Removal of number of maximum correction requests

Rule	Ver	By	Change
A5.3.2	2025 1.0	FB	Removed ACC-PT and PS. Added VSV. Split ESF into ESF-1 and ESF-2. Split CRD penalties into BOM, CEXP and CSUP.
A5.3.2	2025 1.1	FB	Re-introduced Photo Submission
A5.3.2	2025 1.0	FB	Note 3 changed to include penalty for consistent neglect of requested changes
A5.3.2	2025 1.0	FB	Removed Note 4 & 5 pertaining to ACC-PT & PS document revisions and document approval
A5.3.2	2025 1.0	FB	Added Note 4 pertaining to PS document revisions and document approval
A5.3.3	2024 2.0	FB	Penalty listed for incorrect file naming.
A5.3.3	2025 1.0	FB	Penalty listed for missed slot booking for virtual judging session.
A5.3.4	2024 1.0	FB	Further rule on the approval of certain documents
A5.4.1	2024 1.0	FB	Clarification on appeal process for team's de-registration for specific event
A5.5	2025 1.0	FB	Removed section on Photo Submission
A5.5	2025 1.1	FB	Re-introduced Photo Submission
A5.6	2025 1.0	FB	Included Vehicle Status Video (VSV)
A5.7	2021 1.0	FB	Removed SES Approval from third party. SES for monocoque chassis must be submitted directly to competition officials as per deadline.
A5.8	2021 1.0	FB	Included section on Team Member Information.
A5.8.1	2024 1.0	FB	Clarified TMI can also include names of members who cannot attend on-site competition
A5.8.1	2025 1.0	FB	Mentioned requirement for student membership.
A5.8.5	2025 1.0	FB	Removed mention of complimentary members.
A5.8.6	2025 1.0	FB	Increased maximum participating team members to 60
A5.9	2021 1.0	FB	Included section on Participation Certificates
A5.9	2024 1.0	FB	Removed on-site participation requirement for certificate provision
A5.10	2021 1.0	FB	Included section on Teams Categorization.
A5.10	2025 1.0	FB	Removed PS and ACC-PT. Added VSV for team categorization.
A5.10	2025 1.1	FB	Re-introduced PS along with other requirements for team categorization.
A5.11	2021 1.0	FB	Included section on Negative Scoring.
A6.1	2024 1.0	FB	Inclusion of rules pertaining to arrival of vehicles on site as well
A6.3.1	2024 1.0	FB	Clarified team captains' briefings
A6.3.2	2021 1.0	FB	Included note about drivers missing opportunity to participate
A6.4.7	2021 1.0	FB	Included note on questionable content posted on social media
A6.5.5	2024 1.0	FB	Clarified rule for mobility devices with exception of those used for medical disability
A6.5.6	2024 1.0	FB	Retained rule for prohibition of motorized devices on competition site
A6.7.3	2024 1.1	FSG	Removed
A6.7.5	2023 1.3	FB	Removal of helmet as exception. Clarified.
A6.7.7	2024 1.1	FSG	Clarified rule, mentioned front wing instead of vehicle
A6.8.3	2021 1.0	FB	Cranking engines in pits is not allowed.
A6.10	2024 1.1	FSG	Added rules for working on an EV

Rule	Ver	By	Change
A6.10.7	2024 1.0	FB	Insertion of rule clarifying ON status of TS within pits
A6.11.10	2024 1.0	FB	Designated areas for storage of TSAC and spare cells
A6.11.11	2024 1.0	FB	Designated areas for storage of TSAC after competition hours
A6.13	2024 1.0	FB	Inserted section for trash cleanup on-site
T1.1.2	2024 1.1	FSG	Added definition of bodywork
T1.1.12	2024 1.1	FSG	Harmonized impact structures under respective rule
T1.1.16	2024 1.1	FSG	Updated definition of rollover protection envelope
T1.1.18	2024 1.1	FSG	Updated definition of surface envelope
T2.2.1	2024 1.1	FSG	Added restriction for active suspension
T2.3.2	2024 1.1	FSG	Added rule about the shape of the bodywork
T2.3.4	2024 1.1	FSG	Clarified rule
T2.5.2	2024 1.1	FSG	Clarified rule, addition of drive pegs
T2.6.5	2021 1.0	FB	Clarification of usage of dry and wet tires.
T2.6.6	2021 1.0	FB	Clarification of usage of dry and wet tires.
T2.7.9	2024 1.1	FSG	Prescribed position of steering rack
T3.2.1	2024 1.1	FSG	Changed value to resolve historical discrepancy with SES and updated
T3.4.4	2024 1.1	FSG	Added thickness restriction for asymmetrical lay-ups
T3.5.4	2024 1.1	FSG	Added rule to define not quasi-isotropic laminate direction and alignment
T3.6	2021 1.0	FB	Removed requirement for SE3D submission.
T3.15.2	2024 1.1	FSG	Added rule to remove inconsistencies between side and other impact structures
T3.15.3	2024 1.1	FSG	Added minimum absorbed energy requirement for two baseline steel tubes and updated rule to remove inconsistencies between side and other impact structures
T3.17.1	2024 1.1	FSG	Clarified rule
T3.17.3	2024 1.1	FSG	Clarified rule
T3.17.5	2024 1.1	FSG	Redefined IA attachment requirements
T3.17.7	2024 1.1	FSG	Added minimum adhesive strength requirement for "standard" honeycomb IA
T3.17.7	2025 1.2	FB	Removed "honeycomb", applicable for all standard IA and mentioned T3.2.8
T3.19.1	2024 1.1	FSG	Clarified allowance of testing mass and enforcement rule
T3.19.4	2024 1.1	FSG	Added physical testing requirement for non-crushable object(s) located in direct front view of the AIP
T3.19.7	2021 1.0	FB	Rule for de-registration of team conducting IA test on manned student vehicle
T3.19.7	2024 1.0	FB	Clarification for de-registration from competition.
T4.8.7	2024 1.1	FSG	Require sold layer
T5.2.2	2024 1.0	FB	Allowance for extension of 2nd year harness
T5.5.3	2024 1.1	FSG	Clarified rule by separation of bar and bracing
T6.1.9	2024 1.1	FSG	Clarified positioning of the brake system
T6.1.11	2024 1.1	FSG	Clarified that brake pedal includes the pedal face
T6.2.3	2024 1.1	FSG	Changed requirements for BOTS
T6.3.2	2025 1.0	FB	Changed wording and context from 'may' to 'must'.

Rule	Ver	By	Change
T7.2.3	2024 1.1	FSG	Clarified wording for heat resistant cover plate positioning
T7.2.7	2024 1.1	FSG	Clarified engine and motor(s) cooling specification
T8.3.1	2024 1.1	FSG	Unified minimum radius for aerodynamic devices and bodywork
T9.1.1	2024 1.1	FSG	Added exception for gas springs
T10.1.5	2024 1.1	FSG	Added new rule about fasteners
T10.3	2021 1.0	FB	Included section on Self-made Fasteners
T11.2	2021 1.0	FB	Included mention of car number on master switch handle
T11.4.7	2024 1.1	FSG	Added rule that shutdown buttons must be red
T11.5.4	2024 1.1	FSG	Clarified wording for inertia switch mounting
T11.5.5	2021 1.0	FB	Inertia switch should be directly acting. External relay circuits are prohibited.
T11.7.4	2025 1.0	FB	Further requirements added for EV
T11.8.5	2024 1.1	FSG	Changed requirements for APPS
T11.9.3	2024 1.1	FSG	Moved SCS wording to a separate rule
T11.10	2024 1.1	FSG	Unified wording for electrical component mounting. Addition of "camera"
T12.1.1	2025 1.0	FB	Mention of prefix prior to numerical values in vehicle number
T12.1.2	2025 1.0	FB	Vehicle number on vehicle must include prefix
T12.2.1	2021 1.0	FB	Included mention of college name, if A 4.1.4 applies
T13.2.2	2024 1.1	FSG	Changed wording for positioning the jacks
T13.2.3	2024 1.1	FSG	Changed size of jacks
T13.3.2	2024 1.1	FSG	Removed the standards that expire after 31.12.2023
T13.3.3	2024 1.1	FSG	Added frontal head restraint system standards
T13.3.10	2024 1.1	FSG	Added validity of fire resistant clothing
T13.3.12	2024 1.1	FSG	Clarified embroidered driver's clothing
T13.3.13	2024 1.1	FSG	Updated fire resistant material usage in driver's clothing
T13.4.1	2021 1.0	FB	Included allowance of dry chemical / powder ABC extinguishers in India
T13.5	2021 1.0	FB	Camera Mounts rule retained
CV1.3.2	2024 1.1	FSG	Harmonized impact structures
CV1.7.2	2021 1.0	FB	Removed E 85 fueled vehicle
CV2.1.1	2021 1.0	FB	91 Octane as available gasoline only.
CV2.2	2024 1.1	FSG	Removed redundant rule about fuel system parts below the chassis (already defined by EV4.4.1)
CV2.3.5	2021 1.0	FB	Drain hole / valve requirement detailed.
CV2.4.1	2024 1.1	FSG	Added temperature rating for fuel lines
CV2.4.2	2024 1.1	FSG	Clarified rule
CV2.8.3	2025 1.0	FB	Clarified detail on the use of check-valve
EV1.2.1	2024 1.1	FSG	Clarified test voltage, added working voltage requirement.
EV1.2.1	2024 1.1	FSG	Require working voltage only if given in the datasheet
EV2.1.3	2021 1.1	FB	Corrected reference to rule T7.3.4.
EV2.3	2024 1.1	FSG	Removed APPS/ brake pedal plausibility check

Rule	Ver	By	Change
EV3.1.1	2024 1.1	FSG	Require solid layer
EV3.1.2	2024 1.1	FSG	Added LVS ground measuring point
EV3.2.5	2024 1.1	FSG	Relaxed overcurrent protection of motors
EV4.3.6	2024 1.1	FSG	Removed PCB spacing exception for integrated circuits
EV4.4	2024 1.1	FSG	Removed redundant rule about TS parts below the chassis (already defined by EV4.4.1)
EV4.4.2	2024 1.1	FSG	Harmonized impact structures, clarified T3.16 reference and added exception for outboard wheel motors
EV4.4.2	2025 1.0	FB	Further clarification provided on TSAC height above impact structure
EV4.5.2	2024 1.1	FSG	Moved requirement to a different rule
EV4.5.3	2024 1.1	FSG	Added requirement from a different rule
EV4.5.12	2025 1.0	FB	Screw type connectors not allowed in TSAC
EV4.5.12	2025 1.3	FB	Update regarding usage of screw type connectors in TSAC
EV4.5.13	2024 1.1	FSG	Relaxed rule
EV4.5.14	2024 1.1	FSG	Clarified rule
EV4.7.5	2024 1.1	FSG	Clarified rule
EV4.7.7	2024 1.1	FSG	Linked bolted and soldered connections to the high current path requirements
EV4.8.1	2024 1.1	FSG	Relaxed rule
EV4.8.2	2024 1.1	FSG	Relaxed rule
EV4.9.4	2025 1.0	FB	No part of the discharge circuit must be inside the TSAC.
EV4.10.3	2025 1.4	FB	Corrected the value to 50 VAC RMS
EV4.10.8	2024 1.1	FSG	Defined angle per side
EV4.10.12	2025 1.0	FB	Updated rule
EV4.10.13	2025 1.0	FB	Updated rule
EV4.10.14	2025 1.0	FB	Updated rule
EV4.10.14	2025 1.4	FB	Incorrect rule number was mentioned, updated it to EV4.10.13
EV4.12.1	2024 1.1	FSG	Clarified rule
EV5.4.3	2024 1.1	FSG	Limited to TSAL's green light
EV5.4.5	2025 1.0	FB	Additional clarification provided
EV5.4.10	2024 1.1	FSG	Defined voltage indicator supply
EV5.5	2024 1.1	FSG	Removed redundant rule on joining walls and floor
EV5.5.1	2024 1.1	FSG	Harmonized impact structures
EV5.5.2	2024 1.1	FSG	Harmonized impact structures, clarified T3.16 reference
EV5.5.3	2024 1.1	FSG	Require 60 degree C for calculations
EV5.5.3	2025 1.0	FB	Further clarification of entire TSAC
EV5.5.10	2024 1.1	FSG	Relaxed rule, loading $\geq$ 80% of one large surface is sufficient
EV5.5.11	2024 1.1	FSG	Require testing of friction-based cell mounting
EV5.5.13	2025 1.3	FB	Interchanged order with EV5.5.14
EV5.5.14	2025 1.3	FB	Interchanges order with EV5.5.13

Rule	Ver	By	Change
EV5.5.15	2024 1.1	FSG	Defined max total cutout area
EV5.5.16	2024 1.1	FSG	Mentioned as a separate rule along with the point for cooling ducts and their mountings
EV5.6.3	2024 1.1	FSG	Shortened rule without changing the rule
EV5.6.4	2024 1.1	FSG	Removed redundant rule about fuse rating
EV5.7.1	2024 1.1	FSG	Changed to voltage at the vehicle side of the AIRs
EV5.8.4	2024 1.1	FSG	Clarified rule
EV5.8.4	2025 1.0	FB	Further clarification provided
EV5.8.12	2024 1.1	FSG	Require a single overview showing all values
EV6.1.5	2024 1.0	FB	Clarified rule
EV6.3.2	2024 1.1	FSG	Added Bender ISOMETER® iso165C-1, Bender A-ISOMETER® iso-F1 IR155-4203 and -4204
EV7.1.10	2024 1.1	FSG	Added charger labeling
EV7.2.1	2025 1.0	FB	Added direction for the shutdown button on the hand cart
EV8.1.6	2024 1.1	FSG	Detailed handcart firewall specification
EV8.1.8	2024 1.1	FSG	Added rule that hand cart must be larger than TSAC
EV8.1.10	2024 1.1	FSG	Require dedicated label on hand cart
EV8.1.10	2025 1.0	FB	Added direction for the label on the hand cart
EV9.1.1	2024 1.0	FB	ESF Parts removed
EV9.2	2021 1.0	FB	Included section for FMEA
EV9.3	2025 1.0	FB	Removed ACC-PT section
IN1.1.1	2024 1.0	FB	Vehicle weighing is optional
IN1.1.2	2024 1.0	FB	Included order of technical inspection
IN1.5.1	2024 1.1	FSG	Allowed installation and removal of protective sensor covers
IN3.1.5	2025 1.0	FB	Removed
IN4.1.3	2024 1.1	FSG	Move and rephrase BSPD test
IN5.1.1	2024 1.1	FSG	Require that test piece and test fixture must be presented at mechanical inspection
IN12.1.3	2024 1.1	FSG	Clarified rule
S1	2023 1.0	FB	Significant change throughout BPP section
S1.1.1	2024 1.1	FSG	Clarified rule
S1.1.3	2024 1.1	FSG	Removed redundant information
S1.5.1	2025 1.0	FB	Requirement for live video feed during the virtual session.
S1.7	2023 4.0	FB	Revised Business Plan Presentation Scoring
S2.2	2025 1.0	FB	Clarified Cost and Manufacturing Event Procedure
S2.2.3	2025 1.0	FB	Modified to include on-site participation requirements
S2.2.4	2023 1.4	FB	Correction of 'two' parts to 'three' parts.
S2.2.8	2025 1.0	FB	Clubbed with S2.2.3
S2.3	2021 1.0	FB	Reference to www.formulastudent.de

Rule	Ver	By	Change
S2.3.4	2021 1.0	FB	Compulsory required for hardcopy CRD set at the event.
S2.4.4	2024 1.1	FSG	Moved "fastener" definition to BOM and clarified they should not be listed
S2.4.5	2024 1.1	FSG	Self made fastener clarification
S2.10.4	2023 1.0	FB	Change of multiplier to 85.
S3	2023 1.0	FB	Significant change throughout ED section
S3.1.3	2025 1.0	FB	Removed CRM round. Reduced to design prelims, followed by finals.
S3.2	2025 1.0	FB	Removed CRM judging event related content.
S3.5.2	2025 1.0	FB	Modified CRM event judging criteria
S3.5.6	2024 1.1	FSG	Changed condition of spare cells
S3.5.6	2024 1.1	FSG	S3.5.6 to be applicable for Engineering Design Finals.
S3.6.1	2025 1.0	FB	Modified vehicle required condition for engineering design prelims.
S3.8	2025 1.0	FB	Updated ED scoring
D1.1.1	2024 1.0	FB	Retained original number of drivers permitted.
D2.3.2	2021 1.0	FB	Ground clearance may be tested at any time.
D4.2.1	2025 1.0	FB	Retained original driving procedure.
D4.4	2024 1.1	FSG	Changed scoring formula to refer to table 3 for maximum number of points
D5.1.1	2024 1.1	FSG	Removed restriction that cones are not marked
D5.2.1	2025 1.0	FB	Retained original driving procedure.
D5.4	2024 1.1	FSG	Changed scoring formula to refer to table 3 for maximum number of points
D6.3	2024 1.1	FSG	Changed scoring formula to refer to table 3 for maximum number of points
D7.6.6	2024 1.1	FSG	Clarified tire change after puncture
D7.7.4	2024 1.1	FSG	Clarified rule
D7.8.4	2023 1.0	FB	Changed Tmax multiplier for both categories.
D7.8	2024 1.1	FSG	Changed scoring formula to refer to table 3 for maximum number of points
D7.9	2024 1.1	FSG	Changed scoring formula to refer to table 3 for maximum number of points
D9.2.4	2024 1.1	FSG	Added definition of being too slow
D9.2.6	2024 1.1	FSG	Added new rule about penalties
D9.4.2	2024 1.1	FSG	Clarified that DQ(s) apply to fastest <i>valid</i> run(s)

ABBREVIATIONS

AIP	Anti Intrusion Plate	IMD	Insulation Monitoring Device
AIR	Accumulator Isolation Relay	LPI	Low Pressure Injection
AMS	Accumulator Management System	LV	Low Voltage
APPS	Accelerator Pedal Position Sensor	LVMS	Low Voltage Master Switch
BOM	Bill of Material	LVS	Low Voltage System
BOTS	Brake Over-Travel Switch	OC	Off-course
BPP	Business Plan Presentation Event	OEM	Original Equipment Manufacturer
BPPV	Business Plan Pitch Video	PCB	Printed Circuit Board
BSE	Brake System Encoder	PS	Photographic Submissions
BSPD	Brake System Plausibility Device	R2D	Ready-to-drive
CBOM	Costed Bill of Material	RES	Remote Emergency System
CRMR	Concept-Resources-Management Report	RMS	Root Mean Square
CRD	Cost Report Documents	SCS	System Critical Signal
CV	Internal Combustion Engine Vehicle	SDC	Shutdown Circuit
DBOM	Detailed Bill of Material	SE3D	Structural Equivalency 3D Model
DI	Direct Injection	SES	Structural Equivalency Spreadsheet
DNA	Did Not Attempt	SVCR	Second Year Vehicle Compliance Report
DNF	Did Not Finish	TMI	Team Member Information
DOO	Down or Out	TPS	Throttle Position Sensor
DQ	Disqualified	TS	Tractive System
DSS	Design Spec Sheet	TSAC	Tractive System Accumulator Container
DV	Driverless Vehicle	TSAL	Tractive System Active Light
EAIR	ESF Add Item Request	TSMP	Tractive System Measuring point
EBS	Emergency Brake System	TSMS	Tractive System Master Switch
ECU	Electronic Control Unit	USS	Unsafe Stop
EDP	Engineering Design Presentation	VSV	Vehicle Status Video
EI	Flexural Rigidity		
ESF	Electrical System Form		
ESO	Electrical System Officer		
ESOQ	Electrical System Officer Qualification		
ETC	Electronic Throttle Control		
EV	Electric Vehicle		
HPI	High Pressure Injection		
HV	High Voltage		
HVD	High Voltage Disconnect		
IA	Impact Attenuator		
IAD	Impact Attenuator Data		

A ADMINISTRATIVE REGULATIONS

A1 COMPETITION OVERVIEW

A1.1 Competition Objective

A1.1.1 The competition challenges teams of university students to conceive, design, fabricate, develop and compete with small, formula style, race cars.

A1.2 Competition Procedure

A1.2.1 The competition is split into the following categories:

- Internal Combustion Engine Vehicle (CV)
- Electric Vehicle (EV)

A1.2.2 All vehicles must meet the requirements defined in chapters T and either EV or CV, depending on their drivetrain type.

A1.2.3 The competition starts with a series of technical inspections described in chapter IN to check the vehicle for safety and compliance with the rules.

A1.2.4 The competition is divided into a series of static and dynamic events described in chapters S and D.

A1.2.5 Maximum points are awarded as described in Table 3.

A1.2.6 The team with the most overall points will win the competition for its category.

A1.3 Competition Information

A1.3.1 The competition specific rules and information are defined [on the competition website](#).

A1.3.2 The official language of the competition is English.

A1.3.3 Every organizer of a competition based on this document bears the sole responsibility.

A2 VEHICLE ELIGIBILITY

A2.1 Student Competition

- A2.1.1 Vehicles entered into the competition must be conceived, designed and maintained by the student team members without direct involvement from external professional engineers, racers, machinists or related professionals.

CV & EV	
Static Events:	
Business Plan Presentation	75 Points
Cost & Manufacturing	100 Points
Engineering Design	150 Points
Dynamic Events:	
Skid Pad	75 Points
Acceleration	75 Points
Autocross	100 Points
Endurance	325 Points
Efficiency	100 Points
Overall	1000 Points

Table 3: Maximum points awarded

- A2.1.2 The student team may use any information from professionals or from academics as long as the information is given as a discussion of alternatives with their pros and cons.
- A2.1.3 Professionals may not make design decisions or drawings.
- A2.1.4 Students should perform fabrication tasks wherever possible.

A2.2 First Year Vehicles

- A2.2.1 A vehicle may only be used for one year, counting from the first day onsite of its first competition.
- A2.2.2 To be classified as new, a vehicle must have, at minimum, a newly manufactured chassis with significant changes in the primary structure to its predecessor.
- A2.2.3 If there is any question about whether or not the car is in fact a first year vehicle, it will be the sole responsibility of the team to produce such evidence as the organizers or judges may require.

A2.3 Second Year Vehicles

- A2.3.1 This rule is only applicable to teams participating in the Electric Category at Formula Bharat. The second year vehicle must be modified (if required) to comply with the rule book of that competition year.

A2.3.2 There will be no penalties applied for participating as a second year vehicle.

Note: For the FB2025 competition, first year vehicles that participated at FB2024 will be considered as a second year vehicle.

A2.3.3 Teams participating with a second year vehicle are required to submit a Second Year Vehicle Compliance Report (SVCR). The report must contain proof that the competition vehicle is not older than one year. Information presented must include details of the previous competitions attended by competition vehicle, details of the previous competition vehicle as in predecessor (if any), photographic details to prove significant changes in chassis as between competition vehicle and predecessor, any approved technical inspection documents etc. The competition vehicle will only be approved as a second year vehicle once the SVCR is approved.

A2.3.4 This rule does not apply to teams participating in the Combustion Category.

A3 RULES OF CONDUCT

A3.1 General Officials Authority

A3.1.1 The officials reserve the right to revise the schedule of the competition and/or interpret or modify the competition rules at any time and in any manner that is, in their sole judgment, required for safe and efficient operation.

A3.1.2 All team members are required to cooperate with, and follow all instructions from the officials.

A3.1.3 Official announcements shall be considered part of these rules.

A3.1.4 All guidelines and clarifications posted on the competition website for the current season including any competition handbook are considered part of these rules.

A3.1.5 Questions concerning the meaning or intent of the rules will be resolved by the officials.

A3.2 Official Instructions

A3.2.1 Failure of a team member to follow an instruction or command directed specifically to that team or team member will result in 25 penalty points being deducted from the team's overall score.

A3.3 Arguments with Officials

A3.3.1 Argument with, or disobedience to, any official will result in the team being eliminated from the competition.

A3.4 Unsportsmanlike Conduct

A3.4.1 In the event of unsportsmanlike conduct, 25 penalty points will be deducted from the team's overall score. A second violation will result in expulsion of the team from the competition.

A3.5 Violations of Intent

- A3.5.1 Violation of the intent of a rule will be considered a violation of the rule itself.
- A3.5.2 Any parts, devices or software fragments designed with the intent to violate a rule, will be considered as a violation.

A3.6 Questions about the Rules

- A3.6.1 Questions about the rules may be asked to the officials.
- A3.6.2 The frequently asked questions (FAQ) section on the competition website must be checked before submitting a question.
- A3.6.3 The officials will only answer questions that are not already answered in the rules or FAQs or that require new or novel interpretation.
- A3.6.4 Refer to the competition website for specific directions on how to submit a rules question.

A3.7 Protests

A3.7.1 Preliminary Review– Required

If a team has a question about scoring, judging, policies or any official action it must be brought to the officials' attention within the announced protest period for an informal preliminary review before a protest can be filed.

A3.7.2 Cause for Protest

A team may protest any rule interpretation, score or official action which they feel has caused some actual, non-trivial, harm to their team, or has had a substantive effect on their score.

A3.7.3 Protest Format and Forfeit

All protests must be filed in writing and presented to the officials by the team captain. In order to have a protest considered, a team must post a 25 point protest bond which will be forfeited if their protest is rejected.

- A3.7.4 The decision of the officials regarding any protest will be in a written form and is final.

A3.8 Penalties

- A3.8.1 Rule violations result in at least 20 penalty points, unless explicitly defined otherwise. The penalty points will be deducted from the team's overall score.
- A3.8.2 Overall penalties apply to CV and EV ~~and DC score~~, except for penalties concerning events which are not part of the respective ~~category class or cup~~.

A4 GENERAL REQUIREMENTS FOR TEAMS & PARTICIPANTS

A4.1 Teams per University

- A4.1.1 A university may register a CV team and an EV team.
- A4.1.2 For the purposes of registering and competing, a university's CV team and EV team are considered to be separate and independent entities.
- A4.1.3 Teams which are formed with members from two or more universities are treated as a single team. In such a case, the team must inform the organizers upon registration as to which university will be represented.
- A4.1.4 In the case where multiple colleges located in multiple cities or districts are grouped under a common University, either autonomous or through affiliation, the team must register under their College name.

A4.2 Team Members

- A4.2.1 A team member may only be part of one team, work on one vehicle and take part in static and dynamic events for only one team.
- A4.2.2 Each team must have one team member identified as the team captain. The team captain is the main contact person for the officials during the registration process and the competition. The team captain must have a 'current' student status at the attended College or University, at the time of the competition. It is the team captain's responsibility to communicate any competition updates to the team members.
- A4.2.3 Persons who have previously attended any official event as a judge are not allowed to participate as team members.
- A4.2.4 Each team is also required to identify two additional team members during the registration process who will serve as communication liaisons between the team and the competition, should the team captain not be available. These additional team members must have a 'current' student status at the attended College or University, at the time of the competition.
- A4.2.5 Any changes in the team's leadership roster can only be communicated to the competition by the team captain or by either of the two registered additional team members via the email addresses provided during registration.

A4.3 Student Status

- A4.3.1 Team members must be enrolled as degree seeking undergraduate or graduate students in any university. Team members who have graduated within the eleven month period prior to the competition remain eligible to participate.
- A4.3.2 Students who have already graduated from a degree program and are seeking another degree of the same level or below are not allowed to participate.
- A4.3.3 Students seeking a PhD degree/PhD students or equivalent are not allowed to participate.
- A4.3.4 Team members must have Student Membership level status for the competition season, procured from Membership by Formula Bharat.

A4.4 Age

A4.4.1 Team members must be at least 16 years of age.

A4.5 Driver's License

A4.5.1 Team members who will drive a competition vehicle at any time during a competition must present a valid, government issued driver's license for passenger cars, containing a photograph.

A4.5.2 Designated drivers for the team are required to bring a hardcopy of both sides of their license to the competition site. Upon registration, they will be required to sign a bond and pay a fee that shall be collected by the venue. The amount for the fee shall be mentioned on the competition website closer to the event date.

A4.6 Insurance

A4.6.1 Each participant, including faculty advisors and volunteers, must provide proof of valid private liability & individual health insurance for the competition.

A4.7 Liability Waiver

A4.7.1 All onsite participants, including faculty advisors and volunteers must sign a liability waiver which can be found on the competition website.

A4.7.2 All onsite participants under 18 years of age must submit the Under 18 liability waiver prior to the competition. This shall be made available via the competition website.

A4.8 [EV ONLY] Electrical System Officer (ESO)

A4.8.1 Every participating team has to appoint one to four ESOs for the competition.

A4.8.2 The ESOs are responsible for all electrical work carried out on the vehicle during the competition.

A4.8.3 The ESOs are the only persons in the team who may declare the vehicle electrically safe, in order for work to be performed on any system of the vehicle by the team.

A4.8.4 The ESOs must be valid team members, which means that they must have student status (see A4.3).

A4.8.5 The ESOs must be contactable by phone at all times during the competition.

A4.8.6 An ESO must accompany the vehicle whenever it is operated or moved around at the competition site.

A4.8.7 If only one ESO is named by the team, this ESO may not be a driver.

A4.8.8 An appropriate Electrical System Officer Qualification (ESOQ) requires the proof of a practical and theoretical training for working on the TS. Regarding content, the training should be on the basis of DGUV 209-093 stage 2E/3E (<https://fsg.one/4i5SP>) and held by an external expert. Teams receiving training from providers or programs other than those mentioned on the competition website must provide details of the training which include

details of the program, topics covered within the training, format of training, training provider credentials etc. Additionally, the certificate issued must contain the level of training received (as in, 1E / 2E/ 3E).

- A4.8.9 Each team must have a minimum of one ESO trained in 3E. Only ESOs with 3E training are allowed to work on live high voltage systems.
- A4.8.10 It is recommended that all other team members receive an 1E training instruction. This can be provided by an external provider or from one of the team's certified ESO itself.

A4.9 Faculty Advisor

- A4.9.1 Each team is expected to have a Faculty Advisor appointed by the university (or college, where applicable). The Faculty Advisor is expected (however not mandatory) to accompany the team to the competition. In the case that the Faculty Advisor cannot attend, the Team Captain will be considered by competition officials to be the official university representative.
- A4.9.2 Faculty Advisors may advise their teams on general engineering and engineering project management theory.
- A4.9.3 Faculty Advisors may not design any part of the vehicle nor directly participate in the development of any documentation or presentation.
- A4.9.4 Additionally, Faculty Advisors may not fabricate nor assemble any components nor assist in the preparation, maintenance, testing or operation of the vehicle. In brief – Faculty Advisors may not design, build or repair any part of the car.
- A4.9.5 The appointed Faculty Advisor must be the participating institution's Faculty member and the individual should have completed their undergraduate studies 3 years prior to assuming such a post.

A5 DOCUMENTATION & DEADLINES

A5.1 Required Documents and Forms

- A5.1.1 The following documents and forms must be submitted by the action deadlines defined on the competition website:
- IAD, SES, BPPV, CRMR, EDP, DSS, CRD (BOM, CEXP, CSUP), PS, VSV, TMI,
 - [EV ONLY] FMEA, ESOQ, SVCR, ESF-1, ESF-2

A5.2 Submission

- A5.2.1 Uploaded documents may only be viewed by members of the submitting team, authorized judges and officials.
- A5.2.2 By submitting documents via the competition website, the team agrees that they may be reproduced and distributed by the officials, in both complete and edited versions, for educational purposes.

- A5.2.3 Documents and videos that are largely incomplete or not readable will be considered as not submitted.
- A5.2.4 Teams must submit documents in the prescribed method as mentioned on the competition website for both template and non-template driven documents.
- A5.2.5 Discovery of any forged documentation by the team, such as datasheets with incorrect values, submissions with incorrect data / images, etc. shall result in de-registration of the team from the competition.

A5.3 Penalties

- A5.3.1 The following table indicates penalties and consequences apply to **late or non-submissions**:

Document	Late Submission: Points penalty per 24h	Penalty deduction from?	Non-Submission: After 7 days
ESOQ [EV]	10	Overall	DR – IN & D
FMEA [EV]	10	Overall	DR – IN & D
SVCR [EV]	10	Overall	DR – IN & D
SES	10	Overall	DR – IN & D
ESF-1 [EV]	10	Overall	DR – IN & D
ESF-2 [EV]	10	Overall	DR – IN & D
IAD	10	Overall	DR – IN & D
BPPV	10	BPP	DR – BPP, 0 pts BPP
CRMR	10	ED	DR – ED, 0 pts ED
DSS	10	ED	DR – ED, 0 pts ED
EDP	10	ED	DR – ED, 0 pts ED
PS	10	Overall	DR – IN & D
VSV	10	Overall	DR – IN & D
TMI	-	-	DR - Competition
CRD (BOM)	10	CR	DR – CR, 0 pts CR
CRD (CEXP)	10	CR	DR – CR, 0 pts CR
CRD (CSUP)	10	CR	DR – CR, 0 pts CR

Legend: DR – De-registered; IN – Technical Inspection events; D –Dynamic events; BPP – Business Plan Presentation event; ED – Engineering Design event; CR – Cost & Manufacturing event

Note 1: TMI – No submission of TMI by deadline will result in team members' inability to receive electronic certificates and inability to participate at the on-site event.

Note 2: No response to official's communication on delayed or non-submission of the documents shall result in de-registration of the team **from the competition**.

Note 3: Teams de-registered from any specific event(s) (except for those de-registered from the competition) may still be eligible for participation certificates, provided the TMI is submitted by the deadline. If the team has been de-registered (DR) from all sub-events (BPP, ED, CR, IN, and D), it will result in the team being de-registered (DR) from the entire competition. Consequently, a certificate of participation will not be issued in this scenario.

A5.3.2 Corrected files must be uploaded within 168 hours of receiving a reviewer notice. Certain documents may not require approval. The following table indicates penalties and consequences apply to delayed submission towards **correction requests**, post the grace period mentioned above:

Document	Late Correction Submission: Points penalty per 24h	Penalty deduction from?	Non-Submission: After 7 days
ESOQ [EV]	5	Overall	DR – IN & D
FMEA [EV]	5	Overall	DR – IN & D
SVCR [EV]	5	Overall	DR – IN & D
SES	5	Overall	DR – IN & D
ESF-1 [EV]	5	Overall	DR – IN & D
ESF-2 [EV]	5	Overall	DR – IN & D
IAD	5	Overall	DR – IN & D
BPPV	5	BPP	DR – BPP, 0 pts BPP
CRM	5	ED	DR – ED, 0 pts ED
DSS	5	ED	DR – ED, 0 pts ED
EDP	5	ED	DR – ED, 0 pts ED
PS	5	Overall	Tier 2
VSV	5	Overall	Tier 2
TMI	-	-	-
CRD (BOM)	5	CR	DR – CR, 0 pts CR
CRD (CEXP)	5	CR	DR – CR, 0 pts CR
CRD (CSUP)	5	CR	DR – CR, 0 pts CR

Note 1: Simultaneous requests for different parts within one document or form will be penalized independently of each other.

Note 2: Unless the first revision is requested from the competition officials, uploading a revision before such request for a document would automatically make the latest submitted document the ‘first submission’, and any late submission penalties as per [A5.3.1](#) shall apply.

Note 3: If the review panel observes consistent neglect of certain changes by the team, a flat penalty of 20 points will be imposed for that specific document upon the initial instance. Subsequent occurrences will incur additional penalty points each time they are repeated.

Note 4: Comments made by the reviewer on the PS, or during the PS Team Calls must be responded to via the originally submitted PS only. Concerns raised must be addressed appropriately, before three weeks of the competition dates, for the teams Tier level to be assigned (Refer to [A5.10](#)).

A5.3.3 The following table indicates penalties and consequences apply to incorrect file naming and formatting. Please note tables in [A5.3.1](#) and [A5.3.2](#) for column of points’ deduction (i.e. Overall or Event-Specific with each respective document)

- Incorrect file type: 5 penalty points
- Incorrect file naming: 2 penalty points
- Incorrect template: Considered as non-submission

- Incorrect EDP link within ED supporting document: Considered as non-submission
- Exceeding page / slide limit (this includes a non-required cover page as well): 10 penalty points
- Exceeding pitch or presentation time limit: 10 penalty points
- (For non-template files) Missing Team Number, Team Name, Institution Name, Document Name in Header and Page number, Total Number of pages in Footer: 0-5 penalty points
- Missed Presentation Session with less than 48 hour notice: 50 points
- Missed slot booking for virtual judging session (BPP Prelims / ED Prelims / Cost and Manufacturing Prelims: DR from particular event (Business Plan Presentation / Engineering Design / Cost and Manufacturing)

Note: While there is no penalty for file size, teams are requested to keep to the minimum possible size to ensure that judges and reviewers can easily download or review the file on any device and to also ensure that the team avoids uploading issues.

A5.3.4 The competition website will state the last day for approval for certain documents. Any final document revisions must be submitted at least two weeks before the last day of approval. Teams which do not have the listed documents approved by the stated deadline on the competition website will be automatically de-registered from the specific event or from the competition, as listed in the table in [A5.3.1](#).

A5.4 De-registration

A5.4.1 A team which is de-registered from the competition has a single chance to apply for a place on the waiting list. A team which is de-registered from specific events in the competition has a single chance to appeal their status.

A5.4.2 To apply, the team must complete the following within 24 hours after the de-registration notification:

- Submit an informal application to the officials
- Correct the reason for de-registration (e.g. upload of a document)

A5.4.3 If the application is positively confirmed by the officials, the team will be

- Placed at the end of the waiting list
- Receive 20 penalty points

A5.4.4 Applications will be declined if the rework is inadequate or de-registration was caused by misbehavior of the team.

A5.5 Photographic Submissions (PS)

A5.5.1 All teams must submit images showing the various views of the vehicle driving prior to the competition. The checklist of views required, including the method of submission shall be specified on the competition website.

A5.5.2 Teams that attend other events with their vehicle, in proximity to the next competition, must ensure that the photos for submission are captured before attending those events to prevent the situation of missing the submission deadline.

A5.5.2 Teams that attend other events with their vehicle, in proximity to the next competition, must ensure that the photos for submission are captured before attending those events to prevent the situation of missing the submission deadline.

A5.6 Vehicle Status Video (VSV)

A5.6.1 All teams must submit a video showing the vehicle driving prior to the competition. The video must be submitted before the deadline specified on the competition website.

A5.6.2 The video must show the following sequences in the described order:

- Standing still
- 360° video around the vehicle (close up, may overlap with the following two bullet points)
- [EV ONLY] Activate TS
- [CV ONLY] Start engine
- Straight driving, minimum distance is 30 m, minimum speed is 10 km/h for vehicles with driver
- Full stop
- 180° cornering
- Straight driving back to start point, minimum speed is 10 km/h for vehicles with driver
- Standing still

A5.6.3 The video must fulfill the following criteria:

- Continuous video from a third person view - no assembled sequences
- Vehicle must be clearly visible (light, video resolution, frames and frequency)
- Vehicle must run under its own power
- Driving must follow A6.4.6
- Vehicle must be presented in ready-to-race conditions incl. body work
- No crossing in front of the vehicle after [EV ONLY] TS activated / [CV ONLY] engine started
- [EV ONLY] Tractive System Active Light (TSAL), [DC ONLY] Autonomous System Status Indicator (ASSI), and brake light, must be clearly visible in the video
- [EV ONLY] Ready-to-drive (R2D) sound must be audible in the video
- Must not exceed a length of 60 seconds. File size may be limited, see the competition handbook.
- File format must be common e.g. avi, mpg, mp4, wmv

A5.6.4 The VSV will be reviewed in order of submission. A review may take up to two weeks.

A5.6.5 If a team receives a “fail” for its video prior to the VSV deadline, the video will be treated as not submitted. A new submission is possible afterwards. In all other situations [A5.4](#) and [A5.3](#) apply.

A5.6.6 A team which uploads a VSV with a previous year vehicle will be de-registered from the competition.

A5.7 ~~[Removed]~~

A5.8 Team Member Information (TMI)

- A5.8.1 All team members who plan on attending the competition on-site or who would like to receive participation certificates, must have Student Membership level for the competition season, procured via the Membership by Formula Bharat (MFB) platform.
- A5.8.2 All team members must provide details towards the Team Member Information (TMI) submission available on the competition website by the specified deadline. This information includes but is not limited to Full Name, Contact Email, Phone Number, Age, Year of Study, Medical Emergency contact information (which must be next of kin) etc.
- A5.8.3 The TMI submission criteria will be made available on the competition website approximately two months prior to the event.
- No new team member entries shall be allowed past the deadline or on-site.
- A5.8.4 The team captain is responsible for confirming participation of team members, [ON-SITE ONLY] for providing their insurance information and uploading insurance scans, under 18 liability waivers' scans (if any) and for providing driver license information.
- A5.8.5 Confirmed participants with incorrect or incomplete insurance information (including scanned copies) shall have their participation status revoked on-site at the competition.
- A5.8.6 A maximum of 60 team members may participate on a team.
- A5.8.7 Late submission fees and extra member fees shall be on the competition website.

A5.9 Participation Certificates

- A5.9.1 Participants who are listed on the TMI with their complete information and have submitted all relevant documents shall receive a participation certificate within four weeks of the competition completion.
- A5.9.2 The competition organizers shall not be distributing printed (hardcopy) versions of the certificates. The team may request a signed and stamped letter addressed to their institution to confirm the list of team members who attended and participated at the event.

A5.10 Teams Categorization

- A5.10.1 The competition organizers reserve the right to classify participating teams into Tier 1 and Tier 2 lines for technical inspection purposes, prior to the competition. This classification is based on the submission and quality of the Photographic Submissions (PS), Vehicle Status Video (VSV) and approval status of documents pertaining to IN and D events.
- A5.10.2 Notice for teams categorized as Tier 2 due to poor submissions shall be done by the date specified on the competition website.
- A5.10.3 Tier 1 teams will get prioritized at the Technical Inspection queue over Tier 2 teams. Comprehensive details on arrival time and registration shall be provided in the competition website prior to the competition dates.

A5.11 Negative Scoring

- A5.11.1 Should the team's total score or individual static score result in a negative score (as in below 0 points) due to late submission (A5.3) or delayed correction requests (A5.4) penalties, the specific result will be capped at 0 points.

A6 GENERAL RULES

A6.1 Arrival and Removal of Vehicle from the Site

- A6.1.1 Teams that do not have a 'DR - IN & D' status, must arrive with their vehicle to the competition site within the first two days of the competition during operational hours and must register for queuing at technical inspection. Teams that do not do so will be automatically de-registered from further participation in IN and D events.
- A6.1.2 [EV ONLY] Teams must present their accumulator for inspection no later than before the end of the second day of accumulator inspection, as within operational hours, as mentioned in the competition schedule. Teams that do not do so will be automatically de-registered from further participation in Accumulator Inspection (IN3), and subsequently in certain IN events and all D events.
- A6.1.3 Teams may remove their vehicle ([EV ONLY] vehicle without tractive system accumulator) from the competition site during the competition if no technical inspection stickers have been received. Once a team has received a competition technical inspection sticker, they are not allowed to leave the competition site. Doing so without appropriate approvals will result in removal of the sticker and disqualification from the competition.
- A6.1.4 Teams that remove their vehicle from the competition during the competition can only do so during the site's operational hours, as per the competition schedule, and will have to make their own provisions in moving the vehicle in and out of the competition site. Refer to the competition handbook for further details on restrictions on movement of vehicles off-site during the competition days.

A6.2 Forfeit for Non-Appearence

- A6.2.1 It is the responsibility of each team to be in the right place at the right time.
- A6.2.2 If a team is not present and ready to compete at the scheduled time, they forfeit an attempt at that event.

A6.3 Team and Driver Briefings

- A6.3.1 All team captains or designated team representatives must attend the team captains' briefing for that day.
- A6.3.2 Drivers who have missed attending the driver's briefing for the day will not be allowed to drive the car at any event on that particular day.

A6.4 Testing and Work Safety

- A6.4.1 Competition organizers are not responsible for the use of the vehicles outside of their competition.

-
- A6.4.2 The competition officials disassociate themselves from all activities of the teams besides their own competition and associated events.
- A6.4.3 All teams are advised to follow common practices and common sense when working on the vehicle and when operating the vehicle, before, during and after a competition.
- A6.4.4 The vehicles must not participate in events not suitable for this type of vehicles, like hill climbs, drag races or similar.
- A6.4.5 Teams must never use their vehicles for wheel-to-wheel races.
- A6.4.6 The following listed requirements are considered the minimum for a testing/operating environment to qualify as safe. Following these guidelines does not guarantee safety under all circumstances:
- Driver wearing full protection gear according to T13.3
 - Working TSAL, IMD, AMS, ASSI, RES, EBS, APPS/brake pedal plausibility check, APPS, and ETC plausibility check if applicable
 - Rules compliant chassis and mounted impact attenuator
 - No other passenger cars, trucks etc. being parked or driven on the same premise at the same time, unless the areas are clearly separated
 - No running under low visibility conditions
 - No running at speeds above typical event speeds
 - No running in areas where crashing into obstacles at the height of the driver's head is possible, such that parts of the vehicle may pass below an obstacle, but the driver's head can be trapped between the obstacle and the main hoop for example.
- A6.4.7 Organizers reserve the right to disqualify a team registered for their competition in case of unsafe driving behavior, especially if the reputation of the competition, sponsors and other teams is compromised. **This includes any questionable material posted on social media by registered participating teams under the competition.**
- A6.5 Onsite Working Safety**
- A6.5.1 Everyone in the dynamic area and everybody working on the vehicle must wear appropriate, closed-toed shoes.
- A6.5.2 When using metal cutting equipment, eye protection is required for the operator as well as any team member assisting. When operating loud tools, hearing protection is required.
- A6.5.3 Any operation producing litter or debris, e.g. cutting of carbon fiber, should not be performed in the pits.
- A6.5.4 When jacking up the vehicle a safe and stable support device rated for the load must be used.
- A6.5.5 **The use of motorcycles, quads, scooters, skateboards, rollerblades or similar mobility devices by team members and spectators in any part of the competition area is prohibited. Mobility devices used to assist with an individual's medical disability is accepted.**
- A6.5.6 **The use of self-propelled pit carts, tool boxes, tire carriers or similar motorized devices in any part of the competition site is prohibited.**
-

A6.6 Alcohol and Illegal Material

- A6.6.1 Alcohol, illegal drugs, weapons or other illegal material are prohibited on the competition site during the competition.
- A6.6.2 If any team member is tested with an alcohol level higher than 0.0 %, he or she will be immediately disqualified for the rest of the competition. A second team member being found to have an alcohol level higher than 0.0 % will result in the entire team being disqualified immediately.

A6.7 Vehicle Movement

- A6.7.1 Vehicles must not move under their own power anywhere other than on the practice or competition tracks.
- A6.7.2 [EV ONLY] The detachable handle or key of the Tractive System Master Switch (TSMS) must be completely removed and kept by an ESO. The lockout/tagout function of the TSMS (see EV6.2.2) must be used.

~~A6.7.3~~ [EV ONLY]

- A6.7.4 Vehicles must be pushed at a normal walking pace by means of a “pushbar” (see T13.1) and with a team member in the cockpit wearing the required driver equipment (helmet included) as defined in T13.3 except for arm restraints and balaclava.
- A6.7.5 The team member in the cockpit must have full control of steering and braking.
- A6.7.6 When the pushbar is attached to the vehicle, the engine/tractive system must remain switched off.
- A6.7.7 Vehicles with wings are required to have two team members walking on either side of the front wing whenever the vehicle is being pushed.

A6.8 [CV ONLY] Engine Running

- A6.8.1 Running engines is not allowed in the pits.
- A6.8.2 Engine running is allowed in the engine test area and in the dynamic area, when the following conditions are met:
- The vehicle must have passed mechanical inspection.
 - The vehicle must be jacked up using a quick jack (see T13.2).
 - A driver, wearing required driver equipment (see T13.3), must be seated in the cockpit.
 - A fire extinguisher must be immediately available.
 - Driven wheels can only remain fitted to the vehicle if they will not rotate.
 - No one is allowed under the vehicle while the engine is running.
- A6.8.3 Cranking engines in pits is not allowed.

A6.9 Fueling and Oil

- A6.9.1 Fueling may only take place at the fuel station and must be conducted by officials only.
- A6.9.2 Open fuel containers are not permitted at the competition.

A6.9.3 Waste oil must be taken to the fuel station for disposal.

A6.10 [EV ONLY] Working on the Vehicle

A6.10.1 All activities require the TSAL to be green.

A6.10.2 A prominent manual sign indicating the “TSAL green” state must be present whenever the LVS is switched off and the requirements for an only green TSAL according to [EV4.10](#) are met.

A6.10.3 All activities on the vehicle, except when working on an active TS, require the High Voltage Disconnect (HVD) to be removed.

A6.11 [EV ONLY] Working on the Tractive System

A6.11.1 Activities on the Tractive System (TS), except for the accumulator ([see A6.12](#)) must take place in the pit.

A6.11.2 All activities require the attendance of the ESO.

A6.11.3 For activities on the inactive TS, the following procedure must be carried out:

- The vehicle must be barred from anyone not involved in the work, by using barrier tape.
- The Tractive System Master Switch (TSMS) must be switched off.
- It must be assured that the TS cannot be restarted, by, at a minimum, using the lockout/tag out of the TSMS.
- A check for zero-potential must be carried out.
- A sign that declares the vehicle is electrically safe must be installed. The name of the ESO who is supervising the activities must be noted on the sign. This ESO is the only person who may remove the sign and the barrier.

A6.11.4 In case of measurements on the active TS or an activation of the TS in the **designated areas** for purposes, the following steps must be followed:

- The vehicle must be barred from anyone not involved in the work, by using barrier tape.
- The vehicle must be jacked up and the driven wheels removed.
- One team member must be prepared to push a shutdown button at any time.
- The TS must only be activated for as long as necessary.
- Appropriate insulated tools and equipment must be used.
- Safety glasses with side shields and compliant safety gloves must be worn by all participating team members when parts of the TS are exposed.
- No other work on the vehicle is permitted when the TS is active.

A6.11.5 If the TSAL is flashing red or malfunctioning, the TS is considered as active.

A6.11.6 There must be at least one team member present, who is not directly involved in the work, but who could assist in case of an incident.

A6.11.7 Turning ON the TS inside pits is restricted. Working on the vehicle with TS ON is only allowed in the designated areas specified by the officials.

A6.12 [EV ONLY] Working on Tractive System Accumulators

- A6.12.1 Opening or working on accumulator containers is only allowed in the provided work places in the charging area ([see A6.13](#)).
- A6.12.2 All activities require the attendance of an ESO.
- A6.12.3 Whenever the accumulator containers are opened, the cell segments must be separated with the maintenance plugs ([see EV5.4.4](#)).
- A6.12.4 Appropriate insulated tools and equipment must be used.
- A6.12.5 Safety glasses with side shields and compliant safety gloves must be worn by all participating team members.
- A6.12.6 There must be at least one team member present, who is not directly involved in the work conducted on the accumulator, but who could assist in case of an incident.
- A6.12.7 Moving accumulator cells and/or accumulator segment(s) around at the competition site is only permitted if they are inside a completely closed accumulator container.
- A6.12.8 All parts and modules of the TSAC that are not currently being worked on must be covered at least according to IPxxB while working on the accumulator container.
- A6.12.9 Additional safety measures may be included in the respective competition [handbook or on the competition website](#).
- A6.12.10 The TSAC and any spare cells have to be stored in a designated area specified by competition officials.
- A6.12.11 The TSAC must be stored in designated areas specified by competition officials after the competition's daily operational hours, even after a vehicle passes technical inspections. The TSAC shall not be stored in the team's pit.

A6.13 [EV ONLY] Charging

- A6.13.1 There will be a separated charging area on the competition site. Charging TS accumulators is only allowed inside this area.
- A6.13.2 Accumulators must be removed from the vehicle and placed on the accumulator container hand cart ([see EV8.1](#)) for charging.
- A6.13.3 The label [EV5.3.6](#) or an additional label according to [EV5.3.6](#) must be visible during charging.
- A6.13.4 No grinding, drilling, etc. is allowed in the charging area.
- A6.13.5 At least one team member who has knowledge of the charging process must stay with the accumulator(s) during charging.

A6.14 Trash Cleanup

- A6.14.1 Cleanup of trash and debris is the responsibility of the teams.

- The team's work area should be kept uncluttered.
- At the end of the day, each team must clean all debris from their area and help with maintaining a clean paddock.

A6.14.2 Teams must remove all of their material and trash when leaving the site at the end of the competition.

A6.14.3 Teams that abandon furniture, or that leave a paddock that requires special cleaning, will be billed for removal and/or cleanup costs.

T GENERAL TECHNICAL REQUIREMENTS

T1 DEFINITIONS

T1.1 Chassis Definitions

- T1.1.1 Chassis – The fabricated structural assembly that supports all functional vehicle systems. This assembly may be a single welded structure, multiple welded structures or a combination of composite and welded structures.
- T1.1.2 **Bodywork** – the outermost surface of the chassis or any fairing parts and covers.
- T1.1.3 Cockpit – The volume which accommodates the driver which is defined by the top of the vehicle, the floor closeout, the inner side of the bodywork, the front bulkhead and the firewall.
- T1.1.4 Chassis member – A minimum representative single piece of uncut, continuous tubing or equivalent structure.
- T1.1.5 Front bulkhead – A planar structure that defines the forward plane of the chassis and provides protection for the driver's feet (in front view, together with the AIP, covers the driver's feet).
- T1.1.6 Front bulkhead support (FBHS) – A structure that defines the side of the chassis from front bulkhead back to the top of the upper side impact structure and the front hoop.
- T1.1.7 Front hoop – A roll bar located above the driver's legs, in proximity to the steering wheel.
- T1.1.8 Impact Attenuator (IA) – A deformable, energy absorbing device located forward of the front bulkhead.
- T1.1.9 Main hoop – A roll bar located alongside or just behind the driver's torso.
- T1.1.10 Monocoque – A chassis made of composite material.
- T1.1.11 Node-to-node triangulation – An arrangement of chassis members projected onto a plane, where a co-planar load applied in any direction, at any node, results in only tensile or compressive forces in the chassis members as shown in Figure 1 (below).




Figure 1: Node-to-node triangulation of chassis members (left correct and right incorrect).

- T1.1.12 Primary structure – The primary structure is comprised of the following components:
- Main hoop
 - Front hoop
 - Roll hoop braces and supports
 - [Impact structures as mentioned under T3.15](#)
 - Front bulkhead
 - Front bulkhead support system
 - All chassis members, guides and supports that transfer load from the driver's restraint system into the above mentioned components of the primary structure
- T1.1.13 Roll hoops – Both the front hoop and the main hoop are classified as “roll hoops”
- T1.1.14 Roll hoop bracing – The structure from a roll hoop to the roll hoop bracing support.
- T1.1.15 Roll hoop bracing supports – The structure from the lower end of the roll hoop bracing back to the roll hoop(s).
- T1.1.16 [Rollover protection envelope – the union of](#)
- [the primary structure and any additional structures fixed to the primary structure which meet the minimum specification defined in T3.2 or equivalent](#)
 - [the plane from the top of the main hoop to the top of the front hoop](#)
 - [the plane from the top of the main hoop to the rearmost structure according to T3.2 or equivalent](#)
- [Example depicted in figure 2.](#)
- T1.1.17 Side impact structure – The area of the side of the chassis between the front hoop and the main hoop and from the chassis floor to the height as required in [T3.15](#) above the lowest inside chassis point between front hoop and main hoop.
- T1.1.18 [Surface envelope – the surface envelope is the surface of the union of the rollover protection envelope, see T1.1.16, and the volume defined by](#)
- [the top of the main hoop and the outside edges of the four tires](#)
 - [a plane from the top of the main hoop to the top of the front bulkhead](#)
 - [a plane from the top of the main hoop to the the rearmost structure according to T3.2 or equivalent](#)
 - [a projection in side view of the lower boundaries of the rollover protection envelope](#)
- [Example depicted in figure 3.](#)




Figure 2: Rollover protection envelope [T1.1.16](#), thick lines are primary structure members according to [T3.2](#)




Figure 3: Surface Envelope [T1.1.18](#)

T1.2 Material Definitions

T1.2.1 Fire Retardant – A material meeting one of the following standards:

- UL94 V-0 for the minimum used material thickness
- FAR 25.853(a)(1)(i)

Equivalent standards are only accepted, if the team shows equivalence and this is approved by the officials prior to the event.

T1.2.2 Coolant - A substance used for heat transfer by convection.

T1.3 Electrical Definitions

T1.3.1 Direct Connection – Two devices or circuits are directly connected if the connection is not routed through any common PCB and does not include any devices or functionality other than overcurrent protection or connectors.

T2 GENERAL DESIGN REQUIREMENTS

T2.1 Vehicle Configuration

T2.1.1 The vehicle must be designed and fabricated in accordance with good engineering practices.

T2.1.2 The vehicle must be open-wheeled, single seat and open cockpit (a formula style body) with four wheels that are not in a straight line.

T2.1.3 Open wheel vehicles must satisfy the following (see also Figure 4):

- The wheel/tire assembly must be unobstructed when viewed from the side.
- No part of the vehicle may enter a keep-out-zone defined by two lines extending vertically from positions 75 mm in front of and 75 mm behind the outer diameter of the front and rear tires in the side view of the vehicle, with steering straight ahead. This keep-out zone extends laterally from the outside plane of the wheel/tire to the inboard plane of the wheel/tire assembly.




Figure 4: Keep-out-zones for the definition of an open-wheeled vehicle.

T2.2 Ground Clearance

- T2.2.1 The minimum static ground clearance of any portion of the vehicle, other than the tires, including a driver, must be 30 mm. *If an active suspension system is installed, the static ground clearance is measured in the lowest adjustable position.*
- T2.2.2 Sliding skirts or other aerodynamic devices that by design, fabrication or as a consequence of moving, contact the track surface are prohibited.

T2.3 Bodywork

- T2.3.1 There must be no openings through the bodywork into the driver compartment other than that required for the cockpit opening. Minimal openings around the front suspension and steering system components are allowed.
- T2.3.2 *In any side view in front of the cockpit opening and outside the area defined in T8.2 all parts of the bodywork must have no external concave radii of curvatures. Any gaps between bodywork and other parts must be reduced to a minimum.*
- T2.3.3 Enclosed chassis structures and structures between the chassis and the ground must have two venting holes of at least 25 mm diameter in the lowest part of the structure to prevent accumulation of liquids. Additional holes are required when multiple local lowest parts exist in the structure.
- T2.3.4 *The bodywork in front of the front wheels with the tangent of surface above 45° relative to the forward direction must have a radius of at least 38 mm along the top, sides and bottom of all affected edges.*

T2.4 Suspension

- T2.4.1 The vehicle must be equipped with fully operational front and rear suspension systems including shock absorbers and a usable wheel travel of at least 50 mm and a minimum jounce of 25 mm with driver seated.
- T2.4.2 All suspension mounting points must be visible at technical inspection, either by direct view or by removing any covers.

T2.5 Wheels

- T2.5.1 Any wheel mounting system that uses a single retaining nut must incorporate a device to prevent loosening of the nut and the wheel. A second nut ("jam nut") does not meet these requirements.
- T2.5.2 Wheel lug bolts and studs must be made of steel or titanium. The team must be able to show good engineering practice and provide adequate strength by calculations. [Wheel lug bolts, drive pegs and studs must not be hollow.](#)
- T2.5.3 Aluminum wheel nuts may be used, but they must be hard anodized and in pristine condition.

T2.6 Tires

- T2.6.1 Vehicles must have two types of tires as follows:
- Dry tires - The tires on the vehicle when it is presented for technical inspection are defined as its "dry tires".
 - Wet tires - Wet tires may be any size or type of treaded or grooved tire provided:
 - The tread pattern or grooves were molded in by the tire manufacturer or were cut by the tire manufacturer or their appointed agent. Any grooves that have been cut must have documentary proof that it was done in accordance with these rules.
 - There is a minimum tread depth of 2.4 mm.
- T2.6.2 Tires on the same axle must have the same manufacturer, size and compound.
- T2.6.3 Tire warmers are not allowed.
- T2.6.4 Special agents that increase traction may not be added to the tires or track surface.
- T2.6.5 [A team can choose to use a single set of tires which are designed for "dry" and "wet" conditions. If so, the tires need to be treaded or grooved compliant to T2.5.1 in order to be deemed as "fit" to run under "wet" conditions. Tires in violation of T2.5.1 or with no treads/grooves are not considered "wet" tires, and hence a vehicle with these tires cannot race if the track is deemed "wet". However, these tires can be used as dry tires.](#)
- T2.6.6 [Tires that are specifically constructed by manufacturers to be run in wet conditions can be used only under "Damp" or "Wet" operating conditions \(D3.2.1\) of the track and cannot be used as dry tires.](#)

T2.7 Steering

- T2.7.1 Steering systems using cables or belts for actuation are prohibited.

- T2.7.2 The steering wheel must directly mechanically actuate the front wheels.
- T2.7.3 The steering system must have positive steering stops that prevent the steering linkages from locking up. The stops must be placed on the rack and must prevent the tires and rims from contacting any other parts. Steering actuation must be possible during standstill.
- T2.7.4 Allowable steering system free play is limited to a total of 7° measured at the steering wheel.
- T2.7.5 The steering wheel must be attached to the column with a quick disconnect. The driver must be able to operate the quick disconnect while in the normal driving position with gloves on.
- T2.7.6 The steering wheel must be no more than 250 mm rearward of the front hoop. This distance is measured horizontally, on the vehicle centerline, from the rear surface of the front hoop to the forward most surface of the steering wheel with the steering in any position.
- T2.7.7 The steering wheel must have a continuous perimeter that is near circular or near oval. The outer perimeter profile may have some straight sections, but no concave sections.
- T2.7.8 In any angular position, the top of the steering wheel must be no higher than the top-most surface of the front hoop.
- T2.7.9 The steering rack must be mechanically attached to the primary structure [and all stationary parts must be within the rollover protection envelope, see T1.1.16.](#)
- T2.7.10 Joints between all components attaching the steering wheel to the steering rack must be mechanical and visible at technical inspection. Bonded joints are allowed in accordance with [T3.2.8.](#)
- T2.7.11 Rear wheel steering, which can be electrically actuated, is permitted if mechanical stops limit the range of angular movement of the rear wheels to a maximum of 6°. This must be demonstrated with a driver in the vehicle and the team must provide the equipment for the steering angle range to be verified at technical inspection.

T2.8 Wheelbase

- T2.8.1 The vehicle must have a wheelbase of at least 1525 mm.

T2.9 Track and Rollover Stability

- T2.9.1 The smaller track of the vehicle (front or rear) must be no less than 75% of the larger track.
- T2.9.2 The track and center of gravity of the vehicle must combine to provide adequate rollover stability.

T3 GENERAL CHASSIS DESIGN

T3.1 General Requirements

- T3.1.1 Among other requirements, the vehicle's structure must include:
- Two roll hoops that are braced

- A front bulkhead with support system and IA
- Side impact structures

T3.2 Minimum Material Requirements

T3.2.1 Table 4 shows the minimum requirements for the members of the primary structure if made from steel tubing.

Item or application	Minimum wall thickness	Minimum cross sectional area	Minimum area moment of inertia
Main and front hoops, shoulder harness mounting bar	2.0 mm	173 mm ²	11 320 mm ⁴
Impact structures, front bulkhead, roll hoop bracing, driver's restraint harness attachment (except as noted above)	1.2 mm	119 mm ²	8509 mm ⁴
Front bulkhead support, main hoop bracing supports	1.2 mm	91 mm ²	6695 mm ⁴

Table 4: Minimum Material Requirements

T3.2.2 Steel tubing has to be made from unalloyed carbon steel with a maximum content of 0.3% carbon, 1.7% manganese and 0.6% of any other element. All other steel grades are considered alternative materials and require additional testing and documentation ([see T3.3](#)).

T3.2.3 Except for inspection holes, any holes drilled in any part which is a member of the primary structure must be considered in the SES.

T3.2.4 The steel properties used for the calculations in the SES must be:

Non-welded strength for continuous material calculations:

- Young's Modulus (E) = 200 GPa
- Yield Strength (S_y) = 305 MPa
- Ultimate Strength (S_u) = 365 MPa

Welded strength for discontinuous material such as joint calculations:

- Yield Strength (S_y) = 180 MPa
- Ultimate Strength (S_u) = 300 MPa

T3.2.5 Any tubing with a wall thickness less than 1.2 mm or a minimum area moment of inertia less than 6695 mm⁴ is considered non-structural and will be ignored when assessing compliance to any rule regarding the vehicle structure.

T3.2.6 If a member of the primary structure (except for the roll hoops) is a bent tube or made from multiple tubes an additional tube must support it. This support tube must:

- Have its attachment point at the position along the bend tube where it deviates farthest from a straight line connecting both ends.
- Be of the same dimension as the supported tube(s).
- Terminate at a node of the chassis.
- Be angled no more than 30° from the plane of the supported tube(s).

T3.2.7 Any welded seams shape must not be mechanically altered in any way.

T3.2.8 Where bonded joints are applicable and governed by the rules, a 50% reduction shall be applied to all nominal and tested adhesive values. Bonded joints in the primary structure must be documented in the SES.

T3.3 Alternative Materials

T3.3.1 Alternative materials may be used for all parts of the primary structure and the tractive system accumulator container with the following exceptions:

- The main hoop and the main hoop bracing must be steel
- The front hoop must be metal
- Any welded structures of the primary structure must be steel
- However, the front hoop may be an aluminum welded structure

T3.3.2 If any other materials than steel tubing are used in the primary structure or the tractive system accumulator container, physical testing is required to show equivalency to the minimum material properties for steel in T3.2.

T3.3.3 If alloyed steel as defined by T3.2.2 is used, the team has to include tests and documentation in the SES to show structural equivalency. This may include, but is not limited to:

- Receipts and data sheets of the used tubing materials
- Documentation about welding processes and filler materials
- Documentation about heat treatments
- Tests showing adequate strength and elongation at break in the welded condition.

T3.4 Composite Structures

T3.4.1 If composite structures are used in the primary structure or the TSAC, the Flexural Rigidity (EI) of that structure must be calculated with the tools and formulas in the SES. The actual geometry and curvature of the panel may be taken into account for the main hoop bracing support, the front hoop bracing, the front bulkhead support structure, the shoulder harness bar, the TS and TSAC protective structure. For all other areas the EI must be calculated as the EI of a flat panel about its neutral axis. This panel must have the same composition as the structure used in the primary structure or the TSAC.

T3.4.2 If composite materials are used in the primary structure or the TSAC, the SES must include:

- Material type(s)
- Cloth weights
- Resin type
- Fiber orientation
- Number of layers
- Core material
- Lay-up technique

- 3-point-bend test and shear test data

- T3.4.3 For any laminate in the primary structure or the TSAC, the maximum weight content of parallel fibers, relative to the weight of all fibers in the laminate, is 50%. All fibers laid within any orientation $\pm 10^\circ$ count as parallel in this case.
- T3.4.4 If an asymmetrical lay-up is used in the primary structure, the thinner skin must have a thickness of at least 40 % of the thicker skin.
- T3.4.5 Wherever backing plates are required, they must be fully supported by the structure they are attached to.
- T3.4.6 Backing plates must have a continuous perimeter that is near circular or near oval. The outer perimeter profile may have some straight sections, but no concave sections. Backing plates must not have any cut-outs within their outside perimeter except for the holes for bolts.

T3.5 Laminate Testing

- T3.5.1 If composite materials are used for any part of the primary structure or the tractive system accumulator container the team must:

- Build a representative test panel which must measure exactly 275 mm $\times$ 500 mm that has the same design, laminate and fabrication method as used for the respective part of the primary structure represented as a flat panel. The sides of the test panel must not be laminated (core material must be visible).
- Perform a 3-point bending test on this panel

The data from these tests and pictures of the test samples and test setup must be included in the SES. In the pictures, the following must be identifiable: distance between the two supports, dimensions of the load applicator and test sample marking as per T3.5.4. The test results must be used to derive strength and stiffness properties used in the SES formula for all laminate panels.

Representative test panels for parts of the TSAC may use smaller dimensions, provided that the panel core thickness is 5 mm or smaller. This representative test panel must then measure 150 mm $\times$ 275 mm. In this case, the distance between the two test panel supports must be at least 200 mm and the load applicator must have a radius of at least 5 mm. T3.5.5 and T3.5.6 do not apply.

- T3.5.2 If a panel represents side impact structure it must be proven that it has at least the same properties as two steel tubes meeting the requirements for side impact structure tubes for buckling modulus, yield strength and absorbed energy.
- T3.5.3 Composite structures with different core thicknesses but otherwise identical construction may use material properties derived from a single test panel. The panel with the thicker core must be tested and the structure using derived material properties may not use a core thickness of less than 66 % of the tested panel.
- T3.5.4 When a laminate is not quasi-isotropic, i.e. has equal strength and stiffness in the 0° , 90° and $\pm 45^\circ$ direction, the results from the 3 point bending test will be assigned to the 0° lay-up direction. To show equivalence in the SES, the 0° lay-up direction must be used and oriented accordingly in the chassis.

- T3.5.5 The test samples must be presented at technical inspection. All samples must be marked with the following non-removable (e.g.: permanent marker or engraving, but no sticker) information: laminated structure acronym and date of testing.
- T3.5.6 The distance between the two test panel supports must be at least 400 mm.
- T3.5.7 The load applicator used to test any panel or tube must be metallic and have a radius of 50 mm.
- T3.5.8 The load applicator must overhang the test piece to prevent edge loading.
- T3.5.9 There must be no material between the load applicator and the test piece.
- T3.5.10 Perimeter shear tests must be completed which measure the force required to push or pull a 25 mm diameter flat punch through a flat laminate sample. The sample must be at least 100 mm × 100 mm. Core and skin thicknesses must be identical to those used in the actual chassis structure and be manufactured using the same materials and processes.
- T3.5.11 The test fixture must support the entire sample, except for a 32 mm hole aligned co-axially with the punch. The sample must not be clamped to the fixture.

T3.6 Structural Documentation

- T3.6.1 All teams must submit a Structural Equivalency Spreadsheet (SES).
- T3.6.2 The SES spreadsheet form can be downloaded from the competition website.
- T3.6.3 ~~Removed.~~
- T3.6.4 Vehicles must be fabricated in accordance with the materials and processes described in the SES.
- T3.6.5 Teams must bring a copy of the approved SES to technical inspection.

T3.7 Roll Hoops

- T3.7.1 Both roll hoops must be securely integrated to the primary structure using node-to-node triangulation or equivalent joining methods.
- T3.7.2 The minimum radius of any bend, measured at the tube centerline, must be at least three times the tube outside diameter. Bends must be smooth and continuous with no evidence of crimping or wall failure. The minimum area moment of inertia (see T3.2) must be maintained in all areas, including the bends of the manufactured tubes.
- T3.7.3 In a plane perpendicular to the longitudinal axis of the vehicle and through the lower endpoints of the roll hoop, no part of the primary structure may lie below 30 mm of the endpoints of the roll hoop.
- T3.7.4 Roll hoops attached to a composite primary structure must be mechanically attached at the top and bottom of both sides of the structure and at intermediate locations if needed to show equivalency. The lower roll hoop tubing attachment points must be within 50 mm of the endpoints of the roll hoop.

T3.7.5 Mounting plates welded to the roll hoops must be at least 2 mm thick steel or 3 mm thick aluminum, dependent on the roll hoop material.

T3.7.6 Both roll hoops must have one 4.5 mm hole in a non-critical straight location and its surface at this point must be unobstructed for at least 180°.

T3.8 Main Hoop

T3.8.1 The main hoop must be constructed of a single piece of uncut, continuous, closed section steel tubing.

T3.8.2 In the side view the portion of the main hoop which is above its upper attachment point to the side impact structure must be inclined less than 10° from vertical.

T3.8.3 In the side view any bends in the main hoop above its upper attachment point to the primary structure must be braced to a node of the main hoop bracing support structure with tubing meeting the requirements of main hoop bracing.

T3.8.4 In the side view any portion lower than the upper attachment point to the side impact structure must be inclined either forward or not more than 10° rearward.

T3.9 Front Hoop

T3.9.1 The front hoop must be constructed of a continuous and closed section.

T3.9.2 If the front hoop is made from more than one piece it must be supported by node-to-node triangulation or an equivalent construction.

T3.9.3 In the side view, no part of the front hoop can be inclined more than 20° from vertical.

T3.9.4 If the front hoop is a welded construction made from multiple aluminum profiles, the equivalent yield strength must be considered in the as-welded condition unless the team demonstrates and shows proof that it has been properly solution heat treated and artificially aged. The team must supply sufficient documentation proving the appropriate heat treatment process was performed.

T3.9.5 The front hoop requires six attachment points, two on each side connecting to the front bulkhead support structures and two connecting to the front hoop bracing, and must therefore show equivalency to 180 kN, as follows from T3.16.1 and T3.11.4.

T3.9.6 Fully laminating the front hoop to the monocoque is acceptable. Fully laminating means that the hoop has to be encapsulated with laminate around its whole circumference, see Figure 5. Equivalence to T3.7.4 must be shown in the SES. The laminate encapsulating the front hoop must overlap by at least 25 mm on each side. It must have the same lay-up as the laminate that it is connecting to.




Figure 5: Front hoop laminating requirements

T3.10 Main Hoop Bracing

- T3.10.1 The main hoop must be supported to the front or the rear by bracing tubes on each side of the main hoop.
- T3.10.2 In the side view the main hoop and the main hoop braces must not lie on the same side of a vertical line coincident with the top of the main hoop.
- T3.10.3 The main hoop braces must be attached to the main hoop no lower than 160 mm below the top-most surface of the main hoop. The included angle formed by the main hoop and the main hoop braces must be at least 30°.
- T3.10.4 The main hoop braces must be straight.
- T3.10.5 The lower ends of the main hoop braces must be supported back to the upper attachment point of the main hoop to the side impact structure and to the lower attachment point of the main hoop to the side impact structure by a node-to-node triangulated structure or equivalent composite structure.
- T3.10.6 If any item which extends outside of the primary structure is attached to the main hoop braces, additional bracing is required to prevent bending loads in a rollover situation.

T3.11 Front Hoop Bracing

- T3.11.1 The front hoop bracing attaches on each side of the front hoop as well as the structure forward of the driver's feet. A minimum of two tubes without any bends must be straight on a line in the side view of the frame and must have a minimum distance of 100 mm between each other at the front hoop.
- T3.11.2 The front hoop bracing structure must be attached no lower than 50 mm below the top-most surface of the front hoop, see Figure 6.
- T3.11.3 If the front hoop is inclined more than 10° to the rear, additional braces extending rearwards are required.
- T3.11.4 Composite front hoop bracing structures and their attachments cannot be counted towards the front bulkhead support structures and vice-versa for the structural equivalency documentation.




Figure 6: Front hoop bracing, main hoop bracing and steering wheel requirements

T3.12 Mechanically Attached Roll Hoop Bracing

- T3.12.1 Any non-welded joint at either end of a bracing must be either a double-lug joint (Figure 7) or a sleeved joint (Figure 8).
- T3.12.2 If threaded fasteners are used they are considered critical fasteners and must comply with T10.1.
- T3.12.3 Spherical rod ends are prohibited.
- T3.12.4 Double lug-joints must include a capping arrangement, see Figure 6.
- T3.12.5 In a double-lug joint each lug must be at least 4.5 mm thick and the pin or bolt must be 10 mm metric grade 8.8 minimum. The attachment holes in the lugs and in the attached bracing must be a close fit with the pin or bolt.
- T3.12.6 For sleeved joints the sleeve must have a minimum length of 38 mm either side of the joint and be a close-fit around the base tubes. The wall thickness of the sleeve must be at least that of the bracing tubes. The bolts must be 6 mm metric grade 8.8 minimum. The holes in the sleeves and tubes must be a close-fit with the bolts.




Figure 7: Double lug joint




Figure 8: Sleeved joint

- T3.12.7 For sleeved joints the sleeve must have a minimum length of 38 mm either side of the joint and be a close-fit around the base tubes. The wall thickness of the sleeve must be at least that of the bracing tubes. The bolts must be 6 mm metric grade 8.8 minimum. The holes in the sleeves and tubes must be a close-fit with the bolts.

T3.13 Front Bulkhead

- T3.13.1 Any alternative material used for the front bulkhead must have a perimeter shear strength equivalent to a 1.5 mm thick steel plate.
- T3.13.2 If the front bulkhead is part of a composite structure and is modeled as an "L" shape, the EI of the front bulkhead about the vertical and lateral axes must be equivalent to a steel tube meeting the requirements for the front bulkhead. The length of the section perpendicular to the bulkhead may be a maximum of 25 mm measured from the rearmost face of the bulkhead.

T3.14 Front Bulkhead Support

- T3.14.1 The front bulkhead must be supported back to the front hoop by a minimum of three tubes on each side; an upper member, a lower member and diagonal bracing to provide triangulation.
- The upper support member must be attached to the front bulkhead a maximum of 50 mm below the top-most surface of the front bulkhead, and attached to the front hoop a maximum of 50 mm below the upper side impact member. If the attachment point of the upper member is greater than 100 mm above the upper side impact member, node-to-node triangulated bracing is required to transfer load to the main hoop.
 - The lower support member must be attached to the base of the front bulkhead and the base of the front hoop.
 - The diagonal bracing must triangulate the upper and lower support members' node-to-node.
- T3.14.2 If the front bulkhead support is part of a composite structure, it must have equivalent EI to the sum of the EI of the six baseline steel tubes that it replaces and it must not be counted towards the composite front hoop bracing structures for the structural equivalency documentation (i.e. [T3.11.4](#)).

- T3.14.3 The EI of the vertical side of the front bulkhead support structure must be equivalent to at least the EI of one baseline steel tube that it replaces.
- T3.14.4 The perimeter shear strength of the monocoque laminate in the front bulkhead support structure must be at least 4 kN.

T3.15 Impact Structures

- T3.15.1 The side impact structure must consist of at least three steel tubes ([see T3.2](#)) on each side of the cockpit (Figure 9).
- The upper member must connect the main hoop and the front hoop.
 - The upper member must be at a height between 240 mm and 320 mm above the lowest inside chassis point between the front and main hoop.
 - The lower member must connect the bottom of the main hoop and the bottom of the front hoop.
 - The diagonal member must triangulate the upper and lower member between the roll hoops node-to-node.




Figure 9: Side impact structure

- T3.15.2 Other impact structures, [see CV1.3.2](#), [EV4.4.2](#) and [EV5.5.2](#), must be fully triangulated structures and consist of at least three steel tubes, [see T3.2](#), on each side and rearward of the component that needs to be protected.
- If the component projects outwards from the roll hoops to the side, the front of the component must also be protected.
 - The upper member must not be higher than 320 mm above the lowest inside chassis point between the front and main hoop.
- T3.15.3 If the side impact structure is part of a composite structure, the following is required:
- The region of the structure up to a height of 320 mm above the lowest inside chassis point between the front and main hoop must have an EI equal to the three baseline steel tubes that it replaces. An example for side impact structure is given in Figure 10.
 - The vertical impact structure must have an EI equivalent to two baseline steel tubes and half the horizontal floor must have an EI equivalent to one baseline steel tube.

- The vertical impact structure must have an absorbed energy equivalent to two baseline steel tubes, [exceeding 65 J](#).
- The perimeter shear strength must be at least 7.5 kN.




Figure 10: Side impact structure monocoque

T3.16 Bolted Primary Structure Attachments

- T3.16.1 If two parts of the primary structure are bolted together, each attachment point between the two parts must be able to carry a load of 30 kN in any direction.
- T3.16.2 Data obtained from the laminate perimeter shear strength test must be used to prove that adequate shear area is provided.
- T3.16.3 Each attachment point requires a minimum of two 8 mm metric grade 8.8 bolts and steel backing plates with a minimum thickness of 2 mm.
- T3.16.4 For the attachment of front hoop bracing, main hoop bracing and main hoop bracing support to the primary structure the use of one 10 mm metric grade 8.8 bolt is sufficient, if the bolt is on the centerline of the tube, see Figure 11.
- T3.16.5 When using bolted joints within the primary structure, no crushing of the laminate core material is permitted.
- T3.16.6 For the AIP to front bulkhead attachment, and if two panels or plates of the primary structure are bolted together, for each 200 mm of reference perimeter a minimum of one 8mm metric grade 8:8 bolt(s) must be used, rounded up to the next integer. Smaller, but more, bolts may be used, if equivalency is shown. The bolts must be evenly distributed over the circumference using good engineering practices. The reference perimeter is the outside perimeter of the attached part at the connection. The bolts are considered critical fasteners and must comply with [T10](#).




Figure 11: Bolted roll hoop bracing support

T3.17 Impact Attenuator (IA)

T3.17.1 Each vehicle must be equipped with an IA [assembly consisting of an IA and AIP](#).

T3.17.2 The IA must be:

- Installed forward of the front bulkhead.
- At least 100 mm high and 200 mm wide for a minimum distance of 200 mm forward of the front bulkhead.
- No portion of the required 100 X 200 X 200 mm³ volume of the IA can be positioned more than 350 mm above the ground
- Not able to penetrate the front bulkhead in the event of an impact.
- Attached securely and directly to the AIP.
- Not part of the non-structural bodywork.
- Designed with a closed front section.
- Cannot be wider or higher than the AIP.

T3.17.3 [The baseline design for the AIP is a 1.5 mm solid steel or 4.0 mm solid aluminum plate.](#)

- If the IA and AIP (IA assembly) are bolted to the front bulkhead, it must be the same size as the outside dimensions of the front bulkhead.
- If it is welded to the front bulkhead, it must extend at least to the centerline of the front bulkhead tubing in all directions.
- The AIP must not extend past the outside edges of the front bulkhead.

T3.17.4 Alternative AIP designs are permissible if equivalency to [T3.17.3](#) is proven, either by physical testing as in [T3.19.2](#).

T3.17.5 [The IA may be attached to the AIP by a minimum of four 8 mm metric grade 8.8 bolts that are considered critical fasteners and must comply with \[T10\]\(#\). Attachment\(s\) using adhesive must be able to carry a load of 60 kN in any direction.](#)

T3.17.6 The attachment of the IA assembly must be designed to provide an adequate load path for transverse and vertical loads in the event of off-center and off-axis impacts. Segmented foam attenuators must have the segments bonded together to prevent sliding or parallelogramming.

T3.17.7 A team may use one of the “standard” FSAE IAs, in order to avoid testing, provided that:

- if the front bulkhead width is larger than 400mm and/or its height is larger than 350mm a diagonal or X-bracing that is a front bulkhead support tube or an approved equivalent per T3.2, must be included in the front bulkhead. Or equivalent for monocoque bulkheads.
- must use a 1.5 mm solid steel AIP that is welded along its full perimeter to a steel bulkhead or use a 4 mm solid aluminum AIP that is bolted to any bulkhead with a minimum of eight 8 mm metric grade 8.8 bolts.
- if the “standard” honeycomb IA is used, the IA must be of pre-crushed type.
- adhesive used to mount the “standard” IA to the AIP must have a shear strength of at least 24 MPa, also rule T3.2.8 must be satisfied.

T3.17.8 If the standard IA is used, but does not comply with the requirements of T3.17.7, physical testing must be carried out to prove that the AIP does not permanently deflect more than 25 mm.

T3.18 Impact Attenuator Data Requirement

T3.18.1 All teams must submit an IA data report using the Impact Attenuator Data (IAD) template provided at the competition website.

T3.19 Impact Attenuator Test Requirements

T3.19.1 The IA assembly, when mounted on the front of a vehicle with a total mass of 300 kg and impacting a solid, non-yielding impact barrier with a velocity of impact of 7 m/s, must meet the following requirements:

- Decelerate the vehicle at a rate not exceeding 20 g average and 40 g peak.
- The energy absorbed in this event must meet or exceed 7350 J.
- Teams using the standard IA are not required to submit test data with their IAD report, but all other requirements must be included.

Equivalent (higher) test velocities are only allowed to accommodate for a lower total testing mass, as long as the energy absorbed is 7350 J or more. If these requirements cannot be met, a team must use the standard IA.

T3.19.2 During the IA test:

- The IA must be attached to the AIP using the intended vehicle attachment method.
- The IA assembly must be attached to a test fixture that has geometry representative of the intended chassis and equal or higher stiffness and strength representative of the intended chassis. When alternative materials are used for the AIP, the test fixture must be a copy of the intended primary structure (i.e. materials, lay-up, joining methods).
- There must be at least 50 mm clearance rearwards of the AIP to the test fixture.
- No part of the AIP may permanently deflect more than 25 mm beyond the position of the AIP before the test.

T3.19.3 Teams using IAs (typically structural noses) directly attached to the front bulkhead, which shortcut the load path through the bulk of the AIP, must conduct an additional test. This test must prove that the AIP can withstand a load of 120 kN (300 kg multiplied by 40 g), where the load applicator matches the minimum IA dimensions.

T3.19.4 Vehicles with aerodynamic devices and/or sensors in front of the front bulkhead must not exceed the peak deceleration of T3.19.1 for the combination of their IA assembly and the

non-crushable object(s). One of the following three methods may be used to prove the design does not exceed 120 kN:

- Physical testing of the IA assembly including any attached non-crushable object(s) or structurally representative dummies thereof in front of the AIP. When non-crushable object(s) are located in front view of the AIP, physical testing is required.
- Combining the peak force from physical testing of the IA assembly with the failure load for the mounting of the non-crushable object(s), calculated from fastener shear and/or link buckling.
- Combining the “standard” IA peak load of 95 kN with the failure load for the mounting of the non-crushable object(s), calculated from fastener shear and/or link buckling.

T3.19.5 Dynamic testing (sled, pendulum, drop tower, etc.) of the IA may only be conducted at a dedicated test facility. This facility may be part of the university, but must be supervised by professional staff. Teams are not allowed to design their own dynamic test apparatus.

T3.19.6 When using acceleration data from the dynamic test, the average deceleration must be calculated based on the raw unfiltered data. If peaks above the 40 g limit are present in the data, a 100 Hz, 3rd order, low pass Butterworth (−3 dB at 100 Hz) filter may be applied.

T3.19.7 Conducting an IA test by using a manned student vehicle prototype to drive (powered or unpowered) into any structure, will result in de-registration of the team from the competition.

T3.20 Non-Crushable Objects

T3.20.1 All non-crushable objects (e.g. pedals, master cylinders, hydraulic reservoirs) must be rearward of the rearmost plane of the front bulkhead and at least 25 mm behind the AIP at any time, except for environment perception sensors, aerodynamic devices and their mountings.

T4 COCKPIT

T4.1 Cockpit Opening

T4.1.1 The size of the cockpit opening needs to be sufficient for the template shown on the left in Figure 11 to pass vertically from the opening below the top of the side impact structure when held horizontally. The template may be moved fore and aft.

T4.1.2 If the side impact structure is not made of tubes, the template must pass until it is 320 mm above the lowest inside chassis point between the front and main hoop.

T4.1.3 The steering wheel, seat and all padding may be removed for the template to fit. Any other parts may only be removed if they are integrated with the steering wheel.

T4.2 Cockpit Internal Cross Section

T4.2.1 The cockpit must provide a free internal cross section sufficient for the template shown on the right in Figure 12 to pass from the cockpit opening to a point 100 mm rearwards of the face of the rearmost pedal in an inoperative position. The template may be moved up and down. Adjustable pedals must be in their most forward position.

- | | |
|--------|---|
| T4.2.2 | The steering wheel and any padding that can be removed without the use of tools while the driver is seated may be removed for the template to fit. |
| T4.2.3 | The driver's feet and legs must be completely contained within the primary structure when the driver is seated normally and the driver's feet are touching the pedals. In the side and front views, any part of the driver's feet or legs must not extend above or outside of this structure. |

T4.3 Percy (95th percentile male)

- T4.3.1 When seated normally and restrained by the driver's restraint system, the helmet of a 95th percentile male and all of the team's drivers must, see Figure 13:
- Be a minimum of 50 mm away from the straight line drawn from the top of the main hoop to the top of the front hoop.
 - Be a minimum of 50 mm away from the straight line drawn from the top of the main hoop to the lower end of the main hoop bracing if the bracing extends rearwards.
 - Be no further rearwards than the rear surface of the main hoop if the main hoop bracing extends forwards.




Figure 12: Cockpit opening template (left) and cockpit internal cross section template (right)

- T4.3.2 The 95th percentile male is represented by a two dimensional figure consisting of two circles of 200 mm diameter (one representing the hips and buttocks and one representing the shoulder region) and one circle of 300 mm (representing the head with helmet).
- T4.3.3 The two 200 mm circles are connected by a straight line measuring 490 mm. The 300 mm circle is connected by a straight line measuring 280 mm with the upper 200 mm circle.
- T4.3.4 The figure has to be positioned in the vehicle as follows, see Figure 14:
- The seat adjusted to the rearmost position
 - The pedals adjusted to the front-most position

- The bottom 200 mm circle is placed on the seat bottom. The distance between the center of the circle and the rearmost actuation face of the pedals must be minimum 915 mm.
- The middle circle positioned on the seat back
- The upper 300 mm circle is positioned 25 mm away from the head restraint.

T4.4 Side Tubes

- T4.4.1 If there is any chassis member alongside the driver at the height of the neck of any of the drivers in the team, a metal tube or piece of sheet metal must be attached to the chassis to prevent the driver's shoulders from passing under that chassis member.




Figure13: Minimum helmet clearance




Figure 14: Percy placement

T4.5 Driver's Harness Attachment

- T4.5.1 Any harness attachment to a monocoque must be using one 10 mm metric grade 8.8 bolt or two 8 mm metric grade 8.8 bolts (or bolts of an equivalent norm) and steel backing plates with a minimum thickness of 2 mm.
- T4.5.2 Any harness that is fastened to the primary structure using brackets must use two 8 mm metric grade 8.8 or stronger fasteners.
- T4.5.3 It must be proven that the attachments for shoulder and lap belts can support a load of 13 kN and the attachment points of the anti-submarine belts can support a load of 6.5 kN.
- T4.5.4 If the lap belts and anti-submarine belts are attached less than 100 mm apart, these must support a total load of 19.5 kN.
- T4.5.5 If the belts are attached to a laminated structure or the mounting brackets and tabs are not made from steel at least 1.6 mm or aluminum at least 4.0 mm thick, physical testing is required. The following requirements must be met:
- Load is applied to a test sample representing the tubular or laminated structure and must use the same brackets and tabs
 - Edges of the test fixture supporting the sample must be a minimum of 125 mm from the load application point.
 - The width of the shoulder harness test sample must not be any wider than the shoulder harness panel height used to show equivalency for the shoulder harness mounting bar.
 - Designs with attachments near a free edge may not support the free edge during the test.
 - Harness loads must be tested with the worst case for the range of the angles specified for the driver's harness.

T4.6 Driver's Seat

- T4.6.1 The lowest point of the driver's seat must in the side view not extend below the upper face of the lowest side impact structure member or have a longitudinal tube (or tubes) that meet the material requirements for the side impact structure (T3.2), passing underneath the lowest point of the seat.
- T4.6.2 Adequate heat insulation must be provided to ensure that the driver is not able to contact any parts of the vehicle with a surface temperature above 60°C. The insulation may be external to the cockpit or incorporated with the driver's seat or firewall. The design must address all three types of heat transfer with the following minimum requirements between the heat source and the part that the driver could contact:
- (a) Conduction insulation by:
 - No direct contact, or
 - A heat resistant, conduction insulation material with a minimum thickness of 8 mm.
 - (b) Convection insulation by a minimum air gap of 25 mm.
 - (c) Radiation insulation by:
 - i. A solid metal heat shield with a minimum thickness of 0.4 mm or
 - ii. Reflective foil or tape when combined with T4.6.2.a.ii.

T4.7 Floor Closeout

- T4.7.1 All vehicles must have a floor closeout made of one or more panels, which separate the driver from the ground.
- T4.7.2 The closeout must extend from the front bulkhead to the firewall.
- T4.7.3 The panels must be made of a solid, non-brittle material.
- T4.7.4 If multiple panels are used, gaps between panels may not exceed 3 mm.

T4.8 Firewall

- T4.8.1 A firewall must separate the driver compartment from all components of the fuel supply system, hydraulic fluid (except brake system and dampers), flammable liquids, the low voltage battery and any TS component ([see EV1.1.1](#)).
- T4.8.2 The firewall must cover any straight line between the parts mentioned in [T4.8.1](#) and any part of the tallest driver below a plane 100 mm above the bottom of the helmet.
- T4.8.3 The firewall must be a non-permeable surface made from a rigid, fire resistant material ([see T1.2.1](#)) which must be rigidly mounted to the vehicle's structure.
- T4.8.4 Any firewall must seal completely against the passage of fluids, especially at the sides and the floor of the cockpit.
- T4.8.5 Pass-throughs for wiring, cables, etc. are permitted if grommets are used to seal the pass-through.
- T4.8.6 Multiple panels may be used to form the firewall but must overlap at least 5 mm and be sealed at the joints. Any sealing material must not be vital to the structural integrity of the firewall.
- T4.8.7 [EV ONLY] The TS firewall between driver and TS components must be composed of two layers:
 - One [solid](#) layer, facing the TS side, must be made of aluminum with a thickness of at least 0.5 mm. This part of the TS firewall must be grounded according to [EV3.1](#).
 - The second layer, facing the driver, must be made of an electrically insulating and fire retardant material ([see T1.2.1](#)). The second layer must not be made of CFRP.
 - The thickness of the second layer must be sufficient to prevent penetrating this layer with a 4 mm wide screwdriver and 250 N of force.

A sample of the tractive system firewall must be presented at technical inspection.
- T4.8.8 [EV ONLY] Conductive parts (except for the chassis) may not protrude through the TS firewall or must be properly insulated on the driver's side. [The driver must not be able to touch uninsulated firewall mounting points while operating the vehicle.](#)
- T4.8.9 [EV ONLY] TS parts outside of the envelope ([see EV4.4.3](#)) do not need a firewall.

T4.9 Accessibility of Controls

T4.9.1 All vehicle controls must be operated from inside the cockpit without any part of the driver, e.g. hands, arms or elbows, being outside the vertical planes tangent to the outermost surface of the side impact structure.

T4.10 Driver Visibility

T4.10.1 The driver must have adequate visibility to the front and sides of the vehicle. Seated in a normal driving position, the driver must have a minimum field of vision of 100° to either side. The required visibility may be obtained by the driver turning their head and/or the use of mirrors.

T4.10.2 If mirrors are required to meet T4.10.1, they must remain in place and be adjusted to enable the required visibility throughout all dynamic events.

T4.11 Driver Egress

T4.11.1 All drivers must be able to exit to the side of the vehicle in less than 5 s with the driver in the fully seated position, hands in the driving position on the connected steering wheel (in all possible steering positions) and wearing the required driver equipment as in T13.3. The egress time will stop when the driver has both feet on the ground.

T5 DRIVER RESTRAINT SYSTEM**T5.1 Definitions**

T5.1.1 6-point system – Consists of a two-piece lap belt (minimum width 50 mm), two shoulder straps (minimum width 75 mm) and two leg or anti-submarine straps (minimum width 50 mm).

T5.1.2 7-point system – Same as the 6-point system except it has three anti-submarine straps.

T5.1.3 Upright driving position – Position with a seat back angled at 30° or less from the vertical as measured along the line joining the two 200 mm circles of the 95th percentile male template as defined in T4.3 and positioned per T4.3.4.

T5.1.4 Reclined driving position – Position with a seat back angled at more than 30° from the vertical as measured along the line joining the two 200 mm circles of the 95th percentile male template as defined in T4.3 and positioned per T4.3.4.

T5.2 Belts - General

T5.2.1 All drivers must use a 6-point or 7-point restraint harness meeting the following specifications:

- All driver restraint systems must meet SFI Specification 16.1, SFI Specification 16.5, SFI Specification 16.6, FIA specification 8853/2016.
- The belts must bear the appropriate dated labels.
- The material of all straps must be in perfect condition.
- There must be a single metal-to-metal latch type quick release for all straps.

- All lap belts must incorporate a tilt lock adjuster (“quick adjuster”). A tilt lock adjuster in each portion of the lap belt is highly recommended. Lap belts with “pull-up” adjusters are recommended over “pull-down” adjusters.
- Vehicles with a “reclined driving position” must have either anti-submarine belts with tilt lock adjusters (“quick adjusters”) or have two sets of anti-submarine belts installed.
- The shoulder harness must be the “over-the-shoulder type”. Only separate shoulder straps are permitted (i.e. “Y”-type shoulder straps are not allowed). The “H”-type configuration is allowed.
- The shoulder harness straps must be threaded through the three bar adjusters in accordance with the manufacturer’s instructions.
- When a HANS device is used by the driver, FIA certified 50 mm wide shoulder harnesses are allowed.

T5.2.2 SFI spec harnesses must be replaced following December 31st of the 2nd year after the date of manufacture as indicated by the label. FIA spec harnesses must be replaced following December 31st of the year marked on the label.

Note: Teams competing at Formula Bharat may extend the use of the harness until January 31st of the 3rd year after the date of manufacture as indicated by the label.

T5.2.3 The restraint system must be worn tightly at all times.

T5.3 Belt, Strap and Harness Installation - General

T5.3.1 The lap belt, shoulder harness and anti-submarine strap(s) must be securely mounted to the primary structure. This structure and any guide or support for the belts must meet the minimum requirements of T3.2.

T5.3.2 Harnesses, belts and straps must not pass through a firewall, i.e. all harness attachment points must be on the driver’s side of any firewall.

T5.3.3 The attachment of the driver’s restraint system to a monocoque structure requires an approved SES per T3.6. The lap belts and anti-submarine belts must not be routed over the sides of the seat. Where the belts or harness pass through a hole in the seat, the seat must be rolled or grommited to prevent chafing of the belts.

T5.4 Lap Belt Mounting

T5.4.1 The lap belt must pass around the pelvic area below the anterior superior iliac spines (the hip bones).

T5.4.2 The lap belts should come through the seat at the bottom of the sides of the seat to maximize the wrap of the pelvic surface and continue in a straight line to the anchorage point.

T5.4.3 In the side view, the lap belt must be capable of pivoting freely by using either a shouldered bolt or an eye bolt attachment.

T5.4.4 With an “upright driving position”, in the side view the lap belt must be at an angle of between 45° and 65° to the horizontal.

T5.4.5 With a “reclined driving position”, in the side view the lap belt must be between an angle of 60° and 80° to the horizontal.

T5.4.6 The centerline of the lap belt at the seat bottom should be between 0 mm to 76 mm forward of the seat back to seat bottom junction as in Figure 14 (below).

T5.5 Shoulder Harness

T5.5.1 The shoulder harness must be mounted behind the driver to a structure that meets the requirements of the primary structure. However, it cannot be mounted to the main hoop bracing or attendant structure without additional bracing to prevent loads being transferred into the main hoop bracing.

T5.5.2 If the harness is mounted to a tube that is not straight, the joints between this tube and the structure to which it is mounted must be reinforced in the side view by triangulation tubes to prevent torsional rotation of the harness mounting tube. Supporting calculations are required. Analysis method: Use 7 kN load per attachment and the range of angles in T5.5.5, calculate that the bent shoulder harness bar triangulation stresses are less than as welded yield strength T3.2.4 for combined bending and shear and does not fail in column buckling. If the team chooses not to perform the strength analysis T3.2.6 will apply.

T5.5.3 The strength of any shoulder harness bar and bracing tubes must be proven in the relevant tab of the team's SES submission.

T5.5.4 The shoulder harness mounting points must be between 180 mm and 230 mm apart, measured center to center.

T5.5.5 From the driver's shoulders rearwards to the mounting point or structural guide, the shoulder harness must be between 10° above the horizontal and 20° below the horizontal as in Figure 14.




Figure 15: Lap belt and shoulder harness mounting

T5.6 Anti-Submarine Belt Mounting

T5.6.1 The anti-submarine belts of a 6 point harness should be mounted in one of the following setups:

- With the belts going vertically down from the groin, or angled up to 20° rearwards. The anchorage points should be approximately 100 mm apart.
- With the anchorage points on the primary structure at or near the lap belt anchorages, the driver sitting on the anti-submarine belts and the belts coming up around the groin to the release buckle.

T5.7 Head Restraint

- T5.7.1 A head restraint must be provided on the vehicle to limit the rearward motion of the driver's head.
- T5.7.2 The head restraint must:
- Be vertical or near vertical in the side view.
 - Be padded with an energy absorbing material with a minimum thickness of 40 mm that meets either the SFI 45.2 standard, or is listed in the FIA technical list no 17 as a type B material for single seater cars.
 - Have a minimum width and height of 150 mm.
 - Be located so that for each driver:
 - The restraint is no more than 25 mm away from the back of the driver's helmet, with the driver in their normal driving position.
 - The contact point of the back of the driver's helmet on the head restraint is no less than 50 mm from any edge of the head restraint.
- T5.7.3 The head restraint, its attachment and its mounting must withstand a force of 890 N applied in the rearward direction at any point on its surface.

T5.8 Roll Bar Padding

- T5.8.1 Any portion of the roll bar, roll bar bracing or chassis which might be contacted by the driver's helmet must be covered with a minimum thickness of 12 mm of padding which meets SFI spec 45.1 or FIA 8857-2001.

T5.9 Driver's Leg Protection

- T5.9.1 All moving suspension and steering components and other sharp edges inside the cockpit between the front hoop and a vertical plane 100 mm rearward of the pedals, must be shielded with solid material.
- T5.9.2 Covers over suspension and steering components must be removable to allow inspection of the mounting points.

T6 BRAKE SYSTEM

T6.1 Brake System - General

- T6.1.1 The vehicle must be equipped with a hydraulic brake system that acts on all four wheels and is operated by a single control.
- T6.1.2 The brake system must have two independent hydraulic circuits such that in the case of a leak or failure at any point in the system, effective braking power is maintained on at least two wheels. Each hydraulic circuit must have its own fluid reserve, either by the use of separate reservoirs or by the use of a dammed reservoir.
- T6.1.3 [The brake system must be sealed to prevent leakage.](#)
- T6.1.4 A single brake acting on a limited-slip differential is acceptable.

- T6.1.5 “Brake-by-wire” systems are prohibited.
- T6.1.6 Unarmored plastic brake lines are prohibited.
- T6.1.7 The brake system must be protected from failure of the drivetrain ([see T7.3.2](#)) from touching any movable part and from minor collisions.
- T6.1.8 In the side view any portion of the brake system that is mounted on the sprung part of the vehicle must not project below the lower surface of the chassis.
- T6.1.9 [Any part of the brake system must be within the surface envelope, see T1.1.18.](#)
- T6.1.10 The brake pedal and its mounting must be designed to withstand a force of 2 kN without any failure of the brake system or pedal box. This may be tested by pressing the pedal with the maximum force that can be exerted by any official when seated normally.
- T6.1.11 The brake pedal, [including pedal face](#), must be fabricated from steel or aluminum or machined from steel, aluminum or titanium.
- T6.1.12 [EV ONLY] The first 90% of the brake pedal travel may be used to regenerate brake energy without actuating the hydraulic brake system. The remaining brake pedal travel must directly actuate the hydraulic brake system, but brake energy regeneration may remain active.

T6.2 Brake Over-Travel Switch (BOTS)

- T6.2.1 A brake pedal over-travel switch must be installed on the vehicle as part of the shutdown circuit, as in [EV6](#) or [CV4.1](#). This switch must be installed so that in the event of a failure in [at](#) least one of the brake circuits the brake pedal over travel will result in the shutdown circuit being opened. This must function for all possible brake pedal and brake balance settings without damaging any part of the vehicle.
- T6.2.2 Repeated actuation of the switch must not close the shutdown circuit, and it must be designed so that the driver cannot reset it.
- T6.2.3 [The BOTS must be a push-pull, push-rotate or flip type mechanical switch. It may consist of a series connection of switches.](#)

T6.3 Brake Light

- T6.3.1 The vehicle must be equipped with one brake light that is illuminated if and only if
- the hydraulic brake system is actuated
 - [EV ONLY] or the electric brake system is actuated ([see EV2.2.2](#))
- T6.3.2 The brake light must meet the following requirements:
- A red light with a black background.
 - Rectangular, triangular or near round shape.
 - Minimum shining surface of 15 cm² with even luminous intensity.
 - Clearly visible from the rear in very bright sunlight.
 - When LED lights are used without a diffuser, they [must](#) not be more than 20 mm apart.
 - If a single line of LEDs is used, the minimum length is 150 mm.

- T6.3.3 In the side view, the brake light must be oriented vertical or near vertical and mounted between the wheel centerline and driver's shoulder level. Viewed from the back it should be positioned approximately at the vehicle's centerline.

T7 POWERTRAIN

T7.1 Transmission and Drive

- T7.1.1 Any transmission and drivetrain may be used.
- T7.1.2 Movement of the vehicle without a person in the vehicle and with the master switch(es) in the off position must be possible.

T7.2 Coolant Fluid and System Sealing

- T7.2.1 [CV ONLY] Water-cooled engines must only use plain water.
- T7.2.2 [EV ONLY] TS components may only use plain water, air or oil as the coolant.
- T7.2.3 Cooling systems using plain water (except outboard wheel motors and their cooling hoses) must have a heat resistant (Permanently rated for at least 100 °C), rigid and rigidly mounted cover [which covers any part of the tallest driver below a plane 100 mm above the bottom of the helmet](#).
- T7.2.4 Any cooling or lubrication system must be sealed to prevent leakage.
- T7.2.5 Separate catch cans must be employed to retain fluids other than plain water from any vents for the cooling system or combustion engine lubrication system. Each catch-can must have a minimum volume of 10% of the fluid being contained or 900 ml whichever is greater.
- T7.2.6 Any vent for other systems containing liquid lubricant or coolant must have a catch-can with a minimum volume of 10% of the fluid being contained or 100 ml, whichever is greater.
- T7.2.7 All parts of the engine cooling, [motor\(s\) cooling](#) and lubrication system, including their mountings, must be rated for at least 120 °C or the temperatures the respective fluid may reach, whichever is higher.
- T7.2.8 Catch cans must be rigidly mounted to the chassis and located rearwards of the firewall below the driver's shoulder level.
- T7.2.9 Any catch can must vent through a hose with a minimum internal diameter of 3 mm down to the bottom level of the chassis and must exit outside the bodywork.

T7.3 Drive Train Shields and Guards

- T7.3.1 The lowest point of any lubrication system can only be lower than the line between the lowest point of the main hoop and the lowest chassis member behind the lubrication system if it is protected from hitting the ground by a structure mounted directly to the chassis.
- T7.3.2 Exposed rotating final drivetrain parts, such as gears, clutches, chains and belts must be fitted with scatter shields. Scatter shields and their mountings must:

- Be constructed of non-perforated 2 mm steel or 3 mm aluminum alloy 6061-T6.
 - Be attached with 6 mm metric grade 8.8 or stronger and must comply with T10.1.
- T7.3.3 Scatter shields for high-speed rotating final drivetrain parts (such as electric motors, clutches, sprockets, gears etc.) that have an OEM casing that do not comply with T7.3.2 may be used, if material is added to achieve the minimum required thickness.
- T7.3.4 [EV ONLY] When an electrical motor casing is rotating around the stator or is perforated, a scatter shield must be included around the motor. This scatter shield must be at least 1 mm thick and made from aluminum alloy 6061-T6 or steel.
- T7.3.5 Scatter shields for chains and belts must be centered on the centerline of the chain or belt and remain aligned with the chain or belt under all conditions. The minimum width of the scatter shield should be at least three times the width of the chain or belt. The minimum material requirements are:
- For metallic chains and belts: 2 mm steel.
 - For non-metallic chains and belts: 3 mm aluminum alloy 6061-T6.
- T7.3.6 All fasteners attaching scatter shields and guards must be 6 mm metric grade 8.8 or stronger and must comply with T10.1.
- T7.3.7 Finger guards are required to cover any drivetrain parts that spin while the vehicle is stationary with the engine running. Finger guards may be made of lighter material, sufficient to resist finger forces. Mesh or perforated material may be used but must prevent the passage of a 12 mm diameter object through the guard.

T8 AERODYNAMIC DEVICES

T8.1 Definition Aerodynamic Device

- T8.1.1 A specifically designed structure mounted on the vehicle to guide the airflow around the vehicle, increasing the downforce acting on the vehicle and/or lowering its drag. The mounting of this structure is not regarded as an aerodynamic device, unless it is intentionally designed to be one.




Figure 16: Maximum dimensions and positioning of aerodynamic devices. The positioning space is further restricted ([see T2.1](#)).

T8.2 Restrictions for Aerodynamic Devices

T8.2.1 Height restrictions:

- All aerodynamic devices forward of a vertical plane through the rearmost portion of the front face of the driver head restraint support, excluding any padding, set to its most rearward position, must be lower than 500 mm from the ground.
- All aerodynamic devices in front of the front axle and extending further outboard than the most inboard point of the front tire/wheel must be lower than 250 mm from the ground.
- All aerodynamic devices rearward of a vertical plane through the rearmost portion of the front face of the driver head restraint support, excluding any padding, set to its most rearward position must be lower than 1.2 m from the ground.

T8.2.2 Width restrictions:

- All aerodynamic devices lower than 500 mm from the ground and further rearward than the front axle, must not be wider than a vertical plane touching the most outboard point of the front and rear wheel/tire.
- All aerodynamic devices higher than 500 mm from the ground, must not extend outboard of the most inboard point of the rear wheel/tire.

T8.2.3 Length restrictions:

- All aerodynamic devices must not extend further rearward than 250 mm from the rearmost part of the rear tires.
- All aerodynamic devices must not extend further forward than 700 mm from the fronts of the front tires.

T8.2.4 All restrictions must be fulfilled with the wheels pointing straight and with any suspension setup with or without a driver seated in the vehicle.

T8.3 Minimum Edge Radii of Bodywork and Aerodynamic Devices

T8.3.1 For all edges that could come into contact with any standing pedestrian without reaching to the vehicle, the minimum radius of the bodywork and aerodynamic devices is 3 mm for all forward facing edges and 1 mm for all other edges.

T8.4 Aerodynamic Devices Stability and Strength

T8.4.1 Any aerodynamic device must be able to withstand a force of 200 N distributed over a minimum surface of 225 cm² and not deflect more than 10 mm in the load carrying direction.

T8.4.2 Any aerodynamic device must be able to withstand a force of 50 N applied in any direction at any point and not deflect more than 25 mm.

T9 COMPRESSED GAS SYSTEMS AND HIGH PRESSURE HYDRAULICS

T9.1 Compressed Gas Cylinders and Lines

T9.1.1 Any system on the vehicle that uses a compressed gas as an actuating medium, [except for gas springs](#), must comply with the following requirements:

- The working gas must be non-flammable.
- The pressure inside compressed gas systems must not exceed 10 bar.
- Compressed gas cylinders/tanks may exceed the 10 bar limit, if a pressure regulator, which limits the output pressure to a maximum of 10 bar, is mounted directly onto them.
- Gas cylinders/tanks must be of proprietary manufacture, designed and built for the pressure being used. Gas cylinders/tanks must be certified and labeled or stamped appropriately.
- Gas cylinders/tanks and lines must be protected from rollover, collision from any direction, or damage resulting from the failure of rotating equipment.
- Gas cylinders/tanks and their pressure regulators must be located within the rollover protection envelope [T1.1.15](#).
- Gas cylinders/tanks and their pressure regulators, must be shielded from the driver. The shields must be steel or aluminum with a minimum thickness of 1 mm.
- Gas cylinders/tanks and their pressure regulators must be protected from damage by the driver or any moving parts.
- Gas cylinders/tanks must be securely mounted to the chassis, engine or transmission.
- The axis of the gas cylinder/tank must not point at the driver.

- Gas cylinders/tanks must be insulated from any heat sources.
- All used parts must be appropriate for the maximum possible operating pressure.

T9.2 High Pressure Hydraulic Pumps and Lines

T9.2.1 The driver and anyone standing outside the vehicle must be shielded from any hydraulic pumps and lines with line pressures of 2100 kPa or higher. The shields must be steel or aluminum with a minimum thickness of 1 mm. Brake lines are not considered as high pressure hydraulic lines.

T10 FASTENERS

T10.1 Critical Fasteners

T10.1.1 Critical fasteners are defined as bolts, nuts, and other fasteners utilized in the primary structure, the steering, braking, driver's harness, suspension systems and those specifically designated as critical fasteners in the respective rule.

T10.1.2 All threaded critical fasteners must be at least 4 mm metric grade 8.8 (OEM parts 3 mm metric grade 8.8), equivalent size or of that specified in the referencing rule, whichever is larger.

T10.1.3 All threaded critical fasteners must be of the type hexagon bolts (ISO 4017, ISO 4014 or an equivalent standard) or socket head cap screws (ISO 4762, DIN 7984, ISO 7379 or an equivalent standard.) including their fine-pitch thread versions.

T10.1.4 Any bolted joint in the primary structure and mounting of the TSAC to the chassis using either tabs or brackets, must have an edge distance ratio "e/D" of 1.5 or greater. "D" equals the hole diameter and "e" equals the distance from the hole centerline to the nearest free edge of the tab or bracket. Any tabs attaching suspension members to the primary structure are not required to meet this rule.

T10.1.5 [For steering and suspension systems, alternative fasteners are allowed if equivalency to T10.1.2 and T10.1.3 can be shown.](#)

T10.2 Securing Fasteners

T10.2.1 All critical fasteners must be secured from unintentional loosening by the use of positive locking mechanisms.

T10.2.2 The following methods are accepted as positive locking mechanisms:

- Correctly installed safety wiring.
- Cotter pins.
- Nylon lock nuts (ISO 7040, ISO 10512, EN 1663 or an equivalent standard) for locations where no temperature rating above 80 °C is required.
- Prevailing torque lock nuts (DIN 980, ISO 7042 or equivalent, and jet nuts or K-nuts).
- Locking plates.
- Tab washers.

Any locking mechanism based on pre-tensioning or an adhesive is not considered a positive locking mechanism.

- T10.2.3 Snap or retaining rings according to DIN 471, DIN 472, or equivalent standard are permitted in OEM applications and for securing bearings and springs given that they do not bear any loads under normal driving conditions.
- T10.2.4 A minimum of two full threads must project from any lock nut.
- T10.2.5 All spherical rod ends and spherical bearings on the steering or suspension must be in double shear or captured by having a screw/bolt head or washer with an outer diameter that is larger than the spherical bearing housing inner diameter.
- T10.2.6 Adjustable tie-rod ends must be constrained with a jam nut to prevent loosening.

T10.3 Self-made Fasteners

- T10.3.1 Teams that use self-made fasteners will need to present documentation with appropriate reasoning, calculations and testing during the mechanical inspection. A technical inspector may request for additional documentation should the material presented be deemed questionable.
- T10.3.2 Queries over self-made fasteners can be made directly to the Rules Committee prior to the competition.

T11 ELECTRICAL COMPONENTS

T11.1 Low Voltage System (LVS)

- T11.1.1 The Low Voltage System (LVS) is defined as
- [CV ONLY] all electrical circuits of the vehicle.
 - [EV ONLY] every electrical part that is not part of the TS ([see EV1.1.1](#))
- T11.1.2 The maximum permitted voltage that may occur between any two electrical connections in the LVS is 60 V DC or 50 V AC RMS.
- T11.1.3 All LVS parts must be adequately insulated.
- T11.1.4 [CV ONLY] The following systems are excluded from the LVS voltage limit ([see T11.1.2](#)):
- High voltage systems for ignition
 - High voltage systems for injectors
 - Voltages internal to OEM charging systems designed for <60 V DC output.
- T11.1.5 [EV ONLY] The LVS must not use orange wiring or conduit.
- T11.1.6 [EV ONLY] The LVS must be grounded to the chassis.

T11.2 Master Switches

- T11.2.1 Master switches ([see T11.3](#) and [EV6.2](#)) must be a mechanical switch of the rotary type, with a red, removable handle. The handle must have a width of at least 50 mm and must only be removable in an electrically open position. **The handle must have the car number mentioned on it.** They must be direct acting, i.e. they must not act through a relay or logic.

T11.2.2 Master switches must be located on the right side of the vehicle, in proximity to the main hoop, at the 95th percentile male driver's shoulder height, as defined in [T4.3](#), and be easily actuated from outside the vehicle.

The center of any master switch must not be mounted lower than the vertical distance of the template's ([see T4.3](#)) middle circle center to the ground surface multiplied by 0.8.

T11.2.3 The "ON" position of the switch must be in the horizontal position and must be marked accordingly. The "OFF" position of the master switch must also be clearly marked.

T11.2.4 Master switches must be rigidly mounted to the vehicle and must not be removed during maintenance.

T11.2.5 [EV ONLY] Master switches must be mounted next to each other.

T11.3 Low Voltage Master Switch (LVMS)

T11.3.1 An LVMS according to [T11.2](#) must completely disable

- [EV ONLY] power to the LVS
- [CV ONLY] power from the Low Voltage (LV) battery and the alternator to the LVS

T11.3.2 The LVMS must be mounted in the middle of a completely red circular area of ≥ 50 mm diameter placed on a high contrast background.

T11.3.3 The LVMS must be marked with "LV" and a symbol showing a red spark in a white edged blue triangle.

T11.4 Shutdown Buttons

T11.4.1 A system of three shutdown buttons must be installed on the vehicle.

T11.4.2 Each shutdown button must be a push-pull or push-rotate mechanical emergency switch where pushing the button opens the shutdown circuit ([see EV6.1](#) and [CV4.1](#)).

T11.4.3 One button must be located on each side of the vehicle behind the driver's compartment at approximately the level of the driver's head. The minimum allowed diameter of the shutdown buttons on both sides of the vehicle is 40 mm. The buttons must be easily reachable from outside the vehicle.

T11.4.4 One shutdown button serves as a cockpit-mounted shutdown button and must

- have a minimum diameter of 24 mm
- be located in easy reach of a belted-in driver
- be alongside of the steering wheel and unobstructed by the steering wheel or any other part of the vehicle

T11.4.5 The international electrical symbol consisting of a red spark on a white-edged blue triangle must be affixed in close proximity to each shutdown button.

T11.4.6 Shutdown buttons must be rigidly mounted to the vehicle and must not be removed during maintenance.

T11.4.7 [Shutdown buttons must be red.](#)

T11.5 Inertia Switch

- T11.5.1 An inertia switch must be part of the shutdown circuit (see [EV6.1](#) and [CV4.1](#)) such that an impact will result in the shutdown circuit being opened. The inertia switch must latch until manually reset.
- T11.5.2 The device must trigger due to an omni-directional peak acceleration of ≤ 8 g for a half sine test pulse of ≥ 50 ms length and ≤ 13 g for a half sine test pulse of ≥ 20 ms length. The “Sensata Resettable Crash Sensor” should meet those requirements.
- T11.5.3 The device must not include any semiconductor components.
- T11.5.4 The device must be rigidly attached to the vehicle and installed according to manufacturer specification to the vehicle. It must be possible to demount the device so that its functionality may be tested by shaking it.
- T11.5.5 Inertia switch should be directly acting. External relay circuits are prohibited.

T11.6 Brake System Plausibility Device (BSPD)

- T11.6.1 A standalone non-programmable circuit, the BSPD, must open the shutdown circuit (see [EV6.1](#) and [CV4.1](#)) when hard braking occurs, whilst
- [EV ONLY] ≥ 5 kW power is delivered to the motors.
 - [CV ONLY] the throttle position is more than 25 % over idle position.
- The shutdown circuit must remain open until power cycling the LVMS or the BSPD may reset itself if the opening condition is no longer present for more than 10 s.
- T11.6.2 The action of opening the shutdown circuit must occur if the implausibility is persistent for more than 500 ms.
- T11.6.3 The BSPD must be directly supplied (see [T11.3.1](#)) from the LVMS (see [T11.3](#)).
- T11.6.4 Standalone is defined as there is no additional functionality implemented on all required Printed Circuit Boards (PCBs). The interfaces must be reduced to the minimum necessary signals, i.e. power supply, required sensors and the shutdown circuit. Supply and sensor signals must not be routed through any other devices before entering the BSPD.
- T11.6.5 To detect hard braking, a brake system pressure sensor must be used. The threshold must be chosen such that there are no locked wheels and the brake pressure is ≤ 30 bar.
- T11.6.6 [EV ONLY] To measure power delivery, a DC circuit current sensor only must be used. The threshold must be chosen to an equivalent of ≤ 5 kW for maximum TS voltage.
- T11.6.7 It must be possible to separately disconnect each sensor signal wire for technical inspection.
- T11.6.8 All necessary signals are System Critical Signal (SCS) (see [T11.9](#)).
- T11.6.9 [EV ONLY] The team must prove the function of the BSPD during technical inspection by sending an appropriate signal that represents the current, in order to achieve ≤ 5 kW whilst pressing the brake pedal. This test must prove the functionality of the complete BSPD except for any commercially available current sensors.

T11.6.10 [EV ONLY] The BSPD including all required sensors must not be installed inside the accumulator container.

T11.7 LV Batteries

T11.7.1 LV batteries are all batteries connected to the LVS.

T11.7.2 LV batteries must be securely attached to the chassis and located within the rollover protection envelope ([see T1.1.15](#)).

T11.7.3 Any wet-cell battery located in the driver compartment must be enclosed in a non-conductive, water proof (according to IPX7 or higher, IEC 60529) and acid resistant container.

T11.7.4 LV batteries must have a rigid and sturdy casing. **For EV ONLY:**

- The enclosure must be fire retardant ([see T1.2.1](#)).
- Must comply with [EV4.5.1](#).
- If the enclosure is in the TS loadpath; additionally, the enclosure and its mounting must comply with [EV5.5.9](#).

T11.7.5 Completely closed LV battery cases must have an overpressure relief. Venting gases must be separated from the driver by a firewall.

T11.7.6 Ungrounded terminals must be insulated.

T11.7.7 LV batteries must be protected from short circuits, not more than 100 mm from ungrounded terminals.

T11.7.8 Battery packs based on lithium chemistry other than lithium iron phosphate (LiFePO₄):

- Must have a fire retardant casing ([see T1.2.1](#)).
- Must include overcurrent protection that trips at or below the maximum specified discharge current of the cells.
- Must include over temperature protection of at least 30% of the cells, meeting [EV5.8.3](#), that trips when any cell leaves the allowed temperature range according to the manufacturer's datasheet, but not more than 60°C, for more than 1 s and disconnects the battery.
- Must include voltage protection of all cells that trips when any cell leaves the allowed voltage range according to the manufacturer's datasheet for more than 500 ms and disconnects the battery.
- It must be possible to display all cell voltages and measured temperatures, e.g. by connecting a laptop.
- Must meet [EV5.8.10](#).
- Signals needed to fulfill these requirements are SCS ([see T11.9](#)).

T11.8 Accelerator Pedal Position Sensor (APPS)

T11.8.1 T11.8 only apply for electric vehicles (see chapter EV), or internal combustion vehicles using Electronic Throttle Control (ETC) ([see CV1.6](#)).

T11.8.2 The APPS must be actuated by a foot pedal.

- T11.8.3 Pedal travel is defined as the percentage of travel from fully released position to a fully applied position where 0% is fully released and 100% is fully applied.
- T11.8.4 The foot pedal must return to the 0% position when not actuated. The foot pedal must have a positive stop preventing the mounted sensors from being damaged or overstressed. Two springs must be used to return the foot pedal to the 0% position and each spring must work when the other is disconnected. Springs in the APPS are not accepted as return springs.
- T11.8.5 At least two separate sensors must be used as APPSs. [The sensors may share the housing.](#)
- T11.8.6 If analog sensors are used, they must have different, non-intersecting transfer functions. A short circuit between the signal lines must always result in an implausibility according to [T11.8.9](#).
- T11.8.7 The APPS signals are SCSs ([see T11.9](#)).
- T11.8.8 If an implausibility occurs between the values of the APPSs and persists for more than 100 ms
- [EV ONLY] The power to the motor(s) must be immediately shut down completely. It is not necessary to completely deactivate the tractive system, the motor controller(s) shutting down the power to the motor(s) is sufficient.
 - [CV ONLY] The power to the electronic throttle must be immediately shut down.
- T11.8.9 Implausibility is defined as a deviation of more than ten percentage points pedal travel between any of the used APPSs or any failure according to [T11.9](#).
- T11.8.10 If three sensors are used, then in the case of an APPS implausibility, any two sensors that are plausible may be used to define the torque target and the 3rd APPS may be ignored.
- T11.8.11 It must be possible to separately disconnect each APPS signal wire to check all functionalities.
- T11.8.12 A fully released accelerator pedal must result in:
- [EV ONLY] A wheel torque of ≤ 0 N m
 - [CV ONLY] An idle position or lower throttle set-point. This may only be exceeded during a gearshift for a maximum of 500ms.

T11.9 System Critical Signals (SCSs)

- T11.9.1 SCS are defined as all electrical signals which
- Influence actions on the shutdown circuit ([see CV4.1](#) and [EV6.1](#)).
 - Influence the wheel torque.
 - [EV ONLY] Influence indicators according to [EV5.8.9](#), [EV4.10](#) or [EV6.3.7](#).
- T11.9.2 Any of the following SCS single failures must result in a safe state of all connected systems:
- (a) Failures of signals transmitted by cable:
- Open circuit
 - Short circuit to ground

(b) Failures of analog sensor signals transmitted by cable:

- Short circuit to supply voltage

(c) Failures of sensor signals used in programmable devices:

- Implausibility due to out of range signals, e.g. mechanically impossible angle of an angle sensor.

(d) Failures of digitally transmitted signals by cable or wireless:

- Data corruption (e.g. checked by a checksum)
- Loss and delay of messages (e.g. checked by transmission time outs)

Signals might be a member of multiple signal classes, e.g. analog signals transmitted by cable might be a member of T11.9.2.a, T11.9.2.b and T11.9.2.c.

If a signal failure is correctable, e.g. due to redundancy or worst case values, the safe state must be entered as soon as an additional non correctable failure occurs.

T11.9.3 If a signal failure is correctable, e.g. due to redundancy or worst case values, the safe state must be entered as soon as an additional non correctable failure occurs.

T11.9.4 The maximum allowed delay of messages according to T11.9.2.d must be chosen depending on the impact of delayed messages to the connected system, but must not exceed 500ms.

T11.9.5 Safe state is defined depending on the signals as follows:

- signals only influencing indicators – Indicating a failure of its own function or of the connected system
- low voltage battery signals – At least one pole is electrically disconnected from the rest of the vehicle
- [EV ONLY] For all others signals – opened shutdown circuit and opened AIRs
- [CV ONLY] For all others signals – opened shutdown circuit and stopped engine

T11.9.6 Indicators according to T11.9.1 with safe state “illuminated” (e.g. absence of failures is not actively indicated) must be illuminated for 1s to 3s for visible check after power cycling the LVMS.

T11.10 Sensors, Cameras & Electrical Components Mounting

T11.10.1 All sensors, cameras and components must be securely mounted. For all mounts, T2.3.3 applies.

T11.10.2 Sensors, cameras and components may not come into contact with the driver’s helmet under any circumstances.

T11.10.3 All sensors, cameras and components must be positioned within the surface envelope (see T1.1.17) or within the box defined in T8.2.

T11.10.4 Passive antennas which do not incorporate active electronic parts, e.g. amplifiers with the longest side <100 mm may additionally to T11.10.3 protrude from the surface envelope see T1.1.17, but not their mounting.

T12 VEHICLE IDENTIFICATION

T12.1 Vehicle Number

T12.1.1 Each vehicle will be assigned a number at the time of its entry into a competition. The number will have an alphabet located at the prefix: C for CV and E for EV.

T12.1.2 Vehicle numbers must appear on the vehicle at the front and both sides as follows:

- Height: At least 150 mm high;
- Font: Roman Sans-Serif characters. Italic, outline, serif, or shadow numbers are prohibited.
- Stroke width and spacing between numbers: At least 20 mm.
- Color: Either white numbers on a black background or black numbers on a white background.
- Background shape: The number background must be one of the following: round, oval, square or rectangular. There must be at least 25 mm between the edge of the numbers and the edge of the background.
- Clear: The numbers must not be obscured by parts of the vehicle.
- Entire vehicle number, along with the prefix must appear on the vehicle.

T12.2 University Name

T12.2.1 The university name (or college name, where applicable per A4.1.4) must be written fully. Only the following abbreviations in the university name are accepted if the city name is written fully:

- University → Uni
- Technical University → TU
- University of Applied Sciences → UAS
- Berufsakademie → BA
- If the university officially uses an abbreviation in their proper name, this abbreviation is accepted.

T12.2.2 The name must be displayed and written in Roman Sans-Serif characters of at least 50 mm high on both sides of the vehicle.

T12.2.3 The characters must be clearly visible at a distance and placed on a high contrast background.

T12.3 Timing Equipment

T12.3.1 All vehicles will get timing equipment provided by the competition organizers.

T13 VEHICLE AND DRIVER EQUIPMENT

T13.1 Pushbar

T13.1.1 Each team must have a removable device (called the pushbar) that attaches to the rear of the vehicle and allows two people to push and pull the vehicle while standing erect behind the vehicle.

- T13.1.2 The pushbar must have a red color.
- T13.1.3 The university name (or college name, where applicable per [A4.1.4](#)) must be written on the push bar. The characters must be clearly visible and placed on a high contrast background.
- T13.1.4 The pushbar must be capable of slowing and stopping the forward motion of the vehicle and pulling it rearwards.
- T13.1.5 An approved fire extinguisher ([see T13.4.1](#)) must be mounted to the pushbar such that it is quickly accessible.
- T13.1.6 [EV ONLY] Two pairs of high-voltage insulating gloves and a multimeter with two 4 mm banana plug test leads rated for 1000 V CAT III or better must be attached to the pushbar. The HV gloves must be protected by a case or similar means from mechanical damage, humidity and sunlight. It must be possible to open the case without using tools.

T13.2 Jacks

- T13.2.1 Each team must have one or two removable devices (jacks) that hold the vehicle, so that all driven wheels are at least 100 mm off the ground.
- T13.2.2 [Positioning of the device\(s\) must be safe.](#)
- T13.2.3 In the lifted position:
- The vehicle must be adequately supported and stable
 - It must be safe for a driver to enter and exit the vehicle
 - The device(s) must not extend [out of the vehicle's projected surface area.](#)
- T13.2.4 On both sides of the vehicle, the devices pickup points must be indicated by orange triangles.
- T13.2.5 The university name (or college name, where applicable per [A4.1.4](#)) must be written on the quick jack. The characters must be clearly visible and placed on a high contrast background.

T13.3 Driver Equipment

- T13.3.1 The equipment specified below must be worn by the driver anytime while in the cockpit with the engine running or with the tractive system active for electric vehicles and anytime between starting a dynamic event and either finishing or abandoning a dynamic event. Removal of any driver equipment during the event will result in disqualification.
- T13.3.2 A well-fitting, closed face helmet that meets one of the following certifications and is labeled as such:
- [Snell K2015, K2020, M2015, M2020, SA2020, EA2016 or newer](#)
 - [SFI 31.1/2015, 31.1/2020, 41.1/2015, 41.1/2020 or newer](#)
 - [FIA 8860-2010, FIA 8860-2018, FIA 8859-2015 or newer](#)

Open faced helmets and off-road helmets (helmets without integrated eye shields) are not approved. All helmets to be used in the competition must be presented during technical inspection where approved helmets will be stickered.

- T13.3.3 If Frontal Head Restraint systems (FHR, HANS) are used, they must be certified to one of the following standards and be labeled as such:
- FIA 8858-2010
 - FIA 8860-2004
 - SFI 38.1
- T13.3.4 A balaclava which covers the driver's head, hair and neck, made from acceptable fire resistant material as defined in T13.3.11, or a full helmet skirt of acceptable fire resistant material.
- T13.3.5 A fire resistant one piece suit, made from a minimum of two layers that covers the body from the neck down to the ankles and the wrists. The suit must be certified to one of the following standards and be labeled as such:
- SFI 3-2A/5 (or higher)
 - SFI 3.4/5 (or higher)
 - FIA Standard 8856-2000
 - FIA Standard 8856-2018
- T13.3.6 Fire resistant underwear (long pants and long sleeve t-shirt). This fire resistant underwear must be made from acceptable fire resistant material as listed in T13.3.11 and must cover the driver's body completely from neck down to ankles and wrists.
- T13.3.7 Fire resistant socks made from acceptable fire resistant material as defined in T13.3.11, that cover the bare skin between the driver's suit and the boots or shoes.
- T13.3.8 Fire resistant shoes made from acceptable fire resistant material as defined in T13.3.11. The shoes must be certified to the standard and labeled as such:
- SFI Spec 3.3
 - FIA Standard 8856-2000
 - FIA Standard 8856-2018
- T13.3.9 Fire resistant gloves made from acceptable fire resistant material as defined in T13.3.11.
- Gloves of all leather construction or fire resistant gloves constructed using leather palms with no insulating fire resisting material underneath are not acceptable.
- T13.3.10 Fire resistant clothing must not be older than 10 years, recognisable since no FIA hologram label present.
- T13.3.11 Arm restraints are required and must be worn such that the driver can release them and exit the vehicle unassisted regardless of the vehicle's position. Arm restraints must be commercially manufactured according to SFI Standard 3.3 or equivalent.
- T13.3.12 All driver equipment covered in T13.3 must be in good condition. Specifically, it must not have any tears, rips, open seams, areas of significant wear or abrasion or stains which might compromise fire resistant performance. Teams must be able to show that the clothing still meets the requirements of T13.3 if driver's clothing is embroidered. **This requires, but is not limited to, that only the outer shell is perforated.** The officials reserve the right to impound all non-approved driver equipment until the end of the competition.

T13.3.13 For the purpose of this section some, but not all, of the approved fire resistant materials are: [Nomex](#), [Aramid](#), [Belcotex](#) and [Indura](#).

T13.3.14 T-shirts, socks or other undergarments made from nylon or any other synthetic material which will melt when exposed to high heat are prohibited.

T13.4 Fire Extinguishers

T13.4.1 Each team must have at least two dry chemical/dry powder fire extinguishers with a minimum firefighting agent capacity of 0.9 kg.

T13.4.2 The following are the minimum accepted ratings:

- USA, Canada and Brazil: 10BC or 1A 10BC
- Europe: 34B or 5A 34B
- Australia: 20BE or 1A 10BE
- [India: Dry chemical or dry powder ABC fire extinguishers are acceptable.](#)

Extinguishers of larger capacity (higher numerical ratings) are acceptable.

T13.4.3 Aqueous Film Forming Foam (AFFF) fire extinguishers are prohibited. Halon extinguishers and systems are prohibited.

T13.4.4 All extinguishers must be equipped with a manufacturer installed pressure/charge gauge.

T13.4.5 Except for the initial inspection, one extinguisher must readily be available in the team's paddock area, and the second must accompany the vehicle wherever the vehicle is moved. Both extinguishers must be presented with the vehicle at technical inspection.

T13.4.6 Hand held fire extinguishers are not permitted to be mounted on or in the vehicle.

T13.5 Camera Mounts

[T13.5.1 The mounts for video/photographic cameras must be of a safe and secure design:](#)

- [All camera installations must be approved at technical inspection.](#)
- [Helmet mounted cameras are prohibited.](#)
- [The body of any camera or recording unit must be secured at a minimum of two points on different sides of the camera body. If a tether is used to restrain the camera, the tether length must be limited so that the camera cannot contact the driver.](#)

CV INTERNAL COMBUSTION ENGINE VEHICLES

CV1 INTERNAL COMBUSTION ENGINE POWERTRAINS

CV1.1 Engine Limitation

CV1.1.1 The engine(s) used to power the vehicle must be a piston engine(s) using a four-stroke primary heat cycle with a displacement not exceeding 710 cm³ per cycle. Hybrid powertrains, such as those using electric motors running off stored energy, are prohibited.

CV1.2 Starter

CV1.2.1 Each vehicle must be equipped with an on-board starter, which must be used to start the vehicle.

CV1.3 Air Intake System

CV1.3.1 All parts of the engine air and fuel control systems (including the throttle and the complete air intake system, including the air filter and any air boxes) must lie within the surface defined by the top of the roll bar and the outside edge of the four tires. (See Figure 2).

CV1.3.2 Any portion of the air intake system that is less than 350 mm above the ground must be protected from impacts, see [T3.15](#). Impact protection must follow [T3.16](#) when having bolted attachments.

CV1.3.3 The intake manifold must be securely attached to the engine block or cylinder head with brackets and mechanical fasteners. The threaded fasteners used to secure the intake manifold are considered critical fasteners and must comply with [T10](#).

CV1.3.4 Intake systems with significant mass or cantilever from the cylinder head must be supported to prevent stress to the intake system. Supports to the engine must be rigid. Supports to the chassis must incorporate isolation to allow for engine movement and chassis torsion.

CV1.4 Throttle

CV1.4.1 The vehicle must be equipped with a throttle body. The throttle body may be of any size or design.

CV1.4.2 The throttle must be actuated mechanically by a foot pedal, i.e. via a cable or a rod system (see [CV1.5](#)), or by an ETC system (see [CV1.6](#)).

CV1.4.3 Throttle position is defined as the percentage of travel from fully closed to fully open where 0% is fully closed and 100% is fully open. The idle position is the average position of the throttle body while the engine is idling.

CV1.4.4 The throttle system mechanism must be protected from debris ingress to prevent jamming.

CV1.5 Mechanical Throttle Actuation

- CV1.5.1 CV1.5 only applies if no ETC system is used.
- CV1.5.2 The throttle actuation system must use at least two return springs located at the throttle body, so that the failure of any one of the two springs will not prevent the throttle returning to the idle position.
- CV1.5.3 Each return spring must be capable of returning the throttle to the idle position with the other disconnected.
- CV1.5.4 Springs in the Throttle Position Sensor (TPS) are not acceptable as return springs.
- CV1.5.5 Throttle cables must be located at least 50 mm from any exhaust system component and out of the exhaust stream.
- CV1.5.6 Throttle cables or rods must have smooth operation and must not have the possibility of binding or sticking. They must be protected from being bent or kinked by the driver's foot during operation or when entering the vehicle.
- CV1.5.7 A positive pedal stop must be incorporated on the accelerator pedal to prevent over-stressing the throttle cable or actuation system.

CV1.6 Electronic Throttle Control (ETC)

- CV1.6.1 CV1.6 only applies if ETC is used.
- CV1.6.2 The team must be able to demonstrate the functionality of all safety features and error detections of the ETC system at technical inspection, see IN.
- CV1.6.3 The ETC system must be equipped with at least the following sensors:
- Accelerator Pedal Position Sensor (APPSs) as defined in T11.8
 - Two Throttle Position Sensor (TPSs) to measure the throttle position.
- CV1.6.4 All ETC signals are System Critical Signals (SCSs) (see T11.9).
- CV1.6.5 When power is removed, the electronic throttle must immediately close at least to idle position $\pm 5\%$. An interval of one second is allowed for the throttle to close to idle, failure to achieve this within the required interval must result in immediate disabling of power to ignition, fuel injectors and fuel pump. This action must remain active until the TPS signals indicate the throttle has returned to idle position $\pm 5\%$ for at least one second.
- CV1.6.6 If plausibility does not occur between the values of at least two TPSs and this persists for more than 100 ms, the power to the electronic throttle must be immediately shut down. Plausibility is defined as a deviation of less than ten percentage points between the sensor values as defined in CV1.4.3 and no detected failures as defined in T11.9.
- CV1.6.7 The electronic throttle must use at least two sources of energy capable of returning the throttle to the closed position. One of the sources may be the device that normally actuates the throttle, e.g. a DC motor, but the other device(s) must be a return spring that can return the throttle to the idle position in the event of a loss of actuator power.
- CV1.6.8 Springs in the TPSs are not acceptable as return springs.

- CV1.6.9 The power to the electronic throttle must be immediately shut down, as defined in [CV1.6.6](#), if the throttle position differs by more than 10 % from the expected target TPS position for more than 500 ms.

CV1.7 Intake System Restrictor

- CV1.7.1 In order to limit the power capability from the engine, a single circular restrictor must be placed in the intake system and all engine airflow must pass through the restrictor. The only allowed sequences of components are the following:
- a. For naturally aspirated engines, the sequence must be: throttle body, restrictor, and engine. (See Figure 17)
 - b. For turbocharged or supercharged engines, the sequence must be: restrictor, compressor, throttle body, engine. (See Figure 18)
- CV1.7.2 The maximum restrictor diameters which must be respected at all times during the competition are:
- a. Gasoline fueled vehicles - 20mm
- CV1.7.3 The restrictor must be located to facilitate measurement during the inspection process.
- CV1.7.4 The circular restricting cross section may not be movable or flexible in any way, e.g. the restrictor must not be part of the movable portion of a barrel throttle body.

CV1.8 Turbochargers and Superchargers

- CV1.8.1 The intake air may be cooled with an intercooler. Only ambient air may be used to remove heat from the intercooler system. Air-to-air and water-to air intercoolers are permitted. The coolant of a water-to-air intercooler system must be plain water without any additives.
- CV1.8.2 If pop-off valves, recirculation valves, or heat exchangers (intercoolers) are used, they may only be positioned in the intake system as shown in Figure 17.
- CV1.8.3 Plenums anywhere upstream of the throttle body are prohibited. A “plenum” is any tank or volume that is a significant enlargement of the normal intake runner system.
- CV1.8.4 The maximum allowable internal diameter of the intake runner system between the restrictor and throttle body is 60 mm diameter, or the equivalent area of 2827 mm² if non-circular.

CV1.9 Crankcase / Engine Lubrication Venting

- CV1.9.1 Any crankcase or engine lubrication vent lines routed to the intake system must be connected upstream of the intake system restrictor.
- CV1.9.2 Crankcase breathers that pass through the oil catch tank(s) to exhaust systems, or vacuum devices that connect directly to the exhaust system, are prohibited.




Figure 17: Intake configuration for naturally aspirated engines.




Figure 18: Intake configuration for turbocharged or supercharged engines.

CV2 FUEL AND FUEL SYSTEM

CV2.1 Fuel

- CV2.1.1 The available fuel types will be unleaded gasoline **91 Octane**.
- CV2.1.2 The vehicles must be operated with the fuels provided at the competition.
- CV2.1.3 No agents other than fuel and air may be induced into the combustion chamber.
- CV2.1.4 The temperature of fuel introduced into the fuel system may not be changed with the intent to improve calculated efficiency.

CV2.2 Fuel System Location Requirements

- CV2.2.1 The fuel tank must be located within the rollover protection envelope (see [T1.1.16](#)), except the fuel filler neck if it is 350 mm above the ground.
- CV2.2.2 All parts of the fuel storage and supply system must lie within the surface envelope (see [T1.1.18](#))
- CV2.2.3 All parts of the fuel storage and supply system must be adequately protected against any heat sources and located at least 50 mm from any exhaust system component.

CV2.2.4 All parts of the fuel system which can come in contact with the fuel must be rated for permanent contact with fuel.

CV2.3 Fuel Tanks

CV2.3.1 The fuel tank is defined as the part of the fuel containment device that is in contact with the fuel. It may be made of a rigid material or a flexible material.

CV2.3.2 The fuel tank must be securely attached to the vehicle structure with mountings that allow some flexibility such that chassis flex cannot unintentionally load the fuel tank.

CV2.3.3 The fuel tank must not touch any part of the vehicle other than its mounting and parts of the fuel system at any time.

CV2.3.4 Any fuel tank that is made from a flexible material, for example a bladder fuel cell or a bag tank, must be enclosed within a rigid fuel tank container which is securely attached to the vehicle structure. Fuel tank containers (containing a bladder fuel cell or bag tank) may be load carrying.

CV2.3.5 The fuel system must have a provision for emptying the fuel tank. A drain hole or drain valve is required on fuel tanks such that the fuel can directly be drained to the ground or a container or pan kept below the vehicle. The drain hole needs to be easily accessible and should not require disassembly of the tank. If there is a diffuser or floor that runs between the fuel tank and the ground, a hose can be connected to the drain hole such that the drained fuel can be routed around the diffuser/floor and eventually to the ground level.

CV2.3.6 The fuel tank, by design, must not have a variable capacity.

CV2.4 Fuel Lines for Low Pressure Systems

CV2.4.1 Fuel lines between fuel tank and fuel rail and return lines must:

- have
 - reinforced rubber fuel lines with an abrasion protection with a fuel hose clamp which has a full 360° wrap, a nut and bolt system for tightening and rolled edges to prevent the clamp cutting into the hose, or, or
 - metal braided hoses with crimped-on or reusable, threaded fittings.
- be rated for temperatures of at least 120°C.

CV2.4.2 For reinforced rubber fuel lines with hose & clamp style connections beaded or barbed hose fittings must be used.

CV2.4.3 Fuel lines must be securely attached to the vehicle and/or engine.

CV2.4.4 All fuel lines must be shielded from possible rotating equipment failure or collision damage.

CV 2.4.5 All fuel lines must be fitted in such a way that any leakage cannot result in the accumulation of fuel in the cockpit.

CV2.5 Fuel Injection System Requirements

Low Pressure Injection (LPI) fuel systems are those functioning at a pressure below 10 bar and High Pressure Injection (HPI) fuel systems are those functioning at a T10 bar pressure or above. Direct Injection (DI) fuel systems are those where the injection occurs directly into the combustion chamber.

CV2.5.1 The following requirements apply to LPI fuel systems:

- The fuel lines must comply with [CV2.4](#).
- The fuel rail must be securely attached to the engine cylinder block, cylinder head, or intake manifold with mechanical fasteners. The threaded fasteners used to secure the fuel rail are considered critical fasteners and must comply with [T10](#).
- The use of fuel rails made from plastic, carbon fiber or rapid prototyping flammable materials is prohibited. However, the use of unmodified Original Equipment Manufacturer (OEM) Fuel Rails manufactured from these materials is acceptable.

CV2.5.2 The following requirements apply to HPI and DI fuel systems:

- All high pressure fuel lines must be stainless steel rigid line or Aeroquip FC807 smooth bore PTFE hose with stainless steel reinforcement and visible Nomex tracer yarn. Use of elastomeric seals is prohibited. Lines must be rigidly connected every 100 mm by mechanical fasteners to structural engine components.
- The fuel rail must be securely attached to the engine cylinder head with mechanical fasteners. The fastening method must be sufficient to hold the fuel rail in place with the maximum regulated pressure acting on the injector internals and neglecting any assistance from in-cylinder pressure acting on the injector tip. The threaded fasteners used to secure the fuel rail are considered critical fasteners and must comply with [T10](#).
- The fuel pump must be rigidly mounted to structural engine components.
- A fuel pressure regulator must be fitted between the high and low pressure sides of the fuel system in parallel with the DI boost pump. The external regulator must be used even if the DI boost pump comes equipped with an internal regulator.
- Prior to the tilt test specified in [IN7](#), engines fitted with mechanically actuated fuel pumps must be run to fill and pressure the system downstream of the high pressure pump.

CV2.6 Fuel Tank Filler Neck and Sight Tube

CV2.6.1 The fuel tank must have a filler neck which:

- has at least an inner diameter of 35 mm at any point between the fuel tank and the top of the fuel filler cap.
- is angled at no more than 30° from the vertical
- is accompanied by a clear fuel resistant sight tube above the top of the fuel tank with a length of at least 125 mm vertical height for reading the fuel level, see [Figure 19](#).
- is made of material that is permanently rated for temperatures of at least 120 °C.

CV2.6.2 A clear filler neck tube may be used as a sight tube.

CV2.6.3 A permanent, non-moveable, clear and easily visible fuel level line must be located between 12 mm and 25 mm below the top of the visible portion of the sight tube. This line will be used as the fill line for the tilt test ([IN7.1](#)), and before and after the endurance test to measure the amount of fuel used during the endurance event.




Figure 19: Minimum requirements fuel tank filler neck.

CV2.6.4 The filler neck opening must be directly accessible without removing any parts of the vehicle except for the fuel filler cap.

CV2.6.5 The filler neck must have a fuel filler cap that can withstand severe vibrations or high pressures such as could occur during a vehicle rollover event.

CV2.7 Tank Filling Requirement

CV2.7.1 The fuel tank must be capable of being filled to capacity without manipulating the tank or the vehicle in any manner. The fuel system must be designed in a way that during refueling of the vehicle on a level surface, the formation of air cavities or other effects that cause the fuel level observed at the sight tube to drop after movement or operation of the vehicle (other than due to consumption) is prevented.

CV2.7.2 The fuel system must be designed such that the spillage during refueling cannot contact the driver position, exhaust system, hot engine parts, or the ignition system.

CV2.8 Venting Systems

CV2.8.1 The fuel tank venting systems must be designed such that fuel cannot spill during hard cornering or acceleration.

CV2.8.2 All fuel vent lines must be equipped with a check valve to prevent fuel leakage when the tank is inverted. All fuel vent lines must exit outside the bodywork.

- CV2.8.3 Only check-valves for fuel vent application are permissible. The use of inline, one-way, or non-return one-way check-valves is strictly prohibited. The check-valve must facilitate the unrestricted entry and exit of air when in an upright position, and while in an inverted position, it must block the flow of fluids.

CV3 EXHAUST SYSTEM AND NOISE CONTROL

CV3.1 Exhaust System General

- CV3.1.1 The exhaust outlet must be routed to the side or rear of the vehicle and so that the driver is not subjected to fumes at any speed considering the draft of the vehicle.
- CV3.1.2 The exhaust outlet(s) must not extend more than 450 mm behind the centerline of the rear axle and shall be no more than 600 mm above the ground.
- CV3.1.3 Any exhaust components (headers, mufflers, etc.) that protrude from the side of the chassis in front of the rear axle must be shielded to prevent contact by persons approaching the vehicle or a driver exiting the vehicle. The temperature of the outer surface must not be harmful to a person touching it.
- CV3.1.4 The application of fibrous/absorbent material, e.g. “headerwrap”, to the outside of an exhaust manifold or exhaust system is prohibited.

CV3.2 Maximum Sound Level

- CV3.2.1 The maximum sound level test speed for a given engine will be the engine speed that corresponds to an average piston speed of 15.25 m/s. The calculated speed will be rounded to the nearest 500 rpm. The maximum permitted sound level up to this calculated speed is 110 dB(C), fast weighting.
- CV3.2.2 The idle test speed for a given engine will be up to the team and determined by their calibrated idle speed. If the idle speed varies then the vehicle will be tested across the range of idle speeds determined by the team. At idle the maximum permitted sound level is 103 dB(C), fast weighting.

CV4 SHUTDOWN SYSTEM

CV4.1 Shutdown Circuit

- CV4.1.1 The shutdown circuit directly controls all electrical power to the ignition, fuel injectors and all fuel pumps. It must act through a minimum of two mechanical relays. One relay for the fuel pump and at least one relay for injection and ignition.

An explanatory schematic of the required shutdown circuit, is shown in Figure 20.

- CV4.1.2 The shutdown circuit is defined as a series connection of at least the LVMS (see T11.3), the BSPD (see T11.6), three shutdown buttons (see T11.4), the BOTS (see T6.2) and the inertia switch (see T11.5).

CV4.1.3 All circuits that are part of the shutdown circuit must be designed in a way that in the de-energized/disconnected state they open the shutdown circuit.




Figure 20: Explanatory example schematic of the required shutdown circuit

EV ELECTRIC VEHICLES

EV1 DEFINITIONS

EV1.1 Tractive System (TS)

EV1.1.1 Tractive System (TS) – every part that is electrically connected to the motor(s) and TS accumulators.

EV1.1.2 TS enclosures – every housing or enclosure containing parts of the TS.

EV1.2 Galvanic Isolation

EV1.2.1 Galvanic Isolation – two electric circuits are defined as galvanically isolated, if all of the following are true:

- the resistance between both circuits is $\geq 500 \Omega/V$, related to the maximum TS voltage of the vehicle, at a test voltage of maximum TS voltage or 250 V, whichever is higher.
- The isolation voltage RMS, AC for 1 min, between both circuits is higher than three times the maximum TS voltage or 750 V, whichever is higher.
- [The working voltage of the isolation barrier, if specified in the datasheet, is higher than the maximum TS voltage.](#)

EV2 ELECTRIC POWERTRAIN

EV2.1 Motors

EV2.1.1 Only electric motors are allowed.

EV2.1.2 Motor attachments must follow [T10](#).

EV2.1.3 Motor casings must follow [T7.3](#).

EV2.1.4 The motor(s) must be connected to the accumulator through a motor controller.

EV2.2 Power Limitation

EV2.2.1 The TS power at the outlet of the TSAC must not exceed 80 kW.

EV2.2.2 Regenerating energy is allowed and unrestricted.

EV2.2.3 Wheels must not be spun in reverse.

EV3 GENERAL REQUIREMENTS

EV3.1 Grounding

EV3.1.1 TS enclosures, see [EV1.1.2](#), must consist of either

- a grounded **solid** layer made of at least 0.5 mm thick electrically conductive material, aluminum or better, having a resistance below 300 mΩ, measured with a current of 1A, to LVS ground and able to continuously carry at least 10% of the TS accumulator main fuse current rating or
- be fully made out of electrically insulating materials having an isolation resistance of at least 2MW, measured with a voltage of 500V. The enclosure must be rigid and must prevent possible mechanical penetrations. Protruding electrically conductive parts, such as fasteners or connectors, must follow EV3.1.2

The TSAC might use at least 0.9 mm thick steel layer as the grounded layer.

EV3.1.2 Electrically conductive seat, driver harness, and firewall mounting points **as well as the aluminum layer of the TS firewall, see T4.8, and the LVS ground measuring point, see EV4.7.8,** must have a resistance below 300 mΩ, measured with a current of 1A, to LVS ground and be able to continuously carry at least 10% of the TS accumulator main fuse current rating.

EV3.1.3 Parts of the vehicle which are or may become electrically conductive within 100 mm of any TS component must have a resistance below 100Ω to LVS ground

EV3.1.4 The rotating part of the wheels may not be grounded.

EV3.2 Overcurrent Protection

EV3.2.1 All electrical systems must have appropriate overcurrent protection.

EV3.2.2 The continuous current rating of the overcurrent protection must not be greater than the continuous current rating of any electrical component, for example wire, busbar or other conductor that it protects.

i.e. if multiple pins of a connector are used to carry currents in parallel, each pin must be appropriately protected.

EV3.2.3 All overcurrent protection devices must have an interrupt current rating which is higher than the theoretical short circuit current of the system that it protects.

EV3.2.4 All overcurrent protection devices must be rated for the highest voltage in the systems they protect. All devices used must be rated for DC.

EV3.2.5 All overcurrent protection devices which are part of the TS must not rely on programmable logic. **The overcurrent protection function of motor controllers/inverters for the motor outputs may rely on programmable logic.**

EV3.2.6 The overcurrent protection must be designed for the expected surrounding temperature range but at least for 0°C to 85°C.

EV3.2.7 The TS high current path through the accumulator(s) must be fused.

EV4 TRACTIVE SYSTEM (TS)

EV4.1 General Requirements

EV4.1.1 The maximum permitted voltage that may occur between any two electrical connections is 600 V DC and for motor controller/inverters internal low energy control signals 630 V DC.

EV4.1.2 All components in the TS must be rated for the maximum TS voltage.

The TS area of a PCB (see EV4.3.6), is considered as one component. Every input connected to the TS must be rated to the maximum TS voltage.

EV4.1.3 All components must be rated for the maximum possible temperature which may occur during usage.

EV4.1.4 Fans with > 50W total power must not be connected to the TS.

EV4.2 TS System Enclosures

EV4.2.1 TS enclosures, see EV1.1.2, must be labeled with (a) reasonably sized sticker(s) according to “ISO 7010-W012” (triangle with black lightning bolt on yellow background). The sticker must also contain the text “High Voltage” if the voltage is more than 60 V DC or 50 V AC RMS.

EV4.3 Separation of Traction System and Grounded Low Voltage System

EV4.3.1 The entire TS and LVS must be completely galvanically isolated (see EV1.2.1 and IN4.1.1).

EV4.3.2 All connections from a TS component to external devices, such as laptops must include galvanic isolation, see EV1.2.1.

EV4.3.3 TS and LVS circuits must be physically segregated such that they are not running through the same conduit or connector, except for interlock circuit connections.

EV4.3.4 Where both TS and LVS are present within an enclosure, they must be separated by barriers made of moisture resistant insulating materials or maintain the following spacing through air, or over a surface:

Voltage	Spacing
$U < 100 \text{ V DC}$	10 mm
$100 \text{ V DC} < U < 200 \text{ V DC}$	20 mm
$U > 200 \text{ V DC}$	30 mm

EV4.3.5 Components and cables capable of movement must be positively restrained to maintain spacing.

EV4.3.6 If TS and LVS are on the same PCB, they must be on separate well defined areas of the board, meeting the spacing requirements in Table 5, each area clearly marked with “TS” or “LV”. The outline of the area required for spacing must be marked.

Voltage	Over Surface	Through Air (Cut in Board)	Conformal Coating
0 V DC to 50 V DC	1.6 mm	1.6 mm	1.0 mm
50 V DC to 150 V DC	6.4 mm	3.2 mm	2.0 mm
150 V DC to 300 V DC	9.5 mm	6.4 mm	3.0 mm
300 V DC to 600 V DC	12.7 mm	9.5 mm	4.0 mm

Table 5: Spacing required between TS and LV.

“Conformal coating” refers to a coating insulator, solder resist is not a coating.

EV4.3.7 Teams must be prepared to demonstrate spacing on team-built equipment. For inaccessible circuitry, fully assembled spare boards must be available.

EV4.4 Positioning of Tractive System Parts

EV4.4.1 Except what is permitted according to EV4.4.3, all parts belonging to the TS including cables and wiring must be located within the rollover protection envelope, see T1.1.16. “Part” is the whole device such as the complete HVD.

EV4.4.2 Any part of the TS that is less than 350 mm above the ground, except what is permitted according to EV4.4.3, must be protected from impacts, see T3.15. Impact protection must follow T3.16 when having bolted attachments. TS wiring in front of the front hoop may alternatively be shielded by the front bulkhead support structure according to T3.14. The TSAC must be no higher than the top of the impact structure as mentioned in EV5.5.1.

EV4.4.3 Outboard wheel motors are allowed only if

- an interlock is routed along the TS wiring such that the shutdown circuit, see EV6, is opened before the TS wiring or its clamping fails
- an interlock is routed along a suspension member such that the shutdown circuit, see EV6, is opened if the suspension fails
- TS wiring is not be able to reach the cockpit opening or the driver regardless of where it breaks
- wiring outside of the rollover protection envelope, see T 1.1.15 is minimum length
- wiring outside of an impact structure or front bulkhead support structure (see EV4.4.2), is minimum length
- Minimum length is the shortest distance plus extra wiring caused by bending radius.

EV4.5 Tractive System Insulation, Wiring and Conduit

EV4.5.1 All live parts of the TS must be protected from being touched. This must include team members working on or inside the vehicle. This is tested with a 100 mm long, 6 mm diameter insulated test probe when the TS enclosures are in place.

EV4.5.2 Insulation material that is rated for the maximum TS voltage must be used. Using only insulating tape or rubber-like paint for insulation is prohibited.

EV4.5.3 The temperature rating for TS wiring, connections, and insulation must be appropriate for the expected surrounding temperatures but at least 85°C.

EV4.5.4 TS components and containers must be protected from moisture in the form of rain or puddles (see IN9).

-
- EV4.5.5 It must be possible to clearly assign and prove wire gauge, temperature rating and insulation voltage to each used wire.
- EV4.5.6 All TS wiring must be completed to professional standards with appropriately sized conductors and terminals and with adequate strain relief and protection from loosening due to vibration etc.
- EV4.5.7 TS wiring must be located out of the way of possible snagging or damage.
- EV4.5.8 All TS wiring that runs outside of TS enclosures must:
- Be enclosed in separate orange non-conductive conduit or use an orange shielded cable. The conduit must be securely anchored to the vehicle, but not to wire, at least at each end.
 - Be securely anchored at least at each end so that it can withstand a force of 200 N without straining the cable end crimp.
- Body work is not sufficient to meet this enclosure requirement.
- EV4.5.9 Any shielded cable must have the shield grounded.
- EV4.5.10 Every TS connector outside of a housing must include a pilot contact/interlock line which is part of the shutdown circuit. Housings only used to avoid interlocks are prohibited.
- EV4.5.11 All TS connections must be designed so that they use intentional current paths through conductors such as copper or aluminum and should not rely on steel bolts to be the primary conductor.
- EV4.5.12 All TS connections must not include compressible material such as plastic in the stack-up or as a fastener. FR-4 is allowed. Screw type connectors are allowed to be used inside the TSAC if only it is part of an OEM product given that the OEM product is automotive grade or is tested for appropriate vibrations.
- EV4.5.13 TS connectors outside of TS enclosures must be designed in a way that the TS cannot be activated, see [EV4.11](#), if connected in any way other than the design intent configuration.
- EV4.5.14 All electrical connections, including bolts, nuts, and other fasteners, in the high current path of the TS must be secured from unintentional loosening. Fasteners must use positive locking mechanisms, see [T10.2](#), that are suitable for high temperatures, see [EV4.5.3](#).
- Components, e.g. inverters, certified for automotive use might be allowed without positive locking feature, if connections are completed as recommended by the manufacturers' datasheet and no positive locking is possible.
- EV4.5.15 Teams must be prepared to demonstrate positive locking. For inaccessible connections, appropriate photographs must be available.
- EV4.5.16 Soldered connections in the high current path are only allowed if all of the following are true:
- connections on PCBs
 - the connected devices are not cells or wires
 - the devices are additionally mechanically secured against loosening
-

EV4.6 Data Logger

- EV4.6.1 A calibrated data logger will be provided by the officials and must be inserted during competition. The data logger measures TS voltage and TS current.
- EV4.6.2 The data logger must be in an easily accessible location so that it is possible to insert, remove or replace it within 15 min in ready to race condition.
- EV4.6.3 The data logger must not be placed within the accumulator container.
- EV4.6.4 All current supplying the TS must run through the data logger. The data logger must be inserted in the negative TS supply between the most negative AIR(s) and the inverters.
- EV4.6.5 The TS voltage sense connection of the data logger must be directly connected ([see T1.3.1](#)) to the most positive AIR(s) on the vehicle side. The direct connection must not carry any current.
- EV4.6.6 The data logger must be directly supplied ([see T1.3.1](#)) from the LVMS.
- EV4.6.7 The specification of the data logger will be available [on the competition website](#).

EV4.7 Tractive System Measuring point (TSMP)

- EV4.7.1 Two TSMPs must be installed directly next to the master switches ([see EV6.2](#)).
- EV4.7.2 The TSMPs must be directly connected ([see T1.3.1](#)) to the intermediate circuit capacitors even if the HVD has been opened or the TS accumulator is disconnected.
- EV4.7.3 4 mm shrouded banana jacks rated for 1000V CAT III or better must be used for the TSMPs.
- EV4.7.4 The TSMPs must be directly connected to the positive and negative motor controller/inverter supply. The TSMPs must be marked “TS+” and “TS-” and exclusively mounted on an orange background.
- EV4.7.5 The TSMPs must be protected by a non-conductive housing that can be opened without tools. [The cover must always be mechanically linked to the vehicle](#).
- EV4.7.6 Each TSMP must be secured with a current limiting resistor according to the following table. Fusing of the TSMPs is prohibited. The resistors power rating must be chosen such that they are able to continuously carry the current if both TSMPs are short circuited.

Maximum TS Voltage	Resistor Value
$U_{max} \leq 200 \text{ V DC}$	5 k Ω
$200 \text{ V DC} < U_{max} \leq 400 \text{ V DC}$	10 k Ω
$400 \text{ V DC} < U_{max} \leq 600 \text{ V DC}$	15 k Ω

- EV4.7.7 All electrical connections needed for TSMP, including bolts, nuts and other fasteners, must be secured from unintentional loosening by the use of positive locking mechanisms. [Bolted connections must follow T10.2, soldered connections EV4.5.16.](#)

EV4.7.8 Next to the TSMPs a LVS ground measuring point must be installed. A 4 mm black shrouded banana jack must be connected to LVS ground and must be marked “GND”.

EV4.8 High Voltage Disconnect (HVD)

EV4.8.1 It must be possible to disconnect at least one pole of the TS accumulator by quickly removing an unobstructed and directly accessible element, fuse or connector. It must be possible to disconnect the HVD without removing any bodywork. **The HVD must be above 350 mm from the ground. Remote actuation of the HVD through a long handle, rope, or wire is not permitted.**

EV4.8.2 **Any ESO must be able to remove the HVD within 10 s when the vehicle is in ready-to-race condition.**

EV4.8.3 A dummy connector or similar may be required to restore the system’s isolation (see EV4.5). The dummy connector must be attached to the pushbar (see T13.1), if not in use.

EV4.8.4 The HVD must be clearly marked with “HVD”.

EV4.8.5 No tools must be necessary to open the HVD. An interlock is required (see EV4.5.10).

EV4.9 Discharge Circuit

EV4.9.1 If a discharge circuit is required to meet EV6.1.5, it must be designed to handle the maximum tractive system voltage permanently.

After three subsequent discharges within 15s in total, the discharge time specified in EV6.1.5 may be exceeded. Full discharging functionality must be given after a reasonable time with a deactivated discharge circuit.

EV4.9.2 The discharge circuit must be wired in a way that it is always active whenever the shutdown circuit is open. Furthermore, the discharge circuit must be fail-safe such that it still discharges the intermediate circuit capacitors if the HVD has been opened or the TS accumulator is disconnected.

EV4.9.3 Fusing of the discharge main current path is prohibited.

EV4.9.4 **No part of the discharge circuit must be inside the TSAC.**

EV4.10 Tractive System Active Light (TSAL)

EV4.10.1 The vehicles must include a single TSAL that must indicate the TS status. The TSAL must not perform any other functions. A TSAL with multiple LEDs in one housing is allowed.

EV4.10.2 The TSAL itself must have a red light, flashing continuously with a frequency between 2 Hz and 5 Hz and a duty cycle of 50%, active if and only if the LVS is active and the voltage across DC-link capacitors exceeds

- 60 VDC or or 50 VAC Root Mean Square (RMS)
- Half the nominal TS voltage

whichever is lower.

- EV4.10.3 The TSAL itself must have a green light, continuously on, active if and only if the LVS is active and ALL of the following conditions are true:
- All AIRs are opened.
 - The pre-charge relay, see [EV5.7.2](#), is opened.
 - The voltage at the vehicle side of the AIRs inside the TSAC does not exceed 60 VDC or 50 VAC RMS.
- EV4.10.4 The mentioned voltage detection must be performed inside the respective TS enclosure.
- EV4.10.5 The mentioned states of the relays (opened/closed) are the actual mechanical states. The mechanical state can differ from the intentional state, i.e. if a relay is stuck. Any circuitry detecting the mechanical state must meet [EV5.6.2](#).
- EV4.10.6 The voltage detection circuit of the red light and the relay state and voltage detection circuit of the green light must be independent. Any plausibility check between both lights is not allowed. A TSAL state with both lights simultaneously active might occur and must not be prevented.
- EV4.10.7 The TSAL must:
- Be located lower than the highest point of the main hoop and including the mounting within the rollover protection envelope, see [T1.1.15](#).
 - Be no lower than 75 mm from the highest point of the main hoop.
 - Not be able to contact the driver's helmet in any circumstances.
- EV4.10.8 The entire illuminated surface of the TSAL must be clearly visible:
- Except for angles less than 10° [on each side](#) which are blocked by the main hoop.
 - From a point 1.60 m vertically from ground level, within 3 m horizontal radius from the TSAL.
 - In direct sunlight.
- EV4.10.9 The TSAL and all needed circuitry must be hard wired electronics. Software control is not permitted.
- EV4.10.10 A green indicator light in the cockpit that is easily visible even in bright sunlight and clearly marked with "TS off" must light up if TSAL green light is on, see [EV4.10.3](#).
- EV4.10.11 Signals influencing the TSAL and the indicator according to [EV4.10.10](#) are SCS, see [T11.9](#). The individual safe state of each of the TSAL lights is off. The TSAL has an active indication of absence of failures (continuous green illumination) and thus the red light must not be illuminated for visible check, see [T11.9.5](#).
- EV4.10.12 The TSAL's red light voltage detection circuit must include SCS Check, as required by [T11.9.2\(b\)](#), and turn TSAL red light off in case of sensor signal failure.
- EV4.10.13 TSAL green light must enter safe state:
- if TSAL's green light relay state detection circuit detects implausibility between the intentional and mechanical state of the relay (AIR and Precharge relay)
 - if TSAL's green light voltage detection circuit detects implausibility, as required by [T11.9.2\(b\)](#)

EV 4.10.14 A latching circuit is required to latch safe state caused by [EV4.10.13](#). It must not be triggered during normal operation conditions and must only be reset by power-cycling the LVS.

EV4.11 Activating the Tractive System

EV4.11.1 The TS is active if any of the AIRs or the pre-charge relay is closed.

EV4.11.2 The driver must be able to activate and deactivate the TS from within the cockpit without the assistance of any other person.

~~EV4.11.3 [DV Only]~~

EV4.11.4 Closing the shutdown circuit by any part defined in [EV7.1.2](#) must not (re-)activate the tractive system. Additional action must be required.

~~EV4.11.5 [DV Only]~~

EV4.11.6 The vehicle is ready to drive as soon as the motor(s) will respond to the input of the APPS.

EV4.11.7 After the TS has been activated, additional actions must be required by the driver to set the vehicle to ready-to-drive mode (e.g. pressing a dedicated start button). The transition to ready-to-drive mode must only be possible during the actuation of the mechanical brakes and a simultaneous dedicated additional action.

EV4.11.8 The ready-to-drive mode must be left immediately when the shutdown circuit is opened.

EV4.12 Ready-To-Drive Sound

EV4.12.1 [The vehicle must make a characteristic sound, continuously for at least 1 s and a maximum of 3 s while entering R2D mode.](#)

EV4.12.2 The sound level must be a minimum of 80 dBA and a maximum of 90 dBA, fast weighting in a radius of 2 m around the vehicle.

EV4.12.3 The used sound must be easily recognizable. No animal voices, song parts or sounds that could be interpreted as offensive will be accepted.

EV4.12.4 The vehicle must not make any other sounds similar to the ready-to-drive sound.

EV5 TRACTIVE SYSTEM ENERGY STORAGE

EV5.1 Definitions

EV5.1.1 Cell – a battery cell or super-capacitor.

EV5.1.2 Cell Energy – the maximum cell voltage times the nominal capacity of the used cell.

EV5.1.3 TS Accumulator – all cells that store the electrical energy to be used by the TS as a whole.

EV5.1.4 TS Accumulator Container (TSAC) – a container which contains the TS accumulator.

EV5.1.5 TS Accumulator Segments – sub-divisions of the TS accumulator.

EV5.2 Allowed Tractive System Accumulators

EV5.2.1 All types of accumulators except molten salt and thermal batteries are allowed.

EV5.2.2 Fuel cells are prohibited.

EV5.3 Tractive System Energy Storage – General Requirements

EV5.3.1 All cells which store the TS energy must be enclosed in (an) accumulator container(s).

EV5.3.2 Each accumulator segment must not exceed a maximum static voltage of 120 V DC and a maximum energy of 6 MJ ([see EV5.1.2](#)) and a maximum mass of 12 kg.

EV5.3.3 If spare TS accumulators are used, they must be of the same size, weight and type as those that are replaced. Spare accumulator packs must be presented at technical inspection.

EV5.3.4 Spare cells must be stored in an electrically insulated container made of fire retardant material ([see T1.2.1](#)). The container must be labeled according to [EV5.3.8](#).

EV5.3.5 Spare accumulators and spare cells must be presented at technical inspection.

EV5.3.6 It must be possible to open the TSAC for technical inspection.

EV5.3.7 Each TSAC must be removable from the vehicle while still remaining rules compliant without the need to install extra components. A dummy connector or similar may be used to restore the system's isolation ([see EV4.5](#)).

EV5.3.8 The vehicle number, the university name, the ESO phone number(s), **cell chemistry used and max TS voltage** must be displayed and written in Roman Sans-Serif characters of at least 20 mm high on the lid of each accumulator container. The characters must be clearly visible and placed on a high contrast background.

EV5.4 Tractive System Energy Storage – Electrical Configuration

EV5.4.1 If the TSAC is made from an electrically conductive material, the insulation barrier must be adequately protected against conductive penetrations.

EV5.4.2 Every TSAC must contain at least one fuse and at least two AIRs ([see EV5.6](#) and [EV3.2.7](#)).

EV5.4.3 LVS must not be included in the TSAC except where inherently required. Exceptions include the AIRs, TS DC/DC converters, the Accumulator Management System(AMS), the Insulation Monitoring Device (IMD), [the TSAL's green light circuitry](#), and cooling fans.

EV5.4.4 Maintenance plugs must allow electrical separation of all internal cell segments ([see EV5.3.2](#)). The separation must affect both poles of all segments including the first and last segment.

EV5.4.5 Maintenance plugs must

- not require tools to separate the TSAC segments.
- be non-conductive on surfaces that do not provide any electrical connection.

- be designed in a way that it is physically impossible to electrically connect them in any way other than the design intent configuration.
- protected against accidental reconnection.
- be designed such that it is clearly visible whether the connection is open or closed. Electrically controlled switches must not be used.
- **should be completely detached from the TSAC when in a removed state i.e they should be kept in a separate box.**

Upon removal of all maintenance plugs, no voltage should be present at the TSAC side of AIR.

- EV5.4.6 Each TS accumulator segment must be electrically insulated by the use of suitable and fire retardant ([see T1.2.1](#)), material between the segments and on top of the segment to prevent arc flashes caused by inter segment contact or by parts/tools accidentally falling into the TSAC during maintenance.
- EV5.4.7 Every wire used in a TSAC, regardless of whether it is part of the LVS or TS, must be rated to the maximum TS voltage.
- EV5.4.8 Each TSAC must have a prominent indicator, a voltmeter or a red LED visible even in bright sunlight that will illuminate whenever a voltage greater than 60 V DC or half the maximum TS voltage, whichever is lower, is present at the vehicle side of the AIRs.
- EV5.4.9 The indicator must be clearly visible while disconnecting the TSAC from the vehicles. The indicator must be clearly marked with “Voltage Indicator”.
- EV5.4.10 **The indicator must be hard-wired electronics without software control, directly and only supplied by the TS from the vehicle side of the AIRs, and always working, even if the accumulator is disconnected from the LVS or removed from the vehicle.**

EV5.5 Tractive System Energy Storage – Mechanical Configuration

- EV5.5.1 **All TSACs must lie within and be attached to the primary structure or any additional structures fixed to the primary structure that meet the minimum specification for impact structures, see [T3.2](#), no higher than the top of the impact structure, see [T3.15](#).**
- EV5.5.2 **The TSAC(s) must be protected from impacts, see [T3.15](#). Impact protection must follow [T3.16](#) when having bolted attachments. The TSAC must not be part of this structure.**
- EV5.5.3 **All materials used inside the TSAC and the TSAC itself, as well as all structural parts used to comply with [EV5.5.8](#) must be fire retardant, see [T1.2.1](#). All calculations must be conducted for an ambient temperature of 60°C except for metallic materials and continuous fiber-reinforced laminates.**
- EV5.5.4 The TSAC must be constructed of steel or aluminum. With the following requirements:
- The bottom of the accumulator container must be at least 1.25 mm thick if made from steel or 3.2 mm if made from aluminum.
 - The internal and external vertical walls, covers and lids must be at least 0.9 mm thick if made from steel or 2.3 mm if made from aluminum.

Alternative materials are allowed with proof of equivalency per [T3.3](#) or for composite materials per [EV5.5.5](#). This must be documented in the SES. When alternative materials are used, test samples must be presented at technical inspection.

EV5.5.5 Composite TSAC(s) must satisfy the following requirements:

- Data obtained from the laminate perimeter shear strength test and three point bending test (T3.5), should be used to prove adequate strength is provided.
- Each attachment point requires steel backing plates with a minimum thickness of 2 mm. Alternate materials may be used for backing plates if equivalency is approved.
- The calculations and physical test results must be included in the SES.

EV5.5.6 The floor and walls of the TSAC must be joined by welds, bonding and/or fasteners.

EV5.5.7 The TSAC must consist of electrically insulating internal vertical walls with a minimum of 75% of the height of the external vertical walls, that divide the TSAC into sections of a maximum of 12 kg. These walls must not divide any accumulator segment (see EV5.3.2).

EV5.5.8 The accumulator segments (EV5.3.2), must be separated by a rigid, electrically insulating and fire retardant barrier (see T1.2.1).

EV5.5.9 The TSAC itself, the mounting of the TSAC to the chassis and the mounting of the cells to the container must be designed to withstand the following accelerations:

- 40 g in the longitudinal direction (forward/aft)
- 40 g in the lateral direction (left/right)
- 20 g in the vertical direction (up/down)

Calculations and/or tests must be documented in the SES. All considered TSAC attachment points must follow EV5.5.13. TSACs made of materials as stated in EV5.5.4 or EV5.5.5 may need further reinforcement in order to comply with this rule.

EV5.5.10 Pouch cells must be fixed using one or both of the large surface(s) only. Each used surface must be fixed on at least 80%. Tabs of pouch cells must not carry mechanical loads and must not press into the pouch.

EV5.5.11 Friction-based cell mounting requires physical testing and must be documented in the SES. Mechanically representative test cells or cell mockups can be used for testing.

EV5.5.12 All fasteners used within or to mount the TSAC must comply with T10. Fasteners within the accumulator used for non-structural accumulator parts (e.g. PCBs etc.) do not have to follow T10.1.2. Fasteners made of electrically non-conductive material within the accumulator used for non-structural accumulator parts do not have to follow T10.

EV5.5.13 Any brackets used to mount the TSAC must be made of steel 1.6 mm thick or aluminum 4 mm thick and must have gussets to carry bending loads. Each attachment point including brackets, backing plates and inserts, must be able to withstand 20 kN in any direction.

EV5.5.14 The AIRs and the main fuse (see EV3.2.7) must be separated with an electrically insulated and fire retardant material (see T1.2.1) from the rest of the TS accumulator. Air is not considered to be a suitable insulation material in this case.

EV5.5.15 Holes, both internal and external, in the TSAC are only allowed for the wiring-harness, ventilation, cooling or fasteners. The TSAC must still be compliant with all other rules, especially the ones concerning its structural requirements. The total cutout area must be below 25% of the area of the respective single wall. External holes must be sealed according to EV4.5.

- EV5.5.16 External openings in the TSAC or mounted ducts must not point toward the driver or the operator of the accumulator hand cart even though there is a firewall, see [T4.8](#), in between. Ducts and their mounting must be fire retardant, see [T1.2.1](#), and properly sealed.
- EV5.5.17 A sticker according to “ISO 7010-W012” (triangle with black lightning bolt on yellow background) with triangle side length of at least 100 mm and the text “Always Energized” must be applied on every TSAC. The sticker must also contain the text “High Voltage” if the voltage is more than 60 V DC or 25 V AC.
- EV5.5.18 Any TS accumulators that may vent an explosive gas must have a ventilation system to prevent the vented gas from reaching an explosive concentration.
- EV5.5.19 Every TSAC which is completely sealed must also have a pressure relief valve to prevent high-pressure in the container.
- EV5.5.20 The design of the TSAC and its contents must be documented in the SES including materials used, drawings, images, fastener locations, segment weight, cell and segment position.

EV5.6 Accumulator Isolation Relays (AIRs)

- EV5.6.1 At least two AIRs must be fitted inside each accumulator container.
- EV5.6.2 The AIRs must open both poles of the accumulator. If the AIRs are open, no TS voltage may be present outside of the accumulator container and the vehicle side of the AIRs must be galvanically isolated from the accumulator side (see [EV1.2.1](#)).
- EV5.6.3 The AIRs must be mechanical relays of a “normally open” type.

EV5.7 Pre-Charge Circuit

- EV5.7.1 A circuit that ensures that the voltage at the vehicle side of the AIRs is pre-charged to at least 95% of the actual TS accumulator voltage before closing the second AIR must be implemented.
- EV5.7.2 The pre-charge circuit must use a mechanical, normally open type relay. All pre-charge current must pass through this relay.

EV5.8 Accumulator Management System (AMS)

- EV5.8.1 Each TS accumulator must be monitored by an AMS whenever the LVS is active or the accumulator is connected to a charger.
- EV5.8.2 Every TSAC must contain its full AMS including its own and AMS exclusive SDC power stage, see [EV6.1](#).
- EV5.8.3 The AMS must continuously measure
- all cell voltages
 - the TS current
 - the temperature of thermally critical cells
 - for lithium based cells: the temperature of at least 30% of the cells equally distributed within the accumulator container(s)

- EV5.8.4 Cell temperature must be measured at the negative terminal of the respective cell. The sensor used must be in direct contact with the electrically exposed negative terminal or less than 10 mm along the high current path away from the terminal in direct contact with the respective busbar. It is acceptable to monitor multiple cells with one sensor if this requirement is met for all cells sensed by the sensor. The attachment method of the thermistor on the negative terminal must be documented in ESF. If epoxy is used, proof must be shown that the measurement is not affected by the epoxy interface.
- EV5.8.5 The maximum cell temperature is 60°C or the limit stated in the cell data sheet, whichever is lower.
- EV5.8.6 ~~(Removed)~~
- EV5.8.7 The AMS must switch off the TS via the shutdown circuit, if critical voltage, temperature or current values according to the cell manufacturer's datasheet or these rules are persistently detected for more than:
- 500 ms for voltage and current values
 - 1 s for temperature values
- The accuracy and noise of the measurement must be taken into account for these.
- EV5.8.8 AMS cell voltage measurement inputs, temperature measurement inputs and supply voltage of decentralized AMS slaves may be rated below the maximum TS voltage if the team has proven by calculations in the Electrical System Form (ESF) ([see EV9](#)) that the input voltage rating is reasonably chosen.
- EV5.8.9 A red indicator light in the cockpit that is easily visible from inside and outside the cockpit even in bright sunlight and clearly marked with the lettering "AMS" must light up if the AMS opens the shutdown circuit. It must stay illuminated until the error state has been manually reset ([see EV6.1.6](#)). Signals controlling this indicator are SCS ([see T11.9](#)).
- EV5.8.10 AMS signals are System Critical Signals, ([see T11.9](#)).
- EV5.8.11 It must be possible to individually disconnect the current sensor, one temperature sensor and one cell voltage measurement wire during technical inspection, if any wire is used.
- EV5.8.12 The AMS must be able to read and display all measured values according to [EV5.8.2](#) in a [single overview](#) e.g. by connecting a laptop to the AMS.

EV6 SHUTDOWN CIRCUIT AND SYSTEMS

EV6.1 Shutdown Circuit

- EV6.1.1 The shutdown circuit directly carries the current driving the AIRs, [see EV5.6](#), and the pre-charge circuitry, [see EV5.7](#).
- EV6.1.2 The shutdown circuit is defined as a series connection of at least two master switches, three shutdown buttons, the BOTS ([see T6.2](#)), the IMD, the inertia switch ([see T11.5](#)), the BSPD ([see T11.6](#)), all required interlocks and the AMS. An explanatory schematic of the required shutdown circuit, excluding any possible interlock circuitry, is shown in Figure 21.

- EV6.1.3 All parts of the shutdown circuit defined in [EV6.1.2](#) must be on the high-side connection of the AIR coils.
- EV6.1.4 The Tractive System Master Switch (TSMS) ([see EV6.2](#)) must be the last switch before the AIRs except for pre-charge circuitry and hardwired interlocks.
- EV6.1.5 If the shutdown circuit is opened, the TS must be shutdown by opening all AIRs and the voltage in the TS must drop to below 60 V DC and 50 VAC RMS in less than five seconds. All accumulator current flow must stop immediately.

The action of opening the shutdown circuit may be delayed by ≤ 250 ms to signal the action to the motor controllers and reduce the TS current before the AIRs are opened. The AIR supply must be abruptly switched off before reaching the minimum AIR supply voltage.




Figure 21: Explanatory example schematic of the required shutdown circuit

- EV6.1.6 If the shutdown circuit is opened by the AMS or the IMD, it has to be latched open by a non-programmable logic that can only be manually reset by a person at the vehicle who is not the driver.
- EV6.1.7 All circuits that are part of the shutdown circuit must be designed in a way, that in the de-energized/disconnected state they are open such that each circuit will remove the current controlling the AIRs.
- EV6.1.8 It must be possible to demonstrate that all features of the shutdown circuit function correctly. This includes all interlocks.
- EV6.1.9 Every system that is required to or is able to open the shutdown circuit must have its own, non-programmable, power stage to achieve this. The respective power stages must be designed to be able to carry the shutdown circuit current, e.g. AIR inrush currents, and such

that a failure cannot result in electrical power being fed back into the electrical shutdown circuit.

EV6.1.10 The shutdown buttons, the BOTS, the TSMS and all interlocks must not act through any power stage.

EV6.1.11 All signals influencing the shutdown circuit are SCSs ([see T11.9](#)).

EV6.2 Tractive System Master Switch (TSMS)

EV6.2.1 A TSMS according to [T11.2](#) must be part of the shutdown circuit ([see EV6.1.2](#)).

EV6.2.2 The TSMS must be fitted with a “lockout/tagout” capability to prevent accidental activation of the TS. The ESO must ensure that it is locked in the off position whenever work is done on the vehicle or no ESO is present.

EV6.2.3 The TSMS must be mounted in the middle of a completely orange circular area of ≥ 50 mm diameter placed on a high contrast background.

EV6.2.4 The TSMS must be marked with “TS” and a symbol according to “ISO 7010-W012” (triangle with black lightning bolt on yellow background).

EV6.3 Insulation Monitoring Device (IMD)

EV6.3.1 Every vehicle must have an IMD installed in the TS system.

EV6.3.2 The IMD must be a Bender A-ISOMETER® iso-F1 IR155-3203, -3204, -4203, or -4204, or a Bender ISOMETER® iso165C-1, or equivalent IMD approved for automotive use. Equivalency may be approved by the officials’ based on the following criteria: robustness to vibration, operating temperature range, IP rating, availability of a direct output, a self-test facility and must not be powered by the system which is monitored.

EV6.3.3 The response value of the IMD must be set to $\geq 500 \Omega/v$, related to the maximum TS operation voltage.

EV6.3.4 The IMD must be connected on the vehicle side of the AIRs.

EV6.3.5 One IMD chassis ground measurement line must be connected to the grounded TSAC or the respective grounded enclosure of the IMD. The other chassis ground measurement line must be connected to the main hoop. Each connection must use a separate conductor, rated for at least maximum TS voltage. An open circuit in any of this ground measurement connections must result in an opened shutdown circuit.

EV6.3.6 In case of an insulation failure or an IMD failure, the IMD must open the shutdown circuit. This must be done without the influence of any programmable logic. See also [EV6.1.6](#) regarding the re-activation of the TS after an insulation fault.

EV6.3.7 A red indicator light in the cockpit that is easily visible from inside and outside the cockpit even in bright sunlight and clearly marked with the lettering “IMD” must light up if the IMD opens the shutdown circuit. It must stay illuminated until the error state has been manually reset ([see EV6.1.6](#)). Signals controlling this indicator are SCS ([see T11.9](#)).

EV7 CHARGERS

EV7.1 Chargers General Requirements

- EV7.1.1 Only chargers presented and sealed at technical inspection are allowed. All connections of the charger(s) must be isolated and covered. No open connections are allowed.
- EV7.1.2 Exposed conductive parts and the TSAC must be connected to protective earth (PE).
- EV7.1.3 All chargers must either be accredited to a recognized standard e.g. CE, or when built by the team, must comply with all electrical requirements for the vehicle TS, e.g. EV4.3, EV3.1 and EV4.2.
- EV7.1.4 TS charging leads must be orange.
- EV7.1.5 When charging, the AMS must be live and must be able to turn off the charger in the event that a fault is detected.
- EV7.1.6 The charger must include a push type emergency stop button which has a minimum diameter of 24 mm and must be clearly labeled.
- EV7.1.7 When charging the accumulator, an IMD as described in EV6.3 must be active and must be able to shut down the charger. Either the charger must incorporate an active IMD or an active IMD must be within the accumulator. Other than stated in EV6.3, the second chassis ground measurement line must be connected to the casing of the charger instead of the main hoop.
- EV7.1.8 An IMD indicator light as defined in EV6.3.7 must be available during charging.
- EV7.1.9 The charger must include TSMPs as described in EV4.7. Other than stated, the TSMPs must be connected to the HV output of the charger.
- EV7.1.10 All indicators, switches, buttons, and connectors of the charger must be labeled.

EV7.2 Charging Shutdown Circuit

- EV7.2.1 When charging, the charging shutdown circuit consists of at least the charger shutdown button (see EV7.1.6), the IMD and the AMS. The shutdown button must be towards the person moving the handcart.
- EV7.2.2 If the shutdown circuit is opened the charging system must remain disabled and the shutdown circuit opened, until it is manually reset.
- EV7.2.3 The charging shutdown systems must comply with EV6.1.1, EV6.1.5, EV6.1.7, EV6.1.8 and EV6.1.9.
- EV7.2.4 All signals influencing the charger shutdown circuit are SCS (see T11.9).

EV8 TS ACCUMULATOR CONTAINER HAND CART

EV8.1 TS Accumulator Container Hand Cart

- EV8.1.1 A hand cart(s) must be used for transporting the accumulator container(s) around the competition site.
- EV8.1.2 The hand cart must have at least four wheels.
- EV8.1.3 The hand cart must have a brake which is always on and only released if someone pushes the handle, or similar.
- EV8.1.4 The brake must be capable of stopping the fully loaded accumulator container hand cart.
- EV8.1.5 The hand cart must be able to carry the load of the TSAC(s).
- EV8.1.6 The hand cart must provide a firewall to protect the person while moving the hand cart. The firewall must have the same width as the hand cart, start at the lowest point of the hand cart excluding the wheels and be at least 30 cm higher than the hand cart handle and the TSAC. *The firewall must be made from a rigid, fire retardant material, see T1.2.1, and be transparent from 1.3 m above the ground.*
- EV8.1.7 The TSAC(s) must be mechanically fixed to the hand cart to enable safe transportation.
- EV8.1.8 *The TSAC(s) must not protrude the hand cart.*
- EV8.1.9 The TSAC(s) must be protected from vibrations and shocks during normal operation of the cart, e.g. by the use of air tires.
- EV8.1.10 *The hand cart itself must have a label according to EV5.3.8 on its firewall below the hand cart handle. The label should be facing towards the person moving the handcart.*
- EV8.1.11 The overall floor space used by the fully loaded hand cart must not exceed 1200mm x 800mm. If the TSAC is larger than the allowed floor space, exceptions may be approved by the officials prior to the competition.

EV9 ELECTRICAL SYSTEM FORM (ESF) and FAILURE MODES AND EFFECTS ANALYSIS (FMEA)

EV9.1 [EV ONLY] Electrical System Form (ESF)

- EV9.1.1 Prior to the competition, all teams must submit clearly structured documentation of their entire electrical system (including control and TS) called the ESF.
- EV9.1.2 *Templates of the ESF shall be made available on the competition website.*

EV9.2 [EV ONLY] Failure Modes and Effects Analysis (FMEA)

- EV9.2.1 *Teams must submit a complete failure modes and effects analysis (FMEA) of the TS by the deadline published on the competition website.*

EV9.2.2 A template including required failures to be described will be made available online. Pictures, schematics and data sheets referenced in the FMEA must be included in the FMEA on additional table pages.

~~EV9.3 [EV ONLY] Accumulator Pre-Tech Inspection (ACC-PT)~~

IN TECHNICAL INSPECTIONS

IN1 GENERAL

IN1.1 Technical Inspection Process

IN1.1.1 The technical inspection is divided into the following parts:

- Pre-Inspection
- [EV ONLY] Accumulator Inspection
- [EV ONLY] Electrical Inspection
- Mechanical Inspection
- Tilt Test
- Vehicle Weighing (Optional)
- [CV ONLY] Noise Test
- [EV ONLY] Rain Test
- Brake Test

IN1.1.2 The technical inspection process will be held in the following order:

Combustion	Electric
Pre-Inspection	Pre-Inspection
Mechanical Inspection	Accumulator Inspection
Tilt Test	Electrical / Mechanical Inspection*
Noise Test	Rain Test
Brakes Test	Tilt Test
	Brakes Test

*Electrical Inspection and Mechanical Inspection can be conducted in either order.

IN1.2 General Rules

IN1.2.1 Each vehicle must pass all parts of technical inspection before it may participate in any dynamic event.

~~IN1.2.2 [DV Only]~~

IN1.2.3 Passing the technical inspections is not a certification of complete rules compliance of the vehicle.

IN1.2.4 The technical inspection sheet includes several inspection points and will be provided on the competition website prior to the competition. It must always stay with the [push bar](#).

-
- IN1.2.5 The officials may inspect other points not mentioned on the technical inspection sheet to ensure compliance with the rules.
- IN1.2.6 Teams are responsible for confirming that their vehicle and the required equipment satisfies the requirements and restrictions of the rules before presenting it for technical inspection.
- IN1.2.7 Vehicles must be presented for technical inspection in ready-to-race condition.
- IN1.2.8 Safety uncritical rule violations without a benefit to the team that cannot be changed at the event may result in at least 20 penalty points for the teams, depending on officials' decision. Safety uncritical violations with a minor benefit to the team that cannot be changed at the event may result in at least 40 penalty points for the team. The penalty points will be deducted from the team's overall score.
- IN1.2.9 All items on the inspection sheet must be clearly visible for the officials without using instruments such as endoscopes or mirrors. Visible access may be provided by removing body panels or by providing removable access panels.
- IN1.2.10 The vehicle must maintain all required specifications throughout the competition.
- IN1.2.11 Officials reserve the right to ask the team for drilling of additional inspection holes to check the chassis for compliance with the rules.
- IN1.2.12 Officials will mark or seal various different approved parts. Removal of, or damage to the seals will void the inspection approval.
- IN1.2.13 Once the vehicle is approved for competition, any damage to the vehicle that requires repair(s) will void the inspection approval. After completion of the repair(s), the vehicle must be re-submitted to technical inspection for re-approval.
- IN 1.2.14 The officials reserve the right to prohibit the use of parts that could pose a safety risk to drivers, track marshalls or the environment.

IN1.3 Technical Inspection Sticker

- IN1.3.1 The competition technical inspection stickers will be placed on the nose of the vehicle.
- IN1.3.2 If a vehicle is no longer in compliance with the rules, the officials will set the vehicle's technical inspection status to fail, remove the respective inspection sticker(s) from the vehicle and note the reason for revoking the technical inspection approval in the technical inspection sheet.

IN1.4 Inspection Responsible Person

- IN1.4.1 To accelerate the technical inspection process, the team must appoint one team member as inspection responsible person. [EV ONLY] For electrical inspection and accumulator inspection this has to be an ESO.
- IN1.4.2 This inspection responsible person must be:
- Familiar with the vehicle.
 - Able to show compliance of the vehicle with all points mentioned on the technical inspection sheet.

- Able to perform the technical inspection autonomously observed by the officials, when asked.

IN1.4.3 Should the inspection responsible person be unable to perform one of these requirements, or the vehicle and all necessary items are not ready, the technical inspection will be aborted and the team will be asked to leave the technical inspection area.

IN1.5 Modifications and Repairs

IN1.5.1 After technical inspection, the only modifications permitted to the vehicle are:

- Adjustment of belts, chains and clutches
- Adjustment of the brake bias
- Adjustment of the driver restraint system, head restraint, seat and pedal assembly
- Substitution of the head restraint or seat insert for different drivers
- Adjustment to engine operating parameters, e.g. fuel mixture and ignition timing
- Adjustment of mirrors
- Adjustment of the suspension where no part substitution, other than springs, sway bars and shims, is required
- Adjustment of tire pressure
- Adjustment of winglet angles, but not the position of the complete aerodynamic device in relation to the vehicle
- Replenishment of fluids
- Replacement of defective tires or brake pads. Replacement tires and brake pads must be identical in material/composition/size to those presented and approved at technical inspection.
- Changing wheels and tires for “wet” or “damp” conditions as allowed in [D3.2](#) and [D7.5](#)
- Software calibration changes
- Recharging low voltage batteries
- Recharging TS accumulators
- [Installing and removing protective sensor covers, if approved during technical inspection](#)

IN2 PRE-INSPECTION

IN2.1 Pre-Inspection Required Items

IN2.1.1 The following items must be presented for pre-inspection:

- All helmets
- All driver’s equipment and other safety gear
- Two sets of four tires mounted on rims for dry and wet driving conditions
- Two unused and in date fire extinguishers

IN3 [EV ONLY] ACCUMULATOR INSPECTION

IN3.1 Accumulator Inspection General Definitions

IN3.1.1 Cell modules or stacks do not need to be disassembled when AIRs, fuses, pre- and discharge circuit and positive locking mechanism of the maintenance plugs are reachable and visible for the officials.

IN3.1.2 ~~(Removed)~~

IN3.1.3 The accumulator charger will be inspected and sealed.

IN3.1.4 The set of basic tools will be checked.

IN3.1.5 ~~(Removed)~~

IN3.2 Accumulator Inspection Required Items

IN3.2.1 The following items must be presented at accumulator inspection:

- All TS accumulators
- Accumulator hand cart
- Accumulator charger
- Basic Tools (see IN3.2.2)
- Tools needed for the (dis)assembly of parts
- Samples of self designed PCBs that are part of the tractive system and inside the accumulator container (see EV4.3.6)
- Data sheets for all parts used in the accumulator
- Original delivery notes for material without serial number printed on according to T1.2.1
- Print-outs of rule questions (if applicable)

IN3.2.2 The following basic tools in good condition must be presented:

- Insulated cable shears
- Insulated screwdrivers
- Multimeter with protected probe tips and two 4 mm banana plug test leads rated for 1000 V CAT III or better
- Insulated tools, if screwed connections are used in the tractive system
- Face shield
- at least two pairs of HV insulating gloves (not expired)
- Two HV insulating blankets of at least 1.0 m² each
- Safety glasses with side shields for all team members that might work on the tractive system or accumulator

All electrical safety items must be rated for at least the maximum tractive system voltage.

IN4 [EV ONLY] ELECTRICAL INSPECTION

IN4.1 Electrical Inspection General Definitions

IN4.1.1 The insulation resistance between the TS and LVS ground will be measured. Vehicles with a maximum TS voltage less than or equal to 250 V will be probed with 250 V and vehicles with a maximum TS voltage greater than 250 V with 500 V.

To pass this test, the measured insulation resistance must be at least 500 Ω /V related to the maximum TS voltage of the vehicle.

IN4.1.2 The IMD will be tested by connecting a resistor between the TSMP ([see EV4.7](#)) and LVS ground connector ([see EV4.7.8](#)).

The test is passed if the IMD shuts down the TS within 30 s at a fault resistance of 50% below the response value which corresponds to 250 Ω /V.

IN4.1.3 The BSPD will be tested by sending an appropriate signal that represents the current, to achieve ≤ 5 kW whilst pressing the brake pedal. This test must prove the functionality of the complete BSPD except for any commercially available current sensors. Ends of a current transducer's auxiliary winding must be insulated.

IN4.2 Electrical Inspection Required Items

IN4.2.1 The following items must be presented at electrical inspection:

- One ESO
- Vehicle with mounted TS accumulator
- Quick jack and push bar
- Samples of self designed PCBs that are part of the tractive system and are outside of the accumulator container ([see EV4.3.7](#))
- Tools needed for the BSPD check ([see T11.6.9](#))
- Data sheets for all parts used in the tractive system
- Original delivery notes for material without serial number printed on according to [T1.2.1](#)
- Tools needed for the (dis)assembly of parts for electrical inspection
- Print-outs of rule questions (if applicable)
- The connectors needed
 - to safely close the SDC while the HVD is removed and
 - to safely supply the TS using the same shrouded receptacles as used for TSMP when the TS accumulator is unconnected

IN5 MECHANICAL INSPECTION

IN5.1 Mechanical Inspection Required Items

IN5.1.1 The following items must be presented at mechanical inspection:

- The vehicle in ready-to-race condition
- [Jacks and push bar](#)
- The tallest driver of the team

- Copies of any safety structure equivalency forms
- Copies of any impact attenuator data requirement
- Print-outs of rule questions (if applicable)
- [IA test piece and \(representative\) test fixture \(except for teams with “standard” IA\)](#)
- Teams with a monocoque: laminate test specimen(s)
- Teams using alloyed steel: test specimen(s)
- Only tools needed for the (dis)assembly of parts for mechanical inspection

~~IN6 [DV ONLY] DRIVERLESS INSPECTION~~

IN7 TILT TEST

IN7.1 Tilt Test Procedure

- IN7.1.1 The tilt test will be conducted with the tallest driver fully strapped in normal driving position.
- IN7.1.2 The tilt test will be conducted with all vehicle fluids at their maximum fill level.
- IN7.1.3 The vehicle will be placed upon the tilt table and to an angle of 60°. There must be no fluid leaks and all wheels must remain in contact with the tilt table surface.

IN8 VEHICLE WEIGHING

IN8.1 Vehicle Weighing Procedure

- IN8.1.1 All vehicles must be weighed in ready-to-race condition.
- IN8.1.2 All fluids must be at their maximum fill level for weighing.

IN9 [EV ONLY] RAIN TEST

IN9.1 Rain Test General Definitions

- IN9.1.1 Vehicles must have passed electrical inspection, see [IN4](#), to attempt the rain test.

IN9.2 Rain Test Procedure

- IN9.2.1 The vehicle must be in ready-to-race condition. All components and constructions used to protect the vehicle from water during the rain test must be used during the entire competition.
- IN9.2.2 The tractive system must be active during the rain test.
- IN9.2.3 The vehicle must be jacked up using the quick jack ([see T13.2](#)) and all driven wheels must be removed.
- IN9.2.4 The vehicle must not be in ready-to-drive mode ([see EV4.11](#)).

- IN9.2.5 The test will be conducted without a driver.
- IN9.2.6 Water will be sprayed at the vehicle from any possible direction. The water spray is similar to a vehicle driving in rain and not a direct high-pressure stream of water.
- IN9.2.7 The test is passed if the IMD is not triggered while water is sprayed at the vehicle for 120s and 120s after the water spray has stopped.

IN10 [CV ONLY] NOISE TEST

IN10.1 Noise Test Procedure

- IN10.1.1 The sound level will be measured during a static test.
- IN10.1.2 The vehicle must be compliant at all engine speeds up to the maximum test speed (see CV3.2.1).
- IN10.1.3 Teams must bring a laptop to indicate the engine speed measured by the Electronic Control Unit (ECU).
- IN10.1.4 Measurements will be made with a free-field microphone placed free from obstructions at the exhaust outlet level, 0.5 m from the end of the exhaust outlet, at an angle of 45° with the outlet in the horizontal plane.
- IN10.1.5 Where more than one exhaust outlet is present, the test will be repeated for each exhaust and the highest reading will be used.
- IN10.1.6 If the exhaust has any form of active tuning or throttling device or system, it must be compliant with the rules in all positions. Manually adjustable tuning devices must require tools to change them and must not be moved or modified after the noise test is passed. The position of the device must be visible to the officials and manually operable by the officials during the noise test.
- IN10.1.7 The test will be run with the gearbox in neutral. During this test the vehicle must be jacked up using the quick jack (see T13.2).
- IN10.1.8 After passing the noise test the function of the master switch, the cockpit-mounted shutdown button and the inertia switch will be tested.
- IN10.1.9 After passing IN10.1.8 the air tightness of the intake system will be tested by closing off the inlet after which the engine must stall.

IN11 BRAKE TEST

IN11.1 Brake Test Procedure

- IN11.1.1 Lock all four wheels and stop the vehicle in a straight line at the end of an acceleration run specified by the officials without stalling the engine.

- IN11.1.2 [EV ONLY] After accelerating, the tractive system must be switched off by the driver and the driver must brake using only the mechanical brakes. It is acceptable for the TSAL to switch to green shortly after the vehicle has come to a complete stop as the reduction of the system voltage may take up to 5 s.
- IN11.1.3 The brake light and TSAL illumination will be checked and the officials will verify if the illumination is satisfactory for external observation.
- IN11.1.4 [EV ONLY] The ready-to-drive sound will be checked and the officials will verify if the sound level is satisfactory.
- IN11.1.5 If the vehicle is unable to pass the test after three attempts, the vehicle must be repaired and then brought back for retesting.

IN12 POST EVENT INSPECTION

IN12.1 Post Event Inspection Procedure

- IN12.1.1 The officials reserve the right to impound any vehicle at any time during or after any of the dynamic events to check for compliance with the rules. If necessary the vehicle will remain with the officials until the violation of the rule was discussed with the team.
- IN12.1.2 After the endurance event, the vehicle must be placed in parcfermé where no team member may access the vehicle.
- IN12.1.3 **During and after** any dynamic event, the vehicle must be in compliance with the rules.
- IN12.1.4 For each violation of the rules, the team receives a separate penalty as follows:
- Group A: Violation of the rules without advantage for the team
 - Group B: Violation of the rules with advantage for the team (e.g. aerodynamic device)

	Acceleration	Skidpad	Autocross	Endurance
Group A	0.3 s	0.2 s	2 s	30 s
Group B	1 s	0.6 s	5 s	2 min

The penalty applies to all runs since the vehicle entered the dynamic area the last time.

- IN12.1.5 Violation of the rules concerning safety or the environment (e.g. BOTS, safety harness issues, ground clearance, fluid leaks, other than plain water, noise) results in a Disqualified (DQ) since entering the dynamic area.
- IN12.1.6 Losing a part of the vehicle on the track will result in DQ for that particular run.
- IN12.1.7 Changes in vehicle weight of more than ± 5 kg compared to the official technical inspection weight (see IN8) results in a 20 point penalty for each kg the tolerance is exceeded by. E.g. a weight difference of ± 6.2 kg results in a 40 point penalty.

- IN12.1.8 [EV ONLY] The vehicle must be able to enter ready-to-drive mode (see EV4.11) during post inspection process for all tests requiring this mode. Violation will result in DQ.
- IN12.1.9 [EV ONLY] Directly after endurance and leaving parc fermé, every team must come back to the charging area to disassemble the temperature logging device (if used by the competition) from the TS accumulator (see EV5.8.5).
- IN12.1.10 [EV ONLY] Directly after endurance and leaving parc fermé, the data logger (see EV4.6) will be disassembled from the vehicle.

S STATIC EVENTS

S1 BUSINESS PLAN PRESENTATION EVENT (BPP)

S1.1 Business Plan Presentation Objective

S1.1.1 The objective of the BPP is to assess the team's ability to develop and to present a comprehensive business model. This business model must relate to the team's specific prototype vehicle or a specific component of it. In doing so, the business must offer the vehicle or component as a product, or sell a service based on it, providing a rewarding business opportunity that creates a monetary profit.

S1.1.2 The judges should be treated as if they were potential investors or partners for the presented business model.

S1.1.3 The quality of the actual prototype will not be considered as part of the BPP judging.

S1.2 Business Plan Procedure

S1.2.1 Prior to the competition, the team must submit a pitch video and participate in an online web presentation delivery [at the Business Plan Presentation Prelims \(See S1.4\)](#).

S1.2.2 The top teams are then judged by all business judges in the BPP finals at the competition.

S1.3 Pitch Video (BPPV)

S1.3.1 To convince the potential investors or partners that the team's presentation is worthy of their time, it is required that a Business Plan Pitch Video (BPPV) is submitted before the competition. The pitch video should be considered as the first impression of the business idea and has to contain the relevant investment figures.

S1.3.2 The BPPV must be submitted online via the competition website, not later than the deadline specified in the competition handbook. The BPPV must be uploaded on a video sharing platform of your choice (Youtube, Vimeo etc.). Please do not upload on Google Drive. The video link must be publicly accessible. If uploaded on Youtube, the privacy setting of the video must be changed to 'Unlisted' so that only those with the link can view the video and it will not be displayed publicly on your channel as well.

S1.3.3 The link to the BPPV should be submitted within a document consisting of only 1 (one) A4 page. The document must only include the BPPV link. No additional external links to be added.

S1.3.4 The BPPV must not exceed a length of 60 seconds.

S1.3.5 A missing pitch video submission will forfeit the team's participation in the prelims. Additionally, if the judges find the pitch video to be of 'poor form', the judges may choose to cancel the team's presentation preliminaries time slot.

S1.4 Deep Dive Topic

- S 1.4.1 Prior to the competition a specific deep dive topic, which has to be part of the ten minutes presentation, will be published on the competition website.

S1.5 Presentation Prelims

- S1.5.1 The presentation prelims shall take place virtually.
- S1.5.2 Presentations are limited to a maximum of ten minutes. The judges will stop any presentation exceeding ten minutes.
- S1.5.3 The presentation will not be interrupted by questions. Immediately following the presentation there will be a question and answer session.
- S1.5.4 One or more team members may present the business plan.
- S1.5.5 All team members involved in the BPP must have their video feed turned on, failing to do so will lead to de-registration from the Business Plan Presentation event. The presentation by team members must be delivered 'live' (i.e. not recorded, with the exception of any promotional video showcased as a part of the delivery). The team members who have been introduced may answer the judges' questions even if they were not actually presenting.
- S1.5.6 Teams that fail to make their presentation within their assigned time period will receive zero points for the BPP.
- S1.5.7 For the online presentation, teams must ensure reliability of internet connection and positioning of media transmission device for best focus and sound. Lighting of space, choice of background and external noise must be paid attention to, to avoid interruptions during the presentation. Teams may choose to switch between live presentation and media display (PowerPoint, video etc.) at any point, during the course of the presentation delivery.

S1.6 Business Plan Presentation Finals

- S1.6.1 Some teams may be chosen to participate in the BPP finals to determine the BPP winner. The BPP finals will be held separately from the initial judging and teams will be informed about their participation during the event.
- S1.6.2 The BPP finals will be a public event at the competition.
- S1.6.3 Data projectors or screens with VGA or HDMI (type A) input connectors and audio jacks will be provided for video and audio signal transmission. Teams planning to use other presentation equipment are responsible for bringing it themselves. The competition organizers shall not be liable for mishaps that may occur while connecting personal devices to data projectors or other equipment.

S1.7 Business Plan Presentation Scoring

- S1.7.1 The BPP will be evaluated on the categories specified in the following table:

Category	Points
Pitch Video	10
Novelty	5

Content	30
Finances	15
Deep Dive Topic	10
Demonstration and Structure	10
Delivery	10
Questions	10
Total	100

S1.7.2 If the business model presented does not relate to one of the areas listed within [S1.1.1](#), 25 penalty points will be deducted from the team's BPP scoring.

S1.7.3 The scoring of the BPP is based on the average of the scores given by each of the judges.

S1.7.4 The scoring for the non-finalist is calculated as followed:

$$BPP\ Score = 70 \times \frac{P_{Team}}{P_{Max}}$$

P_{Team} is the score awarded to the team

P_{max} is the highest score awarded to any team not participating in the finals

S1.7.5 The scoring of the BPP finalists will vary from 71 to 75 points and is scored immediately after the BPP finals by all judges.

S2 COST AND MANUFACTURING EVENT

S2.1 Cost and Manufacturing Objective

S2.1.1 The objective of the cost and manufacturing event is to evaluate the team's understanding of the manufacturing processes and costs associated with the construction of a prototype race car. This includes trade off decisions between content and cost, make or buy decisions and understanding the differences between prototype and mass production.

S2.2 Cost and Manufacturing Procedure

S2.2.1 Prior to the competition, three Cost Report Documents (CRD) ([see S2.3](#)) must be submitted to the competition website by the deadline specified by the competition. The Cost and Manufacturing event will have 2 rounds: Round 1: Preliminary Judging (Virtual), Round 2: Finals (On-site).

S2.2.2 Round 1: Cost and Manufacturing Prelims will take place virtually. Teams will have to showcase a live view of their physical prototype. This preliminary round shall determine which teams will move to the finals. During the virtual judging session, participants must ensure that their video is turned on and also provide a live feed of the vehicle; failure to comply with either requirement will result in disqualification from the Cost and Manufacturing Event.

S2.2.3 Round 2: Cost and Manufacturing Finals will be held at the competition on-site. Teams are allowed to bring electronic, handwritten, or printed handouts, flip charts or similar to the event, but the space available may be limited. Teams may also bring any photographs, drawings, charts, spare parts or other material that they believe are supportive to the event, but the space provided for cost and manufacturing event judging may be limited. The teams

must present their vehicle at the designated time to the judges. Teams that miss their time slot will be disqualified from the Cost and Manufacturing event.

S2.2.4 During the competition, a discussion with the judges will take place, next to the team's vehicle. The discussion is split into three parts:

S2.2.5 Part1 "Bill of Material (BOM) Discussion":

A discussion to evaluate the team's ability to prepare an accurate engineering and manufacturing BOM for the complete vehicle. The team must prove the following:

- The specification of the vehicle in the CRD accurately reflects the vehicle brought to the competition.
- The costs within the Costed Bill of Material (CBOM) part of the BOM are correct and realistic.
- The manufacturing feasibility of the vehicle.

S2.2.6 Part 2 "Cost Understanding":

A discussion to evaluate the general cost and manufacturing knowledge of the team.

S2.2.7 Part 3 "Real Case":

A specific task to evaluate the cost and manufacturing knowledge in a certain field. The real case task will be published on the competition website prior to the competition.

S2.3 Cost Report Documents (CRD)

S2.3.1 The CRD consists of the following documents:

- The BOM including DBOM and CBOM created online on the www.formulastudent.de website.
- The supporting material file uploaded as a pdf file to the competition website
- The cost explanation file uploaded as a pdf file to the competition website

S2.3.2 Changes to the CRD will not be permitted after the deadline.

S2.3.3 A changelog of the changes on the vehicle since the submission deadline of the CRD can be presented at the BOM discussion to the judges. Missing parts of the BOM cannot be part of the changelog.

S2.3.4 It is compulsory for at least one set of CRD to be presented as hard copy, printed double-sided, to the event discussion. Any additional sets can be provided as either hard copy or digital versions.

S2.3.5 The website tool will provide a printable pdf version of the BOM.

S2.3.6 The hard copy must be in a ring binder with DIN A4 pages (or similar).

S2.3.7 The team must ensure that two judges are able to review the CRD independently.

S2.3.8 The presented CRD must be identical with the uploaded versions, otherwise five penalty points will be deducted from the team's cost event score.

S2.4 Bill of Material (BOM)

S2.4.1 The BOM is a sorted list for every vehicle part.

- S2.4.2 The BOM must list all parts and equipment fitted to the prototype vehicle at any time during the competition.
- S2.4.3 The BOM is structured as follows:
- The BOM is broken down into “systems” (see [S2.4.4](#)), which are defined by the website tool.
 - Each “system” is broken down into “assemblies”, which are defined by the website tool.
 - Each “assembly” is broken down into “parts”, which must be defined by the team
 - Each “assembly” or “sub-assembly” is broken down into “parts”, which must be defined by the team.
- S2.4.4 “Fasteners” are additional items necessary to assemble the “part” and should not be listed.
- S2.4.5 A self-manufactured “fastener” is considered a “part”.
- S2.4.6 The “systems” are:
- Brake System
 - Engine and Drivetrain
 - Chassis and Body
 - Electrical
 - Miscellaneous, Fit and Finish
 - Steering System
 - Suspension System
 - Wheels, Wheel Bearings and Tires
- S2.4.7 The “assemblies” of each “system” are provided by the website tool.
- S2.4.8 When adding “parts” to the BOM, the comments section should be reviewed thoroughly. The chosen part name must clearly describe what is included. For example, if a spring is included, the “part” should not be called “damper”.
- S2.4.9 Only metric units must be used within the BOM.
- S2.4.10 Only dry tires and wheels per [T2.6.1](#) need to be included in the BOM.
- S2.4.11 Two or three systems of the BOM have to be a DBOM (see [S2.5](#)).
- S2.4.12 One or two systems of the DBOM have to be a CBOM (see [S2.6](#)).

S2.5 Detailed Bill of Material (DBOM)

- S2.5.1 The manufacturing processes and assembly processes of all parts from two or three BOM systems specified [on the competition website](#) must be listed in the DBOM.
- S2.5.2 Additional to the BOM, the DBOM must:
- Include the actual associated manufacturing processes for each part as used for the prototype vehicle.
 - Include tooling (e.g. welding jigs, molds, patterns and dies).
 - Not include any cost, except for the “systems” described in [S2.6](#).

S2.5.3 Additional to the structure of the BOM, the DBOM is structured as follows:

- Each “part” is broken down into “materials” and “processes”.
- Each “process” may be broken down into “tooling” and “fasteners”, if applicable.

S2.5.4 Each constituent “part” of an “assembly” must be classified as “bought” or “made”.

S2.5.5 For each “bought part”, only fasteners must be included (if required). If the part was modified, the associated processes for this modification must be included.

S2.5.6 For each “made part” the raw material, all production processes, tooling and all required fasteners must be included.

S2.5.7 “Processes” are the necessary operations to produce the “part” out of the “material”.

S2.5.8 “Material” is the raw material of a part, eg. aluminum.

S2.5.9 “Tooling” is the necessary tools used for transforming the “material” into the desired shape.

S2.5.10 “Fasteners” are additional items necessary to assemble the “part”.

S2.6 Costed Bill of Material (CBOM)

S2.6.1 The actual costs of the prototype vehicle as presented must be included for one or two BOM system(s) specified [in the competition website](#).

S2.6.2 The cost calculations must include the costs of materials, fabrication, bought parts and assembly to the vehicle and must be completed as realistically as possible.

S2.6.3 The cost calculations must exclude research, development and capital expenditures for real estates (e.g. plant or development hours of the team).

S2.6.4 All costs must be displayed in EUR. For calculating the prices in EUR from other currencies, the team must provide the exchange rates used.

S2.6.5 There is no maximum cost. Receipts are not required for any items.

S2.6.6 If production tooling is associated with processes that are specific to the part geometry, it must be included. For example the dies to stamp out a chassis bracket are tooling.

S2.6.7 The costs of hand or power tools must not be included.

S2.6.8 The estimations for machining rates, hourly rates, included overheads etc. must be shown.

S2.7 Supporting Material File

S2.7.1 The supporting material file is a document containing additional information which allows the judges to understand the BOM. It should include drawings, exploded view drawings and/or pictures of the vehicle and the parts included in the BOM.

S2.8 Cost Explanation File

S2.8.1 The cost explanation file is a document containing additional explanations, which allow the judges to understand the costs within the CBOM part of the BOM.

- S2.8.2 The cost explanation file should point out which cost model was used and which types of costs are included. It should also contain which specific cost figures were used, e.g. the cost of one machine operation hour.

S2.9 Cost and Manufacturing Vehicle Condition

- S2.9.1 Vehicles must be presented for cost and manufacturing judging in finished condition, fully assembled, complete, ready-to-race.
- S2.9.2 The judges will not evaluate any vehicle that is presented at the cost and manufacturing event, in what they consider to be an unfinished state and will award zero points for the entire event.
- S2.9.3 Vehicles may be presented for judging without having passed technical inspection, even if final tuning and setup is in progress.
- S2.9.4 Covers and/or parts may be removed during the judging to facilitate access and presentation of components or concepts.

S2.10 Cost and Manufacturing Scoring

- S2.10.1 The following maximum scores apply for the cost and manufacturing event:

Category	Points
Format and Accuracy of Documents	5
Knowledge of Documents and Vehicle	5
BOM and its discussion	35
Discussion Part 2 “Cost Understanding”	35
Part 3 “Real Case”	20
Total	100

- S2.10.2 If items are missing from the BOM, points are deducted until zero points are scored for “BOM and BOM discussion”:

Missing Item	Points
Assembly	-5
Part	-3
Process / Material	-1

- S2.10.3 A maximum of four top teams may be chosen to participate in the cost and manufacturing finals to determine the cost and manufacturing event winner. The cost and manufacturing finals will be held separately from the initial judging and teams will be informed about their participation during the event.

- S2.10.4 The scoring for the non-finalist is calculated as follows:

$$COST\ Score = 85 \times \frac{P_{Team}}{P_{Max}}$$

P_{Team} is the score awarded to the team

P_{max} is the highest score awarded to any team not participating in the finals

S2.10.5 The scoring of the cost and manufacturing finalists will vary from 100 to 86 points.

S2.10.6 In case of no cost finals the scoring is calculated as followed:

$$COST\ Score = P_{Team}$$

S3 ENGINEERING DESIGN EVENT

S3.1 Engineering Design Objective

S3.1.1 The concept of the Engineering Design event is to evaluate the student's engineering process and effort that went into the design of a vehicle, meeting the intent of the competition.

S3.1.2 Proprietary components and systems that are incorporated into the vehicle design as finished items are not evaluated as a student designed unit, but are only assessed on the team's selection and application of that unit.

S3.1.3 The Engineering Design event will be split into two rounds. The preliminary judging round will take place on a virtual platform, followed by a finals round that will be held at the competition site. Only a selected few teams will move into the finals round.

S3.2 Concept-Resources-Management Report (CRMR)

S3.2.1 The CRMR should be submitted prior to the deadline mentioned on the website. Based on the submitted CRMR, the team will be scored and feedback will be provided.

S3.2.2 The CRMR should contain details on the design development phase of the conceptual prototype which focuses on key highlights of the vehicle concept and the processes involved in the same. This includes but is not limited to goals (overall team goals, overall design goals, section-based goals etc.), key strategies employed (procurement, manufacturing, recruitment, budgeting, finance etc.) and management processes (team, timeline, constraints etc.)

S3.2.3 A fully built prototype is not required for this report.

S3.2.4 The CRMR must not exceed ten A4-sized pages.

S3.2.5 If included, cover sheets and tables of contents will be counted towards the ten allotted pages.

S3.2.6 The CRMR may include additional external links to references; however, it is to be assumed that the judging panel may not refer to these links.

S3.2.7 Non submission/ Incomplete / Poor submission of the CRMR will result in de-registration of the team from the ED judging event. This will be left up to the discretion of the judging panel. The CRMR guidelines and rubrics will be released separately on the competition website.

S3.3 Design Spec Sheet (DSS)

- S3.3.1 A completed DSS must be submitted online on the competition website.

S3.4 Engineering Design Presentation (EDP)

- S3.4.1 The EDP acts as a formal introduction of the final prototype's design to the design judges. It will be submitted prior to the engineering design judging event.

- S3.4.2 The EDP should be considered as an extension to the CRMR, with a primary focus on the engineering design of the prototype and the reasoning behind the design.

- S3.4.3 The EDP is a maximum 20 minute recorded video presentation which should contain a brief description of the overall vehicle's engineering design with a review and derivation of the team's design objectives. Any information to scope, explain or highlight design features, concepts, methods or objectives to express the value and performance of the vehicle to the judges shall be included at the teams' discretion.

TIP: Do not cram too many slides within a minute of presentation. Try to keep the slides less heavy on text. Do not fast forward the audio; ensure coherence. Remember, this presentation is just meant to be an introduction.

- S3.4.4 The EDP must be uploaded on a video sharing platform of your choice (Youtube, Vimeo etc.). Please do not upload on Google Drive. The video link must be publicly accessible. If uploaded on Youtube, the privacy setting of the video must be changed to 'Unlisted' so that only those with the link can view the video and it will not be displayed publicly on your channel as well.

- S3.4.5 The link to the EDP should be submitted within a document consisting of 1 (one) A4 cover page. The page may include additional external links to references; however, it is to be assumed that the judging panel may not refer to these links.

S3.5 Engineering Design Event Procedure

- S3.5.1 The design event starts with the submission of the CRMR, DSS, EDP and their review respectively.

- S3.5.2 Prior to the competition, teams will present their knowledge and their vehicle to the judges during a preliminary round via a virtual platform, which will evaluate the teams' performance following the design objectives stated in S3.1. During the Preliminary round, participants must ensure that their video is turned on and also provide a live feed of the vehicle; failure to comply with either requirement will result in disqualification from the Engineering Design Event.

- S3.5.3 Some teams may be chosen to participate in the design finals at the competition site to determine the engineering design event winner. Teams that have been selected for the finals will be informed about their participation during the event.

- S3.5.4 Teams may showcase any photographs, drawings, charts, spare parts or other material that they believe are supportive to the design event. For the finals, participating teams must note that the space provided will be limited.

S3.5.5 [EV ONLY] Only sealed accumulator containers which passed the accumulator inspection may be presented or mounted in the vehicle. They must not be opened.

S3.5.6 [EV ONLY] At the finals, only discharged, below 5% State of Charge, accumulator cells each having all terminals electrically isolated may be presented.

S3.6 Engineering Design Vehicle Condition

S3.6.1 For the virtual preliminary design judging round, the vehicle need not be in ready-to-race condition, but it is mandatory to present a live video feed with the vehicle in focus. A fully assembled vehicle is preferable.

S3.6.2 For the finals, the vehicles must be presented in finished condition, fully assembled, complete and ready-to-race. The judges will not evaluate any vehicle that is presented at the design event in what they consider to be an unfinished state and will award zero points for the entire design event.

S3.6.3 Vehicles may be presented for design judging without having passed technical inspection, even if final tuning and setup is in progress.

S3.6.4 Covers and/or parts may be removed during the design judging to facilitate access and presentation of components or concepts.

S3.7 Engineering Design Judging Criteria

S3.7.1 The judges will evaluate the engineering effort based upon the team's CRMR, DSS and EDP responses to questions and an inspection of the vehicle.

S3.7.2 The judges will inspect the vehicle to determine if the design concepts are adequate and appropriate for the application (relative to the objectives set forth in the rules).

S3.7.3 The judges may deduct points if the team cannot adequately explain the engineering and construction of the vehicle.

S3.7.4 The rubrics for each round will be made available on the competition website.

S3.8 Engineering Design Scoring

S3.8.1 The overall engineering design event maximum scoring is 150 points for CV/EV.

• CRMR	30 pts
• EDP, DSS, Design Judging Prelims	60 pts
• Design Judging Finals	60 pts
	150 pts

D DYNAMIC EVENT REGULATIONS

D1 DYNAMIC EVENTS GENERAL

D1.1 Driver Limitations

D1.1.1 In total, a minimum of four and a maximum of six drivers are allowed for each team.

D1.1.2 An individual driver may not drive in more than two dynamic events.

D1.1.3 The endurance and efficiency event is considered a single event.

D1.2 Dynamic Area and Dynamic Vests

D1.2.1 The technical inspections and all dynamic events are held in the dynamic area.

D1.2.2 Four dynamic vests are handed out to each team by the officials and must be worn in the dynamic area.

D1.2.3 Only four members per team, including the driver, may enter the dynamic area.

D1.2.4 Drivers must not wear the dynamic vest when sitting in the vehicle. The driver's vest must not be attached to the vehicle.

D1.2.5 The number of tools that may be used in this area is restricted to those which can be safely carried by the four team members in one trip.

D1.2.6 Engines may be run in the staging queue on the order of the officials.

D2 DRIVING RULES

D2.1 Flags

D2.1.1 Flag signals are commands that must be obeyed immediately and without question.

~~D2.1.2 [DV ONLY]~~

D2.1.3 BLACK FLAG – The driver must pull into the driver change area for discussion with the officials concerning an incident. A time penalty may be assessed.

D2.1.4 BLACK FLAG WITH ORANGE DOT – Mechanical black flag. The driver must pull into the driver change area for a mechanical inspection of the vehicle, something has been observed that requires a closer inspection.

D2.1.5 BLUE FLAG – The driver must pull into the designated passing zone to be passed by a faster competitor. The driver must obey the track marshals' signals at the end of the passing zone.

D2.1.6 CHECKERED FLAG – The session has been completed. The driver must exit the course at the first opportunity.

D2.1.7 GREEN FLAG –

- a. The session has started, the driver may enter the course under direction of the track marshals. In case of stalling, the vehicle can be restarted, but the driver has to await another green flag as the opening in traffic may have closed.
- b. The driver is clear to re-enter the track after using the slow lane to let a faster vehicle pass.
- c. The driver may pick up speed again after a yellow flag was displayed.

D2.1.8 RED FLAG – The driver must come to an immediate safe and controlled stop on the course and must follow track marshals directions.

D2.1.9 YELLOW FLAG – Danger, the driver must slow down, something has happened beyond the flag station, no overtaking unless directed by the track marshals.

D2.1.10 RED AND YELLOW STRIPED FLAG – The track is slippery or something is on the racing surface that should not be there. The driver must be prepared for evasive maneuvers to avoid the situation.

D2.2 Driving Under Power

D2.2.1 During driving, the mechanical integrity of the vehicle must be maintained.

D2.2.2 Vehicles must not be driven in reverse.

D2.2.3 The vehicle must be capable of starting and restarting without external assistance / batteries at all times.

D2.2.4 Push starts are prohibited.

D2.2.5 Vehicles may only be driven under power when running in a dynamic event, on the practice track and during brake test.

D2.2.6 Driving off-site is absolutely prohibited. Teams found to have driven their vehicle at an off-site location during the period of the competition will be excluded from the competition.

D2.2.7 Burnouts prior to and during the events are prohibited.

D2.3 Ground Clearance

D2.3.1 Sliding skirts or other aerodynamic devices that by design, fabrication or as a consequence of moving, contact the track surface are prohibited. Any violation may be penalized by a mechanical black flag.

D2.3.2 The ground clearance may be tested at any time.

D2.4 Practice Track

D2.4.1 A practice track for testing and tuning vehicles is available.

~~D2.4.2~~ [DV ONLY]

D2.4.3 To use the practice track, vehicles must have passed all technical inspections.

D2.4.4 Practice or testing at any location other than the practice track is absolutely forbidden.

D3 WEATHER CONDITIONS

D3.1 Operating Conditions

D3.1.1 The following track conditions are recognized:

- Dry
- Damp
- Wet

D3.1.2 The operating condition is decided by the officials and may change at any time.

D3.1.3 The current operating condition will be prominently displayed at the dynamic area.

D3.2 Tires Allowed

D3.2.1 Teams must run the tires allowed for each operating condition:

Operating Condition	Tires Allowed
Dry	Dry
Damp	Dry or Wet
Wet	Wet

D3.2.2 When the operating condition is damp, teams may change between dry tires and wet tires:

- Any time during the acceleration, skidpad, and autocross events.
- Any time before taking the green flag to start endurance.

D3.2.3 If an event had varied operating conditions, the minimum performance levels to score points may be adjusted if deemed appropriate by the officials.

D3.2.4 Only one set of tires per type (dry/wet) may be used during all the dynamic events. The brake test, practice area and the static events are excluded from this regulation.

D4 SKIDPAD EVENT

D4.1 Skidpad Track Layout

D4.1.1 The skidpad course consists of two pairs of concentric circles in a figure of eight pattern.

D4.1.2 The centers of these circles are 18.25 m apart. The inner circles are 15.25 m in diameter and the outer circles are 21.25 m in diameter.

D4.1.3 16 cones are placed around the inside of each inner circle. 13 cones are positioned around the outside of each outer circle, in the pattern shown in the skidpad layout diagram.

- D4.1.4 Each circle is marked with a line, outside the inner circle and inside the outer circle.
- D4.1.5 The driving path is the 3 m wide path between the inner and outer circles. The vehicles enter and exit through gates on a 3 m wide path that is tangent to the circles where they meet.
- D4.1.6 The line between the centers of the circles defines the start/finish line. A lap is defined as traveling around one of the circles, starting and ending at the start/finish line.




Figure 22: Skidpad Track Layout

D4.2 Skidpad Procedure

- D4.2.1 Each team has four runs, driven by two drivers with two runs each.
- D4.2.2 Each driver has the option to make a second run immediately after their first run.
- D4.2.3 The starting order is based on the time the team arrives at the skidpad event. Teams on their first run will receive priority.
- D4.2.4 Starting - A green flag is used to indicate that the driver may start.
- D4.2.5 The vehicle will enter perpendicular to the figure of eight and will take one full lap on the right circle to establish the turn. The next lap will be on the right circle and will be timed. Immediately following the second lap, the vehicle will enter the left circle for the third lap. The fourth lap will be on the left circle and will be timed. Immediately upon finishing the fourth lap, the vehicle will exit the track perpendicular to the figure of eight and moving in the same direction as entered.

~~D4.3~~ — ~~[DV ONLY]~~ Skidpad Procedure

D4.4 Skidpad Scoring

- D4.4.1 The run time is the average time of the timed left and the timed right circle plus penalties which are added after the averaging.
- D4.4.2 5% of the maximum points for the event according to table 3 are awarded to every team that finishes at least one run without DNF or DQ.
- D4.4.3 If a team's run time including penalties is below $T_{\max}$, additional points based on the following formula are given:

$$SKIDPAD_SCORE = 0.95 P_{\max} \left(\frac{\left(\frac{T_{\max}}{T_{\text{team}}} \right)^2 - 1}{0.5625} \right)$$

$P_{\max}$ is the maximum points for the event according to table 3.

T_{team} is the team's best run time including penalties.

$T_{\max}$ is 1.25 times the time of the fastest vehicle including penalties.

D5 ACCELERATION EVENT

D5.1 Acceleration Track Layout

- D5.1.1 The acceleration track is a straight line with a length of 75 m from starting line to finish line. The track is at least 3 m wide. Cones are placed along the track at intervals of about 5 m.

D5.2 Acceleration Procedure

- D5.2.1 Each team has four runs, driven by two drivers with two runs each.
- D5.2.2 Each driver has the option to make a second run immediately after their first run.
- D5.2.3 Staging - The foremost part of the vehicle is staged 0.30 m behind the starting line. Vehicles will accelerate from a standing start.
- D5.2.4 Starting - A green flag is used to indicate that the driver may start. Timing starts after the vehicle crosses the starting line and stops after it crosses the finish line.
- D5.2.5 The starting order is based on the time the team arrives at the acceleration event. Teams on their first run will receive priority.

~~D5.3~~ — ~~[DV ONLY]~~

D5.4 Acceleration Scoring

- D5.4.1 5% of the maximum points for the event according to table 3 are awarded to every team that finishes at least one manual mode run without a DNF or DQ.

D5.4.2 If a team's best time including penalties is below $T_{\max}$, additional points based on the following formula are given:

$$ACCELERATION_SCORE = 0.95 P_{\max} \left(\frac{\frac{T_{\max}}{T_{\text{team}}} - 1}{0.5} \right)$$

$P_{\max}$ is the maximum points for the event according to table 3.

T_{team} is the team's best run time including penalties.

$T_{\max}$ is 1.5 times the time of the fastest vehicle including penalties.

D6 AUTOCROSS EVENT

D6.1 Autocross Track Layout

D6.1.1 The autocross track layout is a handling course built to the following guidelines:

- Straights: No longer than 80 m
- **Constant Turns: up to 50 m diameter**
- Hairpin Turns: Minimum of 9 m outside diameter (of the turn)
- Slaloms: Cones in a straight line with 7.5 m to 12 m spacing
- Miscellaneous: Chicanes, multiple turns, decreasing radius turns, etc.
- The minimum track width is 3 m.

D6.1.2 The length of the autocross track is less than 1.5 km.

D6.2 Autocross Procedure

D6.2.1 Each team has up to four runs, driven by two drivers with two runs each.

D6.2.2 Each driver has the option to make a second run immediately after their first run.

D6.2.3 Staging - The vehicle is staged at a staging line prior to the starting line.

D6.2.4 Starting - A green flag is used to indicate that the driver may start. Timing starts only after the vehicle crosses the starting line and stops after it crosses the finish line.

D6.2.5 The starting order is based on the time the team arrives at the autocross event. Teams on their first run will receive priority.

D6.3 Autocross Scoring

D6.3.1 5% of the maximum points for the event according to table 3 are awarded to every team that finishes at least one run without DNF or DQ.

D6.3.2 If a team's corrected elapsed time is below $T_{\max}$, points based on the following formula are given:

$$AUTOCROSS_SCORE = 0.95 P_{\max} \left(\frac{\frac{T_{\max}}{T_{\text{team}}} - 1}{0.25} \right)$$

$P_{\max}$ is the maximum points for the event according to table 3.

T_{team} is the team's best run time including penalties.

$T_{\max}$ is 1.25 times the time of the fastest vehicle including penalties.

D7 ENDURANCE AND EFFICIENCY EVENT

D7.1 Endurance Track Layout

D7.1.1 The endurance track layout is a closed lap circuit built to the following guidelines:

- Straights: No longer than 80 m
- Constant Turns: up to 50 m diameter
- Hairpin Turns: Minimum of 9 m outside diameter (of the turn)
- Slaloms: Cones in a straight line with 9 m to 15 m spacing
- Miscellaneous: Chicanes, multiple turns, decreasing radius turns, etc.
- The minimum track width is 3 m

D7.1.2 The length of one lap of the endurance track is approximately 1 km.

D7.1.3 The length of the complete endurance is approximately 22 km.

D7.2 Endurance Procedure

D7.2.1 Before entering the event, each CV's fuel tank must be filled to the fuel level line (see [CV2.6.3](#), "Fuel Level Line") at the fueling station. During fueling, once filled to the scribe line, no shaking or tilting of the tank, the fuel system or the entire vehicle is allowed.

D7.2.2 There is only one run for the endurance event.

D7.2.3 Staging - The vehicle is staged at a staging line prior to the starting line. The timer starts only after the vehicle crosses the start line.

D7.2.4 Starting - A green flag is used to indicate that the driver may start. Timing starts only after the vehicle crosses the starting line.

D7.2.5 The first driver will drive for 11 km and will then be signaled into the driver change area.

D7.2.6 After the driver change specified in [D7.4](#), the second driver will drive for an additional 11 km and will be signaled to exit the track after crossing the finish line.

D7.2.7 After leaving the track, the vehicle must be powered down.

D7.2.8 For CV, the second driver will proceed directly to the fueling station. The tank will be filled to the refill mark and the amount of fuel will be recorded.

D7.3 Endurance Running Order

- D7.3.1 The running order for the endurance will be established in a way that vehicles with similar speeds shall be on the track together.
- D7.3.2 The running order will be published as announced on [the competition website](#).
- D7.3.3 The procedure for handling the running order will be defined [on the competition website](#).

D7.4 Passing

- D7.4.1 During the endurance event, overtaking is only permissible in the designated passing zones and under the control of the track marshals.
- D7.4.2 Passing zones have two parallel lanes, a slow lane only used by the vehicles that are being overtaken and a fast lane for the vehicles that are overtaking.
- D7.4.3 Passing zones may be situated on either the left or right of the fast lane.
- D7.4.4 The passing zone procedure will be as follows:
- A slower leading vehicle will be shown the blue flag and must drive into the slow lane and decelerate.
 - The following faster vehicle will continue in the fast lane to pass the slow vehicle.
 - The vehicle that has been overtaken may re-enter the track when the track marshal who is in charge of that passing zone is showing the green flag.
- D7.4.5 The passing rules do not apply to vehicles that are stopped on track or vehicles that have spun out and are not moving. When passing a stationary vehicle, it is critical to slow down, drive cautiously and to follow the instructions from the track marshals.

D7.5 Endurance Driver Change Procedure

- D7.5.1 Only three team members including the driver may enter the driver change area. They may only bring the tools required to adjust the vehicle to accommodate the second driver and/or change tires.
- D7.5.2 For electric vehicles one of the team members must be an ESO.
- D7.5.3 During the driver change, the team may:
- perform changes to accommodate the second driver
 - operate the master switch(es)
 - change tires as per [D7.5](#).
- No other work may be performed during the driver change.
- D7.5.4 Each team is given three minutes to change their driver.
- D7.5.5 The driver change time will start once the vehicle is stopped in the driver change area and the first driver has turned off the engine for CV or turned off the tractive system for EVs.
- D7.5.6 [EV ONLY] The TSMS must be switched off by the ESO and the TSAL must have changed to green color, before anyone is allowed to touch the vehicle or to climb out the vehicle.

- D7.5.7 The first driver will climb out the vehicle and any necessary adjustments will be made to the vehicle to fit the second driver (seat cushions, head restraint, pedal position, etc.). The second driver will then be secured in the vehicle.
- D7.5.8 When the second driver is fully secured in the vehicle, the vehicle has restarted and is ready-to-drive again, the driver change time is stopped.
- D7.5.9 If the driver change takes longer than three minutes, the extra time is included in the final time.

D7.6 Endurance Event Tire Changes

- D7.6.1 All tire changes after a vehicle has received the green flag to start the endurance event must take place in the driver change area.
- D7.6.2 If the operating condition changes to wet during endurance, the track will be red flagged and all vehicles brought into the driver change area.
- D7.6.3 If a team wants to change tires, the officials must be informed beforehand.
- D7.6.4 In some cases, tire changes can be carried out directly after the driver change, for others the team must make an extra stop.
- D7.6.5 The allowed tire changes and associated conditions are given in the following tables.

Existing Operating Conditions	Currently Running on	Condition changes to Dry	Condition changes to Damp	Condition changes to Wet
Dry	Dry Tires	–	A	B
Damp	Dry Tires	–	A	B
Damp	Wet Tires	C	C	–
Wet	Wet Tires	C	C	–

	Requirement	Allowed at Driver Change?	Time Allowed
A	May change from dry to wet	Yes	Note 1
B	Must change from dry to wet	Yes	Note 1
C	May change from wet to dry	No	Note 2

Note 1: Any time in excess of ten minutes without driver change, or thirteen minutes with driver change, is added to the team's total time for endurance.

Note 2: The time used to change to dry tires is added to the team's total time for endurance.

- D7.6.6 Teams that have incurred a puncture during the endurance event due to external factors (e.g. debris on track) may change the tire with no time penalty, [if the vehicle reaches the driver change area under its own power without external assistance](#).
- D7.6.7 The wheel will be inspected by the officials. If the deflation was not caused by external factors, the vehicle will be scored DNF.

- D7.6.8 Deflation caused by running off course or impacting barriers or other objects due to driver error will not be regarded as external factors.

D7.7 Endurance Specific Regulations

- D7.7.1 Teams are prohibited from working on or fueling their vehicles during the run.
- D7.7.2 Wheel-to-wheel racing is prohibited.
- D7.7.3 If a vehicle stalls out on the track, it is allowed one lap by the vehicle that is following it (approximately one minute) to restart.
- D7.7.4 If a vehicle has a restart problem at the driver change or after a red flag, it is allowed 2 min to restart the engine or to enable the TS. The 2 min start from the time the driver first tries to restart the engine or to enable the TS. The time is added to the endurance time.
- D7.7.5 If restarts are not accomplished within the above times, the vehicle is scored as DNF for the run.
- D7.7.6 If a vehicle breaks down it will be removed from the course and will not be allowed to re-enter the course.
- D7.7.7 Team members may be instructed by the officials to retrieve broken down vehicles. This recovery may only be carried out under the control of the officials.

D7.8 Endurance Scoring

- D7.8.1 Each lap of the endurance event is individually timed. The corrected elapsed time is determined by subtracting the extra-long lap for the driver change from the total time and adding any penalty times.
- D7.8.2 The post event technical inspection (see IN12) must be passed to score points in the endurance event.
- D7.8.3 10% of the maximum points for the event according to table 3 are awarded to every team that finishes endurance without DNF or DQ.
- D7.8.4 If a team's corrected elapsed time is below T_{max} , additional points based on the following formula are given:

$$ENDURANCE_SCORE = 0.9 P_{max} \times \left(\frac{\frac{T_{Max}}{T_{team}} - 1}{0.1} \right)$$

P_{max} is the maximum points for the event according to table 3.

T_{team} is the team's corrected elapsed time.

T_{max} is 1.1 times of the corrected elapsed time of the fastest vehicle.

D7.9 Efficiency Scoring

- D7.9.1 Efficiency is measured during the endurance event.

D7.9.2 Only vehicles which meet all of the following requirements are considered for efficiency scoring:

- the vehicle received points for the endurance event
- the uncorrected elapsed endurance time does not exceed 1.1 times the uncorrected elapsed time of the fastest vehicle
- [CV ONLY] the consumed fuel mass does not exceed 15 kg / 100 km 91 Octane

D7.9.3 [CV ONLY] Fuel pumps must be on and fuel valves must be opened during refueling.

~~D7.9.4 [CV ONLY] The measured fuel mass of vehicles using E85 fuel is divided by 1.45 to be comparable to the vehicles using 98 RON.~~

D7.9.5 [EV ONLY] The endurance energy is calculated as the time integrated value of the measured voltage multiplied by the measured current logged by the data logger, see EV4.6. Regenerated energy is multiplied by 0.9 and subtracted from the used energy.

D7.9.6 Efficiency points based on the following formula are given:

$$EFFICIENCY_SCORE = P_{max} \left(\frac{EF_{max} - EF_{team}}{EF_{max} - EF_{min}} \right)$$

with

P_{max} is the maximum points for the event according to table 3

EF_{team} the team's efficiency factor

EF_{min} the lowest efficiency factor of all teams which were considered for efficiency

EF_{max} is defined as $1.5 \cdot EF_{min}$

D7.9.7 The efficiency factor is calculated based on the following formula:

$$EF = T^2 \cdot E$$

with

T uncorrected elapsed driving time

E [CV ONLY] corrected used fuel volume / [EV ONLY] used energy

~~D8 [DV ONLY] TRACKDRIVE AND EFFICIENCY EVENT~~

D9 DYNAMIC EVENTS PENALTIES

D9.1 General Penalties

D9.1.1 Penalties will not be assessed for accident avoidance or other reasons deemed sufficient by the officials.

D9.1.2 A cone is Down or Out (DOO) if the cone has been knocked over or the entire base of the cone lies outside the box marked around the cone in its undisturbed position.

~~D9.1.3~~ ~~[DV ONLY]~~

D9.1.4 The DOO penalty (see [D9.1.7](#)) is added for each DOO including entry and exit gate cones before the start and after the finish line, that occur on that particular run.

D9.1.5 Off-course (OC)

- An OC occurs when the vehicle has all four wheels outside the course boundary as indicated by edge marking.
- Missing one or more gates of a given slalom at autocross or endurance is counted as one OC per occurrence.
- When an OC occurs, the driver must re-enter the track at the next possible point.
- When re-entering the driver needs to wait for a gap and follow the instructions of the track marshals.

~~D9.1.6~~ ~~[DV ONLY]~~

D9.1.7

	Acceleration	Skidpad	Autocross	Endurance
DOO	2 s	0.2 s	2 s	2 s
OC	DNF	DNF	10 s	10 s

D9.1.8 DNF equals zero points for that run.

D9.1.9 DQ equals zero points for that run.

D9.1.10 If a team Did Not Attempt (DNA) an event the score is zero points.

D9.1.11 Each run with an incorrect number of laps at skidpad is classified as DNF.

D9.1.12 Failure to obey a flag: one minute time penalty.

D9.1.13 Reckless or aggressive driving or “Over Driving”: black flag (see [D2.1.3](#))

D9.1.14 Vehicle to vehicle contact: Two minutes up to disqualification depending on the nature of the incident.

D9.1.15 If a vehicle stalls before passing the finish line and cannot restart without external assistance, the vehicle is DNF for that run.

D9.1.16 If a vehicle is not able to start the run, within 30 s after receiving a green flag or go-signal, the vehicle is DQ for that run.

D9.2 Endurance Penalties

D9.2.1 Teams that are running out-of-order as defined [on the competition website](#), are penalized by two minutes and may then run at the discretion of the officials.

-
- D9.2.2 Mechanical Problem: The time taken for mechanical inspection under a “mechanical black flag” (see [D2.1.4](#)) is considered officials’ time and is not included in the team’s total time. If the inspection reveals a mechanical integrity problem the vehicle is scored DNF.
- D9.2.3 If it is impossible to impose a penalty by a stop under a black flag, e.g. not enough laps left, the officials may add an appropriate time penalty to the team’s elapsed time.
- D9.2.4 A team may be disqualified if their vehicle is too slow or being driven without proper control. A vehicle is considered to be too slow if the average speed, based on lap times, for two consecutive laps is below 8 m/s in dry conditions or below 5 m/s in wet or damp conditions.
- D9.2.5 Any violation to the procedure of driver change ([D7.5.3](#)) will lead to a time penalty of up to two minutes.
- D9.2.6 All rules and penalties from IN12 are also applicable during driver change.
- D9.3 [CV ONLY] Efficiency Penalties**
- D9.3.1 Should the fuel level change after refueling due to effects such as described in [CV2.7.1](#), then the difference in fuel level will be measured and twice the amount will be added to the official fuel consumption figure.
- D9.4 [EV ONLY] Power and Voltage Violation Penalties**
- D9.4.1 A violation is defined as using more than the maximum power (see [EV2.2](#)) or exceeding the specified voltage (see [EV4.1.1](#)) after a moving average over 500 ms is applied to the respective data logger signal (see [EV4.6](#)).
- D9.4.2 Each violation is a DQ for the fastest valid run of the event. If a violation occurred during two runs, the two fastest valid runs will be DQ etc.
- D9.4.3 The respective data and the resulting decision of violations may be made public.
- D9.4.4 Non-availability of data logger data due to the team’s fault will be treated as a violation.