Rubrica: Systems Design

Learning a black box, one proven rule at a time

Reto 2 · La caja negra · rubrica.dev · Kevin Vicent · v8

The black box is an unknown decision procedure. We find its rules with experiments. We prove each rule against the real service. Then we compile the rules into a deterministic replica. Most agent systems need an LLM judge. Our system has an exact judge: the original service.

1. Problem

A legacy **ledger service** receives text messages on `POST /msg`. The body is `{"m": "CMD;arg…;control"}`. The commands are `PING`, `ALTA`, `CONSULTA`, `DEPOSITO`, `TRANSFER` and `ANULA`. The service also has `/__reset` and `/health`.

We must build a replacement. After `/__reset`, each response must have **the same status and body** as the original. The tests do not compare headers or JSON key order. There are **100 hidden tests**: 40 single requests, 45 sequences of 2–5 steps, 15 sequences of 6–12 steps. Every quirk is part of the contract (Hyrum's Law): `"recieved"`, `"comando desconocido "`, `cuentaId` vs. `cuenta_id`. The replica must not call the original. **The service changes during the day. The tests use the 20:00 version.**

ID	Assumption	Status	How we test it
A1	The output depends only on state and request	open	Replay one sequence twice after reset
A2	Each token has its own state; `/__reset` restores `AC-0001`, `OP-0001`	README	Reset, then repeat a sequence
A3	The control is an integer checksum on the arguments only (values 3–98)	hypothesis	Fit offline, then targeted probes
A3b	The control is checked before the account lookup	**proven**	Bad control + missing account → E202
A4	Tests are sequential	README	—

Hard cases: the control formula · auth (team token, other token, no token) · **error precedence** (E2xx integrity, E301/E302 syntax, E401 lookup, E506/E507 business) · ID sequences · `ANULA` twice · limits · unknown routes · **drift**.

Out of scope: headers (the tests do not compare them) · latency under the 5 s step limit.

3. How we measure: evals first

We optimize against evals and protect them from Goodhart's Law: **corpus** = train · **held-out fuzz** = test · **canary** = "is the eval still true?" · **hidden set** = final test.

- **M1 Exact match** (official comparator): 100% on the corpus (versioned per service version) and the 20 `ejemplos`; **≥ 95% on held-out fuzz**. We never fix code against held-out fuzz.
- **M2 Coverage:** command × precondition × error matrix. Low-confidence rules and empty cells first. **Budget: 8,000 requests/day, 10/s per token.** Plan (565 already spent): 1,435 discovery · 2,500 fuzz · 500 canary · 3,000 reserve.
- **M3 Drift:** a 10-request canary every 10 min (480 requests, 12:00–20:00). Full replay only if it fails. Detect in ≤ 10 min, fix in ≤ 45 min.
- **Checksum eval:** predict all logged controls (train) and new strings with digits, lowercase and accents (test).
- **Seeded tests:** each error alone and **in pairs**, control ±1, case variants, arity ±1, `ANULA` twice, transfers near the limit.
- **3 validations:** only if M1 did not decrease (~13:30, ~17:30, ~19:30).

2. Architecture: dual-process, one ontology

1. **Agent harness (System 2, offline).** A person and a reasoning model use only recorded tools: `probe`, `sequence`, `fuzz`, `shrink`, `diff`. Each request becomes one line of `experimentos.jsonl`, with its hypothesis and `X-Req`. **Rule: no request without a prediction.** A code gate (a planned `beforeToolCall` hook) blocks a request if it has no prediction, if the log already predicts it, or if it exceeds the budget.
2. **Hypothesis search, not answer search.** Our first sweep tried controls 0–99 and used 543 requests. Now the harness fits candidate rules offline, at zero cost. Then it sends the request that eliminates the most candidates. **Target: one formula in fewer than 50 probes.**
3. **Service ontology (memory).** Each rule is typed: `Rule{command, when, then, effect, evidence, confianza}`. The checksum is a typed slot: `Checksum{scope, mapping, base, modulus, transform}`. One table does three jobs: the replica **executes** it, `SPEC.md` is **generated** from it (7 sections, `confirmado / probable / supuesto`), and the tests come from its evidence.
4. **Replica (System 1, runtime).** HTTP adapter → serial queue → decision core `handle(state[token], msg) → (state, resp)`. Order (we still test this precedence): route → auth → parse → control → command → arity → lookup → business rule → effect. State is in memory.

Decision	Chosen	Rejected, and why
Runtime	**Compiled rule table**	*LLM in the replica (allowed, ≤ 5 s):* not exact, not repeatable. *Record and replay:* fails on new inputs.
Discovery	**A person and a model in a harness**, exact oracle	*Free LLM chat:* no proof, no log. *Autonomous agent:* false spec claims lose points. *Manual curl:* too slow.
Knowledge	**Typed ontology**, one source for code, spec and tests	*Separate spec, code and tests:* they diverge after the change. *RAG over logs:* approximate recall.
Checks	**Code for all exact checks** (budget gate, checksum, rule replay). A **System One classifier** only for drift triage and model routing; it fails closed.	*LLM judge as verifier:* false passes. The original is a free, exact judge.
Server and hosting	**Minimal server we control** (exact bodies, also for unknown routes); **one always-on instance**	*Framework defaults:* different 404/405 bodies. *Autoscaling:* each instance has its own state.

Risks: formula outside our family (add candidates, probe again) · budget runs out (cache, never repeat) · late drift (canary runs until 20:00).