

National University of Computer and Emerging Sciences



**Lab Manual**  
*for*  
**Object Oriented Programming**

Course Instructor	Dr. Saira Karim
Lab Instructor(s)	Ms. Sonia Anum Ms. Mamoon Akbar
Section	OOP BSCS-2A
Semester	Spring 2022

Department of Computer Science  
FAST-NU, Lahore, Pakistan

**Lab Manual 6**

## Objectives:

After performing this lab, students shall be able to:

- ✓ Create overloaded constructors
- ✓ Create destructors
- ✓ Handle dynamic memory for class data members as well as declaring objects.

## **Problem 1**

In this task, we are going to create a small scale **Event Management System**. First make two files: **event.cpp**, **event.h** to separate class header and implementation.

1. Create a **class Event** with following variables: **char\* event\_name**, **char\* event\_venue**, **char event\_date[11]** and **char event\_time[9]**.
  - Input format for event\_date: dd-mm-yyyy
  - Input format for event\_time: hh:mm am/pm
2. Implement default constructor and overloaded constructor. Print “Default Constructor Called” and “Overloaded Constructor Called” in the respective constructors. The declaration for overloaded constructor is as follows:
  - **Event(char event\_name[20], char event\_venue[50], char event\_date[11], char event\_time[9]);**
3. Implement all setters and getters for class Event.
4. Implement the destructor **~Event()** for class **Event**. Print “Destructor Called” in the destructor. Deallocate all the dynamically allocated memory of class data members.
5. Implement **addEventOver** function that should not be a part of Event class. This function will add a new **Event** using overloaded constructor.  
**Event\* addEventOver(Event \*eve);**
6. Implement **addEventSet** function that should not be a part of Event class. This function will add a new **Event** using setters.  
**void addEventSet(Event eve);**
7. Implement **displayEvent()** function. This will display event details of dynamic class object. You can use getters in this function.

### **Sample Menu Program:**

*Menu Program*

*Add New Event Using Overloaded Constructor: Enter 1*

*Add New Event Using Setters: Enter 2*

*Display Event: Enter 3*

*Exit: Enter 0*

*Enter your choice: 1*

*Add New Event*

*Enter event name: Programming 101*

*Enter event venue: Rafaqat Ali Auditorium*

*Enter event date: 06-10-2020*

*Enter event time: 11:30 AM*

### **Note:**

- Deallocate all dynamically allocated memory.
- Do not use copy constructor.
- Do not use strcpy() function. Copy the character array manually where needed based on ending '\0' character.
- Follow all the code indentation, naming conventions and code commenting guidelines.