FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

GEOTECHNICAL INVESTIGATION

Halden Prairie Subdivision

Prepared by Bexley Geoscience

August 4, 2026

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

2.0 FIELD EXPLORATION

Twenty-two borings were drilled to depths of 15 to 25 feet.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

APPENDIX

Boring logs and laboratory test results (not reproduced in text).

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

TABLE OF CONTENTS

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

3.3 GROUNDWATER

Groundwater was not encountered during drilling in the northern and central borings. In the southwest quadrant, groundwater was encountered between 5.5 and 7.0 feet below existing grade in borings B-14 through B-18. Groundwater levels will fluctuate seasonally.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

APPENDIX

Boring logs and laboratory test results (not reproduced in text).

TABLE OF CONTENTS

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

2.0 FIELD EXPLORATION

Twenty-two borings were drilled to depths of 15 to 25 feet.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.

4.2 SOIL PLASTICITY

Atterberg limits tests were performed on the near-surface clays. The plasticity indices ranging from 38 to 52 indicate a high potential for volume change. Building pads should include at least 2 feet of select fill or moisture-conditioned subgrade.

TABLE OF CONTENTS

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

2.0 FIELD EXPLORATION

Twenty-two borings were drilled to depths of 15 to 25 feet.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.

APPENDIX

Boring logs and laboratory test results (not reproduced in text).

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

TABLE OF CONTENTS

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

6.4 DETENTION POND EXCAVATIONS

Pond side slopes should be no steeper than 4 horizontal to 1 vertical. Due to shallow groundwater, excavations deeper than 6 feet in the southwest will require dewatering and evaluation of a liner.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

APPENDIX

Boring logs and laboratory test results (not reproduced in text).

7.1 PAVEMENT RECOMMENDATIONS

For residential streets we recommend 7 inches of reinforced concrete over 6 inches of lime-stabilized subgrade. Lime application rates should be confirmed by laboratory testing prior to construction.

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

2.0 FIELD EXPLORATION

Twenty-two borings were drilled to depths of 15 to 25 feet.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

8.2 UTILITY TRENCHES

All trench excavations exceeding 5 feet in depth will require a trench safety system. Dewatering will likely be required for deeper utilities in the southwest portion of the site.

APPENDIX

Boring logs and laboratory test results (not reproduced in text).

TABLE OF CONTENTS

1.0 INTRODUCTION

This report presents the results of our subsurface exploration.

FICTIONAL DEMONSTRATION DOCUMENT. All names, sites, values and criteria are invented. Not for construction or professional use.

2.0 FIELD EXPLORATION

Twenty-two borings were drilled to depths of 15 to 25 feet.

3.0 SITE GEOLOGY

The site is underlain by clay soils typical of the coastal plain.

5.0 FOUNDATION DISCUSSION

General considerations for slab-on-grade construction are presented below.