

B505/I500: Applied Algorithms

HW2 (Due: **Feb. 12 Monday Noon**)

<http://darwin.informatics.indiana.edu/col/courses/B505-18>

1. (10 pts) Illustrate the operation of `Heap_extract_max` on the heap $A = \langle 15, 13, 9, 5, 12, 8, 7, 4, 0, 6, 2, 1 \rangle$;
2. (15 pts) You are given an array of n elements, and you notice that some of these elements are duplicates; that is they appear more than one time in the array. Devise an algorithm to remove all duplicates from the array in time $O(n \log n)$.
3. (15 pts) A sequence of n operations is performed on a data structure. The i th operation costs i if i is an exact power of 2, and 1 otherwise. Use aggregate analysis to determine the amortized cost per operation.
4. (15 pts) A sequence of stack operations is performed on a stack whose size never exceeds k . After every k operations, a copy of the entire stack is made for backup purposes. Show that the cost of n stack operations, including copying the stack, is $O(n)$ by assigning suitable amortized costs to the various stack operations.
5. (15 pts) Suppose we wish not only to increment a counter but also to reset it to zero (i.e., make all bits in it 0). Show how to implement a counter as an array of bits so that any sequence of increment or reset operations takes time $O(n)$ on an initially zero counter.
6. (15 pts) What is the total cost of executing n of the stack operations `PUSH`, `POP`, and `MULTIPOP`, assuming that the stack begins with s_0 objects and finishes with s_n objects?
7. (15 pts) Illustrate the insertion of the keys 5, 28, 19, 15, 20, 33, 12, 17, 10 into a hash table with collisions resolved by chaining. Let the table has 9 slots, and let the hash function be $h(k) = k \bmod 9$.