
Tentamensdatum: 2021-08-27, 09:00 - 13:00

Tillåtna hjälpmedel: Inga

Totalt antal uppgifter: 7st, 100p

Jourhavande lärare: 0920 / 49 20 44

1. Insert numbers 36, 24, 14, 26, and 16 *in that order* (that is, first insert 36, then insert 24, ...) into each of the following data structures (initially empty):

(a) a min-heap. Show the array that represents the min-heap obtained. **(4p)**

(b) a hash table of size 10 with the hash function $h(x, i) = (x \bmod 10 + i) \bmod 10$, $i = 0, 1, \dots, 9$. Draw the hash table. **(4p)**

(c) a binary search tree. Draw the binary search tree. **(4p)**

2. State the running time of the following algorithms on sorting n elements (in $\Theta(\cdot)$ notation): **(9p)**

	best case	worst case	average case
quicksort			
insertionsort			
mergesort			

3. Given a (weighted) graph G with the adjacency-matrix representation:

	a	b	c	d	e
a	—	5	1	—	—
b	—	—	—	2	—
c	—	3	—	—	—
d	—	—	2	—	—
e	—	—	—	—	1

(a) Draw this graph. **(3p)**

(b) Draw a depth-first search *tree* starting at vertex a . **(3p)**

(c) Draw a breadth-first search *tree* starting at vertex e . **(3p)**

(d) Execute Dijkstra's algorithm on G , starting at source node a . Show the progress of the algorithm by filling the following table. **(5p)**

	a	b	c	d	e
initialization	0	∞	∞	∞	∞
after 1 st iteration					
after 2 nd iteration					
after 3 rd iteration					
after 4 th iteration					

4. Short Answer Questions.

No justification is required. For *True/False* questions, a statement is *True* only if it is true in all cases while it is *False* if it is not true in some case.

(a) $n^2 + 9 \cdot \frac{n^2 \log n}{1000 \log \log n} - 20 + 12 \cdot n = O(n^2)$. True or False? **(3p)**

(b) Suppose that a graph $G = (V, E)$ is represented by its adjacency matrix. Give the running time of a depth-first search (in $\Theta(\cdot)$ notation). **(3p)**

(c) In a hash table of size m with n elements in which collisions are resolved by chaining, an insert operation takes average-case constant time, under the assumption of simple uniform hashing. True or False? **(3p)**

- (d) Give the worst-case asymptotic time complexity (in $\Theta(\cdot)$ notation) of the following algorithm, in terms of the input size n . **(5p)**

```
def f(n):
    if n < 2: return 0
    count ← 0
    if n is even:
        for i = 1 to n: count ← count + 10
    else:
        for i = 1 to n2: count ← count + 1
    return count
```

You may assume that addition and assignment take constant steps.

- (e) Give a recurrence relation for $T(n)$, the worst-case running time of the following algorithm, where n is the input size. **(5p)**

```
def f(n):
    if n ≤ 1: return 10
    count ← 0
    for i = 1 to n log n: count ← 1 + f(n - 1)
    return count
```

You may assume that addition and assignment take constant steps.

- (f) Prim's minimum spanning tree algorithm works even there are negative-weight cycles in the input graph. True or False? **(3p)**
- (g) Given a weighted, directed graph $G = (V, E)$ with no negative-weight cycles. Suppose that the number of edges on any single-source shortest path from the source s is at most k . Then, we can terminate Bellman-Ford after k passes and return the shortest paths. True or False? What is the running time (in $\Theta(\cdot)$ notation)? **(5p)**
- (h) The difference between the heights of a standard binary search tree and a red-black tree is at most $\log n$. True or False? **(3p)**

5. Multiple-Choice Questions.

Each of the following questions has exactly *one* correct answer and is worth 3 points. An incorrect answer will give -1 point. An answer with more than one choices will receive -1 point as well. The complete assignment (1)-(5) will give no less than 0 points.

- (1) The worst-case run time of bucketsort is
- $\Theta(n)$
 - $\Theta(\log n)$
 - $\Theta(n \log n)$
 - $\Theta(n^2)$
- (2) Which data structure is used in depth-first search of a graph to hold nodes?
- tree
 - queue
 - stack
 - heap

- (3) Given a weighted directed acyclic graph $G = (V, E)$ represented by its adjacency lists, we can compute shortest paths from a single source in $\Theta(V + E)$ time by
- doing a breadth-first search on G .
 - running Dijkstra's algorithm on G .
 - running Bellman-Ford's algorithm on G .
 - relaxing the edges of G according to a topological sort of its vertices.
- (4) Let A be an algorithm that solves a given problem of size n in $\Theta(n^3)$ in the worst case. Which of the following statements is true?
- A takes at most n^3 time on every input of size n .
 - A takes at most $c \times n^3$ time on every input of size n , where $c > 0$ is a constant.
 - A takes at least n^3 time on every input of size n .
 - A takes n^3 time on every input of size n .
- (5) Which of the following statements is true about sorting algorithms?
- Heapsort is stable.
 - Countingsort is in-place.
 - Insertionsort is in-place.
 - Bucketsort is stable.

When presenting an algorithm, a clear and complete high-level description will suffice. Code is not required.

6. A binary tree is *perfect* if both the left and right subtrees of any node in the tree are perfect and the sizes of these two subtrees differ by at most 4. Design a worst-case linear-time divide-and-conquer algorithm for checking whether a given binary tree is perfect or not. **(10p)**
7. Given an array $A = \langle a_1, a_2, \dots, a_n \rangle$ of length n that contains k ($0 \leq k \leq n$) *bad* elements and $n - k$ *good* elements in some arbitrary order. The problem is to determine which elements are *bad* using operations *OR*. The *OR* operator can take any number of elements and return *True* if and only if one or more of its operands is *bad*. Design a worst-case $O(k \log \frac{n}{k})$ -time algorithm to solve this problem. Analyze your algorithm. The complexity is measured by the number of *OR* operations used and other common operations. **(10p)**

For example, $A = \left\langle \begin{array}{|c|c|c|c|c|} \hline a_1 & a_2 & a_3 & a_4 & a_5 \\ \hline god & bad & bad & god & bad \\ \hline \end{array} \right\rangle$. Your algorithm should return a_2, a_3 , and a_5 .