INFOCUS IN10

Display

Native Aspect Ratio: 4x3 Supported Aspect Ratio: 4:3, 16:9

Brightness: (Video Optimized Lumens)

High Bright: 1800 Lumens Eco Mode: Not Available

Contrast Ratio: 1100 : 1 Full On/Full Off

Display Technology: DLP™ by Texas Instruments®: 0.7" XGA DMD DDR

Data Compatibility: VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024)

Video Compatibility: Full NTSC, PAL, SECAM, 480p, 576p, 720p, 1080i

Color Wheel (DLP Only): 4-segment, 2-speed

Native Resolution: XGA

Projector Placement: Rear Projection, Front Projection

SMPTE Brightness: Not Available

Lamp Wattage: High Bright: 120 Watts

Eco Mode: Not Available High Bright: 4000 Hours

Lamp Life: Fight Addo Hodis Eco Mode: Not Available

Minimum Image Size: 2.7 ft (0,82 m)

Maximum Image Size: 22.2 ft (6,77 m)

Standard Lens Zoom: 1.25 : 1

Standard Lens Throw Ratio: 1.85 - 2.35:1 (Distance/Width)

Standard Lens Image Offset

Ratio:

110% (+/- 5%)

Standard Lens Projection

Distance:

5 - 32.3 ft (1,52 - 9,85 m)

Digital Keystone Correction

(Vertical):

+/- 15°

Digital Keystone Correction

(Horizontal):

Not Available

Lens Shift: Not Available

Inputs and Outputs

DVI: Number of Inputs: 1

Requires optional M1 to DVI cable

M1: Number of Inputs: 1

Accepts VESA and DVI with M1 cable

HDMI: Not Available BNC: Not Available

Component (RCA): Number of Inputs: 1

Requires M1 to Component adapter.

VESA (HD15): Number of Inputs: 1

Requires M1 to VESA cable

S-Video: Number of Inputs: 1
4-pin mini-DIN

Number of Inputs: 1

Composite (RCA): Video only

Standard Definition TV: Composite RCA, S-Video

Enhanced Definition TV: M1-DA
High Definition TV: M1-DA
Computer: M1-DA

HDCP Support: No Stereo RCA Jacks Inputs: No Stereo 3.5 mm Mini-jack Inputs: Yes

12v trigger for motorized

screens (3.5 mm mini-jack):

No

Projector Control: Projector Keypad, Remote

Speakers: 1-Watt speaker

Monitor Output: Nο

Audio Output: Not Available

Compatibility

Data Compatibility: VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024)

H-Sync Range: 15 - 100kHz V-Sync Range: 43.5 - 130Hz

Video Compatibility: Full NTSC, PAL, SECAM, 480p, 576p, 720p, 1080i

General

Actual Dimensions:

Audible Noise: 32 dB

> Height: 2.5 in (6,35 cm) **Length:** 6.1 in (15,49 cm)

Width: 7.8 in (19,81 cm)

Actual Weight: 2.4 lbs (1,09 kg)

Height: 13 in (33,02 cm)

Length: 14 in (35,56 cm) Shipping Dimensions:

Width: 12 in (30,48 cm)

Shipping Weight: 7 lbs (3,18 kg)

3 Years Door-Step Swap **Projector Warranty:**

Lamp Warranty: 1 year Accessories Warranty: 90 days

Operating temperature:

(at sea level)

41 - 104° F (5 - 40° C)

Maximum Altitude Supported: 10000 ft (3048 m)

Typical Power Consumption: 155 Watts Maximum Power Consumption: Not Available

Power Supply: 100 - 240 Volts at 50 - 60 Hz

English, French, German, Italian, Japanese, Korean, Norwegian, Menu Languages:

Portuguese, Simplified Chinese, Spanish, Traditional Chinese

FCC A (US/Canada), CCC (China), IRAM (Argentina), GOST (Russia), UL Approvals: & cUL (US/Canada), TUV GS (Germany), NOM (Mexico), C-Tick (Australia)

www.lampe-videoprojecteur.info