

## INFOCUS LPX1

### Display

Native Aspect Ratio:	4x3
Supported Aspect Ratio:	16:9, 4:3
Brightness: (max ANSI lumens)	High Bright: 1100 Lumens Eco Mode: Not Available
Contrast Ratio:	2000 : 1 Full On/Full Off
Display Technology:	DLP by Texas Instruments: 0.55" SVGA DDR DMD
Data Compatibility:	SVGA (800x600), XGA (1024x768), VGA (640x480)
Video Compatibility:	1080i, 480i, 576i, 576p, 720p, 480p, Full NTSC, PAL, SECAM
Color Wheel (DLP Only):	4-segment, 2x
Native Resolution:	SVGA
Projector Placement:	Ceiling Projection, Front Projection, Rear Projection
SMPTE Brightness:	
Lamp Wattage:	High Bright: 150 Watts Eco Mode: Not Available
Lamp Life:	High Bright: 4000 Hours Eco Mode: Not Available
Minimum Image Size:	2.7 ft (0,82 m)
Maximum Image Size:	21.6 ft (6,58 m)
Standard Lens Zoom:	1.2:1 : 1
Standard Lens Throw Ratio:	1.89 - 2.27 (Distance/Width)
Standard Lens Image Offset Ratio:	
Standard Lens Projection Distance:	5 - 32.3 ft (1,52 - 9,85 m)
Digital Keystone Correction (Vertical):	20
Digital Keystone Correction (Horizontal):	
Lens Shift:	Not Available

### Inputs and Outputs

DVI:	Not Available
M1:	Not Available
HDMI:	Not Available
BNC:	Not Available
Component (RCA):	Not Available
VESA (HD15):	<b>Number of Inputs: 1</b>
S-Video:	<b>Number of Inputs: 1</b>
Composite (RCA):	<b>Number of Inputs: 1</b>
Standard Definition TV:	S-Video, Composite RCA
Enhanced Definition TV:	VGA
High Definition TV:	VGA
Computer:	VGA
HDCP Support:	No
Stereo RCA Jacks Inputs:	No
Stereo 3.5 mm Mini-jack Inputs:	Yes
12v trigger for motorized screens (3.5 mm mini-jack):	No

Projector Control:	Projector Keypad, Remote
Speakers:	2.5 Watt mono speaker
Monitor Output:	Yes
Audio Output:	Audio Input: 3.5mm mini-jack (Computer and Video)

### Compatibility

Data Compatibility:	SVGA (800x600), XGA (1024x768), VGA (640x480)
H-Sync Range:	31.5 - 80kHz
V-Sync Range:	50 - 85Hz
Video Compatibility:	1080i, 480i, 576i, 576p, 720p, 480p, Full NTSC, PAL, SECAM

### General

Audible Noise:	37 dB
Actual Dimensions:	<b>Height:</b> 15 in (38,1 cm) <b>Length:</b> 19 in (48,26 cm) <b>Width:</b> 15 in (38,1 cm)
Actual Weight:	6.8 lbs (3,08 kg) <b>Height:</b> 15 in (38,1 cm) <b>Length:</b> 19 in (48,26 cm) <b>Width:</b> 15 in (38,1 cm)
Shipping Dimensions:	
Shipping Weight:	14 lbs (6,35 kg)
Projector Warranty:	N/A
Lamp Warranty:	N/A
Accessories Warranty:	N/A
Operating temperature: (at sea level)	41 - 104° F (5 - 40° C)
Maximum Altitude Supported:	10000 ft (3048 m)
Typical Power Consumption:	200 Watts
Maximum Power Consumption:	250 Watts
Power Supply:	100 - 240 Volts at 50 - 60 Hz
Menu Languages:	English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese
Approvals:	UL, c-UL, TUV GS, CE, GOST, C-Tick, NOM, IRAM, FCC B, CISPR22 /EN55022, EN 55024 /

**[www.lampe-videoprojecteur.info](http://www.lampe-videoprojecteur.info)**