

INFOCUS X10

Display

Native Aspect Ratio:	16x9
Supported Aspect Ratio:	16:9, 4:3
Brightness: (Video Optimized Lumens)	High Bright: 1200 Lumens Eco Mode: 960 Lumens
Contrast Ratio:	2500 : 1 Full On/Full Off
Display Technology:	DarkChip1™ 1080p DLP™ by Texas Instruments
Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), 720p (1280x720), 1080p (1920x1080), 480p (854x480), 576p (1024x576)
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1035i, 1080i, 1080p/24, 1080p/30, 1080p/50, 1080p/60
Color Wheel (DLP Only):	7-segment, D65K (6500K) color calibrated
Native Resolution:	1080p
Projector Placement:	Ceiling Projection, Front Projection, Rear Projection
SMPTE Brightness:	Up to 13.5' (4m) diagonal with 1.0 gain screen
Lamp Wattage:	High Bright: 300 Watts Eco Mode: 250 Watts
Lamp Life:	High Bright: 2000 Hours Eco Mode: 2500 Hours
Minimum Image Size:	3.06 ft (0,93 m)
Maximum Image Size:	16.92 ft (5,16 m)
Standard Lens Zoom:	1.2 : 1
Standard Lens Throw Ratio:	1.85-2.22:1 (Distance/Width)
Standard Lens Image Offset Ratio:	136%
Standard Lens Projection Distance:	4.92 - 32.8 ft (1,5 - 10 m)
Digital Keystone Correction (Vertical):	+/- 13°
Digital Keystone Correction (Horizontal):	Not Available
Lens Shift:	Not Available

Inputs and Outputs

DVI:	Number of Inputs: 1 Requires M1 to DVI cable (SP-DVI-D-R)
M1:	Number of Inputs: 1 Accepts VGA, DVI, HDMI, & Component Video through optional M1-DA adapters.
HDMI:	Number of Inputs: 1 HDCP Supported
BNC:	Not Available
Component (RCA):	Number of Inputs: 1
VESA (HD15):	Number of Inputs: 1 Requires M1 to VGA cable (SP-DVI-A-R)
S-Video:	Number of Inputs: 1 4-pin mini-DIN
Composite (RCA):	Number of Inputs: 1
Standard Definition TV:	Composite RCA, S-Video, Component RCA

Enhanced Definition TV:	Component RCA, HDMI, M1-DA
High Definition TV:	Component RCA, M1-DA, HDMI
Computer:	M1-DA
HDCP Support:	Yes
Stereo RCA Jacks Inputs:	No
Stereo 3.5 mm Mini-jack Inputs:	No
12v trigger for motorized screens (3.5 mm mini-jack):	Yes
Projector Control:	RS-232, Remote, Projector Keypad
Speakers:	Not Available
Monitor Output:	No
Audio Output:	Not Available

Compatibility

Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), 720p (1280x720), 1080p (1920x1080), 480p (854x480), 576p (1024x576)
H-Sync Range:	31.5 - 80kHz
V-Sync Range:	50 - 85Hz
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1035i, 1080i, 1080p/24, 1080p/30, 1080p/50, 1080p/60

General

Audible Noise:	30 dB
Actual Dimensions:	Height: 5.83 in (14,81 cm) Length: 17 in (43,18 cm) Width: 18.75 in (47,63 cm)
Actual Weight:	14.1 lbs (6,4 kg) Height: 10.5 in (26,67 cm)
Shipping Dimensions:	Length: 23.4 in (59,44 cm) Width: 21.6 in (54,86 cm)
Shipping Weight:	21.2 lbs (9,62 kg)
Projector Warranty:	2 Years Door-Step Swap
Lamp Warranty:	6 months
Accessories Warranty:	90 days
Operating temperature: (at sea level)	50 - 95° F (10 - 35° C)
Maximum Altitude Supported:	7500 ft (2286 m)
Typical Power Consumption:	350 Watts
Maximum Power Consumption:	375 Watts
Power Supply:	100 - 240 Volts at 50 - 60 Hz
Menu Languages:	English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese
Approvals:	UL, c-UL, TUV GS, GOST, C-Tick, NOM, IRAM, FCC Class B, ICES-003 Class B, CISPR22/EN55022, EN55024/CISPR24, CB certified in accordance with IEC60950-1/EN60950-2, MIC, CE, VCCI, WEEE

www.lampe-videoprojecteur.info