

"Event simulation - Click, Focus, Blur"

IF i have two input in my Page and ordered me (on open Page Focus on input num two without enter on it) i will do this :

```
Let two = document.querySelector  
(".two");
```

```
window.onload = Function () {  
  two.Focus();
```

```
}
```

And if i want to open link exist in Page once input num one is Blur i will do this :

```
one.onblur = Function () {  
  document.links[0].click();
```

```
}
```

*

*

"ClassList Object And Methods"

Let element = document. " " ("my-div"),

```
console.log(element.classList);
```

show ^{All} every class's what the element have and it's type is object.

(.length) → Determine the ~~number~~ length of element's class List.

(.contains) → Research about class Name in the class List if it found it return true else return False.


(.item(index)) → Find the Class Name by it index.

(.add(" ", " ", ...)) → Add New classes to the element.

(.remove(" ", " ", ...)) → Remove the classes from the element.

(.toggle(" ")) → IF class Name what you give is exist in element it will remove it else if it is not exist it will add it as a new class.

"Css styling And styleSheets"

Let element = document. " " ("my-div")
 element.style. (" ") = " " ;  قواعد CSS
فمثلاً: size

if the Property contain more than
 word write the words like this:
 " " . style . backgroundColor = "red";

if i want to concatenate the Property
 i will do this:

" " . style . CssText = "color:red; font-size:
 14px; " ;

if i want to remove Property:

" " . style . removeProperty (" ");

Property's name

it remove Property from inline style

if i want to add new Property:

Syntax: setProperty (PropertyName,
 Value, Priority)

element.style.setProperty الأولوية
 ("font-size", "40px", important
 "important");

if i want to implement to apply
this previous methods on stylesheet
: ~~document~~ document.styleSheets[0].rules

ملف ال style الأول ←
ال Selector text ~~ال~~ ←

{ div
font-size: 14px;

} يجب كده object .

.. styleSheets[0].rules[0].style.
removeProperty("line-height");

أو أي خاصية من الـ
استخدمها قبل كده.

"Before, After, Prepend, Append"
Remove

Deal with Elements.

in HTML

i have div has id (my-div) and
in this div exist span.

in js

Let element = " " ("my-div");

Let create p = document.createElement("p");

~~example~~ if i want to add a new value
before any element:

element.before(" ");

Text or element

after

element.after(" ");

Text or element

~~before~~ (.before()) (.after())

Add new ~~the~~ Value or Element
out the element after or
before it.

RC: 27/9/21

Date:

ROX

رقم:

التاريخ:

if i want to add new value or
element ~~in the end of the element~~ in the
end of the element:
element.append(createdP);

" " " " "

start of " " :
element.prepend(");

if i want to remove any element:
element.remove();

↓ Do not accept
any value

*

*

"DOM Traversing"

الانتقال بين العناصر في ال DOM

if i want to access to ~~the~~ next element to another element:

element.nextElementSibling;

يوصلنا للعنصر الذي يليه لو فني بين العنصر ده واللي بعده أي قيمة أخرى ليست عنصر.

" " " " " next value

element.nextSibling;

يوصلنا للقيمة اللي بعد العنصر ده.

" " " " " Previous element

element.PreviousElementSibling;

يوصلنا للعنصر اللي قبله العنصر الأخر.

" " " " " Previous value

element.PreviousSibling;

يوصلنا للقيمة اللي قبل العنصر الأخر.

if i want to access to the Parent element:

element.ParentElement;

"DOM Cloning"

الاستنساخ في ال DOM
`element.cloneNode( )` ; Deep Argument
 True أو False ← ينسخ العنصر بالAttributes وال
 Elements التي بداخله.
 ← ينسخ العنصر بالAttributes فقط.

* # 100 "Add Event Listener"

إضافة Event على العنصر
`myP.addEventListener("click",
 Function () {
 // block Code .
 })`

مميزات التي يعالجها في الطريقة العادية:

- Use without `on` → استخدام ال Event بدون
- Attach Multiple Events. → `on`
- Error Test → إضافة أكثر من
 Event وتفيدهم
 كلهم
 يظهر Error عند استخدام
 Text بدل ال Function.

* # 101 "DOM challenge"

Code In Codepen.io