MBC Platform — Source Code

Generated: 2026-04-02T16:33:07.026Z

Total files: 128

Table of Contents

artifacts/api-server/build.mjs
artifacts/api-server/package.json
artifacts/api-server/src/app.ts
artifacts/api-server/src/index.ts
artifacts/api-server/src/lib/logger.ts
artifacts/api-server/src/routes/blood-requests.ts
artifacts/api-server/src/routes/dashboard.ts
artifacts/api-server/src/routes/donors.ts
artifacts/api-server/src/routes/health.ts
artifacts/api-server/src/routes/hospitals.ts
artifacts/api-server/src/routes/index.ts
artifacts/api-server/tsconfig.json
artifacts/mbc-platform/components.json
artifacts/mbc-platform/package.json
artifacts/mbc-platform/src/App.tsx
artifacts/mbc-platform/src/components/layout/Footer.tsx
artifacts/mbc-platform/src/components/layout/Layout.tsx
artifacts/mbc-platform/src/components/layout/Navbar.tsx
artifacts/mbc-platform/src/components/ui/accordion.tsx
artifacts/mbc-platform/src/components/ui/alert-dialog.tsx
artifacts/mbc-platform/src/components/ui/alert.tsx
artifacts/mbc-platform/src/components/ui/aspect-ratio.tsx
artifacts/mbc-platform/src/components/ui/avatar.tsx
artifacts/mbc-platform/src/components/ui/badge.tsx
artifacts/mbc-platform/src/components/ui/breadcrumb.tsx
artifacts/mbc-platform/src/components/ui/button-group.tsx
artifacts/mbc-platform/src/components/ui/button.tsx
artifacts/mbc-platform/src/components/ui/calendar.tsx
artifacts/mbc-platform/src/components/ui/card.tsx
artifacts/mbc-platform/src/components/ui/carousel.tsx
artifacts/mbc-platform/src/components/ui/chart.tsx
artifacts/mbc-platform/src/components/ui/checkbox.tsx
artifacts/mbc-platform/src/components/ui/collapsible.tsx
artifacts/mbc-platform/src/components/ui/command.tsx
artifacts/mbc-platform/src/components/ui/context-menu.tsx
artifacts/mbc-platform/src/components/ui/dialog.tsx
artifacts/mbc-platform/src/components/ui/drawer.tsx
artifacts/mbc-platform/src/components/ui/dropdown-menu.tsx
artifacts/mbc-platform/src/components/ui/empty.tsx
artifacts/mbc-platform/src/components/ui/field.tsx
artifacts/mbc-platform/src/components/ui/form.tsx
artifacts/mbc-platform/src/components/ui/hover-card.tsx
artifacts/mbc-platform/src/components/ui/input-group.tsx
artifacts/mbc-platform/src/components/ui/input-otp.tsx
artifacts/mbc-platform/src/components/ui/input.tsx
artifacts/mbc-platform/src/components/ui/item.tsx
artifacts/mbc-platform/src/components/ui/kbd.tsx
artifacts/mbc-platform/src/components/ui/label.tsx
artifacts/mbc-platform/src/components/ui/menubar.tsx
artifacts/mbc-platform/src/components/ui/navigation-menu.tsx
artifacts/mbc-platform/src/components/ui/pagination.tsx
artifacts/mbc-platform/src/components/ui/popover.tsx
artifacts/mbc-platform/src/components/ui/progress.tsx
artifacts/mbc-platform/src/components/ui/radio-group.tsx
artifacts/mbc-platform/src/components/ui/resizable.tsx
artifacts/mbc-platform/src/components/ui/scroll-area.tsx
artifacts/mbc-platform/src/components/ui/select.tsx
artifacts/mbc-platform/src/components/ui/separator.tsx
artifacts/mbc-platform/src/components/ui/sheet.tsx
artifacts/mbc-platform/src/components/ui/sidebar.tsx
artifacts/mbc-platform/src/components/ui/skeleton.tsx
artifacts/mbc-platform/src/components/ui/slider.tsx
artifacts/mbc-platform/src/components/ui/sonner.tsx
artifacts/mbc-platform/src/components/ui/spinner.tsx
artifacts/mbc-platform/src/components/ui/switch.tsx
artifacts/mbc-platform/src/components/ui/table.tsx
artifacts/mbc-platform/src/components/ui/tabs.tsx
artifacts/mbc-platform/src/components/ui/textarea.tsx
artifacts/mbc-platform/src/components/ui/toast.tsx
artifacts/mbc-platform/src/components/ui/toaster.tsx
artifacts/mbc-platform/src/components/ui/toggle-group.tsx
artifacts/mbc-platform/src/components/ui/toggle.tsx
artifacts/mbc-platform/src/components/ui/tooltip.tsx
artifacts/mbc-platform/src/hooks/use-mobile.tsx
artifacts/mbc-platform/src/hooks/use-toast.ts
artifacts/mbc-platform/src/lib/utils.ts
artifacts/mbc-platform/src/main.tsx
artifacts/mbc-platform/src/pages/about.tsx
artifacts/mbc-platform/src/pages/contact.tsx
artifacts/mbc-platform/src/pages/education.tsx
artifacts/mbc-platform/src/pages/emergency.tsx
artifacts/mbc-platform/src/pages/home.tsx
artifacts/mbc-platform/src/pages/locator.tsx
artifacts/mbc-platform/src/pages/not-found.tsx
artifacts/mbc-platform/src/pages/register-donor.tsx
artifacts/mbc-platform/src/pages/request-blood.tsx

```
lib/api-client-react/package.json
lib/api-client-react/src/custom-fetch.ts
lib/api-client-react/src/generated/api.schemas.ts
lib/api-client-react/src/generated/api.ts
lib/api-client-react/src/index.ts
lib/api-client-react/tsconfig.json
lib/api-spec/orval.config.ts
lib/api-spec/package.json
lib/api-zod/package.json
lib/api-zod/src/generated/api.ts
lib/api-zod/src/generated/types/bloodRequest.ts
lib/api-zod/src/generated/types/createBloodRequestBody.ts
lib/api-zod/src/generated/types/createDonorBody.ts
lib/api-zod/src/generated/types/dashboardStats.ts
lib/api-zod/src/generated/types/dashboardStatsBloodTypeBreakdownItem.ts
lib/api-zod/src/generated/types/donor.ts
lib/api-zod/src/generated/types/emergencyRequest.ts
lib/api-zod/src/generated/types/getEmergencyFeed200.ts
lib/api-zod/src/generated/types/getEmergencyFeedParams.ts
lib/api-zod/src/generated/types/healthStatus.ts
lib/api-zod/src/generated/types/hospital.ts
lib/api-zod/src/generated/types/index.ts
lib/api-zod/src/generated/types/listBloodRequests200.ts
lib/api-zod/src/generated/types/listBloodRequestsParams.ts
lib/api-zod/src/generated/types/listDonors200.ts
lib/api-zod/src/generated/types/listDonorsParams.ts
lib/api-zod/src/generated/types/listHospitals200.ts
lib/api-zod/src/generated/types/listHospitalsParams.ts
lib/api-zod/src/index.ts
lib/api-zod/tsconfig.json
lib/db/drizzle.config.ts
lib/db/package.json
lib/db/src/index.ts
lib/db/src/schema/blood_requests.ts
lib/db/src/schema/donors.ts
lib/db/src/schema/hospitals.ts
lib/db/src/schema/index.ts
lib/db/tsconfig.json
package.json
scripts/src/hello.ts
tsconfig.base.json
tsconfig.json
```

File: artifacts/api-server/build.mjs

```
   1 | import { createRequire } from "node:module";
   2 | import path from "node:path";
   3 | import { fileURLToPath } from "node:url";
   4 | import { build as esbuild } from "esbuild";
   5 | import esbuildPluginPino from "esbuild-plugin-pino";
   6 | import { rm } from "node:fs/promises";
   7 |
   8 | // Plugins (e.g. 'esbuild-plugin-pino') may use `require` to resolve dependencies
   9 | globalThis.require = createRequire(import.meta.url);
  10 |
  11 | const artifactDir = path.dirname(fileURLToPath(import.meta.url));
  12 |
  13 | async function buildAll() {
  14 |   const distDir = path.resolve(artifactDir, "dist");
  15 |   await rm(distDir, { recursive: true, force: true });
  16 |
  17 |   await esbuild({
  18 |     entryPoints: [path.resolve(artifactDir, "src/index.ts")],
  19 |     platform: "node",
  20 |     bundle: true,
  21 |     format: "esm",
  22 |     outdir: distDir,
  23 |     outExtension: { ".js": ".mjs" },
  24 |     logLevel: "info",
  25 |     // Some packages may not be bundleable, so we externalize them, we can add more here as needed.
  26 |     // Some of the packages below may not be imported or installed, but we're adding them in case they are in the
future.
  27 |     // Examples of unbundleable packages:
  28 |     // - uses native modules and loads them dynamically (e.g. sharp)
  29 |     // - use path traversal to read files (e.g. @google-cloud/secret-manager loads sibling .proto files)
  30 |     external: [
  31 |       "*.node",
  32 |       "sharp",
  33 |       "better-sqlite3",
  34 |       "sqlite3",
  35 |       "canvas",
  36 |       "bcrypt",
  37 |       "argon2",
  38 |       "fsevents",
  39 |       "re2",
  40 |       "farmhash",
  41 |       "xxhash-addon",
  42 |       "bufferutil",
  43 |       "utf-8-validate",
  44 |       "ssh2",
  45 |       "cpu-features",
  46 |       "dtrace-provider",
  47 |       "isolated-vm",
  48 |       "lightningcss",
  49 |       "pg-native",
  50 |       "oracledb",
  51 |       "mongodb-client-encryption",
  52 |       "nodemailer",
  53 |       "handlebars",
  54 |       "knex",
  55 |       "typeorm",
  56 |       "protobufjs",
  57 |       "onnxruntime-node",
  58 |       "@tensorflow/*",
  59 |       "@prisma/client",
  60 |       "@mikro-orm/*",
  61 |       "@grpc/*",
  62 |       "@swc/*",
  63 |       "@aws-sdk/*",
  64 |       "@azure/*",
  65 |       "@opentelemetry/*",
  66 |       "@google-cloud/*",
  67 |       "@google/*",
  68 |       "googleapis",
  69 |       "firebase-admin",
  70 |       "@parcel/watcher",
  71 |       "@sentry/profiling-node",
  72 |       "@tree-sitter/*",
  73 |       "aws-sdk",
  74 |       "classic-level",
  75 |       "dd-trace",
  76 |       "ffi-napi",
  77 |       "grpc",
  78 |       "hiredis",
  79 |       "kerberos",
  80 |       "leveldown",
  81 |       "miniflare",
  82 |       "mysql2",
  83 |       "newrelic",
  84 |       "odbc",
  85 |       "piscina",
  86 |       "realm",
  87 |       "ref-napi",
  88 |       "rocksdb",
  89 |       "sass-embedded",
  90 |       "sequelize",
  91 |       "serialport",
  92 |       "snappy",
  93 |       "tinypool",
  94 |       "usb",
  95 |       "workerd",
  96 |       "wrangler",
  97 |       "zeromq",
  98 |       "zeromq-prebuilt",
  99 |       "playwright",
```

```
100 |       "puppeteer",
101 |       "puppeteer-core",
102 |       "electron",
103 |     ],
104 |     sourcemap: "linked",
105 |     plugins: [
106 |       // pino relies on workers to handle logging, instead of externalizing it we use a plugin to handle it
107 |       esbuildPluginPino({ transports: ["pino-pretty"] })
108 |     ],
109 |     // Make sure packages that are cjs only (e.g. express) but are bundled continue to work in our esm output file
110 |     banner: {
111 |       js: `import { createRequire as __bannerCrReq } from 'node:module';
112 | import __bannerPath from 'node:path';
113 | import __bannerUrl from 'node:url';
114 |
115 | globalThis.require = __bannerCrReq(import.meta.url);
116 | globalThis.__filename = __bannerUrl.fileURLToPath(import.meta.url);
117 | globalThis.__dirname = __bannerPath.dirname(globalThis.__filename);
118 |     `,
119 |     },
120 |   });
121 | }
122 |
123 | buildAll().catch((err) => {
124 |   console.error(err);
125 |   process.exit(1);
126 | });
127 |
```

— end of file —

File: artifacts/api-server/package.json

```
 1 | {
 2 |   "name": "@workspace/api-server",
 3 |   "version": "0.0.0",
 4 |   "private": true,
 5 |   "type": "module",
 6 |   "scripts": {
 7 |     "dev": "export NODE_ENV=development && pnpm run build && pnpm run start",
 8 |     "build": "node ./build.mjs",
 9 |     "start": "node --enable-source-maps ./dist/index.mjs",
10 |     "typecheck": "tsc -p tsconfig.json --noEmit"
11 |   },
12 |   "dependencies": {
13 |     "@workspace/api-zod": "workspace:*",
14 |     "@workspace/db": "workspace:*",
15 |     "cookie-parser": "^1.4.7",
16 |     "cors": "^2",
17 |     "drizzle-orm": "catalog:",
18 |     "express": "^5",
19 |     "pino": "^9",
20 |     "pino-http": "^10"
21 |   },
22 |   "devDependencies": {
23 |     "@types/cookie-parser": "^1.4.10",
24 |     "@types/cors": "^2.8.19",
25 |     "@types/express": "^5.0.6",
26 |     "@types/node": "catalog:",
27 |     "esbuild": "^0.27.3",
28 |     "esbuild-plugin-pino": "^2.3.3",
29 |     "pino-pretty": "^13",
30 |     "thread-stream": "3.1.0"
31 |   }
32 | }
33 |
```

— end of file —

File: artifacts/api-server/src/app.ts

```
 1 | import express, { type Express } from "express";
 2 | import cors from "cors";
 3 | import pinoHttp from "pino-http";
 4 | import router from "./routes";
 5 | import { logger } from "./lib/logger";
 6 |
 7 | const app: Express = express();
 8 |
 9 | app.use(
10 |   pinoHttp({
11 |     logger,
12 |     serializers: {
13 |       req(req) {
14 |         return {
15 |           id: req.id,
16 |           method: req.method,
17 |           url: req.url?.split("?")[0],
18 |         };
19 |       },
20 |       res(res) {
21 |         return {
22 |           statusCode: res.statusCode,
23 |         };
24 |       },
25 |     },
26 |   }),
27 | );
28 | app.use(cors());
29 | app.use(express.json());
30 | app.use(express.urlencoded({ extended: true }));
31 |
32 | app.use("/api", router);
33 |
34 | export default app;
35 |
```

— end of file —

File: artifacts/api-server/src/index.ts

```
import app from "./app";
import { logger } from "./lib/logger";

const rawPort = process.env["PORT"];

if (!rawPort) {
  throw new Error(
    "PORT environment variable is required but was not provided.",
  );
}

const port = Number(rawPort);

if (Number.isNaN(port) || port <= 0) {
  throw new Error(`Invalid PORT value: "${rawPort}"`);
}

app.listen(port, (err) => {
  if (err) {
    logger.error({ err }, "Error listening on port");
    process.exit(1);
  }

  logger.info({ port }, "Server listening");
});

```

— end of file —

File: artifacts/api-server/src/lib/logger.ts

```
  1 | import pino from "pino";
  2 |
  3 | const isProduction = process.env.NODE_ENV === "production";
  4 |
  5 | export const logger = pino({
  6 |   level: process.env.LOG_LEVEL ?? "info",
  7 |   redact: [
  8 |     "req.headers.authorization",
  9 |     "req.headers.cookie",
 10 |     "res.headers['set-cookie']",
 11 |   ],
 12 |   ...(isProduction
 13 |     ? {}
 14 |     : {
 15 |         transport: {
 16 |           target: "pino-pretty",
 17 |           options: { colorize: true },
 18 |         },
 19 |       }),
 20 | });
 21 |
```

— end of file —

File: artifacts/api-server/src/routes/blood-requests.ts

```
 1 | import { Router, type IRouter } from "express";
 2 | import { db } from "@workspace/db";
 3 | import { bloodRequestsTable } from "@workspace/db/schema";
 4 | import {
 5 |   ListBloodRequestsQueryParams,
 6 |   CreateBloodRequestBody,
 7 | } from "@workspace/api-zod";
 8 | import { eq, and, sql } from "drizzle-orm";
 9 |
10 | const router: IRouter = Router();
11 |
12 | router.get("/blood-requests", async (req, res) => {
13 |   const query = ListBloodRequestsQueryParams.parse(req.query);
14 |   const conditions = [];
15 |
16 |   if (query.urgency) {
17 |     conditions.push(eq(bloodRequestsTable.urgency, query.urgency));
18 |   }
19 |   if (query.bloodType) {
20 |     conditions.push(eq(bloodRequestsTable.bloodType, query.bloodType));
21 |   }
22 |   if (query.status) {
23 |     conditions.push(eq(bloodRequestsTable.status, query.status));
24 |   }
25 |   if (query.city) {
26 |     conditions.push(eq(bloodRequestsTable.city, query.city));
27 |   }
28 |
29 |   const requests = await db
30 |     .select()
31 |     .from(bloodRequestsTable)
32 |     .where(conditions.length > 0 ? and(...conditions) : undefined)
33 |     .orderBy(bloodRequestsTable.createdAt);
34 |
35 |   const [{ count }] = await db
36 |     .select({ count: sql<number>`count(*)::int` })
37 |     .from(bloodRequestsTable)
38 |     .where(conditions.length > 0 ? and(...conditions) : undefined);
39 |
40 |   res.json({ requests, total: count });
41 | });
42 |
43 | router.post("/blood-requests", async (req, res) => {
44 |   const body = CreateBloodRequestBody.parse(req.body);
45 |
46 |   const [request] = await db
47 |     .insert(bloodRequestsTable)
48 |     .values({ ...body })
49 |     .returning();
50 |
51 |   res.status(201).json(request);
52 | });
53 |
54 | export default router;
55 |
```

— end of file —

File: artifacts/api-server/src/routes/dashboard.ts

```
1 | import { Router, type IRouter } from "express";
2 | import { db } from "@workspace/db";
3 | import { donorsTable, bloodRequestsTable, hospitalsTable } from "@workspace/db/schema";
4 | import { GetEmergencyFeedQueryParams } from "@workspace/api-zod";
5 | import { eq, and, sql, desc, gte } from "drizzle-orm";
6 |
7 | const router: IRouter = Router();
8 |
9 | router.get("/dashboard/stats", async (_req, res) => {
10 |   const [donorsCount] = await db
11 |     .select({ count: sql<number>`count(*)::int` })
12 |     .from(donorsTable);
13 |
14 |   const [{ totalDonations }] = await db
15 |     .select({ totalDonations: sql<number>`coalesce(sum(total_donations), 0)::int` })
16 |     .from(donorsTable);
17 |
18 |   const [activeRequests] = await db
19 |     .select({ count: sql<number>`count(*)::int` })
20 |     .from(bloodRequestsTable)
21 |     .where(eq(bloodRequestsTable.status, "active"));
22 |
23 |   const [hospitalsCount] = await db
24 |     .select({ count: sql<number>`count(*)::int` })
25 |     .from(hospitalsTable);
26 |
27 |   const oneMonthAgo = new Date();
28 |   oneMonthAgo.setMonth(oneMonthAgo.getMonth() - 1);
29 |
30 |   const [donationsThisMonth] = await db
31 |     .select({ count: sql<number>`count(*)::int` })
32 |     .from(donorsTable)
33 |     .where(gte(donorsTable.createdAt, oneMonthAgo));
34 |
35 |   const bloodTypeBreakdown = await db
36 |     .select({
37 |       bloodType: donorsTable.bloodType,
38 |       count: sql<number>`count(*)::int`,
39 |     })
40 |     .from(donorsTable)
41 |     .groupBy(donorsTable.bloodType);
42 |
43 |   res.json({
44 |     totalDonors: donorsCount.count,
45 |     totalDonations: totalDonations,
46 |     activeRequests: activeRequests.count,
47 |     partnerHospitals: hospitalsCount.count,
48 |     livesSaved: Math.floor(totalDonations * 3),
49 |     donationsThisMonth: donationsThisMonth.count,
50 |     bloodTypeBreakdown,
51 |   });
52 | });
53 |
54 | router.get("/dashboard/emergency-feed", async (req, res) => {
55 |   const query = GetEmergencyFeedQueryParams.parse(req.query);
56 |   const conditions = [eq(bloodRequestsTable.status, "active")];
57 |
58 |   if (query.city) {
59 |     conditions.push(eq(bloodRequestsTable.city, query.city));
60 |   }
61 |
62 |   const limit = query.limit ?? 10;
63 |
64 |   const requests = await db
65 |     .select()
66 |     .from(bloodRequestsTable)
67 |     .where(and(...conditions))
68 |     .orderBy(desc(bloodRequestsTable.createdAt))
69 |     .limit(limit);
70 |
71 |   const now = new Date();
72 |   const emergencies = requests.map((r) => ({
73 |     id: r.id,
74 |     patientName: r.patientName,
75 |     bloodType: r.bloodType,
76 |     unitsNeeded: r.unitsNeeded,
77 |     hospitalName: r.hospitalName,
78 |     city: r.city,
79 |     urgency: r.urgency,
80 |     contactPhone: r.contactPhone,
81 |     minutesAgo: Math.floor((now.getTime() - new Date(r.createdAt).getTime()) / 60000),
82 |     status: r.status,
83 |   }));
84 |
85 |   res.json({ emergencies });
86 | });
87 |
88 | export default router;
89 |
```

— end of file —

File: artifacts/api-server/src/routes/donors.ts

```
 1 | import { Router, type IRouter } from "express";
 2 | import { db } from "@workspace/db";
 3 | import { donorsTable } from "@workspace/db/schema";
 4 | import {
 5 |   ListDonorsQueryParams,
 6 |   RegisterDonorBody,
 7 | } from "@workspace/api-zod";
 8 | import { eq, and, sql } from "drizzle-orm";
 9 |
10 | const router: IRouter = Router();
11 |
12 | router.get("/donors", async (req, res) => {
13 |   const query = ListDonorsQueryParams.parse(req.query);
14 |   const conditions = [];
15 |
16 |   if (query.bloodType) {
17 |     conditions.push(eq(donorsTable.bloodType, query.bloodType));
18 |   }
19 |   if (query.city) {
20 |     conditions.push(eq(donorsTable.city, query.city));
21 |   }
22 |
23 |   const limit = query.limit ?? 20;
24 |   const offset = query.offset ?? 0;
25 |
26 |   const donors = await db
27 |     .select()
28 |     .from(donorsTable)
29 |     .where(conditions.length > 0 ? and(...conditions) : undefined)
30 |     .limit(limit)
31 |     .offset(offset);
32 |
33 |   const [{ count }] = await db
34 |     .select({ count: sql<number>`count(*)::int` })
35 |     .from(donorsTable)
36 |     .where(conditions.length > 0 ? and(...conditions) : undefined);
37 |
38 |   res.json({ donors, total: count });
39 | });
40 |
41 | router.post("/donors", async (req, res) => {
42 |   const body = RegisterDonorBody.parse(req.body);
43 |
44 |   const isEligible = !body.hasChronicDisease && body.weight >= 50;
45 |
46 |   const [donor] = await db
47 |     .insert(donorsTable)
48 |     .values({
49 |       ...body,
50 |       isEligible,
51 |     })
52 |     .returning();
53 |
54 |   res.status(201).json(donor);
55 | });
56 |
57 | export default router;
58 |
```

— end of file —

File: artifacts/api-server/src/routes/health.ts

```
 1 | import { Router, type IRouter } from "express";
 2 | import { HealthCheckResponse } from "@workspace/api-zod";
 3 |
 4 | const router: IRouter = Router();
 5 |
 6 | router.get("/healthz", (_req, res) => {
 7 |   const data = HealthCheckResponse.parse({ status: "ok" });
 8 |   res.json(data);
 9 | });
10 |
11 | export default router;
12 |
```

— end of file —

File: artifacts/api-server/src/routes/hospitals.ts

```
 1 | import { Router, type IRouter } from "express";
 2 | import { db } from "@workspace/db";
 3 | import { hospitalsTable } from "@workspace/db/schema";
 4 | import { ListHospitalsQueryParams } from "@workspace/api-zod";
 5 | import { eq, and, sql } from "drizzle-orm";
 6 |
 7 | const router: IRouter = Router();
 8 |
 9 | router.get("/hospitals", async (req, res) => {
10 |   const query = ListHospitalsQueryParams.parse(req.query);
11 |   const conditions = [];
12 |
13 |   if (query.city) {
14 |     conditions.push(eq(hospitalsTable.city, query.city));
15 |   }
16 |
17 |   const hospitals = await db
18 |     .select()
19 |     .from(hospitalsTable)
20 |     .where(conditions.length > 0 ? and(...conditions) : undefined);
21 |
22 |   const [{ count }] = await db
23 |     .select({ count: sql<number>`count(*)::int` })
24 |     .from(hospitalsTable)
25 |     .where(conditions.length > 0 ? and(...conditions) : undefined);
26 |
27 |   res.json({ hospitals, total: count });
28 | });
29 |
30 | export default router;
31 |
```

— end of file —

File: artifacts/api-server/src/routes/index.ts

```
import { Router, type IRouter } from "express";
import healthRouter from "./health";
import donorsRouter from "./donors";
import bloodRequestsRouter from "./blood-requests";
import hospitalsRouter from "./hospitals";
import dashboardRouter from "./dashboard";

const router: IRouter = Router();

router.use(healthRouter);
router.use(donorsRouter);
router.use(bloodRequestsRouter);
router.use(hospitalsRouter);
router.use(dashboardRouter);

export default router;

```

— end of file —

File: artifacts/api-server/tsconfig.json

```
1 | {
2 |   "extends": "../../tsconfig.base.json",
3 |   "compilerOptions": {
4 |     "outDir": "dist",
5 |     "rootDir": "src",
6 |     "types": ["node"]
7 |   },
8 |   "include": ["src"],
9 |   "references": [
10 |     {
11 |       "path": "../../lib/db"
12 |     },
13 |     {
14 |       "path": "../../lib/api-zod"
15 |     }
16 |   ]
17 | }
18 |
```

— end of file —

File: artifacts/mbc-platform/components.json

```
1 | {
2 |     "$schema": "https://ui.shadcn.com/schema.json",
3 |     "style": "new-york",
4 |     "rsc": false,
5 |     "tsx": true,
6 |     "tailwind": {
7 |       "config": "",
8 |       "css": "src/index.css",
9 |       "baseColor": "neutral",
10 |       "cssVariables": true,
11 |       "prefix": ""
12 |     },
13 |     "aliases": {
14 |       "components": "@/components",
15 |       "utils": "@/lib/utils",
16 |       "ui": "@/components/ui",
17 |       "lib": "@/lib",
18 |       "hooks": "@/hooks"
19 |     }
20 | }
```

— end of file —

File: artifacts/mbc-platform/package.json

```
 1 | {
 2 |   "name": "@workspace/mbc-platform",
 3 |   "version": "0.0.0",
 4 |   "private": true,
 5 |   "type": "module",
 6 |   "scripts": {
 7 |     "dev": "vite --config vite.config.ts --host 0.0.0.0",
 8 |     "build": "vite build --config vite.config.ts",
 9 |     "serve": "vite preview --config vite.config.ts --host 0.0.0.0",
10 |     "typecheck": "tsc -p tsconfig.json --noEmit"
11 |   },
12 |   "devDependencies": {
13 |     "@hookform/resolvers": "^3.10.0",
14 |     "@radix-ui/react-accordion": "^1.2.4",
15 |     "@radix-ui/react-alert-dialog": "^1.1.7",
16 |     "@radix-ui/react-aspect-ratio": "^1.1.3",
17 |     "@radix-ui/react-avatar": "^1.1.4",
18 |     "@radix-ui/react-checkbox": "^1.1.5",
19 |     "@radix-ui/react-collapsible": "^1.1.4",
20 |     "@radix-ui/react-context-menu": "^2.2.7",
21 |     "@radix-ui/react-dialog": "^1.1.7",
22 |     "@radix-ui/react-dropdown-menu": "^2.1.7",
23 |     "@radix-ui/react-hover-card": "^1.1.7",
24 |     "@radix-ui/react-label": "^2.1.3",
25 |     "@radix-ui/react-menubar": "^1.1.7",
26 |     "@radix-ui/react-navigation-menu": "^1.2.6",
27 |     "@radix-ui/react-popover": "^1.1.7",
28 |     "@radix-ui/react-progress": "^1.1.3",
29 |     "@radix-ui/react-radio-group": "^1.2.4",
30 |     "@radix-ui/react-scroll-area": "^1.2.4",
31 |     "@radix-ui/react-select": "^2.1.7",
32 |     "@radix-ui/react-separator": "^1.1.3",
33 |     "@radix-ui/react-slider": "^1.2.4",
34 |     "@radix-ui/react-slot": "^1.2.0",
35 |     "@radix-ui/react-switch": "^1.1.4",
36 |     "@radix-ui/react-tabs": "^1.1.4",
37 |     "@radix-ui/react-toast": "^1.2.7",
38 |     "@radix-ui/react-toggle": "^1.1.3",
39 |     "@radix-ui/react-toggle-group": "^1.1.3",
40 |     "@radix-ui/react-tooltip": "^1.2.0",
41 |     "@replit/vite-plugin-cartographer": "catalog:",
42 |     "@replit/vite-plugin-dev-banner": "catalog:",
43 |     "@replit/vite-plugin-runtime-error-modal": "catalog:",
44 |     "@tailwindcss/typography": "^0.5.15",
45 |     "@tailwindcss/vite": "catalog:",
46 |     "@tanstack/react-query": "catalog:",
47 |     "@types/node": "catalog:",
48 |     "@types/react": "catalog:",
49 |     "@types/react-dom": "catalog:",
50 |     "@vitejs/plugin-react": "catalog:",
51 |     "@workspace/api-client-react": "workspace:*",
52 |     "class-variance-authority": "catalog:",
53 |     "clsx": "catalog:",
54 |     "cmdk": "^1.1.1",
55 |     "date-fns": "^3.6.0",
56 |     "embla-carousel-react": "^8.6.0",
57 |     "framer-motion": "catalog:",
58 |     "input-otp": "^1.4.2",
59 |     "lucide-react": "catalog:",
60 |     "next-themes": "^0.4.6",
61 |     "react": "catalog:",
62 |     "react-day-picker": "^9.11.1",
63 |     "react-dom": "catalog:",
64 |     "react-hook-form": "^7.55.0",
65 |     "react-icons": "^5.4.0",
66 |     "react-resizable-panels": "^2.1.7",
67 |     "recharts": "^2.15.2",
68 |     "sonner": "^2.0.7",
69 |     "tailwind-merge": "catalog:",
70 |     "tailwindcss": "catalog:",
71 |     "tw-animate-css": "^1.4.0",
72 |     "vaul": "^1.1.2",
73 |     "vite": "catalog:",
74 |     "wouter": "^3.3.5",
75 |     "zod": "catalog:"
76 |   }
77 | }
78 |
```

— end of file —

File: artifacts/mbc-platform/src/App.tsx

```
1 | import { Switch, Route, Router as WouterRouter } from "wouter";
2 | import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
3 | import { Toaster } from "@/components/ui/toaster";
4 | import { TooltipProvider } from "@/components/ui/tooltip";
5 | import { Layout } from "@/components/layout/Layout";
6 | import NotFound from "@/pages/not-found";
7 | import Home from "@/pages/home";
8 | import RegisterDonor from "@/pages/register-donor";
9 | import RequestBlood from "@/pages/request-blood";
10 | import Locator from "@/pages/locator";
11 | import Education from "@/pages/education";
12 | import Emergency from "@/pages/emergency";
13 | import About from "@/pages/about";
14 | import Contact from "@/pages/contact";
15 |
16 | const queryClient = new QueryClient({
17 |   defaultOptions: {
18 |     queries: {
19 |       retry: 1,
20 |       refetchOnWindowFocus: false,
21 |     },
22 |   },
23 | });
24 |
25 | function Router() {
26 |   return (
27 |     <Layout>
28 |       <Switch>
29 |         <Route path="/" component={Home} />
30 |         <Route path="/register-donor" component={RegisterDonor} />
31 |         <Route path="/request-blood" component={RequestBlood} />
32 |         <Route path="/locator" component={Locator} />
33 |         <Route path="/education" component={Education} />
34 |         <Route path="/emergency" component={Emergency} />
35 |         <Route path="/about" component={About} />
36 |         <Route path="/contact" component={Contact} />
37 |         <Route component={NotFound} />
38 |       </Switch>
39 |     </Layout>
40 |   );
41 | }
42 |
43 | function App() {
44 |   return (
45 |     <QueryClientProvider client={queryClient}>
46 |       <TooltipProvider>
47 |         <WouterRouter base={import.meta.env.BASE_URL.replace(/\/$/, "")}>
48 |           <Router />
49 |         </WouterRouter>
50 |         <Toaster />
51 |       </TooltipProvider>
52 |     </QueryClientProvider>
53 |   );
54 | }
55 |
56 | export default App;
57 |
```

— end of file —

File: artifacts/mbc-platform/src/components/layout/Footer.tsx

```
   1 | import { Link } from "wouter";
   2 | import { Droplets, Heart, Phone, Mail, MapPin } from "lucide-react";
   3 |
   4 | export function Footer() {
   5 |   return (
   6 |     <footer className="bg-slate-50 border-t border-border pt-16 pb-8">
   7 |       <div className="container mx-auto px-4 md:px-6">
   8 |         <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-10 mb-12">
   9 |           <div>
  10 |             <Link href="/" className="flex items-center gap-2 mb-4">
  11 |               <Droplets className="w-6 h-6 text-primary" />
  12 |               <span className="font-bold text-xl tracking-tight text-foreground">
  13 |                 MBC
  14 |               </span>
  15 |             </Link>
  16 |             <p className="text-muted-foreground text-sm leading-relaxed mb-6">
  17 |               Main Blood Center connects donors with patients in real-time. Every drop counts in our mission to
save lives.
  18 |             </p>
  19 |             <div className="flex items-center gap-3">
  20 |               <div className="w-10 h-10 rounded-full bg-primary/10 flex items-center justify-center text-primary">
  21 |                 <Heart className="w-5 h-5" />
  22 |               </div>
  23 |               <div>
  24 |                 <p className="text-xs text-muted-foreground font-medium">Emergency Hotline</p>
  25 |                 <p className="font-bold text-foreground">1-800-MBC-BLOOD</p>
  26 |               </div>
  27 |             </div>
  28 |           </div>
  29 |
  30 |           <div>
  31 |             <h3 className="font-semibold text-foreground mb-4">Quick Links</h3>
  32 |             <ul className="space-y-3">
  33 |               <li>
  34 |                 <Link href="/register-donor" className="text-sm text-muted-foreground hover:text-primary
transition-colors">
  35 |                   Register as Donor
  36 |                 </Link>
  37 |               </li>
  38 |               <li>
  39 |                 <Link href="/request-blood" className="text-sm text-muted-foreground hover:text-primary transition-
colors">
  40 |                   Request Blood
  41 |                 </Link>
  42 |               </li>
  43 |               <li>
  44 |                 <Link href="/locator" className="text-sm text-muted-foreground hover:text-primary transition-
colors">
  45 |                   Find a Center
  46 |                 </Link>
  47 |               </li>
  48 |               <li>
  49 |                 <Link href="/emergency" className="text-sm text-muted-foreground hover:text-primary transition-
colors">
  50 |                   Live Emergency Feed
  51 |                 </Link>
  52 |               </li>
  53 |             </ul>
  54 |           </div>
  55 |
  56 |           <div>
  57 |             <h3 className="font-semibold text-foreground mb-4">Information</h3>
  58 |             <ul className="space-y-3">
  59 |               <li>
  60 |                 <Link href="/education" className="text-sm text-muted-foreground hover:text-primary transition-
colors">
  61 |                   Education & FAQ
  62 |                 </Link>
  63 |               </li>
  64 |               <li>
  65 |                 <Link href="/about" className="text-sm text-muted-foreground hover:text-primary transition-colors">
  66 |                   About MBC
  67 |                 </Link>
  68 |               </li>
  69 |               <li>
  70 |                 <Link href="/contact" className="text-sm text-muted-foreground hover:text-primary transition-
colors">
  71 |                   Contact Us
  72 |                 </Link>
  73 |               </li>
  74 |             </ul>
  75 |           </div>
  76 |
  77 |           <div>
  78 |             <h3 className="font-semibold text-foreground mb-4">Contact</h3>
  79 |             <ul className="space-y-4">
  80 |               <li class="flex items-start gap-3 text-sm text-muted-foreground">
  81 |                 <MapPin className="w-4 h-4 mt-0.5 text-primary shrink-0" />
  82 |                 <span>123 Medical Center Blvd<br />Metropolis, NY 10001</span>
  83 |               </li>
  84 |               <li class="flex items-center gap-3 text-sm text-muted-foreground">
  85 |                 <Phone class="w-4 h-4 text-primary shrink-0" />
  86 |                 <span>+1 (555) 123-4567</span>
  87 |               </li>
  88 |               <li class="flex items-center gap-3 text-sm text-muted-foreground">
  89 |                 <Mail class="w-4 h-4 text-primary shrink-0" />
  90 |                 <span>support@mbc-network.org</span>
  91 |               </li>
  92 |             </ul>
  93 |           </div>
```

```
  94 |         </div>
  95 |
  96 |         <div className="border-t border-border pt-8 flex flex-col md:flex-row items-center justify-between gap-4">
  97 |           <p className="text-xs text-muted-foreground">
  98 |             &copy; {new Date().getFullYear()} Main Blood Center. All rights reserved.
  99 |           </p>
 100 |           <div className="flex items-center gap-4">
 101 |             <span className="text-xs text-muted-foreground hover:text-foreground cursor-pointer transition-
colors">Privacy Policy</span>
 102 |             <span className="text-xs text-muted-foreground hover:text-foreground cursor-pointer transition-
colors">Terms of Service</span>
 103 |           </div>
 104 |         </div>
 105 |       </div>
 106 |     </footer>
 107 |   );
 108 | }
 109 |
```

— end of file —

File: artifacts/mbc-platform/src/components/layout/Layout.tsx

```
import { Navbar } from "./Navbar";
import { Footer } from "./Footer";
import { ReactNode } from "react";

export function Layout({ children }: { children: ReactNode }) {
  return (
    <div className="min-h-[100dvh] flex flex-col bg-background text-foreground">
      <Navbar />
      <main className="flex-1 pt-[72px]">
        {children}
      </main>
      <Footer />
    </div>
  );
}

```

— end of file —

File: artifacts/mbc-platform/src/components/layout/Navbar.tsx

```
   1 | import { Link, useLocation } from "wouter";
   2 | import { Button } from "@/components/ui/button";
   3 | import { Activity, Heart, Droplets, Menu, X, AlertCircle } from "lucide-react";
   4 | import { useState, useEffect } from "react";
   5 | import { motion, AnimatePresence } from "framer-motion";
   6 |
   7 | export function Navbar() {
   8 |   const [location] = useLocation();
   9 |   const [isScrolled, setIsScrolled] = useState(false);
  10 |   const [mobileMenuOpen, setMobileMenuOpen] = useState(false);
  11 |
  12 |   useEffect(() => {
  13 |     const handleScroll = () => {
  14 |       setIsScrolled(window.scrollY > 10);
  15 |     };
  16 |     window.addEventListener("scroll", handleScroll);
  17 |     return () => window.removeEventListener("scroll", handleScroll);
  18 |   }, []);
  19 |
  20 |   const navLinks = [
  21 |     { href: "/locator", label: "Find Center" },
  22 |     { href: "/education", label: "Learn" },
  23 |     { href: "/emergency", label: "Live Feed", icon: <Activity className="w-4 h-4 mr-1 text-primary animate-pulse" /
> },
  24 |     { href: "/about", label: "About" },
  25 |   ];
  26 |
  27 |   return (
  28 |     <header
  29 |       className={`fixed top-0 w-full z-50 transition-all duration-300 ${
  30 |         isScrolled ? "bg-white/95 backdrop-blur-md border-b border-border shadow-sm py-2" : "bg-white py-4"
  31 |       }`}
  32 |     >
  33 |       <div className="container mx-auto px-4 md:px-6">
  34 |         <div className="flex items-center justify-between">
  35 |           <Link href="/" className="flex items-center gap-2 group">
  36 |             <div className="bg-primary/10 p-2 rounded-lg group-hover:bg-primary/20 transition-colors">
  37 |               <Droplets className="w-6 h-6 text-primary" />
  38 |             </div>
  39 |             <span className="font-bold text-xl tracking-tight text-foreground">
  40 |               MBC
  41 |             </span>
  42 |           </Link>
  43 |
  44 |           {/* Desktop Nav */}
  45 |           <nav className="hidden lg:flex items-center gap-6">
  46 |             {navLinks.map((link) => (
  47 |               <Link
  48 |                 key={link.href}
  49 |                 href={link.href}
  50 |                 className={`text-sm font-medium transition-colors hover:text-primary flex items-center ${
  51 |                   location === link.href ? "text-primary" : "text-muted-foreground"
  52 |                 }`}
  53 |               >
  54 |                 {link.icon}
  55 |                 {link.label}
  56 |               </Link>
  57 |             ))}
  58 |           </nav>
  59 |
  60 |           {/* Actions */}
  61 |           <div className="hidden lg:flex items-center gap-4">
  62 |             <Link href="/register-donor">
  63 |               <Button variant="outline" className="border-primary/20 hover:bg-primary/5 font-medium">
  64 |                 <Heart className="w-4 h-4 mr-2 text-primary" />
  65 |                 Register as Donor
  66 |               </Button>
  67 |             </Link>
  68 |             <Link href="/request-blood">
  69 |               <Button variant="destructive" className="font-semibold shadow-md hover:shadow-lg transition-all
active:scale-95 flex items-center gap-2">
  70 |                 <AlertCircle className="w-4 h-4" />
  71 |                 Request Blood (Emergency)
  72 |               </Button>
  73 |             </Link>
  74 |           </div>
  75 |
  76 |           {/* Mobile Toggle */}
  77 |           <button
  78 |             className="lg:hidden p-2 text-foreground"
  79 |             onClick={() => setMobileMenuOpen(!mobileMenuOpen)}
  80 |           >
  81 |             {mobileMenuOpen ? <X className="w-6 h-6" /> : <Menu className="w-6 h-6" />}
  82 |           </button>
  83 |         </div>
  84 |       </div>
  85 |
  86 |       {/* Mobile Nav */}
  87 |       <AnimatePresence>
  88 |         {mobileMenuOpen && (
  89 |           <motion.div
  90 |             initial={{ opacity: 0, height: 0 }}
  91 |             animate={{ opacity: 1, height: "auto" }}
  92 |             exit={{ opacity: 0, height: 0 }}
  93 |             className="lg:hidden border-t border-border bg-white overflow-hidden"
  94 |           >
  95 |             <div className="container mx-auto px-4 py-4 flex flex-col gap-4">
  96 |               {navLinks.map((link) => (
  97 |                 <Link
  98 |                   key={link.href}
```

```
 99 |                    href={link.href}
100 |                    onClick={() => setMobileMenuOpen(false)}
101 |                    className={`text-sm font-medium py-2 flex items-center ${
102 |                      location === link.href ? "text-primary" : "text-foreground"
103 |                    }`}
104 |                  >
105 |                    {link.icon}
106 |                    {link.label}
107 |                  </Link>
108 |                ))}
109 |                <div className="flex flex-col gap-3 pt-4 border-t border-border">
110 |                  <Link href="/register-donor" onClick={() => setMobileMenuOpen(false)}>
111 |                    <Button variant="outline" className="w-full justify-center">
112 |                      <Heart className="w-4 h-4 mr-2" />
113 |                      Register as Donor
114 |                    </Button>
115 |                  </Link>
116 |                  <Link href="/request-blood" onClick={() => setMobileMenuOpen(false)}>
117 |                    <Button variant="destructive" className="w-full justify-center font-bold">
118 |                      <AlertCircle className="w-4 h-4 mr-2" />
119 |                      Emergency Blood Request
120 |                    </Button>
121 |                  </Link>
122 |                </div>
123 |              </div>
124 |            </motion.div>
125 |          )}
126 |        </AnimatePresence>
127 |      </header>
128 |    );
129 | }
130 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/accordion.tsx

```
   1 | import * as React from "react"
   2 | import * as AccordionPrimitive from "@radix-ui/react-accordion"
   3 | import { ChevronDown } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const Accordion = AccordionPrimitive.Root
   8 |
   9 | const AccordionItem = React.forwardRef<
  10 |   React.ElementRef<typeof AccordionPrimitive.Item>,
  11 |   React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>
  12 | >(({ className, ...props }, ref) => (
  13 |   <AccordionPrimitive.Item
  14 |     ref={ref}
  15 |     className={cn("border-b", className)}
  16 |     {...props}
  17 |   />
  18 | ))
  19 | AccordionItem.displayName = "AccordionItem"
  20 |
  21 | const AccordionTrigger = React.forwardRef<
  22 |   React.ElementRef<typeof AccordionPrimitive.Trigger>,
  23 |   React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>
  24 | >(({ className, children, ...props }, ref) => (
  25 |   <AccordionPrimitive.Header className="flex">
  26 |     <AccordionPrimitive.Trigger
  27 |       ref={ref}
  28 |       className={cn(
  29 |         "flex flex-1 items-center justify-between py-4 text-sm font-medium transition-all hover:underline text-
left [&[data-state=open]>svg]:rotate-180",
  30 |         className
  31 |       )}
  32 |       {...props}
  33 |     >
  34 |       {children}
  35 |       <ChevronDown className="h-4 w-4 shrink-0 text-muted-foreground transition-transform duration-200" />
  36 |     </AccordionPrimitive.Trigger>
  37 |   </AccordionPrimitive.Header>
  38 | ))
  39 | AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName
  40 |
  41 | const AccordionContent = React.forwardRef<
  42 |   React.ElementRef<typeof AccordionPrimitive.Content>,
  43 |   React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
  44 | >(({ className, children, ...props }, ref) => (
  45 |   <AccordionPrimitive.Content
  46 |     ref={ref}
  47 |     className="overflow-hidden text-sm data-[state=closed]:animate-accordion-up data-[state=open]:animate-
accordion-down"
  48 |     {...props}
  49 |   >
  50 |     <div className={cn("pb-4 pt-0", className)}>{children}</div>
  51 |   </AccordionPrimitive.Content>
  52 | ))
  53 | AccordionContent.displayName = AccordionPrimitive.Content.displayName
  54 |
  55 | export { Accordion, AccordionItem, AccordionTrigger, AccordionContent }
  56 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/alert-dialog.tsx

```
   1 | import * as React from "react"
   2 | import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 | import { buttonVariants } from "@/components/ui/button"
   6 |
   7 | const AlertDialog = AlertDialogPrimitive.Root
   8 |
   9 | const AlertDialogTrigger = AlertDialogPrimitive.Trigger
  10 |
  11 | const AlertDialogPortal = AlertDialogPrimitive.Portal
  12 |
  13 | const AlertDialogOverlay = React.forwardRef<
  14 |   React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
  15 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
  16 | >(({ className, ...props }, ref) => (
  17 |   <AlertDialogPrimitive.Overlay
  18 |     className={cn(
  19 |       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
  20 |       className
  21 |     )}
  22 |     {...props}
  23 |     ref={ref}
  24 |   />
  25 | ))
  26 | AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName
  27 |
  28 | const AlertDialogContent = React.forwardRef<
  29 |   React.ElementRef<typeof AlertDialogPrimitive.Content>,
  30 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
  31 | >(({ className, ...props }, ref) => (
  32 |   <AlertDialogPortal>
  33 |     <AlertDialogOverlay />
  34 |     <AlertDialogPrimitive.Content
  35 |       ref={ref}
  36 |       className={cn(
  37 |         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
bg-background p-6 shadow-lg duration-200 dat...
  38 |         className
  39 |       )}
  40 |       {...props}
  41 |     />
  42 |   </AlertDialogPortal>
  43 | ))
  44 | AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName
  45 |
  46 | const AlertDialogHeader = ({
  47 |   className,
  48 |   ...props
  49 | }: React.HTMLAttributes<HTMLDivElement>) => (
  50 |   <div
  51 |     className={cn(
  52 |       "flex flex-col space-y-2 text-center sm:text-left",
  53 |       className
  54 |     )}
  55 |     {...props}
  56 |   />
  57 | )
  58 | AlertDialogHeader.displayName = "AlertDialogHeader"
  59 |
  60 | const AlertDialogFooter = ({
  61 |   className,
  62 |   ...props
  63 | }: React.HTMLAttributes<HTMLDivElement>) => (
  64 |   <div
  65 |     className={cn(
  66 |       "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
  67 |       className
  68 |     )}
  69 |     {...props}
  70 |   />
  71 | )
  72 | AlertDialogFooter.displayName = "AlertDialogFooter"
  73 |
  74 | const AlertDialogTitle = React.forwardRef<
  75 |   React.ElementRef<typeof AlertDialogPrimitive.Title>,
  76 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>
  77 | >(({ className, ...props }, ref) => (
  78 |   <AlertDialogPrimitive.Title
  79 |     ref={ref}
  80 |     className={cn("text-lg font-semibold", className)}
  81 |     {...props}
  82 |   />
  83 | ))
  84 | AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName
  85 |
  86 | const AlertDialogDescription = React.forwardRef<
  87 |   React.ElementRef<typeof AlertDialogPrimitive.Description>,
  88 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>
  89 | >(({ className, ...props }, ref) => (
  90 |   <AlertDialogPrimitive.Description
  91 |     ref={ref}
  92 |     className={cn("text-sm text-muted-foreground", className)}
  93 |     {...props}
  94 |   />
  95 | ))
  96 | AlertDialogDescription.displayName =
  97 |   AlertDialogPrimitive.Description.displayName
  98 |
```

```
 99 | const AlertDialogAction = React.forwardRef<
100 |   React.ElementRef<typeof AlertDialogPrimitive.Action>,
101 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>
102 | >(({ className, ...props }, ref) => (
103 |   <AlertDialogPrimitive.Action
104 |     ref={ref}
105 |     className={cn(buttonVariants(), className)}
106 |     {...props}
107 |   />
108 | ))
109 | AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName
110 |
111 | const AlertDialogCancel = React.forwardRef<
112 |   React.ElementRef<typeof AlertDialogPrimitive.Cancel>,
113 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>
114 | >(({ className, ...props }, ref) => (
115 |   <AlertDialogPrimitive.Cancel
116 |     ref={ref}
117 |     className={cn(
118 |       buttonVariants({ variant: "outline" }),
119 |       "mt-2 sm:mt-0",
120 |       className
121 |     )}
122 |     {...props}
123 |   />
124 | ))
125 | AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName
126 |
127 | export {
128 |   AlertDialog,
129 |   AlertDialogPortal,
130 |   AlertDialogOverlay,
131 |   AlertDialogTrigger,
132 |   AlertDialogContent,
133 |   AlertDialogHeader,
134 |   AlertDialogFooter,
135 |   AlertDialogTitle,
136 |   AlertDialogDescription,
137 |   AlertDialogAction,
138 |   AlertDialogCancel,
139 | }
140 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/alert.tsx

```
   1 | import * as React from "react"
   2 | import { cva, type VariantProps } from "class-variance-authority"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const alertVariants = cva(
   7 |   "relative w-full rounded-lg border px-4 py-3 text-sm [&>svg+div]:translate-y-[-3px] [&>svg]:absolute
[&>svg]:left-4 [&>svg]:top-4 [&>svg]:text-foreground [...
   8 |   {
   9 |     variants: {
  10 |       variant: {
  11 |         default: "bg-background text-foreground",
  12 |         destructive:
  13 |           "border-destructive/50 text-destructive dark:border-destructive [&>svg]:text-destructive",
  14 |       },
  15 |     },
  16 |     defaultVariants: {
  17 |       variant: "default",
  18 |     },
  19 |   }
  20 | )
  21 |
  22 | const Alert = React.forwardRef<
  23 |   HTMLDivElement,
  24 |   React.HTMLAttributes<HTMLDivElement> & VariantProps<typeof alertVariants>
  25 | >(({ className, variant, ...props }, ref) => (
  26 |   <div
  27 |     ref={ref}
  28 |     role="alert"
  29 |     className={cn(alertVariants({ variant }), className)}
  30 |     {...props}
  31 |   />
  32 | ))
  33 | Alert.displayName = "Alert"
  34 |
  35 | const AlertTitle = React.forwardRef<
  36 |   HTMLParagraphElement,
  37 |   React.HTMLAttributes<HTMLHeadingElement>
  38 | >(({ className, ...props }, ref) => (
  39 |   <h5
  40 |     ref={ref}
  41 |     className={cn("mb-1 font-medium leading-none tracking-tight", className)}
  42 |     {...props}
  43 |   />
  44 | ))
  45 | AlertTitle.displayName = "AlertTitle"
  46 |
  47 | const AlertDescription = React.forwardRef<
  48 |   HTMLParagraphElement,
  49 |   React.HTMLAttributes<HTMLParagraphElement>
  50 | >(({ className, ...props }, ref) => (
  51 |   <div
  52 |     ref={ref}
  53 |     className={cn("text-sm [&_p]:leading-relaxed", className)}
  54 |     {...props}
  55 |   />
  56 | ))
  57 | AlertDescription.displayName = "AlertDescription"
  58 |
  59 | export { Alert, AlertTitle, AlertDescription }
  60 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/aspect-ratio.tsx

```
1 | import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio"
2 |
3 | const AspectRatio = AspectRatioPrimitive.Root
4 |
5 | export { AspectRatio }
6 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/avatar.tsx

```
"use client"

import * as React from "react"
import * as AvatarPrimitive from "@radix-ui/react-avatar"

import { cn } from "@/lib/utils"

const Avatar = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Root
    ref={ref}
    className={cn(
      "relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full",
      className
    )}
    {...props}
  />
))
Avatar.displayName = AvatarPrimitive.Root.displayName

const AvatarImage = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Image>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Image>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Image
    ref={ref}
    className={cn("aspect-square h-full w-full", className)}
    {...props}
  />
))
AvatarImage.displayName = AvatarPrimitive.Image.displayName

const AvatarFallback = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Fallback>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Fallback>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Fallback
    ref={ref}
    className={cn(
      "flex h-full w-full items-center justify-center rounded-full bg-muted",
      className
    )}
    {...props}
  />
))
AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName

export { Avatar, AvatarImage, AvatarFallback }

```

— end of file —

File: artifacts/mbc-platform/src/components/ui/badge.tsx

```
   1 | import * as React from "react"
   2 | import { cva, type VariantProps } from "class-variance-authority"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const badgeVariants = cva(
   7 |   // @replit
   8 |   // Whitespace-nowrap: Badges should never wrap.
   9 |   "whitespace-nowrap inline-flex items-center rounded-md border px-2.5 py-0.5 text-xs font-semibold transition-
colors focus:outline-none focus:ring-2 focus:r...
  10 |   " hover-elevate ",
  11 |   {
  12 |     variants: {
  13 |       variant: {
  14 |         default:
  15 |           // @replit shadow-xs instead of shadow, no hover because we use hover-elevate
  16 |           "border-transparent bg-primary text-primary-foreground shadow-xs",
  17 |         secondary:
  18 |           // @replit no hover because we use hover-elevate
  19 |           "border-transparent bg-secondary text-secondary-foreground",
  20 |         destructive:
  21 |           // @replit shadow-xs instead of shadow, no hover because we use hover-elevate
  22 |           "border-transparent bg-destructive text-destructive-foreground shadow-xs",
  23 |           // @replit shadow-xs" - use badge outline variable
  24 |         outline: "text-foreground border [border-color:var(--badge-outline)]",
  25 |       },
  26 |     },
  27 |     defaultVariants: {
  28 |       variant: "default",
  29 |     },
  30 |   }
  31 | )
  32 |
  33 | export interface BadgeProps
  34 |   extends React.HTMLAttributes<HTMLDivElement>,
  35 |     VariantProps<typeof badgeVariants> {}
  36 |
  37 | function Badge({ className, variant, ...props }: BadgeProps) {
  38 |   return (
  39 |     <div className={cn(badgeVariants({ variant }), className)} {...props} />
  40 |   )
  41 | }
  42 |
  43 | export { Badge, badgeVariants }
  44 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/breadcrumb.tsx

```
  1 | import * as React from "react"
  2 | import { Slot } from "@radix-ui/react-slot"
  3 | import { ChevronRight, MoreHorizontal } from "lucide-react"
  4 |
  5 | import { cn } from "@/lib/utils"
  6 |
  7 | const Breadcrumb = React.forwardRef<
  8 |   HTMLElement,
  9 |   React.ComponentPropsWithoutRef<"nav"> & {
 10 |     separator?: React.ReactNode
 11 |   }
 12 | >({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb" {...props} />)
 13 | Breadcrumb.displayName = "Breadcrumb"
 14 |
 15 | const BreadcrumbList = React.forwardRef<
 16 |   HTMLOListElement,
 17 |   React.ComponentPropsWithoutRef<"ol">
 18 | >({ className, ...props }, ref) => (
 19 |   <ol
 20 |     ref={ref}
 21 |     className={cn(
 22 |       "flex flex-wrap items-center gap-1.5 break-words text-sm text-muted-foreground sm:gap-2.5",
 23 |       className
 24 |     )}
 25 |     {...props}
 26 |   />
 27 | ))
 28 | BreadcrumbList.displayName = "BreadcrumbList"
 29 |
 30 | const BreadcrumbItem = React.forwardRef<
 31 |   HTMLLIElement,
 32 |   React.ComponentPropsWithoutRef<"li">
 33 | >({ className, ...props }, ref) => (
 34 |   <li
 35 |     ref={ref}
 36 |     className={cn("inline-flex items-center gap-1.5", className)}
 37 |     {...props}
 38 |   />
 39 | ))
 40 | BreadcrumbItem.displayName = "BreadcrumbItem"
 41 |
 42 | const BreadcrumbLink = React.forwardRef<
 43 |   HTMLAnchorElement,
 44 |   React.ComponentPropsWithoutRef<"a"> & {
 45 |     asChild?: boolean
 46 |   }
 47 | >({ asChild, className, ...props }, ref) => {
 48 |   const Comp = asChild ? Slot : "a"
 49 |
 50 |   return (
 51 |     <Comp
 52 |       ref={ref}
 53 |       className={cn("transition-colors hover:text-foreground", className)}
 54 |       {...props}
 55 |     />
 56 |   )
 57 | })
 58 | BreadcrumbLink.displayName = "BreadcrumbLink"
 59 |
 60 | const BreadcrumbPage = React.forwardRef<
 61 |   HTMLSpanElement,
 62 |   React.ComponentPropsWithoutRef<"span">
 63 | >({ className, ...props }, ref) => (
 64 |   <span
 65 |     ref={ref}
 66 |     role="link"
 67 |     aria-disabled="true"
 68 |     aria-current="page"
 69 |     className={cn("font-normal text-foreground", className)}
 70 |     {...props}
 71 |   />
 72 | ))
 73 | BreadcrumbPage.displayName = "BreadcrumbPage"
 74 |
 75 | const BreadcrumbSeparator = ({
 76 |   children,
 77 |   className,
 78 |   ...props
 79 | }: React.ComponentProps<"li">) => (
 80 |   <li
 81 |     role="presentation"
 82 |     aria-hidden="true"
 83 |     className={cn("[&>svg]:w-3.5 [&>svg]:h-3.5", className)}
 84 |     {...props}
 85 |   >
 86 |     {children ?? <ChevronRight />}
 87 |   </li>
 88 | )
 89 | BreadcrumbSeparator.displayName = "BreadcrumbSeparator"
 90 |
 91 | const BreadcrumbEllipsis = ({
 92 |   className,
 93 |   ...props
 94 | }: React.ComponentProps<"span">) => (
 95 |   <span
 96 |     role="presentation"
 97 |     aria-hidden="true"
 98 |     className={cn("flex h-9 w-9 items-center justify-center", className)}
 99 |     {...props}
100 |   >
```

```
101 |     <MoreHorizontal className="h-4 w-4" />
102 |     <span className="sr-only">More</span>
103 |   </span>
104 | )
105 | BreadcrumbEllipsis.displayName = "BreadcrumbElipssis"
106 |
107 | export {
108 |   Breadcrumb,
109 |   BreadcrumbList,
110 |   BreadcrumbItem,
111 |   BreadcrumbLink,
112 |   BreadcrumbPage,
113 |   BreadcrumbSeparator,
114 |   BreadcrumbEllipsis,
115 | }
116 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/button-group.tsx

```
   1 | import { Slot } from "@radix-ui/react-slot"
   2 | import { cva, type VariantProps } from "class-variance-authority"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 | import { Separator } from "@/components/ui/separator"
   6 |
   7 | const buttonGroupVariants = cva(
   8 |   "flex w-fit items-stretch has-[>[data-slot=button-group]]:gap-2 [&>*]:focus-visible:relative [&>*]:focus-
visible:z-10 has-[select[aria-hidden=true]:last-ch...
   9 |   {
  10 |     variants: {
  11 |       orientation: {
  12 |         horizontal:
  13 |           "[&>*:not(:first-child)]:rounded-l-none [&>*:not(:first-child)]:border-l-0 [&>*:not(:last-
child)]:rounded-r-none",
  14 |         vertical:
  15 |           "flex-col [&>*:not(:first-child)]:rounded-t-none [&>*:not(:first-child)]:border-t-0 [&>*:not(:last-
child)]:rounded-b-none",
  16 |       },
  17 |     },
  18 |     defaultVariants: {
  19 |       orientation: "horizontal",
  20 |     },
  21 |   }
  22 | )
  23 |
  24 | function ButtonGroup({
  25 |   className,
  26 |   orientation,
  27 |   ...props
  28 | }: React.ComponentProps<"div"> & VariantProps<typeof buttonGroupVariants>) {
  29 |   return (
  30 |     <div
  31 |       role="group"
  32 |       data-slot="button-group"
  33 |       data-orientation={orientation}
  34 |       className={cn(buttonGroupVariants({ orientation }), className)}
  35 |       {...props}
  36 |     />
  37 |   )
  38 | }
  39 |
  40 | function ButtonGroupText({
  41 |   className,
  42 |   asChild = false,
  43 |   ...props
  44 | }: React.ComponentProps<"div"> & {
  45 |   asChild?: boolean
  46 | }) {
  47 |   const Comp = asChild ? Slot : "div"
  48 |
  49 |   return (
  50 |     <Comp
  51 |       className={cn(
  52 |         "bg-muted shadow-xs flex items-center gap-2 rounded-md border px-4 text-sm font-medium
[&_svg:not([class*='size-'])]:size-4 [&_svg]:pointer-events-no...
  53 |         className
  54 |       )}
  55 |       {...props}
  56 |     />
  57 |   )
  58 | }
  59 |
  60 | function ButtonGroupSeparator({
  61 |   className,
  62 |   orientation = "vertical",
  63 |   ...props
  64 | }: React.ComponentProps<typeof Separator>) {
  65 |   return (
  66 |     <Separator
  67 |       data-slot="button-group-separator"
  68 |       orientation={orientation}
  69 |       className={cn(
  70 |         "bg-input relative !m-0 self-stretch data-[orientation=vertical]:h-auto",
  71 |         className
  72 |       )}
  73 |       {...props}
  74 |     />
  75 |   )
  76 | }
  77 |
  78 | export {
  79 |   ButtonGroup,
  80 |   ButtonGroupSeparator,
  81 |   ButtonGroupText,
  82 |   buttonGroupVariants,
  83 | }
  84 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/button.tsx

```
   1 | import * as React from "react"
   2 | import { Slot } from "@radix-ui/react-slot"
   3 | import { cva, type VariantProps } from "class-variance-authority"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const buttonVariants = cva(
   8 |   "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium transition-
colors focus-visible:outline-none focus-visible:...
   9 | " hover-elevate active-elevate-2",
  10 |   {
  11 |     variants: {
  12 |       variant: {
  13 |         default:
  14 |            // @replit: no hover, and add primary border
  15 |            "bg-primary text-primary-foreground border border-primary-border",
  16 |         destructive:
  17 |           "bg-destructive text-destructive-foreground shadow-sm border-destructive-border",
  18 |         outline:
  19 |           // @replit Shows the background color of whatever card / sidebar / accent background it is inside of.
  20 |           // Inherits the current text color. Uses shadow-xs. no shadow on active
  21 |           // No hover state
  22 |           " border [border-color:var(--button-outline)] shadow-xs active:shadow-none ",
  23 |         secondary:
  24 |           // @replit border, no hover, no shadow, secondary border.
  25 |           "border bg-secondary text-secondary-foreground border border-secondary-border ",
  26 |         // @replit no hover, transparent border
  27 |         ghost: "border border-transparent",
  28 |         link: "text-primary underline-offset-4 hover:underline",
  29 |       },
  30 |       size: {
  31 |         // @replit changed sizes
  32 |         default: "min-h-9 px-4 py-2",
  33 |         sm: "min-h-8 rounded-md px-3 text-xs",
  34 |         lg: "min-h-10 rounded-md px-8",
  35 |         icon: "h-9 w-9",
  36 |       },
  37 |     },
  38 |     defaultVariants: {
  39 |       variant: "default",
  40 |       size: "default",
  41 |     },
  42 |   }
  43 | )
  44 |
  45 | export interface ButtonProps
  46 |   extends React.ButtonHTMLAttributes<HTMLButtonElement>,
  47 |     VariantProps<typeof buttonVariants> {
  48 |   asChild?: boolean
  49 | }
  50 |
  51 | const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  52 |   ({ className, variant, size, asChild = false, ...props }, ref) => {
  53 |     const Comp = asChild ? Slot : "button"
  54 |     return (
  55 |       <Comp
  56 |         className={cn(buttonVariants({ variant, size, className }))}
  57 |         ref={ref}
  58 |         {...props}
  59 |       />
  60 |     )
  61 |   }
  62 | )
  63 | Button.displayName = "Button"
  64 |
  65 | export { Button, buttonVariants }
  66 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/calendar.tsx

```
"use client"

import * as React from "react"
import {
  ChevronDownIcon,
  ChevronLeftIcon,
  ChevronRightIcon,
} from "lucide-react"
import { DayButton, DayPicker, getDefaultClassNames } from "react-day-picker"

import { cn } from "@/lib/utils"
import { Button, buttonVariants } from "@/components/ui/button"

function Calendar({
  className,
  classNames,
  showOutsideDays = true,
  captionLayout = "label",
  buttonVariant = "ghost",
  formatters,
  components,
  ...props
}: React.ComponentProps<typeof DayPicker> & {
  buttonVariant?: React.ComponentProps<typeof Button>["variant"]
}) {
  const defaultClassNames = getDefaultClassNames()

  return (
    <DayPicker
      showOutsideDays={showOutsideDays}
      className={cn(
        "bg-background group/calendar p-3 [--cell-size:2rem] [[data-slot=card-content]_&]:bg-transparent [[data-slot=popover-content]_&]:bg-transparent",
        String.raw`rtl:**:[.rdp-button\_next>svg]:rotate-180`,
        String.raw`rtl:**:[.rdp-button\_previous>svg]:rotate-180`,
        className
      )}
      captionLayout={captionLayout}
      formatters={{
        formatMonthDropdown: (date) =>
          date.toLocaleString("default", { month: "short" }),
        ...formatters,
      }}
      classNames={{
        root: cn("w-fit", defaultClassNames.root),
        months: cn(
          "relative flex flex-col gap-4 md:flex-row",
          defaultClassNames.months
        ),
        month: cn("flex w-full flex-col gap-4", defaultClassNames.month),
        nav: cn(
          "absolute inset-x-0 top-0 flex w-full items-center justify-between gap-1",
          defaultClassNames.nav
        ),
        button_previous: cn(
          buttonVariants({ variant: buttonVariant }),
          "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
          defaultClassNames.button_previous
        ),
        button_next: cn(
          buttonVariants({ variant: buttonVariant }),
          "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
          defaultClassNames.button_next
        ),
        month_caption: cn(
          "flex h-[--cell-size] w-full items-center justify-center px-[--cell-size]",
          defaultClassNames.month_caption
        ),
        dropdowns: cn(
          "flex h-[--cell-size] w-full items-center justify-center gap-1.5 text-sm font-medium",
          defaultClassNames.dropdowns
        ),
        dropdown_root: cn(
          "has-focus:border-ring border-input shadow-xs has-focus:ring-ring/50 has-focus:ring-[3px] relative rounded-md border",
          defaultClassNames.dropdown_root
        ),
        dropdown: cn(
          "bg-popover absolute inset-0 opacity-0",
          defaultClassNames.dropdown
        ),
        caption_label: cn(
          "select-none font-medium",
          captionLayout === "label"
            ? "text-sm"
            : "[&>svg]:text-muted-foreground flex h-8 items-center gap-1 rounded-md pl-2 pr-1 text-sm [&>svg]:size-3.5",
          defaultClassNames.caption_label
        ),
        table: "w-full border-collapse",
        weekdays: cn("flex", defaultClassNames.weekdays),
        weekday: cn(
          "text-muted-foreground flex-1 select-none rounded-md text-[0.8rem] font-normal",
          defaultClassNames.weekday
        ),
        week: cn("mt-2 flex w-full", defaultClassNames.week),
        week_number_header: cn(
          "w-[--cell-size] select-none",
          defaultClassNames.week_number_header
        ),
```

```
 98 |         week_number: cn(
 99 |           "text-muted-foreground select-none text-[0.8rem]",
100 |           defaultClassNames.week_number
101 |         ),
102 |         day: cn(
103 |           "group/day relative aspect-square h-full w-full select-none p-0 text-center [&:first-child[data-
selected=true]_button]:rounded-l-md [&:last-child[d...
104 |           defaultClassNames.day
105 |         ),
106 |         range_start: cn(
107 |           "bg-accent rounded-l-md",
108 |           defaultClassNames.range_start
109 |         ),
110 |         range_middle: cn("rounded-none", defaultClassNames.range_middle),
111 |         range_end: cn("bg-accent rounded-r-md", defaultClassNames.range_end),
112 |         today: cn(
113 |           "bg-accent text-accent-foreground rounded-md data-[selected=true]:rounded-none",
114 |           defaultClassNames.today
115 |         ),
116 |         outside: cn(
117 |           "text-muted-foreground aria-selected:text-muted-foreground",
118 |           defaultClassNames.outside
119 |         ),
120 |         disabled: cn(
121 |           "text-muted-foreground opacity-50",
122 |           defaultClassNames.disabled
123 |         ),
124 |         hidden: cn("invisible", defaultClassNames.hidden),
125 |         ...classNames,
126 |       }}
127 |       components={{
128 |         Root: ({ className, rootRef, ...props }) => {
129 |           return (
130 |             <div
131 |               data-slot="calendar"
132 |               ref={rootRef}
133 |               className={cn(className)}
134 |               {...props}
135 |             />
136 |           )
137 |         },
138 |         Chevron: ({ className, orientation, ...props }) => {
139 |           if (orientation === "left") {
140 |             return (
141 |               <ChevronLeftIcon className={cn("size-4", className)} {...props} />
142 |             )
143 |           }
144 |
145 |           if (orientation === "right") {
146 |             return (
147 |               <ChevronRightIcon
148 |                 className={cn("size-4", className)}
149 |                 {...props}
150 |               />
151 |             )
152 |           }
153 |
154 |           return (
155 |             <ChevronDownIcon className={cn("size-4", className)} {...props} />
156 |           )
157 |         },
158 |         DayButton: CalendarDayButton,
159 |         WeekNumber: ({ children, ...props }) => {
160 |           return (
161 |             <td {...props}>
162 |               <div className="flex size-[--cell-size] items-center justify-center text-center">
163 |                 {children}
164 |               </div>
165 |             </td>
166 |           )
167 |         },
168 |         ...components,
169 |       }}
170 |       {...props}
171 |     />
172 |   )
173 | }
174 |
175 | function CalendarDayButton({
176 |   className,
177 |   day,
178 |   modifiers,
179 |   ...props
180 | }: React.ComponentProps<typeof DayButton>) {
181 |   const defaultClassNames = getDefaultClassNames()
182 |
183 |   const ref = React.useRef<HTMLButtonElement>(null)
184 |   React.useEffect(() => {
185 |     if (modifiers.focused) ref.current?.focus()
186 |   }, [modifiers.focused])
187 |
188 |   return (
189 |     <Button
190 |       ref={ref}
191 |       variant="ghost"
192 |       size="icon"
193 |       data-day={day.date.toLocaleDateString()}
194 |       data-selected-single={
195 |         modifiers.selected &&
196 |         !modifiers.range_start &&
197 |         !modifiers.range_end &&
198 |         !modifiers.range_middle
199 |       }
```

```
 200 |       data-range-start={modifiers.range_start}
 201 |       data-range-end={modifiers.range_end}
 202 |       data-range-middle={modifiers.range_middle}
 203 |       className={cn(
 204 |         "data-[selected-single=true]:bg-primary data-[selected-single=true]:text-primary-foreground data-[range-
middle=true]:bg-accent data-[range-middle=tru...
 205 |         defaultClassNames.day,
 206 |         className
 207 |       )}
 208 |       {...props}
 209 |     />
 210 |   )
 211 | }
 212 |
 213 | export { Calendar, CalendarDayButton }
 214 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/card.tsx

```
 1 | import * as React from "react"
 2 |
 3 | import { cn } from "@/lib/utils"
 4 |
 5 | const Card = React.forwardRef<
 6 |   HTMLDivElement,
 7 |   React.HTMLAttributes<HTMLDivElement>
 8 | >(({ className, ...props }, ref) => (
 9 |   <div
10 |     ref={ref}
11 |     className={cn(
12 |       "rounded-xl border bg-card text-card-foreground shadow",
13 |       className
14 |     )}
15 |     {...props}
16 |   />
17 | ))
18 | Card.displayName = "Card"
19 |
20 | const CardHeader = React.forwardRef<
21 |   HTMLDivElement,
22 |   React.HTMLAttributes<HTMLDivElement>
23 | >(({ className, ...props }, ref) => (
24 |   <div
25 |     ref={ref}
26 |     className={cn("flex flex-col space-y-1.5 p-6", className)}
27 |     {...props}
28 |   />
29 | ))
30 | CardHeader.displayName = "CardHeader"
31 |
32 | const CardTitle = React.forwardRef<
33 |   HTMLDivElement,
34 |   React.HTMLAttributes<HTMLDivElement>
35 | >(({ className, ...props }, ref) => (
36 |   <div
37 |     ref={ref}
38 |     className={cn("font-semibold leading-none tracking-tight", className)}
39 |     {...props}
40 |   />
41 | ))
42 | CardTitle.displayName = "CardTitle"
43 |
44 | const CardDescription = React.forwardRef<
45 |   HTMLDivElement,
46 |   React.HTMLAttributes<HTMLDivElement>
47 | >(({ className, ...props }, ref) => (
48 |   <div
49 |     ref={ref}
50 |     className={cn("text-sm text-muted-foreground", className)}
51 |     {...props}
52 |   />
53 | ))
54 | CardDescription.displayName = "CardDescription"
55 |
56 | const CardContent = React.forwardRef<
57 |   HTMLDivElement,
58 |   React.HTMLAttributes<HTMLDivElement>
59 | >(({ className, ...props }, ref) => (
60 |   <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
61 | ))
62 | CardContent.displayName = "CardContent"
63 |
64 | const CardFooter = React.forwardRef<
65 |   HTMLDivElement,
66 |   React.HTMLAttributes<HTMLDivElement>
67 | >(({ className, ...props }, ref) => (
68 |   <div
69 |     ref={ref}
70 |     className={cn("flex items-center p-6 pt-0", className)}
71 |     {...props}
72 |   />
73 | ))
74 | CardFooter.displayName = "CardFooter"
75 |
76 | export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }
77 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/carousel.tsx

```
  1 | import * as React from "react"
  2 | import useEmblaCarousel, {
  3 |   type UseEmblaCarouselType,
  4 | } from "embla-carousel-react"
  5 | import { ArrowLeft, ArrowRight } from "lucide-react"
  6 |
  7 | import { cn } from "@/lib/utils"
  8 | import { Button } from "@/components/ui/button"
  9 |
 10 | type CarouselApi = UseEmblaCarouselType[1]
 11 | type UseCarouselParameters = Parameters<typeof useEmblaCarousel>
 12 | type CarouselOptions = UseCarouselParameters[0]
 13 | type CarouselPlugin = UseCarouselParameters[1]
 14 |
 15 | type CarouselProps = {
 16 |   opts?: CarouselOptions
 17 |   plugins?: CarouselPlugin
 18 |   orientation?: "horizontal" | "vertical"
 19 |   setApi?: (api: CarouselApi) => void
 20 | }
 21 |
 22 | type CarouselContextProps = {
 23 |   carouselRef: ReturnType<typeof useEmblaCarousel>[0]
 24 |   api: ReturnType<typeof useEmblaCarousel>[1]
 25 |   scrollPrev: () => void
 26 |   scrollNext: () => void
 27 |   canScrollPrev: boolean
 28 |   canScrollNext: boolean
 29 | } & CarouselProps
 30 |
 31 | const CarouselContext = React.createContext<CarouselContextProps | null>(null)
 32 |
 33 | function useCarousel() {
 34 |   const context = React.useContext(CarouselContext)
 35 |
 36 |   if (!context) {
 37 |     throw new Error("useCarousel must be used within a <Carousel />")
 38 |   }
 39 |
 40 |   return context
 41 | }
 42 |
 43 | const Carousel = React.forwardRef<
 44 |   HTMLDivElement,
 45 |   React.HTMLAttributes<HTMLDivElement> & CarouselProps
 46 | >(
 47 |   (
 48 |     {
 49 |       orientation = "horizontal",
 50 |       opts,
 51 |       setApi,
 52 |       plugins,
 53 |       className,
 54 |       children,
 55 |       ...props
 56 |     },
 57 |     ref
 58 |   ) => {
 59 |     const [carouselRef, api] = useEmblaCarousel(
 60 |       {
 61 |         ...opts,
 62 |         axis: orientation === "horizontal" ? "x" : "y",
 63 |       },
 64 |       plugins
 65 |     )
 66 |     const [canScrollPrev, setCanScrollPrev] = React.useState(false)
 67 |     const [canScrollNext, setCanScrollNext] = React.useState(false)
 68 |
 69 |     const onSelect = React.useCallback((api: CarouselApi) => {
 70 |       if (!api) {
 71 |         return
 72 |       }
 73 |
 74 |       setCanScrollPrev(api.canScrollPrev())
 75 |       setCanScrollNext(api.canScrollNext())
 76 |     }, [])
 77 |
 78 |     const scrollPrev = React.useCallback(() => {
 79 |       api?.scrollPrev()
 80 |     }, [api])
 81 |
 82 |     const scrollNext = React.useCallback(() => {
 83 |       api?.scrollNext()
 84 |     }, [api])
 85 |
 86 |     const handleKeyDown = React.useCallback(
 87 |       (event: React.KeyboardEvent<HTMLDivElement>) => {
 88 |         if (event.key === "ArrowLeft") {
 89 |           event.preventDefault()
 90 |           scrollPrev()
 91 |         } else if (event.key === "ArrowRight") {
 92 |           event.preventDefault()
 93 |           scrollNext()
 94 |         }
 95 |       },
 96 |       [scrollPrev, scrollNext]
 97 |     )
 98 |
 99 |     React.useEffect(() => {
100 |       if (!api || !setApi) {
```

```
101 |         return
102 |       }
103 |
104 |       setApi(api)
105 |     }, [api, setApi])
106 |
107 |     React.useEffect(() => {
108 |       if (!api) {
109 |         return
110 |       }
111 |
112 |       onSelect(api)
113 |       api.on("reInit", onSelect)
114 |       api.on("select", onSelect)
115 |
116 |       return () => {
117 |         api?.off("select", onSelect)
118 |       }
119 |     }, [api, onSelect])
120 |
121 |     return (
122 |       <CarouselContext.Provider
123 |         value={{
124 |           carouselRef,
125 |           api: api,
126 |           opts,
127 |           orientation:
128 |             orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),
129 |           scrollPrev,
130 |           scrollNext,
131 |           canScrollPrev,
132 |           canScrollNext,
133 |         }}
134 |       >
135 |         <div
136 |           ref={ref}
137 |           onKeyDownCapture={handleKeyDown}
138 |           className={cn("relative", className)}
139 |           role="region"
140 |           aria-roledescription="carousel"
141 |           {...props}
142 |         >
143 |           {children}
144 |         </div>
145 |       </CarouselContext.Provider>
146 |     )
147 |   }
148 | )
149 | Carousel.displayName = "Carousel"
150 |
151 | const CarouselContent = React.forwardRef<
152 |   HTMLDivElement,
153 |   React.HTMLAttributes<HTMLDivElement>
154 | >(({ className, ...props }, ref) => {
155 |   const { carouselRef, orientation } = useCarousel()
156 |
157 |   return (
158 |     <div ref={carouselRef} className="overflow-hidden">
159 |       <div
160 |         ref={ref}
161 |         className={cn(
162 |           "flex",
163 |           orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col",
164 |           className
165 |         )}
166 |         {...props}
167 |       />
168 |     </div>
169 |   )
170 | })
171 | CarouselContent.displayName = "CarouselContent"
172 |
173 | const CarouselItem = React.forwardRef<
174 |   HTMLDivElement,
175 |   React.HTMLAttributes<HTMLDivElement>
176 | >(({ className, ...props }, ref) => {
177 |   const { orientation } = useCarousel()
178 |
179 |   return (
180 |     <div
181 |       ref={ref}
182 |       role="group"
183 |       aria-roledescription="slide"
184 |       className={cn(
185 |         "min-w-0 shrink-0 grow-0 basis-full",
186 |         orientation === "horizontal" ? "pl-4" : "pt-4",
187 |         className
188 |       )}
189 |       {...props}
190 |     />
191 |   )
192 | })
193 | CarouselItem.displayName = "CarouselItem"
194 |
195 | const CarouselPrevious = React.forwardRef<
196 |   HTMLButtonElement,
197 |   React.ComponentProps<typeof Button>
198 | >(({ className, variant = "outline", size = "icon", ...props }, ref) => {
199 |   const { orientation, scrollPrev, canScrollPrev } = useCarousel()
200 |
201 |   return (
202 |     <Button
203 |       ref={ref}
```

```
204 |       variant={variant}
205 |       size={size}
206 |       className={cn(
207 |         "absolute  h-8 w-8 rounded-full",
208 |         orientation === "horizontal"
209 |           ? "-left-12 top-1/2 -translate-y-1/2"
210 |           : "-top-12 left-1/2 -translate-x-1/2 rotate-90",
211 |         className
212 |       )}
213 |       disabled={!canScrollPrev}
214 |       onClick={scrollPrev}
215 |       {...props}
216 |     >
217 |       <ArrowLeft className="h-4 w-4" />
218 |       <span className="sr-only">Previous slide</span>
219 |     </Button>
220 |   )
221 | })
222 | CarouselPrevious.displayName = "CarouselPrevious"
223 |
224 | const CarouselNext = React.forwardRef<
225 |   HTMLButtonElement,
226 |   React.ComponentProps<typeof Button>
227 | >(({ className, variant = "outline", size = "icon", ...props }, ref) => {
228 |   const { orientation, scrollNext, canScrollNext } = useCarousel()
229 |
230 |   return (
231 |     <Button
232 |       ref={ref}
233 |       variant={variant}
234 |       size={size}
235 |       className={cn(
236 |         "absolute h-8 w-8 rounded-full",
237 |         orientation === "horizontal"
238 |           ? "-right-12 top-1/2 -translate-y-1/2"
239 |           : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",
240 |         className
241 |       )}
242 |       disabled={!canScrollNext}
243 |       onClick={scrollNext}
244 |       {...props}
245 |     >
246 |       <ArrowRight className="h-4 w-4" />
247 |       <span className="sr-only">Next slide</span>
248 |     </Button>
249 |   )
250 | })
251 | CarouselNext.displayName = "CarouselNext"
252 |
253 | export {
254 |   type CarouselApi,
255 |   Carousel,
256 |   CarouselContent,
257 |   CarouselItem,
258 |   CarouselPrevious,
259 |   CarouselNext,
260 | }
261 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/chart.tsx

```
   1 | import * as React from "react"
   2 | import * as RechartsPrimitive from "recharts"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | // Format: { THEME_NAME: CSS_SELECTOR }
   7 | const THEMES = { light: "", dark: ".dark" } as const
   8 |
   9 | export type ChartConfig = {
  10 |   [k in string]: {
  11 |     label?: React.ReactNode
  12 |     icon?: React.ComponentType
  13 |   } & (
  14 |     | { color?: string; theme?: never }
  15 |     | { color?: never; theme: Record<keyof typeof THEMES, string> }
  16 |   )
  17 | }
  18 |
  19 | type ChartContextProps = {
  20 |   config: ChartConfig
  21 | }
  22 |
  23 | const ChartContext = React.createContext<ChartContextProps | null>(null)
  24 |
  25 | function useChart() {
  26 |   const context = React.useContext(ChartContext)
  27 |
  28 |   if (!context) {
  29 |     throw new Error("useChart must be used within a <ChartContainer />")
  30 |   }
  31 |
  32 |   return context
  33 | }
  34 |
  35 | const ChartContainer = React.forwardRef<
  36 |   HTMLDivElement,
  37 |   React.ComponentProps<"div"> & {
  38 |     config: ChartConfig
  39 |     children: React.ComponentProps<
  40 |       typeof RechartsPrimitive.ResponsiveContainer
  41 |     >["children"]
  42 |   }
  43 | >(({ id, className, children, config, ...props }, ref) => {
  44 |   const uniqueId = React.useId()
  45 |   const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`
  46 |
  47 |   return (
  48 |     <ChartContext.Provider value={{ config }}>
  49 |       <div
  50 |         data-chart={chartId}
  51 |         ref={ref}
  52 |         className={cn(
  53 |           "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-muted-foreground
[&_.recharts-cartesian-grid_line[stroke='#cc...
  54 |           className
  55 |         )}
  56 |         {...props}
  57 |       >
  58 |         <ChartStyle id={chartId} config={config} />
  59 |         <RechartsPrimitive.ResponsiveContainer>
  60 |           {children}
  61 |         </RechartsPrimitive.ResponsiveContainer>
  62 |       </div>
  63 |     </ChartContext.Provider>
  64 |   )
  65 | })
  66 | ChartContainer.displayName = "Chart"
  67 |
  68 | const ChartStyle = ({ id, config }: { id: string; config: ChartConfig }) => {
  69 |   const colorConfig = Object.entries(config).filter(
  70 |     ([, config]) => config.theme || config.color
  71 |   )
  72 |
  73 |   if (!colorConfig.length) {
  74 |     return null
  75 |   }
  76 |
  77 |   return (
  78 |     <style
  79 |       dangerouslySetInnerHTML={{
  80 |         __html: Object.entries(THEMES)
  81 |           .map(
  82 |             ([theme, prefix]) => `
  83 | ${prefix} [data-chart=${id}] {
  84 | ${colorConfig
  85 |   .map(([key, itemConfig]) => {
  86 |     const color =
  87 |       itemConfig.theme?.[theme as keyof typeof itemConfig.theme] ||
  88 |       itemConfig.color
  89 |     return color ? `  --color-${key}: ${color};` : null
  90 |   })
  91 |   .join("\n")}
  92 | }
  93 | `
  94 |           )
  95 |           .join("\n"),
  96 |       }}
  97 |     />
  98 |   )
  99 | }
```

```
 100 |
 101 | const ChartTooltip = RechartsPrimitive.Tooltip
 102 |
 103 | const ChartTooltipContent = React.forwardRef<
 104 |   HTMLDivElement,
 105 |   React.ComponentProps<typeof RechartsPrimitive.Tooltip> &
 106 |     React.ComponentProps<"div"> & {
 107 |       hideLabel?: boolean
 108 |       hideIndicator?: boolean
 109 |       indicator?: "line" | "dot" | "dashed"
 110 |       nameKey?: string
 111 |       labelKey?: string
 112 |     }
 113 | >(
 114 |   (
 115 |     {
 116 |       active,
 117 |       payload,
 118 |       className,
 119 |       indicator = "dot",
 120 |       hideLabel = false,
 121 |       hideIndicator = false,
 122 |       label,
 123 |       labelFormatter,
 124 |       labelClassName,
 125 |       formatter,
 126 |       color,
 127 |       nameKey,
 128 |       labelKey,
 129 |     },
 130 |     ref
 131 |   ) => {
 132 |     const { config } = useChart()
 133 |
 134 |     const tooltipLabel = React.useMemo(() => {
 135 |       if (hideLabel || !payload?.length) {
 136 |         return null
 137 |       }
 138 |
 139 |       const [item] = payload
 140 |       const key = `${labelKey || item?.dataKey || item?.name || "value"}`
 141 |       const itemConfig = getPayloadConfigFromPayload(config, item, key)
 142 |       const value =
 143 |         !labelKey && typeof label === "string"
 144 |           ? config[label as keyof typeof config]?.label || label
 145 |           : itemConfig?.label
 146 |
 147 |       if (labelFormatter) {
 148 |         return (
 149 |           <div className={cn("font-medium", labelClassName)}>
 150 |             {labelFormatter(value, payload)}
 151 |           </div>
 152 |         )
 153 |       }
 154 |
 155 |       if (!value) {
 156 |         return null
 157 |       }
 158 |
 159 |       return <div className={cn("font-medium", labelClassName)}>{value}</div>
 160 |     }, [
 161 |       label,
 162 |       labelFormatter,
 163 |       payload,
 164 |       hideLabel,
 165 |       labelClassName,
 166 |       config,
 167 |       labelKey,
 168 |     ])
 169 |
 170 |     if (!active || !payload?.length) {
 171 |       return null
 172 |     }
 173 |
 174 |     const nestLabel = payload.length === 1 && indicator !== "dot"
 175 |
 176 |     return (
 177 |       <div
 178 |         ref={ref}
 179 |         className={cn(
 180 |           "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-background px-2.5 py-1.5
text-xs shadow-xl",
 181 |           className
 182 |         )}
 183 |       >
 184 |         {!nestLabel ? tooltipLabel : null}
 185 |         <div className="grid gap-1.5">
 186 |           {payload
 187 |             .filter((item) => item.type !== "none")
 188 |             .map((item, index) => {
 189 |               const key = `${nameKey || item.name || item.dataKey || "value"}`
 190 |               const itemConfig = getPayloadConfigFromPayload(config, item, key)
 191 |               const indicatorColor = color || item.payload.fill || item.color
 192 |
 193 |               return (
 194 |                 <div
 195 |                   key={item.dataKey}
 196 |                   className={cn(
 197 |                     "flex w-full flex-wrap items-stretch gap-2 [&>svg]:h-2.5 [&>svg]:w-2.5 [&>svg]:text-muted-
foreground",
 198 |                     indicator === "dot" && "items-center"
 199 |                   )}
 200 |                 >
```

```
201 |                   {formatter && item?.value !== undefined && item.name ? (
202 |                     formatter(item.value, item.name, item, index, item.payload)
203 |                   ) : (
204 |                     <>
205 |                       {itemConfig?.icon ? (
206 |                         <itemConfig.icon />
207 |                       ) : (
208 |                         !hideIndicator && (
209 |                           <div
210 |                             className={cn(
211 |                               "shrink-0 rounded-[2px] border-[--color-border] bg-[--color-bg]",
212 |                               {
213 |                                 "h-2.5 w-2.5": indicator === "dot",
214 |                                 "w-1": indicator === "line",
215 |                                 "w-0 border-[1.5px] border-dashed bg-transparent":
216 |                                   indicator === "dashed",
217 |                                 "my-0.5": nestLabel && indicator === "dashed",
218 |                               }
219 |                             )}
220 |                             style={
221 |                               {
222 |                                 "--color-bg": indicatorColor,
223 |                                 "--color-border": indicatorColor,
224 |                               } as React.CSSProperties
225 |                             }
226 |                           />
227 |                         )
228 |                       )}
229 |                       <div
230 |                         className={cn(
231 |                           "flex flex-1 justify-between leading-none",
232 |                           nestLabel ? "items-end" : "items-center"
233 |                         )}
234 |                       >
235 |                         <div className="grid gap-1.5">
236 |                           {nestLabel ? tooltipLabel : null}
237 |                           <span className="text-muted-foreground">
238 |                             {itemConfig?.label || item.name}
239 |                           </span>
240 |                         </div>
241 |                         {item.value && (
242 |                           <span className="font-mono font-medium tabular-nums text-foreground">
243 |                             {item.value.toLocaleString()}
244 |                           </span>
245 |                         )}
246 |                       </div>
247 |                     </>
248 |                   )}
249 |                 </div>
250 |               )
251 |             })}
252 |         </div>
253 |       </div>
254 |     )
255 |   }
256 | )
257 | ChartTooltipContent.displayName = "ChartTooltip"
258 |
259 | const ChartLegend = RechartsPrimitive.Legend
260 |
261 | const ChartLegendContent = React.forwardRef<
262 |   HTMLDivElement,
263 |   React.ComponentProps<"div"> &
264 |     Pick<RechartsPrimitive.LegendProps, "payload" | "verticalAlign"> & {
265 |       hideIcon?: boolean
266 |       nameKey?: string
267 |     }
268 | >(
269 |   (
270 |     { className, hideIcon = false, payload, verticalAlign = "bottom", nameKey },
271 |     ref
272 |   ) => {
273 |     const { config } = useChart()
274 |
275 |     if (!payload?.length) {
276 |       return null
277 |     }
278 |
279 |     return (
280 |       <div
281 |         ref={ref}
282 |         className={cn(
283 |           "flex items-center justify-center gap-4",
284 |           verticalAlign === "top" ? "pb-3" : "pt-3",
285 |           className
286 |         )}
287 |       >
288 |         {payload
289 |           .filter((item) => item.type !== "none")
290 |           .map((item) => {
291 |             const key = `${nameKey || item.dataKey || "value"}`
292 |             const itemConfig = getPayloadConfigFromPayload(config, item, key)
293 |
294 |             return (
295 |               <div
296 |                 key={item.value}
297 |                 className={cn(
298 |                   "flex items-center gap-1.5 [&>svg]:h-3 [&>svg]:w-3 [&>svg]:text-muted-foreground"
299 |                 )}
300 |               >
301 |                 {itemConfig?.icon && !hideIcon ? (
302 |                   <itemConfig.icon />
303 |                 ) : (
```

```
                    <div
                      className="h-2 w-2 shrink-0 rounded-[2px]"
                      style={{
                        backgroundColor: item.color,
                      }}
                    />
                  )}
                  {itemConfig?.label}
                </div>
              )
            })}
        </div>
      )
    }
)
ChartLegendContent.displayName = "ChartLegend"

// Helper to extract item config from a payload.
function getPayloadConfigFromPayload(
  config: ChartConfig,
  payload: unknown,
  key: string
) {
  if (typeof payload !== "object" || payload === null) {
    return undefined
  }

  const payloadPayload =
    "payload" in payload &&
    typeof payload.payload === "object" &&
    payload.payload !== null
      ? payload.payload
      : undefined

  let configLabelKey: string = key

  if (
    key in payload &&
    typeof payload[key as keyof typeof payload] === "string"
  ) {
    configLabelKey = payload[key as keyof typeof payload] as string
  } else if (
    payloadPayload &&
    key in payloadPayload &&
    typeof payloadPayload[key as keyof typeof payloadPayload] === "string"
  ) {
    configLabelKey = payloadPayload[
      key as keyof typeof payloadPayload
    ] as string
  }

  return configLabelKey in config
    ? config[configLabelKey]
    : config[key as keyof typeof config]
}

export {
  ChartContainer,
  ChartTooltip,
  ChartTooltipContent,
  ChartLegend,
  ChartLegendContent,
  ChartStyle,
}
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/checkbox.tsx

```
   1 | import * as React from "react"
   2 | import * as CheckboxPrimitive from "@radix-ui/react-checkbox"
   3 | import { Check } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const Checkbox = React.forwardRef<
   8 |   React.ElementRef<typeof CheckboxPrimitive.Root>,
   9 |   React.ComponentPropsWithoutRef<typeof CheckboxPrimitive.Root>
  10 | >(({ className, ...props }, ref) => (
  11 |   <CheckboxPrimitive.Root
  12 |     ref={ref}
  13 |     className={cn(
  14 |       "grid place-content-center peer h-4 w-4 shrink-0 rounded-sm border border-primary shadow focus-
visible:outline-none focus-visible:ring-1 focus-visible:...
  15 |       className
  16 |     )}
  17 |     {...props}
  18 |   >
  19 |     <CheckboxPrimitive.Indicator
  20 |       className={cn("grid place-content-center text-current")}
  21 |     >
  22 |       <Check className="h-4 w-4" />
  23 |     </CheckboxPrimitive.Indicator>
  24 |   </CheckboxPrimitive.Root>
  25 | ))
  26 | Checkbox.displayName = CheckboxPrimitive.Root.displayName
  27 |
  28 | export { Checkbox }
  29 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/collapsible.tsx

```
"use client"

import * as CollapsiblePrimitive from "@radix-ui/react-collapsible"

const Collapsible = CollapsiblePrimitive.Root

const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger

const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent

export { Collapsible, CollapsibleTrigger, CollapsibleContent }

```

— end of file —

File: artifacts/mbc-platform/src/components/ui/command.tsx

```
   1 | "use client"
   2 |
   3 | import * as React from "react"
   4 | import { type DialogProps } from "@radix-ui/react-dialog"
   5 | import { Command as CommandPrimitive } from "cmdk"
   6 | import { Search } from "lucide-react"
   7 |
   8 | import { cn } from "@/lib/utils"
   9 | import { Dialog, DialogContent } from "@/components/ui/dialog"
  10 |
  11 | const Command = React.forwardRef<
  12 |   React.ElementRef<typeof CommandPrimitive>,
  13 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive>
  14 | >(({ className, ...props }, ref) => (
  15 |   <CommandPrimitive
  16 |     ref={ref}
  17 |     className={cn(
  18 |       "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
  19 |       className
  20 |     )}
  21 |     {...props}
  22 |   />
  23 | ))
  24 | Command.displayName = CommandPrimitive.displayName
  25 |
  26 | const CommandDialog = ({ children, ...props }: DialogProps) => {
  27 |   return (
  28 |     <Dialog {...props}>
  29 |       <DialogContent className="overflow-hidden p-0">
  30 |         <Command className="[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-
heading]]:text-muted-foreground [&_[cmdk-group]...
  31 |           {children}
  32 |         </Command>
  33 |       </DialogContent>
  34 |     </Dialog>
  35 |   )
  36 | }
  37 |
  38 | const CommandInput = React.forwardRef<
  39 |   React.ElementRef<typeof CommandPrimitive.Input>,
  40 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Input>
  41 | >(({ className, ...props }, ref) => (
  42 |   <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
  43 |     <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
  44 |     <CommandPrimitive.Input
  45 |       ref={ref}
  46 |       className={cn(
  47 |         "flex h-10 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-muted-foreground
disabled:cursor-not-allowed disabled:opacity-...
  48 |         className
  49 |       )}
  50 |       {...props}
  51 |     />
  52 |   </div>
  53 | ))
  54 |
  55 | CommandInput.displayName = CommandPrimitive.Input.displayName
  56 |
  57 | const CommandList = React.forwardRef<
  58 |   React.ElementRef<typeof CommandPrimitive.List>,
  59 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.List>
  60 | >(({ className, ...props }, ref) => (
  61 |   <CommandPrimitive.List
  62 |     ref={ref}
  63 |     className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
  64 |     {...props}
  65 |   />
  66 | ))
  67 |
  68 | CommandList.displayName = CommandPrimitive.List.displayName
  69 |
  70 | const CommandEmpty = React.forwardRef<
  71 |   React.ElementRef<typeof CommandPrimitive.Empty>,
  72 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Empty>
  73 | >((props, ref) => (
  74 |   <CommandPrimitive.Empty
  75 |     ref={ref}
  76 |     className="py-6 text-center text-sm"
  77 |     {...props}
  78 |   />
  79 | ))
  80 |
  81 | CommandEmpty.displayName = CommandPrimitive.Empty.displayName
  82 |
  83 | const CommandGroup = React.forwardRef<
  84 |   React.ElementRef<typeof CommandPrimitive.Group>,
  85 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Group>
  86 | >(({ className, ...props }, ref) => (
  87 |   <CommandPrimitive.Group
  88 |     ref={ref}
  89 |     className={cn(
  90 |       "overflow-hidden p-1 text-foreground [&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:py-1.5 [&_[cmdk-
group-heading]]:text-xs [&_[cmdk-group-head...
  91 |       className
  92 |     )}
  93 |     {...props}
  94 |   />
  95 | ))
  96 |
  97 | CommandGroup.displayName = CommandPrimitive.Group.displayName
```

```
 98 |
 99 | const CommandSeparator = React.forwardRef<
100 |   React.ElementRef<typeof CommandPrimitive.Separator>,
101 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Separator>
102 | >(({ className, ...props }, ref) => (
103 |   <CommandPrimitive.Separator
104 |     ref={ref}
105 |     className={cn("-mx-1 h-px bg-border", className)}
106 |     {...props}
107 |   />
108 | ))
109 | CommandSeparator.displayName = CommandPrimitive.Separator.displayName
110 |
111 | const CommandItem = React.forwardRef<
112 |   React.ElementRef<typeof CommandPrimitive.Item>,
113 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Item>
114 | >(({ className, ...props }, ref) => (
115 |   <CommandPrimitive.Item
116 |     ref={ref}
117 |     className={cn(
118 |       "relative flex cursor-default gap-2 select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none
data-[disabled=true]:pointer-events-none data-...
119 |       className
120 |     )}
121 |     {...props}
122 |   />
123 | ))
124 |
125 | CommandItem.displayName = CommandPrimitive.Item.displayName
126 |
127 | const CommandShortcut = ({
128 |   className,
129 |   ...props
130 | }: React.HTMLAttributes<HTMLSpanElement>) => {
131 |   return (
132 |     <span
133 |       className={cn(
134 |         "ml-auto text-xs tracking-widest text-muted-foreground",
135 |         className
136 |       )}
137 |       {...props}
138 |     />
139 |   )
140 | }
141 | CommandShortcut.displayName = "CommandShortcut"
142 |
143 | export {
144 |   Command,
145 |   CommandDialog,
146 |   CommandInput,
147 |   CommandList,
148 |   CommandEmpty,
149 |   CommandGroup,
150 |   CommandItem,
151 |   CommandShortcut,
152 |   CommandSeparator,
153 | }
154 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/context-menu.tsx

```
   1 | import * as React from "react"
   2 | import * as ContextMenuPrimitive from "@radix-ui/react-context-menu"
   3 | import { Check, ChevronRight, Circle } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const ContextMenu = ContextMenuPrimitive.Root
   8 |
   9 | const ContextMenuTrigger = ContextMenuPrimitive.Trigger
  10 |
  11 | const ContextMenuGroup = ContextMenuPrimitive.Group
  12 |
  13 | const ContextMenuPortal = ContextMenuPrimitive.Portal
  14 |
  15 | const ContextMenuSub = ContextMenuPrimitive.Sub
  16 |
  17 | const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup
  18 |
  19 | const ContextMenuSubTrigger = React.forwardRef<
  20 |   React.ElementRef<typeof ContextMenuPrimitive.SubTrigger>,
  21 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubTrigger> & {
  22 |     inset?: boolean
  23 |   }
  24 | >(({ className, inset, children, ...props }, ref) => (
  25 |   <ContextMenuPrimitive.SubTrigger
  26 |     ref={ref}
  27 |     className={cn(
  28 |       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[state=open...
  29 |       inset && "pl-8",
  30 |       className
  31 |     )}
  32 |     {...props}
  33 |   >
  34 |     {children}
  35 |     <ChevronRight className="ml-auto h-4 w-4" />
  36 |   </ContextMenuPrimitive.SubTrigger>
  37 | ))
  38 | ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName
  39 |
  40 | const ContextMenuSubContent = React.forwardRef<
  41 |   React.ElementRef<typeof ContextMenuPrimitive.SubContent>,
  42 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubContent>
  43 | >(({ className, ...props }, ref) => (
  44 |   <ContextMenuPrimitive.SubContent
  45 |     ref={ref}
  46 |     className={cn(
  47 |       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data-
[state=open]:animate-in data-[state=closed]:...
  48 |       className
  49 |     )}
  50 |     {...props}
  51 |   />
  52 | ))
  53 | ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName
  54 |
  55 | const ContextMenuContent = React.forwardRef<
  56 |   React.ElementRef<typeof ContextMenuPrimitive.Content>,
  57 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Content>
  58 | >(({ className, ...props }, ref) => (
  59 |   <ContextMenuPrimitive.Portal>
  60 |     <ContextMenuPrimitive.Content
  61 |       ref={ref}
  62 |       className={cn(
  63 |         "z-50 max-h-[--radix-context-menu-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-hidden
rounded-md border bg-popover p-1 text-popo...
  64 |         className
  65 |       )}
  66 |       {...props}
  67 |     />
  68 |   </ContextMenuPrimitive.Portal>
  69 | ))
  70 | ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName
  71 |
  72 | const ContextMenuItem = React.forwardRef<
  73 |   React.ElementRef<typeof ContextMenuPrimitive.Item>,
  74 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Item> & {
  75 |     inset?: boolean
  76 |   }
  77 | >(({ className, inset, ...props }, ref) => (
  78 |   <ContextMenuPrimitive.Item
  79 |     ref={ref}
  80 |     className={cn(
  81 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-
accent focus:text-accent-foreground data-[d...
  82 |       inset && "pl-8",
  83 |       className
  84 |     )}
  85 |     {...props}
  86 |   />
  87 | ))
  88 | ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName
  89 |
  90 | const ContextMenuCheckboxItem = React.forwardRef<
  91 |   React.ElementRef<typeof ContextMenuPrimitive.CheckboxItem>,
  92 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.CheckboxItem>
  93 | >(({ className, children, checked, ...props }, ref) => (
  94 |   <ContextMenuPrimitive.CheckboxItem
  95 |     ref={ref}
  96 |     className={cn(
```

```
  97 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
focus:bg-accent focus:text-accent-foreground da...
  98 |       className
  99 |     )}
 100 |     checked={checked}
 101 |     {...props}
 102 |   >
 103 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 104 |       <ContextMenuPrimitive.ItemIndicator>
 105 |         <Check className="h-4 w-4" />
 106 |       </ContextMenuPrimitive.ItemIndicator>
 107 |     </span>
 108 |     {children}
 109 |   </ContextMenuPrimitive.CheckboxItem>
 110 | ))
 111 | ContextMenuCheckboxItem.displayName =
 112 |   ContextMenuPrimitive.CheckboxItem.displayName
 113 |
 114 | const ContextMenuRadioItem = React.forwardRef<
 115 |   React.ElementRef<typeof ContextMenuPrimitive.RadioItem>,
 116 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.RadioItem>
 117 | >(({ className, children, ...props }, ref) => (
 118 |   <ContextMenuPrimitive.RadioItem
 119 |     ref={ref}
 120 |     className={cn(
 121 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
focus:bg-accent focus:text-accent-foreground da...
 122 |       className
 123 |     )}
 124 |     {...props}
 125 |   >
 126 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 127 |       <ContextMenuPrimitive.ItemIndicator>
 128 |         <Circle className="h-4 w-4 fill-current" />
 129 |       </ContextMenuPrimitive.ItemIndicator>
 130 |     </span>
 131 |     {children}
 132 |   </ContextMenuPrimitive.RadioItem>
 133 | ))
 134 | ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName
 135 |
 136 | const ContextMenuLabel = React.forwardRef<
 137 |   React.ElementRef<typeof ContextMenuPrimitive.Label>,
 138 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Label> & {
 139 |     inset?: boolean
 140 |   }
 141 | >(({ className, inset, ...props }, ref) => (
 142 |   <ContextMenuPrimitive.Label
 143 |     ref={ref}
 144 |     className={cn(
 145 |       "px-2 py-1.5 text-sm font-semibold text-foreground",
 146 |       inset && "pl-8",
 147 |       className
 148 |     )}
 149 |     {...props}
 150 |   />
 151 | ))
 152 | ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName
 153 |
 154 | const ContextMenuSeparator = React.forwardRef<
 155 |   React.ElementRef<typeof ContextMenuPrimitive.Separator>,
 156 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Separator>
 157 | >(({ className, ...props }, ref) => (
 158 |   <ContextMenuPrimitive.Separator
 159 |     ref={ref}
 160 |     className={cn("-mx-1 my-1 h-px bg-border", className)}
 161 |     {...props}
 162 |   />
 163 | ))
 164 | ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName
 165 |
 166 | const ContextMenuShortcut = ({
 167 |   className,
 168 |   ...props
 169 | }: React.HTMLAttributes<HTMLSpanElement>) => {
 170 |   return (
 171 |     <span
 172 |       className={cn(
 173 |         "ml-auto text-xs tracking-widest text-muted-foreground",
 174 |         className
 175 |       )}
 176 |       {...props}
 177 |     />
 178 |   )
 179 | }
 180 | ContextMenuShortcut.displayName = "ContextMenuShortcut"
 181 |
 182 | export {
 183 |   ContextMenu,
 184 |   ContextMenuTrigger,
 185 |   ContextMenuContent,
 186 |   ContextMenuItem,
 187 |   ContextMenuCheckboxItem,
 188 |   ContextMenuRadioItem,
 189 |   ContextMenuLabel,
 190 |   ContextMenuSeparator,
 191 |   ContextMenuShortcut,
 192 |   ContextMenuGroup,
 193 |   ContextMenuPortal,
 194 |   ContextMenuSub,
 195 |   ContextMenuSubContent,
 196 |   ContextMenuSubTrigger,
 197 |   ContextMenuRadioGroup,
```

```
198 | }
199 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/dialog.tsx

```
   1 | import * as React from "react"
   2 | import * as DialogPrimitive from "@radix-ui/react-dialog"
   3 | import { X } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const Dialog = DialogPrimitive.Root
   8 |
   9 | const DialogTrigger = DialogPrimitive.Trigger
  10 |
  11 | const DialogPortal = DialogPrimitive.Portal
  12 |
  13 | const DialogClose = DialogPrimitive.Close
  14 |
  15 | const DialogOverlay = React.forwardRef<
  16 |   React.ElementRef<typeof DialogPrimitive.Overlay>,
  17 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
  18 | >(({ className, ...props }, ref) => (
  19 |   <DialogPrimitive.Overlay
  20 |     ref={ref}
  21 |     className={cn(
  22 |       "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
  23 |       className
  24 |     )}
  25 |     {...props}
  26 |   />
  27 | ))
  28 | DialogOverlay.displayName = DialogPrimitive.Overlay.displayName
  29 |
  30 | const DialogContent = React.forwardRef<
  31 |   React.ElementRef<typeof DialogPrimitive.Content>,
  32 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
  33 | >(({ className, children, ...props }, ref) => (
  34 |   <DialogPortal>
  35 |     <DialogOverlay />
  36 |     <DialogPrimitive.Content
  37 |       ref={ref}
  38 |       className={cn(
  39 |         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
bg-background p-6 shadow-lg duration-200 dat...
  40 |         className
  41 |       )}
  42 |       {...props}
  43 |     >
  44 |       {children}
  45 |       <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background
transition-opacity hover:opacity-100 focus:outlin...
  46 |         <X className="h-4 w-4" />
  47 |         <span className="sr-only">Close</span>
  48 |       </DialogPrimitive.Close>
  49 |     </DialogPrimitive.Content>
  50 |   </DialogPortal>
  51 | ))
  52 | DialogContent.displayName = DialogPrimitive.Content.displayName
  53 |
  54 | const DialogHeader = ({
  55 |   className,
  56 |   ...props
  57 | }: React.HTMLAttributes<HTMLDivElement>) => (
  58 |   <div
  59 |     className={cn(
  60 |       "flex flex-col space-y-1.5 text-center sm:text-left",
  61 |       className
  62 |     )}
  63 |     {...props}
  64 |   />
  65 | )
  66 | DialogHeader.displayName = "DialogHeader"
  67 |
  68 | const DialogFooter = ({
  69 |   className,
  70 |   ...props
  71 | }: React.HTMLAttributes<HTMLDivElement>) => (
  72 |   <div
  73 |     className={cn(
  74 |       "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
  75 |       className
  76 |     )}
  77 |     {...props}
  78 |   />
  79 | )
  80 | DialogFooter.displayName = "DialogFooter"
  81 |
  82 | const DialogTitle = React.forwardRef<
  83 |   React.ElementRef<typeof DialogPrimitive.Title>,
  84 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
  85 | >(({ className, ...props }, ref) => (
  86 |   <DialogPrimitive.Title
  87 |     ref={ref}
  88 |     className={cn(
  89 |       "text-lg font-semibold leading-none tracking-tight",
  90 |       className
  91 |     )}
  92 |     {...props}
  93 |   />
  94 | ))
  95 | DialogTitle.displayName = DialogPrimitive.Title.displayName
  96 |
  97 | const DialogDescription = React.forwardRef<
```

```
 98 |   React.ElementRef<typeof DialogPrimitive.Description>,
 99 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
100 | >(({ className, ...props }, ref) => (
101 |   <DialogPrimitive.Description
102 |     ref={ref}
103 |     className={cn("text-sm text-muted-foreground", className)}
104 |     {...props}
105 |   />
106 | ))
107 | DialogDescription.displayName = DialogPrimitive.Description.displayName
108 |
109 | export {
110 |   Dialog,
111 |   DialogPortal,
112 |   DialogOverlay,
113 |   DialogTrigger,
114 |   DialogClose,
115 |   DialogContent,
116 |   DialogHeader,
117 |   DialogFooter,
118 |   DialogTitle,
119 |   DialogDescription,
120 | }
121 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/drawer.tsx

```
  1 | import * as React from "react"
  2 | import { Drawer as DrawerPrimitive } from "vaul"
  3 |
  4 | import { cn } from "@/lib/utils"
  5 |
  6 | const Drawer = ({
  7 |   shouldScaleBackground = true,
  8 |   ...props
  9 | }: React.ComponentProps<typeof DrawerPrimitive.Root>) => (
 10 |   <DrawerPrimitive.Root
 11 |     shouldScaleBackground={shouldScaleBackground}
 12 |     {...props}
 13 |   />
 14 | )
 15 | Drawer.displayName = "Drawer"
 16 |
 17 | const DrawerTrigger = DrawerPrimitive.Trigger
 18 |
 19 | const DrawerPortal = DrawerPrimitive.Portal
 20 |
 21 | const DrawerClose = DrawerPrimitive.Close
 22 |
 23 | const DrawerOverlay = React.forwardRef<
 24 |   React.ElementRef<typeof DrawerPrimitive.Overlay>,
 25 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>
 26 | >(({ className, ...props }, ref) => (
 27 |   <DrawerPrimitive.Overlay
 28 |     ref={ref}
 29 |     className={cn("fixed inset-0 z-50 bg-black/80", className)}
 30 |     {...props}
 31 |   />
 32 | ))
 33 | DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName
 34 |
 35 | const DrawerContent = React.forwardRef<
 36 |   React.ElementRef<typeof DrawerPrimitive.Content>,
 37 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>
 38 | >(({ className, children, ...props }, ref) => (
 39 |   <DrawerPortal>
 40 |     <DrawerOverlay />
 41 |     <DrawerPrimitive.Content
 42 |       ref={ref}
 43 |       className={cn(
 44 |         "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-background",
 45 |         className
 46 |       )}
 47 |       {...props}
 48 |     >
 49 |       <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
 50 |       {children}
 51 |     </DrawerPrimitive.Content>
 52 |   </DrawerPortal>
 53 | ))
 54 | DrawerContent.displayName = "DrawerContent"
 55 |
 56 | const DrawerHeader = ({
 57 |   className,
 58 |   ...props
 59 | }: React.HTMLAttributes<HTMLDivElement>) => (
 60 |   <div
 61 |     className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)}
 62 |     {...props}
 63 |   />
 64 | )
 65 | DrawerHeader.displayName = "DrawerHeader"
 66 |
 67 | const DrawerFooter = ({
 68 |   className,
 69 |   ...props
 70 | }: React.HTMLAttributes<HTMLDivElement>) => (
 71 |   <div
 72 |     className={cn("mt-auto flex flex-col gap-2 p-4", className)}
 73 |     {...props}
 74 |   />
 75 | )
 76 | DrawerFooter.displayName = "DrawerFooter"
 77 |
 78 | const DrawerTitle = React.forwardRef<
 79 |   React.ElementRef<typeof DrawerPrimitive.Title>,
 80 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
 81 | >(({ className, ...props }, ref) => (
 82 |   <DrawerPrimitive.Title
 83 |     ref={ref}
 84 |     className={cn(
 85 |       "text-lg font-semibold leading-none tracking-tight",
 86 |       className
 87 |     )}
 88 |     {...props}
 89 |   />
 90 | ))
 91 | DrawerTitle.displayName = DrawerPrimitive.Title.displayName
 92 |
 93 | const DrawerDescription = React.forwardRef<
 94 |   React.ElementRef<typeof DrawerPrimitive.Description>,
 95 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
 96 | >(({ className, ...props }, ref) => (
 97 |   <DrawerPrimitive.Description
 98 |     ref={ref}
 99 |     className={cn("text-sm text-muted-foreground", className)}
100 |     {...props}
```

```
101 |   />
102 | ))
103 | DrawerDescription.displayName = DrawerPrimitive.Description.displayName
104 |
105 | export {
106 |   Drawer,
107 |   DrawerPortal,
108 |   DrawerOverlay,
109 |   DrawerTrigger,
110 |   DrawerClose,
111 |   DrawerContent,
112 |   DrawerHeader,
113 |   DrawerFooter,
114 |   DrawerTitle,
115 |   DrawerDescription,
116 | }
117 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/dropdown-menu.tsx

```
"use client"

import * as React from "react"
import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const DropdownMenu = DropdownMenuPrimitive.Root

const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger

const DropdownMenuGroup = DropdownMenuPrimitive.Group

const DropdownMenuPortal = DropdownMenuPrimitive.Portal

const DropdownMenuSub = DropdownMenuPrimitive.Sub

const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup

const DropdownMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent data-[state=open]:bg-accent [&_svg]:poi...
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto" />
  </DropdownMenuPrimitive.SubTrigger>
))
DropdownMenuSubTrigger.displayName =
  DropdownMenuPrimitive.SubTrigger.displayName

const DropdownMenuSubContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data-[state=open]:animate-in data-[state=closed]:...
      className
    )}
    {...props}
  />
))
DropdownMenuSubContent.displayName =
  DropdownMenuPrimitive.SubContent.displayName

const DropdownMenuContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <DropdownMenuPrimitive.Portal>
    <DropdownMenuPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 max-h-[var(--radix-dropdown-menu-content-available-height)] min-w-[8rem] overflow-y-auto overflow-x-hidden rounded-md border bg-popover p-1 tex...
        "data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out...
        className
      )}
      {...props}
    />
  </DropdownMenuPrimitive.Portal>
))
DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName

const DropdownMenuItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none transition-colors focus:bg-accent focus:text-a...
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName

```

```
  96 | const DropdownMenuCheckboxItem = React.forwardRef<
  97 |   React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
  98 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
  99 | >(({ className, children, checked, ...props }, ref) => (
 100 |   <DropdownMenuPrimitive.CheckboxItem
 101 |     ref={ref}
 102 |     className={cn(
 103 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
transition-colors focus:bg-accent focus:text-ac...
 104 |       className
 105 |     )}
 106 |     checked={checked}
 107 |     {...props}
 108 |   >
 109 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 110 |       <DropdownMenuPrimitive.ItemIndicator>
 111 |         <Check className="h-4 w-4" />
 112 |       </DropdownMenuPrimitive.ItemIndicator>
 113 |     </span>
 114 |     {children}
 115 |   </DropdownMenuPrimitive.CheckboxItem>
 116 | ))
 117 | DropdownMenuCheckboxItem.displayName =
 118 |   DropdownMenuPrimitive.CheckboxItem.displayName
 119 |
 120 | const DropdownMenuRadioItem = React.forwardRef<
 121 |   React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
 122 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
 123 | >(({ className, children, ...props }, ref) => (
 124 |   <DropdownMenuPrimitive.RadioItem
 125 |     ref={ref}
 126 |     className={cn(
 127 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
transition-colors focus:bg-accent focus:text-ac...
 128 |       className
 129 |     )}
 130 |     {...props}
 131 |   >
 132 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 133 |       <DropdownMenuPrimitive.ItemIndicator>
 134 |         <Circle className="h-2 w-2 fill-current" />
 135 |       </DropdownMenuPrimitive.ItemIndicator>
 136 |     </span>
 137 |     {children}
 138 |   </DropdownMenuPrimitive.RadioItem>
 139 | ))
 140 | DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName
 141 |
 142 | const DropdownMenuLabel = React.forwardRef<
 143 |   React.ElementRef<typeof DropdownMenuPrimitive.Label>,
 144 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {
 145 |     inset?: boolean
 146 |   }
 147 | >(({ className, inset, ...props }, ref) => (
 148 |   <DropdownMenuPrimitive.Label
 149 |     ref={ref}
 150 |     className={cn(
 151 |       "px-2 py-1.5 text-sm font-semibold",
 152 |       inset && "pl-8",
 153 |       className
 154 |     )}
 155 |     {...props}
 156 |   />
 157 | ))
 158 | DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName
 159 |
 160 | const DropdownMenuSeparator = React.forwardRef<
 161 |   React.ElementRef<typeof DropdownMenuPrimitive.Separator>,
 162 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>
 163 | >(({ className, ...props }, ref) => (
 164 |   <DropdownMenuPrimitive.Separator
 165 |     ref={ref}
 166 |     className={cn("-mx-1 my-1 h-px bg-muted", className)}
 167 |     {...props}
 168 |   />
 169 | ))
 170 | DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName
 171 |
 172 | const DropdownMenuShortcut = ({
 173 |   className,
 174 |   ...props
 175 | }: React.HTMLAttributes<HTMLSpanElement>) => {
 176 |   return (
 177 |     <span
 178 |       className={cn("ml-auto text-xs tracking-widest opacity-60", className)}
 179 |       {...props}
 180 |     />
 181 |   )
 182 | }
 183 | DropdownMenuShortcut.displayName = "DropdownMenuShortcut"
 184 |
 185 | export {
 186 |   DropdownMenu,
 187 |   DropdownMenuTrigger,
 188 |   DropdownMenuContent,
 189 |   DropdownMenuItem,
 190 |   DropdownMenuCheckboxItem,
 191 |   DropdownMenuRadioItem,
 192 |   DropdownMenuLabel,
 193 |   DropdownMenuSeparator,
 194 |   DropdownMenuShortcut,
 195 |   DropdownMenuGroup,
 196 |   DropdownMenuPortal,
```

```
197 |   DropdownMenuSub,
198 |   DropdownMenuSubContent,
199 |   DropdownMenuSubTrigger,
200 |   DropdownMenuRadioGroup,
201 | }
202 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/empty.tsx

```
   1 | import { cva, type VariantProps } from "class-variance-authority"
   2 |
   3 | import { cn } from "@/lib/utils"
   4 |
   5 | function Empty({ className, ...props }: React.ComponentProps<"div">) {
   6 |   return (
   7 |     <div
   8 |       data-slot="empty"
   9 |       className={cn(
  10 |         "flex min-w-0 flex-1 flex-col items-center justify-center gap-6 text-balance rounded-lg border-dashed p-6
text-center md:p-12",
  11 |         className
  12 |       )}
  13 |       {...props}
  14 |     />
  15 |   )
  16 | }
  17 |
  18 | function EmptyHeader({ className, ...props }: React.ComponentProps<"div">) {
  19 |   return (
  20 |     <div
  21 |       data-slot="empty-header"
  22 |       className={cn(
  23 |         "flex max-w-sm flex-col items-center gap-2 text-center",
  24 |         className
  25 |       )}
  26 |       {...props}
  27 |     />
  28 |   )
  29 | }
  30 |
  31 | const emptyMediaVariants = cva(
  32 |   "mb-2 flex shrink-0 items-center justify-center [&_svg]:pointer-events-none [&_svg]:shrink-0",
  33 |   {
  34 |     variants: {
  35 |       variant: {
  36 |         default: "bg-transparent",
  37 |         icon: "bg-muted text-foreground flex size-10 shrink-0 items-center justify-center rounded-lg
[&_svg:not([class*='size-'])]:size-6",
  38 |       },
  39 |     },
  40 |     defaultVariants: {
  41 |       variant: "default",
  42 |     },
  43 |   }
  44 | )
  45 |
  46 | function EmptyMedia({
  47 |   className,
  48 |   variant = "default",
  49 |   ...props
  50 | }: React.ComponentProps<"div"> & VariantProps<typeof emptyMediaVariants>) {
  51 |   return (
  52 |     <div
  53 |       data-slot="empty-icon"
  54 |       data-variant={variant}
  55 |       className={cn(emptyMediaVariants({ variant, className }))}
  56 |       {...props}
  57 |     />
  58 |   )
  59 | }
  60 |
  61 | function EmptyTitle({ className, ...props }: React.ComponentProps<"div">) {
  62 |   return (
  63 |     <div
  64 |       data-slot="empty-title"
  65 |       className={cn("text-lg font-medium tracking-tight", className)}
  66 |       {...props}
  67 |     />
  68 |   )
  69 | }
  70 |
  71 | function EmptyDescription({ className, ...props }: React.ComponentProps<"p">) {
  72 |   return (
  73 |     <div
  74 |       data-slot="empty-description"
  75 |       className={cn(
  76 |         "text-muted-foreground [&>a:hover]:text-primary text-sm/relaxed [&>a]:underline [&>a]:underline-offset-4",
  77 |         className
  78 |       )}
  79 |       {...props}
  80 |     />
  81 |   )
  82 | }
  83 |
  84 | function EmptyContent({ className, ...props }: React.ComponentProps<"div">) {
  85 |   return (
  86 |     <div
  87 |       data-slot="empty-content"
  88 |       className={cn(
  89 |         "flex w-full min-w-0 max-w-sm flex-col items-center gap-4 text-balance text-sm",
  90 |         className
  91 |       )}
  92 |       {...props}
  93 |     />
  94 |   )
  95 | }
  96 |
  97 | export {
  98 |   Empty,
```

```
 99 |   EmptyHeader,
100 |   EmptyTitle,
101 |   EmptyDescription,
102 |   EmptyContent,
103 |   EmptyMedia,
104 | }
105 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/field.tsx

```
   1 | "use client"
   2 |
   3 | import { useMemo } from "react"
   4 | import { cva, type VariantProps } from "class-variance-authority"
   5 |
   6 | import { cn } from "@/lib/utils"
   7 | import { Label } from "@/components/ui/label"
   8 | import { Separator } from "@/components/ui/separator"
   9 |
  10 | function FieldSet({ className, ...props }: React.ComponentProps<"fieldset">) {
  11 |   return (
  12 |     <fieldset
  13 |       data-slot="field-set"
  14 |       className={cn(
  15 |         "flex flex-col gap-6",
  16 |         "has-[>[data-slot=checkbox-group]]:gap-3 has-[>[data-slot=radio-group]]:gap-3",
  17 |         className
  18 |       )}
  19 |       {...props}
  20 |     />
  21 |   )
  22 | }
  23 |
  24 | function FieldLegend({
  25 |   className,
  26 |   variant = "legend",
  27 |   ...props
  28 | }: React.ComponentProps<"legend"> & { variant?: "legend" | "label" }) {
  29 |   return (
  30 |     <legend
  31 |       data-slot="field-legend"
  32 |       data-variant={variant}
  33 |       className={cn(
  34 |         "mb-3 font-medium",
  35 |         "data-[variant=legend]:text-base",
  36 |         "data-[variant=label]:text-sm",
  37 |         className
  38 |       )}
  39 |       {...props}
  40 |     />
  41 |   )
  42 | }
  43 |
  44 | function FieldGroup({ className, ...props }: React.ComponentProps<"div">) {
  45 |   return (
  46 |     <div
  47 |       data-slot="field-group"
  48 |       className={cn(
  49 |         "group/field-group @container/field-group flex w-full flex-col gap-7 data-[slot=checkbox-group]:gap-3
[&>[data-slot=field-group]]:gap-4",
  50 |         className
  51 |       )}
  52 |       {...props}
  53 |     />
  54 |   )
  55 | }
  56 |
  57 | const fieldVariants = cva(
  58 |   "group/field data-[invalid=true]:text-destructive flex w-full gap-3",
  59 |   {
  60 |     variants: {
  61 |       orientation: {
  62 |         vertical: ["flex-col [&>*]:w-full [&>.sr-only]:w-auto"],
  63 |         horizontal: [
  64 |           "flex-row items-center",
  65 |           "[&>[data-slot=field-label]]:flex-auto",
  66 |           "has-[>[data-slot=field-content]]:[&>[role=checkbox],[role=radio]]:mt-px has-[>[data-slot=field-
content]]:items-start",
  67 |         ],
  68 |         responsive: [
  69 |           "@md/field-group:flex-row @md/field-group:items-center @md/field-group:[&>*]:w-auto flex-col [&>*]:w-
full [&>.sr-only]:w-auto",
  70 |           "@md/field-group:[&>[data-slot=field-label]]:flex-auto",
  71 |           "@md/field-group:has-[>[data-slot=field-content]]:items-start @md/field-group:has-[>[data-slot=field-
content]]:[&>[role=checkbox],[role=radio]]:mt-...
  72 |         ],
  73 |       },
  74 |     },
  75 |     defaultVariants: {
  76 |       orientation: "vertical",
  77 |     },
  78 |   }
  79 | )
  80 |
  81 | function Field({
  82 |   className,
  83 |   orientation = "vertical",
  84 |   ...props
  85 | }: React.ComponentProps<"div"> & VariantProps<typeof fieldVariants>) {
  86 |   return (
  87 |     <div
  88 |       role="group"
  89 |       data-slot="field"
  90 |       data-orientation={orientation}
  91 |       className={cn(fieldVariants({ orientation }), className)}
  92 |       {...props}
  93 |     />
  94 |   )
  95 | }
  96 |
```

```
 97 | function FieldContent({ className, ...props }: React.ComponentProps<"div">) {
 98 |   return (
 99 |     <div
100 |       data-slot="field-content"
101 |       className={cn(
102 |         "group/field-content flex flex-1 flex-col gap-1.5 leading-snug",
103 |         className
104 |       )}
105 |       {...props}
106 |     />
107 |   )
108 | }
109 |
110 | function FieldLabel({
111 |   className,
112 |   ...props
113 | }: React.ComponentProps<typeof Label>) {
114 |   return (
115 |     <Label
116 |       data-slot="field-label"
117 |       className={cn(
118 |         "group/field-label peer/field-label flex w-fit gap-2 leading-snug group-data-[disabled=true]/
field:opacity-50",
119 |         "has-[>[data-slot=field]]:w-full has-[>[data-slot=field]]:flex-col has-[>[data-slot=field]]:rounded-md has-
[>[data-slot=field]]:border [&>[data-slot=...
120 |         "has-data-[state=checked]:bg-primary/5 has-data-[state=checked]:border-primary dark:has-data-
[state=checked]:bg-primary/10",
121 |         className
122 |       )}
123 |       {...props}
124 |     />
125 |   )
126 | }
127 |
128 | function FieldTitle({ className, ...props }: React.ComponentProps<"div">) {
129 |   return (
130 |     <div
131 |       data-slot="field-label"
132 |       className={cn(
133 |         "flex w-fit items-center gap-2 text-sm font-medium leading-snug group-data-[disabled=true]/
field:opacity-50",
134 |         className
135 |       )}
136 |       {...props}
137 |     />
138 |   )
139 | }
140 |
141 | function FieldDescription({ className, ...props }: React.ComponentProps<"p">) {
142 |   return (
143 |     <p
144 |       data-slot="field-description"
145 |       className={cn(
146 |         "text-muted-foreground text-sm font-normal leading-normal group-has-[[data-orientation=horizontal]]/
field:text-balance",
147 |         "nth-last-2:-mt-1 last:mt-0 [[data-variant=legend]+&]:-mt-1.5",
148 |         "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
149 |         className
150 |       )}
151 |       {...props}
152 |     />
153 |   )
154 | }
155 |
156 | function FieldSeparator({
157 |   children,
158 |   className,
159 |   ...props
160 | }: React.ComponentProps<"div"> & {
161 |   children?: React.ReactNode
162 | }) {
163 |   return (
164 |     <div
165 |       data-slot="field-separator"
166 |       data-content={!!children}
167 |       className={cn(
168 |         "relative -my-2 h-5 text-sm group-data-[variant=outline]/field-group:-mb-2",
169 |         className
170 |       )}
171 |       {...props}
172 |     >
173 |       <Separator className="absolute inset-0 top-1/2" />
174 |       {children && (
175 |         <span
176 |           className="bg-background text-muted-foreground relative mx-auto block w-fit px-2"
177 |           data-slot="field-separator-content"
178 |         >
179 |           {children}
180 |         </span>
181 |       )}
182 |     </div>
183 |   )
184 | }
185 |
186 | function FieldError({
187 |   className,
188 |   children,
189 |   errors,
190 |   ...props
191 | }: React.ComponentProps<"div"> & {
192 |   errors?: Array<{ message?: string } | undefined>
193 | }) {
194 |   const content = useMemo(() => {
```

```
195 |     if (children) {
196 |       return children
197 |     }
198 |
199 |     if (!errors) {
200 |       return null
201 |     }
202 |
203 |     if (errors?.length === 1 && errors[0]?.message) {
204 |       return errors[0].message
205 |     }
206 |
207 |     return (
208 |       <ul className="ml-4 flex list-disc flex-col gap-1">
209 |         {errors.map(
210 |           (error, index) =>
211 |             error?.message && <li key={index}>{error.message}</li>
212 |         )}
213 |       </ul>
214 |     )
215 |   }, [children, errors])
216 |
217 |   if (!content) {
218 |     return null
219 |   }
220 |
221 |   return (
222 |     <div
223 |       role="alert"
224 |       data-slot="field-error"
225 |       className={cn("text-destructive text-sm font-normal", className)}
226 |       {...props}
227 |     >
228 |       {content}
229 |     </div>
230 |   )
231 | }
232 |
233 | export {
234 |   Field,
235 |   FieldLabel,
236 |   FieldDescription,
237 |   FieldError,
238 |   FieldGroup,
239 |   FieldLegend,
240 |   FieldSeparator,
241 |   FieldSet,
242 |   FieldContent,
243 |   FieldTitle,
244 | }
245 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/form.tsx

```
  1 | import * as React from "react"
  2 | import * as LabelPrimitive from "@radix-ui/react-label"
  3 | import { Slot } from "@radix-ui/react-slot"
  4 | import {
  5 |   Controller,
  6 |   FormProvider,
  7 |   useFormContext,
  8 |   type ControllerProps,
  9 |   type FieldPath,
 10 |   type FieldValues,
 11 | } from "react-hook-form"
 12 |
 13 | import { cn } from "@/lib/utils"
 14 | import { Label } from "@/components/ui/label"
 15 |
 16 | const Form = FormProvider
 17 |
 18 | type FormFieldContextValue<
 19 |   TFieldValues extends FieldValues = FieldValues,
 20 |   TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
 21 | > = {
 22 |   name: TName
 23 | }
 24 |
 25 | const FormFieldContext = React.createContext<FormFieldContextValue | null>(null)
 26 |
 27 | const FormField = <
 28 |   TFieldValues extends FieldValues = FieldValues,
 29 |   TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
 30 | >({
 31 |   ...props
 32 | }: ControllerProps<TFieldValues, TName>) => {
 33 |   return (
 34 |     <FormFieldContext.Provider value={{ name: props.name }}>
 35 |       <Controller {...props} />
 36 |     </FormFieldContext.Provider>
 37 |   )
 38 | }
 39 |
 40 | const useFormField = () => {
 41 |   const fieldContext = React.useContext(FormFieldContext)
 42 |   const itemContext = React.useContext(FormItemContext)
 43 |   const { getFieldState, formState } = useFormContext()
 44 |
 45 |   if (!fieldContext) {
 46 |     throw new Error("useFormField should be used within <FormField>")
 47 |   }
 48 |
 49 |   if (!itemContext) {
 50 |     throw new Error("useFormField should be used within <FormItem>")
 51 |   }
 52 |
 53 |   const fieldState = getFieldState(fieldContext.name, formState)
 54 |
 55 |   const { id } = itemContext
 56 |
 57 |   return {
 58 |     id,
 59 |     name: fieldContext.name,
 60 |     formItemId: `${id}-form-item`,
 61 |     formDescriptionId: `${id}-form-item-description`,
 62 |     formMessageId: `${id}-form-item-message`,
 63 |     ...fieldState,
 64 |   }
 65 | }
 66 |
 67 | type FormItemContextValue = {
 68 |   id: string
 69 | }
 70 |
 71 | const FormItemContext = React.createContext<FormItemContextValue | null>(null)
 72 |
 73 | const FormItem = React.forwardRef<
 74 |   HTMLDivElement,
 75 |   React.HTMLAttributes<HTMLDivElement>
 76 | >(({ className, ...props }, ref) => {
 77 |   const id = React.useId()
 78 |
 79 |   return (
 80 |     <FormItemContext.Provider value={{ id }}>
 81 |       <div ref={ref} className={cn("space-y-2", className)} {...props} />
 82 |     </FormItemContext.Provider>
 83 |   )
 84 | })
 85 | FormItem.displayName = "FormItem"
 86 |
 87 | const FormLabel = React.forwardRef<
 88 |   React.ElementRef<typeof LabelPrimitive.Root>,
 89 |   React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root>
 90 | >(({ className, ...props }, ref) => {
 91 |   const { error, formItemId } = useFormField()
 92 |
 93 |   return (
 94 |     <Label
 95 |       ref={ref}
 96 |       className={cn(error && "text-destructive", className)}
 97 |       htmlFor={formItemId}
 98 |       {...props}
 99 |     />
100 |   )
```

```
101 | })
102 | FormLabel.displayName = "FormLabel"
103 |
104 | const FormControl = React.forwardRef<
105 |   React.ElementRef<typeof Slot>,
106 |   React.ComponentPropsWithoutRef<typeof Slot>
107 | >(({ ...props }, ref) => {
108 |   const { error, formItemId, formDescriptionId, formMessageId } = useFormField()
109 |
110 |   return (
111 |     <Slot
112 |       ref={ref}
113 |       id={formItemId}
114 |       aria-describedby={
115 |         !error
116 |           ? `${formDescriptionId}`
117 |           : `${formDescriptionId} ${formMessageId}`
118 |       }
119 |       aria-invalid={!!error}
120 |       {...props}
121 |     />
122 |   )
123 | })
124 | FormControl.displayName = "FormControl"
125 |
126 | const FormDescription = React.forwardRef<
127 |   HTMLParagraphElement,
128 |   React.HTMLAttributes<HTMLParagraphElement>
129 | >(({ className, ...props }, ref) => {
130 |   const { formDescriptionId } = useFormField()
131 |
132 |   return (
133 |     <p
134 |       ref={ref}
135 |       id={formDescriptionId}
136 |       className={cn("text-[0.8rem] text-muted-foreground", className)}
137 |       {...props}
138 |     />
139 |   )
140 | })
141 | FormDescription.displayName = "FormDescription"
142 |
143 | const FormMessage = React.forwardRef<
144 |   HTMLParagraphElement,
145 |   React.HTMLAttributes<HTMLParagraphElement>
146 | >(({ className, children, ...props }, ref) => {
147 |   const { error, formMessageId } = useFormField()
148 |   const body = error ? String(error?.message ?? "") : children
149 |
150 |   if (!body) {
151 |     return null
152 |   }
153 |
154 |   return (
155 |     <p
156 |       ref={ref}
157 |       id={formMessageId}
158 |       className={cn("text-[0.8rem] font-medium text-destructive", className)}
159 |       {...props}
160 |     >
161 |       {body}
162 |     </p>
163 |   )
164 | })
165 | FormMessage.displayName = "FormMessage"
166 |
167 | export {
168 |   useFormField,
169 |   Form,
170 |   FormItem,
171 |   FormLabel,
172 |   FormControl,
173 |   FormDescription,
174 |   FormMessage,
175 |   FormField,
176 | }
177 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/hover-card.tsx

```
   1 | import * as React from "react"
   2 | import * as HoverCardPrimitive from "@radix-ui/react-hover-card"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const HoverCard = HoverCardPrimitive.Root
   7 |
   8 | const HoverCardTrigger = HoverCardPrimitive.Trigger
   9 |
  10 | const HoverCardContent = React.forwardRef<
  11 |   React.ElementRef<typeof HoverCardPrimitive.Content>,
  12 |   React.ComponentPropsWithoutRef<typeof HoverCardPrimitive.Content>
  13 | >(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  14 |   <HoverCardPrimitive.Content
  15 |     ref={ref}
  16 |     align={align}
  17 |     sideOffset={sideOffset}
  18 |     className={cn(
  19 |       "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-
[state=open]:animate-in data-[state=closed]:animate-out...
  20 |       className
  21 |     )}
  22 |     {...props}
  23 |   />
  24 | ))
  25 | HoverCardContent.displayName = HoverCardPrimitive.Content.displayName
  26 |
  27 | export { HoverCard, HoverCardTrigger, HoverCardContent }
  28 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/input-group.tsx

```
   1 | import * as React from "react"
   2 | import { cva, type VariantProps } from "class-variance-authority"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 | import { Button } from "@/components/ui/button"
   6 | import { Input } from "@/components/ui/input"
   7 | import { Textarea } from "@/components/ui/textarea"
   8 |
   9 | function InputGroup({ className, ...props }: React.ComponentProps<"div">) {
  10 |   return (
  11 |     <div
  12 |       data-slot="input-group"
  13 |       role="group"
  14 |       className={cn(
  15 |         "group/input-group border-input dark:bg-input/30 shadow-xs relative flex w-full items-center rounded-md
border outline-none transition-[color,box-sha...
  16 |         "h-9 has-[>textarea]:h-auto",
  17 |
  18 |         // Variants based on alignment.
  19 |         "has-[>[data-align=inline-start]]:[&>input]:pl-2",
  20 |         "has-[>[data-align=inline-end]]:[&>input]:pr-2",
  21 |         "has-[>[data-align=block-start]]:h-auto has-[>[data-align=block-start]]:flex-col has-[>[data-align=block-
start]]:[&>input]:pb-3",
  22 |         "has-[>[data-align=block-end]]:h-auto has-[>[data-align=block-end]]:flex-col has-[>[data-align=block-end]]:
[&>input]:pt-3",
  23 |
  24 |         // Focus state.
  25 |         "has-[[data-slot=input-group-control]:focus-visible]:ring-ring has-[[data-slot=input-group-control]:focus-
visible]:ring-1",
  26 |
  27 |         // Error state.
  28 |         "has-[[data-slot][aria-invalid=true]]:ring-destructive/20 has-[[data-slot][aria-invalid=true]]:border-
destructive dark:has-[[data-slot][aria-invalid=...
  29 |
  30 |         className
  31 |       )}
  32 |       {...props}
  33 |     />
  34 |   )
  35 | }
  36 |
  37 | const inputGroupAddonVariants = cva(
  38 |   "text-muted-foreground flex h-auto cursor-text select-none items-center justify-center gap-2 py-1.5 text-sm font-
medium group-data-[disabled=true]/input-gr...
  39 |   {
  40 |     variants: {
  41 |       align: {
  42 |         "inline-start":
  43 |           "order-first pl-3 has-[>button]:ml-[-0.45rem] has-[>kbd]:ml-[-0.35rem]",
  44 |         "inline-end":
  45 |           "order-last pr-3 has-[>button]:mr-[-0.4rem] has-[>kbd]:mr-[-0.35rem]",
  46 |         "block-start":
  47 |           "[.border-b]:pb-3 order-first w-full justify-start px-3 pt-3 group-has-[>input]/input-group:pt-2.5",
  48 |         "block-end":
  49 |           "[.border-t]:pt-3 order-last w-full justify-start px-3 pb-3 group-has-[>input]/input-group:pb-2.5",
  50 |       },
  51 |     },
  52 |     defaultVariants: {
  53 |       align: "inline-start",
  54 |     },
  55 |   }
  56 | )
  57 |
  58 | function InputGroupAddon({
  59 |   className,
  60 |   align = "inline-start",
  61 |   ...props
  62 | }: React.ComponentProps<"div"> & VariantProps<typeof inputGroupAddonVariants>) {
  63 |   return (
  64 |     <div
  65 |       role="group"
  66 |       data-slot="input-group-addon"
  67 |       data-align={align}
  68 |       className={cn(inputGroupAddonVariants({ align }), className)}
  69 |       onClick={(e) => {
  70 |         if ((e.target as HTMLElement).closest("button")) {
  71 |           return
  72 |         }
  73 |         e.currentTarget.parentElement?.querySelector("input")?.focus()
  74 |       }}
  75 |       {...props}
  76 |     />
  77 |   )
  78 | }
  79 |
  80 | const inputGroupButtonVariants = cva(
  81 |   "flex items-center gap-2 text-sm shadow-none",
  82 |   {
  83 |     variants: {
  84 |       size: {
  85 |         xs: "h-6 gap-1 rounded-[calc(var(--radius)-5px)] px-2 has-[>svg]:px-2
[&>svg:not([class*='size-'])]:size-3.5",
  86 |         sm: "h-8 gap-1.5 rounded-md px-2.5 has-[>svg]:px-2.5",
  87 |         "icon-xs":
  88 |           "size-6 rounded-[calc(var(--radius)-5px)] p-0 has-[>svg]:p-0",
  89 |         "icon-sm": "size-8 p-0 has-[>svg]:p-0",
  90 |       },
  91 |     },
  92 |     defaultVariants: {
  93 |       size: "xs",
```

```
  94 |     },
  95 |   }
  96 | )
  97 |
  98 | function InputGroupButton({
  99 |   className,
 100 |   type = "button",
 101 |   variant = "ghost",
 102 |   size = "xs",
 103 |   ...props
 104 | }: Omit<React.ComponentProps<typeof Button>, "size"> &
 105 |   VariantProps<typeof inputGroupButtonVariants>) {
 106 |   return (
 107 |     <Button
 108 |       type={type}
 109 |       data-size={size}
 110 |       variant={variant}
 111 |       className={cn(inputGroupButtonVariants({ size }), className)}
 112 |       {...props}
 113 |     />
 114 |   )
 115 | }
 116 |
 117 | function InputGroupText({ className, ...props }: React.ComponentProps<"span">) {
 118 |   return (
 119 |     <span
 120 |       className={cn(
 121 |         "text-muted-foreground flex items-center gap-2 text-sm [&_svg:not([class*='size-'])]:size-4
[&_svg]:pointer-events-none",
 122 |         className
 123 |       )}
 124 |       {...props}
 125 |     />
 126 |   )
 127 | }
 128 |
 129 | function InputGroupInput({
 130 |   className,
 131 |   ...props
 132 | }: React.ComponentProps<"input">) {
 133 |   return (
 134 |     <Input
 135 |       data-slot="input-group-control"
 136 |       className={cn(
 137 |         "flex-1 rounded-none border-0 bg-transparent shadow-none focus-visible:ring-0 dark:bg-transparent",
 138 |         className
 139 |       )}
 140 |       {...props}
 141 |     />
 142 |   )
 143 | }
 144 |
 145 | function InputGroupTextarea({
 146 |   className,
 147 |   ...props
 148 | }: React.ComponentProps<"textarea">) {
 149 |   return (
 150 |     <Textarea
 151 |       data-slot="input-group-control"
 152 |       className={cn(
 153 |         "flex-1 resize-none rounded-none border-0 bg-transparent py-3 shadow-none focus-visible:ring-0 dark:bg-
transparent",
 154 |         className
 155 |       )}
 156 |       {...props}
 157 |     />
 158 |   )
 159 | }
 160 |
 161 | export {
 162 |   InputGroup,
 163 |   InputGroupAddon,
 164 |   InputGroupButton,
 165 |   InputGroupText,
 166 |   InputGroupInput,
 167 |   InputGroupTextarea,
 168 | }
 169 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/input-otp.tsx

```
   1 | import * as React from "react"
   2 | import { OTPInput, OTPInputContext } from "input-otp"
   3 | import { Minus } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const InputOTP = React.forwardRef<
   8 |   React.ElementRef<typeof OTPInput>,
   9 |   React.ComponentPropsWithoutRef<typeof OTPInput>
  10 | >(({ className, containerClassName, ...props }, ref) => (
  11 |   <OTPInput
  12 |     ref={ref}
  13 |     containerClassName={cn(
  14 |       "flex items-center gap-2 has-[:disabled]:opacity-50",
  15 |       containerClassName
  16 |     )}
  17 |     className={cn("disabled:cursor-not-allowed", className)}
  18 |     {...props}
  19 |   />
  20 | ))
  21 | InputOTP.displayName = "InputOTP"
  22 |
  23 | const InputOTPGroup = React.forwardRef<
  24 |   React.ElementRef<"div">,
  25 |   React.ComponentPropsWithoutRef<"div">
  26 | >(({ className, ...props }, ref) => (
  27 |   <div ref={ref} className={cn("flex items-center", className)} {...props} />
  28 | ))
  29 | InputOTPGroup.displayName = "InputOTPGroup"
  30 |
  31 | const InputOTPSlot = React.forwardRef<
  32 |   React.ElementRef<"div">,
  33 |   React.ComponentPropsWithoutRef<"div"> & { index: number }
  34 | >(({ index, className, ...props }, ref) => {
  35 |   const inputOTPContext = React.useContext(OTPInputContext)
  36 |   const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index]
  37 |
  38 |   return (
  39 |     <div
  40 |       ref={ref}
  41 |       className={cn(
  42 |         "relative flex h-9 w-9 items-center justify-center border-y border-r border-input text-sm shadow-sm
transition-all first:rounded-l-md first:border-l ...
  43 |         isActive && "z-10 ring-1 ring-ring",
  44 |         className
  45 |       )}
  46 |       {...props}
  47 |     >
  48 |       {char}
  49 |       {hasFakeCaret && (
  50 |         <div className="pointer-events-none absolute inset-0 flex items-center justify-center">
  51 |           <div className="h-4 w-px animate-caret-blink bg-foreground duration-1000" />
  52 |         </div>
  53 |       )}
  54 |     </div>
  55 |   )
  56 | })
  57 | InputOTPSlot.displayName = "InputOTPSlot"
  58 |
  59 | const InputOTPSeparator = React.forwardRef<
  60 |   React.ElementRef<"div">,
  61 |   React.ComponentPropsWithoutRef<"div">
  62 | >(({ ...props }, ref) => (
  63 |   <div ref={ref} role="separator" {...props}>
  64 |     <Minus />
  65 |   </div>
  66 | ))
  67 | InputOTPSeparator.displayName = "InputOTPSeparator"
  68 |
  69 | export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator }
  70 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/input.tsx

```
   1 | import * as React from "react"
   2 |
   3 | import { cn } from "@/lib/utils"
   4 |
   5 | const Input = React.forwardRef<HTMLInputElement, React.ComponentProps<"input">>(
   6 |   ({ className, type, ...props }, ref) => {
   7 |     return (
   8 |       <input
   9 |         type={type}
  10 |         className={cn(
  11 |           "flex h-9 w-full rounded-md border border-input bg-transparent px-3 py-1 text-base shadow-sm transition-
colors file:border-0 file:bg-transparent fi...
  12 |           className
  13 |         )}
  14 |         ref={ref}
  15 |         {...props}
  16 |       />
  17 |     )
  18 |   }
  19 | )
  20 | Input.displayName = "Input"
  21 |
  22 | export { Input }
  23 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/item.tsx

```
   1 | import * as React from "react"
   2 | import { Slot } from "@radix-ui/react-slot"
   3 | import { cva, type VariantProps } from "class-variance-authority"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 | import { Separator } from "@/components/ui/separator"
   7 |
   8 | function ItemGroup({ className, ...props }: React.ComponentProps<"div">) {
   9 |   return (
  10 |     <div
  11 |       role="list"
  12 |       data-slot="item-group"
  13 |       className={cn("group/item-group flex flex-col", className)}
  14 |       {...props}
  15 |     />
  16 |   )
  17 | }
  18 |
  19 | function ItemSeparator({
  20 |   className,
  21 |   ...props
  22 | }: React.ComponentProps<typeof Separator>) {
  23 |   return (
  24 |     <Separator
  25 |       data-slot="item-separator"
  26 |       orientation="horizontal"
  27 |       className={cn("my-0", className)}
  28 |       {...props}
  29 |     />
  30 |   )
  31 | }
  32 |
  33 | const itemVariants = cva(
  34 |   "group/item [a]:hover:bg-accent/50 focus-visible:border-ring focus-visible:ring-ring/50 [a]:transition-colors
flex flex-wrap items-center rounded-md border...
  35 |   {
  36 |     variants: {
  37 |       variant: {
  38 |         default: "bg-transparent",
  39 |         outline: "border-border",
  40 |         muted: "bg-muted/50",
  41 |       },
  42 |       size: {
  43 |         default: "gap-4 p-4 ",
  44 |         sm: "gap-2.5 px-4 py-3",
  45 |       },
  46 |     },
  47 |     defaultVariants: {
  48 |       variant: "default",
  49 |       size: "default",
  50 |     },
  51 |   }
  52 | )
  53 |
  54 | function Item({
  55 |   className,
  56 |   variant = "default",
  57 |   size = "default",
  58 |   asChild = false,
  59 |   ...props
  60 | }: React.ComponentProps<"div"> &
  61 |   VariantProps<typeof itemVariants> & { asChild?: boolean }) {
  62 |   const Comp = asChild ? Slot : "div"
  63 |   return (
  64 |     <Comp
  65 |       data-slot="item"
  66 |       data-variant={variant}
  67 |       data-size={size}
  68 |       className={cn(itemVariants({ variant, size, className }))}
  69 |       {...props}
  70 |     />
  71 |   )
  72 | }
  73 |
  74 | const itemMediaVariants = cva(
  75 |   "flex shrink-0 items-center justify-center gap-2 group-has-[[data-slot=item-description]]/item:translate-y-0.5
group-has-[[data-slot=item-description]]/ite...
  76 |   {
  77 |     variants: {
  78 |       variant: {
  79 |         default: "bg-transparent",
  80 |         icon: "bg-muted size-8 rounded-sm border [&_svg:not([class*='size-'])]:size-4",
  81 |         image:
  82 |           "size-10 overflow-hidden rounded-sm [&_img]:size-full [&_img]:object-cover",
  83 |       },
  84 |     },
  85 |     defaultVariants: {
  86 |       variant: "default",
  87 |     },
  88 |   }
  89 | )
  90 |
  91 | function ItemMedia({
  92 |   className,
  93 |   variant = "default",
  94 |   ...props
  95 | }: React.ComponentProps<"div"> & VariantProps<typeof itemMediaVariants>) {
  96 |   return (
  97 |     <div
  98 |       data-slot="item-media"
```

```
 99 |       data-variant={variant}
100 |       className={cn(itemMediaVariants({ variant, className }))}
101 |       {...props}
102 |     />
103 |   )
104 | }
105 |
106 | function ItemContent({ className, ...props }: React.ComponentProps<"div">) {
107 |   return (
108 |     <div
109 |       data-slot="item-content"
110 |       className={cn(
111 |         "flex flex-1 flex-col gap-1 [&+[data-slot=item-content]]:flex-none",
112 |         className
113 |       )}
114 |       {...props}
115 |     />
116 |   )
117 | }
118 |
119 | function ItemTitle({ className, ...props }: React.ComponentProps<"div">) {
120 |   return (
121 |     <div
122 |       data-slot="item-title"
123 |       className={cn(
124 |         "flex w-fit items-center gap-2 text-sm font-medium leading-snug",
125 |         className
126 |       )}
127 |       {...props}
128 |     />
129 |   )
130 | }
131 |
132 | function ItemDescription({ className, ...props }: React.ComponentProps<"p">) {
133 |   return (
134 |     <p
135 |       data-slot="item-description"
136 |       className={cn(
137 |         "text-muted-foreground line-clamp-2 text-balance text-sm font-normal leading-normal",
138 |         "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
139 |         className
140 |       )}
141 |       {...props}
142 |     />
143 |   )
144 | }
145 |
146 | function ItemActions({ className, ...props }: React.ComponentProps<"div">) {
147 |   return (
148 |     <div
149 |       data-slot="item-actions"
150 |       className={cn("flex items-center gap-2", className)}
151 |       {...props}
152 |     />
153 |   )
154 | }
155 |
156 | function ItemHeader({ className, ...props }: React.ComponentProps<"div">) {
157 |   return (
158 |     <div
159 |       data-slot="item-header"
160 |       className={cn(
161 |         "flex basis-full items-center justify-between gap-2",
162 |         className
163 |       )}
164 |       {...props}
165 |     />
166 |   )
167 | }
168 |
169 | function ItemFooter({ className, ...props }: React.ComponentProps<"div">) {
170 |   return (
171 |     <div
172 |       data-slot="item-footer"
173 |       className={cn(
174 |         "flex basis-full items-center justify-between gap-2",
175 |         className
176 |       )}
177 |       {...props}
178 |     />
179 |   )
180 | }
181 |
182 | export {
183 |   Item,
184 |   ItemMedia,
185 |   ItemContent,
186 |   ItemActions,
187 |   ItemGroup,
188 |   ItemSeparator,
189 |   ItemTitle,
190 |   ItemDescription,
191 |   ItemHeader,
192 |   ItemFooter,
193 | }
194 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/kbd.tsx

```
   1 | import { cn } from "@/lib/utils"
   2 |
   3 | function Kbd({ className, ...props }: React.ComponentProps<"kbd">) {
   4 |   return (
   5 |     <kbd
   6 |       data-slot="kbd"
   7 |       className={cn(
   8 |         "bg-muted text-muted-foreground pointer-events-none inline-flex h-5 w-fit min-w-5 select-none items-center
justify-center gap-1 rounded-sm px-1 font-...
   9 |         "[&_svg:not([class*='size-'])]:size-3",
  10 |         "[[data-slot=tooltip-content]_&]:bg-background/20 [[data-slot=tooltip-content]_&]:text-background dark:
[[data-slot=tooltip-content]_&]:bg-background/...
  11 |         className
  12 |       )}
  13 |       {...props}
  14 |     />
  15 |   )
  16 | }
  17 |
  18 | function KbdGroup({ className, ...props }: React.ComponentProps<"div">) {
  19 |   return (
  20 |     <kbd
  21 |       data-slot="kbd-group"
  22 |       className={cn("inline-flex items-center gap-1", className)}
  23 |       {...props}
  24 |     />
  25 |   )
  26 | }
  27 |
  28 | export { Kbd, KbdGroup }
  29 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/label.tsx

```
"use client"

import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const labelVariants = cva(
  "text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
)

const Label = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> &
    VariantProps<typeof labelVariants>
>(({ className, ...props }, ref) => (
  <LabelPrimitive.Root
    ref={ref}
    className={cn(labelVariants(), className)}
    {...props}
  />
))
Label.displayName = LabelPrimitive.Root.displayName

export { Label }

```

— end of file —

File: artifacts/mbc-platform/src/components/ui/menubar.tsx

```
   1 | import * as React from "react"
   2 | import * as MenubarPrimitive from "@radix-ui/react-menubar"
   3 | import { Check, ChevronRight, Circle } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | function MenubarMenu({
   8 |   ...props
   9 | }: React.ComponentProps<typeof MenubarPrimitive.Menu>) {
  10 |   return <MenubarPrimitive.Menu {...props} />
  11 | }
  12 |
  13 | function MenubarGroup({
  14 |   ...props
  15 | }: React.ComponentProps<typeof MenubarPrimitive.Group>) {
  16 |   return <MenubarPrimitive.Group {...props} />
  17 | }
  18 |
  19 | function MenubarPortal({
  20 |   ...props
  21 | }: React.ComponentProps<typeof MenubarPrimitive.Portal>) {
  22 |   return <MenubarPrimitive.Portal {...props} />
  23 | }
  24 |
  25 | function MenubarRadioGroup({
  26 |   ...props
  27 | }: React.ComponentProps<typeof MenubarPrimitive.RadioGroup>) {
  28 |   return <MenubarPrimitive.RadioGroup {...props} />
  29 | }
  30 |
  31 | function MenubarSub({
  32 |   ...props
  33 | }: React.ComponentProps<typeof MenubarPrimitive.Sub>) {
  34 |   return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props} />
  35 | }
  36 |
  37 | const Menubar = React.forwardRef<
  38 |   React.ElementRef<typeof MenubarPrimitive.Root>,
  39 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
  40 | >(({ className, ...props }, ref) => (
  41 |   <MenubarPrimitive.Root
  42 |     ref={ref}
  43 |     className={cn(
  44 |       "flex h-9 items-center space-x-1 rounded-md border bg-background p-1 shadow-sm",
  45 |       className
  46 |     )}
  47 |     {...props}
  48 |   />
  49 | ))
  50 | Menubar.displayName = MenubarPrimitive.Root.displayName
  51 |
  52 | const MenubarTrigger = React.forwardRef<
  53 |   React.ElementRef<typeof MenubarPrimitive.Trigger>,
  54 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
  55 | >(({ className, ...props }, ref) => (
  56 |   <MenubarPrimitive.Trigger
  57 |     ref={ref}
  58 |     className={cn(
  59 |       "flex cursor-default select-none items-center rounded-sm px-3 py-1 text-sm font-medium outline-none focus:bg-
accent focus:text-accent-foreground data-[...
  60 |       className
  61 |     )}
  62 |     {...props}
  63 |   />
  64 | ))
  65 | MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName
  66 |
  67 | const MenubarSubTrigger = React.forwardRef<
  68 |   React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
  69 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
  70 |     inset?: boolean
  71 |   }
  72 | >(({ className, inset, children, ...props }, ref) => (
  73 |   <MenubarPrimitive.SubTrigger
  74 |     ref={ref}
  75 |     className={cn(
  76 |       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[state=open...
  77 |       inset && "pl-8",
  78 |       className
  79 |     )}
  80 |     {...props}
  81 |   >
  82 |     {children}
  83 |     <ChevronRight className="ml-auto h-4 w-4" />
  84 |   </MenubarPrimitive.SubTrigger>
  85 | ))
  86 | MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName
  87 |
  88 | const MenubarSubContent = React.forwardRef<
  89 |   React.ElementRef<typeof MenubarPrimitive.SubContent>,
  90 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
  91 | >(({ className, ...props }, ref) => (
  92 |   <MenubarPrimitive.SubContent
  93 |     ref={ref}
  94 |     className={cn(
  95 |       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data-
[state=open]:animate-in data-[state=closed]:...
  96 |       className
  97 |     )}
```

```
  98 |     {...props}
  99 |   />
 100 | ))
 101 | MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName
 102 |
 103 | const MenubarContent = React.forwardRef<
 104 |   React.ElementRef<typeof MenubarPrimitive.Content>,
 105 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
 106 | >(
 107 |   (
 108 |     { className, align = "start", alignOffset = -4, sideOffset = 8, ...props },
 109 |     ref
 110 |   ) => (
 111 |     <MenubarPrimitive.Portal>
 112 |       <MenubarPrimitive.Content
 113 |         ref={ref}
 114 |         align={align}
 115 |         alignOffset={alignOffset}
 116 |         sideOffset={sideOffset}
 117 |         className={cn(
 118 |           "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md
data-[state=open]:animate-in data-[state=clo...
 119 |           className
 120 |         )}
 121 |         {...props}
 122 |       />
 123 |     </MenubarPrimitive.Portal>
 124 |   )
 125 | )
 126 | MenubarContent.displayName = MenubarPrimitive.Content.displayName
 127 |
 128 | const MenubarItem = React.forwardRef<
 129 |   React.ElementRef<typeof MenubarPrimitive.Item>,
 130 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {
 131 |     inset?: boolean
 132 |   }
 133 | >(({ className, inset, ...props }, ref) => (
 134 |   <MenubarPrimitive.Item
 135 |     ref={ref}
 136 |     className={cn(
 137 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-
accent focus:text-accent-foreground data-[d...
 138 |       inset && "pl-8",
 139 |       className
 140 |     )}
 141 |     {...props}
 142 |   />
 143 | ))
 144 | MenubarItem.displayName = MenubarPrimitive.Item.displayName
 145 |
 146 | const MenubarCheckboxItem = React.forwardRef<
 147 |   React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
 148 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
 149 | >(({ className, children, checked, ...props }, ref) => (
 150 |   <MenubarPrimitive.CheckboxItem
 151 |     ref={ref}
 152 |     className={cn(
 153 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
focus:bg-accent focus:text-accent-foreground da...
 154 |       className
 155 |     )}
 156 |     checked={checked}
 157 |     {...props}
 158 |   >
 159 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 160 |       <MenubarPrimitive.ItemIndicator>
 161 |         <Check className="h-4 w-4" />
 162 |       </MenubarPrimitive.ItemIndicator>
 163 |     </span>
 164 |     {children}
 165 |   </MenubarPrimitive.CheckboxItem>
 166 | ))
 167 | MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName
 168 |
 169 | const MenubarRadioItem = React.forwardRef<
 170 |   React.ElementRef<typeof MenubarPrimitive.RadioItem>,
 171 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
 172 | >(({ className, children, ...props }, ref) => (
 173 |   <MenubarPrimitive.RadioItem
 174 |     ref={ref}
 175 |     className={cn(
 176 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none
focus:bg-accent focus:text-accent-foreground da...
 177 |       className
 178 |     )}
 179 |     {...props}
 180 |   >
 181 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
 182 |       <MenubarPrimitive.ItemIndicator>
 183 |         <Circle className="h-4 w-4 fill-current" />
 184 |       </MenubarPrimitive.ItemIndicator>
 185 |     </span>
 186 |     {children}
 187 |   </MenubarPrimitive.RadioItem>
 188 | ))
 189 | MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName
 190 |
 191 | const MenubarLabel = React.forwardRef<
 192 |   React.ElementRef<typeof MenubarPrimitive.Label>,
 193 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {
 194 |     inset?: boolean
 195 |   }
 196 | >(({ className, inset, ...props }, ref) => (
```

```
197 |   <MenubarPrimitive.Label
198 |     ref={ref}
199 |     className={cn(
200 |       "px-2 py-1.5 text-sm font-semibold",
201 |       inset && "pl-8",
202 |       className
203 |     )}
204 |     {...props}
205 |   />
206 | ))
207 | MenubarLabel.displayName = MenubarPrimitive.Label.displayName
208 |
209 | const MenubarSeparator = React.forwardRef<
210 |   React.ElementRef<typeof MenubarPrimitive.Separator>,
211 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>
212 | >(({ className, ...props }, ref) => (
213 |   <MenubarPrimitive.Separator
214 |     ref={ref}
215 |     className={cn("-mx-1 my-1 h-px bg-muted", className)}
216 |     {...props}
217 |   />
218 | ))
219 | MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName
220 |
221 | const MenubarShortcut = ({
222 |   className,
223 |   ...props
224 | }: React.HTMLAttributes<HTMLSpanElement>) => {
225 |   return (
226 |     <span
227 |       className={cn(
228 |         "ml-auto text-xs tracking-widest text-muted-foreground",
229 |         className
230 |       )}
231 |       {...props}
232 |     />
233 |   )
234 | }
235 | MenubarShortcut.displayname = "MenubarShortcut"
236 |
237 | export {
238 |   Menubar,
239 |   MenubarMenu,
240 |   MenubarTrigger,
241 |   MenubarContent,
242 |   MenubarItem,
243 |   MenubarSeparator,
244 |   MenubarLabel,
245 |   MenubarCheckboxItem,
246 |   MenubarRadioGroup,
247 |   MenubarRadioItem,
248 |   MenubarPortal,
249 |   MenubarSubContent,
250 |   MenubarSubTrigger,
251 |   MenubarGroup,
252 |   MenubarSub,
253 |   MenubarShortcut,
254 | }
255 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/navigation-menu.tsx

```
   1 | import * as React from "react"
   2 | import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu"
   3 | import { cva } from "class-variance-authority"
   4 | import { ChevronDown } from "lucide-react"
   5 |
   6 | import { cn } from "@/lib/utils"
   7 |
   8 | const NavigationMenu = React.forwardRef<
   9 |   React.ElementRef<typeof NavigationMenuPrimitive.Root>,
  10 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Root>
  11 | >(({ className, children, ...props }, ref) => (
  12 |   <NavigationMenuPrimitive.Root
  13 |     ref={ref}
  14 |     className={cn(
  15 |       "relative z-10 flex max-w-max flex-1 items-center justify-center",
  16 |       className
  17 |     )}
  18 |     {...props}
  19 |   >
  20 |     {children}
  21 |     <NavigationMenuViewport />
  22 |   </NavigationMenuPrimitive.Root>
  23 | ))
  24 | NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName
  25 |
  26 | const NavigationMenuList = React.forwardRef<
  27 |   React.ElementRef<typeof NavigationMenuPrimitive.List>,
  28 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.List>
  29 | >(({ className, ...props }, ref) => (
  30 |   <NavigationMenuPrimitive.List
  31 |     ref={ref}
  32 |     className={cn(
  33 |       "group flex flex-1 list-none items-center justify-center space-x-1",
  34 |       className
  35 |     )}
  36 |     {...props}
  37 |   />
  38 | ))
  39 | NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName
  40 |
  41 | const NavigationMenuItem = NavigationMenuPrimitive.Item
  42 |
  43 | const navigationMenuTriggerStyle = cva(
  44 |   "group inline-flex h-9 w-max items-center justify-center rounded-md bg-background px-4 py-2 text-sm font-medium
transition-colors hover:bg-accent hover:tex...
  45 | )
  46 |
  47 | const NavigationMenuTrigger = React.forwardRef<
  48 |   React.ElementRef<typeof NavigationMenuPrimitive.Trigger>,
  49 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Trigger>
  50 | >(({ className, children, ...props }, ref) => (
  51 |   <NavigationMenuPrimitive.Trigger
  52 |     ref={ref}
  53 |     className={cn(navigationMenuTriggerStyle(), "group", className)}
  54 |     {...props}
  55 |   >
  56 |     {children}{" "}
  57 |     <ChevronDown
  58 |       className="relative top-[1px] ml-1 h-3 w-3 transition duration-300 group-data-[state=open]:rotate-180"
  59 |       aria-hidden="true"
  60 |     />
  61 |   </NavigationMenuPrimitive.Trigger>
  62 | ))
  63 | NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName
  64 |
  65 | const NavigationMenuContent = React.forwardRef<
  66 |   React.ElementRef<typeof NavigationMenuPrimitive.Content>,
  67 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Content>
  68 | >(({ className, ...props }, ref) => (
  69 |   <NavigationMenuPrimitive.Content
  70 |     ref={ref}
  71 |     className={cn(
  72 |       "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-
[motion^=from-]:fade-in data-[motion^=to-]:fade-out data-[moti...
  73 |       className
  74 |     )}
  75 |     {...props}
  76 |   />
  77 | ))
  78 | NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName
  79 |
  80 | const NavigationMenuLink = NavigationMenuPrimitive.Link
  81 |
  82 | const NavigationMenuViewport = React.forwardRef<
  83 |   React.ElementRef<typeof NavigationMenuPrimitive.Viewport>,
  84 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Viewport>
  85 | >(({ className, ...props }, ref) => (
  86 |   <div className={cn("absolute left-0 top-full flex justify-center")}>
  87 |     <NavigationMenuPrimitive.Viewport
  88 |       className={cn(
  89 |         "origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidden
rounded-md border bg-popover text-popover-...
  90 |         className
  91 |       )}
  92 |       ref={ref}
  93 |       {...props}
  94 |     />
  95 |   </div>
  96 | ))
  97 | NavigationMenuViewport.displayName =
```

```
  98 |   NavigationMenuPrimitive.Viewport.displayName
  99 |
 100 | const NavigationMenuIndicator = React.forwardRef<
 101 |   React.ElementRef<typeof NavigationMenuPrimitive.Indicator>,
 102 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Indicator>
 103 | >(({ className, ...props }, ref) => (
 104 |   <NavigationMenuPrimitive.Indicator
 105 |     ref={ref}
 106 |     className={cn(
 107 |       "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-[state=visible]:animate-in data-
[state=hidden]:animate-out data-[state=hidden]...
 108 |       className
 109 |     )}
 110 |     {...props}
 111 |   >
 112 |     <div className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
 113 |   </NavigationMenuPrimitive.Indicator>
 114 | ))
 115 | NavigationMenuIndicator.displayName =
 116 |   NavigationMenuPrimitive.Indicator.displayName
 117 |
 118 | export {
 119 |   navigationMenuTriggerStyle,
 120 |   NavigationMenu,
 121 |   NavigationMenuList,
 122 |   NavigationMenuItem,
 123 |   NavigationMenuContent,
 124 |   NavigationMenuTrigger,
 125 |   NavigationMenuLink,
 126 |   NavigationMenuIndicator,
 127 |   NavigationMenuViewport,
 128 | }
 129 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/pagination.tsx

```
  1 | import * as React from "react"
  2 | import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react"
  3 |
  4 | import { cn } from "@/lib/utils"
  5 | import { ButtonProps, buttonVariants } from "@/components/ui/button"
  6 |
  7 | const Pagination = ({ className, ...props }: React.ComponentProps<"nav">) => (
  8 |   <nav
  9 |     role="navigation"
 10 |     aria-label="pagination"
 11 |     className={cn("mx-auto flex w-full justify-center", className)}
 12 |     {...props}
 13 |   />
 14 | )
 15 | Pagination.displayName = "Pagination"
 16 |
 17 | const PaginationContent = React.forwardRef<
 18 |   HTMLUListElement,
 19 |   React.ComponentProps<"ul">
 20 | >(({ className, ...props }, ref) => (
 21 |   <ul
 22 |     ref={ref}
 23 |     className={cn("flex flex-row items-center gap-1", className)}
 24 |     {...props}
 25 |   />
 26 | ))
 27 | PaginationContent.displayName = "PaginationContent"
 28 |
 29 | const PaginationItem = React.forwardRef<
 30 |   HTMLLIElement,
 31 |   React.ComponentProps<"li">
 32 | >(({ className, ...props }, ref) => (
 33 |   <li ref={ref} className={cn("", className)} {...props} />
 34 | ))
 35 | PaginationItem.displayName = "PaginationItem"
 36 |
 37 | type PaginationLinkProps = {
 38 |   isActive?: boolean
 39 | } & Pick<ButtonProps, "size"> &
 40 |   React.ComponentProps<"a">
 41 |
 42 | const PaginationLink = ({
 43 |   className,
 44 |   isActive,
 45 |   size = "icon",
 46 |   ...props
 47 | }: PaginationLinkProps) => (
 48 |   <a
 49 |     aria-current={isActive ? "page" : undefined}
 50 |     className={cn(
 51 |       buttonVariants({
 52 |         variant: isActive ? "outline" : "ghost",
 53 |         size,
 54 |       }),
 55 |       className
 56 |     )}
 57 |     {...props}
 58 |   />
 59 | )
 60 | PaginationLink.displayName = "PaginationLink"
 61 |
 62 | const PaginationPrevious = ({
 63 |   className,
 64 |   ...props
 65 | }: React.ComponentProps<typeof PaginationLink>) => (
 66 |   <PaginationLink
 67 |     aria-label="Go to previous page"
 68 |     size="default"
 69 |     className={cn("gap-1 pl-2.5", className)}
 70 |     {...props}
 71 |   >
 72 |     <ChevronLeft className="h-4 w-4" />
 73 |     <span>Previous</span>
 74 |   </PaginationLink>
 75 | )
 76 | PaginationPrevious.displayName = "PaginationPrevious"
 77 |
 78 | const PaginationNext = ({
 79 |   className,
 80 |   ...props
 81 | }: React.ComponentProps<typeof PaginationLink>) => (
 82 |   <PaginationLink
 83 |     aria-label="Go to next page"
 84 |     size="default"
 85 |     className={cn("gap-1 pr-2.5", className)}
 86 |     {...props}
 87 |   >
 88 |     <span>Next</span>
 89 |     <ChevronRight className="h-4 w-4" />
 90 |   </PaginationLink>
 91 | )
 92 | PaginationNext.displayName = "PaginationNext"
 93 |
 94 | const PaginationEllipsis = ({
 95 |   className,
 96 |   ...props
 97 | }: React.ComponentProps<"span">) => (
 98 |   <span
 99 |     aria-hidden
100 |     className={cn("flex h-9 w-9 items-center justify-center", className)}
```

```
101 |     {...props}
102 |   >
103 |     <MoreHorizontal className="h-4 w-4" />
104 |     <span className="sr-only">More pages</span>
105 |   </span>
106 | )
107 | PaginationEllipsis.displayName = "PaginationEllipsis"
108 |
109 | export {
110 |   Pagination,
111 |   PaginationContent,
112 |   PaginationLink,
113 |   PaginationItem,
114 |   PaginationPrevious,
115 |   PaginationNext,
116 |   PaginationEllipsis,
117 | }
118 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/popover.tsx

```
   1 | import * as React from "react"
   2 | import * as PopoverPrimitive from "@radix-ui/react-popover"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const Popover = PopoverPrimitive.Root
   7 |
   8 | const PopoverTrigger = PopoverPrimitive.Trigger
   9 |
  10 | const PopoverAnchor = PopoverPrimitive.Anchor
  11 |
  12 | const PopoverContent = React.forwardRef<
  13 |   React.ElementRef<typeof PopoverPrimitive.Content>,
  14 |   React.ComponentPropsWithoutRef<typeof PopoverPrimitive.Content>
  15 | >(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  16 |   <PopoverPrimitive.Portal>
  17 |     <PopoverPrimitive.Content
  18 |       ref={ref}
  19 |       align={align}
  20 |       sideOffset={sideOffset}
  21 |       className={cn(
  22 |         "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-
[state=open]:animate-in data-[state=closed]:animate-o...
  23 |         className
  24 |       )}
  25 |       {...props}
  26 |     />
  27 |   </PopoverPrimitive.Portal>
  28 | ))
  29 | PopoverContent.displayName = PopoverPrimitive.Content.displayName
  30 |
  31 | export { Popover, PopoverTrigger, PopoverContent, PopoverAnchor }
  32 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/progress.tsx

```
"use client"

import * as React from "react"
import * as ProgressPrimitive from "@radix-ui/react-progress"

import { cn } from "@/lib/utils"

const Progress = React.forwardRef<
  React.ElementRef<typeof ProgressPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ProgressPrimitive.Root>
>(({ className, value, ...props }, ref) => (
  <ProgressPrimitive.Root
    ref={ref}
    className={cn(
      "relative h-2 w-full overflow-hidden rounded-full bg-primary/20",
      className
    )}
    {...props}
  >
    <ProgressPrimitive.Indicator
      className="h-full w-full flex-1 bg-primary transition-all"
      style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
    />
  </ProgressPrimitive.Root>
))
Progress.displayName = ProgressPrimitive.Root.displayName

export { Progress }

```

— end of file —

File: artifacts/mbc-platform/src/components/ui/radio-group.tsx

```
   1 | import * as React from "react"
   2 | import * as RadioGroupPrimitive from "@radix-ui/react-radio-group"
   3 | import { Circle } from "lucide-react"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const RadioGroup = React.forwardRef<
   8 |   React.ElementRef<typeof RadioGroupPrimitive.Root>,
   9 |   React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Root>
  10 | >(({ className, ...props }, ref) => {
  11 |   return (
  12 |     <RadioGroupPrimitive.Root
  13 |       className={cn("grid gap-2", className)}
  14 |       {...props}
  15 |       ref={ref}
  16 |     />
  17 |   )
  18 | })
  19 | RadioGroup.displayName = RadioGroupPrimitive.Root.displayName
  20 |
  21 | const RadioGroupItem = React.forwardRef<
  22 |   React.ElementRef<typeof RadioGroupPrimitive.Item>,
  23 |   React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Item>
  24 | >(({ className, ...props }, ref) => {
  25 |   return (
  26 |     <RadioGroupPrimitive.Item
  27 |       ref={ref}
  28 |       className={cn(
  29 |         "aspect-square h-4 w-4 rounded-full border border-primary text-primary shadow focus:outline-none focus-
visible:ring-1 focus-visible:ring-ring disable...
  30 |         className
  31 |       )}
  32 |       {...props}
  33 |     >
  34 |       <RadioGroupPrimitive.Indicator className="flex items-center justify-center">
  35 |         <Circle className="h-3.5 w-3.5 fill-primary" />
  36 |       </RadioGroupPrimitive.Indicator>
  37 |     </RadioGroupPrimitive.Item>
  38 |   )
  39 | })
  40 | RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName
  41 |
  42 | export { RadioGroup, RadioGroupItem }
  43 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/resizable.tsx

```
   1 | "use client"
   2 |
   3 | import { GripVertical } from "lucide-react"
   4 | import * as ResizablePrimitive from "react-resizable-panels"
   5 |
   6 | import { cn } from "@/lib/utils"
   7 |
   8 | const ResizablePanelGroup = ({
   9 |   className,
  10 |   ...props
  11 | }: React.ComponentProps<typeof ResizablePrimitive.PanelGroup>) => (
  12 |   <ResizablePrimitive.PanelGroup
  13 |     className={cn(
  14 |       "flex h-full w-full data-[panel-group-direction=vertical]:flex-col",
  15 |       className
  16 |     )}
  17 |     {...props}
  18 |   />
  19 | )
  20 |
  21 | const ResizablePanel = ResizablePrimitive.Panel
  22 |
  23 | const ResizableHandle = ({
  24 |   withHandle,
  25 |   className,
  26 |   ...props
  27 | }: React.ComponentProps<typeof ResizablePrimitive.PanelResizeHandle> & {
  28 |   withHandle?: boolean
  29 | }) => (
  30 |   <ResizablePrimitive.PanelResizeHandle
  31 |     className={cn(
  32 |       "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0 after:left-1/2
after:w-1 after:-translate-x-1/2 focus-visible:...
  33 |       className
  34 |     )}
  35 |     {...props}
  36 |   >
  37 |     {withHandle && (
  38 |       <div className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-border">
  39 |         <GripVertical className="h-2.5 w-2.5" />
  40 |       </div>
  41 |     )}
  42 |   </ResizablePrimitive.PanelResizeHandle>
  43 | )
  44 |
  45 | export { ResizablePanelGroup, ResizablePanel, ResizableHandle }
  46 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/scroll-area.tsx

```
1 | import * as React from "react"
2 | import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area"
3 |
4 | import { cn } from "@/lib/utils"
5 |
6 | const ScrollArea = React.forwardRef<
7 |   React.ElementRef<typeof ScrollAreaPrimitive.Root>,
8 |   React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.Root>
9 | >(({ className, children, ...props }, ref) => (
10 |   <ScrollAreaPrimitive.Root
11 |     ref={ref}
12 |     className={cn("relative overflow-hidden", className)}
13 |     {...props}
14 |   >
15 |     <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">
16 |       {children}
17 |     </ScrollAreaPrimitive.Viewport>
18 |     <ScrollBar />
19 |     <ScrollAreaPrimitive.Corner />
20 |   </ScrollAreaPrimitive.Root>
21 | ))
22 | ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName
23 |
24 | const ScrollBar = React.forwardRef<
25 |   React.ElementRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>,
26 |   React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>
27 | >(({ className, orientation = "vertical", ...props }, ref) => (
28 |   <ScrollAreaPrimitive.ScrollAreaScrollbar
29 |     ref={ref}
30 |     orientation={orientation}
31 |     className={cn(
32 |       "flex touch-none select-none transition-colors",
33 |       orientation === "vertical" &&
34 |         "h-full w-2.5 border-l border-l-transparent p-[1px]",
35 |       orientation === "horizontal" &&
36 |         "h-2.5 flex-col border-t border-t-transparent p-[1px]",
37 |       className
38 |     )}
39 |     {...props}
40 |   >
41 |     <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border" />
42 |   </ScrollAreaPrimitive.ScrollAreaScrollbar>
43 | ))
44 | ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName
45 |
46 | export { ScrollArea, ScrollBar }
47 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/select.tsx

```
   1 | "use client"
   2 |
   3 | import * as React from "react"
   4 | import * as SelectPrimitive from "@radix-ui/react-select"
   5 | import { Check, ChevronDown, ChevronUp } from "lucide-react"
   6 |
   7 | import { cn } from "@/lib/utils"
   8 |
   9 | const Select = SelectPrimitive.Root
  10 |
  11 | const SelectGroup = SelectPrimitive.Group
  12 |
  13 | const SelectValue = SelectPrimitive.Value
  14 |
  15 | const SelectTrigger = React.forwardRef<
  16 |   React.ElementRef<typeof SelectPrimitive.Trigger>,
  17 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
  18 | >(({ className, children, ...props }, ref) => (
  19 |   <SelectPrimitive.Trigger
  20 |     ref={ref}
  21 |     className={cn(
  22 |       "flex h-9 w-full items-center justify-between whitespace-nowrap rounded-md border border-input bg-
transparent px-3 py-2 text-sm shadow-sm ring-offset-b...
  23 |       className
  24 |     )}
  25 |     {...props}
  26 |   >
  27 |     {children}
  28 |     <SelectPrimitive.Icon asChild>
  29 |       <ChevronDown className="h-4 w-4 opacity-50" />
  30 |     </SelectPrimitive.Icon>
  31 |   </SelectPrimitive.Trigger>
  32 | ))
  33 | SelectTrigger.displayName = SelectPrimitive.Trigger.displayName
  34 |
  35 | const SelectScrollUpButton = React.forwardRef<
  36 |   React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,
  37 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>
  38 | >(({ className, ...props }, ref) => (
  39 |   <SelectPrimitive.ScrollUpButton
  40 |     ref={ref}
  41 |     className={cn(
  42 |       "flex cursor-default items-center justify-center py-1",
  43 |       className
  44 |     )}
  45 |     {...props}
  46 |   >
  47 |     <ChevronUp className="h-4 w-4" />
  48 |   </SelectPrimitive.ScrollUpButton>
  49 | ))
  50 | SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName
  51 |
  52 | const SelectScrollDownButton = React.forwardRef<
  53 |   React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,
  54 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>
  55 | >(({ className, ...props }, ref) => (
  56 |   <SelectPrimitive.ScrollDownButton
  57 |     ref={ref}
  58 |     className={cn(
  59 |       "flex cursor-default items-center justify-center py-1",
  60 |       className
  61 |     )}
  62 |     {...props}
  63 |   >
  64 |     <ChevronDown className="h-4 w-4" />
  65 |   </SelectPrimitive.ScrollDownButton>
  66 | ))
  67 | SelectScrollDownButton.displayName =
  68 |   SelectPrimitive.ScrollDownButton.displayName
  69 |
  70 | const SelectContent = React.forwardRef<
  71 |   React.ElementRef<typeof SelectPrimitive.Content>,
  72 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>
  73 | >(({ className, children, position = "popper", ...props }, ref) => (
  74 |   <SelectPrimitive.Portal>
  75 |     <SelectPrimitive.Content
  76 |       ref={ref}
  77 |       className={cn(
  78 |         "relative z-50 max-h-[--radix-select-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-
hidden rounded-md border bg-popover text-popov...
  79 |         position === "popper" &&
  80 |           "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1 data-
[side=top]:-translate-y-1",
  81 |         className
  82 |       )}
  83 |       position={position}
  84 |       {...props}
  85 |     >
  86 |       <SelectScrollUpButton />
  87 |       <SelectPrimitive.Viewport
  88 |         className={cn(
  89 |           "p-1",
  90 |           position === "popper" &&
  91 |             "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]"
  92 |         )}
  93 |       >
  94 |         {children}
  95 |       </SelectPrimitive.Viewport>
  96 |       <SelectScrollDownButton />
  97 |     </SelectPrimitive.Content>
```

```
  98 |   </SelectPrimitive.Portal>
  99 | ))
 100 | SelectContent.displayName = SelectPrimitive.Content.displayName
 101 |
 102 | const SelectLabel = React.forwardRef<
 103 |   React.ElementRef<typeof SelectPrimitive.Label>,
 104 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>
 105 | >(({ className, ...props }, ref) => (
 106 |   <SelectPrimitive.Label
 107 |     ref={ref}
 108 |     className={cn("px-2 py-1.5 text-sm font-semibold", className)}
 109 |     {...props}
 110 |   />
 111 | ))
 112 | SelectLabel.displayName = SelectPrimitive.Label.displayName
 113 |
 114 | const SelectItem = React.forwardRef<
 115 |   React.ElementRef<typeof SelectPrimitive.Item>,
 116 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>
 117 | >(({ className, children, ...props }, ref) => (
 118 |   <SelectPrimitive.Item
 119 |     ref={ref}
 120 |     className={cn(
 121 |       "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-2 pr-8 text-sm outline-
none focus:bg-accent focus:text-accent-foregr...
 122 |       className
 123 |     )}
 124 |     {...props}
 125 |   >
 126 |     <span className="absolute right-2 flex h-3.5 w-3.5 items-center justify-center">
 127 |       <SelectPrimitive.ItemIndicator>
 128 |         <Check className="h-4 w-4" />
 129 |       </SelectPrimitive.ItemIndicator>
 130 |     </span>
 131 |     <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
 132 |   </SelectPrimitive.Item>
 133 | ))
 134 | SelectItem.displayName = SelectPrimitive.Item.displayName
 135 |
 136 | const SelectSeparator = React.forwardRef<
 137 |   React.ElementRef<typeof SelectPrimitive.Separator>,
 138 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>
 139 | >(({ className, ...props }, ref) => (
 140 |   <SelectPrimitive.Separator
 141 |     ref={ref}
 142 |     className={cn("-mx-1 my-1 h-px bg-muted", className)}
 143 |     {...props}
 144 |   />
 145 | ))
 146 | SelectSeparator.displayName = SelectPrimitive.Separator.displayName
 147 |
 148 | export {
 149 |   Select,
 150 |   SelectGroup,
 151 |   SelectValue,
 152 |   SelectTrigger,
 153 |   SelectContent,
 154 |   SelectLabel,
 155 |   SelectItem,
 156 |   SelectSeparator,
 157 |   SelectScrollUpButton,
 158 |   SelectScrollDownButton,
 159 | }
 160 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/separator.tsx

```
 1 | import * as React from "react"
 2 | import * as SeparatorPrimitive from "@radix-ui/react-separator"
 3 |
 4 | import { cn } from "@/lib/utils"
 5 |
 6 | const Separator = React.forwardRef<
 7 |   React.ElementRef<typeof SeparatorPrimitive.Root>,
 8 |   React.ComponentPropsWithoutRef<typeof SeparatorPrimitive.Root>
 9 | >(
10 |   (
11 |     { className, orientation = "horizontal", decorative = true, ...props },
12 |     ref
13 |   ) => (
14 |     <SeparatorPrimitive.Root
15 |       ref={ref}
16 |       decorative={decorative}
17 |       orientation={orientation}
18 |       className={cn(
19 |         "shrink-0 bg-border",
20 |         orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]",
21 |         className
22 |       )}
23 |       {...props}
24 |     />
25 |   )
26 | )
27 | Separator.displayName = SeparatorPrimitive.Root.displayName
28 |
29 | export { Separator }
30 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/sheet.tsx

```
   1 | "use client"
   2 |
   3 | import * as React from "react"
   4 | import * as SheetPrimitive from "@radix-ui/react-dialog"
   5 | import { cva, type VariantProps } from "class-variance-authority"
   6 | import { X } from "lucide-react"
   7 |
   8 | import { cn } from "@/lib/utils"
   9 |
  10 | const Sheet = SheetPrimitive.Root
  11 |
  12 | const SheetTrigger = SheetPrimitive.Trigger
  13 |
  14 | const SheetClose = SheetPrimitive.Close
  15 |
  16 | const SheetPortal = SheetPrimitive.Portal
  17 |
  18 | const SheetOverlay = React.forwardRef<
  19 |   React.ElementRef<typeof SheetPrimitive.Overlay>,
  20 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Overlay>
  21 | >(({ className, ...props }, ref) => (
  22 |   <SheetPrimitive.Overlay
  23 |     className={cn(
  24 |       "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-
[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
  25 |       className
  26 |     )}
  27 |     {...props}
  28 |     ref={ref}
  29 |   />
  30 | ))
  31 | SheetOverlay.displayName = SheetPrimitive.Overlay.displayName
  32 |
  33 | const sheetVariants = cva(
  34 |   "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-[state=closed]:duration-300 data-
[state=open]:duration-500 data-[state=open]:anim...
  35 |   {
  36 |     variants: {
  37 |       side: {
  38 |         top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-[state=open]:slide-in-from-top",
  39 |         bottom:
  40 |           "inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-[state=open]:slide-in-from-
bottom",
  41 |         left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-
[state=open]:slide-in-from-left sm:max-w-sm",
  42 |         right:
  43 |           "inset-y-0 right-0 h-full w-3/4 border-l data-[state=closed]:slide-out-to-right data-[state=open]:slide-
in-from-right sm:max-w-sm",
  44 |       },
  45 |     },
  46 |     defaultVariants: {
  47 |       side: "right",
  48 |     },
  49 |   }
  50 | )
  51 |
  52 | interface SheetContentProps
  53 |   extends React.ComponentPropsWithoutRef<typeof SheetPrimitive.Content>,
  54 |     VariantProps<typeof sheetVariants> {}
  55 |
  56 | const SheetContent = React.forwardRef<
  57 |   React.ElementRef<typeof SheetPrimitive.Content>,
  58 |   SheetContentProps
  59 | >(({ side = "right", className, children, ...props }, ref) => (
  60 |   <SheetPortal>
  61 |     <SheetOverlay />
  62 |     <SheetPrimitive.Content
  63 |       ref={ref}
  64 |       className={cn(sheetVariants({ side }), className)}
  65 |       {...props}
  66 |     >
  67 |       <SheetPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background
transition-opacity hover:opacity-100 focus:outline...
  68 |         <X className="h-4 w-4" />
  69 |         <span className="sr-only">Close</span>
  70 |       </SheetPrimitive.Close>
  71 |       {children}
  72 |     </SheetPrimitive.Content>
  73 |   </SheetPortal>
  74 | ))
  75 | SheetContent.displayName = SheetPrimitive.Content.displayName
  76 |
  77 | const SheetHeader = ({
  78 |   className,
  79 |   ...props
  80 | }: React.HTMLAttributes<HTMLDivElement>) => (
  81 |   <div
  82 |     className={cn(
  83 |       "flex flex-col space-y-2 text-center sm:text-left",
  84 |       className
  85 |     )}
  86 |     {...props}
  87 |   />
  88 | )
  89 | SheetHeader.displayName = "SheetHeader"
  90 |
  91 | const SheetFooter = ({
  92 |   className,
  93 |   ...props
  94 | }: React.HTMLAttributes<HTMLDivElement>) => (
```

```
 95 |   <div
 96 |     className={cn(
 97 |       "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
 98 |       className
 99 |     )}
100 |     {...props}
101 |   />
102 | )
103 | SheetFooter.displayName = "SheetFooter"
104 |
105 | const SheetTitle = React.forwardRef<
106 |   React.ElementRef<typeof SheetPrimitive.Title>,
107 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Title>
108 | >(({ className, ...props }, ref) => (
109 |   <SheetPrimitive.Title
110 |     ref={ref}
111 |     className={cn("text-lg font-semibold text-foreground", className)}
112 |     {...props}
113 |   />
114 | ))
115 | SheetTitle.displayName = SheetPrimitive.Title.displayName
116 |
117 | const SheetDescription = React.forwardRef<
118 |   React.ElementRef<typeof SheetPrimitive.Description>,
119 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Description>
120 | >(({ className, ...props }, ref) => (
121 |   <SheetPrimitive.Description
122 |     ref={ref}
123 |     className={cn("text-sm text-muted-foreground", className)}
124 |     {...props}
125 |   />
126 | ))
127 | SheetDescription.displayName = SheetPrimitive.Description.displayName
128 |
129 | export {
130 |   Sheet,
131 |   SheetPortal,
132 |   SheetOverlay,
133 |   SheetTrigger,
134 |   SheetClose,
135 |   SheetContent,
136 |   SheetHeader,
137 |   SheetFooter,
138 |   SheetTitle,
139 |   SheetDescription,
140 | }
141 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/sidebar.tsx

```
"use client"

import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, VariantProps } from "class-variance-authority"
import { PanelLeftIcon } from "lucide-react"

import { useIsMobile } from "@/hooks/use-mobile"
import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Separator } from "@/components/ui/separator"
import {
  Sheet,
  SheetContent,
  SheetDescription,
  SheetHeader,
  SheetTitle,
} from "@/components/ui/sheet"
import { Skeleton } from "@/components/ui/skeleton"
import {
  Tooltip,
  TooltipContent,
  TooltipProvider,
  TooltipTrigger,
} from "@/components/ui/tooltip"

const SIDEBAR_COOKIE_NAME = "sidebar_state"
const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7
const SIDEBAR_WIDTH = "16rem"
const SIDEBAR_WIDTH_MOBILE = "18rem"
const SIDEBAR_WIDTH_ICON = "3rem"
const SIDEBAR_KEYBOARD_SHORTCUT = "b"

type SidebarContextProps = {
  state: "expanded" | "collapsed"
  open: boolean
  setOpen: (open: boolean) => void
  openMobile: boolean
  setOpenMobile: (open: boolean) => void
  isMobile: boolean
  toggleSidebar: () => void
}

const SidebarContext = React.createContext<SidebarContextProps | null>(null)

function useSidebar() {
  const context = React.useContext(SidebarContext)
  if (!context) {
    throw new Error("useSidebar must be used within a SidebarProvider.")
  }

  return context
}

function SidebarProvider({
  defaultOpen = true,
  open: openProp,
  onOpenChange: setOpenProp,
  className,
  style,
  children,
  ...props
}: React.ComponentProps<"div"> & {
  defaultOpen?: boolean
  open?: boolean
  onOpenChange?: (open: boolean) => void
}) {
  const isMobile = useIsMobile()
  const [openMobile, setOpenMobile] = React.useState(false)

  // This is the internal state of the sidebar.
  // We use openProp and setOpenProp for control from outside the component.
  const [_open, _setOpen] = React.useState(defaultOpen)
  const open = openProp ?? _open
  const setOpen = React.useCallback(
    (value: boolean | ((value: boolean) => boolean)) => {
      const openState = typeof value === "function" ? value(open) : value
      if (setOpenProp) {
        setOpenProp(openState)
      } else {
        _setOpen(openState)
      }

      // This sets the cookie to keep the sidebar state.
      document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`
    },
    [setOpenProp, open]
  )

  // Helper to toggle the sidebar.
  const toggleSidebar = React.useCallback(() => {
    return isMobile ? setOpenMobile((open) => !open) : setOpen((open) => !open)
  }, [isMobile, setOpen, setOpenMobile])

  // Adds a keyboard shortcut to toggle the sidebar.
  React.useEffect(() => {
    const handleKeyDown = (event: KeyboardEvent) => {
      if (
        event.key === SIDEBAR_KEYBOARD_SHORTCUT &&
```

```
101 |         (event.metaKey || event.ctrlKey)
102 |       ) {
103 |         event.preventDefault()
104 |         toggleSidebar()
105 |       }
106 |     }
107 |
108 |     window.addEventListener("keydown", handleKeyDown)
109 |     return () => window.removeEventListener("keydown", handleKeyDown)
110 |   }, [toggleSidebar])
111 |
112 |   // We add a state so that we can do data-state="expanded" or "collapsed".
113 |   // This makes it easier to style the sidebar with Tailwind classes.
114 |   const state = open ? "expanded" : "collapsed"
115 |
116 |   const contextValue = React.useMemo<SidebarContextProps>(
117 |     () => ({
118 |       state,
119 |       open,
120 |       setOpen,
121 |       isMobile,
122 |       openMobile,
123 |       setOpenMobile,
124 |       toggleSidebar,
125 |     }),
126 |     [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar]
127 |   )
128 |
129 |   return (
130 |     <SidebarContext.Provider value={contextValue}>
131 |       <TooltipProvider delayDuration={0}>
132 |         <div
133 |           data-slot="sidebar-wrapper"
134 |           style={
135 |             {
136 |               "--sidebar-width": SIDEBAR_WIDTH,
137 |               "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
138 |               ...style,
139 |             } as React.CSSProperties
140 |           }
141 |           className={cn(
142 |             "group/sidebar-wrapper has-data-[variant=inset]:bg-sidebar flex min-h-svh w-full",
143 |             className
144 |           )}
145 |           {...props}
146 |         >
147 |           {children}
148 |         </div>
149 |       </TooltipProvider>
150 |     </SidebarContext.Provider>
151 |   )
152 | }
153 |
154 | function Sidebar({
155 |   side = "left",
156 |   variant = "sidebar",
157 |   collapsible = "offcanvas",
158 |   className,
159 |   children,
160 |   ...props
161 | }: React.ComponentProps<"div"> & {
162 |   side?: "left" | "right"
163 |   variant?: "sidebar" | "floating" | "inset"
164 |   collapsible?: "offcanvas" | "icon" | "none"
165 | }) {
166 |   const { isMobile, state, openMobile, setOpenMobile } = useSidebar()
167 |
168 |   if (collapsible === "none") {
169 |     return (
170 |       <div
171 |         data-slot="sidebar"
172 |         className={cn(
173 |           "bg-sidebar text-sidebar-foreground flex h-full w-[var(--sidebar-width)] flex-col",
174 |           className
175 |         )}
176 |         {...props}
177 |       >
178 |         {children}
179 |       </div>
180 |     )
181 |   }
182 |
183 |   if (isMobile) {
184 |     return (
185 |       <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>
186 |         <SheetContent
187 |           data-sidebar="sidebar"
188 |           data-slot="sidebar"
189 |           data-mobile="true"
190 |           className="bg-sidebar text-sidebar-foreground w-[var(--sidebar-width)] p-0 [&>button]:hidden"
191 |           style={
192 |             {
193 |               "--sidebar-width": SIDEBAR_WIDTH_MOBILE,
194 |             } as React.CSSProperties
195 |           }
196 |           side={side}
197 |         >
198 |           <SheetHeader className="sr-only">
199 |             <SheetTitle>Sidebar</SheetTitle>
200 |             <SheetDescription>Displays the mobile sidebar.</SheetDescription>
201 |           </SheetHeader>
202 |           <div className="flex h-full w-full flex-col">{children}</div>
203 |         </SheetContent>
```

```
 204 |       </Sheet>
 205 |     )
 206 |   }
 207 |
 208 |   return (
 209 |     <div
 210 |       className="group peer text-sidebar-foreground hidden md:block"
 211 |       data-state={state}
 212 |       data-collapsible={state === "collapsed" ? collapsible : ""}
 213 |       data-variant={variant}
 214 |       data-side={side}
 215 |       data-slot="sidebar"
 216 |     >
 217 |       {/* This is what handles the sidebar gap on desktop */}
 218 |       <div
 219 |         data-slot="sidebar-gap"
 220 |         className={cn(
 221 |           "relative w-[var(--sidebar-width)] bg-transparent transition-[width] duration-200 ease-linear",
 222 |           "group-data-[collapsible=offcanvas]:w-0",
 223 |           "group-data-[side=right]:rotate-180",
 224 |           variant === "floating" || variant === "inset"
 225 |             ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4))]"
 226 |             : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)]"
 227 |         )}
 228 |       />
 229 |       <div
 230 |         data-slot="sidebar-container"
 231 |         className={cn(
 232 |           "fixed inset-y-0 z-10 hidden h-svh w-[var(--sidebar-width)] transition-[left,right,width] duration-200
ease-linear md:flex",
 233 |           side === "left"
 234 |             ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
 235 |             : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar-width)*-1)]",
 236 |           // Adjust the padding for floating and inset variants.
 237 |           variant === "floating" || variant === "inset"
 238 |             ? "p-2 group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4)+2px)]"
 239 |             : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)] group-data-[side=left]:border-r group-
data-[side=right]:border-l",
 240 |           className
 241 |         )}
 242 |         {...props}
 243 |       >
 244 |         <div
 245 |           data-sidebar="sidebar"
 246 |           data-slot="sidebar-inner"
 247 |           className="bg-sidebar group-data-[variant=floating]:border-sidebar-border flex h-full w-full flex-col
group-data-[variant=floating]:rounded-lg grou...
 248 |         >
 249 |           {children}
 250 |         </div>
 251 |       </div>
 252 |     </div>
 253 |   )
 254 | }
 255 |
 256 | function SidebarTrigger({
 257 |   className,
 258 |   onClick,
 259 |   ...props
 260 | }: React.ComponentProps<typeof Button>) {
 261 |   const { toggleSidebar } = useSidebar()
 262 |
 263 |   return (
 264 |     <Button
 265 |       data-sidebar="trigger"
 266 |       data-slot="sidebar-trigger"
 267 |       variant="ghost"
 268 |       size="icon"
 269 |       className={cn("h-7 w-7", className)}
 270 |       onClick={(event) => {
 271 |         onClick?.(event)
 272 |         toggleSidebar()
 273 |       }}
 274 |       {...props}
 275 |     >
 276 |       <PanelLeftIcon />
 277 |       <span className="sr-only">Toggle Sidebar</span>
 278 |     </Button>
 279 |   )
 280 | }
 281 |
 282 | function SidebarRail({ className, ...props }: React.ComponentProps<"button">) {
 283 |   const { toggleSidebar } = useSidebar()
 284 |
 285 |   // Note: Tailwind v3.4 doesn't support "in-" selectors. So the rail won't work perfectly.
 286 |   return (
 287 |     <button
 288 |       data-sidebar="rail"
 289 |       data-slot="sidebar-rail"
 290 |       aria-label="Toggle Sidebar"
 291 |       tabIndex={-1}
 292 |       onClick={toggleSidebar}
 293 |       title="Toggle Sidebar"
 294 |       className={cn(
 295 |         "hover:after:bg-sidebar-border absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-
linear group-data-[side=left]:-right-4 group-d...
 296 |         "in-data-[side=left]:cursor-w-resize in-data-[side=right]:cursor-e-resize",
 297 |         "[[data-side=left][data-state=collapsed]_&]:cursor-e-resize [[data-side=right][data-
state=collapsed]_&]:cursor-w-resize",
 298 |         "hover:group-data-[collapsible=offcanvas]:bg-sidebar group-data-[collapsible=offcanvas]:translate-x-0
group-data-[collapsible=offcanvas]:after:left-f...
 299 |         "[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",
 300 |         "[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
```

```
301 |         className
302 |       )}
303 |       {...props}
304 |     />
305 |   )
306 | }
307 |
308 | function SidebarInset({ className, ...props }: React.ComponentProps<"main">) {
309 |   return (
310 |     <main
311 |       data-slot="sidebar-inset"
312 |       className={cn(
313 |         "bg-background relative flex w-full flex-1 flex-col",
314 |         "md:peer-data-[variant=inset]:m-2 md:peer-data-[variant=inset]:ml-0 md:peer-data-[variant=inset]:rounded-
xl md:peer-data-[variant=inset]:shadow-sm md...
315 |         className
316 |       )}
317 |       {...props}
318 |     />
319 |   )
320 | }
321 |
322 | function SidebarInput({
323 |   className,
324 |   ...props
325 | }: React.ComponentProps<typeof Input>) {
326 |   return (
327 |     <Input
328 |       data-slot="sidebar-input"
329 |       data-sidebar="input"
330 |       className={cn("bg-background h-8 w-full shadow-none", className)}
331 |       {...props}
332 |     />
333 |   )
334 | }
335 |
336 | function SidebarHeader({ className, ...props }: React.ComponentProps<"div">) {
337 |   return (
338 |     <div
339 |       data-slot="sidebar-header"
340 |       data-sidebar="header"
341 |       className={cn("flex flex-col gap-2 p-2", className)}
342 |       {...props}
343 |     />
344 |   )
345 | }
346 |
347 | function SidebarFooter({ className, ...props }: React.ComponentProps<"div">) {
348 |   return (
349 |     <div
350 |       data-slot="sidebar-footer"
351 |       data-sidebar="footer"
352 |       className={cn("flex flex-col gap-2 p-2", className)}
353 |       {...props}
354 |     />
355 |   )
356 | }
357 |
358 | function SidebarSeparator({
359 |   className,
360 |   ...props
361 | }: React.ComponentProps<typeof Separator>) {
362 |   return (
363 |     <Separator
364 |       data-slot="sidebar-separator"
365 |       data-sidebar="separator"
366 |       className={cn("bg-sidebar-border mx-2 w-auto", className)}
367 |       {...props}
368 |     />
369 |   )
370 | }
371 |
372 | function SidebarContent({ className, ...props }: React.ComponentProps<"div">) {
373 |   return (
374 |     <div
375 |       data-slot="sidebar-content"
376 |       data-sidebar="content"
377 |       className={cn(
378 |         "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-hidden",
379 |         className
380 |       )}
381 |       {...props}
382 |     />
383 |   )
384 | }
385 |
386 | function SidebarGroup({ className, ...props }: React.ComponentProps<"div">) {
387 |   return (
388 |     <div
389 |       data-slot="sidebar-group"
390 |       data-sidebar="group"
391 |       className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
392 |       {...props}
393 |     />
394 |   )
395 | }
396 |
397 | function SidebarGroupLabel({
398 |   className,
399 |   asChild = false,
400 |   ...props
401 | }: React.ComponentProps<"div"> & { asChild?: boolean }) {
402 |   const Comp = asChild ? Slot : "div"
```

```
403 |
404 |   return (
405 |     <Comp
406 |       data-slot="sidebar-group-label"
407 |       data-sidebar="group-label"
408 |       className={cn(
409 |         "text-sidebar-foreground/70 ring-sidebar-ring flex h-8 shrink-0 items-center rounded-md px-2 text-xs font-
medium outline-hidden transition-[margin,op...
410 |         "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",
411 |         className
412 |       )}
413 |       {...props}
414 |     />
415 |   )
416 | }
417 |
418 | function SidebarGroupAction({
419 |   className,
420 |   asChild = false,
421 |   ...props
422 | }: React.ComponentProps<"button"> & { asChild?: boolean }) {
423 |   const Comp = asChild ? Slot : "button"
424 |
425 |   return (
426 |     <Comp
427 |       data-slot="sidebar-group-action"
428 |       data-sidebar="group-action"
429 |       className={cn(
430 |         "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
absolute top-3.5 right-3 flex aspect-square w...
431 |         // Increases the hit area of the button on mobile.
432 |         "after:absolute after:-inset-2 md:after:hidden",
433 |         "group-data-[collapsible=icon]:hidden",
434 |         className
435 |       )}
436 |       {...props}
437 |     />
438 |   )
439 | }
440 |
441 | function SidebarGroupContent({
442 |   className,
443 |   ...props
444 | }: React.ComponentProps<"div">) {
445 |   return (
446 |     <div
447 |       data-slot="sidebar-group-content"
448 |       data-sidebar="group-content"
449 |       className={cn("w-full text-sm", className)}
450 |       {...props}
451 |     />
452 |   )
453 | }
454 |
455 | function SidebarMenu({ className, ...props }: React.ComponentProps<"ul">) {
456 |   return (
457 |     <ul
458 |       data-slot="sidebar-menu"
459 |       data-sidebar="menu"
460 |       className={cn("flex w-full min-w-0 flex-col gap-1", className)}
461 |       {...props}
462 |     />
463 |   )
464 | }
465 |
466 | function SidebarMenuItem({ className, ...props }: React.ComponentProps<"li">) {
467 |   return (
468 |     <li
469 |       data-slot="sidebar-menu-item"
470 |       data-sidebar="menu-item"
471 |       className={cn("group/menu-item relative", className)}
472 |       {...props}
473 |     />
474 |   )
475 | }
476 |
477 | const sidebarMenuButtonVariants = cva(
478 |   "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left text-sm outline-hidden
ring-sidebar-ring transition-[width,height...
479 |   {
480 |     variants: {
481 |       variant: {
482 |         default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
483 |         outline:
484 |           "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent hover:text-sidebar-
accent-foreground hover:shadow-[0_0_0_1px_h...
485 |       },
486 |       size: {
487 |         default: "h-8 text-sm",
488 |         sm: "h-7 text-xs",
489 |         lg: "h-12 text-sm group-data-[collapsible=icon]:p-0!",
490 |       },
491 |     },
492 |     defaultVariants: {
493 |       variant: "default",
494 |       size: "default",
495 |     },
496 |   }
497 | )
498 |
499 | function SidebarMenuButton({
500 |   asChild = false,
501 |   isActive = false,
```

```
  variant = "default",
  size = "default",
  tooltip,
  className,
  ...props
}: React.ComponentProps<"button"> & {
  asChild?: boolean
  isActive?: boolean
  tooltip?: string | React.ComponentProps<typeof TooltipContent>
} & VariantProps<typeof sidebarMenuButtonVariants>) {
  const Comp = asChild ? Slot : "button"
  const { isMobile, state } = useSidebar()

  const button = (
    <Comp
      data-slot="sidebar-menu-button"
      data-sidebar="menu-button"
      data-size={size}
      data-active={isActive}
      className={cn(sidebarMenuButtonVariants({ variant, size }), className)}
      {...props}
    />
  )

  if (!tooltip) {
    return button
  }

  if (typeof tooltip === "string") {
    tooltip = {
      children: tooltip,
    }
  }

  return (
    <Tooltip>
      <TooltipTrigger asChild>{button}</TooltipTrigger>
      <TooltipContent
        side="right"
        align="center"
        hidden={state !== "collapsed" || isMobile}
        {...tooltip}
      />
    </Tooltip>
  )
}

function SidebarMenuAction({
  className,
  asChild = false,
  showOnHover = false,
  ...props
}: React.ComponentProps<"button"> & {
  asChild?: boolean
  showOnHover?: boolean
}) {
  const Comp = asChild ? Slot : "button"

  return (
    <Comp
      data-slot="sidebar-menu-action"
      data-sidebar="menu-action"
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground peer-hover/menu-button:text-sidebar-accent-fo...
        // Increases the hit area of the button on mobile.
        "after:absolute after:-inset-2 md:after:hidden",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        showOnHover &&
          "peer-data-[active=true]/menu-button:text-sidebar-accent-foreground group-focus-within/menu-item:opacity-100 group-hover/menu-item:opacity-100 data...
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuBadge({
  className,
  ...props
}: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-menu-badge"
      data-sidebar="menu-badge"
      className={cn(
        "text-sidebar-foreground pointer-events-none absolute right-1 flex h-5 min-w-5 items-center justify-center rounded-md px-1 text-xs font-medium tabula...
        "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-button:text-sidebar-accent-foreground",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
```

```
601 | }
602 |
603 | function SidebarMenuSkeleton({
604 |   className,
605 |   showIcon = false,
606 |   ...props
607 | }: React.ComponentProps<"div"> & {
608 |   showIcon?: boolean
609 | }) {
610 |   // Random width between 50 to 90%.
611 |   const width = React.useMemo(() => {
612 |     return `${Math.floor(Math.random() * 40) + 50}%`
613 |   }, [])
614 |
615 |   return (
616 |     <div
617 |       data-slot="sidebar-menu-skeleton"
618 |       data-sidebar="menu-skeleton"
619 |       className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
620 |       {...props}
621 |     >
622 |       {showIcon && (
623 |         <Skeleton
624 |           className="size-4 rounded-md"
625 |           data-sidebar="menu-skeleton-icon"
626 |         />
627 |       )}
628 |       <Skeleton
629 |         className="h-4 max-w-[var(--skeleton-width)] flex-1"
630 |         data-sidebar="menu-skeleton-text"
631 |         style={
632 |           {
633 |             "--skeleton-width": width,
634 |           } as React.CSSProperties
635 |         }
636 |       />
637 |     </div>
638 |   )
639 | }
640 |
641 | function SidebarMenuSub({ className, ...props }: React.ComponentProps<"ul">) {
642 |   return (
643 |     <ul
644 |       data-slot="sidebar-menu-sub"
645 |       data-sidebar="menu-sub"
646 |       className={cn(
647 |         "border-sidebar-border mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-l px-2.5 py-0.5",
648 |         "group-data-[collapsible=icon]:hidden",
649 |         className
650 |       )}
651 |       {...props}
652 |     />
653 |   )
654 | }
655 |
656 | function SidebarMenuSubItem({
657 |   className,
658 |   ...props
659 | }: React.ComponentProps<"li">) {
660 |   return (
661 |     <li
662 |       data-slot="sidebar-menu-sub-item"
663 |       data-sidebar="menu-sub-item"
664 |       className={cn("group/menu-sub-item relative", className)}
665 |       {...props}
666 |     />
667 |   )
668 | }
669 |
670 | function SidebarMenuSubButton({
671 |   asChild = false,
672 |   size = "md",
673 |   isActive = false,
674 |   className,
675 |   ...props
676 | }: React.ComponentProps<"a"> & {
677 |   asChild?: boolean
678 |   size?: "sm" | "md"
679 |   isActive?: boolean
680 | }) {
681 |   const Comp = asChild ? Slot : "a"
682 |
683 |   return (
684 |     <Comp
685 |       data-slot="sidebar-menu-sub-button"
686 |       data-sidebar="menu-sub-button"
687 |       data-size={size}
688 |       data-active={isActive}
689 |       className={cn(
690 |         "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
active:bg-sidebar-accent active:text-sidebar-...
691 |         "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-foreground",
692 |         size === "sm" && "text-xs",
693 |         size === "md" && "text-sm",
694 |         "group-data-[collapsible=icon]:hidden",
695 |         className
696 |       )}
697 |       {...props}
698 |     />
699 |   )
700 | }
701 |
702 | export {
```

```
  Sidebar,
  SidebarContent,
  SidebarFooter,
  SidebarGroup,
  SidebarGroupAction,
  SidebarGroupContent,
  SidebarGroupLabel,
  SidebarHeader,
  SidebarInput,
  SidebarInset,
  SidebarMenu,
  SidebarMenuAction,
  SidebarMenuBadge,
  SidebarMenuButton,
  SidebarMenuItem,
  SidebarMenuSkeleton,
  SidebarMenuSub,
  SidebarMenuSubButton,
  SidebarMenuSubItem,
  SidebarProvider,
  SidebarRail,
  SidebarSeparator,
  SidebarTrigger,
  useSidebar,
}
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/skeleton.tsx

```
 1 | import { cn } from "@/lib/utils"
 2 |
 3 | function Skeleton({
 4 |   className,
 5 |   ...props
 6 | }: React.HTMLAttributes<HTMLDivElement>) {
 7 |   return (
 8 |     <div
 9 |       className={cn("animate-pulse rounded-md bg-primary/10", className)}
10 |       {...props}
11 |     />
12 |   )
13 | }
14 |
15 | export { Skeleton }
16 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/slider.tsx

```
   1 | import * as React from "react"
   2 | import * as SliderPrimitive from "@radix-ui/react-slider"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const Slider = React.forwardRef<
   7 |   React.ElementRef<typeof SliderPrimitive.Root>,
   8 |   React.ComponentPropsWithoutRef<typeof SliderPrimitive.Root>
   9 | >(({ className, ...props }, ref) => (
  10 |   <SliderPrimitive.Root
  11 |     ref={ref}
  12 |     className={cn(
  13 |       "relative flex w-full touch-none select-none items-center",
  14 |       className
  15 |     )}
  16 |     {...props}
  17 |   >
  18 |     <SliderPrimitive.Track className="relative h-1.5 w-full grow overflow-hidden rounded-full bg-primary/20">
  19 |       <SliderPrimitive.Range className="absolute h-full bg-primary" />
  20 |     </SliderPrimitive.Track>
  21 |     <SliderPrimitive.Thumb className="block h-4 w-4 rounded-full border border-primary/50 bg-background shadow
transition-colors focus-visible:outline-none f...
  22 |   </SliderPrimitive.Root>
  23 | ))
  24 | Slider.displayName = SliderPrimitive.Root.displayName
  25 |
  26 | export { Slider }
  27 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/sonner.tsx

```
   1 | "use client"
   2 |
   3 | import { useTheme } from "next-themes"
   4 | import { Toaster as Sonner } from "sonner"
   5 |
   6 | type ToasterProps = React.ComponentProps<typeof Sonner>
   7 |
   8 | const Toaster = ({ ...props }: ToasterProps) => {
   9 |   const { theme = "system" } = useTheme()
  10 |
  11 |   return (
  12 |     <Sonner
  13 |       theme={theme as ToasterProps["theme"]}
  14 |       className="toaster group"
  15 |       toastOptions={{
  16 |         classNames: {
  17 |           toast:
  18 |             "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-[.toaster]:border-
border group-[.toaster]:shadow-lg",
  19 |           description: "group-[.toast]:text-muted-foreground",
  20 |           actionButton:
  21 |             "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",
  22 |           cancelButton:
  23 |             "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",
  24 |         },
  25 |       }}
  26 |       {...props}
  27 |     />
  28 |   )
  29 | }
  30 |
  31 | export { Toaster }
  32 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/spinner.tsx

```
 1 | import { Loader2Icon } from "lucide-react"
 2 |
 3 | import { cn } from "@/lib/utils"
 4 |
 5 | function Spinner({ className, ...props }: React.ComponentProps<"svg">) {
 6 |   return (
 7 |     <Loader2Icon
 8 |       role="status"
 9 |       aria-label="Loading"
10 |       className={cn("size-4 animate-spin", className)}
11 |       {...props}
12 |     />
13 |   )
14 | }
15 |
16 | export { Spinner }
17 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/switch.tsx

```
   1 | import * as React from "react"
   2 | import * as SwitchPrimitives from "@radix-ui/react-switch"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const Switch = React.forwardRef<
   7 |   React.ElementRef<typeof SwitchPrimitives.Root>,
   8 |   React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
   9 | >(({ className, ...props }, ref) => (
  10 |   <SwitchPrimitives.Root
  11 |     className={cn(
  12 |       "peer inline-flex h-5 w-9 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent
shadow-sm transition-colors focus-visible:outli...
  13 |       className
  14 |     )}
  15 |     {...props}
  16 |     ref={ref}
  17 |   >
  18 |     <SwitchPrimitives.Thumb
  19 |       className={cn(
  20 |         "pointer-events-none block h-4 w-4 rounded-full bg-background shadow-lg ring-0 transition-transform data-
[state=checked]:translate-x-4 data-[state=un...
  21 |       )}
  22 |     />
  23 |   </SwitchPrimitives.Root>
  24 | ))
  25 | Switch.displayName = SwitchPrimitives.Root.displayName
  26 |
  27 | export { Switch }
  28 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/table.tsx

```
   1 | import * as React from "react"
   2 |
   3 | import { cn } from "@/lib/utils"
   4 |
   5 | const Table = React.forwardRef<
   6 |   HTMLTableElement,
   7 |   React.HTMLAttributes<HTMLTableElement>
   8 | >(({ className, ...props }, ref) => (
   9 |   <div className="relative w-full overflow-auto">
  10 |     <table
  11 |       ref={ref}
  12 |       className={cn("w-full caption-bottom text-sm", className)}
  13 |       {...props}
  14 |     />
  15 |   </div>
  16 | ))
  17 | Table.displayName = "Table"
  18 |
  19 | const TableHeader = React.forwardRef<
  20 |   HTMLTableSectionElement,
  21 |   React.HTMLAttributes<HTMLTableSectionElement>
  22 | >(({ className, ...props }, ref) => (
  23 |   <thead ref={ref} className={cn("[&_tr]:border-b", className)} {...props} />
  24 | ))
  25 | TableHeader.displayName = "TableHeader"
  26 |
  27 | const TableBody = React.forwardRef<
  28 |   HTMLTableSectionElement,
  29 |   React.HTMLAttributes<HTMLTableSectionElement>
  30 | >(({ className, ...props }, ref) => (
  31 |   <tbody
  32 |     ref={ref}
  33 |     className={cn("[&_tr:last-child]:border-0", className)}
  34 |     {...props}
  35 |   />
  36 | ))
  37 | TableBody.displayName = "TableBody"
  38 |
  39 | const TableFooter = React.forwardRef<
  40 |   HTMLTableSectionElement,
  41 |   React.HTMLAttributes<HTMLTableSectionElement>
  42 | >(({ className, ...props }, ref) => (
  43 |   <tfoot
  44 |     ref={ref}
  45 |     className={cn(
  46 |       "border-t bg-muted/50 font-medium [&>tr]:last:border-b-0",
  47 |       className
  48 |     )}
  49 |     {...props}
  50 |   />
  51 | ))
  52 | TableFooter.displayName = "TableFooter"
  53 |
  54 | const TableRow = React.forwardRef<
  55 |   HTMLTableRowElement,
  56 |   React.HTMLAttributes<HTMLTableRowElement>
  57 | >(({ className, ...props }, ref) => (
  58 |   <tr
  59 |     ref={ref}
  60 |     className={cn(
  61 |       "border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted",
  62 |       className
  63 |     )}
  64 |     {...props}
  65 |   />
  66 | ))
  67 | TableRow.displayName = "TableRow"
  68 |
  69 | const TableHead = React.forwardRef<
  70 |   HTMLTableCellElement,
  71 |   React.ThHTMLAttributes<HTMLTableCellElement>
  72 | >(({ className, ...props }, ref) => (
  73 |   <th
  74 |     ref={ref}
  75 |     className={cn(
  76 |       "h-10 px-2 text-left align-middle font-medium text-muted-foreground [&:has([role=checkbox])]:pr-0
[&>[role=checkbox]]:translate-y-[2px]",
  77 |       className
  78 |     )}
  79 |     {...props}
  80 |   />
  81 | ))
  82 | TableHead.displayName = "TableHead"
  83 |
  84 | const TableCell = React.forwardRef<
  85 |   HTMLTableCellElement,
  86 |   React.TdHTMLAttributes<HTMLTableCellElement>
  87 | >(({ className, ...props }, ref) => (
  88 |   <td
  89 |     ref={ref}
  90 |     className={cn(
  91 |       "p-2 align-middle [&:has([role=checkbox])]:pr-0 [&>[role=checkbox]]:translate-y-[2px]",
  92 |       className
  93 |     )}
  94 |     {...props}
  95 |   />
  96 | ))
  97 | TableCell.displayName = "TableCell"
  98 |
  99 | const TableCaption = React.forwardRef<
```

```
100 |   HTMLTableCaptionElement,
101 |   React.HTMLAttributes<HTMLTableCaptionElement>
102 | >(({ className, ...props }, ref) => (
103 |   <caption
104 |     ref={ref}
105 |     className={cn("mt-4 text-sm text-muted-foreground", className)}
106 |     {...props}
107 |   />
108 | ))
109 | TableCaption.displayName = "TableCaption"
110 |
111 | export {
112 |   Table,
113 |   TableHeader,
114 |   TableBody,
115 |   TableFooter,
116 |   TableHead,
117 |   TableRow,
118 |   TableCell,
119 |   TableCaption,
120 | }
121 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/tabs.tsx

```
   1 | import * as React from "react"
   2 | import * as TabsPrimitive from "@radix-ui/react-tabs"
   3 |
   4 | import { cn } from "@/lib/utils"
   5 |
   6 | const Tabs = TabsPrimitive.Root
   7 |
   8 | const TabsList = React.forwardRef<
   9 |   React.ElementRef<typeof TabsPrimitive.List>,
  10 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
  11 | >(({ className, ...props }, ref) => (
  12 |   <TabsPrimitive.List
  13 |     ref={ref}
  14 |     className={cn(
  15 |       "inline-flex h-9 items-center justify-center rounded-lg bg-muted p-1 text-muted-foreground",
  16 |       className
  17 |     )}
  18 |     {...props}
  19 |   />
  20 | ))
  21 | TabsList.displayName = TabsPrimitive.List.displayName
  22 |
  23 | const TabsTrigger = React.forwardRef<
  24 |   React.ElementRef<typeof TabsPrimitive.Trigger>,
  25 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
  26 | >(({ className, ...props }, ref) => (
  27 |   <TabsPrimitive.Trigger
  28 |     ref={ref}
  29 |     className={cn(
  30 |       "inline-flex items-center justify-center whitespace-nowrap rounded-md px-3 py-1 text-sm font-medium ring-
offset-background transition-all focus-visible...
  31 |       className
  32 |     )}
  33 |     {...props}
  34 |   />
  35 | ))
  36 | TabsTrigger.displayName = TabsPrimitive.Trigger.displayName
  37 |
  38 | const TabsContent = React.forwardRef<
  39 |   React.ElementRef<typeof TabsPrimitive.Content>,
  40 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>
  41 | >(({ className, ...props }, ref) => (
  42 |   <TabsPrimitive.Content
  43 |     ref={ref}
  44 |     className={cn(
  45 |       "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-
visible:ring-offset-2",
  46 |       className
  47 |     )}
  48 |     {...props}
  49 |   />
  50 | ))
  51 | TabsContent.displayName = TabsPrimitive.Content.displayName
  52 |
  53 | export { Tabs, TabsList, TabsTrigger, TabsContent }
  54 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/textarea.tsx

```
   1 | import * as React from "react"
   2 |
   3 | import { cn } from "@/lib/utils"
   4 |
   5 | const Textarea = React.forwardRef<
   6 |   HTMLTextAreaElement,
   7 |   React.ComponentProps<"textarea">
   8 | >(({ className, ...props }, ref) => {
   9 |   return (
  10 |     <textarea
  11 |       className={cn(
  12 |         "flex min-h-[60px] w-full rounded-md border border-input bg-transparent px-3 py-2 text-base shadow-sm
placeholder:text-muted-foreground focus-visible...
  13 |         className
  14 |       )}
  15 |       ref={ref}
  16 |       {...props}
  17 |     />
  18 |   )
  19 | })
  20 | Textarea.displayName = "Textarea"
  21 |
  22 | export { Textarea }
  23 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/toast.tsx

```
   1 | import * as React from "react"
   2 | import * as ToastPrimitives from "@radix-ui/react-toast"
   3 | import { cva, type VariantProps } from "class-variance-authority"
   4 | import { X } from "lucide-react"
   5 |
   6 | import { cn } from "@/lib/utils"
   7 |
   8 | const ToastProvider = ToastPrimitives.Provider
   9 |
  10 | const ToastViewport = React.forwardRef<
  11 |   React.ElementRef<typeof ToastPrimitives.Viewport>,
  12 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
  13 | >(({ className, ...props }, ref) => (
  14 |   <ToastPrimitives.Viewport
  15 |     ref={ref}
  16 |     className={cn(
  17 |       "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto
sm:flex-col md:max-w-[420px]",
  18 |       className
  19 |     )}
  20 |     {...props}
  21 |   />
  22 | ))
  23 | ToastViewport.displayName = ToastPrimitives.Viewport.displayName
  24 |
  25 | const toastVariants = cva(
  26 |   "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden rounded-
md border p-6 pr-8 shadow-lg transition-all ...
  27 |   {
  28 |     variants: {
  29 |       variant: {
  30 |         default: "border bg-background text-foreground",
  31 |         destructive:
  32 |           "destructive group border-destructive bg-destructive text-destructive-foreground",
  33 |       },
  34 |     },
  35 |     defaultVariants: {
  36 |       variant: "default",
  37 |     },
  38 |   }
  39 | )
  40 |
  41 | const Toast = React.forwardRef<
  42 |   React.ElementRef<typeof ToastPrimitives.Root>,
  43 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &
  44 |     VariantProps<typeof toastVariants>
  45 | >(({ className, variant, ...props }, ref) => {
  46 |   return (
  47 |     <ToastPrimitives.Root
  48 |       ref={ref}
  49 |       className={cn(toastVariants({ variant }), className)}
  50 |       {...props}
  51 |     />
  52 |   )
  53 | })
  54 | Toast.displayName = ToastPrimitives.Root.displayName
  55 |
  56 | const ToastAction = React.forwardRef<
  57 |   React.ElementRef<typeof ToastPrimitives.Action>,
  58 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
  59 | >(({ className, ...props }, ref) => (
  60 |   <ToastPrimitives.Action
  61 |     ref={ref}
  62 |     className={cn(
  63 |       "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm font-
medium ring-offset-background transition-color...
  64 |       className
  65 |     )}
  66 |     {...props}
  67 |   />
  68 | ))
  69 | ToastAction.displayName = ToastPrimitives.Action.displayName
  70 |
  71 | const ToastClose = React.forwardRef<
  72 |   React.ElementRef<typeof ToastPrimitives.Close>,
  73 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
  74 | >(({ className, ...props }, ref) => (
  75 |   <ToastPrimitives.Close
  76 |     ref={ref}
  77 |     className={cn(
  78 |       "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity hover:text-foreground
focus:opacity-100 focus:outline-none focus...
  79 |       className
  80 |     )}
  81 |     toast-close=""
  82 |     {...props}
  83 |   >
  84 |     <X className="h-4 w-4" />
  85 |   </ToastPrimitives.Close>
  86 | ))
  87 | ToastClose.displayName = ToastPrimitives.Close.displayName
  88 |
  89 | const ToastTitle = React.forwardRef<
  90 |   React.ElementRef<typeof ToastPrimitives.Title>,
  91 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
  92 | >(({ className, ...props }, ref) => (
  93 |   <ToastPrimitives.Title
  94 |     ref={ref}
  95 |     className={cn("text-sm font-semibold", className)}
  96 |     {...props}
```

```
 97 |   />
 98 | ))
 99 | ToastTitle.displayName = ToastPrimitives.Title.displayName
100 |
101 | const ToastDescription = React.forwardRef<
102 |   React.ElementRef<typeof ToastPrimitives.Description>,
103 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
104 | >(({ className, ...props }, ref) => (
105 |   <ToastPrimitives.Description
106 |     ref={ref}
107 |     className={cn("text-sm opacity-90", className)}
108 |     {...props}
109 |   />
110 | ))
111 | ToastDescription.displayName = ToastPrimitives.Description.displayName
112 |
113 | type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>
114 |
115 | type ToastActionElement = React.ReactElement<typeof ToastAction>
116 |
117 | export {
118 |   type ToastProps,
119 |   type ToastActionElement,
120 |   ToastProvider,
121 |   ToastViewport,
122 |   Toast,
123 |   ToastTitle,
124 |   ToastDescription,
125 |   ToastClose,
126 |   ToastAction,
127 | }
128 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/toaster.tsx

```
 1 | import { useToast } from "@/hooks/use-toast"
 2 | import {
 3 |   Toast,
 4 |   ToastClose,
 5 |   ToastDescription,
 6 |   ToastProvider,
 7 |   ToastTitle,
 8 |   ToastViewport,
 9 | } from "@/components/ui/toast"
10 |
11 | export function Toaster() {
12 |   const { toasts } = useToast()
13 |
14 |   return (
15 |     <ToastProvider>
16 |       {toasts.map(function ({ id, title, description, action, ...props }) {
17 |         return (
18 |           <Toast key={id} {...props}>
19 |             <div className="grid gap-1">
20 |               {title && <ToastTitle>{title}</ToastTitle>}
21 |               {description && (
22 |                 <ToastDescription>{description}</ToastDescription>
23 |               )}
24 |             </div>
25 |             {action}
26 |             <ToastClose />
27 |           </Toast>
28 |         )
29 |       })}
30 |       <ToastViewport />
31 |     </ToastProvider>
32 |   )
33 | }
34 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/toggle-group.tsx

```
"use client"

import * as React from "react"
import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group"
import { type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { toggleVariants } from "@/components/ui/toggle"

const ToggleGroupContext = React.createContext<
  VariantProps<typeof toggleVariants>
>({
  size: "default",
  variant: "default",
})

const ToggleGroup = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Root> &
    VariantProps<typeof toggleVariants>
>(({ className, variant, size, children, ...props }, ref) => (
  <ToggleGroupPrimitive.Root
    ref={ref}
    className={cn("flex items-center justify-center gap-1", className)}
    {...props}
  >
    <ToggleGroupContext.Provider value={{ variant, size }}>
      {children}
    </ToggleGroupContext.Provider>
  </ToggleGroupPrimitive.Root>
))

ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName

const ToggleGroupItem = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Item> &
    VariantProps<typeof toggleVariants>
>(({ className, children, variant, size, ...props }, ref) => {
  const context = React.useContext(ToggleGroupContext)

  return (
    <ToggleGroupPrimitive.Item
      ref={ref}
      className={cn(
        toggleVariants({
          variant: context.variant || variant,
          size: context.size || size,
        }),
        className
      )}
      {...props}
    >
      {children}
    </ToggleGroupPrimitive.Item>
  )
})

ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName

export { ToggleGroup, ToggleGroupItem }

```

— end of file —

File: artifacts/mbc-platform/src/components/ui/toggle.tsx

```
   1 | import * as React from "react"
   2 | import * as TogglePrimitive from "@radix-ui/react-toggle"
   3 | import { cva, type VariantProps } from "class-variance-authority"
   4 |
   5 | import { cn } from "@/lib/utils"
   6 |
   7 | const toggleVariants = cva(
   8 |   "inline-flex items-center justify-center gap-2 rounded-md text-sm font-medium transition-colors hover:bg-muted
hover:text-muted-foreground focus-visible:ou...
   9 |   {
  10 |     variants: {
  11 |       variant: {
  12 |         default: "bg-transparent",
  13 |         outline:
  14 |           "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-foreground",
  15 |       },
  16 |       size: {
  17 |         default: "h-9 px-2 min-w-9",
  18 |         sm: "h-8 px-1.5 min-w-8",
  19 |         lg: "h-10 px-2.5 min-w-10",
  20 |       },
  21 |     },
  22 |     defaultVariants: {
  23 |       variant: "default",
  24 |       size: "default",
  25 |     },
  26 |   }
  27 | )
  28 |
  29 | const Toggle = React.forwardRef<
  30 |   React.ElementRef<typeof TogglePrimitive.Root>,
  31 |   React.ComponentPropsWithoutRef<typeof TogglePrimitive.Root> &
  32 |     VariantProps<typeof toggleVariants>
  33 | >(({ className, variant, size, ...props }, ref) => (
  34 |   <TogglePrimitive.Root
  35 |     ref={ref}
  36 |     className={cn(toggleVariants({ variant, size, className }))}
  37 |     {...props}
  38 |   />
  39 | ))
  40 |
  41 | Toggle.displayName = TogglePrimitive.Root.displayName
  42 |
  43 | export { Toggle, toggleVariants }
  44 |
```

— end of file —

File: artifacts/mbc-platform/src/components/ui/tooltip.tsx

```
   1 | "use client"
   2 |
   3 | import * as React from "react"
   4 | import * as TooltipPrimitive from "@radix-ui/react-tooltip"
   5 |
   6 | import { cn } from "@/lib/utils"
   7 |
   8 | const TooltipProvider = TooltipPrimitive.Provider
   9 |
  10 | const Tooltip = TooltipPrimitive.Root
  11 |
  12 | const TooltipTrigger = TooltipPrimitive.Trigger
  13 |
  14 | const TooltipContent = React.forwardRef<
  15 |   React.ElementRef<typeof TooltipPrimitive.Content>,
  16 |   React.ComponentPropsWithoutRef<typeof TooltipPrimitive.Content>
  17 | >(({ className, sideOffset = 4, ...props }, ref) => (
  18 |   <TooltipPrimitive.Portal>
  19 |     <TooltipPrimitive.Content
  20 |       ref={ref}
  21 |       sideOffset={sideOffset}
  22 |       className={cn(
  23 |         "z-50 overflow-hidden rounded-md bg-primary px-3 py-1.5 text-xs text-primary-foreground animate-in fade-
in-0 zoom-in-95 data-[state=closed]:animate-o...
  24 |         className
  25 |       )}
  26 |       {...props}
  27 |     />
  28 |   </TooltipPrimitive.Portal>
  29 | ))
  30 | TooltipContent.displayName = TooltipPrimitive.Content.displayName
  31 |
  32 | export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider }
  33 |
```

— end of file —

File: artifacts/mbc-platform/src/hooks/use-mobile.tsx

```
 1 | import * as React from "react"
 2 |
 3 | const MOBILE_BREAKPOINT = 768
 4 |
 5 | export function useIsMobile() {
 6 |   const [isMobile, setIsMobile] = React.useState<boolean | undefined>(undefined)
 7 |
 8 |   React.useEffect(() => {
 9 |     const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
10 |     const onChange = () => {
11 |       setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
12 |     }
13 |     mql.addEventListener("change", onChange)
14 |     setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
15 |     return () => mql.removeEventListener("change", onChange)
16 |   }, [])
17 |
18 |   return !!isMobile
19 | }
20 |
```

— end of file —

File: artifacts/mbc-platform/src/hooks/use-toast.ts

```
  1 | import * as React from "react"
  2 |
  3 | import type {
  4 |   ToastActionElement,
  5 |   ToastProps,
  6 | } from "@/components/ui/toast"
  7 |
  8 | const TOAST_LIMIT = 1
  9 | const TOAST_REMOVE_DELAY = 1000000
 10 |
 11 | type ToasterToast = ToastProps & {
 12 |   id: string
 13 |   title?: React.ReactNode
 14 |   description?: React.ReactNode
 15 |   action?: ToastActionElement
 16 | }
 17 |
 18 | const actionTypes = {
 19 |   ADD_TOAST: "ADD_TOAST",
 20 |   UPDATE_TOAST: "UPDATE_TOAST",
 21 |   DISMISS_TOAST: "DISMISS_TOAST",
 22 |   REMOVE_TOAST: "REMOVE_TOAST",
 23 | } as const
 24 |
 25 | let count = 0
 26 |
 27 | function genId() {
 28 |   count = (count + 1) % Number.MAX_SAFE_INTEGER
 29 |   return count.toString()
 30 | }
 31 |
 32 | type ActionType = typeof actionTypes
 33 |
 34 | type Action =
 35 |   | {
 36 |       type: ActionType["ADD_TOAST"]
 37 |       toast: ToasterToast
 38 |     }
 39 |   | {
 40 |       type: ActionType["UPDATE_TOAST"]
 41 |       toast: Partial<ToasterToast>
 42 |     }
 43 |   | {
 44 |       type: ActionType["DISMISS_TOAST"]
 45 |       toastId?: ToasterToast["id"]
 46 |     }
 47 |   | {
 48 |       type: ActionType["REMOVE_TOAST"]
 49 |       toastId?: ToasterToast["id"]
 50 |     }
 51 |
 52 | interface State {
 53 |   toasts: ToasterToast[]
 54 | }
 55 |
 56 | const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>()
 57 |
 58 | const addToRemoveQueue = (toastId: string) => {
 59 |   if (toastTimeouts.has(toastId)) {
 60 |     return
 61 |   }
 62 |
 63 |   const timeout = setTimeout(() => {
 64 |     toastTimeouts.delete(toastId)
 65 |     dispatch({
 66 |       type: "REMOVE_TOAST",
 67 |       toastId: toastId,
 68 |     })
 69 |   }, TOAST_REMOVE_DELAY)
 70 |
 71 |   toastTimeouts.set(toastId, timeout)
 72 | }
 73 |
 74 | export const reducer = (state: State, action: Action): State => {
 75 |   switch (action.type) {
 76 |     case "ADD_TOAST":
 77 |       return {
 78 |         ...state,
 79 |         toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
 80 |       }
 81 |
 82 |     case "UPDATE_TOAST":
 83 |       return {
 84 |         ...state,
 85 |         toasts: state.toasts.map((t) =>
 86 |           t.id === action.toast.id ? { ...t, ...action.toast } : t
 87 |         ),
 88 |       }
 89 |
 90 |     case "DISMISS_TOAST": {
 91 |       const { toastId } = action
 92 |
 93 |       // ! Side effects ! - This could be extracted into a dismissToast() action,
 94 |       // but I'll keep it here for simplicity
 95 |       if (toastId) {
 96 |         addToRemoveQueue(toastId)
 97 |       } else {
 98 |         state.toasts.forEach((toast) => {
 99 |           addToRemoveQueue(toast.id)
100 |         })
```

```
      }

      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === toastId || toastId === undefined
            ? {
                ...t,
                open: false,
              }
            : t
        ),
      }
    }
    case "REMOVE_TOAST":
      if (action.toastId === undefined) {
        return {
          ...state,
          toasts: [],
        }
      }
      return {
        ...state,
        toasts: state.toasts.filter((t) => t.id !== action.toastId),
      }
  }
}

const listeners: Array<(state: State) => void> = []

let memoryState: State = { toasts: [] }

function dispatch(action: Action) {
  memoryState = reducer(memoryState, action)
  listeners.forEach((listener) => {
    listener(memoryState)
  })
}

type Toast = Omit<ToasterToast, "id">

function toast({ ...props }: Toast) {
  const id = genId()

  const update = (props: ToasterToast) =>
    dispatch({
      type: "UPDATE_TOAST",
      toast: { ...props, id },
    })
  const dismiss = () => dispatch({ type: "DISMISS_TOAST", toastId: id })

  dispatch({
    type: "ADD_TOAST",
    toast: {
      ...props,
      id,
      open: true,
      onOpenChange: (open) => {
        if (!open) dismiss()
      },
    },
  })

  return {
    id: id,
    dismiss,
    update,
  }
}

function useToast() {
  const [state, setState] = React.useState<State>(memoryState)

  React.useEffect(() => {
    listeners.push(setState)
    return () => {
      const index = listeners.indexOf(setState)
      if (index > -1) {
        listeners.splice(index, 1)
      }
    }
  }, [state])

  return {
    ...state,
    toast,
    dismiss: (toastId?: string) => dispatch({ type: "DISMISS_TOAST", toastId }),
  }
}

export { useToast, toast }
```

— end of file —

File: artifacts/mbc-platform/src/lib/utils.ts

```
1 | import { clsx, type ClassValue } from "clsx"
2 | import { twMerge } from "tailwind-merge"
3 |
4 | export function cn(...inputs: ClassValue[]) {
5 |   return twMerge(clsx(inputs))
6 | }
7 |
```

— end of file —

File: artifacts/mbc-platform/src/main.tsx

```
1 | import { createRoot } from "react-dom/client";
2 | import App from "./App";
3 | import "./index.css";
4 |
5 | createRoot(document.getElementById("root")!).render(<App />);
6 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/about.tsx

```
   1 | import { Users, ShieldCheck, Heart, Target, ArrowRight } from "lucide-react";
   2 | import { Link } from "wouter";
   3 | import { Button } from "@/components/ui/button";
   4 |
   5 | export default function About() {
   6 |   return (
   7 |     <div className="bg-white">
   8 |
   9 |       {/* Hero Section */}
  10 |       <section className="relative pt-20 pb-24 overflow-hidden">
  11 |         <div className="absolute inset-0 z-0">
  12 |           <img
  13 |             src="/images/about.png"
  14 |             alt="Medical team"
  15 |             className="w-full h-full object-cover opacity-20 grayscale"
  16 |           />
  17 |           <div className="absolute inset-0 bg-gradient-to-b from-white via-white/90 to-white"></div>
  18 |         </div>
  19 |
  20 |         <div className="container relative z-10 max-w-4xl mx-auto px-4 text-center">
  21 |           <h1 className="text-4xl md:text-6xl font-bold tracking-tight text-slate-900 mb-6">
  22 |             The beating heart of <br class="hidden md:block"/> emergency response.
  23 |           </h1>
  24 |           <p class="text-xl text-slate-600 leading-relaxed max-w-2xl mx-auto">
  25 |             Main Blood Center was founded on a simple principle: no patient should ever have to wait for blood
when a willing donor is nearby. We built the n...
  26 |           </p>
  27 |         </div>
  28 |       </section>
  29 |
  30 |       {/* Core Values */}
  31 |       <section class="py-20 bg-slate-50 border-y border-slate-200">
  32 |         <div class="container mx-auto px-4 max-w-6xl">
  33 |           <div class="grid md:grid-cols-3 gap-10">
  34 |             <div class="bg-white p-8 rounded-2xl shadow-sm border border-slate-100">
  35 |               <div class="w-14 h-14 bg-red-50 text-red-600 rounded-xl flex items-center justify-center mb-6">
  36 |                 <Target class="w-7 h-7" />
  37 |               </div>
  38 |               <h3 class="text-xl font-bold mb-3 text-slate-900">Speed & Precision</h3>
  39 |               <p class="text-slate-600 leading-relaxed">
  40 |                 In critical moments, minutes matter. Our algorithmic matching system ensures that emergency
requests reach the right donors instantly.
  41 |               </p>
  42 |             </div>
  43 |
  44 |             <div class="bg-white p-8 rounded-2xl shadow-sm border border-slate-100">
  45 |               <div class="w-14 h-14 bg-blue-50 text-blue-600 rounded-xl flex items-center justify-center mb-6">
  46 |                 <ShieldCheck class="w-7 h-7" />
  47 |               </div>
  48 |               <h3 class="text-xl font-bold mb-3 text-slate-900">Clinical Trust</h3>
  49 |               <p class="text-slate-600 leading-relaxed">
  50 |                 We operate under the highest medical standards. Every partner hospital and donation center is
rigorously vetted and certified.
  51 |               </p>
  52 |             </div>
  53 |
  54 |             <div class="bg-white p-8 rounded-2xl shadow-sm border border-slate-100">
  55 |               <div class="w-14 h-14 bg-green-50 text-green-600 rounded-xl flex items-center justify-center
mb-6">
  56 |                 <Heart class="w-7 h-7" />
  57 |               </div>
  58 |               <h3 class="text-xl font-bold mb-3 text-slate-900">Human Connection</h3>
  59 |               <p class="text-slate-600 leading-relaxed">
  60 |                 Technology powers the network, but human generosity fuels it. We treat every donor as a hero
because they are.
  61 |               </p>
  62 |             </div>
  63 |           </div>
  64 |         </div>
  65 |       </section>
  66 |
  67 |       {/* Network / Partners */}
  68 |       <section class="py-24 bg-white">
  69 |         <div class="container mx-auto px-4 text-center max-w-5xl">
  70 |           <h2 class="text-3xl font-bold mb-4 text-slate-900">Our Healthcare Network</h2>
  71 |           <p class="text-lg text-slate-600 mb-16 max-w-2xl mx-auto">
  72 |             We partner with leading hospitals and regional blood banks to ensure your donation gets exactly where
it's needed most.
  73 |           </p>
  74 |
  75 |           <div class="grid grid-cols-2 md:grid-cols-4 gap-8 opacity-60">
  76 |             {/* Placeholder Partner Logos */}
  77 |             {[1, 2, 3, 4, 5, 6, 7, 8].map(i => (
  78 |               <div key={i} class="bg-slate-100 h-24 rounded-lg flex items-center justify-center grayscale
hover:grayscale-0 transition-all cursor-pointer">
  79 |                 <span class="font-bold text-slate-400 text-xl">Hospital {i}</span>
  80 |               </div>
  81 |             ))}
  82 |           </div>
  83 |         </div>
  84 |       </section>
  85 |
  86 |       <section class="py-20 bg-slate-900 text-white text-center">
  87 |         <div class="container mx-auto px-4">
  88 |           <h2 class="text-3xl font-bold mb-6">Join our network today.</h2>
  89 |           <Link href="/register-donor">
  90 |             <Button variant="destructive" size="lg" class="h-14 px-8 text-lg font-bold">
  91 |               Become a Donor
  92 |             </Button>
  93 |           </Link>
```

```
 94 |         </div>
 95 |       </section>
 96 |
 97 |     </div>
 98 |   );
 99 | }
100 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/contact.tsx

```
   1 | import { MapPin, Phone, Mail, Clock, MessageSquare } from "lucide-react";
   2 | import { Button } from "@/components/ui/button";
   3 | import { Input } from "@/components/ui/input";
   4 | import { Textarea } from "@/components/ui/textarea";
   5 |
   6 | export default function Contact() {
   7 |   return (
   8 |     <div className="min-h-screen bg-slate-50 py-12">
   9 |       <div className="container max-w-6xl mx-auto px-4">
  10 |
  11 |         <div className="text-center mb-16">
  12 |           <h1 className="text-4xl font-bold tracking-tight text-slate-900 mb-4">Contact & Support</h1>
  13 |           <p className="text-xl text-slate-600 max-w-2xl mx-auto">
  14 |             We're here to help. Whether you're a donor with a question or a hospital needing immediate assistance.
  15 |           </p>
  16 |         </div>
  17 |
  18 |         <div className="grid lg:grid-cols-5 gap-10">
  19 |
  20 |           {/* Contact Info */}
  21 |           <div className="lg:col-span-2 space-y-8">
  22 |             <div className="bg-destructive text-white rounded-2xl p-8 shadow-lg">
  23 |               <h2 className="text-2xl font-bold mb-2">Emergency Hotline</h2>
  24 |               <p className="text-destructive-foreground/90 mb-6">For hospitals and critical situations only.
Available 24/7.</p>
  25 |               <div className="flex items-center gap-4">
  26 |                 <div className="w-12 h-12 bg-white/20 rounded-full flex items-center justify-center shrink-0">
  27 |                   <Phone className="w-6 h-6" />
  28 |                 </div>
  29 |                 <div className="text-3xl font-bold tracking-tight">1-800-MBC-BLOOD</div>
  30 |               </div>
  31 |             </div>
  32 |
  33 |             <div className="bg-white rounded-2xl p-8 shadow-sm border border-slate-200">
  34 |               <h3 className="text-xl font-bold mb-6 text-slate-900">General Inquiries</h3>
  35 |
  36 |               <div className="space-y-6">
  37 |                 <div className="flex items-start gap-4">
  38 |                   <Mail className="w-6 h-6 text-primary shrink-0 mt-0.5" />
  39 |                   <div>
  40 |                     <p className="font-semibold text-slate-900">Email Us</p>
  41 |                     <p className="text-slate-600">support@mbc-network.org</p>
  42 |                   </div>
  43 |                 </div>
  44 |
  45 |                 <div className="flex items-start gap-4">
  46 |                   <MapPin className="w-6 h-6 text-primary shrink-0 mt-0.5" />
  47 |                   <div>
  48 |                     <p className="font-semibold text-slate-900">Headquarters</p>
  49 |                     <p className="text-slate-600">123 Medical Center Blvd<br />Metropolis, NY 10001</p>
  50 |                   </div>
  51 |                 </div>
  52 |
  53 |                 <div className="flex items-start gap-4">
  54 |                   <Clock className="w-6 h-6 text-primary shrink-0 mt-0.5" />
  55 |                   <div>
  56 |                     <p className="font-semibold text-slate-900">Support Hours</p>
  57 |                     <p className="text-slate-600">Monday - Friday: 8am - 8pm EST<br />Saturday - Sunday: 9am - 5pm
EST</p>
  58 |                   </div>
  59 |                 </div>
  60 |               </div>
  61 |             </div>
  62 |           </div>
  63 |
  64 |           {/* Contact Form */}
  65 |           <div className="lg:col-span-3">
  66 |             <div className="bg-white rounded-2xl p-8 shadow-sm border border-slate-200">
  67 |               <div className="flex items-center gap-3 mb-8">
  68 |                 <MessageSquare className="w-6 h-6 text-primary" />
  69 |                 <h2 className="text-2xl font-bold text-slate-900">Send us a message</h2>
  70 |               </div>
  71 |
  72 |               <form className="space-y-6" onSubmit={(e) => { e.preventDefault(); alert("Message sent
successfully."); }}>
  73 |                 <div className="grid md:grid-cols-2 gap-6">
  74 |                   <div class="space-y-2">
  75 |                     <label class="text-sm font-medium text-slate-700">First Name</label>
  76 |                     <Input placeholder="John" required />
  77 |                   </div>
  78 |                   <div class="space-y-2">
  79 |                     <label class="text-sm font-medium text-slate-700">Last Name</label>
  80 |                     <Input placeholder="Doe" required />
  81 |                   </div>
  82 |                 </div>
  83 |
  84 |                 <div class="space-y-2">
  85 |                   <label class="text-sm font-medium text-slate-700">Email Address</label>
  86 |                   <Input type="email" placeholder="john@example.com" required />
  87 |                 </div>
  88 |
  89 |                 <div class="space-y-2">
  90 |                   <label class="text-sm font-medium text-slate-700">Subject</label>
  91 |                   <Input placeholder="How can we help you?" required />
  92 |                 </div>
  93 |
  94 |                 <div class="space-y-2">
  95 |                   <label class="text-sm font-medium text-slate-700">Message</label>
  96 |                   <Textarea placeholder="Please provide details..." class="h-32 resize-none" required />
  97 |                 </div>
```

```
 98 |
 99 |                  <Button type="submit" size="lg" className="w-full text-base font-bold h-14">
100 |                    Send Message
101 |                  </Button>
102 |                </form>
103 |              </div>
104 |            </div>
105 |
106 |          </div>
107 |        </div>
108 |      </div>
109 |    );
110 | }
111 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/education.tsx

```
   1 | import { motion } from "framer-motion";
   2 | import { BookOpen, CheckCircle2, AlertTriangle, ChevronRight, HelpCircle, Activity } from "lucide-react";
   3 | import { Accordion, AccordionContent, AccordionItem, AccordionTrigger } from "@/components/ui/accordion";
   4 | import { Tabs, TabsContent, TabsList, TabsTrigger } from "@/components/ui/tabs";
   5 | import { Card, CardContent } from "@/components/ui/card";
   6 |
   7 | export default function Education() {
   8 |   const compatibilityData = [
   9 |     { type: "O-", canGive: ["Everyone"], canReceive: ["O-"] },
  10 |     { type: "O+", canGive: ["O+", "A+", "B+", "AB+"], canReceive: ["O+", "O-"] },
  11 |     { type: "A-", canGive: ["A+", "A-", "AB+", "AB-"], canReceive: ["A-", "O-"] },
  12 |     { type: "A+", canGive: ["A+", "AB+"], canReceive: ["A+", "A-", "O+", "O-"] },
  13 |     { type: "B-", canGive: ["B+", "B-", "AB+", "AB-"], canReceive: ["B-", "O-"] },
  14 |     { type: "B+", canGive: ["B+", "AB+"], canReceive: ["B+", "B-", "O+", "O-"] },
  15 |     { type: "AB-", canGive: ["AB+", "AB-"], canReceive: ["AB-", "A-", "B-", "O-"] },
  16 |     { type: "AB+", canGive: ["AB+"], canReceive: ["Everyone"] },
  17 |   ];
  18 |
  19 |   return (
  20 |     <div className="min-h-screen bg-slate-50 py-12">
  21 |       <div className="container max-w-5xl mx-auto px-4 md:px-6">
  22 |
  23 |         <div className="text-center mb-16">
  24 |           <div className="inline-flex items-center justify-center w-16 h-16 rounded-full bg-blue-100 text-blue-600
mb-6">
  25 |             <BookOpen className="w-8 h-8" />
  26 |           </div>
  27 |           <h1 className="text-4xl md:text-5xl font-bold tracking-tight text-foreground mb-6">Knowledge Saves
Lives</h1>
  28 |           <p className="text-xl text-muted-foreground max-w-2xl mx-auto">
  29 |             Understanding blood types, the donation process, and post-care is crucial for a healthy donor network.
  30 |           </p>
  31 |         </div>
  32 |
  33 |         <Tabs defaultValue="compatibility" className="w-full">
  34 |           <TabsList className="grid w-full grid-cols-1 md:grid-cols-3 h-auto p-1 bg-slate-200/50 mb-8 rounded-xl">
  35 |             <TabsTrigger value="compatibility" className="py-3 text-base rounded-lg data-[state=active]:bg-white
data-[state=active]:shadow-sm">Blood Compati...
  36 |             <TabsTrigger value="process" className="py-3 text-base rounded-lg data-[state=active]:bg-white data-
[state=active]:shadow-sm">The Process</TabsTr...
  37 |             <TabsTrigger value="faq" className="py-3 text-base rounded-lg data-[state=active]:bg-white data-
[state=active]:shadow-sm">FAQ</TabsTrigger>
  38 |           </TabsList>
  39 |
  40 |           <TabsContent value="compatibility">
  41 |             <div className="bg-white rounded-2xl shadow-sm border border-border overflow-hidden">
  42 |               <div className="p-8 border-b border-border bg-slate-50/50">
  43 |                 <h2 className="text-2xl font-bold mb-2">Blood Type Compatibility</h2>
  44 |                 <p className="text-muted-foreground">O- is the universal donor. AB+ is the universal recipient.
See exactly who your donation can help.</p>
  45 |               </div>
  46 |               <div className="overflow-x-auto">
  47 |                 <table className="w-full text-sm text-left">
  48 |                   <thead className="text-xs text-slate-500 uppercase bg-slate-50 border-b border-border">
  49 |                     <tr>
  50 |                       <th className="px-6 py-4 font-bold">Blood Type</th>
  51 |                       <th className="px-6 py-4 font-bold">Can Give To</th>
  52 |                       <th className="px-6 py-4 font-bold">Can Receive From</th>
  53 |                     </tr>
  54 |                   </thead>
  55 |                   <tbody>
  56 |                     {compatibilityData.map((row, i) => (
  57 |                       <tr key={row.type} className={`border-b border-border last:border-0 hover:bg-slate-50
transition-colors ${row.type === 'O-' || row.type...
  58 |                         <td className="px-6 py-4">
  59 |                           <span className="inline-flex items-center justify-center w-10 h-10 rounded-full bg-
primary text-white font-bold shadow-sm">
  60 |                             {row.type}
  61 |                           </span>
  62 |                         </td>
  63 |                         <td className="px-6 py-4 font-medium text-slate-700">
  64 |                           {row.canGive.join(", ")}
  65 |                         </td>
  66 |                         <td className="px-6 py-4 font-medium text-slate-700">
  67 |                           {row.canReceive.join(", ")}
  68 |                         </td>
  69 |                       </tr>
  70 |                     ))}
  71 |                   </tbody>
  72 |                 </table>
  73 |               </div>
  74 |             </div>
  75 |           </TabsContent>
  76 |
  77 |           <TabsContent value="process">
  78 |             <div className="grid md:grid-cols-2 gap-8">
  79 |               <div className="space-y-6">
  80 |                 <h2 className="text-2xl font-bold">Before You Donate</h2>
  81 |                 <Card>
  82 |                   <CardContent className="p-6 space-y-4">
  83 |                     <div className="flex gap-4">
  84 |                       <CheckCircle2 className="w-6 h-6 text-green-500 shrink-0" />
  85 |                       <div>
  86 |                         <h4 className="font-semibold text-foreground">Hydrate</h4>
  87 |                         <p className="text-sm text-muted-foreground">Drink plenty of water before your
appointment.</p>
  88 |                       </div>
  89 |                     </div>
  90 |                     <div className="flex gap-4">
  91 |                       <CheckCircle2 className="w-6 h-6 text-green-500 shrink-0" />
```

```
  92 |                        <div>
  93 |                          <h4 className="font-semibold text-foreground">Eat well</h4>
  94 |                          <p className="text-sm text-muted-foreground">Have a healthy, low-fat meal within 2 hours
of donating.</p>
  95 |                        </div>
  96 |                      </div>
  97 |                      <div className="flex gap-4">
  98 |                        <CheckCircle2 className="w-6 h-6 text-green-500 shrink-0" />
  99 |                        <div>
 100 |                          <h4 className="font-semibold text-foreground">Rest</h4>
 101 |                          <p className="text-sm text-muted-foreground">Get a good night's sleep before your donation
day.</p>
 102 |                        </div>
 103 |                      </div>
 104 |                      <div className="flex gap-4">
 105 |                        <AlertTriangle className="w-6 h-6 text-orange-500 shrink-0" />
 106 |                        <div>
 107 |                          <h4 className="font-semibold text-foreground">Avoid Alcohol</h4>
 108 |                          <p className="text-sm text-muted-foreground">Do not consume alcohol 24 hours prior to
donating.</p>
 109 |                        </div>
 110 |                      </div>
 111 |                    </CardContent>
 112 |                  </Card>
 113 |                </div>
 114 |
 115 |                <div className="space-y-6">
 116 |                  <h2 className="text-2xl font-bold">After You Donate</h2>
 117 |                  <Card>
 118 |                    <CardContent className="p-6 space-y-4">
 119 |                      <div className="flex gap-4">
 120 |                        <Activity className="w-6 h-6 text-blue-500 shrink-0" />
 121 |                        <div>
 122 |                          <h4 className="font-semibold text-foreground">Rest briefly</h4>
 123 |                          <p className="text-sm text-muted-foreground">Sit and enjoy a snack and drink for 10-15
minutes.</p>
 124 |                        </div>
 125 |                      </div>
 126 |                      <div className="flex gap-4">
 127 |                        <CheckCircle2 className="w-6 h-6 text-green-500 shrink-0" />
 128 |                        <div>
 129 |                          <h4 className="font-semibold text-foreground">Keep the bandage on</h4>
 130 |                          <p className="text-sm text-muted-foreground">Leave the bandage on for at least 4 hours.</p>
 131 |                        </div>
 132 |                      </div>
 133 |                      <div className="flex gap-4">
 134 |                        <AlertTriangle className="w-6 h-6 text-orange-500 shrink-0" />
 135 |                        <div>
 136 |                          <h4 className="font-semibold text-foreground">No heavy lifting</h4>
 137 |                          <p className="text-sm text-muted-foreground">Avoid strenuous physical activity for the
rest of the day.</p>
 138 |                        </div>
 139 |                      </div>
 140 |                      <div className="flex gap-4">
 141 |                        <CheckCircle2 className="w-6 h-6 text-green-500 shrink-0" />
 142 |                        <div>
 143 |                          <h4 className="font-semibold text-foreground">Hydrate more</h4>
 144 |                          <p className="text-sm text-muted-foreground">Drink extra liquids over the next 24 hours.</
p>
 145 |                        </div>
 146 |                      </div>
 147 |                    </CardContent>
 148 |                  </Card>
 149 |                </div>
 150 |              </div>
 151 |            </TabsContent>
 152 |
 153 |            <TabsContent value="faq">
 154 |              <div className="bg-white rounded-2xl shadow-sm border border-border p-8">
 155 |                <div className="flex items-center gap-3 mb-6">
 156 |                  <HelpCircle className="w-6 h-6 text-primary" />
 157 |                  <h2 className="text-2xl font-bold">Frequently Asked Questions</h2>
 158 |                </div>
 159 |
 160 |                <Accordion type="single" collapsible className="w-full">
 161 |                  <AccordionItem value="item-1">
 162 |                    <AccordionTrigger className="text-left font-semibold text-lg">How long does the donation process
take?</AccordionTrigger>
 163 |                    <AccordionContent className="text-muted-foreground text-base leading-relaxed">
 164 |                      The entire process, from registration to post-donation resting, usually takes about 45 minutes
to an hour. The actual blood draw only tak...
 165 |                    </AccordionContent>
 166 |                  </AccordionItem>
 167 |                  <AccordionItem value="item-2">
 168 |                    <AccordionTrigger className="text-left font-semibold text-lg">Does donating blood hurt?</
AccordionTrigger>
 169 |                    <AccordionContent className="text-muted-foreground text-base leading-relaxed">
 170 |                      You may feel a slight pinch when the needle is inserted, but the actual donation process is
painless for most people.
 171 |                    </AccordionContent>
 172 |                  </AccordionItem>
 173 |                  <AccordionItem value="item-3">
 174 |                    <AccordionTrigger className="text-left font-semibold text-lg">How often can I donate?</
AccordionTrigger>
 175 |                    <AccordionContent className="text-muted-foreground text-base leading-relaxed">
 176 |                      You must wait at least 8 weeks (56 days) between whole blood donations. For platelet
donations, you can donate every 7 days, up to 24 tim...
 177 |                    </AccordionContent>
 178 |                  </AccordionItem>
 179 |                  <AccordionItem value="item-4">
 180 |                    <AccordionTrigger className="text-left font-semibold text-lg">Can I donate if I'm taking
medication?</AccordionTrigger>
 181 |                    <AccordionContent className="text-muted-foreground text-base leading-relaxed">
```

```
 182 |                      Most medications do not prevent you from donating blood. However, some medications (like blood
thinners or certain acne treatments) might...
 183 |                    </AccordionContent>
 184 |                  </AccordionItem>
 185 |                  <AccordionItem value="item-5">
 186 |                    <AccordionTrigger className="text-left font-semibold text-lg">Can I donate if I have a tattoo or
piercing?</AccordionTrigger>
 187 |                    <AccordionContent className="text-muted-foreground text-base leading-relaxed">
 188 |                      Yes, if the tattoo or piercing was applied by a state-regulated entity using sterile needles
and non-reused ink. If not, you must wait 3 ...
 189 |                    </AccordionContent>
 190 |                  </AccordionItem>
 191 |                </Accordion>
 192 |              </div>
 193 |            </TabsContent>
 194 |          </Tabs>
 195 |
 196 |        </div>
 197 |      </div>
 198 |    );
 199 | }
 200 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/emergency.tsx

```
   1 | import { useState, useEffect } from "react";
   2 | import { motion, AnimatePresence } from "framer-motion";
   3 | import { AlertCircle, Clock, MapPin, Activity, Droplets, ArrowRight } from "lucide-react";
   4 | import { useGetEmergencyFeed } from "@workspace/api-client-react";
   5 | import { Button } from "@/components/ui/button";
   6 | import { Link } from "wouter";
   7 |
   8 | export default function Emergency() {
   9 |   const { data, isLoading } = useGetEmergencyFeed({
  10 |     query: {
  11 |       refetchInterval: 5000, // Poll every 5s to feel live
  12 |     }
  13 |   });
  14 |
  15 |   const getUrgencyColor = (urgency: string) => {
  16 |     switch (urgency.toLowerCase()) {
  17 |       case 'critical': return 'bg-destructive text-white border-destructive';
  18 |       case 'high': return 'bg-orange-500 text-white border-orange-500';
  19 |       default: return 'bg-blue-500 text-white border-blue-500';
  20 |     }
  21 |   };
  22 |
  23 |   const getPulseEffect = (urgency: string) => {
  24 |     return urgency.toLowerCase() === 'critical' ? 'animate-pulse' : '';
  25 |   };
  26 |
  27 |   return (
  28 |     <div className="min-h-screen bg-slate-100">
  29 |       {/* Live Header */}
  30 |       <div className="bg-slate-900 text-white py-6 border-b border-slate-800">
  31 |         <div className="container mx-auto px-4 flex items-center justify-between">
  32 |           <div className="flex items-center gap-3">
  33 |             <div className="relative flex h-4 w-4">
  34 |               <span className="animate-ping absolute inline-flex h-full w-full rounded-full bg-red-400
opacity-75"></span>
  35 |               <span className="relative inline-flex rounded-full h-4 w-4 bg-red-500"></span>
  36 |             </div>
  37 |             <h1 className="text-2xl font-bold tracking-tight">Live Emergency Feed</h1>
  38 |           </div>
  39 |           <div className="text-sm font-mono text-slate-400">
  40 |             Auto-updating • {new Date().toLocaleTimeString()}
  41 |           </div>
  42 |         </div>
  43 |       </div>
  44 |
  45 |       <div className="container max-w-4xl mx-auto px-4 py-8">
  46 |
  47 |         {isLoading && !data ? (
  48 |           <div className="space-y-4">
  49 |             {[1, 2, 3].map(i => (
  50 |               <div key={i} className="bg-white p-6 rounded-xl border border-slate-200 shadow-sm animate-pulse
h-40"></div>
  51 |             ))}
  52 |           </div>
  53 |         ) : data?.emergencies.length === 0 ? (
  54 |           <div className="bg-white rounded-2xl p-12 text-center border border-slate-200 shadow-sm">
  55 |             <div className="w-16 h-16 bg-green-100 text-green-600 rounded-full flex items-center justify-center mx-
auto mb-4">
  56 |               <CheckCircle className="w-8 h-8" />
  57 |             </div>
  58 |             <h2 className="text-2xl font-bold mb-2 text-slate-800">No Active Emergencies</h2>
  59 |             <p className="text-slate-500">The network is stable. No critical requests in your area.</p>
  60 |           </div>
  61 |         ) : (
  62 |           <div className="space-y-4">
  63 |             <AnimatePresence>
  64 |               {data?.emergencies.map((req) => (
  65 |                 <motion.div
  66 |                   key={req.id}
  67 |                   initial={{ opacity: 0, x: -20 }}
  68 |                   animate={{ opacity: 1, x: 0 }}
  69 |                   exit={{ opacity: 0, scale: 0.95 }}
  70 |                   layout
  71 |                   className={`bg-white rounded-xl overflow-hidden border shadow-sm transition-all hover:shadow-md
${
  72 |                     req.urgency === 'critical' ? 'border-destructive/50' : 'border-slate-200'
  73 |                   }`}
  74 |                 >
  75 |                   <div className="flex flex-col md:flex-row">
  76 |
  77 |                     {/* Urgency Strip */}
  78 |                     <div className={`w-full md:w-2 ${getUrgencyColor(req.urgency)} h-2 md:h-auto`}></div>
  79 |
  80 |                     <div className="p-6 flex-1 flex flex-col md:flex-row gap-6 items-start md:items-center">
  81 |
  82 |                       {/* Blood Type Badge */}
  83 |                       <div className="shrink-0 flex flex-col items-center justify-center">
  84 |                         <div className={`w-16 h-16 rounded-2xl flex items-center justify-center text-2xl font-
black shadow-inner ${
  85 |                           req.urgency === 'critical' ? 'bg-red-50 text-destructive border-2 border-
destructive/20' : 'bg-slate-100 text-slate-700'
  86 |                         }`}>
  87 |                           {req.bloodType}
  88 |                         </div>
  89 |                         <span className="text-xs font-bold text-slate-500 mt-2 uppercase tracking-
wider">{req.unitsNeeded} Units</span>
  90 |                       </div>
  91 |
  92 |                       {/* Details */}
  93 |                       <div className="flex-1 space-y-2 w-full">
```

```
  94 |                         <div className="flex items-center gap-2 mb-1">
  95 |                           <span className={`text-xs font-bold uppercase tracking-wider px-2 py-0.5 rounded-full
${getUrgencyColor(req.urgency)} ${getPulseEff...
  96 |                             {req.urgency} Priority
  97 |                           </span>
  98 |                           <span className="text-xs text-slate-500 flex items-center">
  99 |                             <Clock className="w-3 h-3 mr-1" /> {req.minutesAgo} mins ago
 100 |                           </span>
 101 |                         </div>
 102 |
 103 |                         <h3 className="text-xl font-bold text-slate-900">{req.hospitalName}</h3>
 104 |
 105 |                         <div className="flex items-center gap-4 text-sm text-slate-600">
 106 |                           <span className="flex items-center"><MapPin className="w-4 h-4 mr-1 text-slate-400" />
{req.city}</span>
 107 |                           <span className="hidden sm:flex items-center"><Droplets className="w-4 h-4 mr-1 text-
slate-400" /> Patient: {req.patientName}</span>
 108 |                         </div>
 109 |                       </div>
 110 |
 111 |                       {/* Action */}
 112 |                       <div className="w-full md:w-auto shrink-0 pt-4 md:pt-0 border-t md:border-t-0 border-
slate-100">
 113 |                         <Link href="/locator">
 114 |                           <Button
 115 |                             className={`w-full md:w-auto font-bold h-12 px-6 ${
 116 |                               req.urgency === 'critical' ? 'bg-destructive hover:bg-destructive/90' : ''
 117 |                             }`}
 118 |                           >
 119 |                             Respond Now <ArrowRight className="w-4 h-4 ml-2" />
 120 |                           </Button>
 121 |                         </Link>
 122 |                       </div>
 123 |
 124 |                     </div>
 125 |                   </div>
 126 |                 </motion.div>
 127 |               ))}
 128 |             </AnimatePresence>
 129 |           </div>
 130 |         )}
 131 |       </div>
 132 |     </div>
 133 |   );
 134 | }
 135 |
 136 | // Needed to avoid missing icon error
 137 | import { CheckCircle } from "lucide-react";
```

— end of file —

File: artifacts/mbc-platform/src/pages/home.tsx

```
   1 | import { Link } from "wouter";
   2 | import { Button } from "@/components/ui/button";
   3 | import { useGetDashboardStats } from "@workspace/api-client-react";
   4 | import { motion } from "framer-motion";
   5 | import { Droplets, Activity, Users, Building, HeartPulse, ArrowRight } from "lucide-react";
   6 | import { Skeleton } from "@/components/ui/skeleton";
   7 |
   8 | export default function Home() {
   9 |   const { data: stats, isLoading } = useGetDashboardStats({ query: { enabled: true } });
  10 |
  11 |   const fadeUp = {
  12 |     hidden: { opacity: 0, y: 20 },
  13 |     visible: { opacity: 1, y: 0, transition: { duration: 0.6, ease: "easeOut" } }
  14 |   };
  15 |
  16 |   const staggerContainer = {
  17 |     hidden: { opacity: 0 },
  18 |     visible: {
  19 |       opacity: 1,
  20 |       transition: {
  21 |         staggerChildren: 0.1
  22 |       }
  23 |     }
  24 |   };
  25 |
  26 |   return (
  27 |     <div className="w-full">
  28 |       {/* Hero Section */}
  29 |       <section className="relative overflow-hidden bg-slate-50 pt-20 pb-24 lg:pt-32 lg:pb-40">
  30 |         <div className="absolute inset-0 z-0">
  31 |           <img
  32 |             src="/images/hero.png"
  33 |             alt="Modern hospital blood donation center"
  34 |             className="w-full h-full object-cover object-center opacity-10 mix-blend-multiply"
  35 |           />
  36 |           <div className="absolute inset-0 bg-gradient-to-t from-slate-50 to-transparent"></div>
  37 |         </div>
  38 |
  39 |         <div className="container relative z-10 mx-auto px-4 md:px-6">
  40 |           <div className="max-w-4xl mx-auto text-center">
  41 |             <motion.div initial="hidden" animate="visible" variants={staggerContainer} className="space-y-6">
  42 |               <motion.div variants={fadeUp} className="inline-flex items-center gap-2 px-3 py-1 rounded-full bg-
primary/10 text-primary text-sm font-medium m...
  43 |                 <Activity className="w-4 h-4 animate-pulse" />
  44 |                 <span>Live Emergency Network</span>
  45 |               </motion.div>
  46 |
  47 |               <motion.h1 variants={fadeUp} className="text-4xl md:text-6xl lg:text-7xl font-bold tracking-tight
text-slate-900 leading-tight">
  48 |                 Every Drop Counts. <br className="hidden md:block" />
  49 |                 <span className="text-primary">Connect. Donate. Save Lives.</span>
  50 |               </motion.h1>
  51 |
  52 |               <motion.p variants={fadeUp} className="text-lg md:text-xl text-slate-600 max-w-2xl mx-auto leading-
relaxed">
  53 |                 MBC is the central lifeline connecting critical patients with compatible donors in real-time. Your
donation today could be the miracle someon...
  54 |               </motion.p>
  55 |
  56 |               <motion.div variants={fadeUp} className="flex flex-col sm:flex-row items-center justify-center gap-4
pt-8">
  57 |                 <Link href="/request-blood" className="w-full sm:w-auto">
  58 |                   <Button size="lg" variant="destructive" className="w-full sm:w-auto h-14 px-8 text-lg font-bold
shadow-lg shadow-destructive/20 hover:shado...
  59 |                     Request Blood (Emergency)
  60 |                   </Button>
  61 |                 </Link>
  62 |                 <Link href="/register-donor" className="w-full sm:w-auto">
  63 |                   <Button size="lg" variant="outline" className="w-full sm:w-auto h-14 px-8 text-lg font-semibold
bg-white hover:bg-slate-50 border-slate-200">
  64 |                     Register as Donor
  65 |                   </Button>
  66 |                 </Link>
  67 |               </motion.div>
  68 |             </motion.div>
  69 |           </div>
  70 |         </div>
  71 |       </section>
  72 |
  73 |       {/* Stats Section */}
  74 |       <section className="py-12 bg-white border-y border-border relative z-20 -mt-10 mx-4 md:mx-auto max-w-6xl
rounded-2xl shadow-sm">
  75 |         <div className="container mx-auto px-4">
  76 |           <div className="grid grid-cols-2 md:grid-cols-4 gap-8 divide-x divide-border">
  77 |             <div className="text-center px-4">
  78 |               <div className="mx-auto w-12 h-12 bg-blue-50 rounded-full flex items-center justify-center mb-3">
  79 |                 <Users className="w-6 h-6 text-blue-600" />
  80 |               </div>
  81 |               <p className="text-sm font-medium text-muted-foreground mb-1">Registered Donors</p>
  82 |               {isLoading ? <Skeleton className="h-8 w-24 mx-auto" /> : <p className="text-3xl font-bold text-
foreground">{stats?.totalDonors.toLocaleString()...
  83 |             </div>
  84 |             <div className="text-center px-4">
  85 |               <div className="mx-auto w-12 h-12 bg-red-50 rounded-full flex items-center justify-center mb-3">
  86 |                 <HeartPulse className="w-6 h-6 text-red-600" />
  87 |               </div>
  88 |               <p className="text-sm font-medium text-muted-foreground mb-1">Lives Saved</p>
  89 |               {isLoading ? <Skeleton className="h-8 w-24 mx-auto" /> : <p className="text-3xl font-bold text-
foreground">{stats?.livesSaved.toLocaleString()}...
  90 |             </div>
```

```
  91 |             <div className="text-center px-4">
  92 |               <div className="mx-auto w-12 h-12 bg-green-50 rounded-full flex items-center justify-center mb-3">
  93 |                 <Droplets className="w-6 h-6 text-green-600" />
  94 |               </div>
  95 |               <p className="text-sm font-medium text-muted-foreground mb-1">Donations (Month)</p>
  96 |               {isLoading ? <Skeleton className="h-8 w-24 mx-auto" /> : <p className="text-3xl font-bold text-
foreground">{stats?.donationsThisMonth.toLocaleS...
  97 |             </div>
  98 |             <div className="text-center px-4">
  99 |               <div className="mx-auto w-12 h-12 bg-purple-50 rounded-full flex items-center justify-center mb-3">
 100 |                 <Building className="w-6 h-6 text-purple-600" />
 101 |               </div>
 102 |               <p className="text-sm font-medium text-muted-foreground mb-1">Partner Hospitals</p>
 103 |               {isLoading ? <Skeleton className="h-8 w-24 mx-auto" /> : <p className="text-3xl font-bold text-
foreground">{stats?.partnerHospitals}</p>}
 104 |             </div>
 105 |           </div>
 106 |         </div>
 107 |       </section>
 108 |
 109 |       {/* How it Works */}
 110 |       <section className="py-24 bg-white">
 111 |         <div className="container mx-auto px-4 md:px-6">
 112 |           <div className="text-center max-w-3xl mx-auto mb-16">
 113 |             <h2 className="text-3xl font-bold tracking-tight mb-4 text-foreground">The MBC Network</h2>
 114 |             <p className="text-muted-foreground text-lg">A seamless, rapid-response system designed to eliminate
delays when every second matters.</p>
 115 |           </div>
 116 |
 117 |           <div className="grid md:grid-cols-3 gap-12 relative">
 118 |             <div className="hidden md:block absolute top-1/2 left-[16%] right-[16%] h-0.5 bg-border -z-10 -
translate-y-1/2"></div>
 119 |
 120 |             <div className="relative bg-white pt-8 px-6 text-center">
 121 |               <div className="w-16 h-16 mx-auto bg-primary text-white rounded-2xl flex items-center justify-center
shadow-lg shadow-primary/20 mb-6 rotate-3">
 122 |                 <Activity className="w-8 h-8 -rotate-3" />
 123 |               </div>
 124 |               <h3 className="text-xl font-bold mb-3">1. Urgent Request</h3>
 125 |               <p className="text-muted-foreground">Hospitals broadcast immediate needs to the MBC network
detailing blood type and urgency.</p>
 126 |             </div>
 127 |
 128 |             <div className="relative bg-white pt-8 px-6 text-center">
 129 |               <div className="w-16 h-16 mx-auto bg-primary text-white rounded-2xl flex items-center justify-center
shadow-lg shadow-primary/20 mb-6 -rotate-3">
 130 |                 <Users className="w-8 h-8 rotate-3" />
 131 |               </div>
 132 |               <h3 className="text-xl font-bold mb-3">2. Instant Match</h3>
 133 |               <p className="text-muted-foreground">Eligible donors in the vicinity with the matching blood type
are immediately notified.</p>
 134 |             </div>
 135 |
 136 |             <div className="relative bg-white pt-8 px-6 text-center">
 137 |               <div className="w-16 h-16 mx-auto bg-primary text-white rounded-2xl flex items-center justify-center
shadow-lg shadow-primary/20 mb-6 rotate-3">
 138 |                 <HeartPulse className="w-8 h-8 -rotate-3" />
 139 |               </div>
 140 |               <h3 className="text-xl font-bold mb-3">3. Life Saved</h3>
 141 |               <p className="text-muted-foreground">The donor visits the nearest center, and the blood is
dispatched to the critical patient.</p>
 142 |             </div>
 143 |           </div>
 144 |         </div>
 145 |       </section>
 146 |
 147 |       {/* Call to Action */}
 148 |       <section className="py-24 bg-slate-50 border-t border-border overflow-hidden relative">
 149 |         <div className="absolute right-0 top-1/2 -translate-y-1/2 translate-x-1/3 opacity-20 pointer-events-none">
 150 |           <img src="/images/blood-drop.png" alt="Decorative blood drop" className="w-[600px] h-[600px] object-
contain" />
 151 |         </div>
 152 |         <div className="container mx-auto px-4 md:px-6 relative z-10">
 153 |           <div className="bg-primary rounded-3xl p-8 md:p-16 flex flex-col md:flex-row items-center justify-
between gap-8 shadow-2xl">
 154 |             <div className="max-w-2xl">
 155 |               <h2 className="text-3xl md:text-4xl font-bold text-white mb-4">Ready to be someone's hero?</h2>
 156 |               <p class="text-primary-foreground/90 text-lg">
 157 |                 Join thousands of donors who are making a real difference. It takes 15 minutes to register and a
lifetime of impact.
 158 |               </p>
 159 |             </div>
 160 |             <div className="shrink-0 flex flex-col sm:flex-row gap-4 w-full md:w-auto">
 161 |               <Link href="/register-donor" className="w-full sm:w-auto">
 162 |                 <Button size="lg" variant="secondary" className="w-full h-14 px-8 text-lg font-bold">
 163 |                   Register Now
 164 |                 </Button>
 165 |               </Link>
 166 |               <Link href="/education" className="w-full sm:w-auto">
 167 |                 <Button size="lg" variant="outline" className="w-full h-14 px-8 text-lg font-medium border-
white/20 text-white hover:bg-white/10 hover:text-w...
 168 |                   Learn More
 169 |                 </Button>
 170 |               </Link>
 171 |             </div>
 172 |           </div>
 173 |         </div>
 174 |       </section>
 175 |     </div>
 176 |   );
 177 | }
 178 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/locator.tsx

```
   1 | import { useState } from "react";
   2 | import { motion } from "framer-motion";
   3 | import { MapPin, Phone, Clock, Search, Filter, Droplets, ArrowRight } from "lucide-react";
   4 | import { useListHospitals } from "@workspace/api-client-react";
   5 |
   6 | import { Input } from "@/components/ui/input";
   7 | import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
   8 | import { Badge } from "@/components/ui/badge";
   9 | import { Skeleton } from "@/components/ui/skeleton";
  10 | import { Button } from "@/components/ui/button";
  11 | import { Card, CardContent } from "@/components/ui/card";
  12 |
  13 | export default function Locator() {
  14 |   const [cityFilter, setCityFilter] = useState<string>("");
  15 |   const [bloodTypeFilter, setBloodTypeFilter] = useState<string>("");
  16 |
  17 |   const { data, isLoading } = useListHospitals({
  18 |     query: {
  19 |       queryKey: ["hospitals", cityFilter, bloodTypeFilter],
  20 |     }
  21 |   }, {
  22 |     request: {
  23 |       url: `/api/hospitals?${cityFilter ? `city=${cityFilter}&` : ""}${bloodTypeFilter ?
`bloodType=${encodeURIComponent(bloodTypeFilter)}` : ""}`
  24 |     }
  25 |   });
  26 |
  27 |   return (
  28 |     <div className="min-h-screen bg-slate-50 py-12">
  29 |       <div className="container mx-auto px-4 md:px-6">
  30 |
  31 |         <div className="max-w-3xl mb-12">
  32 |           <h1 className="text-4xl font-bold tracking-tight text-foreground mb-4">Find a Donation Center</h1>
  33 |           <p className="text-xl text-muted-foreground">Locate hospitals and dedicated blood banks in the MBC
network near you.</p>
  34 |         </div>
  35 |
  36 |         <div className="bg-white p-6 rounded-2xl shadow-sm border border-border mb-10 flex flex-col md:flex-row
gap-4">
  37 |           <div className="flex-1 relative">
  38 |             <Search className="absolute left-3 top-3 h-5 w-5 text-muted-foreground" />
  39 |             <Input
  40 |               placeholder="Search by city..."
  41 |               className="pl-10 h-12 text-lg"
  42 |               value={cityFilter}
  43 |               onChange={(e) => setCityFilter(e.target.value)}
  44 |             />
  45 |           </div>
  46 |           <div className="w-full md:w-64">
  47 |             <Select value={bloodTypeFilter} onValueChange={setBloodTypeFilter}>
  48 |               <SelectTrigger className="h-12 text-lg">
  49 |                 <SelectValue placeholder="Needed Blood Type" />
  50 |               </SelectTrigger>
  51 |               <SelectContent>
  52 |                 <SelectItem value="all">All Types</SelectItem>
  53 |                 {["A+", "A-", "B+", "B-", "AB+", "AB-", "O+", "O-"].map(type => (
  54 |                   <SelectItem key={type} value={type}>{type}</SelectItem>
  55 |                 ))}
  56 |               </SelectContent>
  57 |             </Select>
  58 |           </div>
  59 |           {(cityFilter || bloodTypeFilter && bloodTypeFilter !== "all") && (
  60 |             <Button
  61 |               variant="ghost"
  62 |               className="h-12 px-6"
  63 |               onClick={() => {
  64 |                 setCityFilter("");
  65 |                 setBloodTypeFilter("");
  66 |               }}
  67 |             >
  68 |               Clear
  69 |             </Button>
  70 |           )}
  71 |         </div>
  72 |
  73 |         {isLoading ? (
  74 |           <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-6">
  75 |             {[1, 2, 3, 4, 5, 6].map((i) => (
  76 |               <Card key={i} className="overflow-hidden">
  77 |                 <Skeleton className="h-48 w-full rounded-none" />
  78 |                 <CardContent className="p-6">
  79 |                   <Skeleton className="h-6 w-3/4 mb-4" />
  80 |                   <Skeleton className="h-4 w-full mb-2" />
  81 |                   <Skeleton className="h-4 w-5/6" />
  82 |                 </CardContent>
  83 |               </Card>
  84 |             ))}
  85 |           </div>
  86 |         ) : data?.hospitals.length === 0 ? (
  87 |           <div className="text-center py-20 bg-white rounded-2xl border border-border">
  88 |             <div className="w-16 h-16 mx-auto bg-slate-100 rounded-full flex items-center justify-center mb-4">
  89 |               <MapPin className="w-8 h-8 text-slate-400" />
  90 |             </div>
  91 |             <h3 className="text-xl font-bold mb-2">No centers found</h3>
  92 |             <p class="text-muted-foreground">Try adjusting your search criteria.</p>
  93 |           </div>
  94 |         ) : (
  95 |           <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-6">
  96 |             {data?.hospitals.map((hospital, i) => (
  97 |               <motion.div
```

```
  98 |                  key={hospital.id}
  99 |                  initial={{ opacity: 0, y: 20 }}
 100 |                  animate={{ opacity: 1, y: 0 }}
 101 |                  transition={{ delay: i * 0.05 }}
 102 |                >
 103 |                  <Card className="h-full hover:shadow-md transition-shadow duration-300 border-border group
overflow-hidden flex flex-col">
 104 |                    <div className="h-32 bg-slate-100 relative">
 105 |                      <div className="absolute inset-0 opacity-20 bg-[url('https://www.transparenttextures.com/
patterns/cubes.png')]"></div>
 106 |                      <div className="absolute bottom-4 left-4">
 107 |                        {hospital.isBloodBank ? (
 108 |                          <Badge className="bg-primary hover:bg-primary/90 shadow-sm border-0">Dedicated Blood Bank</
Badge>
 109 |                        ) : (
 110 |                          <Badge variant="secondary" className="bg-white/90 backdrop-blur-sm shadow-sm">Partner
Hospital</Badge>
 111 |                        )}
 112 |                      </div>
 113 |                    </div>
 114 |
 115 |                    <CardContent className="p-6 flex flex-col flex-1">
 116 |                      <h3 className="text-xl font-bold text-foreground mb-4 group-hover:text-primary transition-
colors">{hospital.name}</h3>
 117 |
 118 |                      <div className="space-y-3 mb-6 flex-1">
 119 |                        <div className="flex items-start gap-3 text-muted-foreground text-sm">
 120 |                          <MapPin className="w-4 h-4 mt-0.5 text-primary shrink-0" />
 121 |                          <span>{hospital.address}, {hospital.city}</span>
 122 |                        </div>
 123 |                        <div className="flex items-center gap-3 text-muted-foreground text-sm">
 124 |                          <Phone className="w-4 h-4 text-primary shrink-0" />
 125 |                          <span>{hospital.phone}</span>
 126 |                        </div>
 127 |                        <div className="flex items-center gap-3 text-muted-foreground text-sm">
 128 |                          <Clock className="w-4 h-4 text-primary shrink-0" />
 129 |                          <span>{hospital.operatingHours}</span>
 130 |                        </div>
 131 |                      </div>
 132 |
 133 |                      <div>
 134 |                        <p className="text-xs font-medium text-slate-500 uppercase tracking-wider mb-2 flex items-
center gap-1">
 135 |                          <Droplets className="w-3 h-3" /> Critical Needs
 136 |                        </p>
 137 |                        <div className="flex flex-wrap gap-2">
 138 |                          {hospital.availableBloodTypes.map(type => (
 139 |                            <span key={type} className="inline-flex items-center justify-center w-8 h-8 rounded-md
bg-red-50 text-red-600 font-bold text-sm bor...
 140 |                              {type}
 141 |                            </span>
 142 |                          ))}
 143 |                        </div>
 144 |                      </div>
 145 |
 146 |                      <Button variant="outline" className="w-full mt-6 justify-between group-hover:bg-primary group-
hover:text-white group-hover:border-primary...
 147 |                        Get Directions <ArrowRight className="w-4 h-4 opacity-50 group-hover:opacity-100" />
 148 |                      </Button>
 149 |                    </CardContent>
 150 |                  </Card>
 151 |                </motion.div>
 152 |              ))}
 153 |            </div>
 154 |          )}
 155 |        </div>
 156 |      </div>
 157 |    );
 158 | }
 159 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/not-found.tsx

```
1 | import { Card, CardContent } from "@/components/ui/card";
2 | import { AlertCircle } from "lucide-react";
3 |
4 | export default function NotFound() {
5 |   return (
6 |     <div className="min-h-screen w-full flex items-center justify-center bg-gray-50">
7 |       <Card className="w-full max-w-md mx-4">
8 |         <CardContent className="pt-6">
9 |           <div className="flex mb-4 gap-2">
10 |             <AlertCircle className="h-8 w-8 text-red-500" />
11 |             <h1 className="text-2xl font-bold text-gray-900">404 Page Not Found</h1>
12 |           </div>
13 |
14 |           <p className="mt-4 text-sm text-gray-600">
15 |             Did you forget to add the page to the router?
16 |           </p>
17 |         </CardContent>
18 |       </Card>
19 |     </div>
20 |   );
21 | }
22 |
```

— end of file —

File: artifacts/mbc-platform/src/pages/register-donor.tsx

```
   1 | import { useState } from "react";
   2 | import { useLocation } from "wouter";
   3 | import { useForm } from "react-hook-form";
   4 | import { zodResolver } from "@hookform/resolvers/zod";
   5 | import * as z from "zod";
   6 | import { motion, AnimatePresence } from "framer-motion";
   7 | import { Heart, CheckCircle2, ChevronRight, Droplets, MapPin, Phone, Calendar as CalendarIcon, User, AlertCircle }
from "lucide-react";
   8 |
   9 | import { useRegisterDonor } from "@workspace/api-client-react";
  10 | import { Button } from "@/components/ui/button";
  11 | import { Form, FormControl, FormField, FormItem, FormLabel, FormMessage, FormDescription } from "@/components/ui/
form";
  12 | import { Input } from "@/components/ui/input";
  13 | import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
  14 | import { Checkbox } from "@/components/ui/checkbox";
  15 | import { useToast } from "@/hooks/use-toast";
  16 |
  17 | const formSchema = z.object({
  18 |   firstName: z.string().min(2, "First name is required"),
  19 |   lastName: z.string().min(2, "Last name is required"),
  20 |   bloodType: z.string().min(1, "Blood type is required"),
  21 |   city: z.string().min(2, "City is required"),
  22 |   phone: z.string().min(10, "Valid phone number is required"),
  23 |   dateOfBirth: z.string().min(1, "Date of birth is required"),
  24 |   weight: z.coerce.number().min(50, "Must weigh at least 50kg (110 lbs) to donate"),
  25 |   lastDonationDate: z.string().optional(),
  26 |   hasChronicDisease: z.boolean().default(false),
  27 |   email: z.string().email("Valid email is required").optional().or(z.literal("")),
  28 | });
  29 |
  30 | type FormValues = z.infer<typeof formSchema>;
  31 |
  32 | export default function RegisterDonor() {
  33 |   const [, setLocation] = useLocation();
  34 |   const { toast } = useToast();
  35 |   const [step, setStep] = useState(1);
  36 |   const [isEligible, setIsEligible] = useState<boolean | null>(null);
  37 |
  38 |   const registerDonor = useRegisterDonor();
  39 |
  40 |   const form = useForm<FormValues>({
  41 |     resolver: zodResolver(formSchema),
  42 |     defaultValues: {
  43 |       firstName: "",
  44 |       lastName: "",
  45 |       bloodType: "",
  46 |       city: "",
  47 |       phone: "",
  48 |       dateOfBirth: "",
  49 |       weight: 0,
  50 |       lastDonationDate: "",
  51 |       hasChronicDisease: false,
  52 |       email: "",
  53 |     },
  54 |   });
  55 |
  56 |   const checkEligibility = () => {
  57 |     const values = form.getValues();
  58 |     const isWeightOk = values.weight >= 50;
  59 |     const isDiseaseOk = !values.hasChronicDisease;
  60 |     // Add age check if needed
  61 |
  62 |     if (isWeightOk && isDiseaseOk) {
  63 |       setIsEligible(true);
  64 |       setStep(2);
  65 |     } else {
  66 |       setIsEligible(false);
  67 |     }
  68 |   };
  69 |
  70 |   function onSubmit(data: FormValues) {
  71 |     if (!isEligible) {
  72 |       toast({
  73 |         title: "Ineligible to donate",
  74 |         description: "Based on the provided information, you currently do not meet the eligibility criteria to
donate blood.",
  75 |         variant: "destructive",
  76 |       });
  77 |       return;
  78 |     }
  79 |
  80 |     registerDonor.mutate(
  81 |       { data },
  82 |       {
  83 |         onSuccess: () => {
  84 |           toast({
  85 |             title: "Registration successful",
  86 |             description: "Thank you for registering as a donor. Every drop counts.",
  87 |           });
  88 |           setLocation("/");
  89 |         },
  90 |         onError: () => {
  91 |           toast({
  92 |             title: "Registration failed",
  93 |             description: "There was an error registering your profile. Please try again.",
  94 |             variant: "destructive",
  95 |           });
  96 |         },
  97 |       }
```

```
  98 |     );
  99 |   }
 100 |
 101 |   return (
 102 |     <div className="min-h-screen bg-slate-50 py-12">
 103 |       <div className="container max-w-3xl mx-auto px-4">
 104 |
 105 |         <div className="text-center mb-10">
 106 |           <div className="inline-flex items-center justify-center w-16 h-16 rounded-full bg-primary/10 text-
primary mb-4">
 107 |             <Heart className="w-8 h-8" />
 108 |           </div>
 109 |           <h1 className="text-3xl md:text-4xl font-bold tracking-tight text-foreground mb-4">
 110 |             Register as a Donor
 111 |           </h1>
 112 |           <p className="text-muted-foreground text-lg max-w-xl mx-auto">
 113 |             Join the MBC network. Your commitment today means someone gets a second chance at life tomorrow.
 114 |           </p>
 115 |         </div>
 116 |
 117 |         <div className="bg-white rounded-2xl shadow-xl overflow-hidden border border-border">
 118 |
 119 |           <div className="flex border-b border-border">
 120 |             <div className={`flex-1 text-center py-4 font-medium text-sm transition-colors ${step === 1 ? "bg-
primary/5 text-primary border-b-2 border-primar...
 121 |               1. Eligibility Check
 122 |             </div>
 123 |             <div className={`flex-1 text-center py-4 font-medium text-sm transition-colors ${step === 2 ? "bg-
primary/5 text-primary border-b-2 border-primar...
 124 |               2. Personal Details
 125 |             </div>
 126 |           </div>
 127 |
 128 |           <div className="p-6 md:p-10">
 129 |             <Form {...form}>
 130 |               <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-8">
 131 |
 132 |                 <AnimatePresence mode="wait">
 133 |                   {step === 1 && (
 134 |                     <motion.div
 135 |                       key="step1"
 136 |                       initial={{ opacity: 0, x: -20 }}
 137 |                       animate={{ opacity: 1, x: 0 }}
 138 |                       exit={{ opacity: 0, x: 20 }}
 139 |                       className="space-y-6"
 140 |                     >
 141 |                       <h2 className="text-xl font-bold mb-6">Basic Eligibility</h2>
 142 |
 143 |                       <div className="grid md:grid-cols-2 gap-6">
 144 |                         <FormField
 145 |                           control={form.control}
 146 |                           name="weight"
 147 |                           render={({ field }) => (
 148 |                             <FormItem>
 149 |                               <FormLabel>Body Weight (kg)</FormLabel>
 150 |                               <FormControl>
 151 |                                 <Input type="number" placeholder="e.g. 70" {...field} />
 152 |                               </FormControl>
 153 |                               <FormDescription>Must be at least 50kg</FormDescription>
 154 |                               <FormMessage />
 155 |                             </FormItem>
 156 |                           )}
 157 |                         />
 158 |
 159 |                         <FormField
 160 |                           control={form.control}
 161 |                           name="dateOfBirth"
 162 |                           render={({ field }) => (
 163 |                             <FormItem>
 164 |                               <FormLabel>Date of Birth</FormLabel>
 165 |                               <FormControl>
 166 |                                 <Input type="date" {...field} />
 167 |                               </FormControl>
 168 |                               <FormDescription>Must be between 18 and 65</FormDescription>
 169 |                               <FormMessage />
 170 |                             </FormItem>
 171 |                           )}
 172 |                         />
 173 |                       </div>
 174 |
 175 |                       <FormField
 176 |                         control={form.control}
 177 |                         name="hasChronicDisease"
 178 |                         render={({ field }) => (
 179 |                           <FormItem className="flex flex-row items-start space-x-3 space-y-0 rounded-md border
p-4">
 180 |                             <FormControl>
 181 |                               <Checkbox
 182 |                                 checked={field.value}
 183 |                                 onCheckedChange={field.onChange}
 184 |                               />
 185 |                             </FormControl>
 186 |                             <div className="space-y-1 leading-none">
 187 |                               <FormLabel>
 188 |                                 Do you have any chronic medical conditions?
 189 |                               </FormLabel>
 190 |                               <FormDescription>
 191 |                                 Such as severe heart disease, chronic lung disease, etc.
 192 |                               </FormDescription>
 193 |                             </div>
 194 |                           </FormItem>
 195 |                         )}
 196 |                       />
```

```
197 |
198 |                         {isEligible === false && (
199 |                           <div className="p-4 bg-destructive/10 text-destructive rounded-lg flex items-start gap-3">
200 |                             <AlertCircle className="w-5 h-5 shrink-0 mt-0.5" />
201 |                             <div>
202 |                               <h4 className="font-semibold">Currently Ineligible</h4>
203 |                               <p className="text-sm mt-1">Based on the provided information, you do not meet the
minimum requirements for blood donation. Thank...
204 |                             </div>
205 |                           </div>
206 |                         )}
207 |
208 |                         <Button type="button" size="lg" className="w-full" onClick={checkEligibility}>
209 |                           Continue <ChevronRight className="w-4 h-4 ml-2" />
210 |                         </Button>
211 |                       </motion.div>
212 |                     )}
213 |
214 |                     {step === 2 && (
215 |                       <motion.div
216 |                         key="step2"
217 |                         initial={{ opacity: 0, x: -20 }}
218 |                         animate={{ opacity: 1, x: 0 }}
219 |                         exit={{ opacity: 0, x: 20 }}
220 |                         className="space-y-6"
221 |                       >
222 |                         <h2 className="text-xl font-bold mb-6">Contact & Profile</h2>
223 |
224 |                         <div className="grid md:grid-cols-2 gap-6">
225 |                           <FormField
226 |                             control={form.control}
227 |                             name="firstName"
228 |                             render={({ field }) => (
229 |                               <FormItem>
230 |                                 <FormLabel>First Name</FormLabel>
231 |                                 <FormControl>
232 |                                   <div className="relative">
233 |                                     <User className="absolute left-3 top-3 h-4 w-4 text-muted-foreground" />
234 |                                     <Input className="pl-9" placeholder="John" {...field} />
235 |                                   </div>
236 |                                 </FormControl>
237 |                                 <FormMessage />
238 |                               </FormItem>
239 |                             )}
240 |                           />
241 |
242 |                           <FormField
243 |                             control={form.control}
244 |                             name="lastName"
245 |                             render={({ field }) => (
246 |                               <FormItem>
247 |                                 <FormLabel>Last Name</FormLabel>
248 |                                 <FormControl>
249 |                                   <Input placeholder="Doe" {...field} />
250 |                                 </FormControl>
251 |                                 <FormMessage />
252 |                               </FormItem>
253 |                             )}
254 |                           />
255 |                         </div>
256 |
257 |                         <div className="grid md:grid-cols-2 gap-6">
258 |                           <FormField
259 |                             control={form.control}
260 |                             name="bloodType"
261 |                             render={({ field }) => (
262 |                               <FormItem>
263 |                                 <FormLabel>Blood Type</FormLabel>
264 |                                 <Select onValueChange={field.onChange} defaultValue={field.value}>
265 |                                   <FormControl>
266 |                                     <SelectTrigger>
267 |                                       <SelectValue placeholder="Select blood type" />
268 |                                     </SelectTrigger>
269 |                                   </FormControl>
270 |                                   <SelectContent>
271 |                                     {["A+", "A-", "B+", "B-", "AB+", "AB-", "O+", "O-"].map(type => (
272 |                                       <SelectItem key={type} value={type}>{type}</SelectItem>
273 |                                     ))}
274 |                                   </SelectContent>
275 |                                 </Select>
276 |                                 <FormMessage />
277 |                               </FormItem>
278 |                             )}
279 |                           />
280 |
281 |                           <FormField
282 |                             control={form.control}
283 |                             name="lastDonationDate"
284 |                             render={({ field }) => (
285 |                               <FormItem>
286 |                                 <FormLabel>Last Donation Date (Optional)</FormLabel>
287 |                                 <FormControl>
288 |                                   <div className="relative">
289 |                                     <CalendarIcon className="absolute left-3 top-3 h-4 w-4 text-muted-foreground" />
290 |                                     <Input type="date" className="pl-9" {...field} />
291 |                                   </div>
292 |                                 </FormControl>
293 |                                 <FormMessage />
294 |                               </FormItem>
295 |                             )}
296 |                           />
297 |                         </div>
298 |
```

```
                      <div className="grid md:grid-cols-2 gap-6">
                        <FormField
                          control={form.control}
                          name="phone"
                          render={({ field }) => (
                            <FormItem>
                              <FormLabel>Emergency Contact Number</FormLabel>
                              <FormControl>
                                <div className="relative">
                                  <Phone className="absolute left-3 top-3 h-4 w-4 text-muted-foreground" />
                                  <Input className="pl-9" type="tel" placeholder="+1 (555) 000-0000" {...field} />
                                </div>
                              </FormControl>
                              <FormMessage />
                            </FormItem>
                          )}
                        />

                        <FormField
                          control={form.control}
                          name="email"
                          render={({ field }) => (
                            <FormItem>
                              <FormLabel>Email Address (Optional)</FormLabel>
                              <FormControl>
                                <Input type="email" placeholder="john@example.com" {...field} />
                              </FormControl>
                              <FormMessage />
                            </FormItem>
                          )}
                        />
                      </div>

                      <FormField
                        control={form.control}
                        name="city"
                        render={({ field }) => (
                          <FormItem>
                            <FormLabel>City</FormLabel>
                            <FormControl>
                              <div className="relative">
                                <MapPin className="absolute left-3 top-3 h-4 w-4 text-muted-foreground" />
                                <Input className="pl-9" placeholder="San Francisco" {...field} />
                              </div>
                            </FormControl>
                            <FormDescription>Where you can donate locally</FormDescription>
                            <FormMessage />
                          </FormItem>
                        )}
                      />

                      <div className="flex gap-4 pt-4 border-t border-border">
                        <Button type="button" variant="outline" onClick={() => setStep(1)} className="w-full">
                          Back
                        </Button>
                        <Button type="submit" className="w-full" disabled={registerDonor.isPending}>
                          {registerDonor.isPending ? "Registering..." : "Complete Registration"}
                        </Button>
                      </div>
                    </motion.div>
                  )}
                </AnimatePresence>

              </form>
            </Form>
          </div>
        </div>
      </div>
    </div>
  );
}
```

— end of file —

File: artifacts/mbc-platform/src/pages/request-blood.tsx

```
   1 | import { useState } from "react";
   2 | import { useLocation } from "wouter";
   3 | import { useForm } from "react-hook-form";
   4 | import { zodResolver } from "@hookform/resolvers/zod";
   5 | import * as z from "zod";
   6 | import { motion } from "framer-motion";
   7 | import { AlertCircle, Clock, MapPin, Activity, User, Phone, FileText } from "lucide-react";
   8 |
   9 | import { useCreateBloodRequest } from "@workspace/api-client-react";
  10 | import { Button } from "@/components/ui/button";
  11 | import { Form, FormControl, FormField, FormItem, FormLabel, FormMessage, FormDescription } from "@/components/ui/
form";
  12 | import { Input } from "@/components/ui/input";
  13 | import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
  14 | import { Textarea } from "@/components/ui/textarea";
  15 | import { useToast } from "@/hooks/use-toast";
  16 | import { Alert, AlertDescription, AlertTitle } from "@/components/ui/alert";
  17 |
  18 | const formSchema = z.object({
  19 |   patientName: z.string().min(2, "Patient name is required"),
  20 |   bloodType: z.string().min(1, "Blood type is required"),
  21 |   unitsNeeded: z.coerce.number().min(1, "At least 1 unit is required").max(20, "Max 20 units per request"),
  22 |   hospitalName: z.string().min(2, "Hospital name is required"),
  23 |   city: z.string().min(2, "City is required"),
  24 |   urgency: z.enum(["critical", "high", "standard"]),
  25 |   contactPhone: z.string().min(10, "Valid phone number is required"),
  26 |   notes: z.string().optional(),
  27 | });
  28 |
  29 | type FormValues = z.infer<typeof formSchema>;
  30 |
  31 | export default function RequestBlood() {
  32 |   const [, setLocation] = useLocation();
  33 |   const { toast } = useToast();
  34 |
  35 |   const createRequest = useCreateBloodRequest();
  36 |
  37 |   const form = useForm<FormValues>({
  38 |     resolver: zodResolver(formSchema),
  39 |     defaultValues: {
  40 |       patientName: "",
  41 |       bloodType: "",
  42 |       unitsNeeded: 1,
  43 |       hospitalName: "",
  44 |       city: "",
  45 |       urgency: "high",
  46 |       contactPhone: "",
  47 |       notes: "",
  48 |     },
  49 |   });
  50 |
  51 |   const urgencyWatch = form.watch("urgency");
  52 |
  53 |   function onSubmit(data: FormValues) {
  54 |     createRequest.mutate(
  55 |       { data },
  56 |       {
  57 |         onSuccess: () => {
  58 |           toast({
  59 |             title: "Emergency Request Broadcasted",
  60 |             description: "Your request has been added to the live feed. Eligible donors are being notified.",
  61 |             variant: "default",
  62 |           });
  63 |           setLocation("/emergency");
  64 |         },
  65 |         onError: () => {
  66 |           toast({
  67 |             title: "Request failed",
  68 |             description: "There was an error broadcasting the request. Please try again or call the hotline.",
  69 |             variant: "destructive",
  70 |           });
  71 |         },
  72 |       }
  73 |     );
  74 |   }
  75 |
  76 |   return (
  77 |     <div className="min-h-screen bg-slate-50 py-12">
  78 |       <div className="container max-w-3xl mx-auto px-4">
  79 |
  80 |         <motion.div
  81 |           initial={{ opacity: 0, y: 20 }}
  82 |           animate={{ opacity: 1, y: 0 }}
  83 |           className="bg-white rounded-2xl shadow-2xl overflow-hidden border border-destructive/20 relative"
  84 |         >
  85 |           <div className="absolute top-0 left-0 w-full h-2 bg-destructive"></div>
  86 |
  87 |           <div className="p-6 md:p-10">
  88 |             <div className="flex items-center gap-4 mb-8 pb-8 border-b border-border">
  89 |               <div className="w-16 h-16 bg-destructive/10 rounded-full flex items-center justify-center text-
destructive shrink-0">
  90 |                 <AlertCircle className="w-8 h-8" />
  91 |               </div>
  92 |               <div>
  93 |                 <h1 className="text-3xl font-bold text-foreground">Emergency Blood Request</h1>
  94 |                 <p className="text-muted-foreground mt-1">This request will immediately alert eligible donors in
your area.</p>
  95 |               </div>
  96 |             </div>
  97 |
```

```
  98 |             {urgencyWatch === "critical" && (
  99 |               <Alert variant="destructive" className="mb-8 bg-destructive/5">
 100 |                 <AlertCircle className="h-4 w-4" />
 101 |                 <AlertTitle>Critical Urgency Selected</AlertTitle>
 102 |                 <AlertDescription>
 103 |                   This request will bypass standard queuing and trigger immediate SMS alerts to all matching
donors within a 15-mile radius.
 104 |                 </AlertDescription>
 105 |               </Alert>
 106 |             )}
 107 |
 108 |             <Form {...form}>
 109 |               <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-8">
 110 |
 111 |                 <div className="space-y-6">
 112 |                   <h3 className="text-lg font-bold flex items-center gap-2">
 113 |                     <User className="w-5 h-5 text-primary" /> Patient Details
 114 |                   </h3>
 115 |
 116 |                   <div className="grid md:grid-cols-2 gap-6 bg-slate-50 p-6 rounded-xl border border-border">
 117 |                     <FormField
 118 |                       control={form.control}
 119 |                       name="patientName"
 120 |                       render={({ field }) => (
 121 |                         <FormItem>
 122 |                           <FormLabel>Patient Name or ID</FormLabel>
 123 |                           <FormControl>
 124 |                             <Input placeholder="Enter patient identifier" {...field} />
 125 |                           </FormControl>
 126 |                           <FormMessage />
 127 |                         </FormItem>
 128 |                       )}
 129 |                     />
 130 |
 131 |                     <div className="grid grid-cols-2 gap-4">
 132 |                       <FormField
 133 |                         control={form.control}
 134 |                         name="bloodType"
 135 |                         render={({ field }) => (
 136 |                           <FormItem>
 137 |                             <FormLabel>Blood Type</FormLabel>
 138 |                             <Select onValueChange={field.onChange} defaultValue={field.value}>
 139 |                               <FormControl>
 140 |                                 <SelectTrigger>
 141 |                                   <SelectValue placeholder="Type" />
 142 |                                 </SelectTrigger>
 143 |                               </FormControl>
 144 |                               <SelectContent>
 145 |                                 {["A+", "A-", "B+", "B-", "AB+", "AB-", "O+", "O-"].map(type => (
 146 |                                   <SelectItem key={type} value={type}>{type}</SelectItem>
 147 |                                 ))}
 148 |                               </SelectContent>
 149 |                             </Select>
 150 |                             <FormMessage />
 151 |                           </FormItem>
 152 |                         )}
 153 |                       />
 154 |
 155 |                       <FormField
 156 |                         control={form.control}
 157 |                         name="unitsNeeded"
 158 |                         render={({ field }) => (
 159 |                           <FormItem>
 160 |                             <FormLabel>Units</FormLabel>
 161 |                             <FormControl>
 162 |                               <Input type="number" min="1" max="20" {...field} />
 163 |                             </FormControl>
 164 |                             <FormMessage />
 165 |                           </FormItem>
 166 |                         )}
 167 |                       />
 168 |                     </div>
 169 |                   </div>
 170 |                 </div>
 171 |
 172 |                 <div className="space-y-6">
 173 |                   <h3 className="text-lg font-bold flex items-center gap-2">
 174 |                     <Activity className="w-5 h-5 text-primary" /> Request Logistics
 175 |                   </h3>
 176 |
 177 |                   <div className="bg-slate-50 p-6 rounded-xl border border-border space-y-6">
 178 |                     <FormField
 179 |                       control={form.control}
 180 |                       name="urgency"
 181 |                       render={({ field }) => (
 182 |                         <FormItem>
 183 |                           <FormLabel>Urgency Level</FormLabel>
 184 |                           <Select onValueChange={field.onChange} defaultValue={field.value}>
 185 |                             <FormControl>
 186 |                               <SelectTrigger className={
 187 |                                 field.value === "critical" ? "border-destructive text-destructive font-bold" :
 188 |                                 field.value === "high" ? "border-orange-500 text-orange-600 font-semibold" : ""
 189 |                               }>
 190 |                                 <SelectValue placeholder="Select urgency" />
 191 |                               </SelectTrigger>
 192 |                             </FormControl>
 193 |                             <SelectContent>
 194 |                               <SelectItem value="critical" className="text-destructive font-bold">CRITICAL (Needed
within 2 hours)</SelectItem>
 195 |                               <SelectItem value="high" className="text-orange-600 font-semibold">HIGH (Needed
today)</SelectItem>
 196 |                               <SelectItem value="standard">STANDARD (Needed within 48 hours)</SelectItem>
 197 |                             </SelectContent>
```

```
                        </Select>
                        <FormMessage />
                      </FormItem>
                    )}
                  />

                  <div className="grid md:grid-cols-2 gap-6">
                    <FormField
                      control={form.control}
                      name="hospitalName"
                      render={({ field }) => (
                        <FormItem>
                          <FormLabel>Hospital / Facility Name</FormLabel>
                          <FormControl>
                            <div className="relative">
                              <MapPin className="absolute left-3 top-3 h-4 w-4 text-muted-foreground" />
                              <Input className="pl-9" placeholder="e.g. Mercy General" {...field} />
                            </div>
                          </FormControl>
                          <FormMessage />
                        </FormItem>
                      )}
                    />

                    <FormField
                      control={form.control}
                      name="city"
                      render={({ field }) => (
                        <FormItem>
                          <FormLabel>City</FormLabel>
                          <FormControl>
                            <Input placeholder="Location" {...field} />
                          </FormControl>
                          <FormMessage />
                        </FormItem>
                      )}
                    />
                  </div>
                </div>
              </div>

              <div className="space-y-6">
                <h3 className="text-lg font-bold flex items-center gap-2">
                  <Phone className="w-5 h-5 text-primary" /> Contact & Notes
                </h3>

                <div className="grid md:grid-cols-2 gap-6">
                  <FormField
                    control={form.control}
                    name="contactPhone"
                    render={({ field }) => (
                      <FormItem>
                        <FormLabel>Direct Contact Phone</FormLabel>
                        <FormControl>
                          <Input type="tel" placeholder="Staff or desk number" {...field} />
                        </FormControl>
                        <FormDescription>Where donors/MBC staff can reach you directly</FormDescription>
                        <FormMessage />
                      </FormItem>
                    )}
                  />
                </div>

                <FormField
                  control={form.control}
                  name="notes"
                  render={({ field }) => (
                    <FormItem>
                      <FormLabel>Additional Clinical Notes (Optional)</FormLabel>
                      <FormControl>
                        <Textarea
                          placeholder="Any specific requirements (e.g., CMV negative, irradiated)"
                          className="resize-none"
                          {...field}
                        />
                      </FormControl>
                      <FormMessage />
                    </FormItem>
                  )}
                />
              </div>

              <div className="pt-6">
                <Button
                  type="submit"
                  variant="destructive"
                  size="lg"
                  className="w-full h-14 text-lg font-bold shadow-lg"
                  disabled={createRequest.isPending}
                >
                  {createRequest.isPending ? "Broadcasting Request..." : "Broadcast Emergency Request"}
                </Button>
              </div>
            </form>
          </Form>
        </div>
      </motion.div>
    </div>
  </div>
  );
}
```

— end of file —

File: lib/api-client-react/package.json

```
 1 | {
 2 |   "name": "@workspace/api-client-react",
 3 |   "version": "0.0.0",
 4 |   "private": true,
 5 |   "type": "module",
 6 |   "exports": {
 7 |     ".": "./src/index.ts"
 8 |   },
 9 |   "dependencies": {
10 |     "@tanstack/react-query": "catalog:"
11 |   },
12 |   "peerDependencies": {
13 |     "react": ">=18"
14 |   }
15 | }
16 |
```

— end of file —

File: lib/api-client-react/src/custom-fetch.ts

```
  1 | export type CustomFetchOptions = RequestInit & {
  2 |   responseType?: "json" | "text" | "blob" | "auto";
  3 | };
  4 |
  5 | export type ErrorType<T = unknown> = ApiError<T>;
  6 |
  7 | export type BodyType<T> = T;
  8 |
  9 | export type AuthTokenGetter = () => Promise<string | null> | string | null;
 10 |
 11 | const NO_BODY_STATUS = new Set([204, 205, 304]);
 12 | const DEFAULT_JSON_ACCEPT = "application/json, application/problem+json";
 13 |
 14 | // ---------------------------------------------------------------------------
 15 | // Module-level configuration
 16 | // ---------------------------------------------------------------------------
 17 |
 18 | let _baseUrl: string | null = null;
 19 | let _authTokenGetter: AuthTokenGetter | null = null;
 20 |
 21 | /**
 22 |  * Set a base URL that is prepended to every relative request URL
 23 |  * (i.e. paths that start with `/`).
 24 |  *
 25 |  * Useful for Expo bundles that need to call a remote API server.
 26 |  * Pass `null` to clear the base URL.
 27 |  */
 28 | export function setBaseUrl(url: string | null): void {
 29 |   _baseUrl = url ? url.replace(/\/+$/, "") : null;
 30 | }
 31 |
 32 | /**
 33 |  * Register a getter that supplies a bearer auth token.  Before every fetch
 34 |  * the getter is invoked; when it returns a non-null string, an
 35 |  * `Authorization: Bearer <token>` header is attached to the request.
 36 |  *
 37 |  * Useful for Expo bundles making token-gated API calls.
 38 |  * Pass `null` to clear the getter.
 39 |  *
 40 |  * NOTE: This function should never be used in web applications where session
 41 |  * token cookies are automatically associated with API calls by the browser.
 42 |  */
 43 | export function setAuthTokenGetter(getter: AuthTokenGetter | null): void {
 44 |   _authTokenGetter = getter;
 45 | }
 46 |
 47 | function isRequest(input: RequestInfo | URL): input is Request {
 48 |   return typeof Request !== "undefined" && input instanceof Request;
 49 | }
 50 |
 51 | function resolveMethod(input: RequestInfo | URL, explicitMethod?: string): string {
 52 |   if (explicitMethod) return explicitMethod.toUpperCase();
 53 |   if (isRequest(input)) return input.method.toUpperCase();
 54 |   return "GET";
 55 | }
 56 |
 57 | // Use loose check for URL — some runtimes (e.g. React Native) polyfill URL
 58 | // differently, so `instanceof URL` can fail.
 59 | function isUrl(input: RequestInfo | URL): input is URL {
 60 |   return typeof URL !== "undefined" && input instanceof URL;
 61 | }
 62 |
 63 | function applyBaseUrl(input: RequestInfo | URL): RequestInfo | URL {
 64 |   if (!_baseUrl) return input;
 65 |   const url = resolveUrl(input);
 66 |   // Only prepend to relative paths (starting with /)
 67 |   if (!url.startsWith("/")) return input;
 68 |
 69 |   const absolute = `${_baseUrl}${url}`;
 70 |   if (typeof input === "string") return absolute;
 71 |   if (isUrl(input)) return new URL(absolute);
 72 |   return new Request(absolute, input as Request);
 73 | }
 74 |
 75 | function resolveUrl(input: RequestInfo | URL): string {
 76 |   if (typeof input === "string") return input;
 77 |   if (isUrl(input)) return input.toString();
 78 |   return input.url;
 79 | }
 80 |
 81 | function mergeHeaders(...sources: Array<HeadersInit | undefined>): Headers {
 82 |   const headers = new Headers();
 83 |
 84 |   for (const source of sources) {
 85 |     if (!source) continue;
 86 |     new Headers(source).forEach((value, key) => {
 87 |       headers.set(key, value);
 88 |     });
 89 |   }
 90 |
 91 |   return headers;
 92 | }
 93 |
 94 | function getMediaType(headers: Headers): string | null {
 95 |   const value = headers.get("content-type");
 96 |   return value ? value.split(";", 1)[0].trim().toLowerCase() : null;
 97 | }
 98 |
 99 | function isJsonMediaType(mediaType: string | null): boolean {
100 |   return mediaType === "application/json" || Boolean(mediaType?.endsWith("+json"));
```

```
101 | }
102 |
103 | function isTextMediaType(mediaType: string | null): boolean {
104 |   return Boolean(
105 |     mediaType &&
106 |       (mediaType.startsWith("text/") ||
107 |         mediaType === "application/xml" ||
108 |         mediaType === "text/xml" ||
109 |         mediaType.endsWith("+xml") ||
110 |         mediaType === "application/x-www-form-urlencoded"),
111 |   );
112 | }
113 |
114 | // Use strict equality: in browsers, `response.body` is `null` when the
115 | // response genuinely has no content.  In React Native, `response.body` is
116 | // always `undefined` because the ReadableStream API is not implemented —
117 | // even when the response carries a full payload readable via `.text()` or
118 | // `.json()`.  Loose equality (`== null`) matches both `null` and `undefined`,
119 | // which causes every React Native response to be treated as empty.
120 | function hasNoBody(response: Response, method: string): boolean {
121 |   if (method === "HEAD") return true;
122 |   if (NO_BODY_STATUS.has(response.status)) return true;
123 |   if (response.headers.get("content-length") === "0") return true;
124 |   if (response.body === null) return true;
125 |   return false;
126 | }
127 |
128 | function stripBom(text: string): string {
129 |   return text.charCodeAt(0) === 0xfeff ? text.slice(1) : text;
130 | }
131 |
132 | function looksLikeJson(text: string): boolean {
133 |   const trimmed = text.trimStart();
134 |   return trimmed.startsWith("{") || trimmed.startsWith("[");
135 | }
136 |
137 | function getStringField(value: unknown, key: string): string | undefined {
138 |   if (!value || typeof value !== "object") return undefined;
139 |
140 |   const candidate = (value as Record<string, unknown>)[key];
141 |   if (typeof candidate !== "string") return undefined;
142 |
143 |   const trimmed = candidate.trim();
144 |   return trimmed === "" ? undefined : trimmed;
145 | }
146 |
147 | function truncate(text: string, maxLength = 300): string {
148 |   return text.length > maxLength ? `${text.slice(0, maxLength - 1)}…` : text;
149 | }
150 |
151 | function buildErrorMessage(response: Response, data: unknown): string {
152 |   const prefix = `HTTP ${response.status} ${response.statusText}`;
153 |
154 |   if (typeof data === "string") {
155 |     const text = data.trim();
156 |     return text ? `${prefix}: ${truncate(text)}` : prefix;
157 |   }
158 |
159 |   const title = getStringField(data, "title");
160 |   const detail = getStringField(data, "detail");
161 |   const message =
162 |     getStringField(data, "message") ??
163 |     getStringField(data, "error_description") ??
164 |     getStringField(data, "error");
165 |
166 |   if (title && detail) return `${prefix}: ${title} — ${detail}`;
167 |   if (detail) return `${prefix}: ${detail}`;
168 |   if (message) return `${prefix}: ${message}`;
169 |   if (title) return `${prefix}: ${title}`;
170 |
171 |   return prefix;
172 | }
173 |
174 | export class ApiError<T = unknown> extends Error {
175 |   readonly name = "ApiError";
176 |   readonly status: number;
177 |   readonly statusText: string;
178 |   readonly data: T | null;
179 |   readonly headers: Headers;
180 |   readonly response: Response;
181 |   readonly method: string;
182 |   readonly url: string;
183 |
184 |   constructor(
185 |     response: Response,
186 |     data: T | null,
187 |     requestInfo: { method: string; url: string },
188 |   ) {
189 |     super(buildErrorMessage(response, data));
190 |     Object.setPrototypeOf(this, new.target.prototype);
191 |
192 |     this.status = response.status;
193 |     this.statusText = response.statusText;
194 |     this.data = data;
195 |     this.headers = response.headers;
196 |     this.response = response;
197 |     this.method = requestInfo.method;
198 |     this.url = response.url || requestInfo.url;
199 |   }
200 | }
201 |
202 | export class ResponseParseError extends Error {
203 |   readonly name = "ResponseParseError";
```

```
204 |   readonly status: number;
205 |   readonly statusText: string;
206 |   readonly headers: Headers;
207 |   readonly response: Response;
208 |   readonly method: string;
209 |   readonly url: string;
210 |   readonly rawBody: string;
211 |   readonly cause: unknown;
212 |
213 |   constructor(
214 |     response: Response,
215 |     rawBody: string,
216 |     cause: unknown,
217 |     requestInfo: { method: string; url: string },
218 |   ) {
219 |     super(
220 |       `Failed to parse response from ${requestInfo.method} ${response.url || requestInfo.url} ` +
221 |         `(${response.status} ${response.statusText}) as JSON`,
222 |     );
223 |     Object.setPrototypeOf(this, new.target.prototype);
224 |
225 |     this.status = response.status;
226 |     this.statusText = response.statusText;
227 |     this.headers = response.headers;
228 |     this.response = response;
229 |     this.method = requestInfo.method;
230 |     this.url = response.url || requestInfo.url;
231 |     this.rawBody = rawBody;
232 |     this.cause = cause;
233 |   }
234 | }
235 |
236 | async function parseJsonBody(
237 |   response: Response,
238 |   requestInfo: { method: string; url: string },
239 | ): Promise<unknown> {
240 |   const raw = await response.text();
241 |   const normalized = stripBom(raw);
242 |
243 |   if (normalized.trim() === "") {
244 |     return null;
245 |   }
246 |
247 |   try {
248 |     return JSON.parse(normalized);
249 |   } catch (cause) {
250 |     throw new ResponseParseError(response, raw, cause, requestInfo);
251 |   }
252 | }
253 |
254 | async function parseErrorBody(response: Response, method: string): Promise<unknown> {
255 |   if (hasNoBody(response, method)) {
256 |     return null;
257 |   }
258 |
259 |   const mediaType = getMediaType(response.headers);
260 |
261 |   // Fall back to text when blob() is unavailable (e.g. some React Native builds).
262 |   if (mediaType && !isJsonMediaType(mediaType) && !isTextMediaType(mediaType)) {
263 |     return typeof response.blob === "function" ? response.blob() : response.text();
264 |   }
265 |
266 |   const raw = await response.text();
267 |   const normalized = stripBom(raw);
268 |   const trimmed = normalized.trim();
269 |
270 |   if (trimmed === "") {
271 |     return null;
272 |   }
273 |
274 |   if (isJsonMediaType(mediaType) || looksLikeJson(normalized)) {
275 |     try {
276 |       return JSON.parse(normalized);
277 |     } catch {
278 |       return raw;
279 |     }
280 |   }
281 |
282 |   return raw;
283 | }
284 |
285 | function inferResponseType(response: Response): "json" | "text" | "blob" {
286 |   const mediaType = getMediaType(response.headers);
287 |
288 |   if (isJsonMediaType(mediaType)) return "json";
289 |   if (isTextMediaType(mediaType) || mediaType == null) return "text";
290 |   return "blob";
291 | }
292 |
293 | async function parseSuccessBody(
294 |   response: Response,
295 |   responseType: "json" | "text" | "blob" | "auto",
296 |   requestInfo: { method: string; url: string },
297 | ): Promise<unknown> {
298 |   if (hasNoBody(response, requestInfo.method)) {
299 |     return null;
300 |   }
301 |
302 |   const effectiveType =
303 |     responseType === "auto" ? inferResponseType(response) : responseType;
304 |
305 |   switch (effectiveType) {
306 |     case "json":
```

```
307 |       return parseJsonBody(response, requestInfo);
308 |
309 |     case "text": {
310 |       const text = await response.text();
311 |       return text === "" ? null : text;
312 |     }
313 |
314 |     case "blob":
315 |       if (typeof response.blob !== "function") {
316 |         throw new TypeError(
317 |           "Blob responses are not supported in this runtime. " +
318 |             "Use responseType \"json\" or \"text\" instead.",
319 |         );
320 |       }
321 |       return response.blob();
322 |   }
323 | }
324 |
325 | export async function customFetch<T = unknown>(
326 |   input: RequestInfo | URL,
327 |   options: CustomFetchOptions = {},
328 | ): Promise<T> {
329 |   input = applyBaseUrl(input);
330 |   const { responseType = "auto", headers: headersInit, ...init } = options;
331 |
332 |   const method = resolveMethod(input, init.method);
333 |
334 |   if (init.body != null && (method === "GET" || method === "HEAD")) {
335 |     throw new TypeError(`customFetch: ${method} requests cannot have a body.`);
336 |   }
337 |
338 |   const headers = mergeHeaders(isRequest(input) ? input.headers : undefined, headersInit);
339 |
340 |   if (
341 |     typeof init.body === "string" &&
342 |     !headers.has("content-type") &&
343 |     looksLikeJson(init.body)
344 |   ) {
345 |     headers.set("content-type", "application/json");
346 |   }
347 |
348 |   if (responseType === "json" && !headers.has("accept")) {
349 |     headers.set("accept", DEFAULT_JSON_ACCEPT);
350 |   }
351 |
352 |   // Attach bearer token when an auth getter is configured and no
353 |   // Authorization header has been explicitly provided.
354 |   if (_authTokenGetter && !headers.has("authorization")) {
355 |     const token = await _authTokenGetter();
356 |     if (token) {
357 |       headers.set("authorization", `Bearer ${token}`);
358 |     }
359 |   }
360 |
361 |   const requestInfo = { method, url: resolveUrl(input) };
362 |
363 |   const response = await fetch(input, { ...init, method, headers });
364 |
365 |   if (!response.ok) {
366 |     const errorData = await parseErrorBody(response, method);
367 |     throw new ApiError(response, errorData, requestInfo);
368 |   }
369 |
370 |   return (await parseSuccessBody(response, responseType, requestInfo)) as T;
371 | }
372 |
```

— end of file —

File: lib/api-client-react/src/generated/api.schemas.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
export interface HealthStatus {
  status: string;
}

export interface Donor {
  id: number;
  firstName: string;
  lastName: string;
  bloodType: string;
  city: string;
  phone: string;
  lastDonationDate?: string | null;
  isEligible: boolean;
  totalDonations: number;
  createdAt: string;
}

export interface CreateDonorBody {
  firstName: string;
  lastName: string;
  bloodType: string;
  city: string;
  phone: string;
  dateOfBirth: string;
  lastDonationDate?: string | null;
  weight: number;
  hasChronicDisease: boolean;
  email?: string;
}

export interface BloodRequest {
  id: number;
  patientName: string;
  bloodType: string;
  unitsNeeded: number;
  hospitalName: string;
  city: string;
  urgency: string;
  status: string;
  contactPhone: string;
  notes?: string | null;
  createdAt: string;
  fulfilledAt?: string | null;
}

export interface CreateBloodRequestBody {
  patientName: string;
  bloodType: string;
  unitsNeeded: number;
  hospitalName: string;
  city: string;
  urgency: string;
  contactPhone: string;
  notes?: string | null;
}

export interface Hospital {
  id: number;
  name: string;
  city: string;
  address: string;
  phone: string;
  availableBloodTypes: string[];
  isBloodBank: boolean;
  latitude: number;
  longitude: number;
  operatingHours: string;
}

export type DashboardStatsBloodTypeBreakdownItem = {
  bloodType: string;
  count: number;
};

export interface DashboardStats {
  totalDonors: number;
  totalDonations: number;
  activeRequests: number;
  partnerHospitals: number;
  livesSaved: number;
  donationsThisMonth: number;
  bloodTypeBreakdown: DashboardStatsBloodTypeBreakdownItem[];
}

export interface EmergencyRequest {
  id: number;
  patientName: string;
  bloodType: string;
  unitsNeeded: number;
  hospitalName: string;
  city: string;
  urgency: string;
  contactPhone: string;
```

```
101 |   minutesAgo: number;
102 |   status: string;
103 | }
104 |
105 | export type ListDonorsParams = {
106 |   bloodType?: string;
107 |   city?: string;
108 |   limit?: number;
109 |   offset?: number;
110 | };
111 |
112 | export type ListDonors200 = {
113 |   donors: Donor[];
114 |   total: number;
115 | };
116 |
117 | export type ListBloodRequestsParams = {
118 |   urgency?: string;
119 |   bloodType?: string;
120 |   status?: string;
121 |   city?: string;
122 | };
123 |
124 | export type ListBloodRequests200 = {
125 |   requests: BloodRequest[];
126 |   total: number;
127 | };
128 |
129 | export type ListHospitalsParams = {
130 |   city?: string;
131 |   bloodType?: string;
132 | };
133 |
134 | export type ListHospitals200 = {
135 |   hospitals: Hospital[];
136 |   total: number;
137 | };
138 |
139 | export type GetEmergencyFeedParams = {
140 |   city?: string;
141 |   limit?: number;
142 | };
143 |
144 | export type GetEmergencyFeed200 = {
145 |   emergencies: EmergencyRequest[];
146 | };
147 |
```

— end of file —

File: lib/api-client-react/src/generated/api.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
import { useMutation, useQuery } from "@tanstack/react-query";
import type {
  MutationFunction,
  QueryFunction,
  QueryKey,
  UseMutationOptions,
  UseMutationResult,
  UseQueryOptions,
  UseQueryResult,
} from "@tanstack/react-query";

import type {
  BloodRequest,
  CreateBloodRequestBody,
  CreateDonorBody,
  DashboardStats,
  Donor,
  GetEmergencyFeed200,
  GetEmergencyFeedParams,
  HealthStatus,
  ListBloodRequests200,
  ListBloodRequestsParams,
  ListDonors200,
  ListDonorsParams,
  ListHospitals200,
  ListHospitalsParams,
} from "./api.schemas";

import { customFetch } from "../custom-fetch";
import type { ErrorType, BodyType } from "../custom-fetch";

type AwaitedInput<T> = PromiseLike<T> | T;

type Awaited<O> = O extends AwaitedInput<infer T> ? T : never;

type SecondParameter<T extends (...args: never) => unknown> = Parameters<T>[1];

/**
 * Returns server health status
 * @summary Health check
 */
export const getHealthCheckUrl = () => {
  return `/api/healthz`;
};

export const healthCheck = async (
  options?: RequestInit,
): Promise<HealthStatus> => {
  return customFetch<HealthStatus>(getHealthCheckUrl(), {
    ...options,
    method: "GET",
  });
};

export const getHealthCheckQueryKey = () => {
  return [`/api/healthz`] as const;
};

export const getHealthCheckQueryOptions = <
  TData = Awaited<ReturnType<typeof healthCheck>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof healthCheck>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getHealthCheckQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof healthCheck>>> = ({
    signal,
  }) => healthCheck({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof healthCheck>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type HealthCheckQueryResult = NonNullable<
  Awaited<ReturnType<typeof healthCheck>>
>;
export type HealthCheckQueryError = ErrorType<unknown>;

/**
 * @summary Health check
 */

```

```
101 export function useHealthCheck<
102   TData = Awaited<ReturnType<typeof healthCheck>>,
103   TError = ErrorType<unknown>,
104 >(options?: {
105   query?: UseQueryOptions<
106     Awaited<ReturnType<typeof healthCheck>>,
107     TError,
108     TData
109   >;
110   request?: SecondParameter<typeof customFetch>;
111 }): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
112   const queryOptions = getHealthCheckQueryOptions(options);
113
114   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
115     queryKey: QueryKey;
116   };
117
118   return { ...query, queryKey: queryOptions.queryKey };
119 }
120
121 /**
122  * @summary List registered donors
123  */
124 export const getListDonorsUrl = (params?: ListDonorsParams) => {
125   const normalizedParams = new URLSearchParams();
126
127   Object.entries(params || {}).forEach(([key, value]) => {
128     if (value !== undefined) {
129       normalizedParams.append(key, value === null ? "null" : value.toString());
130     }
131   });
132
133   const stringifiedParams = normalizedParams.toString();
134
135   return stringifiedParams.length > 0
136     ? `/api/donors?${stringifiedParams}`
137     : `/api/donors`;
138 };
139
140 export const listDonors = async (
141   params?: ListDonorsParams,
142   options?: RequestInit,
143 ): Promise<ListDonors200> => {
144   return customFetch<ListDonors200>(getListDonorsUrl(params), {
145     ...options,
146     method: "GET",
147   });
148 };
149
150 export const getListDonorsQueryKey = (params?: ListDonorsParams) => {
151   return [`/api/donors`, ...(params ? [params] : [])] as const;
152 };
153
154 export const getListDonorsQueryOptions = <
155   TData = Awaited<ReturnType<typeof listDonors>>,
156   TError = ErrorType<unknown>,
157 >(
158   params?: ListDonorsParams,
159   options?: {
160     query?: UseQueryOptions<
161       Awaited<ReturnType<typeof listDonors>>,
162       TError,
163       TData
164     >;
165     request?: SecondParameter<typeof customFetch>;
166   },
167 ) => {
168   const { query: queryOptions, request: requestOptions } = options ?? {};
169
170   const queryKey = queryOptions?.queryKey ?? getListDonorsQueryKey(params);
171
172   const queryFn: QueryFunction<Awaited<ReturnType<typeof listDonors>>> = ({
173     signal,
174   }) => listDonors(params, { signal, ...requestOptions });
175
176   return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
177     Awaited<ReturnType<typeof listDonors>>,
178     TError,
179     TData
180   > & { queryKey: QueryKey };
181 };
182
183 export type ListDonorsQueryResult = NonNullable<
184   Awaited<ReturnType<typeof listDonors>>
185 >;
186 export type ListDonorsQueryError = ErrorType<unknown>;
187
188 /**
189  * @summary List registered donors
190  */
191
192 export function useListDonors<
193   TData = Awaited<ReturnType<typeof listDonors>>,
194   TError = ErrorType<unknown>,
195 >(
196   params?: ListDonorsParams,
197   options?: {
198     query?: UseQueryOptions<
199       Awaited<ReturnType<typeof listDonors>>,
200       TError,
201       TData
202     >;
203     request?: SecondParameter<typeof customFetch>;
```

```
204 |   },
205 | ): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
206 |   const queryOptions = getListDonorsQueryOptions(params, options);
207 |
208 |   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
209 |     queryKey: QueryKey;
210 |   };
211 |
212 |   return { ...query, queryKey: queryOptions.queryKey };
213 | }
214 |
215 | /**
216 |  * @summary Register a new donor
217 |  */
218 | export const getRegisterDonorUrl = () => {
219 |   return `/api/donors`;
220 | };
221 |
222 | export const registerDonor = async (
223 |   createDonorBody: CreateDonorBody,
224 |   options?: RequestInit,
225 | ): Promise<Donor> => {
226 |   return customFetch<Donor>(getRegisterDonorUrl(), {
227 |     ...options,
228 |     method: "POST",
229 |     headers: { "Content-Type": "application/json", ...options?.headers },
230 |     body: JSON.stringify(createDonorBody),
231 |   });
232 | };
233 |
234 | export const getRegisterDonorMutationOptions = <
235 |   TError = ErrorType<unknown>,
236 |   TContext = unknown,
237 | >(options?: {
238 |   mutation?: UseMutationOptions<
239 |     Awaited<ReturnType<typeof registerDonor>>,
240 |     TError,
241 |     { data: BodyType<CreateDonorBody> },
242 |     TContext
243 |   >;
244 |   request?: SecondParameter<typeof customFetch>;
245 | }): UseMutationOptions<
246 |   Awaited<ReturnType<typeof registerDonor>>,
247 |   TError,
248 |   { data: BodyType<CreateDonorBody> },
249 |   TContext
250 | > => {
251 |   const mutationKey = ["registerDonor"];
252 |   const { mutation: mutationOptions, request: requestOptions } = options
253 |     ? options.mutation &&
254 |       "mutationKey" in options.mutation &&
255 |       options.mutation.mutationKey
256 |       ? options
257 |       : { ...options, mutation: { ...options.mutation, mutationKey } }
258 |     : { mutation: { mutationKey }, request: undefined };
259 |
260 |   const mutationFn: MutationFunction<
261 |     Awaited<ReturnType<typeof registerDonor>>,
262 |     { data: BodyType<CreateDonorBody> }
263 |   > = (props) => {
264 |     const { data } = props ?? {};
265 |
266 |     return registerDonor(data, requestOptions);
267 |   };
268 |
269 |   return { mutationFn, ...mutationOptions };
270 | };
271 |
272 | export type RegisterDonorMutationResult = NonNullable<
273 |   Awaited<ReturnType<typeof registerDonor>>
274 | >;
275 | export type RegisterDonorMutationBody = BodyType<CreateDonorBody>;
276 | export type RegisterDonorMutationError = ErrorType<unknown>;
277 |
278 | /**
279 |  * @summary Register a new donor
280 |  */
281 | export const useRegisterDonor = <
282 |   TError = ErrorType<unknown>,
283 |   TContext = unknown,
284 | >(options?: {
285 |   mutation?: UseMutationOptions<
286 |     Awaited<ReturnType<typeof registerDonor>>,
287 |     TError,
288 |     { data: BodyType<CreateDonorBody> },
289 |     TContext
290 |   >;
291 |   request?: SecondParameter<typeof customFetch>;
292 | }): UseMutationResult<
293 |   Awaited<ReturnType<typeof registerDonor>>,
294 |   TError,
295 |   { data: BodyType<CreateDonorBody> },
296 |   TContext
297 | > => {
298 |   return useMutation(getRegisterDonorMutationOptions(options));
299 | };
300 |
301 | /**
302 |  * @summary List blood requests
303 |  */
304 | export const getListBloodRequestsUrl = (params?: ListBloodRequestsParams) => {
305 |   const normalizedParams = new URLSearchParams();
306 |
```

```
307 |   Object.entries(params || {}).forEach(([key, value]) => {
308 |     if (value !== undefined) {
309 |       normalizedParams.append(key, value === null ? "null" : value.toString());
310 |     }
311 |   });
312 |
313 |   const stringifiedParams = normalizedParams.toString();
314 |
315 |   return stringifiedParams.length > 0
316 |     ? `/api/blood-requests?${stringifiedParams}`
317 |     : `/api/blood-requests`;
318 | };
319 |
320 | export const listBloodRequests = async (
321 |   params?: ListBloodRequestsParams,
322 |   options?: RequestInit,
323 | ): Promise<ListBloodRequests200> => {
324 |   return customFetch<ListBloodRequests200>(getListBloodRequestsUrl(params), {
325 |     ...options,
326 |     method: "GET",
327 |   });
328 | };
329 |
330 | export const getListBloodRequestsQueryKey = (
331 |   params?: ListBloodRequestsParams,
332 | ) => {
333 |   return [`/api/blood-requests`, ...(params ? [params] : [])] as const;
334 | };
335 |
336 | export const getListBloodRequestsQueryOptions = <
337 |   TData = Awaited<ReturnType<typeof listBloodRequests>>,
338 |   TError = ErrorType<unknown>,
339 | >(
340 |   params?: ListBloodRequestsParams,
341 |   options?: {
342 |     query?: UseQueryOptions<
343 |       Awaited<ReturnType<typeof listBloodRequests>>,
344 |       TError,
345 |       TData
346 |     >;
347 |     request?: SecondParameter<typeof customFetch>;
348 |   },
349 | ) => {
350 |   const { query: queryOptions, request: requestOptions } = options ?? {};
351 |
352 |   const queryKey =
353 |     queryOptions?.queryKey ?? getListBloodRequestsQueryKey(params);
354 |
355 |   const queryFn: QueryFunction<
356 |     Awaited<ReturnType<typeof listBloodRequests>>
357 |   > = ({ signal }) => listBloodRequests(params, { signal, ...requestOptions });
358 |
359 |   return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
360 |     Awaited<ReturnType<typeof listBloodRequests>>,
361 |     TError,
362 |     TData
363 |   > & { queryKey: QueryKey };
364 | };
365 |
366 | export type ListBloodRequestsQueryResult = NonNullable<
367 |   Awaited<ReturnType<typeof listBloodRequests>>
368 | >;
369 | export type ListBloodRequestsQueryError = ErrorType<unknown>;
370 |
371 | /**
372 |  * @summary List blood requests
373 |  */
374 |
375 | export function useListBloodRequests<
376 |   TData = Awaited<ReturnType<typeof listBloodRequests>>,
377 |   TError = ErrorType<unknown>,
378 | >(
379 |   params?: ListBloodRequestsParams,
380 |   options?: {
381 |     query?: UseQueryOptions<
382 |       Awaited<ReturnType<typeof listBloodRequests>>,
383 |       TError,
384 |       TData
385 |     >;
386 |     request?: SecondParameter<typeof customFetch>;
387 |   },
388 | ): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
389 |   const queryOptions = getListBloodRequestsQueryOptions(params, options);
390 |
391 |   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
392 |     queryKey: QueryKey;
393 |   };
394 |
395 |   return { ...query, queryKey: queryOptions.queryKey };
396 | }
397 |
398 | /**
399 |  * @summary Submit a blood request
400 |  */
401 | export const getCreateBloodRequestUrl = () => {
402 |   return `/api/blood-requests`;
403 | };
404 |
405 | export const createBloodRequest = async (
406 |   createBloodRequestBody: CreateBloodRequestBody,
407 |   options?: RequestInit,
408 | ): Promise<BloodRequest> => {
409 |   return customFetch<BloodRequest>(getCreateBloodRequestUrl(), {
```

```
410 |     ...options,
411 |     method: "POST",
412 |     headers: { "Content-Type": "application/json", ...options?.headers },
413 |     body: JSON.stringify(createBloodRequestBody),
414 |   });
415 | };
416 |
417 | export const getCreateBloodRequestMutationOptions = <
418 |   TError = ErrorType<unknown>,
419 |   TContext = unknown,
420 | >(options?: {
421 |   mutation?: UseMutationOptions<
422 |     Awaited<ReturnType<typeof createBloodRequest>>,
423 |     TError,
424 |     { data: BodyType<CreateBloodRequestBody> },
425 |     TContext
426 |   >;
427 |   request?: SecondParameter<typeof customFetch>;
428 | }): UseMutationOptions<
429 |   Awaited<ReturnType<typeof createBloodRequest>>,
430 |   TError,
431 |   { data: BodyType<CreateBloodRequestBody> },
432 |   TContext
433 | > => {
434 |   const mutationKey = ["createBloodRequest"];
435 |   const { mutation: mutationOptions, request: requestOptions } = options
436 |     ? options.mutation &&
437 |       "mutationKey" in options.mutation &&
438 |       options.mutation.mutationKey
439 |       ? options
440 |       : { ...options, mutation: { ...options.mutation, mutationKey } }
441 |     : { mutation: { mutationKey }, request: undefined };
442 |
443 |   const mutationFn: MutationFunction<
444 |     Awaited<ReturnType<typeof createBloodRequest>>,
445 |     { data: BodyType<CreateBloodRequestBody> }
446 |   > = (props) => {
447 |     const { data } = props ?? {};
448 |
449 |     return createBloodRequest(data, requestOptions);
450 |   };
451 |
452 |   return { mutationFn, ...mutationOptions };
453 | };
454 |
455 | export type CreateBloodRequestMutationResult = NonNullable<
456 |   Awaited<ReturnType<typeof createBloodRequest>>
457 | >;
458 | export type CreateBloodRequestMutationBody = BodyType<CreateBloodRequestBody>;
459 | export type CreateBloodRequestMutationError = ErrorType<unknown>;
460 |
461 | /**
462 |  * @summary Submit a blood request
463 |  */
464 | export const useCreateBloodRequest = <
465 |   TError = ErrorType<unknown>,
466 |   TContext = unknown,
467 | >(options?: {
468 |   mutation?: UseMutationOptions<
469 |     Awaited<ReturnType<typeof createBloodRequest>>,
470 |     TError,
471 |     { data: BodyType<CreateBloodRequestBody> },
472 |     TContext
473 |   >;
474 |   request?: SecondParameter<typeof customFetch>;
475 | }): UseMutationResult<
476 |   Awaited<ReturnType<typeof createBloodRequest>>,
477 |   TError,
478 |   { data: BodyType<CreateBloodRequestBody> },
479 |   TContext
480 | > => {
481 |   return useMutation(getCreateBloodRequestMutationOptions(options));
482 | };
483 |
484 | /**
485 |  * @summary List hospitals and blood banks
486 |  */
487 | export const getListHospitalsUrl = (params?: ListHospitalsParams) => {
488 |   const normalizedParams = new URLSearchParams();
489 |
490 |   Object.entries(params || {}).forEach(([key, value]) => {
491 |     if (value !== undefined) {
492 |       normalizedParams.append(key, value === null ? "null" : value.toString());
493 |     }
494 |   });
495 |
496 |   const stringifiedParams = normalizedParams.toString();
497 |
498 |   return stringifiedParams.length > 0
499 |     ? `/api/hospitals?${stringifiedParams}`
500 |     : `/api/hospitals`;
501 | };
502 |
503 | export const listHospitals = async (
504 |   params?: ListHospitalsParams,
505 |   options?: RequestInit,
506 | ): Promise<ListHospitals200> => {
507 |   return customFetch<ListHospitals200>(getListHospitalsUrl(params), {
508 |     ...options,
509 |     method: "GET",
510 |   });
511 | };
512 |
```

```
513 | export const getListHospitalsQueryKey = (params?: ListHospitalsParams) => {
514 |   return [`/api/hospitals`, ...(params ? [params] : [])] as const;
515 | };
516 |
517 | export const getListHospitalsQueryOptions = <
518 |   TData = Awaited<ReturnType<typeof listHospitals>>,
519 |   TError = ErrorType<unknown>,
520 | >(
521 |   params?: ListHospitalsParams,
522 |   options?: {
523 |     query?: UseQueryOptions<
524 |       Awaited<ReturnType<typeof listHospitals>>,
525 |       TError,
526 |       TData
527 |     >;
528 |     request?: SecondParameter<typeof customFetch>;
529 |   },
530 | ) => {
531 |   const { query: queryOptions, request: requestOptions } = options ?? {};
532 |
533 |   const queryKey = queryOptions?.queryKey ?? getListHospitalsQueryKey(params);
534 |
535 |   const queryFn: QueryFunction<Awaited<ReturnType<typeof listHospitals>>> = ({
536 |     signal,
537 |   }) => listHospitals(params, { signal, ...requestOptions });
538 |
539 |   return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
540 |     Awaited<ReturnType<typeof listHospitals>>,
541 |     TError,
542 |     TData
543 |   > & { queryKey: QueryKey };
544 | };
545 |
546 | export type ListHospitalsQueryResult = NonNullable<
547 |   Awaited<ReturnType<typeof listHospitals>>
548 | >;
549 | export type ListHospitalsQueryError = ErrorType<unknown>;
550 |
551 | /**
552 |  * @summary List hospitals and blood banks
553 |  */
554 |
555 | export function useListHospitals<
556 |   TData = Awaited<ReturnType<typeof listHospitals>>,
557 |   TError = ErrorType<unknown>,
558 | >(
559 |   params?: ListHospitalsParams,
560 |   options?: {
561 |     query?: UseQueryOptions<
562 |       Awaited<ReturnType<typeof listHospitals>>,
563 |       TError,
564 |       TData
565 |     >;
566 |     request?: SecondParameter<typeof customFetch>;
567 |   },
568 | ): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
569 |   const queryOptions = getListHospitalsQueryOptions(params, options);
570 |
571 |   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
572 |     queryKey: QueryKey;
573 |   };
574 |
575 |   return { ...query, queryKey: queryOptions.queryKey };
576 | }
577 |
578 | /**
579 |  * @summary Get platform statistics
580 |  */
581 | export const getGetDashboardStatsUrl = () => {
582 |   return `/api/dashboard/stats`;
583 | };
584 |
585 | export const getDashboardStats = async (
586 |   options?: RequestInit,
587 | ): Promise<DashboardStats> => {
588 |   return customFetch<DashboardStats>(getGetDashboardStatsUrl(), {
589 |     ...options,
590 |     method: "GET",
591 |   });
592 | };
593 |
594 | export const getGetDashboardStatsQueryKey = () => {
595 |   return [`/api/dashboard/stats`] as const;
596 | };
597 |
598 | export const getGetDashboardStatsQueryOptions = <
599 |   TData = Awaited<ReturnType<typeof getDashboardStats>>,
600 |   TError = ErrorType<unknown>,
601 | >(options?: {
602 |   query?: UseQueryOptions<
603 |     Awaited<ReturnType<typeof getDashboardStats>>,
604 |     TError,
605 |     TData
606 |   >;
607 |   request?: SecondParameter<typeof customFetch>;
608 | }) => {
609 |   const { query: queryOptions, request: requestOptions } = options ?? {};
610 |
611 |   const queryKey = queryOptions?.queryKey ?? getGetDashboardStatsQueryKey();
612 |
613 |   const queryFn: QueryFunction<
614 |     Awaited<ReturnType<typeof getDashboardStats>>
615 |   > = ({ signal }) => getDashboardStats({ signal, ...requestOptions });
```

```
616 |
617 |   return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
618 |     Awaited<ReturnType<typeof getDashboardStats>>,
619 |     TError,
620 |     TData
621 |   > & { queryKey: QueryKey };
622 | };
623 |
624 | export type GetDashboardStatsQueryResult = NonNullable<
625 |   Awaited<ReturnType<typeof getDashboardStats>>
626 | >;
627 | export type GetDashboardStatsQueryError = ErrorType<unknown>;
628 |
629 | /**
630 |  * @summary Get platform statistics
631 |  */
632 |
633 | export function useGetDashboardStats<
634 |   TData = Awaited<ReturnType<typeof getDashboardStats>>,
635 |   TError = ErrorType<unknown>,
636 | >(options?: {
637 |   query?: UseQueryOptions<
638 |     Awaited<ReturnType<typeof getDashboardStats>>,
639 |     TError,
640 |     TData
641 |   >;
642 |   request?: SecondParameter<typeof customFetch>;
643 | }): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
644 |   const queryOptions = getGetDashboardStatsQueryOptions(options);
645 |
646 |   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
647 |     queryKey: QueryKey;
648 |   };
649 |
650 |   return { ...query, queryKey: queryOptions.queryKey };
651 | }
652 |
653 | /**
654 |  * @summary Get live emergency blood requests
655 |  */
656 | export const getGetEmergencyFeedUrl = (params?: GetEmergencyFeedParams) => {
657 |   const normalizedParams = new URLSearchParams();
658 |
659 |   Object.entries(params || {}).forEach(([key, value]) => {
660 |     if (value !== undefined) {
661 |       normalizedParams.append(key, value === null ? "null" : value.toString());
662 |     }
663 |   });
664 |
665 |   const stringifiedParams = normalizedParams.toString();
666 |
667 |   return stringifiedParams.length > 0
668 |     ? `/api/dashboard/emergency-feed?${stringifiedParams}`
669 |     : `/api/dashboard/emergency-feed`;
670 | };
671 |
672 | export const getEmergencyFeed = async (
673 |   params?: GetEmergencyFeedParams,
674 |   options?: RequestInit,
675 | ): Promise<GetEmergencyFeed200> => {
676 |   return customFetch<GetEmergencyFeed200>(getGetEmergencyFeedUrl(params), {
677 |     ...options,
678 |     method: "GET",
679 |   });
680 | };
681 |
682 | export const getGetEmergencyFeedQueryKey = (
683 |   params?: GetEmergencyFeedParams,
684 | ) => {
685 |   return [
686 |     `/api/dashboard/emergency-feed`,
687 |     ...(params ? [params] : []),
688 |   ] as const;
689 | };
690 |
691 | export const getGetEmergencyFeedQueryOptions = <
692 |   TData = Awaited<ReturnType<typeof getEmergencyFeed>>,
693 |   TError = ErrorType<unknown>,
694 | >(
695 |   params?: GetEmergencyFeedParams,
696 |   options?: {
697 |     query?: UseQueryOptions<
698 |       Awaited<ReturnType<typeof getEmergencyFeed>>,
699 |       TError,
700 |       TData
701 |     >;
702 |     request?: SecondParameter<typeof customFetch>;
703 |   },
704 | ) => {
705 |   const { query: queryOptions, request: requestOptions } = options ?? {};
706 |
707 |   const queryKey =
708 |     queryOptions?.queryKey ?? getGetEmergencyFeedQueryKey(params);
709 |
710 |   const queryFn: QueryFunction<
711 |     Awaited<ReturnType<typeof getEmergencyFeed>>
712 |   > = ({ signal }) => getEmergencyFeed(params, { signal, ...requestOptions });
713 |
714 |   return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
715 |     Awaited<ReturnType<typeof getEmergencyFeed>>,
716 |     TError,
717 |     TData
718 |   > & { queryKey: QueryKey };
```

```
719 | };
720 |
721 | export type GetEmergencyFeedQueryResult = NonNullable<
722 |   Awaited<ReturnType<typeof getEmergencyFeed>>
723 | >;
724 | export type GetEmergencyFeedQueryError = ErrorType<unknown>;
725 |
726 | /**
727 |  * @summary Get live emergency blood requests
728 |  */
729 |
730 | export function useGetEmergencyFeed<
731 |   TData = Awaited<ReturnType<typeof getEmergencyFeed>>,
732 |   TError = ErrorType<unknown>,
733 | >(
734 |   params?: GetEmergencyFeedParams,
735 |   options?: {
736 |     query?: UseQueryOptions<
737 |       Awaited<ReturnType<typeof getEmergencyFeed>>,
738 |       TError,
739 |       TData
740 |     >;
741 |     request?: SecondParameter<typeof customFetch>;
742 |   },
743 | ): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
744 |   const queryOptions = getGetEmergencyFeedQueryOptions(params, options);
745 |
746 |   const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
747 |     queryKey: QueryKey;
748 |   };
749 |
750 |   return { ...query, queryKey: queryOptions.queryKey };
751 | }
752 |
```

— end of file —

File: lib/api-client-react/src/index.ts

```
1 | export * from "./generated/api";
2 | export * from "./generated/api.schemas";
3 | export { setBaseUrl, setAuthTokenGetter } from "./custom-fetch";
4 | export type { AuthTokenGetter } from "./custom-fetch";
5 |
```

— end of file —

File: lib/api-client-react/tsconfig.json

```
 1 | {
 2 |   "extends": "../../tsconfig.base.json",
 3 |   "compilerOptions": {
 4 |     "composite": true,
 5 |     "declarationMap": true,
 6 |     "emitDeclarationOnly": true,
 7 |     "outDir": "dist",
 8 |     "rootDir": "src",
 9 |     "lib": ["dom", "es2022"]
10 |   },
11 |   "include": ["src"]
12 | }
13 |
```

— end of file —

File: lib/api-spec/orval.config.ts

```
1 | import { defineConfig, InputTransformerFn } from "orval";
2 | import path from "path";
3 |
4 | const root = path.resolve(__dirname, "..", "..");
5 | const apiClientReactSrc = path.resolve(root, "lib", "api-client-react", "src");
6 | const apiZodSrc = path.resolve(root, "lib", "api-zod", "src");
7 |
8 | // Our exports make assumptions about the title of the API being "Api" (i.e. generated output is `api.ts`).
9 | const titleTransformer: InputTransformerFn = (config) => {
10 |   config.info ??= {};
11 |   config.info.title = "Api";
12 |
13 |   return config;
14 | };
15 |
16 | export default defineConfig({
17 |   "api-client-react": {
18 |     input: {
19 |       target: "./openapi.yaml",
20 |       override: {
21 |         transformer: titleTransformer,
22 |       },
23 |     },
24 |     output: {
25 |       workspace: apiClientReactSrc,
26 |       target: "generated",
27 |       client: "react-query",
28 |       mode: "split",
29 |       baseUrl: "/api",
30 |       clean: true,
31 |       prettier: true,
32 |       override: {
33 |         fetch: {
34 |           includeHttpResponseReturnType: false,
35 |         },
36 |         mutator: {
37 |           path: path.resolve(apiClientReactSrc, "custom-fetch.ts"),
38 |           name: "customFetch",
39 |         },
40 |       },
41 |     },
42 |   },
43 |   zod: {
44 |     input: {
45 |       target: "./openapi.yaml",
46 |       override: {
47 |         transformer: titleTransformer,
48 |       },
49 |     },
50 |     output: {
51 |       workspace: apiZodSrc,
52 |       client: "zod",
53 |       target: "generated",
54 |       schemas: { path: "generated/types", type: "typescript" },
55 |       mode: "split",
56 |       clean: true,
57 |       prettier: true,
58 |       override: {
59 |         zod: {
60 |           coerce: {
61 |             query: ['boolean', 'number', 'string'],
62 |             param: ['boolean', 'number', 'string'],
63 |             body: ['bigint', 'date'],
64 |             response: ['bigint', 'date'],
65 |           },
66 |         },
67 |         useDates: true,
68 |         useBigInt: true,
69 |       },
70 |     },
71 |   },
72 | });
73 |
```

— end of file —

File: lib/api-spec/package.json

```
  1 | {
  2 |   "name": "@workspace/api-spec",
  3 |   "version": "0.0.0",
  4 |   "private": true,
  5 |   "scripts": {
  6 |     "codegen": "orval --config ./orval.config.ts"
  7 |   },
  8 |   "devDependencies": {
  9 |     "orval": "^8.5.2"
 10 |   }
 11 | }
 12 |
```

— end of file —

File: lib/api-zod/package.json

```
1 | {
2 |   "name": "@workspace/api-zod",
3 |   "version": "0.0.0",
4 |   "private": true,
5 |   "type": "module",
6 |   "exports": {
7 |     ".": "./src/index.ts"
8 |   },
9 |   "dependencies": {
10 |     "zod": "catalog:"
11 |   }
12 | }
13 |
```

— end of file —

File: lib/api-zod/src/generated/api.ts

```
1 | /**
2 |  * Generated by orval v8.5.3 Ø<ßz
3 |  * Do not edit manually.
4 |  * Api
5 |  * MBC - Main Blood Center API
6 |  * OpenAPI spec version: 0.1.0
7 |  */
8 | import * as zod from "zod";
9 |
10 | /**
11 |  * Returns server health status
12 |  * @summary Health check
13 |  */
14 | export const HealthCheckResponse = zod.object({
15 |   status: zod.string(),
16 | });
17 |
18 | /**
19 |  * @summary List registered donors
20 |  */
21 | export const ListDonorsQueryParams = zod.object({
22 |   bloodType: zod.coerce.string().optional(),
23 |   city: zod.coerce.string().optional(),
24 |   limit: zod.coerce.number().optional(),
25 |   offset: zod.coerce.number().optional(),
26 | });
27 |
28 | export const ListDonorsResponse = zod.object({
29 |   donors: zod.array(
30 |     zod.object({
31 |       id: zod.number(),
32 |       firstName: zod.string(),
33 |       lastName: zod.string(),
34 |       bloodType: zod.string(),
35 |       city: zod.string(),
36 |       phone: zod.string(),
37 |       lastDonationDate: zod.string().nullish(),
38 |       isEligible: zod.boolean(),
39 |       totalDonations: zod.number(),
40 |       createdAt: zod.string(),
41 |     }),
42 |   ),
43 |   total: zod.number(),
44 | });
45 |
46 | /**
47 |  * @summary Register a new donor
48 |  */
49 | export const RegisterDonorBody = zod.object({
50 |   firstName: zod.string(),
51 |   lastName: zod.string(),
52 |   bloodType: zod.string(),
53 |   city: zod.string(),
54 |   phone: zod.string(),
55 |   dateOfBirth: zod.string(),
56 |   lastDonationDate: zod.string().nullish(),
57 |   weight: zod.number(),
58 |   hasChronicDisease: zod.boolean(),
59 |   email: zod.string().optional(),
60 | });
61 |
62 | /**
63 |  * @summary List blood requests
64 |  */
65 | export const ListBloodRequestsQueryParams = zod.object({
66 |   urgency: zod.coerce.string().optional(),
67 |   bloodType: zod.coerce.string().optional(),
68 |   status: zod.coerce.string().optional(),
69 |   city: zod.coerce.string().optional(),
70 | });
71 |
72 | export const ListBloodRequestsResponse = zod.object({
73 |   requests: zod.array(
74 |     zod.object({
75 |       id: zod.number(),
76 |       patientName: zod.string(),
77 |       bloodType: zod.string(),
78 |       unitsNeeded: zod.number(),
79 |       hospitalName: zod.string(),
80 |       city: zod.string(),
81 |       urgency: zod.string(),
82 |       status: zod.string(),
83 |       contactPhone: zod.string(),
84 |       notes: zod.string().nullish(),
85 |       createdAt: zod.string(),
86 |       fulfilledAt: zod.string().nullish(),
87 |     }),
88 |   ),
89 |   total: zod.number(),
90 | });
91 |
92 | /**
93 |  * @summary Submit a blood request
94 |  */
95 | export const CreateBloodRequestBody = zod.object({
96 |   patientName: zod.string(),
97 |   bloodType: zod.string(),
98 |   unitsNeeded: zod.number(),
99 |   hospitalName: zod.string(),
100 |   city: zod.string(),
```

```
101 |   urgency: zod.string(),
102 |   contactPhone: zod.string(),
103 |   notes: zod.string().nullish(),
104 | });
105 |
106 | /**
107 |  * @summary List hospitals and blood banks
108 |  */
109 | export const ListHospitalsQueryParams = zod.object({
110 |   city: zod.coerce.string().optional(),
111 |   bloodType: zod.coerce.string().optional(),
112 | });
113 |
114 | export const ListHospitalsResponse = zod.object({
115 |   hospitals: zod.array(
116 |     zod.object({
117 |       id: zod.number(),
118 |       name: zod.string(),
119 |       city: zod.string(),
120 |       address: zod.string(),
121 |       phone: zod.string(),
122 |       availableBloodTypes: zod.array(zod.string()),
123 |       isBloodBank: zod.boolean(),
124 |       latitude: zod.number(),
125 |       longitude: zod.number(),
126 |       operatingHours: zod.string(),
127 |     }),
128 |   ),
129 |   total: zod.number(),
130 | });
131 |
132 | /**
133 |  * @summary Get platform statistics
134 |  */
135 | export const GetDashboardStatsResponse = zod.object({
136 |   totalDonors: zod.number(),
137 |   totalDonations: zod.number(),
138 |   activeRequests: zod.number(),
139 |   partnerHospitals: zod.number(),
140 |   livesSaved: zod.number(),
141 |   donationsThisMonth: zod.number(),
142 |   bloodTypeBreakdown: zod.array(
143 |     zod.object({
144 |       bloodType: zod.string(),
145 |       count: zod.number(),
146 |     }),
147 |   ),
148 | });
149 |
150 | /**
151 |  * @summary Get live emergency blood requests
152 |  */
153 | export const GetEmergencyFeedQueryParams = zod.object({
154 |   city: zod.coerce.string().optional(),
155 |   limit: zod.coerce.number().optional(),
156 | });
157 |
158 | export const GetEmergencyFeedResponse = zod.object({
159 |   emergencies: zod.array(
160 |     zod.object({
161 |       id: zod.number(),
162 |       patientName: zod.string(),
163 |       bloodType: zod.string(),
164 |       unitsNeeded: zod.number(),
165 |       hospitalName: zod.string(),
166 |       city: zod.string(),
167 |       urgency: zod.string(),
168 |       contactPhone: zod.string(),
169 |       minutesAgo: zod.number(),
170 |       status: zod.string(),
171 |     }),
172 |   ),
173 | });
174 |
```

— end of file —

File: lib/api-zod/src/generated/types/bloodRequest.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface BloodRequest {
  id: number;
  patientName: string;
  bloodType: string;
  unitsNeeded: number;
  hospitalName: string;
  city: string;
  urgency: string;
  status: string;
  contactPhone: string;
  notes?: string | null;
  createdAt: string;
  fulfilledAt?: string | null;
}

```

— end of file —

File: lib/api-zod/src/generated/types/createBloodRequestBody.ts

```
 1 | /**
 2 |  * Generated by orval v8.5.3 Ø<ßz
 3 |  * Do not edit manually.
 4 |  * Api
 5 |  * MBC - Main Blood Center API
 6 |  * OpenAPI spec version: 0.1.0
 7 |  */
 8 |
 9 | export interface CreateBloodRequestBody {
10 |   patientName: string;
11 |   bloodType: string;
12 |   unitsNeeded: number;
13 |   hospitalName: string;
14 |   city: string;
15 |   urgency: string;
16 |   contactPhone: string;
17 |   notes?: string | null;
18 | }
19 |
```

— end of file —

File: lib/api-zod/src/generated/types/createDonorBody.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateDonorBody {
  firstName: string;
  lastName: string;
  bloodType: string;
  city: string;
  phone: string;
  dateOfBirth: string;
  lastDonationDate?: string | null;
  weight: number;
  hasChronicDisease: boolean;
  email?: string;
}

```

— end of file —

File: lib/api-zod/src/generated/types/dashboardStats.ts

```
 1 | /**
 2 |  * Generated by orval v8.5.3 Ø<ßz
 3 |  * Do not edit manually.
 4 |  * Api
 5 |  * MBC - Main Blood Center API
 6 |  * OpenAPI spec version: 0.1.0
 7 |  */
 8 | import type { DashboardStatsBloodTypeBreakdownItem } from "./dashboardStatsBloodTypeBreakdownItem";
 9 |
10 | export interface DashboardStats {
11 |   totalDonors: number;
12 |   totalDonations: number;
13 |   activeRequests: number;
14 |   partnerHospitals: number;
15 |   livesSaved: number;
16 |   donationsThisMonth: number;
17 |   bloodTypeBreakdown: DashboardStatsBloodTypeBreakdownItem[];
18 | }
19 |
```

— end of file —

File: lib/api-zod/src/generated/types/dashboardStatsBloodTypeBreakdownItem.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardStatsBloodTypeBreakdownItem = {
  bloodType: string;
  count: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/donor.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface Donor {
  id: number;
  firstName: string;
  lastName: string;
  bloodType: string;
  city: string;
  phone: string;
  lastDonationDate?: string | null;
  isEligible: boolean;
  totalDonations: number;
  createdAt: string;
}

```

— end of file —

File: lib/api-zod/src/generated/types/emergencyRequest.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface EmergencyRequest {
  id: number;
  patientName: string;
  bloodType: string;
  unitsNeeded: number;
  hospitalName: string;
  city: string;
  urgency: string;
  contactPhone: string;
  minutesAgo: number;
  status: string;
}

```

— end of file —

File: lib/api-zod/src/generated/types/getEmergencyFeed200.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
import type { EmergencyRequest } from "./emergencyRequest";

export type GetEmergencyFeed200 = {
  emergencies: EmergencyRequest[];
};

```

— end of file —

File: lib/api-zod/src/generated/types/getEmergencyFeedParams.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export type GetEmergencyFeedParams = {
  city?: string;
  limit?: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/healthStatus.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface HealthStatus {
  status: string;
}

```

— end of file —

File: lib/api-zod/src/generated/types/hospital.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export interface Hospital {
  id: number;
  name: string;
  city: string;
  address: string;
  phone: string;
  availableBloodTypes: string[];
  isBloodBank: boolean;
  latitude: number;
  longitude: number;
  operatingHours: string;
}

```

— end of file —

File: lib/api-zod/src/generated/types/index.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export * from "./bloodRequest";
export * from "./createBloodRequestBody";
export * from "./createDonorBody";
export * from "./dashboardStats";
export * from "./dashboardStatsBloodTypeBreakdownItem";
export * from "./donor";
export * from "./emergencyRequest";
export * from "./getEmergencyFeed200";
export * from "./getEmergencyFeedParams";
export * from "./healthStatus";
export * from "./hospital";
export * from "./listBloodRequests200";
export * from "./listBloodRequestsParams";
export * from "./listDonors200";
export * from "./listDonorsParams";
export * from "./listHospitals200";
export * from "./listHospitalsParams";

```

— end of file —

File: lib/api-zod/src/generated/types/listBloodRequests200.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
import type { BloodRequest } from "./bloodRequest";

export type ListBloodRequests200 = {
  requests: BloodRequest[];
  total: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/listBloodRequestsParams.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export type ListBloodRequestsParams = {
  urgency?: string;
  bloodType?: string;
  status?: string;
  city?: string;
};

```

— end of file —

File: lib/api-zod/src/generated/types/listDonors200.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
import type { Donor } from "./donor";

export type ListDonors200 = {
  donors: Donor[];
  total: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/listDonorsParams.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export type ListDonorsParams = {
  bloodType?: string;
  city?: string;
  limit?: number;
  offset?: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/listHospitals200.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */
import type { Hospital } from "./hospital";

export type ListHospitals200 = {
  hospitals: Hospital[];
  total: number;
};

```

— end of file —

File: lib/api-zod/src/generated/types/listHospitalsParams.ts

```
/**
 * Generated by orval v8.5.3 Ø<ßz
 * Do not edit manually.
 * Api
 * MBC - Main Blood Center API
 * OpenAPI spec version: 0.1.0
 */

export type ListHospitalsParams = {
  city?: string;
  bloodType?: string;
};

```

— end of file —

File: lib/api-zod/src/index.ts

```
1 | export * from "./generated/api";
2 | export * from "./generated/types";
3 |
```

— end of file —

File: lib/api-zod/tsconfig.json

```
  1 | {
  2 |   "extends": "../../tsconfig.base.json",
  3 |   "compilerOptions": {
  4 |     "composite": true,
  5 |     "declarationMap": true,
  6 |     "emitDeclarationOnly": true,
  7 |     "outDir": "dist",
  8 |     "rootDir": "src"
  9 |   },
 10 |   "include": ["src"]
 11 | }
 12 |
```

— end of file —

File: lib/db/drizzle.config.ts

```
 1 | import { defineConfig } from "drizzle-kit";
 2 | import path from "path";
 3 |
 4 | if (!process.env.DATABASE_URL) {
 5 |   throw new Error("DATABASE_URL, ensure the database is provisioned");
 6 | }
 7 |
 8 | export default defineConfig({
 9 |   schema: path.join(__dirname, "./src/schema/index.ts"),
10 |   dialect: "postgresql",
11 |   dbCredentials: {
12 |     url: process.env.DATABASE_URL,
13 |   },
14 | });
15 |
```

— end of file —

File: lib/db/package.json

```
1 | {
2 |   "name": "@workspace/db",
3 |   "version": "0.0.0",
4 |   "private": true,
5 |   "type": "module",
6 |   "exports": {
7 |     ".": "./src/index.ts",
8 |     "./schema": "./src/schema/index.ts"
9 |   },
10 |   "scripts": {
11 |     "push": "drizzle-kit push --config ./drizzle.config.ts",
12 |     "push-force": "drizzle-kit push --force --config ./drizzle.config.ts"
13 |   },
14 |   "dependencies": {
15 |     "drizzle-orm": "catalog:",
16 |     "drizzle-zod": "^0.8.3",
17 |     "pg": "^8.20.0",
18 |     "zod": "catalog:"
19 |   },
20 |   "devDependencies": {
21 |     "@types/node": "catalog:",
22 |     "@types/pg": "^8.18.0",
23 |     "drizzle-kit": "^0.31.9"
24 |   }
25 | }
26 |
```

— end of file —

File: lib/db/src/index.ts

```
 1 | import { drizzle } from "drizzle-orm/node-postgres";
 2 | import pg from "pg";
 3 | import * as schema from "./schema";
 4 |
 5 | const { Pool } = pg;
 6 |
 7 | if (!process.env.DATABASE_URL) {
 8 |   throw new Error(
 9 |     "DATABASE_URL must be set. Did you forget to provision a database?",
10 |   );
11 | }
12 |
13 | export const pool = new Pool({ connectionString: process.env.DATABASE_URL });
14 | export const db = drizzle(pool, { schema });
15 |
16 | export * from "./schema";
17 |
```

— end of file —

File: lib/db/src/schema/blood_requests.ts

```
   1 | import { pgTable, text, serial, integer, timestamp } from "drizzle-orm/pg-core";
   2 | import { createInsertSchema } from "drizzle-zod";
   3 | import { z } from "zod/v4";
   4 |
   5 | export const bloodRequestsTable = pgTable("blood_requests", {
   6 |   id: serial("id").primaryKey(),
   7 |   patientName: text("patient_name").notNull(),
   8 |   bloodType: text("blood_type").notNull(),
   9 |   unitsNeeded: integer("units_needed").notNull(),
  10 |   hospitalName: text("hospital_name").notNull(),
  11 |   city: text("city").notNull(),
  12 |   urgency: text("urgency").notNull(),
  13 |   status: text("status").notNull().default("active"),
  14 |   contactPhone: text("contact_phone").notNull(),
  15 |   notes: text("notes"),
  16 |   createdAt: timestamp("created_at").notNull().defaultNow(),
  17 |   fulfilledAt: timestamp("fulfilled_at"),
  18 | });
  19 |
  20 | export const insertBloodRequestSchema = createInsertSchema(bloodRequestsTable).omit({ id: true, status: true,
createdAt: true, fulfilledAt: true });
  21 | export type InsertBloodRequest = z.infer<typeof insertBloodRequestSchema>;
  22 | export type BloodRequest = typeof bloodRequestsTable.$inferSelect;
  23 |
```

— end of file —

File: lib/db/src/schema/donors.ts

```
   1 | import { pgTable, text, serial, boolean, integer, date, timestamp } from "drizzle-orm/pg-core";
   2 | import { createInsertSchema } from "drizzle-zod";
   3 | import { z } from "zod/v4";
   4 |
   5 | export const donorsTable = pgTable("donors", {
   6 |   id: serial("id").primaryKey(),
   7 |   firstName: text("first_name").notNull(),
   8 |   lastName: text("last_name").notNull(),
   9 |   bloodType: text("blood_type").notNull(),
  10 |   city: text("city").notNull(),
  11 |   phone: text("phone").notNull(),
  12 |   email: text("email"),
  13 |   dateOfBirth: date("date_of_birth").notNull(),
  14 |   lastDonationDate: date("last_donation_date"),
  15 |   weight: integer("weight").notNull(),
  16 |   hasChronicDisease: boolean("has_chronic_disease").notNull().default(false),
  17 |   isEligible: boolean("is_eligible").notNull().default(true),
  18 |   totalDonations: integer("total_donations").notNull().default(0),
  19 |   createdAt: timestamp("created_at").notNull().defaultNow(),
  20 | });
  21 |
  22 | export const insertDonorSchema = createInsertSchema(donorsTable).omit({ id: true, isEligible: true,
totalDonations: true, createdAt: true });
  23 | export type InsertDonor = z.infer<typeof insertDonorSchema>;
  24 | export type Donor = typeof donorsTable.$inferSelect;
  25 |
```

— end of file —

File: lib/db/src/schema/hospitals.ts

```
1 | import { pgTable, text, serial, boolean, real, timestamp } from "drizzle-orm/pg-core";
2 | import { createInsertSchema } from "drizzle-zod";
3 | import { z } from "zod/v4";
4 |
5 | export const hospitalsTable = pgTable("hospitals", {
6 |   id: serial("id").primaryKey(),
7 |   name: text("name").notNull(),
8 |   city: text("city").notNull(),
9 |   address: text("address").notNull(),
10 |   phone: text("phone").notNull(),
11 |   availableBloodTypes: text("available_blood_types").array().notNull().default([]),
12 |   isBloodBank: boolean("is_blood_bank").notNull().default(false),
13 |   latitude: real("latitude").notNull(),
14 |   longitude: real("longitude").notNull(),
15 |   operatingHours: text("operating_hours").notNull(),
16 |   createdAt: timestamp("created_at").notNull().defaultNow(),
17 | });
18 |
19 | export const insertHospitalSchema = createInsertSchema(hospitalsTable).omit({ id: true, createdAt: true });
20 | export type InsertHospital = z.infer<typeof insertHospitalSchema>;
21 | export type Hospital = typeof hospitalsTable.$inferSelect;
22 |
```

— end of file —

File: lib/db/src/schema/index.ts

```
1 | export * from "./donors";
2 | export * from "./blood_requests";
3 | export * from "./hospitals";
4 |
```

— end of file —

File: lib/db/tsconfig.json

```
  1 | {
  2 |   "extends": "../../tsconfig.base.json",
  3 |   "compilerOptions": {
  4 |     "composite": true,
  5 |     "declarationMap": true,
  6 |     "emitDeclarationOnly": true,
  7 |     "outDir": "dist",
  8 |     "rootDir": "src",
  9 |     "types": ["node"]
 10 |   },
 11 |   "include": ["src"]
 12 | }
 13 |
```

— end of file —

File: package.json

```
   1 | {
   2 |   "name": "workspace",
   3 |   "version": "0.0.0",
   4 |   "license": "MIT",
   5 |   "scripts": {
   6 |     "preinstall": "sh -c 'rm -f package-lock.json yarn.lock; case \"$npm_config_user_agent\" in pnpm/*) ;; *) echo
\"Use pnpm instead\" >&2; exit 1 ;; esac'",
   7 |     "build": "pnpm run typecheck && pnpm -r --if-present run build",
   8 |     "typecheck:libs": "tsc --build",
   9 |     "typecheck": "pnpm run typecheck:libs && pnpm -r --filter \"./artifacts/**\" --filter \"./scripts\" --if-
present run typecheck"
  10 |   },
  11 |   "private": true,
  12 |   "devDependencies": {
  13 |     "typescript": "~5.9.2",
  14 |     "prettier": "^3.8.1"
  15 |   },
  16 |   "pnpm": {
  17 |     "overrides": {
  18 |       "lodash": "4.18.0",
  19 |       "path-to-regexp": "8.4.0",
  20 |       "picomatch@^2": "2.3.2",
  21 |       "picomatch@^4": "4.0.4"
  22 |     }
  23 |   }
  24 | }
  25 |
```

— end of file —

File: scripts/src/hello.ts

```
1 | console.log("Hello from @workspace/scripts");
2 |
```

— end of file —

File: tsconfig.base.json

```
1 | {
2 |   "compilerOptions": {
3 |     "isolatedModules": true,
4 |     "lib": ["es2022"],
5 |     "module": "esnext",
6 |     "moduleResolution": "bundler",
7 |     "noEmitOnError": true,
8 |     "noFallthroughCasesInSwitch": true,
9 |     "noImplicitOverride": false,
10 |     "noImplicitReturns": true,
11 |     "noUnusedLocals": false,
12 |     "noImplicitAny": true,
13 |     "noImplicitThis": true,
14 |     "strictNullChecks": true,
15 |     "strictFunctionTypes": false,
16 |     "strictBindCallApply": true,
17 |     "strictPropertyInitialization": true,
18 |     "useUnknownInCatchVariables": true,
19 |     "alwaysStrict": true,
20 |     "skipLibCheck": true,
21 |     "target": "es2022",
22 |     "types": [],
23 |     "customConditions": ["workspace"]
24 |   }
25 | }
26 |
```

— end of file —

File: tsconfig.json

```
 1 | {
 2 |   "extends": "./tsconfig.base.json",
 3 |   "compileOnSave": false,
 4 |   "files": [],
 5 |   "references": [
 6 |     {
 7 |       "path": "./lib/db"
 8 |     },
 9 |     {
10 |       "path": "./lib/api-client-react"
11 |     },
12 |     {
13 |       "path": "./lib/api-zod"
14 |     }
15 |   ]
16 | }
17 |
```

— end of file —