

MIDTERM MCQ QUESTIONS 2026

1) what is the status code that indicates url permanently moved to the new location

Choices:

(200-500-404-305/301 not sure)

2) what is the total width of { width:200px ; padding:15 px; border: 5px ; box-sizing: content - box }

Choices:

(200 - 240 - 260 - 230"not sure)

3) status code in response message is at **(request line - header line -status line -none of them)**

4) what is the output ?

Var x = '5'

Var y = 2

Console.log(x+y)

(52 - "52" - 7 - error)

5)what is the output ?

Var x = '5'

Var y = 2

Console.log(x-y)

(3 - "52" - 52 - error)

6) let x = 5 ;

If (true) {

```
Let x = 2;}
```

```
Console.log(x);
```

What's the output?

(5 - 2 - syntax error - undefined)

7) `var nums = [10,20,30,40,50];`

```
Var result = nums.find( value > 20) . Map ( myfun);
```

```
Function myfun { return value*2;}
```

```
Console.log(result);
```

Choices: (I am not sure about all of them)

A) [40,60,80,100]

B) [30,40,50]

C) [10,20,30,40,50]

D) [20, 40,60,80,100]

8) `var person/student ( something like that) = {`

```
Name : " Ali",
```

```
Age: 19
```

```
}
```

```
Console.log ( person.name + " is " + person.age );
```

What's the output?

Choices:

A) Ali is 19

B) Aliis19

C) error

9) `var name = " Hello World ";`

`Console.log( name.trim);`

Choices:

A) "HelloWorld"

B) "Hello World"

C) "Hello World "

D) " Hello World"

10) --The variable/function names are not precise at all ,but the question has similar idea ---

`var num = 5;`

`var result = square(num);`

`console.log(result);`

`function square(x) {`

`return x * x;`

`}`

How will be the function after applying ES6 version?

Choices:

A) `const square = x => x * x;`

B) `const square = (x) => { x * x };`

C) `const square = (x) => { return x * x; };`

D) `const square = x => return x * x;`

11) what is function that uses keyword await?

Choices:

(Promise - Async - fuction - none of them)

12) --The following code is different from the exam code , but I guess it is the same answer --

```
let myPromise = new Promise(function(resolve, reject) {  
  ok = true;  
  if (ok) {  
    resolve("OK");  
  } else {  
    reject("Error");  
  }  
});  
myPromise.then(  
  function(value) {myDisplayer(value);},  
  function(value) {myDisplayer(value);}  
);
```

When myPromise.then is called?

- A) after resolving (fulfilling)**
- B) after rejecting**
- C) both**

13) what is the output? `Console.log(Null ===undefined);`

Choices:

- A) true**
- B) false**
- C) undefined**
- D) error**

14) `<Div id = "id1">`

This is a `<b>paragraph</b>`

</Div>

```
Var result= document.getElementById("id1");
```

```
Console.log ( result.innerHTML) ;
```

```
Console.log(result.textContent) ;
```

[I am not sure about the code ,but the question was as following]

what is the difference between.innerHTML and .textContent ?

A) Both will print raw text with HTML tags

B) Both will print the text with bold effect

C) . innerHTML will print raw text with HTML tags and . textContent will print the text with bold effect

D) . textContent will print raw text with HTML tags and .innerHTML will print the text with bold effect

15) how to display H₂O in the HTML page ?

Choices

A)<P> H ₂ O</P>

B)<P> H ² O</P>

C)<P> H 2 O</P>

16) <Div id=container>

<p>paragraph 1</p>

<p>paragraph 2</p>

<Div>

<p> paragraph 3</p>

</Div>

</Div>

how many elements will be affected if we apply css styling to #container p { }

Choices (3 - 2 - 1 - 0)

17) How many elements will be changed if we apply css styling to #container > p

Choices (3-2-1-0)

18) what will be selected when we use this? document.querySelector("#main .title")

Choices :

- A) it will get all classes named title inside the main**
- B) it will get the first class named title inside the main**
- C) it will get all classes named main inside the title**
- D) it will get the first class named main inside the title**

19) inheritance question

20) what is the difference between display: none and visibility: hidden?

Choices:

- A) display: none; removes the element from the layout and visibility: hidden hides the element ,but it keeps the element in the layout**
- B) visibility: hidden; removes the element from the layout and display: none hides the element ,but it keeps the element in the layout**
- C) Both remove the element from the layout**
- D) Both hide the element ,but it keeps the element in the layout**

21) var nums= [1,2,3,4];

Console.log(typeof(nums));

what is the output?

Choices:

- A) array**
- B) object**

C) list

D) Boolean

22) `var fruits = ["Apple", "Banana","Orange"];`

`Console.log(fruits.include("banana"));`

Choices:

A) false

B) true

C) undefined

D) error

23) `var nums = [ 1,2,3,4 ];`

`Var sum = nums.reduce( myFun) ;`

`Console.log(sum);`

`Function myFun(total,value) {`

`return total + value ;`

`}`

What is the output?

Choices:(I am not sure about the choices at all)

A) 10

B) undefined

C) error

D) 4

24) `p {`

`Color: blue;`

`}`

```
.title {  
Color: green; }  
  
#main {  
Color: red; }
```

If all of these css styles are applied on all paragraphs (p) , what will be the color of p ?

Choices:

- A) red**
- B) green**
- C) blue**
- D) it will depend on where the style sheet exists**

25) question about using multiple parameters ((...args) or (args...) or (args) or none of them)