
Name: Mohaiya aldossary
Student ID: 2230004579

Introduction to Machine Translation (MT):

Machine Translation is a subfield of AI and linguistics that develops systems capable of translating text from one language to another. The primary goal of machine translation is to enable effective communication between people who speak different languages by automating the process of language translation.



Challenges in Machine Translation:

- Ambiguity

Ex. I went to the bank.

- Idiomatic Expressions

Ex. It's raining cats and dogs.

- Low-Resource Languages

Some languages have very limited data.


Applications of Machine Translation:

- Global Business and E-commerce -Cross-Cultural Communication
- Multilingual Content Creation
- Language Learning

Neural Machine Translation:

Neural Machine Translation is a data-driven approach where a single large neural network learns to represent both the source language and the target language, and to directly map between them. Instead of using manually defined rules or phrase tables, it learns translation patterns automatically from large datasets of bilingual text.

Key Components of Neural Machine Translation:



In [1]:

```
%pip -q install "tensorflow==2.16.1" "numpy>=1.26,<2" "pandas>=2.1,<4" scikit-learn nltk
```

```
Note: you may need to restart the kernel to use updated packages.
[notice] A new release of pip is available: 23.2.1 -> 26.2.2
[notice] To update, run: C:\Users\ezio9\OneDrive\Desktop\IAU\NLP\NLP lab\.lab_work\venv10\Scripts\python.exe -m pip install --upgrade pip
```

In [2]:

```
import tensorflow as tf
from tensorflow.keras.preprocessing.text import Tokenizer
import numpy as np

# Example bilingual dataset
english_sentences = ["Hello.", "How are you?", "This is a machine translation example."]
french_sentences = ["Bonjour.", "Comment ça va?", "Ceci est un exemple de traduction automatique."]

# Tokenize the english sentences
tokenizer_eng = Tokenizer()
tokenizer_eng.fit_on_texts(english_sentences) # Tokenize words and assign an integer ID to each unique word
eng_sequences = tokenizer_eng.texts_to_sequences(english_sentences) # Returns a list of tokens replaced by their index.
Note: words index will start from 1 because 0 is reserved by default for padding (not assigned to any word).
print(f"eng_sequences = {eng_sequences}")
eng_word_index = tokenizer_eng.word_index # Returns the dictionary created by the tokenizer dict {word: index}.
print(f"eng_word_index = {eng_word_index}")
```

```
eng_sequences = [[1], [2, 3, 4], [5, 6, 7, 8, 9, 10]]
eng_word_index = {'hello': 1, 'how': 2, 'are': 3, 'you': 4, 'this': 5, 'is': 6, 'a': 7, 'machine': 8, 'translation': 9, 'example': 10}
```

In [3]:

```
# Tokenize the french sentences
tokenizer_frn = Tokenizer()
tokenizer_frn.fit_on_texts(french_sentences)
frn_sequences = tokenizer_frn.texts_to_sequences(french_sentences)

print(f"frn_sequences = {frn_sequences}")
frn_word_index = tokenizer_frn.word_index
print(f"frn_word_index = {frn_word_index}")
```

```
frn_sequences = [[1], [2, 3, 4], [5, 6, 7, 8, 9, 10, 11]]
frn_word_index = {'bonjour': 1, 'comment': 2, 'ça': 3, 'va': 4, 'ceci': 5, 'est': 6, 'un': 7, 'exemple': 8, 'de': 9,
'traduction': 10, 'automatique': 11}
```

In [4]:

```
from tensorflow.keras.preprocessing.sequence import pad_sequences

# Padding sequences
eng_padded = pad_sequences(eng_sequences) # makes all sequences the same length by padding with zeros at the beginning
(default)
print(f"eng_padded = {eng_padded}")
```

```
eng_padded = [[ 0  0  0  0  0  1]
 [ 0  0  0  2  3  4]
 [ 5  6  7  8  9 10]]
```


In [5]:

```
frn_padded = pad_sequences(frn_sequences)
frn_padded
```

Out[5]:

```
array([[ 0,  0,  0,  0,  0,  0,  1],
       [ 0,  0,  0,  0,  2,  3,  4],
       [ 5,  6,  7,  8,  9, 10, 11]])
```

LSTM Model



In [6]:

```
from sklearn.model_selection import train_test_split

# Train-test split
eng_train, eng_test, frn_train, frn_test = train_test_split(eng_padded, frn_padded, test_size=0.2, random_state=42)

# Define the model
model = tf.keras.Sequential([
    tf.keras.layers.Embedding(input_dim=len(eng_word_index) + 1, output_dim=64),
    tf.keras.layers.LSTM(64),
    tf.keras.layers.RepeatVector(frn_padded.shape[1]), #Length of french sentence
    tf.keras.layers.LSTM(64, return_sequences=True),
    tf.keras.layers.TimeDistributed(tf.keras.layers.Dense(len(frn_word_index) + 1, activation='softmax')) #convert to
probabilities for each frn word
])

model.compile(optimizer='adam', loss='sparse_categorical_crossentropy', metrics=['accuracy'])

# Train the model
model.fit(eng_train, np.expand_dims(frn_train, -1), epochs=50, batch_size=1, validation_split=0.2)

# Evaluate the model
loss, accuracy = model.evaluate(eng_test, np.expand_dims(frn_test, -1))
print(f'Test Accuracy: {accuracy}')
```

```
Epoch 1/50
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 2s/step - accuracy: 0.0000e+00 - loss: 2.4851
▯▯▯
```

```
1/1 ━━━━━━━━━━━━━━━━━━━━ 0s 31ms/step - accuracy: 0.5714 - loss: 2.4249
▒▒▒
```

```
▒▒▒
```

```
▒▒▒
```

Task 2:

Use Case: Language Translation (English-French)

A global e-commerce company wants to expand its reach to French-speaking customers and provide a seamless shopping experience. The company needs a language translation solution to automatically translate product listings, customer reviews, and other relevant content from English to French.

link: https://www.kaggle.com/datasets/devicharith/language-translation-englishfrench

In [8]:

```
from pathlib import Path
from urllib.request import urlopen
from zipfile import ZipFile
from io import BytesIO
import pandas as pd

data_path = Path("data/eng_-french.csv")
if not data_path.exists():
    data_path.parent.mkdir(exist_ok=True)
    url = "https://www.kaggle.com/api/v1/datasets/download/devicharith/language-translation-englishfrench"
    with urlopen(url, timeout=180) as response:
        with ZipFile(BytesIO(response.read())) as archive:
            data_path.write_bytes(archive.read("eng_-french.csv"))

pairs = pd.read_csv(data_path).dropna()
pairs.columns = ["English", "French"]
print("Dataset pairs:", len(pairs))
display(pairs.head())
```

```
Dataset pairs: 175621
```

	English	French
0	Hi.	Salut!
1	Run!	Cours !
2	Run!	Courez !
3	Who?	Qui ?
4	Wow!	Ça alors !

In [9]:

```
import re
import unicodedata

tf.keras.utils.set_random_seed(42)

def normalize(text):
    text = unicodedata.normalize("NFKC", text).lower()
    text = re.sub(r"[^\w\s']", " ", text)
    return " ".join(text.split())

pairs = pairs.map(normalize)
pairs = pairs[(pairs.English.str.split().str.len().between(1, 5)) &
              (pairs.French.str.split().str.len().between(1, 7))]
pairs = pairs.drop_duplicates("English").sample(n=10000, random_state=42)
train_pairs, test_pairs = train_test_split(pairs, test_size=0.1, random_state=42)
train_pairs, val_pairs = train_test_split(train_pairs, test_size=0.1, random_state=42)

source_tokenizer = Tokenizer(oov_token="<unk>")
target_tokenizer = Tokenizer(oov_token="<unk>")
source_tokenizer.fit_on_texts(train_pairs.English)
target_tokenizer.fit_on_texts(train_pairs.French)

def encode(frame):
    source = pad_sequences(source_tokenizer.texts_to_sequences(frame.English),
                           maxlen=5, padding="post")
    target = pad_sequences(target_tokenizer.texts_to_sequences(frame.French),
                           maxlen=7, padding="post")
    return source, target

x_train, y_train = encode(train_pairs)
x_val, y_val = encode(val_pairs)
x_test, y_test = encode(test_pairs)
print("Training pairs:", len(train_pairs))
print("Validation pairs:", len(val_pairs))
print("Test pairs:", len(test_pairs))
print("English vocabulary:", len(source_tokenizer.word_index) + 1)
print("French vocabulary:", len(target_tokenizer.word_index) + 1)
```

```
Training pairs: 8100
Validation pairs: 900
Test pairs: 1000
English vocabulary: 3915
French vocabulary: 5344
```

In [10]:

```
translation_model = tf.keras.Sequential([
    tf.keras.layers.Input(shape=(5,)),
    tf.keras.layers.Embedding(len(source_tokenizer.word_index) + 1, 64, mask_zero=True),
    tf.keras.layers.LSTM(128),
    tf.keras.layers.RepeatVector(7),
    tf.keras.layers.LSTM(128, return_sequences=True),
    tf.keras.layers.TimeDistributed(tf.keras.layers.Dense(
        len(target_tokenizer.word_index) + 1, activation="softmax"))
])
translation_model.compile(optimizer="adam", loss="sparse_categorical_crossentropy")
translation_model.summary()
history = translation_model.fit(
    x_train, y_train, validation_data=(x_val, y_val),
    epochs=30, batch_size=64, verbose=2,
    callbacks=[tf.keras.callbacks.EarlyStopping(
        monitor="val_loss", patience=5, restore_best_weights=True)]
)
```

Model: "sequential_1"

Layer (type)	Output Shape	Param #
embedding_1 (Embedding)	(None, 5, 64)	250,560
lstm_2 (LSTM)	(None, 128)	98,816
repeat_vector_1 (RepeatVector)	(None, 7, 128)	0
lstm_3 (LSTM)	(None, 7, 128)	131,584
time_distributed_1 (TimeDistributed)	(None, 7, 5344)	689,376

Total params: 1,170,336 (4.46 MB)

Trainable params: 1,170,336 (4.46 MB)

Non-trainable params: 0 (0.00 B)

```
Epoch 1/30
127/127 - 6s - 46ms/step - loss: 5.8162 - val_loss: 5.1282
Epoch 2/30
127/127 - 3s - 22ms/step - loss: 4.9604 - val_loss: 5.0517
Epoch 3/30
127/127 - 3s - 22ms/step - loss: 4.8152 - val_loss: 4.9363
Epoch 4/30
127/127 - 3s - 23ms/step - loss: 4.6937 - val_loss: 4.8540
Epoch 5/30
127/127 - 3s - 22ms/step - loss: 4.5985 - val_loss: 4.7904
Epoch 6/30
127/127 - 3s - 22ms/step - loss: 4.5089 - val_loss: 4.7383
Epoch 7/30
127/127 - 3s - 22ms/step - loss: 4.4402 - val_loss: 4.7108
Epoch 8/30
127/127 - 3s - 22ms/step - loss: 4.3890 - val_loss: 4.7029
Epoch 9/30
127/127 - 3s - 22ms/step - loss: 4.3524 - val_loss: 4.6687
Epoch 10/30
127/127 - 3s - 22ms/step - loss: 4.3079 - val_loss: 4.6590
Epoch 11/30
127/127 - 3s - 22ms/step - loss: 4.2636 - val_loss: 4.6398
Epoch 12/30
127/127 - 3s - 23ms/step - loss: 4.2219 - val_loss: 4.6226
Epoch 13/30
127/127 - 3s - 26ms/step - loss: 4.1847 - val_loss: 4.6018
Epoch 14/30
127/127 - 3s - 26ms/step - loss: 4.1551 - val_loss: 4.5821
Epoch 15/30
127/127 - 3s - 26ms/step - loss: 4.1059 - val_loss: 4.5475
Epoch 16/30
127/127 - 3s - 25ms/step - loss: 4.0469 - val_loss: 4.5220
Epoch 17/30
127/127 - 3s - 26ms/step - loss: 3.9946 - val_loss: 4.5090
Epoch 18/30
127/127 - 3s - 26ms/step - loss: 3.9459 - val_loss: 4.4918
Epoch 19/30
127/127 - 3s - 25ms/step - loss: 3.9101 - val_loss: 4.4914
Epoch 20/30
127/127 - 3s - 26ms/step - loss: 3.8757 - val_loss: 4.4893
Epoch 21/30
127/127 - 3s - 25ms/step - loss: 3.8569 - val_loss: 4.4674
```

```
Epoch 22/30
127/127 - 3s - 25ms/step - loss: 3.7947 - val_loss: 4.4453
Epoch 23/30
127/127 - 3s - 25ms/step - loss: 3.7381 - val_loss: 4.4318
Epoch 24/30
127/127 - 3s - 26ms/step - loss: 3.6903 - val_loss: 4.4263
Epoch 25/30
127/127 - 3s - 25ms/step - loss: 3.6436 - val_loss: 4.4121
Epoch 26/30
127/127 - 3s - 25ms/step - loss: 3.5995 - val_loss: 4.4111
Epoch 27/30
127/127 - 3s - 26ms/step - loss: 3.5646 - val_loss: 4.4137
Epoch 28/30
127/127 - 3s - 25ms/step - loss: 3.5476 - val_loss: 4.3616
Epoch 29/30
127/127 - 3s - 25ms/step - loss: 3.5046 - val_loss: 4.3366
Epoch 30/30
127/127 - 3s - 26ms/step - loss: 3.4329 - val_loss: 4.3352
```

In [11]:

```python
from nltk.translate.bleu_score import corpus_bleu, SmoothingFunction

test_loss = translation_model.evaluate(x_test, y_test, verbose=0)
predicted_ids = translation_model.predict(x_test, batch_size=64, verbose=0).argmax(axis=-1)
token_accuracy = (predicted_ids[y_test != 0] == y_test[y_test != 0]).mean()
predictions = target_tokenizer.sequences_to_texts([
    [int(word_id) for word_id in row if word_id != 0] for row in predicted_ids
])
references = [[text.split()] for text in test_pairs.French]
bleu = corpus_bleu(references, [text.split() for text in predictions],
                   smoothing_function=SmoothingFunction().method1)
print(f"Test loss: {test_loss:.4f}")
print(f"Test token accuracy (excluding padding): {token_accuracy:.4f}")
print(f"Test BLEU (0-1, one reference per sentence): {bleu:.4f}")
display(pd.DataFrame({"English": test_pairs.English.to_numpy()[:5],
                      "Reference": test_pairs.French.to_numpy()[:5],
                      "Prediction": predictions[:5]}))

def translate_product(text):
    encoded = pad_sequences(source_tokenizer.texts_to_sequences([normalize(text)]),
                            maxlen=5, padding="post")
    ids = translation_model.predict(encoded, verbose=0).argmax(axis=-1)
    return target_tokenizer.sequences_to_texts([
        [int(word_id) for word_id in ids[0] if word_id != 0]
    ])[0]

for text in ["This is a good product.", "The price is too high.", "I like this shirt."]:
    print(f"English: {text}\nFrench: {translate_product(text)}\n")
```

```
Test loss: 4.3176
Test token accuracy (excluding padding): 0.1671
Test BLEU (0-1, one reference per sentence): 0.0050
```

	English	Reference	Prediction
0	i won't close the door	je ne fermerai pas la porte	je ne pas pas pas pas
1	the antelope ran away	l'antilope s'enfuit	ils sont sont
2	i spoke with tom's assistant	j'ai parlé à l'assistant de tom	je ce que de de de
3	no one is coming	personne ne vient	personne ne
4	i'm not racist	je ne suis pas raciste	je ne pas pas pas

```
English: This is a good product.
French: c'est une une

English: The price is too high.
French: c'est est est
English: I like this shirt.
French: j'aime les
```