Can Field Data Catch a Safety Regression?

Test coverage, sequential monitoring and automated risk reporting for automated-driving software releases. Technical report

Mohammad Albati, Ph.D.

Version 1.1 · November 2026 (adds the standards review and Section 5, the methods explained step by step) · Code: github.com/mohalbati/av-safety-monitoring · DOI 10.5281/zenodo.23858361

Contents

- Summary
- 1. Introduction
  - 1.1 The problem: regressions in a frequently updated safety-critical system
  - 1.2 Questions answered
  - 1.3 Contributions
  - 1.4 Relationship to the companion projects
  - 1.5 How to read this report
- 2. Background and literature review
  - 2.1 Statistical demonstration of safety
  - 2.2 Zero-failure demonstration testing
  - 2.3 Sequential monitoring and the CUSUM
  - 2.4 Risk management lifecycle
  - 2.5 Standards, regulations and guidance for ADS release safety
  - 2.6 What Waymo publishes
- 3. Data and assumptions
  - 3.1 Event rates
  - 3.2 Fleet exposure
  - 3.3 Release model
  - 3.4 What is not used
- 4. Methods
  - 4.1 Detectability: exact one-sample Poisson test
  - 4.2 Release-versus-release comparison
  - 4.3 Staged rollout
  - 4.4 Baseline-rate uncertainty
  - 4.5 Test coverage
  - 4.6 Poisson CUSUM
  - 4.7 Markov-chain verification of the run lengths
  - 4.8 Shewhart comparison
  - 4.9 Family-wise false alarms
  - 4.10 Overdispersion
  - 4.11 Leading-indicator coupling
  - 4.12 Bayesian sequential check
  - 4.13 Risk register
  - 4.14 Simulated release history and automated report
  - 4.15 Software
- 5. The methods explained step by step
  - 5.1 How to read the equations
  - 5.2 Building blocks: rates, exposure and the Poisson distribution
  - 5.3 Detectability: the exact Poisson test (Section 4.1)
  - 5.4 Comparing two releases (Section 4.2)
  - 5.5 Staged rollout (Section 4.3)

5.6 Uncertainty in the baseline: Bayesian estimation (Section 4.4)
5.7 Test coverage: how many scenario runs (Section 4.5)
5.8 The Poisson CUSUM (Section 4.6)
5.9 Verifying run lengths with a Markov chain (Section 4.7)
5.10 The Shewhart chart (Section 4.8)
5.11 False alarms across many charts (Section 4.9)
5.12 Overdispersion (Section 4.10)
5.13 Leading indicators must move with the outcome (Section 4.11)
5.14 The Bayesian sequential check (Section 4.12)
5.15 The risk register (Section 4.13)
5.16 Summary of the methods, their assumptions and sources
6. Results
6.1 How long field data needs to catch a regression
6.2 Staged rollout and release-versus-release comparison
6.3 Uncertainty in the baseline rate
6.4 How much testing replaces the missing field evidence
6.5 Sequential monitoring: design and performance
6.6 CUSUM versus a weekly threshold
6.7 A simulated two-year history
6.8 False alarms add up
6.9 Overdispersion: the hidden risk for frequent metrics
6.10 Leading indicators must move with the outcome
6.11 Risk register
6.12 Automated release health report
7. Discussion: what this means for release gating
7.1 A layered protection scheme
7.2 Alarm design as a system
7.3 Test coverage as a function of risk
7.4 The role of simulation credibility
7.5 Analogies with nuclear practice
8. Verification
9. Limitations
10. Future work
11. Reproduce
References
Appendix A. Equation register
Appendix B. Assumption register
Appendix C. Glossary
Appendix D. Code and output map

Summary

Automated driving systems (ADS) receive software updates every few weeks. Each update can improve the driving, and each can also make some behavior worse. A safety team that owns release risk has to answer two questions for every release:

1. **Was the testing before the release enough?**
2. **If the release did make driving less safe, how quickly would field data show it, and how should the alarms be set?**

This report answers both questions with numbers. It uses event rates derived from public NHTSA Standing General Order (SGO) crash reports for Waymo’s rider-only fleet (271.3 million

miles through June 2026; companion analysis, DOI 10.5281/zenodo.23732384), standard statistical methods, and an open Python code base with verification tests. It does not use any company-internal data.

Main findings

- **Field data catches only frequent outcomes quickly.** With the whole fleet driving about 2.9 million miles a week, a 25% increase in the all-crash rate is detectable in about **6 weeks** (80% power, 5% false alarm). The same increase takes about **65 weeks** for any-injury crashes, **150 weeks** for airbag deployments and about **1,730 weeks (33 years)** for serious-injury-or-worse crashes. Detecting a +25% change always needs about **116 expected baseline events**, whatever the metric; rare outcomes simply take longer to collect them.
- **Staged rollouts make this worse.** A release running on 10% of the fleet needs ten times longer: about a year for a +25% change in all crashes.
- **So release gating for severe outcomes must rely on testing and on leading indicators.** Showing that a scenario type fails less than 1% of the time, at 95% confidence, takes **299 failure-free runs**; for 0.1% it takes **2,995**. Plans that tolerate one or two failures need 1.6–2.1 times more runs but pass good releases more often.
- **Sequential monitoring works, and its design can be verified.** Poisson CUSUM charts, calibrated by simulation to one false alarm per metric every five years, detect a +50% regression in a median of 3 weeks (all crashes) to 70 weeks (serious injuries). An independent Markov-chain calculation reproduces every simulated run length within 2.2%.
- **CUSUM beats a simple weekly threshold** by a factor of about 2 to 5 for moderate regressions in injury and airbag counts.
- **False alarms add up.** Five charts, each with one false alarm per five years, give an **86%** chance of at least one false alarm somewhere in two years. Every alarm needs a fast, cheap triage step.
- **Week-to-week variation breaks naive charts on frequent metrics.** If the true weekly rate varies by 5–20% (weather, city mix, demand), a chart designed for pure Poisson counts on a high-count leading indicator false-alarms every 1 to 11 months instead of every 5 years. Recalibrating the threshold restores the false-alarm interval while keeping detection within about 3 weeks.
- **A leading indicator helps only if it moves with the severe outcome.** If an indicator rises by 12.5% when serious injuries rise 50%, it alarms in about 2 weeks; if it rises by only 2.5%, it takes about a year (median 56 weeks).
- **The reporting can be automated.** One script produces a scored risk register following the ISO 31000 lifecycle, with uncertainty on every score, and a one-page release health report with the bottom line first.

What this means for release gating: gate severe outcomes on risk-weighted scenario testing; establish the credibility of the simulation that carries that testing; monitor leading indicators whose link to severe outcomes is demonstrated; design alarms as a system with a false-alarm budget; and generate the reporting from code so it stays consistent from release to release.

1. Introduction

1.1 The problem: regressions in a frequently updated safety-critical system

An ADS is a software-intensive system that is updated regularly: new maps and cities, new perception and prediction models, changes to the driving policy, and fixes to field issues. Every update is meant to make the system better, but a change that improves one behavior can degrade another. A **regression** in this report is any release whose rate of an undesirable event (a crash, an injury, a hard-braking event) is higher than that of the release before it.

Regression protection is a standard concern in safety-critical industries. In nuclear power, plant modifications go through a safety evaluation before installation and are followed by performance-indicator monitoring afterwards (for example the U.S. reactor oversight performance indicators, NEI 99-02). In automated driving, the safety-case standard UL 4600 asks for safety performance indicators that are monitored in the field and fed back into the safety case. The questions are the same in both industries: what evidence is needed before the change, and how fast would the field reveal a problem after it?

1.2 Questions answered

This report answers seven questions:

- **Q1. Detectability.** How many miles, and how many weeks of fleet driving, does it take to detect a regression of a given size in each safety metric?
- **Q2. Deployment strategy.** How do staged rollouts and release-to-release comparisons change that answer?
- **Q3. Test coverage.** When field data cannot catch a regression in time, how many scenario runs are needed instead, and what are the trade-offs of different test plans?
- **Q4. Sequential monitoring.** How should weekly field monitoring be designed, how fast does it detect a regression, and how can its design be verified?
- **Q5. Robustness.** How do false alarms across many charts, overdispersed counts and weak leading indicators affect monitoring?
- **Q6. Risk register.** How can hazards be scored and ranked with honest uncertainty, following the ISO 31000 lifecycle?
- **Q7. Reporting.** Can the analysis produce a release health report automatically?

1.3 Contributions

1. A quantitative map of what field data can and cannot catch, by metric and regression size, for a large robotaxi fleet, with a simple rule: about 116 expected baseline events to detect +25%.
2. Test-plan sizing linked to risk targets, including plans that allow failures, a Bayesian alternative, and operating-characteristic curves.
3. A calibrated, verified CUSUM monitoring design per metric, with a comparison against a simple threshold chart and a Markov-chain verification.
4. Three robustness studies that matter in practice: the false-alarm budget, overdispersion and leading-indicator coupling.
5. An ISO 31000 risk register with posterior uncertainty and ranking probabilities, and an automatically generated release health report.

6. A review of the standards and regulations that govern ADS release safety (ISO 26262, ISO 21448, ISO/TS 5083, UL 4600, UN R156, UN R185, EU 2022/1426 and others), showing that they require field monitoring and change management but leave the statistical design open (Section 2.5).
7. A step-by-step explanation of every method for non-specialists, with derivations, worked examples and figures (Section 5).
8. Open code with ten verification tests; every number in this report is produced by `scripts/run_all.py`, `scripts/supplementary.py` and `scripts/explainer_figures.py`.

1.4 Relationship to the companion projects

This is the third of three open projects on automated-driving safety:

- **av-safety-bayesian-analysis** (DOI 10.5281/zenodo.23732384) asks how much evidence the fleet record provides. It supplies the event rates used here.
- **av-counterfactual-uq** (DOI 10.5281/zenodo.23838254) asks how certain a counterfactual crash simulation is. It matters here because, when field data cannot protect a release, simulation-based testing must, and its credibility becomes part of the safety evidence.
- **av-safety-monitoring** (this report) asks what protects a release after it ships.




Figure 1. Workflow of the analysis. Public crash data and fleet exposure feed three analyses (detectability, test coverage and field monitoring), which feed a scored risk register and an automatically generated release health report.

1.5 How to read this report

Section 2 reviews the statistical literature and, in detail, the standards and regulations that govern ADS release safety. Section 3 describes the data and every assumption. Section 4 states each method concisely with its equations. **Section 5 explains every method from first principles**, with derivations of all equations, the meaning of every symbol, the assumptions, the sources and worked examples with the study's numbers; it is written for readers without a background in statistics. Section 6 presents the results, Section 7 discusses what they mean for release gating, Section 8 summarizes verification, and Sections 9–11 cover limitations, future work and reproduction. The appendices contain the equation register, the assumption register,

a glossary and the code map. Figures and tables in Sections 2 and 5 are numbered by section (for example Figure 5.3); all others are numbered in sequence.

2. Background and literature review

This section reviews the two bodies of work this report builds on. The first is the statistical literature: how to demonstrate safety from driving data, how to size a test program, and how to monitor a rate over time. The second is the body of standards and regulations that tell an ADS developer what must be shown before a release and what must be watched after it. Section 2.5 reviews the standards in detail, because they set the requirements that the methods of Section 4 turn into numbers.

2.1 Statistical demonstration of safety

The problem of rare events. Kalra and Paddock (2016) asked how many miles an automated fleet would need to drive, with no failures, to show that its fatality rate is below the human rate of about 1.09 deaths per 100 million miles in the United States at that time. Their answer, about 275 million failure-free miles for 95% confidence, and billions of miles to show a 20% improvement, made a point that every later study accepts: driving alone cannot demonstrate safety for the most severe outcomes in any reasonable time. Their arithmetic is the same zero-failure arithmetic used for test plans in Section 4.5.

Comparison with human benchmarks. Since then, developers have published crash-rate comparisons with human benchmarks matched to the same roads and conditions. Waymo's analyses (for example Kusano et al., 2024) compare police-reported and injury crash rates of its rider-only fleet with benchmarks built from state crash data and naturalistic driving. These studies answer "is the fleet safer than humans?", which is a one-time comparison of two rates. They do not address the question of this report: how quickly would the data reveal that a *new release* is worse than the *previous one*.

Bayesian rare-event methods. Nuclear probabilistic risk assessment (PRA) has long estimated rates of rare events from few or zero failures with Bayesian methods (Atwood et al., 2003). The companion analysis applied those methods to Waymo's public record and found, for example, that a new operator needs about 9.1 million miles with zero serious crashes to claim, at 95% confidence, that it beats human drivers on serious injuries. That analysis supplies the rates used here (Section 3.1).

From one rate to a change in rate. Detecting a regression is harder than estimating a rate, because two uncertain quantities are compared. Classic results for comparing Poisson rates (the exact conditional test, and the normal approximation on the log rate ratio) are standard in epidemiology and reliability engineering. Section 4.1 uses the exact one-sample test, and Section 4.2 the two-sample approximation.

2.2 Zero-failure demonstration testing

When failures are rare, reliability engineers size test programs by the number of failure-free trials needed to bound the failure probability. With zero failures in n independent trials, the one-sided upper confidence bound on the failure probability gives the "rule of three": about $3/n$ at 95% confidence (Hanley and Lippman-Hand, 1983). Plans that allow c failures use the exact

binomial bound of Clopper and Pearson (1934). Bayesian versions put a prior distribution on the failure probability; the Jeffreys prior is the default non-informative choice in PRA (Atwood et al., 2003).

These ideas are standardized. IEC 61123:2019 gives compliance test plans for a *success ratio*, that is, for items tested as independent pass/fail trials with a constant failure probability, which is exactly the situation of a scenario library run against a release. It includes fixed-length plans and truncated sequential probability ratio test (SPRT) plans with tables of their operating characteristics. IEC 61124:2023 gives the corresponding plans for a *constant failure rate* (failures per unit time or distance). The U.S. military handbook MIL-HDBK-781A provides similar fixed-length and sequential reliability test plans. All of them describe a plan by its operating characteristic (OC) curve: the probability of passing as a function of the true failure probability, the tool used in Section 4.5.

2.3 Sequential monitoring and the CUSUM

Sequential testing. Wald (1945) introduced the sequential probability ratio test (SPRT): instead of fixing the sample size in advance, the evidence is examined after each observation, and testing stops as soon as the likelihood ratio crosses a boundary. On average the SPRT needs far fewer observations than a fixed-size test with the same error rates.

The CUSUM. Page (1954) turned the same idea into a monitoring tool. The cumulative sum (CUSUM) chart adds up the log-likelihood ratio of “the process has shifted” against “it has not”, resets to zero when the sum becomes negative, and alarms when the sum crosses a threshold h. Lorden (1971) and Moustakides (1986) proved that the CUSUM is optimal: among all procedures with the same mean time between false alarms, it minimizes the worst-case delay in detecting the shift it is tuned for.

Counted data. Lucas (1985) gave the Poisson CUSUM for counts, with a reference value k chosen to detect a shift from a mean of m_0 to m_1 (Section 4.6). Performance is measured by the average run length (ARL): ARL_0, the mean time between false alarms when nothing has changed, and ARL_1, the mean time to detect a real shift. Brook and Evans (1972) showed that the ARL can be computed exactly by treating the CUSUM as a Markov chain (Section 4.7). Hawkins and Olwell (1998) and Montgomery (2019) are the standard textbooks. ISO 7870-4:2021 standardizes CUSUM charts, and ISO 7870-2:2023 the simpler Shewhart charts that alarm on a single unusual observation (Section 4.8).

Health surveillance. CUSUMs are widely used to monitor rare adverse events in health care and public health (Woodall, 2006), for example surgical mortality, where Steiner et al. (2000) introduced a risk-adjusted CUSUM that accounts for patient mix. Rare counts, a changing case mix and many charts monitored at once make that setting a close analogue of crash monitoring for an ADS fleet.

2.4 Risk management lifecycle

ISO 31000:2018 defines risk management as a cycle: establish the context; identify, analyze and evaluate risks; treat them; monitor and review; and communicate and report. IEC 31010:2019 catalogs the techniques used at each step. ISO/IEC Guide 51:2014 defines *tolerable risk* (risk accepted in a given context based on the current values of society) and describes risk reduction as an iterative process of assessment and reduction until the residual risk is tolerable.

This report uses the ISO 31000 lifecycle for the risk register (Section 4.13) and treats CUSUM charts as one implementation of the “monitor and review” step.

2.5 Standards, regulations and guidance for ADS release safety




Figure 2.1. The standards and regulations reviewed in this section, grouped by the question they answer, and how this report relates to them. Most of them require that field performance be monitored and that changes be managed; none prescribes how to design the statistical monitoring, which is the gap this report addresses.

2.5.1 Functional safety: IEC 61508 and ISO 26262

IEC 61508 is the generic standard for the functional safety of electrical, electronic and programmable electronic safety-related systems. It introduced the safety lifecycle, safety integrity levels and the idea that the rigor of development must match the risk. Sector standards, including ISO 26262 for road vehicles, are adaptations of it.

ISO 26262:2018 (second edition, 12 parts) addresses hazards caused by *malfunctioning behavior* of electrical and electronic systems, that is, faults. Hazards are classified by severity, exposure and controllability into Automotive Safety Integrity Levels (ASIL A to D), which set the required rigor. Three parts of it bear directly on release regressions:

- **Change management** (ISO 26262-8): every change to an item, including a software change, needs an impact analysis that identifies the work products and safety activities affected, and the change must be verified before release. A regression is precisely what an incomplete impact analysis lets through.
- **Safety management after release** (ISO 26262-2) and **production, operation, service and decommissioning** (ISO 26262-7): the organization must keep a field-monitoring process to detect safety-relevant anomalies after release and feed them back into development.
- **Confirmation measures** (ISO 26262-2): independent reviews and audits of the safety case and safety activities.

ISO 26262 does not say how fast a field-monitoring process must detect a problem, or how to set its thresholds.

2.5.2 Safety of the intended functionality: ISO 21448

ISO 21448:2022 (SOTIF) covers hazards that arise *without any fault*, from performance limitations of the intended function (for example a perception system that misjudges an unusual object) or from reasonably foreseeable misuse. It divides scenarios into four areas: known safe, known hazardous, unknown hazardous and unknown safe. The aim of SOTIF activities is to shrink the two hazardous areas, the known ones by design and verification, the unknown ones by validation and exploration. Three of its concepts are used in this report:

- **Acceptance criteria and validation targets.** The developer defines what residual risk is acceptable, often from human-driver accident statistics, and derives validation targets (for example a number of miles or scenario runs without a hazardous event) that would demonstrate it with stated confidence. The zero-failure arithmetic of Section 4.5 is one way to derive such targets.
- **Triggering conditions.** Specific conditions of a scenario that trigger hazardous behavior. Scenario types in the test library of Section 4.5 are organized around them.
- **Operation phase activities.** After release, field monitoring must look for new triggering conditions and for evidence that the residual risk is higher than argued, and must feed this back into the SOTIF process.

2.5.3 Safety of ADS: ISO/TS 5083, UL 4600, SAE J3016, IEEE 2846 and the ISO 3450x series

ISO/TS 5083:2025 (Road vehicles, safety for automated driving systems, design, verification and validation) replaced ISO/TR 4804:2020. It ties ISO 26262, ISO 21448 and cybersecurity together into an ADS-level safety case and covers the safety strategy (including risk acceptance criteria and the absence of unreasonable risk), safety by design, verification, validation and operation. Its operation clause includes field monitoring with data collection, change management, and the management of crashes and incidents; its validation clause includes metrics and an example of validation by computing collision rates. These are the activities quantified in Sections 4.1–4.11.

ANSI/UL 4600 (third edition, 2023) is a standard for the *safety case* of autonomous products: a structured argument, supported by evidence, that the system is acceptably safe. It does not prescribe a design method; it lists what the safety case must address and how it is assessed. Central to it are **safety performance indicators (SPIs)**: metrics with defined thresholds that provide evidence that the claims of the safety case remain valid during operation. When an SPI is violated, the safety case must be re-examined and corrected. A Poisson CUSUM on an injury-crash rate or on a leading indicator, with a stated false-alarm interval and detection delay, is a concrete SPI design; Sections 4.6–4.11 give the numbers UL 4600 asks for but does not supply.

SAE J3016:2021 defines the levels of driving automation (0–5) and the operational design domain (ODD), the conditions under which the system is designed to operate. The fleet analyzed here is Level 4. **IEEE 2846-2022** defines minimum reasonable assumptions about the behavior of other road users that an ADS safety model should make. The **ISO 3450x series** standardizes scenario-based testing: vocabulary (ISO 34501:2022), the scenario-based safety evaluation framework (ISO 34502:2022), the ODD taxonomy (ISO 34503:2023), scenario categorization (ISO 34504:2024) and scenario evaluation and test-case generation (ISO 34505:2025). The test-coverage plans of Section 4.5 assume a scenario library organized in this way.

2.5.4 Artificial intelligence and cybersecurity

ISO/PAS 8800:2024 extends ISO 26262 and ISO 21448 to AI elements such as machine-learned perception. It addresses data quality, the AI development lifecycle, verification and validation of AI components, and monitoring after deployment. Because ADS releases often change machine-learned models, regressions in AI behavior are one of the main sources of the regressions studied here. **ISO/SAE 21434:2021** (cybersecurity engineering) and UN Regulation No. 155 (cybersecurity management system) govern security, which matters here mainly because every over-the-air update must be secure.

2.5.5 Software updates: UN Regulation No. 156 and ISO 24089

UN Regulation No. 156 requires vehicle manufacturers to operate an audited **software update management system (SUMS)**. Before an update is released, the manufacturer must identify the target vehicles, check compatibility with each vehicle configuration, assess the impact on safety and on the type approval, test and validate the update, and plan for recovery if an update fails. Each type-approval-relevant software version is identified by a Regulation Software Identification Number (RXSWIN). **ISO 24089:2023** gives the engineering guidance for software updates. These documents make the *process* around each release mandatory; the release-to-release analysis of Sections 4.1–4.5 addresses the *evidence* that a release has not made driving less safe.

2.5.6 Regulation of ADS and crash reporting

United States. The NHTSA **Standing General Order 2021-01** requires manufacturers and operators of ADS and Level 2 vehicles to report qualifying crashes. Its third amendment was issued on 24 April 2025 and took effect on 16 June 2025: the most severe crashes must be reported within five days and less severe ones monthly, and ADS reporting now has a property-damage threshold for less severe crashes. These reports are the data source of this report and of its companion. In April 2025 NHTSA also announced an AV Framework, including an expanded exemption program; in June 2026 it withdrew its January 2025 proposal for a voluntary program (AV STEP). There is no U.S. federal performance standard that sets how safe an ADS release must be or how it must be monitored.

United Nations. UN Regulation No. 157 (Automated Lane Keeping Systems) was the first binding regulation for a Level 3 system. In June 2026, the World Forum WP.29 adopted a UN Regulation (No. 185) and a UN Global Technical Regulation (No. 26) on automated driving systems. Their main elements are a safety management system covering the whole lifecycle, a safety case showing that the ADS is free of unreasonable risk and at least as safe as a competent and careful human driver, validation by simulation, track and real-world testing, and in-service obligations: data storage, prompt reporting of critical events and periodic reporting of safety performance.

European Union. Regulation (EU) 2022/1426 sets the type-approval rules for the ADS of fully automated vehicles in defined use cases (for example hub-to-hub and predefined areas). It requires a safety management system, an assessment showing that the vehicle is free of unreasonable risk compared with manually driven vehicles in comparable services, and **in-service monitoring and reporting (ISMR)**: the manufacturer must collect field data, analyze

safety-relevant incidents and report relevant occurrences to the authorities. An indicative benchmark of 10^{-7} fatalities per hour of operation is given in a footnote.

2.5.7 Analogues from nuclear power

In U.S. nuclear power, a plant change is screened under 10 CFR 50.59 to decide whether it needs prior regulatory approval, and plant performance is tracked through the Reactor Oversight Process performance indicators (NEI 99-02), each with predefined thresholds (green, white, yellow and red bands) and a defined regulatory response at each band. The maintenance rule (10 CFR 50.65) requires licensees to monitor the performance of structures, systems and components against goals and to take corrective action when goals are not met. The structure is the same as the one this report proposes for ADS releases: an evaluation before the change, indicators with thresholds after it, and a predefined response to a threshold crossing.

2.5.8 What the standards require and what this report supplies

Table 2.1. How the standards and regulations relate to release safety, and what this report adds.

Document	What it requires for release and field safety	What it leaves open	Where this report helps
ISO 26262:2018	Impact analysis and verification for every change; field monitoring after release	How fast monitoring must detect a problem; thresholds	Detectability (4.1–4.4); CUSUM design (4.6–4.8)
ISO 21448:2022	Acceptance criteria; validation targets; operation-phase monitoring	Sizing of validation per scenario type; statistical monitoring design	Test-plan sizing and OC curves (4.5)
ISO/TS 5083:2025	ADS safety case; V&V; operation with field monitoring and change management	Quantitative monitoring design	Sections 4.1–4.11
ANSI/UL 4600	SPIs with thresholds, monitored in the field, triggering safety-case updates	Statistical design of SPI thresholds; false-alarm budgets	CUSUM SPIs (4.6); false alarms (4.9); dispersion (4.10); leading indicators (4.11)
ISO 3450x series	Scenario-based testing framework and test-case generation	How many runs per scenario type	Runs per scenario type (4.5)
UN R156 / ISO 24089	Managed, validated, traceable software updates	Evidence that an update did not reduce safety	Release-versus-release comparison (4.2); staged rollout (4.3)
UN R185 / GTR 26; EU 2022/1426	Safety management system; safety case; in-service monitoring and reporting	What can be detected from in-service data, and how quickly	Detectability map (6.1–6.3); release health report (4.14)
NHTSA SGO 2021-01	Crash reporting	Normalization by exposure; trend detection	Rates (3.1); monitoring (4.6)
ISO 31000 / IEC 31010	Risk lifecycle, including monitor and review	Uncertainty in risk scores	Register with posterior intervals and ranking probabilities (4.13)
ISO 7870-2/-4; IEC 61123/61124	Chart and test-plan methods	Application to ADS rates and releases	All of Section 4

The pattern is consistent. Every recent standard and regulation requires field monitoring, change management and evidence that a release keeps risk acceptable. None of them specifies how to design the statistics: which metrics can detect what size of regression in what time, how many scenario runs a release needs, how to set thresholds, or how to budget false alarms across many indicators. Those design questions are the subject of this report.

2.6 What Waymo publishes

Waymo publishes crash-rate comparisons with human benchmarks (for example Kusano et al., 2024) and has described its overall approach to determining the absence of unreasonable risk (Favarò et al., 2023), which combines several complementary methodologies rather than a

single metric. This report does not describe or evaluate Waymo's internal release process; it uses public rates to show, quantitatively, the constraints any such process faces.

3. Data and assumptions

3.1 Event rates

Table 1. Event rates (per million miles). PUBLISHED-DERIVED values come from public NHTSA SGO crash reports for Waymo's rider-only fleet, analyzed in the companion repository; the ASSUMED value is illustrative.

Metric	Rate per million miles	Events behind it	Basis
All reported crashes	7.13	1,934 crashed vehicles	Published-derived: 1,934 / 271.3M miles
Any-injury crashes	0.612	166	Published-derived: posterior median (Jeffreys)
Airbag deployment	0.266	72	Published-derived: posterior median
Serious injury or worse	0.023	6	Published-derived: posterior median
Leading indicator (e.g. hard braking, near misses)	100	–	Assumed; such data are not public

The leading indicator stands for any frequent event that on-board triggers or log review can count, such as hard-braking events, close-following events or disengagement-like interventions. Its value of 100 per million miles is chosen only to represent a metric that is about 14 times more frequent than reported crashes.

3.2 Fleet exposure

The companion analysis found 542 crashed vehicles reported in January–June 2026. At 7.13 crashes per million miles, that corresponds to about 76 million miles in six months:

$$W_{\text{month}} = \frac{542}{7.13 \times 6} \approx 12.7 \,\text{million miles per month}, \qquad W = W_{\text{month}} \times \frac{12}{52} \approx 2.92 \,\text{million miles per week}$$

Expected weekly counts are therefore 20.8 (all crashes), 1.79 (any injury), 0.78 (airbag), 0.067 (serious injury) and 292 (leading indicator).

3.3 Release model

Releases are assumed to go out every four weeks to the whole fleet unless stated otherwise. A regression multiplies the rate of a metric by (1 + *r*) from the release that introduces it. Section 6.2 relaxes the whole-fleet assumption.

3.4 What is not used

No company-internal data. The simulated release history is synthetic. The operational hazards H6–H8 in the risk register have no public data and are flagged as data gaps rather than given invented numbers. Appendix B lists every assumption.

4. Methods

4.1 Detectability: exact one-sample Poisson test

The baseline rate λ_0 is known well from long fleet history (thousands of events for frequent metrics). After a release, N events are observed in M million miles. Under the null hypothesis (no regression), N ~ Poisson(λ_0M). The test alarms if N reaches the critical count

$$c(M) = \min\{n : P(N \geq n \mid \lambda_0 M) \leq \alpha\}, \qquad \alpha = 0.05$$

The power to detect a regression to $\lambda_1 = (1 + r)\lambda_0$ is

$$\text{power}(M) = P(N \geq c(M) \mid \lambda_1 M) = 1 - F_{\text{Pois}}(c(M) - 1;\ \lambda_1 M)$$

Because counts are discrete, power is not monotone in M: it rises in a saw-tooth as c(M) steps up. The exposure reported is therefore the smallest M after which power stays at or above 80% (searched on a fine logarithmic grid from 0.001 to 100,000 million miles). Weeks of fleet driving are M / W.

Worked example (any-injury crashes, +25%). The reported exposure is M = 188.5 million miles (64.5 weeks). The expected baseline count is 0.612 × 188.5 = 115.4 events, the critical count is c = 134 (actual false-alarm rate 4.8%), the expected count under the regression is 144.2, and the power is 81.3%.

4.2 Release-versus-release comparison

When there is no long baseline (for example the first months in a new city), the new release must be compared with the previous one, each observed over M miles. Using the normal approximation for the log rate ratio,

$$\text{Var}\left[\ln\frac{\widehat{\lambda}_1}{\widehat{\lambda}_0}\right] \approx \frac{1}{\lambda_0 M} + \frac{1}{\lambda_1 M}, \qquad M = \frac{\left(z_{1-\alpha} + z_{\text{power}}\right)^2 \left(\frac{1}{\lambda_0} + \frac{1}{\lambda_1}\right)}{\left[\ \ln\ (1+r)\ \right]^2}$$

4.3 Staged rollout

If a release runs on a fraction f of the fleet, it accumulates fM miles per week, so the calendar time to detect scales as 1/f:

$$T_f = \frac{M}{fW}$$

4.4 Baseline-rate uncertainty

For rare outcomes the baseline itself is uncertain. With a Jeffreys prior, the posterior of λ_0 after k events in 271.3 million miles is Gamma(k + ½, 271.3). Detection times are recomputed at the 5th, 50th and 95th posterior percentiles of λ_0.

4.5 Test coverage

Zero-failure plan. To show that a scenario type's failure probability p is below p_0 at confidence C with n failure-free runs:

$$\left(1-p_0\right)^n \le 1-C \quad \Rightarrow \quad n=\left\lceil \frac{\ln\,(1-C)}{\ln\left(1-p_0\right)} \right\rceil \approx \frac{-\ln\,(1-C)}{p_0} \approx \frac{3}{p_0}\;\;(C=0.95)$$

Plans that allow c failures. The release passes if at most c failures occur in n runs; n is the smallest value with

$$F_{\mathrm{Bin}}\left(c;\,n,p_0\right)=\sum_{j=0}^{c}\binom{n}{j}p_0^{\,j}\left(1-p_0\right)^{n-j}\le 1-C$$

Bayesian zero-failure plan. With a Jeffreys prior Beta(½, ½) and zero failures in n runs, the posterior is Beta(½, n + ½); n is the smallest value with P(p < p_0 | data) ≥ C.

Operating characteristic (OC). For a plan (n, c), the probability that a release whose true failure probability is p passes is F_{Bin}(c; n, p). The OC curve shows how often good releases are wrongly held and bad ones wrongly passed.

4.6 Poisson CUSUM

Let X_t be the event count in week t, with in-control mean $m_0 = \lambda_0 W$. The chart is tuned to detect the shift to $m_1 = (1 + r_d)m_0$ with $r_d = 0.25$ (Lucas, 1985):

$$k=\frac{m_1-m_0}{\ln\,(m_1/m_0)},\qquad S_0=0,\qquad S_t=\max\,(0,\,S_{t-1}+X_t-k)\,,\qquad \text{alarm if } S_t\ge h$$

The reference value k lies between m_0 and m_1, so S_t drifts down when the process is in control and up after a regression. The threshold h is chosen so that the in-control ARL is 260 weeks (one false alarm per metric every five years). It is found by bisection on h, with the ARL estimated from 1,500 simulated run lengths at each step. After an alarm the statistic is reset to zero, as it would be after an investigation.

Worked example (all crashes). m_0 = 20.85 crashes per week, m_1 = 26.06, k = 23.35 and h = 16.93. In the simulated history the weekly counts in weeks 55–60 were 23, 20, 17, 19, 22 and 23, all below k, so S_t stayed at 0. The regression starts in week 60; in week 61 the count was 46, S = 0 + 46 − 23.35 = 22.65 ≥ 16.93, and the chart alarmed.

4.7 Markov-chain verification of the run lengths

Brook and Evans (1972) represent the CUSUM statistic as a Markov chain. The statistic is placed on a grid of width 1/g, with g chosen between 100 and 1,200 so that k is represented as exactly as possible within 5,000 states. With K = round(kg) and H = ⌈hg⌉, the transition from state i is to state max(0, i + gX − K) with probability P(X = x), and any state ≥ H is absorbing (an alarm). With R the transition matrix among the H in-control states,

$$\mathbf{ARL}=\left(\mathbf{I}-\mathbf{R}\right)^{-1}\mathbf{1},\qquad \text{ARL from a fresh start}=\mathbf{ARL}_0$$

This is computed independently of the simulation and used to verify it (Section 8).

4.8 Shewhart comparison

A one-sided Shewhart chart alarms when a single week's count reaches a limit c, chosen as the smallest value with P(X ≥ c | m_0) ≤ 1/260. Its ARL is 1 / P(X ≥ c | m). Because counts are

discrete, its ARL_0 is at least 260 weeks and can be much larger.

4.9 Family-wise false alarms

Run lengths of a well-designed CUSUM in control are close to geometric, so the probability that one chart false-alarms within T weeks is about $1 - \exp(-T/ARL_0)$. For m independent charts,

$$P(\text{ at least one false alarm in } T \text{ weeks }) \approx 1 - \exp\left(-\frac{mT}{\mathrm{ARL}_0}\right)$$

The simulated value for the five charts of this study is checked against this approximation.

4.10 Overdispersion

Real weekly counts vary more than Poisson because the underlying rate changes with weather, city mix, events and demand. This is modeled by drawing each week's rate from a Gamma distribution with mean m_0 and coefficient of variation (CV) v, so that counts are negative binomial with

$$\mathrm{Var}\ (X_t) = m_0 + v^2 m_0^2$$

The extra term grows with m_0^2, so overdispersion matters most for frequent metrics. The ARL_0 of the Poisson-designed chart is estimated by simulation for v = 0, 5%, 10% and 20%; for v = 10% the threshold is then recalibrated by bisection to restore $ARL_0 = 260$ weeks, and the cost in detection speed is measured.

4.11 Leading-indicator coupling

Suppose serious injuries rise by 50% and the leading indicator rises by 50β%, where $\beta \in [0, 1]$ measures how strongly the indicator moves with the severe outcome. The median run length of the leading-indicator chart is computed for β = 0, 0.05, 0.10, 0.25, 0.5 and 1 and compared with the serious-injury chart itself.

4.12 Bayesian sequential check

As a second view of the same data, after a suspected change at week t_0 the posterior probability that the rate has increased is computed with a Jeffreys prior:

$$P(\lambda > \lambda_0 \mid N, M) = 1 - F_{\Gamma}\left(\lambda_0;\ N + \tfrac{1}{2},\ M\right)$$

where N is the number of events since t_0 and M the miles since t_0. Unlike the CUSUM, this check needs a candidate change point; in practice it is used after an alarm, or from each release date.

4.13 Risk register

The register follows the ISO 31000 sequence. Hazards H1–H5 come from the companion analysis' event tree and crash-partner breakdown; H6–H8 are operational hazards without public data. For each data-based hazard with n crashes, of which k involved an injury, in 271.3 million miles:

$$\lambda_{\text{crash}} = \frac{n}{271.3}, \qquad P(\text{ injury} \mid \text{crash}) \sim \mathrm{Beta}\left(k + \tfrac{1}{2},\ n - k + \tfrac{1}{2}\right), \qquad \lambda_{\text{injury}} \sim \Gamma\left(k + \tfrac{1}{2},\ 271.3\right)$$

The hazard score is the posterior median injury-crash rate per 100 million miles with a 90% interval. Ranking probabilities are computed from 20,000 joint posterior draws. Each hazard is also given a treatment, a monitoring metric, an owner team and a status (monitor, reduce, accept and monitor, or data gap).

4.14 Simulated release history and automated report

To exercise the monitoring and reporting end to end, 104 weeks of counts are simulated for all five metrics (seed 2026), with releases every four weeks and a +50% regression in every metric from week 60. The same script then writes a one-page HTML release health report: a bottom line, monitoring status per metric (RED for an alarm, AMBER when the statistic is above half the threshold, GREEN otherwise), what field data can and cannot catch, the top data-based risks, the data gaps and recommended actions. An animation of the history (`scripts/make_monitoring_video.py`) shows the charts building week by week.

4.15 Software

The code is a small Python package (`src/avmon`): `rates.py` (inputs and labels), `power.py` (detectability and test plans), `monitor.py` (CUSUM, run lengths, calibration, Markov chain, Shewhart, Bayesian check). `scripts/run_all.py` produces the main results (about 30 s) and `scripts/supplementary.py` the supplementary studies (about 2 minutes). All random sampling uses fixed seeds.

5. The methods explained step by step

Section 4 states each method briefly, as a specialist would. This section explains the same methods from first principles, for a reader who has no background in statistics. For every method it gives the idea in plain words, the science behind it, a derivation of every equation in small steps, the meaning of every symbol, the assumptions and where they come from, and a worked example with the actual numbers of this study. Figures 5.1 to 5.10 illustrate the concepts and the examples.

Nothing in this section changes the analysis; it explains it. All numbers can be reproduced with `python scripts/explainer_figures.py`, which prints them and draws the figures.

5.1 How to read the equations

5.1.1 Notation

Table 5.1. Mathematical notation used in this report.

Notation	Read as	Meaning
$P(A)$	“probability of A”	A number between 0 (impossible) and 1 (certain): the long-run share of times A happens
$P(A \mid B)$	“probability of A given B”	Probability of A when we already know that B is true
$X \sim \text{Poisson}(m)$	“X follows a Poisson distribution with mean m”	X is a random count whose probabilities are given by Eq. (5.4)
$\mathrm{E}[X]$	“expected value of X”	The long-run average of X over many repetitions
$\mathrm{Var}(X)$, $\mathrm{SD}(X)$	“variance”, “standard deviation”	How much X scatters around its average; SD = √Var, in the same units as X
$\Sigma_{j=0}^{c}$	“sum over j from 0 to c”	Add up the expression for $j = 0, 1, \ldots, c$
$\ln(x)$, $\exp(x) = e^{x}$	“natural log”, “exponential”	Inverse functions: $\ln(e^{x}) = x$; $e \approx 2.718$. ln turns products into sums: $\ln(ab) = \ln a + \ln b$
$\lceil x \rceil$	“ceiling of x”	x rounded up to the next whole number
$\min\{n : \text{condition}\}$	“smallest n such that…”	The first whole number that meets the condition
$\max(0, y)$	“maximum of 0 and y”	y if y is positive, otherwise 0
$\approx$	“approximately equal”	Equal up to a small, stated approximation
z_{q}	“the q quantile of the standard normal”	The value below which a fraction q of a bell curve lies: $z_{0.95} = 1.645$, $z_{0.80} = 0.842$
$n!$ and (n choose j)	“n factorial”, “n choose j”	$n! = 1 \times 2 \times \ldots \times n$; ($n$ choose j) = $n! / [j!\,(n-j)!]$, the number of ways to pick j items from n

5.1.2 Symbols

Table 5.2. Symbols used in Sections 3, 4 and 5, with units and values for this study.

Symbol	Meaning	Units	Value(s) in this study
λ, λ_0, λ_1	Event rate; baseline rate; rate after a regression	events per million miles	Table 1 (0.023 to 100)
r	Size of a regression (relative increase in rate)	–	0.10, 0.25, 0.50, 1.00
M	Exposure: miles driven	million miles	varies
W	Fleet miles per week	million miles per week	2.92
N	Number of events counted in M miles	events	varies
X_t	Number of events in week t	events	varies
m_0, m_1	Expected weekly count before and after a regression ($m = \lambda W$)	events per week	0.067 to 292
α	False-alarm probability of a test	–	0.05
power	Probability that a test detects a real regression	–	0.80
c, $c(M)$	Critical count: alarm if $N \geq c$	events	e.g. 134
f	Share of the fleet running a release	–	0.05 to 1
p, p_0	Failure probability of a scenario type; its target	–	0.1% to 10%
C	Confidence level	–	0.90, 0.95, 0.99
n	Number of scenario runs	runs	e.g. 299
c (test plans)	Allowed number of failures in a plan	failures	0, 1, 2, 5
k	CUSUM reference value	events per week	Table 9
h	CUSUM alarm threshold	events	Table 9
S_t	CUSUM statistic after week t	events	≥ 0
ARL, ARL_0, ARL_1	Average run length (weeks to alarm); in control; after a shift	weeks	$ARL_0 = 260$
R	Transition matrix of the Markov chain among in-control states	–	Section 5.9
v	Coefficient of variation of the weekly rate (overdispersion)	–	0 to 0.20
β	Coupling: the indicator rises by β times the rise in serious injuries	–	0 to 1

Symbol	Meaning	Units	Value(s) in this study
k, n (register)	Injury crashes and crashes of a hazard	events	Table 15

5.2 Building blocks: rates, exposure and the Poisson distribution

5.2.1 Rate and exposure

A **rate** is a count divided by the amount of activity that produced it. For a driving fleet, the activity is distance, so rates are expressed per million miles:

$$\lambda = \frac{\text{number of events}}{\text{million miles driven}} \qquad (5.1)$$

Example. 1,934 crashed vehicles in 271.3 million miles give λ = 1,934 / 271.3 = 7.13 crashes per million miles. The **exposure** M is the number of miles over which events are counted. If the rate is λ, the **expected number of events** in M million miles is

$$\mu = \lambda M \qquad (5.2)$$

Weekly fleet exposure (Section 3.2). The fleet's weekly mileage is not published, so it is derived from published crash counts. If 542 crashes were reported in six months at a rate of 7.13 per million miles, the fleet must have driven 542 / 7.13 = 76.0 million miles in six months, or 12.67 million miles per month. A year has 12 months and 52 weeks, so

$$W = 12.67 \times \frac{12}{52} = 2.92 \text{ million miles per week} \qquad (5.3)$$

Expected weekly counts are then $m = \lambda W$: 7.13 × 2.92 = 20.8 crashes, 0.612 × 2.92 = 1.79 injury crashes, 0.023 × 2.92 = 0.067 serious-injury crashes, and so on.

5.2.2 Why counts follow the Poisson distribution

The science. Imagine one week of driving, 2.92 million miles, cut into one-mile pieces. In each mile, an injury crash either happens or not, with a tiny probability p = 0.612 / 1,000,000 = 6.12 × 10^{-7}. If miles are independent, the number of injury crashes in the week is the number of "successes" in n = 2,924,282 trials, a **binomial** count. When n is very large and p very small, with $np = m$ fixed, the binomial probabilities converge to a simpler formula, the **Poisson distribution** (Poisson, 1837):

$$P(X = x) = \frac{m^x e^{-m}}{x!}, \qquad x = 0, 1, 2, \ldots \qquad (5.4)$$

Derivation sketch. The binomial probability of x events is (n choose x) p^x $(1 - p)^{n-x}$. With $p = m/n$: (i) (n choose x) p^x = [$n(n-1)\ldots(n-x+1)/x!$] $(m/n)^x$, which tends to $m^x/x!$ as n grows, because each factor $(n - i)/n$ tends to 1; (ii) $(1 - m/n)^n$ tends to e^{-m}, a classic limit; (iii) $(1 - m/n)^{-x}$ tends to 1. Multiplying the three limits gives Eq. (5.4).

Check with the real numbers. For any-injury crashes in one week, the exact binomial gives $P(X = 0)$ = 0.1670168 and the Poisson formula gives 0.1670168: identical to seven digits.

Properties. A Poisson count has E[X] = m and Var(X) = m, so SD(X) = $\sqrt{m}$. Its only parameter is the mean. Two assumptions are built in: events occur **independently** of each other, and at a **constant rate** over the period. Section 5.12 relaxes the second.




Figure 5.1. Poisson distributions of weekly counts for three metrics. Rare outcomes are almost always zero in a week; frequent ones scatter around their mean with a standard deviation of √m.

Worked examples (Figure 5.1).

- **Serious injury or worse**, m = 0.067 per week: $P(0) = e^{-0.067} = 0.935$; $P(1) = 0.067 \times 0.935 = 0.063$; P(2 or more) = 1 − 0.935 − 0.063 = 0.0021. In 93.5% of weeks nothing is observed, whether or not a regression has happened. This single fact explains most of the results for severe outcomes.
- **Any-injury crashes**, m = 1.79: $P(0) = 0.167$, $P(1) = 0.299$, $P(2) = 0.267$, P(7 or more) = 0.0025.
- **All reported crashes**, m = 20.8: SD = $\sqrt{20.8} = 4.6$. Weeks with 15 or fewer crashes occur 12% of the time and weeks with 30 or more 3.5% of the time, with no change at all in the true rate. Week-to-week swings of ±5 crashes are noise, not signal.

5.2.3 The normal approximation

When m is larger than about 20, the Poisson distribution looks like a bell curve, the **normal distribution**, with the same mean m and standard deviation $\sqrt{m}$ (right panel of Figure 5.1). This is a consequence of the central limit theorem: a Poisson(m) count is the sum of many independent small counts, and sums of many independent pieces are approximately normal. The approximation lets us write simple formulas: a value z standard deviations above the mean is exceeded with a probability that depends only on z. For example, 5% of a normal distribution lies more than $z_{0.95}$ = 1.645 standard deviations above its mean, and 20% lies more than $z_{0.80}$ = 0.842 standard deviations below its mean.

5.3 Detectability: the exact Poisson test (Section 4.1)

5.3.1 The idea

After a release, we count the events N in M million miles. If the release is fine, N should be close to $\lambda_0 M$. If N is much larger, we suspect a regression. The question is: how large must N be before we raise an alarm, and how many miles do we need before a real regression is likely to push N above that level?

5.3.2 Two kinds of error

Any rule that decides from noisy data can be wrong in two ways:

- **False alarm** (type I error): the rule alarms although nothing changed. Its probability is α, set here to 5%.
- **Missed detection** (type II error): the rule stays silent although the rate really increased. The **power** of the rule is the probability of *not* missing it; we require 80%.

The values 5% and 80% are the conventions of applied statistics (Cohen, 1988); Section 4.1 uses them so that results can be compared with other studies.

5.3.3 The critical count

Under “no regression” (the **null hypothesis**), $N \sim \text{Poisson}(\lambda_0 M)$. The rule “alarm if $N \geq c$” has false-alarm probability $P(N \geq c \mid \lambda_0 M)$. We choose the smallest c that keeps this at or below α:

$$c(M) = \min\{n:\, P(N \geq n \mid \lambda_0 M) \leq \alpha\}, \qquad P(N \geq n \mid \mu) = 1 - \sum_{j=0}^{n-1} \frac{\mu^j e^{-\mu}}{j!} \qquad (5.5)$$

The test is called **exact** because it uses the Poisson probabilities themselves, not an approximation. Because counts are whole numbers, the actual false-alarm probability is usually a little below α.

5.3.4 Power

If the release has increased the rate to $\lambda_1 = (1 + r)\lambda_0$, then $N \sim \text{Poisson}(\lambda_1 M)$, and the chance that it reaches the critical count is

$$\text{power}(M) = P(N \geq c(M) \mid \lambda_1 M) \qquad (5.6)$$

More miles mean larger expected counts, and the two distributions (with and without regression) separate, because their means grow in proportion to M while their widths grow only with $\sqrt{M}$. That is why power increases with exposure. The search in Section 4.1 finds the smallest M after which power stays at or above 80%.




Figure 5.2. The exact test for a +25% regression in any-injury crashes at the reported exposure. Blue: counts expected with no regression; orange: counts expected after a +25% regression. The test alarms at 134 or more events. The dark blue tail is the false-alarm probability; the orange area to the right of the red line is the power.

5.3.5 Worked example (any-injury crashes, +25%)

1. Baseline rate $\lambda_0 = 0.612$ per million miles; regression $r = 0.25$, so $\lambda_1 = 0.765$.
2. The search gives $M = 188.5$ million miles, which at 2.92 million miles a week is 64.5 weeks.
3. Expected count with no regression: $\mu_0 = 0.612 \times 188.5 = 115.4$. Its standard deviation is $\sqrt{115.4} = 10.7$.
4. Critical count from Eq. (5.5): $c = 134$. The probability of 134 or more events when 115.4 are expected is 0.048, below 0.05; the probability of 133 or more is above 0.05.
5. Expected count after the regression: $\mu_1 = 0.765 \times 188.5 = 144.2$.
6. Power from Eq. (5.6): $P(N \geq 134 \mid 144.2) = 0.813$.

So after 64.5 weeks of whole-fleet driving, the test would catch a +25% regression in any-injury crashes four times out of five, and would raise a false alarm in fewer than one release in twenty. Figure 5.2 shows the two distributions.

5.3.6 Why detection always needs about 116 expected events

The results in Table 3 show that the number of *expected baseline events* needed, $\lambda_0 M$, is the same for every metric. The normal approximation shows why. Write $\mu_0 = \lambda_0 M$ for the expected baseline count.

1. With no regression, $N \approx \text{Normal}(\mu_0, \sqrt{\mu_0})$. A 5% false-alarm rule alarms when N exceeds $\mu_0 + z_{0.95}\sqrt{\mu_0}$.
2. After a regression, $N \approx \text{Normal}((1 + r)\mu_0, \sqrt{((1 + r)\mu_0)})$. For 80% power, the alarm level must lie $z_{0.80}$ standard deviations *below* this mean: $(1 + r)\mu_0 - z_{0.80}\sqrt{((1 + r)\mu_0)}$.
3. Set the two expressions equal:

$$\mu_0 + z_{0.95}\sqrt{\mu_0} = (1 + r)\,\mu_0 - z_{0.80}\sqrt{(1 + r)\,\mu_0}$$

4. Move the μ_0 terms to one side and divide by $\sqrt{\mu_0}$: $r\sqrt{\mu_0} = z_{0.95} + z_{0.80}\sqrt{(1 + r)}$.
5. Square both sides:

$$\mu_0 = \lambda_0 M = \frac{\left(z_{0.95} + z_{0.80}\sqrt{1+r} \right)^2}{r^2} \qquad (5.7)$$

The rate λ_0 does not appear on the right side, so the number of expected events needed depends only on the size of the regression and on the error rates. For $r = 0.25$: $(1.645 + 0.842 \times 1.118)^2 / 0.0625 = (2.586)^2 / 0.0625 = 107$. The exact Poisson test needs a few more, 116, because counts are discrete and the requirement that power *stays* above 80% is slightly stricter (Figure 5.3). For a serious-injury rate of 0.067 events per week, 116 events take 116 / 0.067 = 1,730 weeks, or 33 years.




Figure 5.3. Expected baseline events needed to detect a regression: the normal-approximation formula (line) and the exact test (points). The rule depends only on the size of the regression, not on the metric.

Assumptions. Events are Poisson (independent, constant rate within the period); the baseline rate is known (relaxed in Section 5.6); the regression is a step change at the release; the whole fleet runs the release (relaxed in Section 5.5).

5.4 Comparing two releases (Section 4.2)

When there is no long history, a new release is compared with the previous one, both observed for M million miles. Now both rates are uncertain.

The science: the log rate ratio. The natural measure of change is the ratio of the two estimated rates, $\hat{\lambda}_1/\hat{\lambda}_0$ (the hat means "estimated from data"). Its logarithm is better behaved: it is symmetric (a doubling and a halving are +0.69 and −0.69) and close to normally distributed. Its variance follows from the **delta method**, a first-order approximation: for a count N with mean μ, $\mathrm{Var}(\ln N) \approx \mathrm{Var}(N)/\mu^2 = \mu/\mu^2 = 1/\mu$. The two counts are independent, so their variances add:

$$\mathrm{Var}\left[\ln \frac{\widehat{\lambda}_1}{\widehat{\lambda}_0} \right] \approx \frac{1}{\lambda_0 M} + \frac{1}{\lambda_1 M} \qquad (5.8)$$

Sample size. The true log ratio is $\ln(1 + r)$. It must be at least $(z_{0.95} + z_{0.80})$ standard deviations away from zero to be detected with 5% false alarms and 80% power, the same reasoning as in Section 5.3.6:

$$\ln\,(\,1+r\,)\;=\;(\,z_{0.95}+z_{0.80}\,)\sqrt{\frac{1}{M}\left(\frac{1}{\lambda_0}+\frac{1}{\lambda_1}\right)}\;\Rightarrow\;M=\frac{(\,z_{0.95}+z_{0.80}\,)^{\,2}\left(\frac{1}{\lambda_0}+\frac{1}{\lambda_1}\right)}{[\,\ln\,(\,1+r\,)\,]^{\,2}}\qquad(\,5.9\,)$$

Worked example (any-injury crashes, +25%). $z_{0.95} + z_{0.80}$ = 2.486, squared 6.183. 1/0.612 + 1/0.765 = 1.634 + 1.307 = 2.941. $[\ln 1.25]^2 = 0.2231^2 = 0.0498$. M = 6.183 × 2.941 / 0.0498 = **365 million miles per release**, almost twice the 189 million miles needed against a known baseline. The factor of about two arises because the old release's rate is now uncertain too, which roughly doubles the variance.

5.5 Staged rollout (Section 4.3)

If a release runs on a fraction f of the fleet, it accumulates $f \times W$ million miles per week. The exposure M needed does not change, because the statistics depend only on the miles driven by the release, so the calendar time grows by $1/f$:

$$T_f=\frac{M}{fW}\qquad(\,5.10\,)$$

Worked example. Any-injury crashes, +25%, on 10% of the fleet: 188.5 / (0.10 × 2.92) = **645 weeks**, ten times the 64.5 weeks for the whole fleet. A canary release therefore limits how many people are exposed while a problem is found by other means; it is not a fast statistical test of crash outcomes.

5.6 Uncertainty in the baseline: Bayesian estimation (Section 4.4)

5.6.1 Bayes' theorem

The baseline rate of a rare outcome is itself uncertain: six serious-injury crashes do not pin down the rate. **Bayesian statistics** describes what we know about an unknown quantity as a probability distribution, and updates it with data using **Bayes' theorem** (Bayes, 1763):

$$\underbrace{p\,(\,\lambda\mid\text{data}\,)}_{\text{posterior}}\;\propto\;\underbrace{P(\,\text{data}\mid\lambda\,)}_{\text{likelihood}}\times\underbrace{p\,(\,\lambda\,)}_{\text{prior}}\qquad(\,5.11\,)$$

In words: what we believe after seeing the data (posterior) is proportional to how well each value of λ explains the data (likelihood) times what we believed before (prior). The symbol ∝ means "proportional to": the right side is rescaled so that the total probability is 1.

5.6.2 The Jeffreys prior

With little prior knowledge, PRA practice uses the **Jeffreys prior** (Jeffreys, 1946; Atwood et al., 2003), which is built from the data model itself so that the answer does not depend on how the parameter is written (for example a rate or its inverse, a mean time between events). It is proportional to the square root of the **Fisher information**, which measures how much one observation tells us about the parameter. For a Poisson count with mean λM, the Fisher information about λ is M/λ, so

$$p\,(\,\lambda\,)\;\propto\sqrt{M/\lambda}\;\propto\;\lambda^{-1/2}\qquad(\,5.12\,)$$

5.6.3 The posterior is a gamma distribution

The likelihood of k events in M million miles is the Poisson probability $(\lambda M)^k\, e^{-\lambda M} / k!$. Multiplying by the prior and dropping factors that do not involve λ:

$$p(\lambda \mid k, M) \;\propto\; \lambda^{k} e^{-\lambda M} \times \lambda^{-1/2} = \lambda^{\left(k+\frac{1}{2}\right)-1} e^{-\lambda M} \qquad (5.13)$$

This is the shape of a **gamma distribution** with shape k + ½ and rate M, written Gamma(k + ½, M). Its mean is (k + ½)/M. Because the prior and posterior belong to the same family, this pair is called **conjugate**, which is why the gamma distribution appears throughout PRA rate estimation.

5.6.4 Worked example (serious injury, 6 events in 271.3 million miles)

1. Posterior: Gamma(6.5, 271.3).
2. Mean: 6.5 / 271.3 = 0.0240 per million miles. Median: 0.0227 (the value used in Table 1, rounded to 0.023). The simple estimate 6 / 271.3 = 0.0221 lies close by.
3. 5th and 95th percentiles: 0.0109 and 0.0412. The rate is known only to within a factor of about four.
4. Each of these values is put into the detectability calculation of Section 5.3. A lower rate means fewer events per week and therefore a longer time to collect the ~116 events: 70 years at the 5th percentile, 34 years at the median and 18 years at the 95th percentile (Table 6).




Figure 5.4. Bayesian updating of the serious-injury rate. Left: the Jeffreys prior, the likelihood of 6 events in 271.3 million miles, and the resulting posterior (scaled to the same height). Right: the posterior with its 5th, 50th and 95th percentiles.

Interpretation. A Bayesian 90% interval states directly that, given the data and the prior, the rate lies between 0.0109 and 0.0412 with 90% probability. A frequentist confidence interval answers a different question (how often the interval-making procedure covers the true value in repeated experiments), but with the Jeffreys prior the two kinds of interval are numerically close.

5.7 Test coverage: how many scenario runs (Section 4.5)

5.7.1 Zero-failure plans and the rule of three

Suppose a scenario type (for example “pedestrian steps out from behind a parked van”) is run n times in simulation, each run an independent draw of the scenario’s details, and the release

passes only if all n runs pass. If the true failure probability per run is p, the probability that all runs pass is $(1 - p)$ multiplied by itself n times, because independent events multiply:

$$P(\text{ all } n \text{ pass} \mid p) = (1-p)^{n} \qquad (5.14)$$

The demonstration logic. We want to show that $p < p_0$ with confidence C. We require that a scenario type that is *just bad enough* ($p = p_0$) would pass all n runs with probability at most $1 - C$. Then passing is unlikely to happen by luck if the scenario type were that bad:

$$\left(1-p_0\right)^{n} \le 1-C$$

Take logarithms of both sides (ln is increasing, so the inequality keeps its direction), $n \ln(1 - p_0) \le \ln(1 - C)$. Dividing by $\ln(1 - p_0)$, which is negative, reverses the inequality:

$$n \ge \frac{\ln\,(1-C)}{\ln\left(1-p_0\right)} \;\Rightarrow\; n = \left\lceil \frac{\ln\,(1-C)}{\ln\left(1-p_0\right)} \right\rceil \qquad (5.15)$$

The rule of three. For small p_0, $\ln(1 - p_0) \approx -p_0$ (first term of the Taylor series), and for $C = 0.95$, $\ln(0.05) = -3.00$. So $n \approx 3/p_0$ (Hanley and Lippman-Hand, 1983).

Worked example (1% target, 95% confidence). $\ln(0.05) = -2.9957$; $\ln(0.99) = -0.01005$; ratio 298.07; rounded up, **n = 299**. Check: $0.99^{299} = 0.0495 \le 0.05$, while $0.99^{298} = 0.0500$ is not. The rule of three gives 300.

5.7.2 The operating characteristic and the cost of harsh plans

The plan's **operating characteristic** (OC) is the probability that a release passes, as a function of the true p (Figure 5). For the 299-run zero-failure plan:

- a scenario type with $p = 0.1\%$, ten times better than the target, passes with probability $0.999^{299} = 0.741$, so a good release is held 26% of the time;
- with $p = 0.3\%$, it passes with probability $0.997^{299} = 0.407$ and is held 59% of the time.

5.7.3 Plans that allow failures

A plan (n, c) passes if at most c of the n runs fail. The number of failures in n independent runs is binomial: the probability of exactly j failures is (n choose j) $p^j(1 - p)^{n-j}$, where (n choose j) counts the ways to choose which j runs failed. The demonstration condition becomes

$$P\left(\text{ at most } c \text{ failures} \mid p_0\right) = \sum_{j=0}^{c} \binom{n}{j} p_0^{j} \left(1-p_0\right)^{n-j} \le 1-C \qquad (5.16)$$

Worked example (c = 1, 1%, 95%). The smallest n that satisfies Eq. (5.16) is **473**: with $n = 473$ the left side is 0.0498. The plan costs 1.6 times as many runs as the zero-failure plan but does not fail a release over one unlucky run.

5.7.4 The Bayesian zero-failure plan

The Bayesian version puts the Jeffreys prior on p. For a pass/fail trial the Fisher information is $1/[p(1 - p)]$, so the Jeffreys prior is $\propto p^{-½}(1 - p)^{-½}$, a **beta distribution** Beta(½, ½). After n

runs with zero failures, the likelihood is $(1-p)^n$, and the posterior is

$$p\,(\,p \mid 0 \text{ failures in } n\,) \;\propto p^{-1/2}\,(\,1-p\,)^{\,n-1/2} \;\Rightarrow\; \text{Beta}\left(\tfrac{1}{2},\, n+\tfrac{1}{2}\right) \qquad (\,5.17\,)$$

We require $P(p < p_0 \mid \text{data}) \geq C$. *Worked example:* for 1% at 95%, the smallest such n is **191** (posterior probability 0.9501). The saving relative to 299 runs comes from the prior, which already places much of its weight on small values of p; it is only as good as that prior (Figure 5.5, right).




Figure 5.5. Sizing a test plan. Left: probability that a scenario type passes all n runs, for three true failure probabilities; a 1% scenario type passes 299 runs less than 5% of the time. Right: the Bayesian posterior for the failure probability after 191 failure-free runs; 95% of it lies below 1%.

Assumptions. Runs are independent and identically distributed draws from the scenario type, the simulator's pass/fail verdict is correct, and the failure probability does not change between runs. Correlated runs (for example small variations of one logged event) carry less information, so the real number needed is larger (Section 9).

5.8 The Poisson CUSUM (Section 4.6)

5.8.1 The idea in plain words

A fixed-sample test (Section 5.3) waits until a set number of miles have been driven and then decides once. A **CUSUM** decides every week. It keeps a running score S: each week it adds the week's count minus an allowance k. If the count is below the allowance, the score goes down (but never below zero); if above, the score goes up. When the score reaches the threshold h, the chart alarms. A useful picture is a bucket with a hole: events pour in, k drains out each week, and the alarm sounds when the bucket overflows.

5.8.2 Where the reference value *k* comes from

The science: the likelihood ratio. Each week's count X is evidence for one of two hypotheses: in control (mean m_0) or shifted (mean m_1). The strength of that evidence is the ratio of the two Poisson probabilities. By Eq. (5.4),

$$\frac{P\,(\,X = x \mid m_1\,)}{P\,(\,X = x \mid m_0\,)} = \frac{m_1^x e^{-m_1}/x!}{m_0^x e^{-m_0}/x!} = \left(\frac{m_1}{m_0}\right)^x e^{-\,(\,m_1 - m_0\,)}$$

Its logarithm, the **log-likelihood ratio**, is

$$\ell\ (\ x\ ) = x \ln \frac{m_1}{m_0} - (\ m_1 - m_0\ ) \qquad (\ 5.18\ )$$

It is positive when x favors the shift and negative when it favors no shift. Evidence from independent weeks adds up, because the log of a product is a sum. Page (1954) showed that the right way to accumulate it, when the shift may start at any time, is to restart at zero whenever the sum becomes negative: $S'_t = \max(0, S'_{t-1} + \ell(X_t))$. Dividing everything by $\ln(m_1/m_0)$, which is positive, does not change when the chart alarms, and gives the familiar form:

$$S_t = \max(0,\ S_{t-1} + X_t - k), \qquad k = \frac{m_1 - m_0}{\ln\ (\ m_1/m_0\ )} \qquad (\ 5.19\ )$$

The reference value k is the count at which a week is neutral evidence ($\ell = 0$). It always lies between m_0 and m_1 (it is their *logarithmic mean*). So, on average, S drifts down by $m_0 - k$ per week when nothing has changed and up by $m_1 - k$ after a shift of the designed size. This optimal form, with k tuned to the shift that matters, is the result of Lucas (1985), and the optimality proofs of Lorden (1971) and Moustakides (1986) apply to it.

5.8.3 Choosing the threshold *h*

A lower h detects sooner but false-alarms more often. h is chosen so that the **in-control average run length** ARL_0, the average number of weeks between false alarms when nothing has changed, is 260 weeks (five years). There is no simple formula for the ARL of a discrete chart, so it is computed: the program guesses h, simulates 1,500 in-control histories, measures their average run length, and halves the interval of possible h values (bisection) until the target is met. Section 5.9 gives an independent, exact check.

5.8.4 Worked example (all reported crashes)

1. $m_0 = 20.85$ crashes per week; the chart is tuned to +25%, so $m_1 = 1.25 \times 20.85 = 26.06$.
2. $k = (26.06 - 20.85) / \ln(1.25) = 5.21 / 0.2231 =$ **23.36**.
3. Average drift of S: in control, $20.85 - 23.36 = -2.5$ per week (the bucket drains); after a +25% shift, +2.7; after +50% ($m = 31.3$), +7.9 per week.
4. Threshold from the calibration: $h = 16.93$.
5. In the simulated history (Figure 5.6), weeks 55 to 60 had 23, 20, 17, 19, 22 and 23 crashes. All are below 23.36, so S stayed at 0. The +50% regression started in week 60. Week 61 had 46 crashes: $S = \max(0, 0 + 46 - 23.36) = 22.64 \geq 16.93$, so the chart alarmed and restarted at zero.
6. A rough estimate of the delay after a +50% shift is h/drift = 16.93 / 7.9 ≈ 2.1 weeks; the exact average from Section 5.9 is 2.8 weeks, slightly longer because S also has to climb back from noise.




Figure 5.6. How the CUSUM works on the simulated history of all reported crashes. Top: weekly counts and the reference value k. Bottom: the CUSUM statistic, the threshold h, and the alarms (triangles); after each alarm the statistic restarts at zero.

Rare outcomes. For serious injuries, $k = 0.075$ and $h = 3.34$. Each event adds about 0.93 ($1 - 0.075$) and each quiet week subtracts 0.075. Ignoring the floor at zero, the chart alarms when n events arrive within t weeks such that $n - 0.075t \geq 3.34$: four events within 8.8 weeks, five within 22 weeks, or six within 35 weeks. With 0.067 events expected per week, four events in nine weeks almost never happen by chance, which is why the false-alarm interval is five years, and why detection after a real +50% shift still takes a median of 70 weeks.

Assumptions. Weekly counts are independent Poisson with a known in-control mean; the shift is a step; the chart restarts after each alarm, as it would after an investigation.

5.9 Verifying run lengths with a Markov chain (Section 4.7)

5.9.1 The idea

Next week's CUSUM value depends only on this week's value and next week's count, not on the earlier history. A process with this property is a **Markov chain** (Markov, 1906). If the possible values of S are listed as **states**, the chart is a walk between states with known transition probabilities, and the average time to reach the alarm state can be computed exactly, without simulation (Brook and Evans, 1972).

5.9.2 Derivation: first-step analysis

Let L_i be the expected number of weeks until an alarm, starting from state i. One week certainly passes; then the chart moves to state j with probability R_{ij}, after which it needs L_j more weeks on average (moves to the alarm state need no more weeks). Hence

$$L_i = 1 + \sum_j R_{ij} L_j \qquad (5.20)$$

for every in-control state i. In matrix form, $\mathbf{L} = \mathbf{1} + \mathbf{R}\,\mathbf{L}$, so $(\mathbf{I} - \mathbf{R})\,\mathbf{L} = \mathbf{1}$, and

$$\mathbf{L} = (\mathbf{I} - \mathbf{R})^{-1}\mathbf{1} \qquad (5.21)$$

where $\mathbf{I}$ is the identity matrix and $\mathbf{1}$ a column of ones. The ARL from a fresh start is the element for $S = 0$.

5.9.3 Worked toy example

To make the method visible, take a tiny chart: weekly counts $X \sim$ Poisson(0.5), $k = 1$ and $h = 3$, so S can only be 0, 1 or 2 before an alarm (Figure 5.7). The Poisson probabilities are $P(0) = 0.6065$, $P(1) = 0.3033$, $P(2) = 0.0758$, $P(3) = 0.0126$, $P(4 \text{ or more}) = 0.0018$.

- From $S = 0$, the new value is $\max(0, 0 + X - 1)$: it stays 0 if $X = 0$ or 1 (0.9098), moves to 1 if $X = 2$ (0.0758), to 2 if $X = 3$ (0.0126), and alarms if $X \geq 4$ (0.0018).
- From $S = 1$: to 0 if $X = 0$ (0.6065), stays 1 if $X = 1$ (0.3033), to 2 if $X = 2$ (0.0758), alarm if $X \geq 3$ (0.0144).
- From $S = 2$: to 1 if $X = 0$ (0.6065), stays 2 if $X = 1$ (0.3033), alarm if $X \geq 2$ (0.0902).

Eq. (5.20) gives three linear equations:

$$\begin{aligned} L_0 &= 1 + 0.9098\,L_0 + 0.0758\,L_1 + 0.0126\,L_2 \\ L_1 &= 1 + 0.6065\,L_0 + 0.3033\,L_1 + 0.0758\,L_2 \\ L_2 &= 1 + 0.6065\,L_1 + 0.3033\,L_2 \end{aligned}$$

Solving them (by substitution or with a computer) gives L_0 = **174.2**, L_1 = 169.3 and L_2 = 148.8 weeks. A simulation of 200,000 run lengths of the same chart gives 174.0 weeks, which confirms the calculation.




Figure 5.7. A toy CUSUM drawn as a Markov chain. Circles are values of the statistic; arrows are weekly transitions with their probabilities; red arrows lead to an alarm.

5.9.4 The real charts

For the real charts, k and h are not whole numbers, so the statistic is placed on a fine grid (steps of $1/g$, with g between 100 and 1,200), giving up to 5,000 states. The same Eq. (5.21) is solved numerically. Table 19 shows that the Markov chain and the simulation agree within 2.2% for all 25 comparisons, which is within the simulation's own random error. Two independent methods giving the same answer is strong evidence that both are implemented correctly.

5.10 The Shewhart chart (Section 4.8)

A **Shewhart chart** (Shewhart, 1931) looks only at the current week: it alarms if one week's count reaches a limit c. Each week is an independent chance to alarm, with probability $q = P(X \geq c)$. The number of weeks to the first alarm then follows a **geometric distribution**, whose mean is

$$\mathrm{ARL} = \frac{1}{q} = \frac{1}{P(\,X \geq c \mid m\,)} \qquad (\,5.22\,)$$

Derivation. The alarm happens in week t if the first $t-1$ weeks are quiet and week t is not: probability $(1-q)^{t-1}\,q$. The mean of this distribution is $\Sigma\, t(1-q)^{t-1}\,q = 1/q$. Intuitively, an event with a 1-in-260 chance per week happens on average once every 260 weeks.

Worked example (serious injury). With $m_0 = 0.067$, $P(X \geq 1) = 0.065$ is far above $1/260 = 0.0038$, so the limit must be $c = 2$: $P(X \geq 2) = 1 - e^{-0.067}(1 + 0.067) = 0.00215$, giving $\mathrm{ARL}_0 = 466$ weeks. After a +50% shift ($m = 0.1005$), $P(X \geq 2) = 0.0047$ and the ARL is 212 weeks, against 91 weeks for the CUSUM (Table 10). *Any-injury crashes*: $P(X \geq 6 \mid 1.79) = 0.0101$ is too high, $P(X \geq 7) = 0.0025$ meets the target, so $c = 7$ and $\mathrm{ARL}_0 = 402$ weeks. Because counts jump in whole numbers, the Shewhart chart cannot be tuned exactly to 260 weeks; the CUSUM can, because h is continuous.

5.11 False alarms across many charts (Section 4.9)

Derivation. If a chart alarms falsely with a small probability of about $1/\mathrm{ARL}_0$ in each week, the probability that it stays quiet for T weeks is $(1 - 1/\mathrm{ARL}_0)^T$. Using $\ln(1-x) \approx -x$ for small x, this is approximately $\exp(-T/\mathrm{ARL}_0)$. For m independent charts, all must stay quiet, so their probabilities multiply: $\exp(-mT/\mathrm{ARL}_0)$. The probability of at least one false alarm is the complement:

$$P(\,\text{at least one false alarm in } T \text{ weeks}\,) \approx 1 - \exp\left(-\frac{mT}{\mathrm{ARL}_0}\right) \qquad (\,5.23\,)$$

Worked example. One chart, two years ($T = 104$), $\mathrm{ARL}_0 = 260$: $1 - \exp(-0.4) = \mathbf{0.33}$. Five charts: $1 - \exp(-2) = \mathbf{0.86}$. Twenty charts with $\mathrm{ARL}_0 = 520$ weeks: $1 - \exp(-4) = \mathbf{0.98}$. The direct simulation reported in Section 6.8 gives 85% for five charts, confirming the approximation. *The lesson:* in a real program with dozens of charts, a false alarm somewhere is practically certain every few months, so a cheap triage step is part of the design, not an afterthought.

5.12 Overdispersion (Section 4.10)

The idea. The Poisson model assumes a constant rate. In reality the weekly rate moves with weather, city mix, holidays and demand. When the rate itself varies, counts scatter more than

Poisson: this is **overdispersion**.

Derivation: the law of total variance. Let the true weekly rate Λ vary from week to week with mean m_0 and standard deviation $v\,m_0$ (so v is its coefficient of variation). Given Λ, the count is Poisson(Λ), with mean and variance both equal to Λ. The law of total variance splits the total variance into the average within-week variance plus the variance of the weekly means:

$$\mathrm{Var}\,(X) = \mathbb{E}[\,\mathrm{Var}\,(X \mid \Lambda)\,] + \mathrm{Var}\,(\mathbb{E}[X \mid \Lambda]\,) = \mathbb{E}[\Lambda] + \mathrm{Var}\,(\Lambda) = m_0 + v^2 m_0^2 \qquad (5.24)$$

When Λ follows a gamma distribution, X follows the **negative binomial** distribution, the standard model for overdispersed counts.

Why frequent metrics suffer most. The Poisson part grows like m_0 and the extra part like m_0^2. Their ratio, $1 + v^2 m_0$, is close to 1 for rare metrics and large for frequent ones (Figure 5.8):

- Leading indicator, $m_0 = 292$, $v = 10\%$: variance $292 + 0.01 \times 292^2 = 1{,}148$, four times the Poisson value; standard deviation 34 instead of 17.
- All reported crashes, $m_0 = 20.8$: variance 25.2 instead of 20.8, 21% more.
- Any-injury crashes: 2% more. Serious injury: 0.07% more.

A chart whose threshold was set for SD 17 sees routine swings of 34 and false-alarms constantly: every 11 weeks instead of every 260 (Table 12). Recalibrating h on the wider distribution (by the same bisection, but simulating negative binomial counts) restores the false-alarm interval.




Figure 5.8. Weekly counts with and without 10% week-to-week variation in the rate. The frequent leading indicator (left) becomes twice as wide; all reported crashes (right) are barely affected.

5.13 Leading indicators must move with the outcome (Section 4.11)

The idea. A leading indicator, such as hard-braking events, is useful only if a release that increases serious injuries also increases the indicator. β measures that coupling: if serious injuries rise by 50%, the indicator rises by 50β%.

The science, through the drift of the chart. The leading-indicator chart has $m_0 = 292.4$ and $k = 327.6$ (tuned for +25%). The average weekly change of its statistic is $m - k$ (Section 5.8.2). With no rise it is $292.4 - 327.6 = -35.2$ events per week: the statistic stays pinned at zero. The drift becomes positive only when the indicator's mean exceeds k, that is, when it rises by more than $k/m_0 - 1 = 12.0\%$ (Figure 5.9):

- a 2.5% rise (β = 0.05): drift −27.9 per week; the chart alarms only when random noise (SD 17 per week) happens to push it up, so the median time is 56 weeks;
- a 12.5% rise (β = 0.25): drift +1.4 per week; median 2 weeks;
- a 25% rise (β = 0.5): drift +37.9; it alarms within a week.

So the value of a leading indicator depends on β, which must be established from data (for example from the events that precede injury crashes), not assumed.




Figure 5.9. Expected weekly change of the leading-indicator CUSUM against how much the indicator rises when serious injuries rise 50%. Below about 12% the statistic drifts down and alarms only by chance.

5.14 The Bayesian sequential check (Section 4.12)

After an alarm, or from a release date t_0, the question "how sure are we that the rate really rose?" is answered with the posterior of Section 5.6. With N events in M million miles since t_0 and the Jeffreys prior, the posterior of the new rate is Gamma(N + ½, M), and

$$P(\lambda > \lambda_0 \mid N, M) = 1 - F_\Gamma\left(\lambda_0;\ N + \tfrac{1}{2},\ M\right) \qquad (5.25)$$

where F_Γ is the gamma cumulative distribution function, the probability that a gamma-distributed quantity is below a given value.

Worked example (serious injury in the simulated history). From week 60 to week 104 (45 weeks), the fleet drove $M = 45 \times 2.92 = 131.6$ million miles and recorded $N = 7$ serious-injury crashes, against $0.023 \times 131.6 = 3.0$ expected at the baseline rate. The posterior is Gamma(7.5, 131.6), with median 0.054 per million miles, and the probability that the rate exceeds 0.023 is **0.979**. Unlike the CUSUM, this calculation needs a candidate start date; its value is to state the strength of the evidence in a form a decision maker can use directly.

5.15 The risk register (Section 4.13)

Each data-based hazard h has n crashes, k of them with an injury, in 271.3 million miles. Three quantities are estimated:

1. **Crash rate**: n / 271.3 per million miles (Eq. 5.1).
2. **Severity**, the probability that a crash of this type causes an injury. With the Jeffreys prior Beta(½, ½) and k injuries in n crashes, the binomial likelihood $p^k(1-p)^{n-k}$ gives the

posterior Beta(k + ½, n − k + ½), by the same steps as Eq. (5.17).

3. **Injury-crash rate**, the score used for ranking: Gamma(k + ½, 271.3), by Eq. (5.13).

Worked example (H3, crashes with cyclists, pedestrians or scooter riders). n = 31 crashes, k = 15 with an injury. Crash rate 31 / 271.3 = 0.114 per million miles. Severity: Beta(15.5, 16.5), median 48.4%. Injury-crash rate: Gamma(15.5, 271.3), median 5.59 per 100 million miles, 90% interval 3.55–8.29. H3 is ranked third by rate, but its severity is six times that of H1 (8.1%), which is why its treatment is “reduce”.

Ranking probabilities. To ask “how sure are we that H1 is the largest risk?”, 20,000 values are drawn at random from each hazard’s posterior, the hazards are ranked in each draw, and the share of draws in which each hazard is first is counted. This **Monte Carlo** method turns the uncertainty in each score into an uncertainty in the ranking. H1 (median 35.4) exceeds H2 (median 25.9) in about 98% of draws (Figure 5.10, Table 16).




Figure 5.10. Uncertainty in the risk register. Left: 20,000 posterior draws of the injury-crash rates of H1 and H2; they overlap only slightly. Right: posterior severity of three hazards; with fewer crashes, the distribution is wider.

5.16 Summary of the methods, their assumptions and sources

Table 5.3. Every method, the question it answers, its key equation, its main assumptions and its source.

Method	Question	Key equation	Main assumptions	Source
Poisson model	How do counts vary by chance?	(5.4)	Independent events, constant rate	Poisson (1837)
Exact test and power	How many miles to detect a regression?	(5.5)–(5.7)	Known baseline; step change	Standard exact test; Cohen (1988) for α and power conventions
Two-sample comparison	Same, with no known baseline	(5.9)	Normal approximation on log ratio	Delta method
Staged rollout	How long on part of the fleet?	(5.10)	Same miles needed	Derived
Bayesian baseline	How uncertain is a rare rate?	(5.11)–(5.13)	Jeffreys prior	Jeffreys (1946); Atwood et al. (2003)
Zero-failure and c-failure plans	How many scenario runs?	(5.15)–(5.16)	Independent, identical runs	Hanley and Lippman-Hand (1983); Clopper and Pearson (1934); IEC 61123
Bayesian plan	Same, with a prior	(5.17)	Jeffreys prior	Atwood et al. (2003)
Poisson CUSUM	How to monitor weekly?	(5.18)–(5.19)	Poisson counts; known m_0; step shift	Page (1954); Lucas (1985); ISO 7870-4
Markov chain	What is the exact run length?	(5.20)–(5.21)	Grid approximation of k and h	Brook and Evans (1972)
Shewhart chart	Simpler alternative	(5.22)	Independent weeks	Shewhart (1931); ISO 7870-2
Family-wise false alarms	How many false alarms overall?	(5.23)	Independent charts; geometric run lengths	Derived
Overdispersion	What if the rate varies?	(5.24)	Gamma-distributed weekly rate	Law of total variance
Leading-indicator coupling	When does an indicator help?	$m - k$ drift	Proportional coupling β	Derived
Bayesian check	How sure is a detected increase?	(5.25)	Jeffreys prior; known start	Jeffreys (1946)
Risk register	Which hazards matter most?	Beta and gamma posteriors	Independent hazards	Atwood et al. (2003); ISO 31000

6. Results

6.1 How long field data needs to catch a regression




Figure 2. Weeks of whole-fleet driving needed to detect a regression with 80% power and a 5% false-alarm rate, by metric and regression size (log scale).

Table 2. Weeks of whole-fleet driving to detect a regression (exact Poisson test, known baseline, 80% power, 5% false alarm). Million miles in brackets.

Metric	+10%	+25%	+50%	+100%
Leading indicator (assumed)	2.3 (6.6)	0.4 (1.2)	0.1 (0.3)	<0.1 (0.1)
All reported crashes	31.9 (93)	5.5 (16)	1.6 (4.6)	0.5 (1.4)
Any-injury crashes	371 (1,085)	64.5 (189)	18.5 (54)	5.7 (17)
Airbag deployment	846 (2,475)	150 (440)	42.6 (125)	13.1 (38)
Serious injury or worse	9,859 (28,831)	1,728 (5,054)	492 (1,437)	152 (444)

A rule of thumb. Multiplying each exposure by its rate gives the expected number of baseline events needed, which is the same for every metric:

Table 3. Expected baseline events needed to detect a regression (80% power, 5% false alarm).

Regression	+10%	+25%	+50%	+100%
Expected baseline events	664	116	33	10

So the question “how long until we would know?” reduces to “how long until we expect about 116 events?”. For serious injuries, at 0.067 per week, that is 33 years.




Figure 3. Power of the exact test. Left: power grows with exposure. Right: for any-injury crashes, power and the actual false-alarm rate move in a saw-tooth because counts are discrete; the actual false-alarm rate always stays below 5%.

6.2 Staged rollout and release-versus-release comparison

Table 4. Weeks to detect a +25% regression when the release runs on part of the fleet.

Metric	5%	10%	25%	50%	100%
Leading indicator (assumed)	7.9	4.0	1.6	0.8	0.4
All reported crashes	111	55	22	11	5.5
Any-injury crashes	1,289	645	258	129	64.5
Airbag deployment	3,009	1,505	602	301	150
Serious injury or worse	34,569	17,285	6,914	3,457	1,728




Figure 4. Staged rollout: weeks to detect a +25% regression against the share of the fleet running the release.

A 10% canary release protects against regressions in a frequent leading indicator within a month, but needs about a year for all reported crashes. A staged rollout is therefore valuable

mainly for limiting exposure while a regression is found by other means, not as a statistical test of crash outcomes.

Comparing two releases with no known baseline roughly doubles the exposure (Table 5). For example, a +25% regression in any-injury crashes needs 365 million miles per release (125 weeks) instead of 189 million.

Table 5. Million miles per release to detect a regression when comparing two releases (normal approximation on the log rate ratio), with weeks in brackets.

Metric	+10%	+25%	+50%	+100%
All reported crashes	182 (62)	31 (11)	8.8 (3.0)	2.7 (0.9)
Any-injury crashes	2,123 (726)	365 (125)	102 (35)	32 (11)
Airbag deployment	4,885 (1,670)	840 (287)	236 (81)	73 (25)
Serious injury or worse	56,492 (19,318)	9,717 (3,323)	2,725 (932)	839 (287)

6.3 Uncertainty in the baseline rate

Table 6. Weeks to detect +25% at the 5th, 50th and 95th posterior percentiles of the baseline rate.

Metric	Events	5th percentile rate	Median	95th percentile rate
Any-injury crashes	166	73 weeks	65 weeks	56 weeks
Airbag deployment	72	183	150	123
Serious injury or worse	6	3,629 (70 years)	1,761 (34 years)	950 (18 years)

Even at the most favorable end of its uncertainty, the serious-injury rate needs 18 years of whole-fleet driving to reveal a +25% regression. The conclusion does not depend on the exact baseline.

6.4 How much testing replaces the missing field evidence

Table 7. Failure-free scenario runs needed to show a failure probability below a target.

Target failure probability	90% confidence	95% confidence	99% confidence
10%	22	29	44
1%	230	299	459
0.1%	2,302	2,995	4,603
0.01%	23,025	29,956	46,050

Table 8. Runs needed at 95% confidence when the plan allows some failures, and with a Bayesian (Jeffreys) zero-failure plan.

Target	0 failures	≤ 1 failure	≤ 2 failures	≤ 5 failures	Bayesian, 0 failures
1%	299	473	628	1,049	191
0.1%	2,995	4,742	6,294	10,511	1,920




Figure 5. Operating characteristic of three test plans for a 1% target at 95% confidence. Plans that tolerate a failure need more runs but pass good releases more often.

The zero-failure plan is the cheapest, but it is harsh on good releases: a scenario type whose true failure probability is 0.1%, ten times better than the target, still fails the 299-run plan 26% of the time; at 0.3% it fails 59% of the time. Plans that allow one or two failures cost 1.6–2.1 times more runs but rarely hold a good release. The Bayesian plan needs about a third fewer runs because the Jeffreys prior already places much of its weight on small failure probabilities; that saving is only as good as the prior, and it should be justified for each scenario type.

These numbers are practical only in simulation. The credibility of the simulation, which the companion project av-counterfactual-uq quantifies for one model class, therefore becomes part of the release evidence.

6.5 Sequential monitoring: design and performance

Table 9. Poisson CUSUM design per metric (weekly counts; tuned for +25%; target ARL_0 260 weeks). Median weeks to the first alarm after a regression starts (simulation).

Metric	Expected weekly count	k	h	ARL_0 (weeks)	+25%	+50%	+100%
All reported crashes	20.8	23.35	16.93	259	6	3	1
Any-injury crashes	1.79	2.005	10.91	271	30	14	7
Airbag deployment	0.778	0.871	8.47	260	45	24	12
Serious injury or worse	0.067	0.075	3.34	256	105	70	43
Leading indicator (assumed)	292	327.6	11.38	233	1	1	1




Figure 6. Average weeks to alarm against regression size: Markov chain (lines) and simulation (crosses).

The CUSUM detects a +25% regression in all reported crashes in about 6 weeks, matching the fixed-sample analysis (5.5 weeks), but it does so continuously, without having to choose a test window. For serious injuries, a +50% regression takes a median of 70 weeks; for any single release that is too slow, but the chart still protects against a persistent drift across several releases.

6.6 CUSUM versus a weekly threshold

Table 10. Average weeks to alarm: one-sided Shewhart chart (alarm when one week's count reaches the limit) and CUSUM, both designed for a false-alarm interval of at least 260 weeks.

Metric	Shewhart limit (ARL_0)	+25% Shewhart / CUSUM	+50%	+100%
All reported crashes	≥ 35 per week (350)	18.5 / 6.8	3.6 / 2.8	1.2 / 1.4
Any-injury crashes	≥ 7 (401)	123 / 36	50 / 16	14 / 7.5
Airbag deployment	≥ 5 (800)	307 / 56	145 / 27	47 / 13
Serious injury or worse	≥ 2 (466)	302 / 140	212 / 91	122 / 52
Leading indicator (assumed)	≥ 340 (282)	1.1 / 1.1	1.0 / 1.0	1.0 / 1.0

For moderate regressions in the rarer counts, the CUSUM is about 2 to 5 times faster because it accumulates evidence over weeks instead of waiting for one unusual week. Part of the Shewhart chart's slowness comes from discreteness: with weekly means below 2, the smallest admissible limit already gives an ARL_0 well above 260 weeks. The Shewhart chart is competitive only for very large shifts, where a single week is already unusual.

6.7 A simulated two-year history



Figure 7. One simulated two-year history with 4-weekly releases and a +50% regression in every metric from week 60. Red markers: detections; grey markers: false alarms.

Table 11. Detections in the simulated history (regression from week 60).

Metric	First alarm	Weeks after change	False alarms before change	Events after change vs expected	Weeks until Bayesian P ≥ 0.95
Leading indicator (assumed)	week 60	1	1 (week 31)	19,610 vs 13,159	1
All reported crashes	week 61	2	0	1,409 vs 938	2
Airbag deployment	week 64	5	1 (week 31)	67 vs 35	5
Any-injury crashes	week 78	19	0	134 vs 81	14
Serious injury or worse	week 81	22	0	7 vs 3.0	21

The serious-injury chart was lucky in this run (median 70 weeks). The Bayesian check, started at the true change point, reaches 95% confidence at about the same time as the CUSUM; in practice it is most useful after an alarm, to state how confident the team is that the rate really rose.




Figure 8. Bayesian check on the same history: posterior probability that each rate has increased, using data since week 60.

6.8 False alarms add up




Figure 9. Probability of at least one false alarm in two years, by number of charts and ARL_0 per chart.

With five charts at ARL_0 = 260 weeks, the probability of at least one false alarm in two years is 86% by the approximation of Section 4.9 and 85% by direct simulation. A realistic program monitors many more metrics, by city, vehicle platform and scenario type; twenty charts at ARL_0 = 520 weeks give a 98% chance of a false alarm in two years. False alarms are therefore not a failure of the method but a certainty to plan for: each alarm needs a cheap, fast triage step (for example, checking the alarmed events, the city and weather mix, and the release notes) before any expensive response.

6.9 Overdispersion: the hidden risk for frequent metrics

Table 12. In-control ARL (weeks between false alarms) of the Poisson-designed charts when the true weekly rate varies from week to week.

Metric	Pure Poisson	CV 5%	CV 10%	CV 20%
All reported crashes (20.8 per week)	263	210	134	49
Any-injury crashes (1.79 per week)	271	260	257	223
Leading indicator (292 per week)	276	47	11	5

Table 13. Recalibrated thresholds for 10% week-to-week variation.

Metric	h (Poisson)	h (recalibrated)	ARL_0 after recalibration	ARL at +25% before / after
All reported crashes	16.9	20.2	259	6.8 / 8.1 weeks
Leading indicator (assumed)	11.4	73.8	269	1.1 / 2.7 weeks

Rare metrics are almost unaffected, because Poisson noise dominates any rate variation. Frequent metrics are badly affected: a leading indicator with only 5% week-to-week variation would false-alarm about once a year instead of once every five years, and with 10% variation about every 11 weeks. The remedy is to estimate the dispersion from historical data and calibrate the threshold on it (or use a negative-binomial CUSUM). After recalibration the leading indicator still detects a +25% change in under 3 weeks.

6.10 Leading indicators must move with the outcome

Table 14. Median weeks to alarm on the leading-indicator chart when serious injuries rise 50% and the indicator rises by a fraction of that.

Indicator rise	0%	2.5%	5%	12.5%	25%	50%
Median weeks to alarm	195 (false alarm only)	56	20	2	1	1




Figure 10. Median weeks to alarm on the leading-indicator chart against how much the indicator rises when serious injuries rise 50%. Dashed line: the serious-injury chart itself.

A leading indicator beats the serious-injury chart (median 70 weeks) as long as it rises by more than about 2.5% when serious injuries rise 50%. Rising by 5% gives a median of 20 weeks, and rising by 12.5% about 2 weeks. Establishing that coupling, for example from the conflict patterns that precede injury crashes, is therefore as important as building the chart.

6.11 Risk register




Figure 11. Data-based hazards ranked by injury-crash rate per 100 million miles (median and 90% interval).

Table 15. Scored risk register (ISO 31000 lifecycle). H1–H5 are data-based (companion analysis); H6–H8 have no public data.

ID	Hazard	Crashes	Crash rate per M mi	P(injury given crash)	Injury crashes per 100M mi (90% interval)	Status	Owner
H1	Struck while stationary	1,194	4.40	8.1%	35.4 (29.8–41.7)	Monitor	Behavior / Planning
H2	Collision while moving	740	2.73	9.5%	25.9 (21.1–31.3)	Monitor	Behavior / Simulation
H3	Cyclist, pedestrian or scooter rider	31	0.11	48.4%	5.6 (3.6–8.3)	Reduce	Perception / Behavior
H4	Motorcycle	25	0.09	20.4%	1.9 (0.8–3.6)	Reduce	Perception
H5	Heavy truck or bus	224	0.83	1.9%	1.5 (0.6–3.1)	Accept and monitor	Behavior
H6	Sensor or compute degradation, in-lane stop	–	–	–	data gap	Data gap	Hardware / Systems
H7	Delayed or incorrect remote assistance	–	–	–	data gap	Data gap	Operations
H8	Behavior regression from a release	–	–	–	monitored (Section 6.5)	Monitor	Safety / Release

Table 16. Ranking probabilities from 20,000 posterior draws.

ID	P(ranked first)	P(in top two)	Median rank
H1	97.8%	100%	1
H2	2.2%	100%	2
H3	0%	0%	3
H4	0%	0%	4
H5	0%	0%	5

The ranking is robust: H1 exceeds H2 with probability 97.8% and H3 exceeds H4 with probability 99.0%. H3 (vulnerable road users) is ranked third by rate but carries the highest severity, with nearly half of its crashes causing an injury; its treatment is therefore “reduce” rather than “monitor”. The register also lists, for each hazard, its treatment, monitoring metric and owner team (`data/risk_register.csv`), so it can be reviewed with the teams that own the design.

6.12 Automated release health report

Release health report — simulated fleet, week 104

Generated automatically by scripts/run_all.py. Simulated data on baseline rates from public NHTSA SGO reports (Repo 1); not Waymo internal data.

> **Bottom line.** 5 of 5 monitored metrics alarmed after a simulated +50% regression entered at week 60: All reported crashes, Any-injury crashes, Airbag deployment, Serious injury or worse, Leading indicator (assumed). Slowest to alarm: Serious injury or worse (22 weeks). Recommend holding the next release and bisecting the week-60 release.

1. Monitoring status (Poisson CUSUM tuned for +25%, one false alarm per metric every 5 years on average)

Metric	Status	First alarm after week 60	False alarms before	Events since week 60 vs expected	P(rate increased)
All reported crashes	RED	61	0	1409 vs 938.1	1.000
Any-injury crashes	RED	78	0	134 vs 80.5	1.000
Airbag deployment	RED	64	1	67 vs 35.0	1.000
Serious injury or worse	RED	81	0	7 vs 3.0	0.979
Leading indicator (assumed)	RED	60	1	19610 vs 13159.3	1.000

With five metrics each tuned to one false alarm per five years, the chance of at least one false alarm somewhere in two years is 85%: every alarm needs a fast, cheap triage step.

2. What field data can and cannot catch

Weeks of whole-fleet driving (2.9M miles/week) to detect a +25% regression with 80% power:

Metric	Weeks
All reported crashes	5.5
Any-injury crashes	64.5
Airbag deployment	150.4
Serious injury or worse	1,728.4
Leading indicator (assumed)	0.4

Serious-injury regressions cannot be caught from field outcomes on any release timescale: release gating must rely on scenario testing and leading indicators.

3. Top data-based risks (injury crashes per 100M miles, 90% interval)

ID	Hazard	Rate	Treatment status
H1	ADS vehicle struck while stationary (stopped or parked)	35.4 (29.8–41.7)	Monitor
H2	Collision while the ADS vehicle is moving	25.9 (21.1–31.3)	Monitor
H3	Conflict with cyclist pedestrian or scooter rider	5.6 (3.6–8.3)	Reduce

4. Data gaps to close

- H6: Sensor or compute degradation leading to an in-lane stop — owner Hardware / Systems
- H7: Delayed or incorrect remote-assistance guidance — owner Operations

5. Recommended actions

1. Hold the next release; bisect the week-60 release with the scenario library.
2. Add the alarmed scenario types to the regression test set.
3. Instrument leading indicators for H6–H8 so they can be monitored.

Figure 12. The one-page release health report generated by `scripts/run_all.py` for the simulated history.

The report is written by the same script that runs the analysis, so every number in it is computed. Its structure follows what a decision maker needs, in order: the bottom line and recommended action; the status of each monitored metric with the evidence behind it; what field data can and cannot catch; the top risks with uncertainty; the data gaps with owners; and the next actions. For a real program, the same structure would be fed from the fleet's event database at each release.

7. Discussion: what this means for release gating

7.1 A layered protection scheme

The results suggest matching each type of evidence to the outcomes it can actually protect:

Table 17. Evidence matched to what it can protect.

Layer	Protects against	Timescale	Evidence from this report
Risk-weighted scenario testing before release	Regressions in severe outcomes	Before release	299 to 3,000 runs per scenario type (Tables 7–8)
Staged rollout	Limits exposure while a problem is found	Weeks	Statistical detection of crash outcomes is slow at 10% (Table 4)
Leading-indicator monitoring	Regressions that move frequent precursors	Days to weeks	Fast if coupled (Table 14); calibrate for dispersion (Table 13)
Crash-outcome monitoring (CUSUM)	Regressions in frequent outcomes; persistent drift	Weeks to months	Table 9
Severe-outcome review	Individual serious events	Every event	Statistical charts are too slow; review each case

7.2 Alarm design as a system

Three practical rules follow. First, tune each chart to the regression size that matters for its metric, and compute its run-length curve (Figure 6) so the team knows how fast it is. Second, budget false alarms across all charts (Figure 9), and plan a triage step that is cheap enough to run for every alarm. Third, calibrate thresholds on historical week-to-week variation, not on the Poisson assumption, especially for frequent metrics (Table 12).

7.3 Test coverage as a function of risk

The zero-failure arithmetic links test coverage directly to a risk target: a scenario type whose consequences are severe gets a tighter target, and therefore more runs, than one whose consequences are minor. Combined with the risk register, this gives a traceable chain from hazard (for example H3, vulnerable road users) to scenario types, to a target failure probability, to a number of runs per release.

7.4 The role of simulation credibility

If release protection for severe outcomes rests on thousands of simulated runs, the simulation becomes part of the safety argument. The companion project av-counterfactual-uq showed, for one class of rear-end conflicts, that a single deterministic replay can hide most of the uncertainty in a counterfactual result. The same discipline (uncertainty quantification, sensitivity analysis and validation against field events) should apply to the simulation used for release gating.

7.5 Analogies with nuclear practice

In nuclear power, plant changes are screened and evaluated before installation, and plant performance is tracked with indicators that have predefined thresholds and responses. The approach here is analogous: risk-informed testing before the release, monitored indicators with thresholds after it, and a documented response to each alarm. One difference is tempo: ADS releases are far more frequent than plant modifications, which is why automation of the analysis and the reporting matters.

8. Verification

Table 18. Verification tests (`python tests/test_core.py`; all pass).

Test	What it checks
Rule of three	299 runs for 1% at 95%; n·p ≈ 3 for 0.1%
False-alarm control	The exact test never exceeds a 5% false-alarm rate
Power at the reported exposure	Power ≥ 80% at, and beyond, the reported exposure
Scaling	Two-sample exposure scales as 1/λ
CUSUM calibration	Simulated ARL_0 within 15% of the target
CUSUM sensitivity	A +50% shift cuts the run length by more than 60%
CUSUM reset	Alarms and resets are counted correctly
Bayesian check	P(rate increased) ≈ 0.5 at the baseline for large counts
Markov chain vs simulation	Brook–Evans ARL within 5% of simulated ARL
Shewhart limit	The limit meets the false-alarm target and is the smallest such limit

Table 19. Run-length verification: simulation (4,000 runs) against the Markov chain, in weeks.

Metric	ARL_0 sim / Markov	+25%	+50%	+100%
All reported crashes	260.8 / 257.0	6.7 / 6.8	2.8 / 2.8	1.5 / 1.4
Any-injury crashes	264.9 / 262.1	35.5 / 36.2	15.8 / 16.0	7.5 / 7.5
Airbag deployment	251.5 / 253.1	56.6 / 55.9	27.1 / 27.3	13.2 / 13.3
Serious injury or worse	257.5 / 261.9	139.1 / 139.8	91.9 / 90.6	51.2 / 51.5
Leading indicator (assumed)	273.6 / 274.9	1.1 / 1.1	1.0 / 1.0	1.0 / 1.0

The largest relative difference across all 25 comparisons is 2.2%, within the Monte Carlo error of 4,000 runs (about 1.6% for an ARL of 260). Two independent methods therefore agree on every run length used in this report.

One subtlety appears for the leading indicator: its threshold sits close to a jump in the discrete run-length distribution, so its ARL_0 is sensitive to the third digit of h (233 weeks in the design table, which used the unrounded threshold and 3,000 runs; 274 weeks with the rounded threshold). In practice this is another reason to calibrate thresholds on historical data.

9. Limitations

- **Public, self-reported data.** Rates come from NHTSA SGO reports, with the limitations described in the companion analysis (self-reporting, redactions, rule changes in 2025).
- **Whole-fleet, constant mileage.** Except in Section 6.2, every release is assumed to run on the whole fleet at constant weekly mileage. Real fleets grow, change their city mix and roll releases out in stages.
- **One rate per metric.** Rates are treated as fleet-wide constants. Real rates differ by city, time of day and weather, which is one source of the overdispersion studied in Section 6.9;

stratified charts would be needed in practice.
- **Assumed leading indicator.** The leading-indicator rate and its coupling to severe outcomes are assumed. Section 6.10 shows how much the conclusions depend on that coupling.
- **Independent scenario runs.** The test-coverage arithmetic assumes runs are independent draws from the scenario type. Correlated runs (for example small variations of one logged event) carry less information.
- **Illustrative risk register.** The register shows the method; it does not describe any company's actual register, and H6–H8 have no data.
- **Synthetic history.** The two-year history is simulated and shows the method, not real performance.

10. Future work

1. **Stratified and risk-adjusted monitoring:** charts by city and conditions, with expected counts adjusted for exposure mix (risk-adjusted CUSUM).
2. **Negative-binomial CUSUM** with dispersion estimated from historical data, compared with the recalibration approach of Section 6.9.
3. **Leading-indicator validation:** estimating the coupling β from field data, for example from the sequence of events before injury crashes.
4. **Change-point estimation** after an alarm, to locate the responsible release, combined with release-to-release bisection on the scenario library.
5. **Test-plan optimization:** allocating a fixed simulation budget across scenario types to minimize residual risk, weighted by the risk register.
6. **Integration with simulation credibility:** carrying the uncertainty of the simulator (companion project 2) into the test-plan arithmetic.

11. Reproduce

```
pip install -r requirements.txt
python tests/test_core.py              # 10 tests
python scripts/run_all.py              # main tables, figures, release report (about 30 s)
python scripts/supplementary.py        # supplementary studies (about 2 minutes)
python scripts/workflow_figure.py      # Figure 1
python scripts/explainer_figures.py    # Section 5 worked examples and Figures 5.1-5.10
dot -Tpng -Gdpi=170 docs/figsrc/standards_map.dot -o results/fig2_1_standards_map.png   #
Figure 2.1
python scripts/make_monitoring_video.py results/monitoring.mp4
results/monitoring_last_frame.png
python scripts/build_docs.py           # this report and the short note (needs pandoc)
```

References

- Albati, M. (2026). How certain is a counterfactual crash simulation? Uncertainty quantification for reference-model benchmarking of automated driving systems. Zenodo. doi:10.5281/zenodo.23838254

- Albati, M. (2026). How much evidence is enough? A Bayesian rare-event analysis of robotaxi crash data. Zenodo. doi:10.5281/zenodo.23732384
- Atwood, C. L., LaChance, J. L., Martz, H. F., Anderson, D. J., Englehardt, M., Whitehead, D., Wheeler, T. (2003). *Handbook of Parameter Estimation for Probabilistic Risk Assessment*. NUREG/CR-6823. U.S. Nuclear Regulatory Commission.
- Bayes, T. (1763). An essay towards solving a problem in the doctrine of chances. *Philosophical Transactions of the Royal Society* 53, 370–418.
- Brook, D., Evans, D. A. (1972). An approach to the probability distribution of CUSUM run length. *Biometrika* 59(3), 539–549.
- Clopper, C. J., Pearson, E. S. (1934). The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika* 26(4), 404–413.
- Cohen, J. (1988). *Statistical Power Analysis for the Behavioral Sciences*, 2nd ed. Lawrence Erlbaum.
- European Commission (2022). Commission Implementing Regulation (EU) 2022/1426 laying down rules for the application of Regulation (EU) 2019/2144 as regards uniform procedures and technical specifications for the type-approval of the automated driving system (ADS) of fully automated vehicles.
- Favarò, F., et al. (2023). Building a credible case for safety: Waymo's approach for the determination of absence of unreasonable risk. arXiv:2306.01917.
- Hanley, J. A., Lippman-Hand, A. (1983). If nothing goes wrong, is everything all right? Interpreting zero numerators. *JAMA* 249(13), 1743–1745.
- Hawkins, D. M., Olwell, D. H. (1998). *Cumulative Sum Charts and Charting for Quality Improvement*. Springer.
- IEEE (2022). *IEEE 2846-2022 Standard for Assumptions in Safety-Related Models for Automated Driving Systems*.
- International Electrotechnical Commission (2010). *IEC 61508:2010 Functional safety of electrical/electronic/programmable electronic safety-related systems*, 2nd ed.
- International Electrotechnical Commission (2019). *IEC 61123:2019 Reliability testing: Compliance test plans for success ratio*, 2nd ed.
- International Electrotechnical Commission (2023). *IEC 61124:2023 Reliability testing: Compliance tests for constant failure rate and constant failure intensity*.
- International Organization for Standardization (2018). *ISO 26262:2018 Road vehicles: Functional safety*.
- International Organization for Standardization (2018). *ISO 31000:2018 Risk management: Guidelines*.
- International Organization for Standardization (2019). *IEC 31010:2019 Risk management: Risk assessment techniques*.
- International Organization for Standardization (2020). *ISO/TR 4804:2020 Road vehicles: Safety and cybersecurity for automated driving systems: Design, verification and validation* (withdrawn, replaced by ISO/TS 5083:2025).
- International Organization for Standardization (2021). *ISO 7870-4:2021 Control charts: Part 4: Cumulative sum charts*.
- International Organization for Standardization (2022). *ISO 21448:2022 Road vehicles: Safety of the intended functionality*.
- International Organization for Standardization (2022–2025). *ISO 34501:2022* (vocabulary), *ISO 34502:2022* (scenario-based safety evaluation framework), *ISO 34503:2023* (ODD taxonomy), *ISO 34504:2024* (scenario categorization), *ISO 34505:2025* (scenario

evaluation and test case generation). Road vehicles: Test scenarios for automated driving systems.
- International Organization for Standardization (2023). *ISO 24089:2023 Road vehicles: Software update engineering*.
- International Organization for Standardization (2023). *ISO 7870-2:2023 Control charts: Part 2: Shewhart control charts*.
- International Organization for Standardization (2024). *ISO/PAS 8800:2024 Road vehicles: Safety and artificial intelligence*.
- International Organization for Standardization (2025). *ISO/TS 5083:2025 Road vehicles: Safety for automated driving systems: Design, verification and validation*.
- ISO and IEC (2014). *ISO/IEC Guide 51:2014 Safety aspects: Guidelines for their inclusion in standards*.
- ISO and SAE International (2021). *ISO/SAE 21434:2021 Road vehicles: Cybersecurity engineering*.
- Jeffreys, H. (1946). An invariant form for the prior probability in estimation problems. *Proceedings of the Royal Society of London A* 186, 453–461.
- Kalra, N., Paddock, S. M. (2016). *Driving to Safety: How Many Miles of Driving Would It Take to Demonstrate Autonomous Vehicle Reliability?* RAND Corporation, RR-1478-RC.
- Kusano, K. D., et al. (2024). Comparison of Waymo rider-only crash data to human benchmarks at 7.1 million miles. *Traffic Injury Prevention* 25(sup1).
- Lorden, G. (1971). Procedures for reacting to a change in distribution. *Annals of Mathematical Statistics* 42(6), 1897–1908.
- Lucas, J. M. (1985). Counted data CUSUM's. *Technometrics* 27(2), 129–144.
- Markov, A. A. (1906). Extension of the law of large numbers to dependent quantities (in Russian). *Izvestiya Fiziko-Matematicheskogo Obshchestva pri Kazanskom Universitete*, 2nd series, 15, 135–156.
- Montgomery, D. C. (2019). *Introduction to Statistical Quality Control*, 8th ed. Wiley.
- Moustakides, G. V. (1986). Optimal stopping times for detecting changes in distributions. *Annals of Statistics* 14(4), 1379–1387.
- National Highway Traffic Safety Administration (2025). Third Amended Standing General Order 2021-01: Incident Reporting Requirements for ADS and Level 2 ADAS (issued 24 April 2025, effective 16 June 2025).
- National Highway Traffic Safety Administration. Standing General Order 2021-01 on crash reporting for vehicles equipped with automated driving systems and Level 2 ADAS (as amended).
- Nuclear Energy Institute. *NEI 99-02: Regulatory Assessment Performance Indicator Guideline*.
- Page, E. S. (1954). Continuous inspection schemes. *Biometrika* 41(1/2), 100–115.
- Poisson, S. D. (1837). *Recherches sur la probabilité des jugements en matière criminelle et en matière civile*. Bachelier, Paris.
- SAE International (2021). *SAE J3016_202104 Taxonomy and Definitions for Terms Related to Driving Automation Systems for On-Road Motor Vehicles*.
- Shewhart, W. A. (1931). *Economic Control of Quality of Manufactured Product*. Van Nostrand.
- Steiner, S. H., Cook, R. J., Farewell, V. T., Treasure, T. (2000). Monitoring surgical performance using risk-adjusted cumulative sum charts. *Biostatistics* 1(4), 441–452.
- U.S. Department of Defense (1996). *MIL-HDBK-781A Handbook for Reliability Test Methods, Plans, and Environments for Engineering, Development, Qualification, and*

Production.
- U.S. Nuclear Regulatory Commission. *10 CFR 50.59 Changes, tests and experiments*; *10 CFR 50.65 Requirements for monitoring the effectiveness of maintenance at nuclear power plants*.
- UL Standards & Engagement (2023). *ANSI/UL 4600 Standard for Safety for the Evaluation of Autonomous Products*, 3rd ed.
- United Nations Economic Commission for Europe (2021). *UN Regulation No. 155: Cyber security and cyber security management system*; *UN Regulation No. 156: Software update and software update management system*; *UN Regulation No. 157: Automated Lane Keeping Systems*.
- United Nations Economic Commission for Europe (2026). *UN Regulation No. 185 and UN Global Technical Regulation No. 26 on Automated Driving Systems* (adopted by WP.29, June 2026).
- Wald, A. (1945). Sequential tests of statistical hypotheses. *Annals of Mathematical Statistics* 16(2), 117–186.
- Woodall, W. H. (2006). The use of control charts in health-care and public-health surveillance. *Journal of Quality Technology* 38(2), 89–104.

Appendix A. Equation register

Table A1. Every equation used, where it is implemented and its source.

No.	Equation	Purpose	Code	Source
A1	$W = 542 / (7.13 \times 6) \times 12/52$	Weekly fleet exposure	`rates.py`	Derived (Section 3.2)
A2	$c(M) = \min\{n : P(N \geq n \mid \lambda_0 M) \leq \alpha\}$	Critical count	`power.py::_critical`	Exact Poisson test
A3	$\text{power}(M) = P(N \geq c(M) \mid \lambda_1 M)$	Power	`power.py::power_one_sample`	Exact Poisson test
A4	$M = (z_{1-\alpha} + z_{\text{power}})^2 (1/\lambda_0 + 1/\lambda_1) / \ln^2(1+r)$	Release vs release	`power.py::miles_to_detect_two_sample`	Normal approximation
A5	$T_f = M / (fW)$	Staged rollout	`supplementary.py S1`	Derived
A6	$\lambda_0 \mid k \sim \text{Gamma}(k + ½, 271.3)$	Baseline uncertainty	`supplementary.py S3`	Jeffreys (1946)
A7	$n = \lceil \ln(1-C)/\ln(1-p_0) \rceil$	Zero-failure runs	`power.py::tests_for_zero_failures`	Hanley and Lippman-Hand (1983)
A8	$F_{\text{Bin}}(c; n, p_0) \leq 1 - C$	Runs with c failures	`supplementary.py S4`	Clopper and Pearson (1934)
A9	$P(p < p_0 \mid \text{Beta}(½, n+½)) \geq C$	Bayesian runs	`supplementary.py S4`	Jeffreys prior
A10	$k = (m_1 - m_0)/\ln(m_1/m_0)$	CUSUM reference value	`monitor.py::PoissonCUSUM`	Lucas (1985)
A11	$S_t = \max(0, S_{t-1} + X_t - k)$	CUSUM statistic	`monitor.py::PoissonCUSUM.path`	Page (1954)
A12	$\text{ARL} = (I - R)^{-1} 1$	Markov-chain run length	`monitor.py::arl_markov`	Brook and Evans (1972)
A13	$c = \min\{c : P(X \geq c \mid m_0) \leq 1/260\}$	Shewhart limit	`monitor.py::shewhart_limit`	Montgomery (2019)
A14	$1 - \exp(-mT/\text{ARL}_0)$	Family-wise false alarms	`supplementary.py S7`	Geometric run lengths
A15	$\text{Var}(X) = m_0 + v^2 m_0^2$	Overdispersion	`supplementary.py S8`	Gamma–Poisson mixture
A16	$P(\lambda > \lambda_0) = 1 - F_\Gamma(\lambda_0; N + ½, M)$	Bayesian check	`monitor.py::bayes_prob_increase`	Jeffreys prior
A17	$\text{Beta}(k+½, n-k+½)$; $\text{Gamma}(k+½, 271.3)$	Register scores	`run_all.py` step 5	Atwood et al. (2003)

Appendix B. Assumption register

Table B1. Assumptions, their basis and their effect.

No.	Assumption	Basis	Effect if wrong
B1	Rates from public SGO data represent fleet-wide rates	Companion analysis; 99.5% match to Waymo's crash list	Detection times scale with 1/λ
B2	Exposure 2.92M miles per week	Derived from 2026 crash counts	Detection times scale with 1/W
B3	Leading indicator at 100 per million miles	Assumed for illustration	Its detection times only
B4	Releases every 4 weeks to the whole fleet	Simplification	Section 6.2 shows staged rollout
B5	Weekly counts are Poisson	Standard for rare events	Section 6.9: large effect for frequent metrics
B6	Regression is a step change in rate	Simplification	Gradual drifts are detected later
B7	Design shift +25%, ARL_0 260 weeks	Choice	Table 9 and Figure 6 show the trade-off
B8	Scenario runs are independent	Simplification	Correlated runs need more runs
B9	Jeffreys prior	PRA default	Matters only for very small counts
B10	Risk register hazards and owners are illustrative	Method demonstration	No effect on the method

Appendix C. Glossary

- **ARL (average run length):** mean number of weeks until a chart alarms. ARL_0 is in control (time between false alarms); ARL_1 after a real change.
- **CUSUM:** cumulative sum control chart; accumulates evidence of a shift over time.
- **Exact Poisson test:** a test that uses the Poisson distribution directly rather than a normal approximation.
- **Leading indicator:** a frequent event (for example hard braking) whose rate moves with rarer, severe outcomes.
- **Operating characteristic (OC):** probability that a test plan passes a release as a function of its true failure probability.
- **Overdispersion:** more week-to-week variation in counts than a Poisson model allows.
- **Power:** probability of detecting a real regression.
- **Regression:** a release whose event rate is higher than the previous release's.
- **SGO:** NHTSA Standing General Order 2021-01 on crash reporting.
- **Bayesian statistics:** describes an unknown quantity by a probability distribution and updates it with data by Bayes' theorem. Prior: belief before the data; likelihood: how well each value explains the data; posterior: belief after the data.
- **Jeffreys prior:** a default prior built from the data model so that the result does not depend on how the parameter is written; Beta(½, ½) for a probability, $\propto \lambda^{-1/2}$ for a rate.

- **Markov chain:** a random process whose next state depends only on the current state; used to compute exact CUSUM run lengths.
- **ODD (operational design domain):** the conditions under which an ADS is designed to operate (SAE J3016).
- **SOTIF:** safety of the intended functionality (ISO 21448): hazards from performance limitations without a fault.
- **SPI (safety performance indicator):** a metric with a threshold that provides evidence that a safety case remains valid in operation (UL 4600).
- **SUMS:** software update management system (UN Regulation No. 156).
- **ISMR:** in-service monitoring and reporting (EU 2022/1426).
- **Type I and type II error:** a false alarm, and a missed detection.

Appendix D. Code and output map

Table D1. Where each result comes from.

Output	Produced by	Report location
`table1_detectability.csv`, `fig1_detectability.png`	`run_all.py` step 1	Table 2, Figure 2
`table2_test_coverage.csv`	`run_all.py` step 2	Table 7
`table3_cusum_design.csv`	`run_all.py` step 3	Table 9
`fig2_release_timeline.png`, `timeline_demo.json`	`run_all.py` step 4	Figure 7, Table 11
`table4_risk_register_scored.csv`, `fig3_risk_register.png`	`run_all.py` step 5	Table 15, Figure 11
`release_health_report.html`	`run_all.py` step 6	Figure 12
`table5–table12`, `fig5–fig11`	`supplementary.py` S1–S11	Sections 6.2–6.11
`fig0_workflow.png`	`workflow_figure.py`	Figure 1
`fig2_1_standards_map.png`	`docs/figsrc/standards_map.dot` (Graphviz)	Figure 2.1
`figE1_*.png–figE10_*.png`, `explainer_numbers.json`	`explainer_figures.py`	Section 5, Figures 5.1–5.10