

Correspondence: Node Mapping to Dia Element

Source feature: Node Mapping
Target feature(s): Dia Element, namespace
Automation type: FullAutomation - EASY
Relation: A GMF Node Mapping specifies how a semantic element is represented as a node in the diagram, including its identity and containment context. In JointJS, this responsibility is realized by defining a Dia Element, whose type and uniqueness are determined through its namespace. Since both constructs serve to introduce a concrete node type tied to a domain element, the mapping is direct and can be fully automated, with namespace composition systematically derived from the GMF mapping context.

Main Strategy:

- 1. [A] take the element property (A) of the node mapping
- 2. [A] take the parent top node/child reference (B) of the node mapping
- 3. [A] check if B has the compartment property (X)
- 4. [-] if X is true
 - 4.1. [A] take the compartment property (C) of B
 - 4.2. [A] take the name property (D) of C
 - 4.3. [A] if not already exist, create a dia element with the var name 'A_D' (E), else 'A_D_i' (E) where i is a counter computed by the last i + 1
 - 4.4. [A] paste 'custom.E' into the namespace of dia element
- 5. [-] if X is false
 - 5.1. [A] if not already exist, create a dia element with the var name 'A' (E), else 'A_i' (E) where i is a counter computed by the last i + 1
 - 5.2. [A] paste 'custom.E' into the namespace of dia element

Structural overview

