Chapter 3 Network exam questions

1. (Single-Answer Question) Which of the following ports is added when you configure uplinks on FusionCompute?
   A. Aggregation port
   B. Storage network port
   C. BMC network port
   D. Port group

2. (True or False) On FusionCompute, a VM NIC can be added to only one security group.
   A. TRUE
   B. FALSE

3. (Single Answer) It provides connection between sets of nodes and allows the connected devices(nodes) to communicate with each other **but it is not a device**. Which of the following fits the above description?
   A. Host.
   B. Network.
   C. Storage Array.
   D. Switch.

4. A VM can have multiple virtual NICs, which correspond to different virtual switches.
   True

5. In Huawei FusionCompute, a DVS can be configured with static routes and multiple types of dynamic routes.
   False

6. Which of the following technologies or devices **cannot isolate broadcast** domains?
   A. VLAN
   B. Hub
   C. Router
   D. Firewall

7. In KVM, there are two methods for connecting VM NICs to a physical network.
   A. Bridge connection and direct connection
   B. Bridge connection and address translation correct
   C. Address translation and passthrough
   D. Passthrough and bridge connection

8. On a physical network, which of the following devices supports **route forwarding** requests?
   A. Physical server NIC
   B. Hub
   C. Layer 2 switch
   D. Router

9. **North/South traffic can be.**

   A. Traffic generated when customers access services in a data center through the internet.
   B. Traffic generated by mutual access between VM's across data centers.

10. East/West traffic can be.
    a. Traffic between VMS in the same data center.
    b. Traffic generated during VM live migration.

11. (Multiple) In Huawei FusionCompute, which of the following are true about the relationship about quantities of VMs and DVSs?
    A. If a VM has multiple NICs, each NIC can be associated with a DVS.
    B. If a VM has multiple NICs, multiple NICs can be associated with the same DVS.
    C. If a VM has one NIC, the NIC can be associated with only one DVS.
    D. If a VM has one NIC, the NIC can be associated with multiple DVSs.

12. (Multiple) The physical switch remote management methods are:

    a. Telnet
    b. SSH
    c. **Web**

13. （Single）Which of the following operations for creating port groups in Huawei FusionCompute is false?
    A. Set the name of the port group to "test".
    B. Set the port type to Common.
    C. Set the VLAN ID to 5000.
    D. Enter "This is a test port." in the description.

14. （multiple）In Huawei FusionCompute, the VLAN ID of a port group is set to 10, which indicates ( ).
    A. **The system will untag the data frames with the VLAN 10 tag that pass through the port group and then forward the data frames.**

    B. **The system will add the VLAN 10 tag to the data frames without a VLAN tag that pass through the port group and then forward the data frames.**

    C. **The system will discard the data frames with a tag other than VLAN 10 that pass through the port group.**

    D. The system will change the tag of data frames with a non-VLAN-10 tag that pass through the port group to VLAN 10 and then forward the data frames.

15. In Huawei FusionCompute, the VLAN ID configured for a DVS must exist on the physical switch to make VM communication normal. **(True)**

16. Which is false about VLAN?
    A. VLAN increases the interface bandwidth of physical switch.
    B. VLAN enhance NW security
    C. Vlan improve network robustness
    D. Vlan isolate broadcast domains

17. （T or **F**）In Huawei FusionCompute, a management IP address must be configured for each DVS to facilitate unified management of DVSs.

18. （**T** or F）If a security group is deleted, the rules in the security group will be deleted as well.

19. （Single）Which of the following technologies can increase the link rate on a switch?
    A. VLAN
    B. VxLAN
    C. LACP
    D. LDAP

20. If two vms run on different physical server they communicate through:
    a. Virtual NIC
    b. Virtual switch
    c. Physical switch
    d. Physical NIC

21. VMs in different VLAN's can use the same IP address, no IP address conflict occurs.
True

22. In Huawei FusionCompute **,Virtual switches are belong to:**
    a. Access ,layer2 switch
    b. Core switch
    c. Aggregation switch

23. In Huawei FusionCompute, which is **true** about virtual NIC?
    a. Virtual NIC Mac and IP addresses can be manually configured.
    b. Virtual NIC doesn't need MAC address
    c. The IP of virtual NIC must manually configured
    d. Virtual NIC Mac and IP addresses are automatically configured by VRM

24. Port group types are:
    a. Common
    b. Trunk
    c. Access
    d. Aggregation

25. Which is mandatory to allow VM to communicate with other VM?
    a. **Add at least one NIC for the VM**
    b. Connect VM physical server to internet
    c. Configure port binding on server
    d. Configure port binding on switch

26. If 2 VMs can ping each other, which device will certainly be used?
    a. Virtual server
    b. Physical NIC
    c. Physical server
    d. **Virtual NIC**

27. If 2 VMs can ping each other, this indicates?
    a. **Both VM's are configured with correct IP address**
    b. They run on the same host
    c. They use the same network segment
    d. They use different network segment

28. Each port of multiple virtual ports in Huawei FusionCompute DVS has its own attributes**. True**

29. In Huawei FusionCompute,the admin can view the DVS ports connected to VMs. **False**

30. The prerequisite for the communication between VMS are:
    A. **Configure correct IP address to VMs**
    B. **Configure correct MAC address to VMS**

31. In Huawei FusionCompute, the management VLAN ID cannot be changed. **False**
32. If some tools installed on the VM, you can set it IP address to 0.0.0.0 **True**

Important Information about:

1. Security group:

- **Security groups protect VM's based on rules not based on port groups.**
- **Security groups is a set of rules like firewall**
- **One physical NIC can be added only to one security group.**
- **One VM can be protected by a single security group**

2. Port group

- **Port group is an aggregation of virtual ports on DVS.**
- **VM NIC is connected to a virtual port in a port group.**
- **One DVS can have multiple port groups**
- **Port group consist of multiple ports with the same attributes**
- **Port group attribute change, not affect VM running.**

3. The uplink

- **Uplink is link between DVS and physical NIC of the host.**
- **One host can has multiple uplinks connected to different DVS.**
- **Multiple DVS cannot share an uplink.**
- **Uplink can correspond to one physical network port or logical port that binds multiple physical network ports.**