Drop missing values

If you're in a hurry or don't have a reason to figure out why your values are missing, one option you have is to just remove any rows or columns that contain missing values. (Note: I don't generally recommend this approach for important projects! It's usually worth it to take the time to go through your data and really look at all the columns with missing values one-by-one to really get to know your dataset.)

```
print (dataset.shape)

dataset2 = dataset.dropna(axis=0)
print (dataset2.shape)

dataset3 = dataset.dropna(axis=1)
print (dataset3.shape)
```

Filling in missing values automatically

```
dataset4 = dataset.fillna(0)

print (dataset.head(10))
print (dataset4.head(10))

dataset5 = dataset.fillna(method='bfill')
print (dataset.head(10))
print (dataset5.head(10))

missing_values_count2 = dataset5.isnull().sum()
print (missing_values_count2)
print ("count2= " , missing_values_count2.sum())

dataset6 = dataset5.fillna(0)
missing_values_count3 = dataset6.isnull().sum()
print (missing_values_count3)
print ("count3= " , missing_values_count3.sum())
```

Scaling and Normalization

Scaling

This means that you're transforming your data so that it fits within a specific scale, like 0-100 or 0-1.

Normalization

Scaling just changes the range of your data. The point of normalization is to change your observations so that they can be described as a normal distribution.

- In scaling, you're changing the range of your data, while in normalization, you're changing the shape of the distribution of your data.