

Payments API

Reference v2

Developer Platform

Contents

Overview	1
Authentication	1
Endpoints	1
Create a charge	1
Example	2
Errors	2

Overview

The Payments API is a JSON-over-HTTPS API. All requests require a bearer token and are scoped to a single merchant account. Base URL: `https://api.example.com/v2`.

Authentication

```
GET /v2/charges HTTP/1.1
Host: api.example.com
Authorization: Bearer sk_live_*****
```

Endpoints

Create a charge

POST /v2/charges

Field	Type	Required	Description
amount	integer	yes	Amount in the smallest currency unit
currency	string	yes	ISO 4217 code, e.g. usd
source	string	yes	A tokenized payment source
metadata	object	no	Arbitrary key/value pairs

Example

```
curl https://api.example.com/v2/charges \  
-H "Authorization: Bearer $KEY" \  
-d amount=1499 -d currency=usd -d source=tok_visa
```

```
{  
  "id": "ch_3Nf",  
  "amount": 1499,  
  "currency": "usd",  
  "status": "succeeded"  
}
```

Errors

The API uses conventional HTTP status codes.

Status	Meaning	Notes
400	invalid_request	A parameter was missing/invalid
401	authentication_error	Bad or missing API key
429	rate_limited	Back off and retry

Idempotency: send an Idempotency-Key header to safely retry POST requests.