

Express + PostgreSQL route reference

Base URL

Production: <https://abouelsaad.cloud>

Local: <http://localhost:4000>

Quick start

Start the API with `pnpm start:api`. It listens on `API_PORT`, defaulting to port 4000. Set `DATABASE_URL` and `BETTER_AUTH_SECRET` or `JWT_SECRET` before starting.

Authentication

Login returns a JWT valid for 7 days. Send it on protected requests using the Authorization header.

```
Authorization: Bearer YOUR_TOKEN
```

Route catalog

METHOD	ENDPOINT	AUTH	DESCRIPTION
GET	/api/health	Public	Returns API availability.
POST	/api/auth/login	Public	Authenticate an admin user.
POST	/api/auth/users	Admin JWT	Create an admin, editor, or author account.
GET	/api/articles	Public	List published articles.
POST	/api/articles	Admin/editor/author JWT	Create an article.
PUT	/api/articles/:id	Admin/editor/author JWT	Update an article.
DELETE	/api/articles/:id	Admin/editor JWT	Delete an article.
GET	/api/portfolio	Public	List portfolio projects; supports ?category=web mobile self.
POST	/api/portfolio	Admin/editor JWT	Create a portfolio project.
DELETE	/api/portfolio/:id	Admin/editor JWT	Delete a portfolio project.
POST	/api/contact	Public	Store a contact message and optionally send email.
GET	/api/contact	Admin/editor JWT	List contact messages.

Request examples

Health check

```
curl https://abouelsaad.cloud/api/health
```

Login

```
curl -X POST https://abouelsaad.cloud/api/auth/login \
  -H 'Content-Type: application/json' \
  -d '{"email":"admin@example.com","password":"your-password"}'
```

Create portfolio project

```
curl -X POST https://abouelsaad.cloud/api/portfolio \
  -H 'Content-Type: application/json' \
  -H 'Authorization: Bearer YOUR_TOKEN' \
  -d '{"title":"Clinic Platform","slug":"clinic-platform","description":"Clinic management platform","category":"web","url":"https://example.com"}'
```

Submit contact form

```
curl -X POST https://abouelsaad.cloud/api/contact \
  -H 'Content-Type: application/json' \
  -d '{"name":"Jane Doe","email":"jane@example.com","message":"I would like to work with you."}'
```

Validation and errors

Invalid JSON or missing fields returns HTTP 400 with Zod field details. Missing or invalid JWT returns 401. Insufficient role returns 403. Unknown records typically return 404. Server failures return 500.

Required environment variables

DATABASE_URL

BETTER_AUTH_SECRET or JWT_SECRET

API_PORT (optional, default 4000)

FRONTEND_URL (optional)

SMTP_HOST, SMTP_PORT, SMTP_SECURE, SMTP_USER, SMTP_PASSWORD, SMTP_FROM (optional email delivery)