

DHCP Relay Agent With Router On A Stick

- 1- Give Ip Computer 192.168.10.10 & 192.1468.20.10
- 2- Configure Switch For Vlan 10 & 20
- 3- Configure Router
- 4- Configure Server DHCP & VLAN30
- 5- Go To Computer Give dhcp

-
- Configure Switch For Vlan 10

```
SW>en
Sw#conf t
SW(config)#VLAN 10
SW(config)#Name IT
SW(config)#int f0/1
Sw(config-if)# switchport access vlan 10
Sw(config-if)#do wr
```

- Configure Switch For Vlan 20

```
SW>en
Sw#conf t
SW(config)#VLAN 20
SW(config)#Name SALES
SW(config)#int f0/1
Sw(config-if)# switchport access vlan 20
Sw(config-if)#do wr
```

```
SW(config)#int g 0/1
Sw(config-if)# switchport mode trunk
Sw(config-if)#do wr
```

- Configure Router

```
R1>en
R1#conf t
R1(config)#int g0/0.10
R1(config-subif)#encapsulation dot1Q 10
R1(config-subif)#ip add 192.168.10.1 255.255.255.0
R1(config-subif)#no shutdown
R1(config-subif)#do wr
```

Configure Server DHCP & VLAN30

```
SW>en
Sw#conf t
SW(config)#VLAN 30
SW(config)#Name DHCP-SER
SW(config)#int f0/5
Sw(config-if)# switchport access vlan 30
Sw(config-if)#do wr
```

Go to Router and config➔

R1>en

R1#conf t

R1(config)#int g0/0.30

R1(config-subif)#encapsulation dot1Q 30

R1(config-subif)#ip add 192.168.30.1 255.255.255.0

R1(config-subif)#exit

R1#show running-config

R1(config)#no ip dhcp pool 10

R1(config)#no ip dhcp pool 20

Go to DHCP-SER and config➔192.168.30.200 & G.W:192.168.30.1

R1(config)#int g0/0.10

R1(config-subif)#ip helper-address 192.168.30.200

R1(config)#int g0/0.20

R1(config-subif)#ip helper-address 192.168.30.200

⇒ Go To Computer Give dhcp

