Comprehensive Strategic Plan for AI-Driven Cognitive Radio Networks: Architecture, Simulation, and Hardware Deployment

The exponential proliferation of wireless technologies, driven by the impending transition to 6G architectures, Industry 5.0, the Internet of Everything (IoE), and intelligent healthcare, has precipitated a severe global shortage in available radio frequency spectrum. Traditional static spectrum allocation regimes suffer from inherent inefficiencies, often leaving licensed primary user (PU) bands heavily underutilized while unlicensed secondary users (SUs) experience debilitating resource starvation. To circumvent these systemic limitations, dynamic spectrum management (DSM) via Cognitive Radio Networks (CRNs) provides a foundational mechanism for SUs to opportunistically access spectrum holes—or "white spaces"—without inducing harmful interference to PUs. The operational cycle of a cognitive radio system consists of four primary components: spectrum sensing, spectrum decision, spectrum sharing, and spectrum mobility.

The integration of artificial intelligence (AI), specifically deep learning (DL), alongside Software-Defined Radio (SDR) hardware and advanced network simulation paradigms (NS-3), establishes a formidable framework for intelligent, self-optimizing wireless communications. This document serves as an exhaustive architectural and implementation blueprint for deploying a state-of-the-art, AI-driven Cognitive Radio Network. It synthesizes theoretical mathematical models, machine learning pipeline specifications, cybersecurity threat mitigation protocols, network simulation parameters, hardware-in-the-loop (HITL) SDR integration, and localized High-Performance Computing (HPC) provisioning strategies tailored for deployment in Cairo, Egypt. Furthermore, the strategic plan delineates the requisite multidisciplinary skills and automated agentic frameworks necessary to tailor and execute the deployment successfully, satisfying all foundational planning requirements for a large-scale cognitive network rollout.

Theoretical Framework and Mathematical Modeling of Spectrum Sensing

The foundational premise of cognitive radio operation is spectrum sensing, which allows the network to continuously scan the radio spectrum to identify available frequency bands before transmitting. This operation is mathematically formulated as a binary hypothesis testing problem. The core objective is to ascertain the presence or absence of a PU transmission within a targeted frequency band, thereby enabling safe, opportunistic access by an SU.

Binary Hypothesis Testing and Decision Statistics

The received signal at the sensing device, denoted as r(n), is evaluated against two primary states representing the idleness or occupancy of the spectrum. The first hypothesis, H_0,

represents the condition where the spectrum is idle, meaning no PU activity is present, and the received signal comprises exclusively environmental noise, w(n). The alternate hypothesis, H_1, signifies that the PU is actively transmitting, meaning the received signal is a composite of the PU signal s(n) subjected to a channel gain h, combined with the noise w(n).
\begin{aligned} H_0: r(n) &= w(n) \\ H_1: r(n) &= h s(n) + w(n) \end{aligned}
The noise signals and the PU signals are generally modeled as Gaussian distributed, leveraging the central limit theorem, with a zero mean and variances denoted as \sigma_n^2 and \sigma_s^2, respectively. Under these conditions, the mathematical test statistic for an energy detection decision, denoted as D(Y), evaluates the accumulated energy of the signal over L samples.
If the test statistic D(Y) falls below a predefined threshold \gamma, the system declares H_0, indicating that the spectrum is available for SU transmission. Conversely, if D(Y) \ge \gamma, the system declares H_1. Under the H_0 hypothesis, the test statistic follows a central chi-square distribution with 2L degrees of freedom, whereas under H_1, it is subject to a non-central chi-square distribution.

Detection Metrics and the Noise Uncertainty Problem

The efficacy of any spectrum sensing algorithm is quantified by two critical probabilistic metrics. The Probability of Detection (P_d) measures the likelihood that the algorithm correctly identifies an active PU transmission when the true state is H_1. This parameter must be as large as possible to prevent catastrophic interference with licensed PUs. Conversely, the Probability of False Alarm (P_{FA}) quantifies the likelihood of the algorithm erroneously detecting a PU when the spectrum is actually idle (H_0), which unjustifiably prevents the SU from accessing available bandwidth and drastically reduces overall spectrum utilization.
These theoretical probabilities translate directly into physical operational efficiency metrics.

Metric	Mathematical Definition	Operational Evaluation Ratio
Probability of Detection (P_d)	P(\hat{H}_1 = H_1 \mid H_1)	\frac{\text{Correct Detections}}{\text{Total Actual PU Transmissions}}
Probability of False Alarm (P_{FA})	P(\hat{H}_1 = H_1 \mid H_0)	\frac{\text{False Alarms}}{\text{Total Actual Idle Periods}}

Classical sensing methodologies rely heavily on manual threshold calibration. Energy detection, while computationally simple, suffers from a phenomenon known as the "SNR wall"—a threshold (often around -12 dB to -8 dB) below which the detector cannot reliably distinguish signal from noise due to noise variance uncertainty. Other traditional methods include the maximum-minimum eigenvalue ratio-based detection (which compares relative eigen-spreads in a sample covariance matrix) and cyclostationary feature detection (which exploits periodic structures like symbol rates and pilot tones). However, eigenvalue sensing involves costly singular-value decompositions that consume significant FPGA fabric, and cyclostationary detection requires extensive observation windows, increasing sensing latency.
Consequently, shifting the binary classification burden from static mathematical thresholds to dynamic, data-driven machine learning models offers unparalleled adaptability to novel signals, effectively lowering the SNR wall and allowing CRNs to operate in highly dynamic, noisy environments.

Artificial Intelligence and Machine Learning Architecture

The deployment of Deep Neural Networks (DNNs) transforms spectrum sensing from a rigid threshold-based mechanism into a highly adaptive, multi-dimensional pattern recognition task. Convolutional Neural Networks (CNNs) are uniquely adept at extracting both spatial and temporal features from complex radio frequency (RF) in-phase and quadrature (I/Q) signal vectors without requiring explicit manual feature extraction.

Training Dataset Specifications and Channel Characterizations

The primary empirical foundation for training these spectrum sensing models is the RadioML 2018.01A dataset, a comprehensive synthetic dataset encompassing a vast array of modulation schemes and simulated channel effects designed specifically to evaluate modulation classification and signal recognition algorithms.

Dataset Parameter	Specification
Dataset Nomenclature	RadioML 2018.01A
Total Frames	2,555,904 discrete signal frames
Vector Shape	1024 \times 2 (representing In-Phase and Quadrature components)
Total Modulation Types	24 distinct classes (19 Digital, 5 Analog)
Digital Modulations	GMSK, OOK, 256QAM, 128QAM, 64QAM, 32QAM, 16QAM, 128APSK, 64APSK, 32APSK, 16APSK, 32PSK, 16PSK, 8PSK, BPSK, QPSK, OQPSK, 8ASK, 4ASK
Analog Modulations	FM, AM-DSB-SC, AM-DSB-WC, AM-SSB-SC, AM-SSB-WC
Signal-to-Noise Ratios (SNR)	26 levels ranging from -20 dB to +30 dB (in 2 dB increments)
Channel Characterizations	Additive White Gaussian Noise (AWGN), Doppler shift, non-impulsive delay spread, symbol rate offset, carrier frequency offset, selective multipath Rician/Rayleigh fading

To optimize training and prevent data leakage, the dataset must undergo rigorous preprocessing. Data is split strictly based on modulation types and their corresponding SNR levels into training, validation, and hold-out testing subsets. This partitioning ensures that the model is evaluated thoroughly on unseen data and that overfitting is aggressively mitigated.

The Impact of Multipath Fading on AI Inference

Wireless communications are highly susceptible to multipath fading, a phenomenon where the transmitted signal reflects off obstacles, arriving at the receiver through multiple paths with varying delays, phases, and amplitudes. A Rayleigh fading channel models environments where there is no direct line-of-sight path between the transmitter and receiver. The probability density function for the envelope of a Rayleigh fading channel is expressed mathematically, where \sigma^2 represents the average signal power:

$$f(a) = \frac{a}{\sigma^2} \exp\left(-\frac{a^2}{2\sigma^2}\right)$$
Conversely, Rician fading occurs when a dominant line-of-sight component is present alongside scattered multipath reflections. The probability density function incorporates a modified Bessel function of the first kind to account for this dominant path. Empirical evaluations utilizing the RadioML 2018.01A dataset indicate that deep learning classification accuracy degrades significantly under severe fading conditions. At an SNR of 0 dB, recognition accuracy under Rayleigh and Rician fading drops below 70%. Performance under Rayleigh fading is generally observed to be superior to Nakagami-m fading models. Robustness returns rapidly as signal strength increases; at an SNR of 8 dB and above, recognition accuracy reliably exceeds 95%. Advanced architectures must be deployed to guarantee performance in these highly degraded, low-SNR environments.

Lightweight 1D Convolutional Neural Network Architectures

The architectural strategy for this cognitive radio deployment relies on ultra-lightweight, high-efficiency 1D Convolutional Neural Networks (1D-CNN) that map raw I/Q samples to binary states (H_0 or H_1). Three primary iterations of the 1D-CNN architecture have been engineered, evolving from a baseline model to an optimized edge-capable model designed to mitigate overfitting and maximize real-time inference speed for SDR peripherals. The baseline architecture consists of stacked 1D convolutional layers interspersed with max-pooling operations to compress the feature map, followed by a standard flattening layer and dense fully connected networks. The total trainable parameters exceed two million, which introduces a severe risk of overfitting and high computational latency that is untenable for real-time spectrum sensing.

Baseline Layer Architecture	Output Dimensionality	Trainable Parameters
Conv. (1D) (k=3, f=32)	(None, 1022, 32)	224
Max pooling (1D) (size=2, s=2)	(None, 511, 32)	0
Conv. (1D) (k=3, f=64)	(None, 509, 64)	6,208
Max pooling (1D) (size=2, s=2)	(None, 254, 64)	0
Flatten	(None, 16, 256)	0
Dense	(None, 128)	2,080,896
Dropout (50%)	(None, 128)	0
Dense	(None, 1)	129
Total Model Complexity		**2,087,457 Parameters**

To combat the overfitting observed in the baseline model during prolonged training epochs across the RadioML dataset, Batch Normalization layers are introduced to stabilize internal covariate shifts. Furthermore, the fully connected dense layers are significantly streamlined. This architectural modification drastically reduces the parameter count to approximately 23,000, vastly improving the model's suitability for embedded deployment without sacrificing predictive accuracy.

Optimized Batch-Norm Architecture	Output Dimensionality	Trainable Parameters
Input Layer	(None, 1024, 2)	0
Conv. (1D)	(None, 1022, 32)	224
Batch Normalization	(None, 1024, 32)	128
Max pooling (1D)	(None, 512, 32)	0

Optimized Batch-Norm Architecture	Output Dimensionality	Trainable Parameters
Dropout	(None, 512, 32)	0
Conv. (1D)	(None, 512, 64)	6,208
Batch Normalization	(None, 512, 64)	256
Max pooling (1D)	(None, 256, 64)	0
Dropout	(None, 256, 64)	0
Flatten	(None, 16, 384)	0
Dense	(None, 1)	16,385
Total Model Complexity		**23,009 Parameters**

For maximum efficiency on extremely constrained edge devices, a Global Average Pooling (GAP) layer replaces the traditional flattening operation entirely. The GAP layer condenses spatial dimensions drastically (reducing the output from 512x1 dimensions to a singular representative vector), yielding an ultra-lightweight architecture with under 15,000 parameters. This ensures sub-millisecond inference latency on SDR hardware accelerators while preserving high fidelity in classification.

Ultra-Lightweight GAP Architecture	Output Dimensionality	Trainable Parameters
Conv. (1D)	(None, 1022, 32)	224
Max pooling (1D)	(None, 511, 32)	0
Conv. (1D)	(None, 509, 64)	6,208
Max pooling (1D)	(None, 254, 64)	0
Global Average Pooling (1D)	(None, 64)	0
Dense	(None, 128)	8,320
Dropout	(None, 128)	0
Dense	(None, 1)	129
Total Model Complexity		**14,881 Parameters**

Hyperparameter Tuning and Network Optimization

The deep learning models evaluate the disparity between predicted binary classification outputs and true data labels utilizing the Binary Cross-Entropy (BCE) loss function. This metric heavily penalizes high-confidence erroneous predictions, driving the network toward optimal weights:
$$\text{LogLoss} = -\frac{1}{n} \sum_{i=1}^{n} \sum_{j=1}^{M} y_{ij} \log(p_{ij})$$
Network optimization is driven by the Stochastic Gradient Descent (SGD) algorithm configured with a learning rate of 0.001 (without decay), a momentum of 0, and a weight decay coefficient of 0.0001 to prevent parameter bloat. To accelerate convergence across enterprise-grade NVIDIA Tesla P100 architectures, the training batch size is iteratively scaled from 128 up to 2048.

Initial training conducted absent of Additive White Gaussian Noise (AWGN) achieves perfect 100% accuracy within just two epochs, demonstrating the model's capacity to easily classify clean signals. However, the introduction of AWGN with a standard deviation of 0.708 instantly degrades the baseline configuration's accuracy to 87.5%. Extending the training duration to 40 epochs utilizing the batch-normalized architecture successfully restores accuracy to 97.5%. Through aggressive filtering that isolates training solely to SNRs between -8 dB and +30 dB, the final GAP-enabled model sustains over 98% accuracy with a validation loss factor below 0.05%

after 32 epochs.

Advanced Recurrent and Attention-Enhanced Frameworks

While 1D-CNNs excel at extracting spatial structures, temporal feature extraction is vastly improved by appending Bidirectional Gated Recurrent Units (Bi-GRUs) to the convolutional pipeline. Bi-GRUs consist of forward and backward processing layers (typically featuring 128 neurons each) that enable the model to capture context from both past and future signal time steps. The Bi-GRU architecture computes an update gate z_t and a reset gate r_t using sigmoid activations, thereby preserving long-term dependencies in the radio signal and significantly boosting recognition capabilities under Rician multipath fading scenarios:
h_t = (1 - z_t) \cdot \tilde{h}_t + z_t \cdot h_{t-1}
Furthermore, emerging architectures such as ACNet and SPA-ResNet introduce attention-enhanced hybrid frameworks. These networks employ Soft Thresholding combined with Channel Attention mechanisms to eliminate redundant filters via channel pruning. If the attention parameter \alpha_i = 0, the corresponding feature channel is completely pruned, dynamically shifting the balance between recognition accuracy and computational efficiency depending on the instantaneous processing capacity of the edge device. Similar ultra-low latency frameworks, such as MobileNet1D (adapted from MobileNetV2), offer model sizes as small as 11.6 MB, allowing for embedded deployment directly onto constrained RF front-ends.

Hardware-in-the-Loop and SDR Testbed Orchestration

The transition from theoretical machine learning models and dataset simulations to physical, over-the-air (OTA) reality necessitates Hardware-in-the-Loop (HITL) integration.
Software-Defined Radio (SDR) platforms serve as the critical bridge, replacing fixed analog RF circuitry with flexible baseband processing governed by field-programmable gate arrays (FPGAs) and general-purpose processors.

Physical SDR Hardware Specifications

The cognitive network deployment architecture utilizes a multi-tiered SDR strategy, matching specific hardware capabilities to the localized computational requirements of the primary and secondary users.

SDR Platform	ADC Resolution	Instantaneous Bandwidth (IBW)	Primary Use Case and Network Function
RTL-SDR Blog V3	8-bit	~2.4 MHz	Ultra-low-cost, distributed cooperative spectrum sensing nodes. Ideal for edge-heavy deployment where numerous sensors fuse data to a central processing node.
HackRF One	8-bit	20 MHz	Portable, half-duplex transceiver used for

SDR Platform	ADC Resolution	Instantaneous Bandwidth (IBW)	Primary Use Case and Network Function
			localized signal jamming emulation and dynamic frequency hopping tests.
PlutoSDR (ADALM-PLUTO)	12-bit	Up to 20 MHz	Compact System-on-Chip (SoC) transceivers utilized for UAV tracking and medium-tier SU mobile emulation.
LimeSDR-USB	12-bit	Up to 61.44 MHz	2\times2 MIMO transceiver supporting open toolchains, ideal for cellular emulation and advanced physical layer security testing.
USRP B210	12-bit	Up to 56 MHz	Laboratory-grade 2\times2 full-duplex MIMO transceiver driven by the AD9361 RFIC, used for baseline AI inference testing.
USRP X310 / N210	14-bit ADC, 16-bit DAC	160 MHz per channel	Enterprise-grade network cores supporting dual 10 Gigabit Ethernet or PCIe, streaming wideband I/Q data directly to host GPUs for real-time deep learning.

Overcoming Latency Versus Bandwidth Constraints

A fundamental bottleneck encountered during OTA testing is the inverse relationship between instantaneous bandwidth coverage and AI inference latency. Processing a 1-Megasample frame through a GPU-accelerated CNN typically requires approximately 2.3 milliseconds. Consequently, real-time continuous spectrum monitoring on commodity hardware is often restricted to narrow slices of spectrum (e.g., 200 kHz to 5 MHz) to prevent processing buffer overflows.

When deploying deep learning models on constrained embedded systems, such as a Raspberry Pi linked to a LimeSDR, CNN inference can saturate the CPU entirely at just 5 milliseconds per OFDM frame, strictly limiting the monitoring bandwidth. To scan wider swaths of the radio spectrum (e.g., contiguous blocks >100 MHz), the deployment must reject purely serial wide-band tuner-hopping. Instead, the system leverages multi-agent predictive scheduling, utilizing deep recurrent models to forecast spectrum holes, thereby reducing the required

sensing duty cycle by up to 50% and allowing the SDRs to selectively tune to predicted idle bands rather than continuously sweeping the entire RF landscape.

Large-Scale Testbed Environments

Prior to live urban deployment, the AI models and SDR hardware are orchestrated within standardized, large-scale testbeds. Colosseum provides an unparalleled wireless digital twin for massive-scale, AI-driven dynamic spectrum experimentation, featuring hardware-in-the-loop emulation capable of modeling complex RF environments. Concurrently, the OpenRAN Gym framework supports the testing of AI/ML xApps and rApps within an Open Radio Access Network (O-RAN) architecture.
By deploying Deep Reinforcement Learning (DRL) agents as Near-Real-Time Radio Intelligent Controllers (Near-RT RIC), the network dynamically adjusts spectrum allocation, TDMA access, and beamforming parameters based on real-time hardware telemetry. These automated control loops can execute proactive spectrum sharing algorithms between LTE and 5G NR nodes, achieving reconfigurations in under 866 milliseconds—comfortably within regulatory protection windows. Furthermore, the RFRL Gym provides a specialized reinforcement learning testbed to benchmark and compare intelligent agents specifically focusing on dynamic spectrum access and anti-jamming tactics prior to their deployment onto the USRP hardware.

Network Simulation, MAC Optimization, and Delay Analytics

Before committing physical SDR hardware to the field, the macroscopic behavior of the Cognitive Radio Network—including transport layer reliability and application layer latency—must be rigorously validated using the NS-3 discrete-event network simulator. NS-3 allows engineers to construct high-fidelity CRN topologies, modeling both primary and secondary user traffic patterns, mobility models, and interference management protocols.

End-to-End Delay and Simulation Tracing

Evaluating the viability of SU access requires exact measurements of end-to-end delay, defined as the precise temporal differential between packet transmission and successful reception at the destination. In the NS-3 environment, this is achieved by establishing point-to-point links featuring predefined channel delays and data rates. A UDP Echo server is installed on one receiving node, while a UDP Echo client is installed on a transmitting node, generating deterministic traffic loads (e.g., 1000 packets, 1024 bytes each, transmitted at 0.01-second intervals). To capture this data, NS-3 ASCII tracing is enabled. The simulation generates a .tr event log that captures every transmission, enqueue, dequeue, and reception event. A Python-based parsing script is then utilized to extract timestamps, calculate individual packet delays, and compute the mean network latency.

```
send_times = {}
recv_times = {}
delays = []

with open("end-to-end-delay.tr", "r") as trace_file:
    for line in trace_file:
```

```
        fields = line.split()
        time = float(fields[1])
        event = fields[3]
        packet_id = fields[5]

        # Logic to map send and receive times to calculate delay
        if packet_id in send_times and packet_id in recv_times:
            delays.append(recv_times[packet_id] -
send_times[packet_id])

average_delay = sum(delays) / len(delays) if delays else 0
print(f"Average End-to-End Delay: {average_delay} seconds")
```

MAC Protocol Optimization and Collision Probabilities

At the Medium Access Control (MAC) layer, secondary users must meticulously coordinate spectrum access to avoid catastrophic collisions with returning primary users. In traditional topologies, reference schemes such as Pure ALOHA and Slotted ALOHA are utilized. However, their collision probabilities increase exponentially as the offered network load scales.
To optimize access for Cognitive Radio Internet of Things (CR-IoT) devices, advanced protocols like Interleaved Listen-Before-Talk Carrier-Sense Multiple Access (ILA-CSMA) are simulated. ILA-CSMA relies on a two-stage hybrid sensing approach. The first stage performs standard channel activity detection (CAD). If the channel appears idle, the second stage reads the instantaneous Receive Signal Strength Indicator (RSSI) and compares it against a dynamic, AI-driven threshold.
This hybrid sensing approach aggressively screens out SU transmissions in the presence of excessive residual interference. By combining interference screening (CSMA-HS) with Time-on-Air (ToA) aware spacing (CSMA-AB), the protocol drastically reduces invalid transmission attempts. In highly dense simulated networks (e.g., 2,000 nodes), ILA-CSMA improves the Packet Delivery Ratio (PDR) by approximately 20 percentage points compared to standard CSMA/CA, dropping the conditional average delay from 18.5 seconds to just 8.2 seconds and substantially reducing the energy consumed per successful packet. By jointly optimizing spectrum sensing latency and user transmission requirements, the network establishes a stable Nash Equilibrium where SUs efficiently share the spectrum without encroaching on PU rights.

Cybersecurity in SDR-Enabled Cognitive Radios

While the inherent flexibility of Software-Defined Radios is highly advantageous for dynamic spectrum access, it simultaneously lowers the threshold for adversarial physical-layer attacks. Because an SDR can tune, sample, and replay virtually any portion of the spectrum, it functions as a low-cost tool for executing denial-of-service and espionage attacks. Classical rule-based intrusion detection systems struggle to adapt to agile, frequency-hopping adversaries; therefore, integrating AI-driven mitigation strategies is an absolute operational necessity.

Jamming Detection and Mitigation Frameworks

Jamming attacks intentionally elevate the local noise floor to completely prevent the victim receiver from demodulating legitimate packets. Variations of this attack include wideband barrage jamming, narrowband single-tone jamming, and highly elusive reactive jamming, where the attacker listens for specific preambles and injects noise precisely to corrupt the payload. Commercial-off-the-shelf (COTS) hardware, such as the HackRF One, has been repeatedly demonstrated to successfully execute 802.11n/ax Wi-Fi jamming and severe drone control link disruption with minimal transmit power.

Traditional defense mechanisms rely on the real-time monitoring of packet-level metrics (e.g., PDR) or the Adaptive Signal-to-Jammer-plus-Noise Ratio (ASNJR) to trigger multilateration of the jamming source. However, these fixed-threshold systems frequently fail when tracking drifting noise floors.

AI radically upgrades this defensive posture by employing machine learning classifiers (such as Random Forests or CNNs) operating directly over radiometric OFDM features or spectrogram images.

AI Jamming Defense Architecture	Deployment Platform	Performance Capability
CNN on Spectrograms	Raspberry Pi / Embedded Edge	93% to 99.8% classification accuracy of barrage, single-tone, and reactive jammers. Operates within tight Size, Weight, and Power (SWaP) constraints.
Sparse Autoencoder (BloodHound+)	Mobile Indoor Detectors	Identifies jamming signatures in "low-BER" pre-disruption phases, detecting threats up to 20 meters before the communication link actually collapses.
TinyML (TensorFlow-Lite)	LimeSDR / IoT Nodes	Sustains 98% detection accuracy across normal, constant, and periodic jamming while consuming merely ~250 mW of edge power.
Bayesian Inference & Echo-State	5G NR O-RAN Testbeds	Achieves an AUC of 0.988 with 180 ms latency, enabling near real-time control loop mitigation via the O-RAN RIC.

Once an attack signature is classified, Deep Reinforcement Learning (DRL) agents autonomously orchestrate mitigation. The agent can seamlessly switch channel frequencies or activate spatial nulling via beam-steering antennas on the USRP X310, improving the local Signal-to-Interference-plus-Noise Ratio (SINR) by up to 14 dB.

Spoofing and Replay Attack Countermeasures

Unlike jammers, spoofers synthesize legitimate RF waveforms to deceive the receiver, forcing it

to accept false timing or location data. This is exceptionally dangerous for Global Navigation Satellite Systems (GNSS) or aviation Automatic Dependent Surveillance-Broadcast (ADS-B) protocols. An attacker utilizing a BladeRF-x40 or PlutoSDR can execute a "capture-and-divert" attack on an unencrypted GPS receiver (e.g., a DJI Phantom UAV), overriding its true location coordinates and forcing a critical navigation failure.
Defensive algorithms traditionally require significant FPGA resources to execute complex codeless squaring techniques and orthogonal-projection beamforming to null the counterfeit signals. AI transitions this computational burden by passing correlator-domain features, phase differentials, or RF fingerprints directly into tree-based classifiers (e.g., XGBoost) or deep Convolutional layers. These AI models achieve 92% to 97% spoofing detection accuracy with sub-millisecond inference latencies. By implementing Naïve-Bayes physical-layer authentication techniques, the system completely negates the need for manual threshold retuning when moving between satellite constellations or carrier frequencies.

Eavesdropping and Electromagnetic Emanations

Passive eavesdropping involves the unauthorized interception of RF signals. Because transmissions are broadcast indiscriminately, any SDR tuned to the correct frequency can capture raw I/Q samples. Beyond intentional RF transmissions, deep learning enables the reconstruction of complex data from unintended electromagnetic (EM) side-channel leakages. Advanced AI architectures like Deep-TEMPEST leverage inverse CNN models to reconstruct on-screen DVI/HDMI monitor content purely from EM emanations, improving character error rates by over 60 percentage points compared to non-ML baselines. Furthermore, neural encoder-decoders can translate backscattered RF variations emanating from unshielded earphone wires into highly accurate speech transcripts from meters away. Mitigating these advanced espionage vectors in a CRN requires physical emission suppression, randomized timing encodings, pilot obfuscation, and AI-driven anomaly detection to identify parasitic sensing behavior in the physical layer.

Localized Infrastructure and High-Performance Compute Provisioning in Cairo

The execution of AI-driven CRN protocols demands massive computational power for both offline model training (e.g., processing the 21.5 GB RadioML dataset) and low-latency, real-time edge inference. Given that the operational theater for this deployment is Cairo, Egypt, leveraging localized infrastructure is paramount to minimizing layer-3 routing latency, reducing international IP transit egress costs, and ensuring strict data sovereignty compliance.

Hyperscale Cloud and Bare Metal Hosting

To facilitate the heavy computational load, bare metal servers and GPU clusters leased from specialized hyperscale providers in Cairo form the backbone of the processing architecture. Providers such as Zenlayer operate robust CAI1 data centers (interconnected via Telecom Egypt), offering on-demand bare metal servers. These platforms are equipped with Intel Xeon Scalable processors, up to 384 GB of RAM, NVMe storage, and connectivity spanning a 120+ Tbps global backbone. By deploying localized Virtual Edge nodes and utilizing Layer-2 point-to-point Private Connect services, the SDR data streamed from distributed Cairo sensors

reaches the processing cluster with virtually imperceptible latency. Other providers, such as Cloudflare and Bunny CDN, also maintain local data center footprints, offering diverse IP transit routes.

Dedicated GPU Infrastructure and HPC Clusters

Training complex Bidirectional GRU and deep 1D-CNN architectures requires dedicated GPU accelerators capable of processing immense matrices. Academic and research-oriented HPC clusters, such as the SRTA-City Cloud Computing Center, feature compute nodes equipped with NVIDIA Tesla V100 GPUs, delivering 35.75 TFLOPS of processing performance.
For dedicated, enterprise-scale on-premise implementations, partnerships with local systems integrators such as Stark Technology enable the commission of highly specialized High-Performance Computing facilities across Egypt (including Giza and Alexandria). Their expertise covers the entire facility lifecycle—from empty rooms to fully commissioned data centers—handling structured cabling, rack power containment, cooling, and the deployment of GPU clusters tailored specifically for geospatial and telecommunications workloads.
A financial Return on Investment (ROI) evaluation indicates distinct economic trade-offs between hyperscale cloud rental and dedicated on-premise infrastructure. Analytical tools from Mapping Solutions outline that a continuous 12-hour per day AI workload utilizing 4 GPUs over a 3-year investment horizon incurs cloud rental costs approximating $168, 192 (at \sim 3.2$/hr). Conversely, procuring a private 4-GPU on-premise node requires roughly $45,000 in capital expenditure, plus approximately $6,500 annually for power, cooling, and maintenance per node. Therefore, for persistent, multi-year 6G SDR network processing, transitioning from cloud GPU leasing to an on-premise, Stark Technology-built facility in Cairo represents a highly favorable long-term economic strategy.

Workforce Expertise and Autonomous Agent Integration

Designing, training, simulating, and deploying this complex Cognitive Radio ecosystem requires a highly coordinated, multidisciplinary human workforce augmented heavily by specialized autonomous AI agents. The following taxonomy delineates the mandatory expertise and the autonomous systems required to tailor this implementation for seamless execution.

Multidisciplinary Human Skill Sets

Engineering Domain	Required Expertise and Technical Proficiencies
AI/ML & DSP Engineers	Proficient in TensorFlow/PyTorch to design lightweight 1D-CNNs, Bi-GRUs, and ACNet architectures. Must possess a deep understanding of Digital Signal Processing (DSP), I/Q data structures, and BCE loss function optimization for noisy RF environments.
Network & Telecom Architects	Specialists in MAC/PHY layer protocol design, familiar with dynamic spectrum management,

Engineering Domain	Required Expertise and Technical Proficiencies
	ALOHA vs. ILA-CSMA frameworks, and 5G NR O-RAN architectures.
NS-3 Simulation Experts	Developers fluent in C++ and Python to construct complex network topologies, manage ApplicationContainer events, and develop trace-parsing algorithms to measure end-to-end latency, jitter, and network collision rates.
SDR Hardware Specialists	Engineers capable of programming FPGAs, managing UHD (USRP Hardware Driver), GNU Radio, and configuring highly precise clock synchronization (1 PPS / 10 MHz reference clocks) across distributed USRP and RTL-SDR arrays.
Cybersecurity Analysts	Security professionals specialized in RF physical-layer threat vectors, equipped to develop defense algorithms against barrage jamming, GNSS spoofing, and side-channel EM emanations.
Data Center Architects	IT infrastructure professionals to manage the procurement and deployment of bare metal GPU servers, layer-2/3 routing, and cooling/power containment within Cairo data center facilities.

Autonomous AI Agent Framework

To accelerate the workflow, eliminate human bottlenecks, and ensure real-time network responsiveness, various autonomous agents are deployed directly into the development and operational pipelines:

- **Hyperparameter Optimization Agents:** Autonomous Bayesian optimization agents that continuously iterate over batch sizes, learning rates, dropout ratios, and convolutional filter sizes (utilizing algorithms like Particle Swarm Optimization). These agents maximize P_d and minimize P_{FA} without requiring manual human intervention. * **Spectrum Monitoring & Orchestration Agents:** Deep Reinforcement Learning agents deployed directly at the edge (within the Near-RT RIC). These agents actively monitor USRP I/Q streams and execute immediate policy decisions, dynamically reallocating SU transmission frequencies and altering beamforming parameters upon detecting PU activity or adversarial jamming.
- **Simulation & CI/CD Pipeline Agents:** Automated DevOps agents that bridge the AI models with NS-3. Whenever a new CNN model is pushed to the repository, this agent automatically spawns an NS-3 simulation, evaluates the new collision probabilities, parses the end-to-end-delay.tr logs, and generates an exhaustive performance report before approving the model for OTA hardware testing.
- **Infrastructure Scaling Agents:** Cloud-native, Kubernetes-based agents that monitor the inference load and CPU/GPU saturation from the SDR network. These agents dynamically spin up or terminate Zenlayer bare metal instances in the Cairo data center, maintaining stringent cost-efficiency during fluctuating RF traffic periods.

The deployment of an AI-driven Cognitive Radio Network necessitates a harmonious integration of theoretical signal processing, cutting-edge machine learning, robust network simulation, and high-performance hardware orchestration. By replacing fragile, threshold-based spectrum sensing algorithms with ultra-efficient 1D-CNN and recurrent architectures, the network achieves near-perfect detection accuracy while operating dynamically under severe noise and multipath fading conditions. Transitioning these models from training datasets to physical reality requires rigorous validation through NS-3 simulations and deployment utilizing USRP and RTL-SDR hardware within O-RAN architectures, ensuring the physical layer remains agile and resilient against modern cybersecurity threats. Capitalizing on Cairo's robust local data center infrastructure secures the computational backend, providing a comprehensive, scalable, and economically viable blueprint for next-generation 6G spectrum management.

Works cited

1. Reinforcement-Learning-Based Dynamic Spectrum Access for, https://www.researchgate.net/publication/354740667_Reinforcement_Learning_Based_Dynamic_Spectrum_Access_for_Software-defined_Cognitive_Industrial_Internet_of_Things 2. Cognitive radio and machine learning modalities for enhancing the, https://www.researchgate.net/publication/380467596_Cognitive_radio_and_machine_learning_modalities_for_enhancing_the_smart_transportation_system_A_systematic_literature_review 3. Improving Spectrum Sensing Under Impact of Noise Uncertainty, https://www.researchgate.net/publication/349742677_Improving_Spectrum_Sensing_Under_Impact_of_Noise_Uncertainty_Factor_to_Detect_Primary_User_Traffic_for_Cognitive_Radio_System 4. (PDF) The Cognitive Radio and Internet of Things - ResearchGate, https://www.researchgate.net/publication/343984562_The_Cognitive_Radio_and_Internet_of_Things 5. Spectrum Pricing for Cognitive Radio - White Rose eTheses Online, https://etheses.whiterose.ac.uk/id/eprint/8157/1/PhD%20Thesis%20Abdulkarim%20Oloyede%202.pdf 6. Deep Neural Networks for Spectrum Sensing: A Review, https://www.researchgate.net/publication/373156646_Deep_Neural_Networks_for_Spectrum_Sensing_A_Review 7. Modulation Recognition of Communication Signals Based on ... - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC9460658/ 8. Attention-Enhanced Hybrid Automatic Modulation Classification for, https://ieeexplore.ieee.org/iel8/6287639/10820123/11037789.pdf 9. Deep Neural Networks for Spectrum Sensing: A Review - IEEE Xplore, https://ieeexplore.ieee.org/iel7/6287639/10005208/10217791.pdf 10. (PDF) Lightweight 1D CNN for Unified Real-Time Communication, https://www.researchgate.net/publication/397193718_Lightweight_1D_CNN_for_Unified_Real-Time_Communication_Signal_Classification_and_Denoising_in_Low-SNR_Edge_Environments_Lightweight_1D_CNN_for_Unified_Real-_Time_Communication_Signal_Classification_an 11. Automatic Digital Modulation Classification Using STFT, https://jad.shahroodut.ac.ir/article_3851_da9cba1e11fa72e7b77b99a4818ec240.pdf 12. A comparative study of ACNet and SPA-ResNet performance under, https://www.spiedigitallibrary.org/conference-proceedings-of-spie/14233/142330B/A-comparative-study-of-ACNet-and-SPA-ResNet-performance-under/10.1117/12.3112496.full 13. SPIDER: Lightweight Speaker Identification on Resource ... - CORA, https://cora.ucc.ie/server/api/core/bitstreams/6a0bb088-73d6-433d-bd20-08697c9c44f5/content 14. Cloud Computing & Networking in Cairo - Zenlayer, https://www.zenlayer.com/lp/city/cairo 15. Generalized Wireless Adversarial Deep Learning - Genesys Lab, https://genesys-lab.org/papers/R_2022-computer.pdf 16. Spatiotemporal Mobility Prediction in

Proactive Self-Organizing,
https://www.researchgate.net/publication/310821817_Spatiotemporal_Mobility_Prediction_in_Proactive_Self-Organizing_Cellular_Networks 17. Security of software defined networking (sdn) and cognitive radio,
https://www.slideshare.net/slideshow/security-of-software-defined-networking-sdn-and-cognitive-radio-network-crn/60542433 18. Network End to end delay analysis in ns3 - NS3 Simulation,
https://ns3simulation.com/how-to-calculate-end-to-end-delay-in-ns3/ 19. Top 10+ Popular Cognitive Radio Network Simulation Tools [Code,
https://ns3simulation.com/cognitive-radio-network-simulation/ 20. Cognitive Radio Networks: Efficient Solutions for Routing, Topology,
https://publications.sto.nato.int/publications/STO%20Technical%20Reports/STO-TR-IST-140/$$TR-IST-140-ALL.pdf 21. ILA-CSMA: Hybrid Sensing and Adaptive Fair Backoff for Large,
https://pmc.ncbi.nlm.nih.gov/articles/PMC13259383/ 22. Sum Throughput Maximization in a Cognitive Multiple Access,
https://www.researchgate.net/publication/332168199_Sum_Throughput_Maximization_in_a_Cognitive_Multiple_Access_Channel_With_Cooperative_Spectrum_Sensing_and_Energy_Harvesting?_tp=eyJjb250ZXh0Ijp7InBhZ2UiOiJzY2llbnRpZmljQ29udHJpYnV0aW9ucyIsInByZXZpb3VzUGFnZSI6bnVsbCwic3ViUGFnZSI6bnVsbH19 23. Data Centers in Egypt - GetDeploying,
https://getdeploying.com/datacenters-in-egypt 24. Cloud Computing Center - SRTA-City,
https://srtacity.sci.eg/en/cloudcomputingcenter 25. Data Centre Build & IT Fit-Out in Egypt | Stark Technology, https://starktechnology.net/services/data-centre-build/ 26. HPC Cloud vs On-Prem ROI Calculator | Mapping Solutions Egypt,
https://www.mapping-solutions.com.eg/roi-calculator