CoolCairo

Block-level urban heat decision support for MENA cities, starting with Nasr City, Cairo

Methodology report

> **Problem statement.** We want to **map** summer heat risk (land surface temperature, the surface materials driving it, and the residents exposed to it) in **fast-growing cities across the Middle East and North Africa**, starting with **Nasr City, Cairo** (June–August 2023–2025) as the first example, so that **city planners** can **decide which blocks to prioritise for cool roofs, street trees, cool pavements and pocket parks**.

Event	Arab Youth Space Hackathon 2026 (UAE Space Agency / Space42)
Challenge	813 Challenge: Urban Expansion, Land Use Change & Heat Risk
Team	Team 46: Dr. Liquaa Mahmoud (team lead), Eng. Mohamed Esmat (technical lead), Eng. Mahmoud Mostafa (data & hyperspectral analyst)
Deliverables	Windows desktop app, reproducible Python analysis (notebooks 00–06), this report, slides, demo video (youtu.be/jkDC3HfMiQc)
Report built	26 October 2026 from commit 566558b

1 Summary

Cities across the Middle East and North Africa sit on desert and grow fast; Cairo's eastern districts are a clear case. Summer surfaces there routinely pass 45 °C, but heat is not even: it follows what the ground is made of. CoolCairo turns open satellite data into a planning tool that answers one question per city block: *how hot is it, why, how many people live there, and what would a cooling measure change?* Nasr City is the first district built and tested; the free, region-wide data lets the same method run in any city, and the same pipeline already runs, unchanged, for four test cities: Algiers, Casablanca, Dubai and Riyadh.

We measure summer land surface temperature (LST) with Landsat 8/9, map surface materials with Sentinel-2, add building footprints and heights (OpenStreetMap, Google Open Buildings) and residents (WorldPop), and aggregate everything to 90 m blocks. A linear model links block temperature to materials and building height; published albedo physics and our model give the effect of four cooling measures. A Windows desktop app shows the district in 3D and lets a planner paint measures onto blocks and read the result live. We also tested whether EnMAP hyperspectral data adds value.

Key results

- **Heat model:** spatially cross-validated R^2 **0.25**, mean absolute error ±1.2 °C, 2,538 urban blocks, 1 km tiles held out together.
- **Heat risk, Nasr City display district:** 95,141 residents and 6,460 person·°C of heat exposure above the east-Cairo urban median (45.7 °C).
- **Cooling measures at full adoption** cut that exposure by 41% (cool roofs), 24% (street trees), 52% (cool pavements) and 60% (pocket parks). Targeting cool roofs and pocket parks at the riskiest third of blocks alone cuts it by **74%**.
- **Urban growth 2016–2023:** building footprint area in east Cairo grew 5.7% and 988 blocks turned from desert to built-up. These new blocks run about 1 °C hotter than established neighbourhoods.
- **Hyperspectral value:** EnMAP block spectra explain block surface temperature at R^2 **0.58** (with our features) versus 0.40 with Sentinel-2. For separating buildings from desert, EnMAP adds nothing beyond a multi-year Sentinel-2 composite.
- **Four test cities** (Section 5.6): the unchanged pipeline reaches spatial R^2 0.16–0.25, and in every test city with a cloud-free EnMAP scene (Algiers, Dubai, Riyadh) EnMAP again explains block heat better than Sentinel-2.

2 Problem and use case

Users. City and district planners in MENA cities (first: Cairo Governorate), and the NGOs and consultancies that prepare greening and retrofit programmes for them.

Decision. Where to cool first, and with which measure in each block, so surface temperatures fall where people live, for their health and for the city's environment. A planner needs to see where heat and people coincide, what drives the heat in each block, and the expected effect of a measure before acting.

Why satellites. Field surveys of surface temperature and materials cannot cover a city block by block every summer. Landsat measures surface temperature every 8 days (two satellites), Sentinel-2 sees materials and vegetation at 10 m every 5 days, and both archives are free, so the same method repeats each year and in any city.

Why the MENA region. Its cities share the problem: a desert climate, dark roofs and asphalt, sandy lots, and fast growth onto the desert. Every dataset used here is free and covers the whole region, so the method runs in any city. Nasr City is the first one built and tested. The same pipeline also runs, with Cairo's settings, for a district in each of four test cities (Section 5.6); these are a test of transfer, not validated results.

Why Nasr City first. A dense, planned district with flat concrete roofs, wide asphalt streets and leftover sandy lots: all four measures apply, and its regular grid makes block-level results easy to read. It borders open desert, which makes the material question (pale roof or bare sand?) hard and worth solving.

3 Study area and data

The model is fitted over east Cairo (Heliopolis, Nasr City, Abbassia; 31.26–31.4° E, 30.0–30.12° N, 23,103 blocks) so it sees real variation in materials and vegetation. The app shows a Nasr City subset of 576 blocks (24 × 24) with 1,901 buildings. All analysis runs in WGS 84 / UTM zone 36N (EPSG:32636).




Figure 1. Model area. (a) Sentinel-2 summer median true colour; (b) Landsat summer median land surface temperature per 90 m block, centred on the urban median. Desert and bare ground (orange) are hotter than the built and irrigated city (blue). The box marks the district shown in the app.

Source	Product and selection	Use	Licence / attribution
Landsat 8/9 (USGS, via Microsoft Planetary Computer)	Collection 2 Level-2 surface temperature (ST_B10), June–August 2023–2025, cloud cover ≤ 10%: 65 scenes (Landsat 8: 33, Landsat 9: 32)	Surface temperature	Public domain
Sentinel-2 L2A (ESA Copernicus, via Planetary Computer)	Same window: 70 granules (2A: 30, 2B: 32, 2C: 8) on 58 acquisition days; bands B02, B03, B04, B08, B11, B12	Materials, vegetation, imagery	Contains modified Copernicus Sentinel data [2023–2025]
EnMAP L2A (DLR EOC Geoservice)	Cairo: one scene, 2025-04-22, 203 usable bands (420–2400 nm, water-vapour windows removed). Test cities: one daytime scene each over Algiers, Dubai and Riyadh (Section 5.6)	Hyperspectral tests	Contains modified EnMAP data © DLR [2022–2025]. Raw data not redistributed
OpenStreetMap (osmnx)	15,129 building footprints, height and level tags	Roofs, heights	© OpenStreetMap contributors, ODbL
Google Open Buildings 2.5D Temporal	Annual layers 2016–2023, 4 m: heights (2023), building presence (growth)	Heights, urban growth	CC BY 4.0 / ODbL
WorldPop Global2 R2025A	2024, 100 m, constrained	Residents per block	CC BY 4.0
NASA Blue Marble Next Generation	July 2004; 2.4 km globe, 500 m over Egypt and the Middle East	Globe in the app	Public domain

Table 1. Data sources. All satellite data are streamed from public STAC archives except EnMAP, which needs a free DLR account and is downloaded manually.

4 Methods

The pipeline is a Python package (*analysis/src/coolcairo*); notebooks 01–06 are thin drivers, and every threshold, date and literature value sits in one config file (*analysis/config/aoi.yaml*) with its source.

4.1 Grid and blocks

Rasters share a 30 m analysis grid (Sentinel-2 also on a 10 m grid). Every number shown to a user is per **90 m block** (3 × 3 Landsat pixels), close to Landsat's native 100 m thermal resolution, so no result claims detail the thermal sensor cannot see.

4.2 Land surface temperature

We use the USGS Collection 2 Level-2 surface temperature product (already corrected for atmosphere and emissivity) rather than deriving LST ourselves. Pixels flagged as fill, cloud, dilated cloud, cirrus or cloud shadow in QA_PIXEL are removed; the per-pixel median over all 65 summer scenes gives a robust typical summer daytime (about 10:30 local overpass) surface temperature, averaged to blocks.

4.3 Surface materials

A transparent rule set classifies each 10 m Sentinel-2 pixel of the summer median composite (clouds, shadows and saturated pixels removed via the scene classification layer):

- **Vegetation:** NDVI > 0.3.
- **Dark surface** (asphalt, dark roofs): mean visible reflectance ≤ 0.14.
- **Bare sand / soil:** remaining pixels with Bare Soil Index > 0.137.
- **Pale surface** (light concrete, pale roofs): everything else.

Pale roofs and desert sand have the same brightness in Cairo, so brightness alone cannot separate them. The BSI threshold was chosen as the best single cut between pixels inside mapped OSM footprints and open ground more than 300 m from any footprint: threshold 0.137, balanced accuracy 75% (notebook 02 re-derives it). OSM footprints then split each class into roof and ground, giving the block shares used by the model: vegetation, dark roof, pale roof, dark ground and bare sand (soil-like pixels inside a footprint count as dusty pale roofs).

4.4 Buildings and heights

Heights follow a priority chain: OSM *height* tag, then OSM *building:levels* × 3.2 m, then the median Google Open Buildings 2.5D height inside the footprint (at least 3 pixels), then a default of 5 storeys. Over the model area 74% of buildings take Open Buildings heights, 25% the default and 1.1% OSM tags.

4.5 Residents and heat exposure

WorldPop 2024 residents (100 m) are resampled to the 30 m grid by area averaging and summed per block. **Heat risk** is the screening indicator *residents* × *degrees above a reference* (person·°C), with the reference set to the median summer LST of urban blocks in the model area (45.66 °C). Blocks cooler than typical built-up east Cairo therefore count zero, and the indicator rises with both heat and people.

4.6 Heat model

Block LST is modelled by ordinary least squares on six features: the shares of vegetation, dark roof, dark ground, bare sand and all roofs, and mean building height. Only urban blocks (≥ 10% roof cover, valid LST) are used, n = 2,538. Pale ground is the reference category, so each coefficient is the change in LST when a whole block switched from pale ground to that surface. A linear model was chosen on purpose: the app evaluates measures as a weighted sum in real time, and every coefficient can be read and checked.

Neighbouring blocks share heat, so random cross-validation would leak and inflate R^2. We report **spatial cross-validation**: blocks are grouped into 1 km tiles and whole tiles are held out (5-fold GroupKFold).

4.7 Cooling measures

Landsat LST of a block is close to the area-weighted mean of its surfaces, so each measure's effect is a *per-unit-area* temperature change times the share of block area treated. Where our regression gives a physically plausible value we use it; where it does not, we use published albedo physics.

Measure	What changes	Effect per unit block area	Basis
Cool roofs	Dark and pale roofs coated white (albedo → 0.7)	−4.64 °C (dark) / −3.60 °C (pale)	−8.0 K per unit albedo (Wang et al. 2020) × albedo change; dark 0.12 (Cairo study, 2025), pale 0.25 (ACPA 2002)
Street trees	Up to 25% of dark ground planted	−3.28 °C	Our regression: vegetation minus dark ground
Cool pavements	Dark ground coated, albedo 0.12 → 0.4	−2.24 °C	Same albedo sensitivity as roofs; conservative against a UAE desert field study (60 → 47 °C)
Pocket parks	Up to 50% of bare sand greened	−6.51 °C	Our regression: vegetation minus bare sand

Table 2. Cooling measures. Caps are assumptions stated in the app: trees leave room for traffic, parks leave room for paths and facilities.

The fitted dark-roof coefficient is negative (dark roofs look *cooler* than pale roofs), which is physically implausible and most likely building shadow being classified as dark roof at 10 m. An automatic sign check flags this and the model therefore uses the literature value for cool roofs; switching to the regression is one config line if better material data fixes the sign.

Cool coatings in practice. Reflective coatings are proven and entering mass production. A radiative-cooling coating kept container-house roofs about 24 °C cooler at the surface than concrete in a 2.5-year field trial in Hong Kong and cut air-conditioning energy by 10% (PolyU 2024); a similar radiative-cooling paint entered mass production in China in 2026, reported as up to 25 °C cooler on surfaces in a six-month test (SCMP 2026, citing *Science and Technology Daily*; not yet independently verified). These are peak surface temperatures of the coated surface itself and are not comparable with our block-average summer medians. Such coatings reflect and emit more than the white paint we model, so our cool-roof effects are conservative.

4.8 Does hyperspectral data add value?

Two controlled tests compare EnMAP with Sentinel-2 on identical pixels, the same classifier and the same spatial folds, so only the spectra differ. EnMAP is also reduced to Sentinel-2's six passbands (box-car average) to separate the effect of spectral detail from that of a different sensor and date.

- **Built vs desert.** 30 m pixels ≥ 90% inside OSM footprints (built, n = 1,211) versus pixels more than 300 m from any footprint and not vegetated (open, n = 78,441); logistic regression with balanced class weights (PCA to 20 components for EnMAP), balanced accuracy.
- **Block heat.** Mean spectrum per block as predictors of block LST, alone and added to our model features; ridge regression with the penalty chosen by inner cross-validation; spatial R^2 with 1, 2 and 3 km held-out tiles.

4.9 Urban growth

Google Open Buildings 2.5D Temporal gives one building map per year (2016–2023, dated 30 June), predicted from Sentinel-2 at an effective 4 m. Its *building presence* band is a model confidence from 0 to 1; a pixel counts as built at ≥ 0.5 (values are strongly two-peaked; 0.4 and 0.6 are reported as a check). Built pixels are averaged to the same 10 m and 90 m grid as every other layer, giving each block a building cover per year. A block is built-up at ≥ 10% cover, the model's urban cut-off, so blocks fall into *built before 2016*, *built 2016–2023* or *still open*. The app also marks built-up blocks whose cover rose by ≥ 5 percentage points as *denser*.

5 Results

5.1 Heat model

The model explains a quarter of the block-to-block variation in held-out areas (spatial R^2 0.25; 0.38 in-sample) with a mean error of ±1.2 °C, against a spread of 1.9 °C (standard deviation) between urban blocks. It is good enough to rank drivers and compare measures, not to predict a single block's temperature exactly; its predictions are compressed towards the mean (Figure 2).

Feature	Coefficient	Reading
Intercept	45.83 °C	Block of pale ground, no buildings
Vegetation share	−3.15	Vegetation cools
Dark roof share	−11.28	Implausible sign: shadow (see 4.7)
Dark ground share	0.12	About as hot as pale ground
Bare sand share	3.36	Sand is the hottest surface
Roof share	2.29	Pale roofs warmer than pale ground
Mean building height	−0.062 per m	Taller blocks are cooler (shade)

Table 3. Fitted coefficients (°C per unit share of block area, or per metre of height).




Figure 2. Observed block LST against predictions for blocks in held-out 1 km tiles.

5.2 Heat risk in Nasr City

Most of the display district is cooler than the east-Cairo urban median (mean block LST 44.7 °C against a 45.7 °C reference). Heat risk therefore concentrates in a few places: a band along the district's northern edge, a handful of isolated blocks in the east, and the south-west corner (Figure 3). These are the blocks a planner would look at first.




Figure 3. Nasr City display district. (a) Sentinel-2 true colour; (b) interim material classes; (c) block LST; (d) heat exposure per block, residents × °C above the reference. White blocks in (d) are cooler than the reference.

5.3 Effect of cooling measures

Averaged over all 2,538 urban blocks, full adoption changes block LST by −1.01 °C (cool roofs), −0.09 °C (street trees), −0.25 °C (cool pavements) and −0.74 °C (pocket parks); the strongest single blocks cool by up to 3.7 °C with roofs and 2.9 °C with parks. Measured in heat exposure, the measures matter more than these averages suggest: exposure counts only degrees above the reference, so one or two degrees of cooling removes most of a hot block's exposure (Figure 4).

Targeting is the point of the tool. Cool roofs and pocket parks on only the 192 riskiest blocks (a third of the district, 22,588 residents) cut district heat exposure from 6,460 to 1,686 person·°C (**−74%**), more than any single measure applied everywhere.




Figure 4. Change in Nasr City heat exposure. Blue: each measure at full adoption within its cap in every block. Orange: the targeted plan shown in the app screenshots (Section 8).

5.4 Value of hyperspectral data

Block heat: EnMAP adds clear value. EnMAP block spectra alone explain block LST at R^2 0.53, against 0.31 for Sentinel-2 and 0.33 for the same EnMAP scene reduced to Sentinel-2's bands, so the gain comes from spectral detail, not from the sensor or date. Added to our features: 0.58 versus 0.40. The advantage holds with 2 and 3 km held-out tiles (0.55 and 0.50 versus 0.44 and 0.40).




Figure 5. Spatial cross-validated R^2 of block LST by predictor set and held-out tile size. Contains modified EnMAP data © DLR [2025].

Built vs desert: EnMAP adds nothing here. The single BSI index reaches a balanced accuracy of 0.76; all six Sentinel-2 bands reach 0.86, more than EnMAP's full spectrum (0.82) or EnMAP reduced to Sentinel-2 bands (0.80). Adding EnMAP to Sentinel-2 changes accuracy from 0.860 to 0.862 (fold spread ±0.027). A 58-day Sentinel-2 median beats a single EnMAP date for this task; the remaining confusion is spatial (mixed pixels), not spectral.

Decision. The app's materials stay on Sentinel-2, which covers every summer and every city. EnMAP's value is in explaining heat: the app reports the EnMAP result with its attribution, and a hyperspectral-based model is the main upgrade path once more cloud-free summer EnMAP scenes over Cairo exist. The same block-heat test in three more cities gives the same answer (Section 5.6).

5.5 Urban growth and heat

Across the model area, building footprint area grew from 37.1 km² in 2016 to 39.2 km² in 2023 (**+2.1 km², +5.7%**), almost every year (Figure 6b). 988 blocks (8.0 km²) changed from open land to built-up; WorldPop counts 61,145 residents in them in 2024. They are partly scattered infill inside the existing city (single blocks crossing the 10% cut-off, some of which will be noise) and partly compact new clusters on the southern desert edge (Figure 6a). Nasr City itself was already built: its building area rose only from 1.29 to 1.33 km², mostly by densification.

New development runs hot. Newly built blocks average 46.9 °C in summer, against 46.0 °C for blocks built before 2016 and 48.6 °C for open desert (Figure 6c). Building on sand cools the surface somewhat, but new districts stay about 1 °C hotter than mature neighbourhoods with their trees and shade, so cooling measures are best designed in while these areas are still being built. This is a comparison across places in one period, not a measured change over time.




Figure 6. Urban growth 2016–2023 from Google Open Buildings Temporal. (a) Block classes, same colours as the app's Growth view; the box marks Nasr City. (b) Building footprint area per year. (c) Mean summer LST (2023–25) by class, with block counts.

Presence cut-off	Footprint area 2016	Footprint area 2023	Newly built-up blocks
0.4	43.3 km²	45.1 km²	1,002
0.5 (used)	37.1 km²	39.2 km²	988
0.6	30.7 km²	33.1 km²	1,066

Table 4. Sensitivity to the building-presence cut-off: absolute areas shift, but growth and the number of newly built blocks stay similar.

5.6 Test cities

To test whether the method transfers, the same pipeline and settings run for one district in each of four more MENA cities: only the geography, projection and WorldPop file change (*analysis/config/aoi_<city>.yaml*, written by *make_city_configs.py*). Each city gets its own model area, model fit, heat reference (its own urban median) and app district, with the same data window (June–August 2023–2025). All four run in the app next to Nasr City.

City (district)	Model blocks	Spatial R² (MAE)	Median block LST	Residents (display)	Heat exposure	Sentinel-2 → EnMAP R²
Cairo (Nasr City)	2,538	0.25 (±1.2 °C)	44.6 °C	95,141	6,460	0.40 → **0.58** (22 Apr 2025)
Algiers (Bab El Oued)	8,664	0.16 (±1.3 °C)	40.3 °C	193,396	25,780	0.26 → **0.49** (30 May 2024)
Casablanca (Hay Mohammadi)	5,581	0.20 (±1.2 °C)	42.3 °C	95,121	55,152	no cloud-free scene
Dubai (Al Karama)	7,537	0.17 (±1.5 °C)	49.5 °C	30,425	10,596	0.31 → **0.63** (05 Aug 2022)
Riyadh (Al Malaz)	5,470	0.25 (±0.8 °C)	52.2 °C	42,239	51,554	0.37 → **0.52** (29 Mar 2023)

Table 5. Test cities next to Cairo. Spatial R² with 1 km held-out tiles; median LST, residents and heat exposure (person·°C above each city's own urban median) for the app's display district; last column: block-heat R² with our features plus Sentinel-2 versus plus EnMAP spectra, same blocks and folds (Section 5.4).

The model transfers at a similar, modest level. Spatial R² ranges from 0.16 to 0.25, against 0.25 in Cairo: enough to rank blocks, as in Cairo, not to predict one block. As in Cairo, every city uses the literature value for cool roofs.

Hyperspectral data helps in every city tested. In all 3 test cities with a usable EnMAP scene, EnMAP spectra explain block heat better than Sentinel-2 with the same features, blocks and folds: Algiers 0.26 → 0.49; Dubai 0.31 → 0.63; Riyadh 0.37 → 0.52. The scenes come from different seasons and years (2022–2024), so the gain does not depend on one date. Casablanca's only daytime scene (17 January 2024) has cloud over the district and is not used.

Data gaps. Google Open Buildings 2.5D Temporal covers Algiers but not Casablanca, Dubai or Riyadh, where most heights are a 5-storey default and there is no growth view. In Algiers, building area in the display district grew from 1.28 to 1.32 km² (2016–2023), with 22 newly built blocks; blocks over the sea (NDVI < 0) are left out of the growth classes. The test cities have no material spot check or local validation yet.

6 Quality control and validation

- **Spatial cross-validation** for every reported R² and accuracy, with tile sizes of 1 km and, for the hyperspectral tests, 2 and 3 km.
- **Coefficient sign checks** run with every fit: dark roofs warmer than pale roofs, vegetation cooler than dark ground and than bare sand. A failed check switches the measure to literature values (the case for cool roofs today).
- **Building heights** checked against OSM-tagged heights (n = 165): bias −1.4 m, mean absolute error 6.2 m, median 4.2 m, correlation r = 0.60.
- **Data provenance**: the app's start-up screen queries the archives for the exact scene IDs used here and shows a live preview from each satellite; scene lists are exported with the data.
- **24 unit tests** (pytest) cover classification rules, block aggregation, the model, intervention arithmetic, the export format and the quick example's numbers.
- **90 automated checks run inside the built app** (*CoolCairo.exe -selftest*), including that every test city's data and maps load; all pass in release v1.2, and the app exits with an error if any fails.

- **Material classes (milestone M2).** 20 stratified random points (5 per class) were compared with Google Maps satellite imagery (Airbus, 2026). 18 could be judged; the interim classes agree at 89% of them. The two misses are a dusty asphalt road and a dusty concrete roof labelled bare sand (the model already counts soil-like pixels inside building footprints as pale roofs). The two points that could not be judged were a shadowed gap and a mixed edge. The check was done by an AI assistant that could see the pipeline's labels, so it is not blind; the sheet (*docs/m2_spot_check.xlsx*) records what was seen at every point for review.

7 Limitations and other measures considered

- **Surface, not air, temperature.** Satellites measure how hot surfaces get, at about 10:30. Studies suggest city-wide cool roofs lower air temperature by roughly 0.1–0.33 °C per +0.1 roof albedo (Santamouris 2014, cited in Wang et al. 2020); the effect on air is smaller and spreads beyond the treated blocks.
- **Block level only.** Landsat's thermal band is 100 m, so no per-building temperature is claimed.
- **Modest model fit** (spatial R^2 0.25). Effects are averages for blocks like the treated one, not guarantees for a single block.
- **Interim material classes.** Rules on Sentinel-2 confuse dark roofs with shadow and dusty surfaces with sand; the spot check found 89% agreement, from 20 points checked non-blind.
- **Growth comes from yearly model predictions** (Open Buildings Temporal), so small year-to-year changes are partly noise; only the 2016 → 2023 change is used. 83% of newly built blocks have almost no OpenStreetMap footprints yet, so the heat model's roof features under-represent the newest areas.
- **One EnMAP scene per city** (Cairo in April; only Dubai's is mid-summer). The hyperspectral result is a strong, repeated signal, not yet a production model.
- **Test cities use Cairo's settings unchanged** (material thresholds, cut-offs, measures) and have no local validation; they show that the method transfers, not that their numbers are final.
- **Heat risk is a screening indicator** (heat × residents). It leaves out vulnerability such as age, housing quality and access to cooling, and WorldPop counts are modelled, not census.
- **Costs are not in the app.** Researched ranges (Egyptian and international prices) are in *docs/intervention_research.md*.

Measures researched and left out of the app. *Green roofs* cool roofs strongly but cost about EGP 5,500–11,000 per m² and need irrigation and structural capacity that most Nasr City roofs lack. *Shade sails* cool the ground beneath them sharply, but a satellite sees the sail's hot upper surface, so the effect cannot be measured or validated with this method. *Water features* (fountains, small lakes) were not modelled: their cooling is local, they use scarce water, and open water was absent from the training blocks.

8 The decision-support tool

CoolCairo is a Windows desktop app (Unity 6). It loads the exported district (*export/district.json*: blocks, buildings, model coefficients, provenance) and evaluates the same linear model in real time. Screenshots below are captured by the app itself (*CoolCairo.exe -screenshots*) from the release build.




a Satellite archive sync: the app queries Planetary Computer and DLR for the scenes used and shows a live preview from each satellite.



b MENA globe (NASA Blue Marble, 2.4 km). Five live cities: Cairo (Nasr City) and the four test cities.



c Approach, ~760 km up: a 500 m Blue Marble image of Egypt and the Middle East keeps the descent sharp.



d End of the fly-in: 10 m Sentinel-2 image of Cairo (2024-08-15), Nasr City in the centre.



e Materials view: vegetation, dark, pale and sand per block, 3D buildings with estimated heights.



f Surface heat view: summer LST per block.



g Heat risk view: residents × °C above the reference.



h Growth view: building cover 2016 → 2023 per block (Google Open Buildings Temporal).



i After a plan (cool roofs and pocket parks on the riskiest third of blocks): live before → after card; coloured rings mark the treated blocks.



j Surface heat after the same plan; the ring key is in the legend.

9 Reproducibility

Everything in this report is rebuilt from code. Python 3.12 dependencies are locked with uv; satellite data stream from public archives without an account.

Step	Command (in *analysis/*)
Install locked dependencies	uv sync
Unit tests	uv run pytest
Data, model, export for the app	uv run python run_pipeline.py
Notebooks 01–06	uv run jupyter lab
Test city (data, model, export)	COOLCAIRO_CONFIG=config/aoi_<city>.yaml COOLCAIRO_DATA_DIR=data/<city> COOLCAIRO_EXPORT_DIR=../export/<city> uv run python run_pipeline.py, then report/city_figures.py
This report	uv run python report/build_report.py
App	Unity 6000.0.83f1: CoolCairo → Setup project and scene, then Build Windows desktop app

EnMAP is optional: with a free DLR EOC Geoservice account, download the scene listed in *analysis/config/enmap_scenes.txt* into *analysis/data/enmap/* (test cities: *enmap_scenes_<city>.txt* into *data/<city>/enmap/*). Without it the pipeline runs and skips the hyperspectral results. Raw EnMAP data are not in the repository (licence).

References

1 Wang, L., Huang, M. & Li, D. (2020). Where are white roofs more effective in cooling the surface? *Geophysical Research Letters* 47(15), e2020GL087853. https://doi.org/10.1029/2020GL087853

2 The impact of increasing urban surface albedo on outdoor air and surface temperatures during summer in newly developed areas (2025). *Scientific Reports*. https://doi.org/10.1038/s41598-025-08574-2

3 American Concrete Pavement Association (2002). Albedo: a measure of pavement surface reflectance. *R&T Update* 3.05 (TRID record). https://trid.trb.org/View/920184

4 Evaluation and thermal performance of cool pavement under desert weather conditions (2023). *Case Studies in Construction Materials*. https://www.sciencedirect.com/science/article/pii/S2214509523001195

5 Hendel, M. (2024). Cool pavements. arXiv:2409.12242. https://arxiv.org/abs/2409.12242

6 Santamouris, M. (2014). Cooling the cities: a review of reflective and green roof mitigation technologies to fight heat island and improve comfort in urban environments. *Solar Energy* 103, 682–703. https://doi.org/10.1016/j.solener.2012.07.003

7 The Hong Kong Polytechnic University (2024). PolyU researchers unveil novel carbon dots-driven green radiative cooling coating. News release, 24 September 2024. polyu.edu.hk (news release)

8 South China Morning Post (2026). Chinese paint cuts wall temperature 25 degrees Celsius in summer test: report. September 2026. scmp.com/news/china/science/article/3367812

9 U.S. Geological Survey. Landsat 8–9 Collection 2 Level-2 Science Product Guide. usgs.gov (product guide)

10 Google Research. Open Buildings 2.5D Temporal Dataset. https://sites.research.google/gr/open-buildings/temporal/

11 WorldPop. Global2 R2025A population counts, Egypt 2024, 100 m constrained. https://doi.org/10.5258/SOTON/WP00839

12 Microsoft Planetary Computer STAC API (Landsat C2 L2, Sentinel-2 L2A). https://planetarycomputer.microsoft.com/

13 DLR Earth Observation Center. EnMAP HSI L2A, EOC Geoservice. https://www.enmap.org/

14 Further intervention and cost sources, each with its link: docs/intervention_research.md

Data attribution. Contains modified Copernicus Sentinel data [2023–2025]. Landsat courtesy of the U.S. Geological Survey. Contains modified EnMAP data © DLR [2022–2025]. Building footprints © OpenStreetMap contributors (ODbL). Google Open Buildings (CC BY 4.0 / ODbL). WorldPop (CC BY 4.0). NASA Blue Marble.