



Alexandria National University Faculty of Computers and Data Science

Lecturer: Dr. Mohamed Abdelhafeez

Course: Web Programming (00204N)

Assignment #4

Question #1: Regarding the following code answer the following questions: -

```
<form name="Calc"> <input type="text" name="txt1" value = "1" size="16">  
<input type="button" value=" 1 " OnClick="Calc.txt1.value += '+1'">  
<input type="button" value=" = " OnClick="Calc.txt1.value = eval(Calc.txt1.value)"> </form>
```

1. "Calc.txt1.value" is the value of a -----
a) function b) text box inside the form c) paragraph d) list element
2. If the button " 1 " is clicked three times immediately after the form is showing then the value of "txt1" will be -----
a) 1 b) 1111 c) 1+1+1+1 d) 111
3. If the button " = " is clicked once immediately after the form is showing then the value of "txt1" will be -----
a) 1 b) 1111 c) 1+1+1+1 d) 111
4. If the button " = " is clicked once immediately after clicking button "1" three times after the form is showing then the value of "txt1" will be -----
a) 1 b) 111= c) 1+1+1+1= d) 4

Question #2: Modify the above code to allow the user to input a list of comma separated numbers including decimal numbers and calculate the sum, avg standard deviation on the input array.

You will have 0..10 digits, decimal point, std, avg, sum, and comma buttons and large text box to enter the data. When the user enter the comma separated numbers and press sum you display the result in a second disabled textbox.

Question #3: Regarding the following JavaScript function answer the following questions: -

```
function clock() { date=new Date(); time=date.toLocaleTimeString();  
document.write(time);  
window.setTimeout("clock()",1000);}
```

5. If the function clock above is set as the value of window.onload event then the function will be executed -----
a) Once b) every 1000 seconds c) every second d) 1000 times
6. If the function clock above is set as the value of onload event of the body then the function will be executed
a) Once b) every 1000 seconds c) every second d) 1000 times
7. if the function is executed it will show -----
a) today's date b) 1000 c) the date when page is loaded d) updated current client time
8. the same functionality of the above function can be achieved using ----- instead of "setTimeout()"
a) setInterval() b) onclick c) setcolck d) window.setTime()



Alexandria National University Faculty of Computers and Data Science

Lecturer: Dr. Mohamed Abdelhafeez

Course: Web Programming (00204N)

Question #4: According to the following requirements, answer the following questions: -

Assume you need to develop the following web page.

The application: Helps the user fill a form

- The form gathers client information, asks for the zip code before the names of the city and state

- As soon as the zip code is entered, the application sends a request to the server, which looks up the city and

state for the given zip code and returns them to the form

- Uses JavaScript to put the city and state names in the form

- Uses PHP on the server to look up the city and state

Welcome to Popcorn online Sales

Buyer's Name:	
Street Address:	
Zip code:	81411
City	Bedrock
State	Colorado



Given the following JavaScript method to put the city and state names in the above form given the zip code, answer the following questions: -

```
1. function getPlace(zip) {  
2.     var xhr = new XMLHttpRequest();  
3.     xhr.onreadystatechange = function () {  
4.         if (xhr.readyState == 4 && xhr.status == 200) {  
5.             var result = xhr.responseText;  
6.             var place = result.split(', ');  
7.             if (document.getElementById("city").value == "")  
8.                 document.getElementById("city").value = place[0];  
9.             if (document.getElementById("state").value == "")  
10.                 document.getElementById("state").value = place[1]; } }  
11.     xhr.open("GET", "getCityState.php?zip=" + zip, true);  
12.     xhr.send(null);}
```

9. The condition "xhr.readyState == 4 && xhr.status == 200" means

- request finished successfully and response is ready
- request finished unsuccessfully and response is ready



Alexandria National University Faculty of Computers and Data Science

Lecturer: Dr. Mohamed Abdelhafeez

Course: Web Programming (00204N)

- c) request finished successfully but response may not be ready
d) None of the mentioned
10. The function in line 3 in the javascript code above is
a) The event handler for onreadystatechange event
b) Will be executed at least one time
c) An anonymous function
d) All of the mentioned
11. Which one of the following syntax may be used to create the html element representing the zip code text box in the above form
a) `<input type = "text" onblur = "getPlace()" />`
b) `<input type = "text" onblur = "getPlace(value)" />`
c) `<input type = "text" onblur = "getPlace(this)" />`
d) `<input type = "text" onblur = "getPlace(this.value)" />`
12. The "onblur" event in the above question may be replaced by ----- event.
a) onfocus b) onchange c) onclick d) onmouseover

Question 5:

Write the PHP code for two partial webpages for ordering food from an online store. The first page you will write is a form in a page named `order.php` that allows the user to choose what kind of food to buy and how many to buy. In your form, include a drop-down menu of food items available. Include a text box for the user to enter a quantity of the item to purchase (2-characters-wide), and an "Order" button to submit the form. The form should look like this:

Food item:

Quantity:

The food items to list should be based on what food items are available in the database. (database name: "inventory", table name: items, each record in the items table represents the name of the item available in the store, its quantity available, and its price per unit)

Write the portion of `order.php` that would appear between `<body>` and `</body>`. You don't need to write any CSS.

The second page you will write is named `order-submit.php`. The form in `order.php` submits its data as a POST request to `order-submit.php`. The output of `order-submit.php` is an HTML page fragment, a single paragraph indicating information about the order as described below. (Do not use `print` or `echo`.)



Alexandria National University

Faculty of Computers and Data Science

Lecturer: Dr. Mohamed AbdElhafeez

Course: Web Programming (00204N)

Here is an example inventory:

apple	4	1.00
chicken	1	3.25
cookie	38	0.25
milk	9	4.50
tomato	27	0.50

In general your task is to look up the price per unit of the item the user is ordering, and use this price to compute the total order cost. For example, if the item costs \$0.50 and the user orders 7 of them, the total order is $7 * 0.50 = \$3.50$.

The page's output in the general successful case is to inform the user that the order was successful, display the total order cost.

The store is only able to complete an order if that food item is in the inventory and the store has enough of that item in stock. For example, if the inventory has 9 'milk' in stock and the user tries to order 10 of 'milk', the following error should be displayed:

Sorry, we don't have 10 of 'milk' in stock.

If an item is not present in the inventory file, assume that its quantity available in stock is 0 and display the same sort of error message.

You do *not* need to modify the `inventory` database or update its quantity of the item being ordered. If the food item or quantity parameters are not passed, issue an HTTP 400 error. If they are present, you may assume that the food item value passed is a string and the quantity value passed is a positive integer.