

2.18) Ampoule LED E27 - SYLVANIA TOLEDO

ToLEDo Retro A60

ToLEDo RT A60 470LM E27 SL

0027160



Range Features

- LED Chip technology using a virtual filament design which creates a warm ambiance similar to traditional lamps
- First lamp of its type to achieve A++ rating up to 134 lm/W
- Suitable for replacement of up to 60W incandescent lamps
- Available in clear and satin versions
- Packed in individual boxes (SL) or in blisters (BL)
- Up to 90% energy saving compared to incandescent lamps
- Cooler burning versus standard LED lamps
- Dimensional compatibility with all fixtures
- Average lifetime from 6000 hours up to 15 000 hours
- 3 years warranty
- WARNING: If the outer glass jacket is broken conductive parts may still be active. Lamps must not be touched before making sure the mains cable is not live. Switch off the main electrical supply before replacing lamp!

LED

PRÉSENTATION DU PRODUIT

Finition de la lampe	Transparent
Forme de la lampe	A60
Température de couleur (K)	2700
Couleur	Homelight
IRC (Ra)	80
À variateur	Non
Code EAN	5410288271606
Classe d'énergie	A++
Équivalent en Watts (W)	40
Embout/Culot	E27
Туре	ToLEDo Retro A60
Watts (nominal) (W)	4
Couleur de lumière	Homelight
Numéro de commande	0027160
Efficacité (protection) (lm/w)	117.5
Durée de vie moyenne (nominale) (h)	15000
Flux lumineux utile (nominal) (lm)	470
Technologie	LED
Tension (V)	220 - 240
la cohérence de la couleur (de SDCM)	6



ToLEDo Retro A60 ToLEDo RT A60 470LM E27 SL 0027160

TABLEAU DE DONNÉES

Données générales	
Durée de vie moyenne (nominale) (h)	15000
Appareillage requis	Non
Finition de la lampe	Transparent
Forme de la lampe	A60
Disponibilité de l'appareillage	Non
À variateur	Non
Utilisation pour applications sèches uniquement	Oui
Code EAN	5410288271606
Classe d'énergie	A++
Lampe économe en énergie	Oui
Application générale	Hospitality; Residential & Consumer
Destination prévue	Non
Embout/Culot	E27
Contenu en mercure de la lampe (mg)	0
Туре	ToLEDo Retro A60
Nombre de cycles de commutation avant une défaillance prématurée (min)	>50,000
Condition de fonctionnement optimal (° C)	25
Numéro de commande	0027160
Longue description	LED Chip technology using a virtual filament design which creates a warm ambiance similar to traditional lamps First lamp of its type to achieve A++ rating - up to 134 lm/W Suitable for replacement of up to 60W incandescent lamps Available in clear and satin versions Packed in individual boxes (SL) or in blisters (BL) Up to 90% energy saving compared to incandescent lamps Cooler burning versus standard LED lamps Dimensional compatibility with all fixtures Average lifetime from 6000 hours up to 15 000 hours 3 years warranty WARNING: If the outer glass jacket is broken conductive parts may still be active. Lamps must not be touched before making sure the mains cable is not live. Switch off the main electrical supply before replacing lamp!
Nom du produit	Toledo RT A60 470LM E27 SL
Durée de vie moyenne (nominale) (h)	15000
Lampe à objectif spécial	Non
Heure de démarrage (max) (s)	0.05
Technologie	LED
Transformateur requis	Non



ToLEDo Retro A60

ToLEDo RT A60 470LM E27 SL

0027160

Temps de préchauffage jusqu'à 60 % de la pleine lumière (max) (s)	< 1s => 60%
Numéro virtuel FI	4740283
Données optiques	
Température de couleur (K)	2700
IRC (Ra)	80
Couleur de lumière	Homelight
Maintien du flux à la fin de la durée de vie nominale (lm)	80
Flux lumineux (nominal) (lm)	470
Flux lumineux utile (nominal) (lm)	470
Convient à l'éclairage d'accentuation	Non
Chromaticité réglable	Non
la cohérence de la couleur (de SDCM)	6
Données physiques	
Couleur	Homelight
Diamètre (mm)	60
Diamètre de lampe (mm) - D	60
Longueur de lampe (mm) - C/L	105
Dimension de la lampe égale à l'équivalent d'une lampe à filament	Oui
Caractéristiques électriques	
Actuel (A)	38
Courant (mA)	38
Équivalent en Watts (W)	40
kWh par 1 000 heures de durée de fonctionnement	4
Facteur de puissance de la lampe	0.5
Watts (nominal) (W)	4
Efficacité (protection) (lm/w)	117.5
Watts (nominal) (W)	4
Tension (V)	220 - 240



ToLEDo Retro A60 ToLEDo RT A60 470LM E27 SL 0027160

